VILLAGE OF GLENCOE

675 Village Court, Glencoe, Illinois 60022
p: (847) 835-4114 | info@villageofglencoe.org | Follow Us: @VGlencoe

www.villageofglencoe.org

Virtual Meeting Information

As the Village of Glencoe and its partner agencies continue to follow social distancing requirements and Governor Pritzker's *Restore Illinois* Plan, the July 15 special Plan Commission meeting will be held virtually via telephone and video conference (individuals may participate either by telephone or by video conference). Individuals may call the following to participate in the meeting:

By Telephone:
Phone Number: (312) 626-679
Webinar ID: 987 1536 3938

By Zoom Video Conference:
Zoom video conference link: Click here

Video conference participants using a computer will be prompted to install the Zoom client; participants using smart phones or tablets must download the Zoom app from their app store.

Public Comment Submittal Options

Option 1: Submit Comments by E-Mail Prior to Meeting
Public comments can be submitted in advance of the meeting by e-mail to glencoemeeting@villageofglencoe.org. Public comments received by 5 p.m. or one hour before the start of the Plan Commission meeting will be read during the Plan Commission meeting under Public Comment. Any comments received during the meeting may be read at the end of the meeting.

All e-mails received will be acknowledged. Public comment is limited to 400 words or less. E-mailed public comments should contain the following:

- The Subject Line of the e-mail should include the following text: "July 15th Plan Commission Meeting Public Comment"
- Name of person submitting comment (address can be provided, but is not required)
- Organization or agency person is submitting comments on behalf of, if applicable
- Topic or agenda item number of interest, or indicate if the public comment is on a matter not listed on the Plan Commission meeting agenda

Option 2: Submit Comments by Phone Prior to Meeting
Individuals without access to e-mail may submit their comments through a voice message by calling (847) 461-1100. Verbal public comments will be read aloud during the meeting and will be limited to three minutes.

MINUTES
VILLAGE OF GLENCOE
PLAN COMMISSION

Virtual Meeting – Video Conference
Wednesday, June 24, 2020 – 7:00 p.m.

1. CALL TO ORDER
The June 24, 2020 meeting of the Plan Commission of the Village of Glencoe, Cook County was called to order virtually at 7:03 p.m.

2. ROLL CALL

The following were in attendance:
Bruce Huvard, Chairman, Public-at-Large Representative
Barbara Miller, Vice-Chairman, Village Board Representative
Georgia Mihalopoulos, Public-at-Large Representative
Dev Mukherjee, School District 35 Representative
Dudley Onderdonk, Glencoe Park District Representative
John Satter, Zoning Board of Appeals Representative
Laura Solon, Glencoe Public Library Representative
James Thompson, Public-at-Large Representative
Greg Turner, Public-at-Large Representative
Peter Van Vechten, Historic Preservation Commission Representative

The following were also in attendance:
Taylor Baxter, Development Services Manager
David Mau, Public Works Director
Lee Brown, Village Planner
Stew Weiss, Village Attorney

3. CONSIDER THE MARCH 4, 2020 PLAN COMMISSION MEETING MINUTES
The minutes from the March 4, 2020 Plan Commission meeting were moved for approval by Commissioner Turner and seconded by Commissioner Satter and approved as drafted.

4. PUBLIC COMMENT TIME
There were no comments from the public.

5. CONSIDERATION OF EXTERIOR APPEARANCE REVIEW FOR PROPOSED WALL SIGN AT 700 VERNON AVENUE
Development Services Manager Taylor Baxter provided a brief overview of the existing acrylic wall sign installed without a permit on the south wall of the building that houses the Hometown Coffee and Juice business located at 700 Vernon Avenue. He clarified the roles of the Zoning Board of Appeals and the

Plan Commission in reviewing and approving wall signs in the downtown business district. The ZBA is responsible for granting variations on the size, ROW encroachment and elevation of the bottom of the wall sign. The PC is responsible for determining whether the sign is appropriate for this location based on the criteria found in the Design Guidelines. It was also noted that if the Plan Commission denied approval of the sign under its authority then the sign application would not go to the Zoning Board.

Lou Rubin, the owner and operator of Hometown Coffee and Juice provided the background on the evolution of the wall sign and its vision and purpose. He hired an artist who designed the image with a 3-dimensional effect to allow the public the ability to interact with the sign in the public right-of-way.

The Chair then asked each Commissioner to weigh in on the wall sign and the comments were largely supportive of the sign as well as the creativity of other past efforts of Hometown, specifically the temporary igloo structures erected on the sidewalk last fall and winter. It was also noted that while this type of sign is not fully contemplated in the present sign code, it is something that is generally of interest and supported by the community, so a future discussion on the sign code is warranted.

Following the discussion, Commissioner Mukherjee moved for and Commissioner Thompson seconded approval of the wall sign erected outside Hometown Coffee and Juice provided that the sign is maintained as a temporary installation not to exceed six months or such shorter period as the Village Board may direct.

The motion was approved by the following vote:

RESULT:	**ACCEPTED**
AYES:	Huvard, Miller, Mihalopoulos, Mukherjee, Onderdonk, Satter, Solon, Thompson, Turner, Van Vechten (10)
NAYS:	None (0)
ABSTAIN:	None (0)
ABSENT:	None (0)

6. STANDING COMMITTEE REPORTS/ANNOUNCEMENTS
Updates were provided on behalf of the Sustainability Task Force, curbside service and reopening plans for the Glencoe Public Library, School District 35's work on plans for the new school year and the Historic Preservation Commission's report on the plans for Booth Cottage relocation in July.

8. SCHEDULE NEXT MEETINGS OF THE PLAN COMMISSION
The next Plan Commission meeting was noted to be a special meeting on July 15, 2020 for the consideration of the Final Plat of Subdivision for the 1801 Green Bay Rd property.

9. ADJOURNMENT
Following a motion by Vice-Chairman Miller and a second by Commissioner Mukherjee the meeting was adjourned at 8:46 p.m.

DRAFT

VILLAGE OF GLENCOE
MEMORANDUM
675 Village Court, Glencoe, Illinois 60022
p: (847) 835-4111 | info@villageofglencoe.org | Follow Us: @VGlencoe
www.villageofglencoe.org

DATE: June 26, 2020

TO: Bruce Huvard, Chair; Plan Commission Members

FROM: David C. Mau, P.E., Public Works Director
Lee M. Brown, FAICP, Village Planner
Taylor Baxter, AICP, Development Services Manager
James Tigue, P.E., CFM, Civil Engineer

SUBJECT: 1801 Green Bay Road Subdivision

I. Summary and Background

The Petitioner, Glencoe Developers LLC, is proposing to develop the 12.2-acre parcel located at 1801 Green Bay Road into a 29-lot, detached single-family residential subdivision ("***Development***"). The Plan Commission reviewed the Preliminary Plat of subdivision for the proposed Development over three public meetings in the summer and fall of 2019. After extensive review and public comment, the Plan Commission passed a recommendation of approval of the Preliminary Plat with conditions on September 25, 2019. On October 17, 2019, the Village Board approved the Preliminary Plat by a resolution that included 20 conditions to be addressed by the Final Plat of subdivision. The Petitioner has since worked to revise the plans for the Development to meet these conditions. Staff analysis of these conditions and the Petitioner's fulfillment of them follows in Section III of this report.

After multiple rounds of submittals and revisions in response to staff review comments over the course of several months, in early June 2020, the Petitioner submitted updated and revised plans sufficient to support a Final Plat review by the Plan Commission. The revised plans do not change the proposed number of lots, site layout, or access and traffic management components of the Development. All proposed changes were made in response to the Village's Board's conditions of approval of the Preliminary Plat. The most substantial changes relate to the Development's proposed stormwater management system.

Following review and public comment, the Plan Commission is required to make a recommendation of approval or denial of the Final Plat, along with any recommended conditions of approval, to the Village Board which will make a final decision on the sufficiency of the plat along with other development approvals. Staff is of the opinion that this final plat has successfully met all the conditions required by the Village Board in its approval of the Preliminary Plat.

II. Role of Plan Commission in Final Plat review

The Plan Commission's role in Final Plat review is to provide a recommendation of approval or denial of the Development, along with any recommended conditions of approval, to the Village Board. This recommendation is to be made in accordance with the criteria for approval of a plat of subdivision set forth in the Village's subdivision code and the Preliminary Plat conditions approved by the Village Board.

Staff has determined that all changes to the Final Plat were made in response to Village Board comments and Preliminary Plat conditions of approval. There have been no changes to the, number, size, or arrangement of lots or rights-of-way. Therefore, the Plan Commission's review of the Final Plat should take into account the previous determination by the Village Board that if the Preliminary Plat conditions of approval are met, the number and location of lots are appropriate as proposed. The Final Plat review is not intended to be a full-scale re-review of the Development, but should rather focus on conformance with the Preliminary Plat and compliance with the Village Board's conditions. As with its Preliminary Plat review, the Plan Commission is tasked with fact-finding and decision-making based on the Final Plat and supporting documentation provided by the Petitioner, along with the testimony it hears and according to the criteria for review.

III. Analysis

A. Traffic and road alignment, site landscaping, tree preservation, neighborhood connectivity, open space, construction impact

There have been no alterations of the lot lines of the proposed 29 subdivided lots or proposed rights of way. The proposed road alignment, intersection improvements, deceleration and turning lanes, traffic control signage, markings and devices, and pedestrian access ways and neighborhood connectivity are consistent with the approved Preliminary Plat as modified by the conditions adopted by the Village Board. Site landscaping is generally consistent with the Preliminary Plat, with modifications that reflect the changes to the stormwater management changes and refinements requested by Village Staff. The tree preservation plan and open space details are consistent with the Preliminary Plat with additional refinements made to management of the site during and post construction, as requested by Village staff. As described below, the stormwater impact of the development on the Village's existing storm sewer system and surrounding private properties is anticipated to be significantly mitigated due to the Development's compliance with the MWRD's requirement that projects subject to the Watershed Management Ordinance (WMO) use the updated rainfall data from the Illinois State Water Survey Bulletin 75 and the Petitioner's subsequent modifications to the stormwater management system.

B. Stormwater management

The Petitioner has revised the stormwater detention system design to accommodate the updated rainfall data projections set forth in the updated ISWS Precipitation Frequency Study, referred to as "***Bulletin 75***". In order to provide the enlarged storm water detention capacity required by from the updated rainfall data included in Bulletin 75, the stormwater detention system was redesigned as with (a) an underground storm water storage system with a discharge to the Terrace Court Basin storm sewer system to the southeast and (b) a combined above-ground and underground storm water detention system with a discharge to Cook County Forest Preserve District (CCFPD) Turnbull Woods property to the northeast.

The underground storm water storage system consists of prefabricated chambers enveloped in stone backfill, to provide storage both within the chamber and the surrounding stone voids. The underground system will be

installed along the east side of Lots 16-24, between Lots 6 and 7, and beneath two permeable paver sections of the proposed Forest Edge roadway. This system will discharge out to the Terrace Court Basin storm sewer underground through a restricted outlet. The discharge rate from the restrictor will be a lower rate than the current overland flow from the property into the basin.

The above-ground storm water detention system consists of conveyance pipes around the bulb of the street and a dry pond (depressional area) in the rear of Lots 23 and 24. This above-ground system will discharge out to Turnbull Woods through a restricted outlet.

The underground and above-ground storm water storage systems will be interconnected via a manhole with a small diameter (1.5"), a low-flow restrictor pipe, and an internal weir to equalize flow during heavy rain events. The internal weir for equalizing flow allows for overland flows to discharge to Turnbull Woods. During rain events in excess of the 100-year storm, overflow will begin to discharge out of the surface discharge to Turnbull Woods. Should additional discharge be necessary, the above ground storm water system will overflow through a concrete weir along the north side of the dry pond onto the Turnbull Woods property. Should even more additional overflow capacity be necessary, internal overflows may discharge into the 12" storm sewer connection to the Terrace Court Basin storm sewer. No overland flow drainage will be directed towards the Terrace Court Basin properties or other adjacent residential properties. Berms are proposed along the east side of the Subdivision to provide additional protection from overland discharges to the adjacent residential properties.

C. Preliminary Plat conditions of approval from Village Board

On October 17, 2019, the Village Board approved the Preliminary Plat for the proposed subdivision of 1801 Green Bay Road. The Board's approving resolution included 20 conditions for the Petitioner to address prior to its submission of a Final Plat to the Village President and Board of Trustees. Since October, the Petitioner has worked to revise the Development plans to address these conditions. The following section analyzes the Petitioner's responses to the conditions.

Storm Water Management and Detention

1. The Final Plat and Final Engineering Plan for the Development must address how the proposed storm water detention system will accommodate extraordinary rainfall events. The system design must incorporate (a) a gravity fed equalizer pipe that will ensure than any rainfall exceeding the capacity of the southern detention basin proposed to be located on Outlot E ("Southern Detention Basin") be transferred to the northern detention basin proposed to be located on Outlot D ("Northern Detention Basin") and released gradually via overland flow; and/or (b) storm water detention basins of sufficient capacity to accommodate the rainfall projections set forth in the updated Bulletin 70 "Frequency Distributions of Heavy Precipitation in Illinois" published by the Illinois State Water Survey dated March 2019 and with the volume required by the most recent version of the Metropolitan Water Reclamation District's Watershed Maintenance Ordinance (WMO) in effect at the time all necessary permits for the storm water detention system are issued by the appropriate permitting authority, whichever is deemed to provide the Village, its storm water infrastructure, and the residents of the surrounding parcels with the greatest protection from unreasonable storm water overlap drainage. The determination of the solution providing the greatest amount of protection shall be made on the advice of the Village Engineer.

The Petitioner has proposed a revised storm water detention system design which includes an underground storm water detention system with a discharge to the Terrace Court Basin storm sewer system to the southeast and both above ground and underground storm water detention systems with a discharge to the

CCFPD Turnbull Woods property to the northeast. These systems are connected via a manhole with a small diameter (1.5") pipe connection and an internal weir for equalizing flow during heavy rain events. The internal weir for equalizing flow allows for overland flows to discharge to Turnbull Woods.

Additionally, the Petitioner has revised the storm water detention system design to accommodate the rainfall data projections included in Bulletin 75.

Note: The Petitioner's storm water management plan including all the detailed calculations and engineering modeling data has been carefully reviewed by the Village's staff engineers along with the Village's storm water consultant, Engineering Resource Associates.

2. The Petitioner must, prior to the approval of the Final Plat for the Development, obtain an easement to permit connection of the Southern Detention Basin to the Terrace Court Basin storm sewer, in a location and manner acceptable to the Village Engineer and in a form acceptable to the Village Attorney.

The Petitioner has purchased the property at 1188 Carol Lane and has commenced the process to reserve and dedicate an easement along the south property line of the property to allow for the installation and maintenance of an underground drainage line that will connect the storm water detention system for the southern portion of the Development to the Terrace Court Basin storm sewer system.

3. The Petitioner shall make all commercial reasonable efforts to include best management practices for creating better water infiltration at areas (other than the detention basins) throughout the site. Such practices should be considered and incorporated when beneficial.

The Petitioner has proposed the installation of pervious pavers installed in two locations of the roadway and a bioswale in the rear yards of Lots 20-23. In addition, all stormwater detention chambers will be surrounded by compacted stone containing air voids that will serve to retain stormwater.

<u>Maintenance of Subdivision Improvements; Declaration</u>

*1. The obligation of the homeowners' association ("**HOA**") to repair, maintain in good working condition, or replace the Storm Water Detention Improvements (as defined below), pedestrian access paths, landscaping, fencing and other commonly owned subdivision improvements (collectively, the "Common Improvements") shall be memorialized in a Declaration of Covenants for the Development ("**Declaration**"), which Declaration shall be executed and recorded against the entirety of the Subject Property by the Petitioner simultaneously with the Final Plat.*

This requirement will be integrated into the Subdivision and Development Agreement, which will be recorded against the parcel. The Village Attorney is also reviewing a preliminary version of the Declaration to ensure that this concept is included.

2. The Declaration shall be in a form and substance acceptable to the Village Attorney and shall clearly establish the right of the Village to either (a) take legal action to compel the HOA to repair, maintain, or replace the Common Improvements, or (b) to enter upon the Subject Property, or any lot thereupon whether privately or commonly owned by the HOA, to undertake such work as may be necessary to repair, maintain, or replace the Common Improvements.

This requirement will be integrated into the Subdivision and Development Agreement, which will be recorded against the parcel. The Village Attorney is also reviewing a preliminary version of the Declaration to ensure that this concept is included.

3. The approvals of the Final Plat and Declaration for the Development shall explicitly provide for the creation of a special service area to be created if deemed necessary by the Village to ensure that sufficient funds are available to pay for the repair, maintenance, or replacement of the Common Improvements as may be needed from time to time in the absence of the HOA assessing sufficient funds for this purpose.

This requirement will be integrated into the Subdivision and Development Agreement, which will be recorded against the parcel. The Developer will be required to agree not to object to the establishment of this "***Backup SSA".*** Staff and the Village Attorney are working together to determine how much of a reserve should be levied to ensure that there are sufficient funds to maintain essential improvements in the event that the Developer or the HOA fails to do so.

4. The Declaration shall include a detailed Operation and Maintenance Plan for the storm water detention basins and all appurtenant mains, pipes, pumps and other facilities (collectively, the "Storm Water Detention Improvements") that shall include a schedule for regular cleaning and landscaping as well as mosquito control measures that will be followed.

This requirement will be integrated into the Subdivision and Development Agreement, which will be recorded against the parcel. The Village Attorney is also reviewing a preliminary version of the Declaration to ensure that these plans are incorporated into the Declaration.

5. Outlot A shall be reserved and dedicated in the Declaration as open space for passive enjoyment of the residents of the Development and the general public. This reservation and dedication shall not preclude the improvement of Outlot A with such accommodations and improvements as picnic seating, benches, shelters, or gazebos, so long as such improvements are open and available to the general public. Outlot A shall remain owned and maintained by the HOA.

This requirement will be integrated into the Subdivision and Development Agreement, which will be recorded against the parcel. The Village Attorney is also reviewing a preliminary version of the Declaration to ensure that this concept is included.

6. Outlot B shall also be subject to an easement for public access and enjoyment.

This requirement will be integrated into the Subdivision and Development Agreement, which will be recorded against the parcel. The Village Attorney is also reviewing a preliminary version of the Declaration to ensure that this concept is included.

<u>Public Rights of Way, Roads, and Sidewalks</u>

1. The Final Plat shall include a permanent irrevocable emergency access easement from the Northwood Drive cul-de-sac to Estates Road through the side yards of either or both Lots 28 and 29 sufficient accommodate the passage of a ten-foot-wide emergency vehicle between the two public rights-of-way.

This has been included on the Final Plat.

2. The Final Plat shall also include a permanent irrevocable pedestrian easement allowing members of the general public to access the Development from the Northwood Drive cul-de-sac. The final configuration and route of such easement shall be approved by the Village Engineer. The pedestrian easement shall be paved, ADA accessible, and considered a Common Improvement to be maintained, repaired, and replaced by the HOA.

Consistent with the condition, above, the Petitioner has proposed a 5-foot wide concrete sidewalk with 2.5 feet of Grasspave along both sides, creating a ten-foot-wide corridor within the emergency and pedestrian access easement.

3. No sidewalks shall be required to be installed on Outlot A, C, D or E, but a sidewalk shall be installed along the frontage of all Lots with street frontage on Estates Road within the dedicated public utility easements.

Consistent with the condition, above, the Petitioner has proposed a 5-foot wide sidewalk along the frontage of all Lots with street frontage on Forest Edge Drive.

*4. The existing masonry entry piers and walls located on the proposed Lot 1 ("**Historic Gateway Features**"), shall be preserved and incorporated into the design and landscaping of the Development. The maintenance of the Historic Gateway Features will be the responsibility of the HOA; provided, however, that the Petitioner shall grant to the Village a preservation easement, or such other legal right deemed sufficient, in the opinion of the Village Attorney, to allow the Village to prevent the destruction, removal, or damage to the Historic Gateway Features and to enforce the HOA's responsibility to maintain the Historic Gateway Features.*

Consistent with the condition, above, the existing masonry entry will be maintained in its current location. This condition will be incorporated into the Subdivision and Development Agreement.

5. That any entrance signage at the Estates Road entry to the Development must conform to the Village's sign ordinance.

The Petitioner is no longer proposing any entrance signage.

6. That all improvements, realignments, re-striping, and other traffic control improvements necessary to align Westley Road and Estates Road, and to reconfigure the lanes, turn lanes, traffic advisory signs, and other traffic control devices recommended in the revised traffic impact study from KLOA, last revised August 16, 2019, be the sole responsibility of the Petitioner to fund and, unless required otherwise by the Village, construct in accordance with all applicable road construction standards.

All traffic control improvements on Green Bay Road, Westley Road and Forest Edge Drive included in the engineering plans prepared by IG Consulting for the Subdivision improvements will be constructed and installed by the Petitioner.

<u>Tree Protection and Landscaping</u>

*1. The Petitioner will be required to enter into a subdivision and development agreement ("**Development Agreement**") requiring the implementation of the tree protection plans (as presented in the application and as otherwise required by the Village Code) for both the Common Improvements and private lot development,*

subject to review and approval by the Village Attorney.

The Petitioner has submitted a tree preservation plan and draft agreement language that is consistent with the tree protection plan as presented as part of the Preliminary Plat of subdivision. In addition to identifying the specific trees that will be lost to the construction of roads, utilities, and other site improvements, the plan identifies in detail the areas that will be enclosed by tree protection fencing during the construction period, and trees that will receive specific root and crown reduction pruning, auguring or air spading or other preventative measures.

2. The Development Agreement will memorialize and quantify, the Petitioner's commitment planting substitute trees on the property "where feasible", with specific exceptions or limits to the determination of "where feasible" to be adopted prior to approval of the Final Plat.

The Village's practice as outlined in the Tree Preservation ordinance is to require a deposit of funds by the developer, in advance of issuance of permits, to compensate for the loss of any existing tree exceeding eight caliper inches in diameter (other than prohibited species and trees of very poor condition). Replacement trees offset the loss of existing caliper inches. The loss of trees due to the construction of public improvements, lot grading, and other site improvement necessary for the preparation of developable lots is the responsibility of the developer. The submitted plans estimate the loss of 82 trees requiring a deposit for compensation of approximately 1,570 caliper inches.

Consistent with the condition, above, the Petitioner has submitted tree replacement plans which indicate the anticipated planting of 189 new trees on the site, totaling approximately 1,100 caliper inches. The proposed siting of trees, "where feasible" have focused along the back lot line of proposed lots, particularly along the eastern edge of the property as a buffer to existing neighborhoods, as street trees along the proposed Forest Edge street pavement, and as infill within the cluster of trees in Outlot A. Areas that have been specifically precluded from planting replacement trees include those areas with underground stormwater detention structures.

Trees within the individual subdivided lots will also be lost but are not part of the calculation of tree preservation deposit at the time of Final Plat approval. Some lots will be unaffected, but most lots have existing trees that are unlikely to be avoided as part of the siting of new homes. Each home builder/new owner will be required to meet the requirements of the tree preservation ordinance and thus, at the time of the request for a building permit, will be required to make a deposit based on the calculation of lost caliper inches resulting from construction of the house they plan to build. The Petitioner cannot know at this time how a home will be sited and which trees will be lost on each lot. The Village has had success in minimizing tree loss when it has been able to discuss the tree preservation ordinance requirements with a prospective home builder in advance of the submission of a building permit request. As such, the Village Staff seeks to include language within the Subdivision and Development Agreement that will require a preapplication conference with each home builder to encourage the preservation of the greatest number of trees on each lot.

3. The Development Agreement will incorporate a tree replacement plan to be approved by the Village arborist to assure that competitive canopies or root disturbances are not likely to result in future tree losses.

Consistent with the condition, above, the submitted tree replacement plan includes siting of trees where pre-existing trees have died or will have been removed due to their decayed condition. These replacement trees

may require sensitivity in addressing the root structure of existing healthy remaining trees, and the development agreement will include language on the use of best management practices.

4. The Development Agreement will require that the removal of existing trees or plants, including invasive species like Buckthorn or other "Removable Trees," as defined in the Village Code, not create nuisance conditions on surrounding parcels, including, without limitation, unreasonable runoff of herbicides or soil erosion.

Consistent with the condition, above, the tree preservation and landscape plans submitted anticipate the removal of all invasive species including buckthorn, poplar, cottonwood, ash, Siberian elm, boxelder, and Norway maple, as well as trees that are dead, dying or otherwise a threat to safety. Language within the Subdivision and Development will address surety of landscape management practice to protect surrounding parcels and public health.

5. The Development Agreement will require that the perimeter fence proposed to be installed around the Development be a uniform board-on-board wood fence at the perimeter of the subdivision on lots 1, 2, 3, 10-22, 28, 29 and Outlots B, E and the western side of Outlot C; and a wrought iron-look fence at the perimeter of the subdivision on lots 23-27, Outlot D and the northern side of Outlot C.

Consistent with the condition, above, the final subdivision plans include specific location and identify the materials planned for perimeter fencing consistent with condition 5.

IV. Recommendation

Staff has thoroughly reviewed the proposed Final Plat and has determined that it is in compliance with the criteria for approval as listed in the Village's Subdivision Ordinance and with the Preliminary Plat conditions of approval required by the Village Board. If the Plan Commission determines that this assessment is correct, staff recommends that the Commission make a recommendation of approval of the Final Plat to the Village Board. The Plan Commission may also recommend approval of the Final Plat with conditions, or, if it determines that staff's assessment of the Final Plat is incorrect, it may recommend denial.

Attachments:

1. Engineering Resource Assoc. – Technical Memorandums (2) – both dated 6/8/20
2. Forest Edge Plat of Subdivision – dated 6/8/20
3. 1801 Green Bay Engineering Plans – dated 5/8/20
4. Forest Edge Landscape Plans – dated 6/8/20
5. Storm Water Report – IG Consulting – dated 5/8/20
6. O & M Report – IG Consulting – dated 6/8/20

Technical Memorandum

Project:
Forest Edge Subdivision Stormwater Management Review

Location:
Glencoe, IL

Prepared For:
Village of Glencoe
675 Village Court
Glencoe, IL 60022

Prepared By:
Engineering Resource Associates, Inc.
3s701 West Avenue, Suite 150
Warrenville, IL 60555
630.393.3060

Prepared On:
June 8, 2020

Introduction

IG Consulting Inc. has submitted plans to develop a 12-acre parcel of land on the east side of Green Bay Road just south of Turnbull Woods and west of Carol Lane. Engineering Resource Associates (ERA) has completed several design reviews to ensure the project has a positive stormwater impact on Carol Lane properties and the recently improved Terrace Court storm sewer system. The latest review was performed on plans and calculations dated May 8, 2020.

Methodology and Purpose

The purpose of the ERA review was to ensure that the plans substantially meet Village and MWRD ordinances prior to submitting to the MWRD for permit. The review was also performed to verify that the changes to the land do not adversely impact neighboring properties and the recently constructed Terrace Court storm sewer system. Utilizing the applicant's design, ERA revised the 2014 Terrace Court study model to evaluate how the proposed land use and design impact the constructed sewer improvements. The Terrace Court technical memorandum summarizes those results and can be found under a separate cover.

Conclusions and Recommendations

Based on our review of the project plans and stormwater report we feel the design meets the requirements set forth by the Village Plan Commission in 2019 and substantially meets Village and MWRD stormwater requirements. The applicant's design has successfully accomplished the following:

1. The detention pond significantly reduces flows to the Terrace Court storm sewer system. A complete analysis of the changes to the Terrace Court system were modeled and a separate technical memo was submitted summarizing the detailed results.
2. The detention pond significantly reduces runoff to the rear yards of homes located on Carol Lane.
3. The detention pond has been sized for the increased rainfall amounts recently adopted by the MWRD.
4. The emergency overflow for the detention pond has been directed into Turnbull Woods and away from Carol Lane Properties and the Terrace Court storm sewer system.
5. The design has provided a storm sewer system with capacity to convey the 10-year storm event with overland flow paths that can convey the 100-year runoff safely to the detention facility.

ERA recommends that the design be submitted to the MWRD for their review and approval. All correspondences with the MWRD and design changes requested by MWRD should be forwarded to the Village for their review as well.

Technical Memorandum

Project:
Terrace Court Storm Sewer Analysis
Forest Edge Subdivision Comparison

Location:
Glencoe, IL

Prepared For:
Village of Glencoe
675 Village Court
Glencoe, IL 60022

Prepared By:
Engineering Resource Associates, Inc.
3s701 West Avenue, Suite 150
Warrenville, IL 60555
630.393.3060

Prepared On:
June 8, 2020

ENGINEERING RESOURCE ASSOCIATES

Table of Contents

Introduction 3

Historical Background 3

Purpose and Methodology 3

Summary of Results 4

Table 1: HWL at Park Place Sag 4

Table 2: HWL at Old Elm Lane Sag 4

Table 3: HWL at Linda Lane 4

Table 4: HWL at Outfall Ditch 4

Conclusions and Recommendations 4

Appendix

Exhibit 1: Revised Terrace Court Watershed

Exhibit 2: Existing Condtions Flooding Limits from 2014 Study

Exhibit 3: Forest Edge Subdivision Existing Conditions Tributary Areas

Exhibit 4: Proposed Conditions 1% Flood Risk from 2014 Study

Thumb Drive Containing XPSWMM Models

Introduction

The Village of Glencoe (Village) completed the Terrace Court Basin Storm Water Drainage Study in December 2014. The study recommended increasing the storm sewer capacity to convey the runoff from a storm with a 1% chance of occurrence in a giving year. The recommended improvements were constructed in 2016 and have resulted in significant improvements to the frequency and severity of flooding in the neighborhood. In 2019 the rainfall data used to size storm sewer systems in Illinois was updated to reflect the trend of more intense rain events. In general, rainfall was increased by approximately 10-15%. In addition, IG Consulting Inc. submitted plans in 2019/2020 to develop approximately 12 acres of property at 1801 Green Bay Road just west of Carol Lane of which a portion of the development is tributary to the Terrace Court improved storm sewer system. The Village of Glencoe requested that Engineering Resource Associates, Inc. (ERA) update the 2014 Drainage Study with the new Illinois rainfall data and compare the system performance with and without the new Forest Edge development to ensure that the design will have a positive impact on the new storm sewer system.

Historical Background

The primary purpose of the original 2014 study was to reduce the frequency and severity of the stormwater leaving the public right-of-way and contributing to private property flooding problems. Exhibit 2 from the original study (attached) shows how frequent and severe flooding was prior to the 2016 improvements. Exhibit 4 from the original study is also attached and depicts the extent of flooding following the 2016 improvements for comparison purposes. It is important to note that public right-of-way improvements alone would not eliminate flood risks for certain areas as shown on Exhibit 4. Internal drainage from the properties surrounded by Carol Lane, Terrace Court, and Park Place drain directly to a significant swale along the south side of the property at 1162 Terrace Court where a storm sewer drains the water under Terrace Court to a swale directly across the street. During extreme storm events water fills the swale opposite of 1162 Terrace Court and wants to back up into the property. A backflow preventer was installed to minimize this backup. However, high water elevations in the swale will block runoff coming from the internal drainage area. Exhibit 4 from the 2014 study depicts that potential flooding during extreme events.

Purpose and Methodology

Utilizing the 2014 hydrologic/hydraulic XPSWMM model ERA updated rainfall data and revised tributary areas of the area west of Carol Lane to reflect the pre and post conditions of the proposed Forest Edge Subdivision (Subdivision) currently under review. The revisions are reflected on Exhibit 1 provided in this memo. The hatched area is what was originally modeled as runoff to the Terrace Court system. This area has been reduced in the Pre- Subdivision model to reflect the 1.6-acre tributary area (Area A) from the Subdivision existing conditions plan provided as Exhibit 3. The hatched area has been replaced by the proposed detention facility release rate in the Post-Subdivision model to reflect the developer's detention design. In addition, the 3.6-acre tributary area (Area B) has been added to the Pre-Subdivision model to mimic the survey from the Subdivision existing conditions plan provided as Exhibit 3. Pre- and Post-Subdivision XPSWMM models were run to understand the impacts to the Terrace Court system. Summary tables have been provided that directly compare the performance of the storm sewer pre- and post- Subdivision.

Summary of Results

The Terrace Court system has four critical areas that determine the extent and severity of flooding. These locations are the sag on Park Place just east of Carol, the sag on Old Elm Lane just north of West Elm Court, the low spot at the north end of Linda Lane, and at the Terrace Court Basin outfall across from 1162 Terrace Court. Tables 1-4 compare the pre- and post- Subdivision water levels at these four critical spots for four significant storm events (10% chance of occurrence or 10-year storm, 4% chance of occurrence or 25-year storm, 2% chance of occurrence or 50-year storm, 1% chance of occurrence or 100-year storm).

Event	*10% Occurrence*		*4% Occurrence*		*2% Occurrence*		*1% Occurrence*	
Model	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*
Water Elevations	667.98	667.92	668.47	668.35	671.34	670.39	672.78	672.32

TABLE 1: HWL at Park Place Sag

*Street ponding begins at approximately 673.25

Event	*10% Occurrence*		*4% Occurrence*		*2% Occurrence*		*1% Occurrence*	
Model	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*
Water Elevations	665.78	665.78	666.58	666.35	670.19	669.64	671.16	671.10

TABLE 2: HWL at Old Elm Lane Sag

*Street ponding begins at approximately 670.60

Event	*10% Occurrence*		*4% Occurrence*		*2% Occurrence*		*1% Occurrence*	
Model	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*
Water Elevations	669.14	669.11	670.70	670.58	675.06	674.07	676.72	676.48

TABLE 3: HWL at Linda Lane

*Street ponding begins at approximately 676.25

Event	*10% Occurrence*		*4% Occurrence*		*2% Occurrence*		*1% Occurrence*	
Model	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*	*PRE*	*POST*
Water Elevations	661.64	661.32	663.19	662.87	664.06	663.79	664.51	664.34

TABLE 4: HWL at Outfall Ditch

Conclusions and Recommendations

Based on the analysis of the pre- and post-Forest Edge Subdivision the proposed development will have a positive impact on the Terrace Court storm sewer system. As shown on the summary tables provided in this technical memorandum the proposed detention facility, as currently designed, will reduce flows to the storm sewer system, reducing water levels and increasing the level of service to the residents in the Terrace Court Basin area. Water elevations in the receiving swale across from 1162 Terrace Court will be reduced, further protecting properties. This improvement alone will not eliminate high water elevations in the receiving ditch from blocking runoff from the internal drainage area. To that end, ERA would recommend that further improvements such as a permanent pump station to relieve the volume of water from the internal drainage area that drains to the 1162 Terrace Court property during extreme rainfall events be investigated.

Exhibit 1
Terrace Court Watershed

Legend

Glencoe Storm Sewer

Watershed Sub Boundary

Watershed Boundary

Watershed Area	
Basin	Area(Acres)
1	0.73
2	0.61
3	0.33
4	4.3
5	0.09
6	0.18
7	3.55
8	0.94
9	0.19
10	1.62
11	3.1
12	0.37
13	1.65
14a	2.25
14b	1.76
15	2.09
16	1.61
17	0.85
18	0.44
19	1.46
20	1.63
21	0.79
22	0.99
23	4.63
24	14.78
Hatched	3.99
Total	54.93

ENGINEERING
RESOURCE ASSOCIATES

1 inch = 100 feet

0 50 100 200 300 400 Feet

Date: 5/13/2020
User Name: glordan
Document Path: O:\Cook County\Glencoe\140706 S Locations\140706 Glencoe Adjusted.mxd



Legend


- Watershed Boundary
- 50% Flood Risk (2-Year Storm Event)
- 10% Flood Risk (10-Year Storm Event)
- 2% Flood Risk (50-Year Storm Event)
- 1% Flood Risk (100-Year Storm Event)
- Manhole
- Existing Storm Sewers
- 1 Foot Contours

EXHIBIT 2
TERRACE COURT
EXISTING CONDITION
FLOODING LIMITS

ENGINEERING RESOURCE ASSOCIATES, INC.
Consulting Engineers, Scientists & Surveyors
www.eraconsultants.com

100 50 0 100 Feet

1 inch = 50 feet



REVISIONS		
DATE	DESCRIPTION	DRAWN BY
06/03/19	VILLAGE REVIEW	S.R.M.
07/22/19	REVISED ENTRANCE	S.R.M.
07/29/19	FOR SUBMITTAL	S.R.M.
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

EXISTING TRIBUTARY EXHIBIT | DESIGN: K.C.L | DRAFTING: S.R.M. | SCALE: 1"=40' | DATE: 05/06/2019

FIRM NO. 184-001330

1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557

1 of 1

COPYRIGHT AS DATED © IG CONSULTING, INC.

C:\IG\18557\Engr\18557-EP.dwg



Legend

- Watershed Boundary
- Existing Storm Sewers
- Manhole
- 1 Foot Contours
- 1% Flood Risk (100-Year Storm Event)
- 2% Flood Risk (50-Year Storm Event)
- 4% Flood RIsk (25-Year Storm Event)

EXHIBIT 4
TERRACE COURT
PROPOSED CONDITION
1% FLOOD RISK SOLUTION
(100-YEAR STORM EVENT)

ENGINEERING RESOURCE ASSOCIATES, INC.
Consulting Engineers, Scientists & Surveyors
www.eraconsultants.com

100 50 0 100 Feet

1 inch = 50 feet

FINAL PLAT OF SUBDIVISION

FOREST EDGE SUBDIVISION

OF

BEING A SUBDIVISION IN THE NORTH QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, COOK COUNTY, ILLINOIS.

EXISTING PINS:
PARCEL 1 = 04-01-200-011
PARCEL 2 = 04-01-200-006

SEND TAX BILL TO:

NAME: _____

ADDRESS: _____

CITY: _____

STATE: _____

TOTAL SUBDIVISION AREA = 12.11 ACRES

RIGHT OF WAY DEDICATION = 1.51 ACRES

SCALE

50 0 25 50 100 200

(IN FEET)
1 inch = 50 ft.

ALL DISTANCES IN FEET AND DECIMAL PARTS THEREOF.
NO DIMENSIONS TO BE ASSUMED FROM SCALING.

COMPARE YOUR DESCRIPTION AND SITE MARKINGS WITH THIS PLAT AND AT ONCE REPORT ANY DISCREPANCIES WHICH YOU MAY FIND.

REFER TO TITLE REPORT FOR ANY EASEMENTS, COVENANTS OR RESTRICTIONS THAT MAY EXIST BUT ARE NOT SHOWN HEREON.

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\18557-SP.dwg

REVISED: 06/08/20
REVISED: 04/17/20
REVISED: 02/20/20
REVISED: 02/19/20
PREPARED: 01/17/20

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

PREPARED FOR: GLENCOE DEVELOPERS LLC | SCALE: 1"=50' | DRAFTED BY: S.R.M. | CHECKED BY:
FIELD CREW: D.J. | FIELD WORK: 2018 | FIRM NO. 184-001330

FINAL PLAT OF SUBDIVISION
FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT NUMBER
18557

FINAL PLAT OF SUBDIVISION
FOREST EDGE SUBDIVISION
OF

BEING A SUBDIVISION IN THE NORTH QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, COOK COUNTY, ILLINOIS.

REVISED: 06/08/20
REVISED: 04/17/20
REVISED: 02/20/20
REVISED: 02/19/20
PREPARED: 01/17/20

PRESIDENT AND BOARD OF TRUSTEES CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

APPROVED AND RIGHT OF WAY DEDICATION HEREBY ACCEPTED, BY THE PRESIDENT AND BOARD OF TRUSTEES OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS

THIS _____ DAY OF _____ A.D., 20__.

_____
VILLAGE PRESIDENT

_____
ATTEST: VILLAGE TREASURER

VILLAGE ENGINEER CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

APPROVED BY THE VILLAGE ENGINEER OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS

THIS _____ DAY OF _____ A.D., 20__.

_____
VILLAGE ENGINEER

PLAN COMMISSION CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

RECOMMENDED BY THE PLAN COMMISSION OF THE VILLAGE OF GLENCOE, ILLINOIS

THIS _____ DAY OF _____ A.D., 20__.

_____
CHAIRMAN

_____
SECRETARY

EASEMENT FOR STORM SEWER

A PERMANENT AND PERPETUAL NON-EXCLUSIVE EASEMENT IS HEREBY GRANTED TO THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS (" VILLAGE"), TO SURVEY, CONSTRUCT, RECONSTRUCT, USE, OPERATE, MAINTAIN, TEST, INSPECT, REPAIR, REPLACE, ALTER, REMOVE OR ABANDON IN PLACE STORM SEWER MAINS, TOGETHER WITH RELATED ATTACHMENTS, EQUIPMENT AND APPURTENANCES THERETO, IN, UPON, UNDER, ALONG AND ACROSS THE AREAS DESIGNATED "STORM SEWER EASEMENT" ON THIS SUBDIVISION PLAT. THE OWNERS OF THE PROPERTY SUBDIVIDED ON THIS PLAT OR ANY PART THEREOF HEREBY RESERVE THE RIGHT TO USE THE AREAS DESIGNATED "STORM SEWER EASEMENT" AND THE ADJACENT PROPERTY IN ANY MANNER THAT WILL NOT PREVENT OR INTERFERE WITH THE EXERCISE BY THE VILLAGE OF THE RIGHTS HEREBY GRANTED; PROVIDED, HOWEVER, THAT THE OWNERS SHALL NOT IN ANY MANNER DISTURB, DAMAGE, DESTROY, INJURE, OBSTRUCT OR PERMIT TO BE OBSTRUCTED THE "STORM SEWER EASEMENT" AT ANY TIME WHATSOEVER WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF THE VILLAGE'S VILLAGE MANAGER.

PUBLIC UTILITY & ACCESS EASEMENT

A PERMANENT AND PERPETUAL NON-EXCLUSIVE EASEMENT IS HEREBY GRANTED TO THE VILLAGE, NORTH SHORE GAS COMPANY, COMCAST CABLE, COMMONWEALTH EDISON COMPANY, AT&T AND WIDE OPEN WEST, THEIR SUCCESSORS AND ASSIGNS, IN ALL AREAS DESIGNATED "PUBLIC UTILITY & ACCESS EASEMENT ON THIS SUBDIVISION PLAT, SAID EASEMENTS SHALL BE FOR THE INSTALLATION, MAINTENANCE, RELOCATION, RENEWAL AND REMOVAL OF PUBLIC UTILITIES, DRAINAGE FACILITIES AND RELATED APPURTENANCES, IN, UNDER, ACROSS, ALONG AND/OR UPON THE SO DESIGNATED PROPERTY. IT SHALL INCLUDE THE RIGHT TO ENTER THE SUBDIVIDED PROPERTY AND SUCH AREAS FOR ALL SUCH PURPOSES, AND THE RIGHT, WITHOUT LIABILITY, TO CUT, TRIM, ALTER AND/OR REMOVE ANY VEGETATION, ROOTS, STRUCTURES OR DEVICES WITHIN THE DESIGNATED EASEMENT PROPERTY AS MAY BE REASONABLY REQUIRED INCIDENT TO THE RIGHT HEREIN GIVEN.

WITHOUT PRIOR WRITTEN CONSENT OF THE GRANTEES, NO BUILDINGS, STRUCTURES OR OTHER OBSTRUCTION SHALL BE CONSTRUCTED, PLANTED OR PLACED IN ANY SUCH EASEMENT AREAS, NOR SHALL ANY OTHER USES BE MADE THEREOF WHICH WILL INTERFERE WITH THE EASEMENTS GRANTED HEREBY. SUCH EASEMENTS SHALL FURTHER BE FOR THE PURPOSE OF SERVING ALL AREAS SHOWN ON THIS PLAT AS WELL AS OTHER PROPERTY, WHETHER OR NOT CONTIGUOUS THERETO, WITH GAS, ELECTRIC, TELEPHONE, FIBER-OPTIC AND/OR CABLE TV, WATERMAINS, SANITARY AND STORM SEWERS.

SUCH EASEMENTS SHALL SURVIVE THE VACATION BY PROPER AUTHORITY OF ANY STREET AND OTHER PUBLIC WAY AND PLACE SHOWN ON THIS PLAT, UNLESS OTHERWISE EXPRESSLY MENTIONED IN AN ORDINANCE OF VACATION.

EMERGENCY & PEDESTRIAN ACCESS EASEMENT

A PERMANENT AND PERPETUAL NON-EXCLUSIVE EASEMENT IS HEREBY RESERVED FOR AND GRANTED TO THE VILLAGE ON, OVER, UPON AND ACROSS, THOSE AREAS DEPICTED ON THE PLAT AS "EMERGENCY & PEDESTRIAN EASEMENT" FOR MUNICIPAL EMERGENCY VEHICULAR USE AND PUBLIC PEDESTRIAN USE, BICYCLE USE (NON-MOTORIZED VEHICLES), AND ACCESS, AND FOR THE VILLAGE TO IMPROVE, INSTALL, CONSTRUCT, RENEW, CLEAR, RECONSTRUCT, REPLACE, REMOVE, REPAIR, ALTER, INSPECT, OPERATE, AND MAINTAIN SAME.

RESTRICTIVE COVENANTS AND EASEMENT FOR STORM WATER MANAGEMENT AREA

1. THE AREA OF THE PROPERTY DESIGNATED ON THIS PLAT AS "STORM WATER MANAGEMENT AREA" SHALL BE CONTINUOUSLY MAINTAINED IN A FIRST RATE MANNER BY FOREST EDGE SUBDIVISION HOMEOWNERS' ASSOCIATION (THE "ASSOCIATION") AND AN EASEMENT ON, UNDER AND ABOVE THE STORM WATER MANAGEMENT AREA IS HEREBY GRANTED TO, AND FOR THE USE AND BENEFIT OF, ALL OF THE LOTS IN THIS SUBDIVISION AND THE HOMEOWNERS' ASSOCIATION FOR THE SOLE PURPOSE OF STORM WATER DETENTION AND DRAINAGE.

2. NO CHANGE SHALL BE MADE IN THE FINISHED GRADE OF THE LAND WITHIN THE STORM WATER MANAGEMENT AREA, NOR SHALL ANY CONSTRUCTION OF ANY KIND WHATSOEVER BE ERECTED OR PERMITTED TO EXIST WITHIN THE STORM WATER MANAGEMENT AREA THAT MIGHT MATERIALLY IMPEDE STORM WATER DRAINAGE THEREIN OR MATERIALLY REDUCE THE STORM WATER DETENTION CAPACITY THEREOF. TREES, SHRUBS, FENCES AND NORMAL LANDSCAPE PLANTING ASIDE FROM THOSE DEPICTED IN THE FINAL ENGINEERING AND LANDSCAPE PLANS FOR THE FOREST EDGE SUBDIVISION SHALL BE PERMITTED WITHIN THE STORM WATER MANAGEMENT AREA ONLY WITH THE PRIOR WRITTEN APPROVAL OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS (THE "VILLAGE").

3. IN THE EVENT THE VILLAGE DETERMINES, IN ITS SOLE AND ABSOLUTE DISCRETION, THAT PRIOR MAINTENANCE OF THE STORM WATER MANAGEMENT AREA, AS REQUIRED BY THE DECLARATION FOR THE FOREST EDGE SUBDIVISION, IS NOT PERFORMED AT ANY TIME, THE VILLAGE, AFTER TEN (10) DAYS PRIOR WRITTEN NOTICE TO THE ASSOCIATION, MAY, BUT SHALL NOT BE OBLIGATED TO, ENTER UPON THE STORM WATER MANAGEMENT AREA FOR THE PURPOSE OF PERFORMING MAINTENANCE WORK ON AND TO THE STORM WATER MANAGEMENT AREA.

4. IN THE EVENT THAT THE VILLAGE SHALL CAUSE TO BE PERFORMED ANY WORK PURSUANT TO THESE PARAGRAPHS, THE VILLAGE SHALL HAVE THE RIGHT TO CHARGE THE ASSOCIATION AN AMOUNT SUFFICIENT TO DEFRAY THE ENTIRE COST OF SUCH WORK OR ACTION, INCLUDING ADMINISTRATIVE COSTS, EITHER BEFORE OR AFTER SUCH COST IS INCURRED. IF THE AMOUNT SO CHARGED IS NOT PAID BY THE ASSOCIATION WITHIN THIRTY (30) DAYS FOLLOWING A DEMAND IN WRITING BY THE VILLAGE FOR SUCH PAYMENT, SUCH CHARGE, TOGETHER WITH INTEREST AND COSTS OF COLLECTION, SHALL BECOME A LIEN UPON THE STORM WATER MANAGEMENT AREA AND LOTS 1-29 IN THIS SUBDIVISION AND THE VILLAGE SHALL HAVE THE RIGHT TO COLLECT SUCH CHARGE, WITH INTEREST AND COSTS, AND TO ENFORCE SUCH LIEN AS IN FORECLOSURE PROCEEDINGS AS PERMITTED BY LAW.

5. NOTHING IN THESE PARAGRAPHS SHALL BE CONSTRUED TO CONSTITUTE A DEDICATION OF ANY PORTION OF THE STORM WATER MANAGEMENT AREA TO, OR AN ACCEPTANCE THEREOF BY, THE VILLAGE.

6. THE VILLAGE SHALL BE UNDER NO OBLIGATION TO EXERCISE THE RIGHTS GRANTED IN THESE PARAGRAPHS EXCEPT AS IT SHALL DETERMINE TO BE IN ITS BEST INTEREST. NO FAILURE TO EXERCISE AT ANY TIME ANY RIGHT HEREIN GRANTED TO THE VILLAGE SHALL BE CONSTRUED AS A WAIVER OF THAT OR ANY OTHER RIGHTS.

7. THESE COVENANTS SHALL RUN WITH THE LAND IN THE SUBDIVISION SHOWN ON THIS PLAT, AND SHALL BE BINDING UPON AND INURE TO THE BENEFIT OF THE OWNERS OF ALL LOTS OF RECORD THEREIN, THEIR RESPECTIVE SUCCESSORS, ASSIGNS AND GRANTEES AND ALL PARTIES CLAIMING BY, THROUGH AND UNDER THEM. ENFORCEMENT OF THESE COVENANTS MAY BE SOUGHT BY THE OWNERS OF ANY LOTS OF RECORD IN THIS SUBDIVISION, ANY PERSON WITH AN INTEREST IN ANY OF SAID LOTS OF RECORD, OR THE VILLAGE OF GLENCOE BY ANY PROCEEDING AT LAW OR IN EQUITY AGAINST ANY PERSON OR PERSONS VIOLATING OR ATTEMPTING TO VIOLATE ANY COVENANT, EITHER TO RESTRAIN VIOLATION, TO COMPEL AFFIRMATIVE ACTION, OR TO RECOVER DAMAGES, AND AGAINST THE LAND TO ENFORCE ANY LIEN CREATED BY THESE COVENANTS.

OPEN SPACE COVENANT AND EASEMENT

THE AREA OF THE PROPERTY DESIGNATED ON THIS PLAT AS "OPEN SPACE EASEMENT AREA" SHALL BE CONTINUOUSLY MAINTAINED AS OPEN SPACE IN ITS NATURAL CONDITION BY FOREST EDGE SUBDIVISION HOMEOWNERS' ASSOCIATION (THE "ASSOCIATION"). NO MANMADE STRUCTURE OF ANY KIND SHALL BE CONSTRUCTED THEREON NOR SHALL ANY GRADING BE PERMITTED EXCEPT FOR THOSE IMPROVEMENTS WHICH ARE INCLUDED IN THE APPROVED PLANS AND SPECIFICATIONS FOR THE SUBDIVISION.

EASEMENT FOR STORM WATER DRAINAGE:

A PERMANENT AND PERPETUAL NON-INCLUSIVE EASEMENT IS HEREBY GRANTED TO THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS ("VILLAGE"), ITS SUCCESSORS AND ASSIGNS, AND TO, AND FOR THE USE AND BENEFIT OF, THE OWNERS OF ALL OF THE LOTS IN THIS SUBDIVISION, FOR THE SOLE PURPOSE OF OVERLAND STORM WATER DRAINAGE, IN, UPON, ALONG AND ACROSS THE AREAS DESIGNATED "EASEMENT FOR STORM WATER DRAINAGE" ON THIS SUBDIVISION PLAT. NO CHANGE SHALL BE MADE IN THE FINISHED GRADE OF THE LAND WITHIN ANY "EASEMENT FOR STORM WATER DRAINAGE," AND NO CONSTRUCTION OF ANY KIND WHATSOEVER SHALL BE ERECTED OR PERMITTED TO EXIST WITHIN ANY "EASEMENT FOR STORM WATER DRAINAGE" THAT MIGHT MATERIALLY REDUCE THE STORM WATER DRAINAGE CAPACITY THEREOF. TREES, SHRUBS, FENCES, AND NORMAL LANDSCAPE PLANTING SHALL BE PERMITTED WITHIN ANY "EASEMENT FOR STORM WATER DRAINAGE" ONLY WITH THE PRIOR WRITTEN APPROVAL OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE. EACH OWNER OF A LOT WITH ANY "EASEMENT FOR STORM WATER DRAINAGE" LOCATED ON IT SHALL MAINTAIN A GRASS COVER ON THE SURFACE OF THAT PORTION OF SUCH LOT LOCATED WITHIN THE "EASEMENT FOR STORM WATER DRAINAGE," AND SHALL KEEP SUCH GRASS AND LANDSCAPING IN A FIRST-CLASS AND TRIMMED CONDITION. THE OWNERS OF LOTS ON WHICH ANY "EASEMENT FOR STORM WATER DRAINAGE" IS LOCATED SHALL NOT IN ANY MANNER DAMAGE, DESTROY, INJURE, OBSTRUCT, OR PERMIT TO BE OBSTRUCTED THE "EASEMENT FOR STORM WATER DRAINAGE" AT ANY TIME WHATSOEVER WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE.

BIOSWALE EASEMENT:

THE AREA OF THE PROPERTY DESIGNATED ON THIS PLAT AS "BIOSWALE EASEMENT" SHALL BE CONTINUOUSLY MAINTAINED IN A FIRST RATE MANNER BY FOREST EDGE SUBDIVISION HOMEOWNERS' ASSOCIATION (THE "ASSOCIATION") AND AN EASEMENT ON, UNDER AND ABOVE THE STORM WATER MANAGEMENT AREA IS HEREBY GRANTED TO, AND FOR THE USE AND BENEFIT OF, ALL OF THE LOTS IN THIS SUBDIVISION AND THE HOMEOWNERS' ASSOCIATION FOR THE SOLE PURPOSE OF STORM WATER DRAINAGE. NO CHANGE SHALL BE MADE IN THE FINISHED GRADE OF THE LAND WITHIN THE BIOSWALE EASEMENT, NOR SHALL ANY CONSTRUCTION OF ANY KIND WHATSOEVER BE ERECTED OR PERMITTED TO EXIST WITHIN THE BIOSWALE EASEMENT THAT MIGHT MATERIALLY IMPEDE STORM WATER DRAINAGE THEREIN. TREES, SHRUBS, FENCES AND NORMAL LANDSCAPE PLANTING ASIDE FROM THOSE DEPICTED IN THE FINAL ENGINEERING AND LANDSCAPE PLANS FOR THE FOREST EDGE SUBDIVISION SHALL BE PERMITTED WITHIN THE BIOSWALE EASEMENT ONLY WITH THE PRIOR WRITTEN APPROVAL OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS.

OWNER'S CERTIFICATE
STATE OF ILLINOIS}
COUNTY OF COOK}S.S.

THIS IS TO CERTIFY THAT HOOVER OWNER, LLC, A DELAWARE LIMITED LIABILITY COMPANY, IS THE OWNER OF THE LAND DESCRIBED IN THE ANNEXED PLAT, AND THAT IT HAS CAUSED THE SAME TO BE SURVEYED AND SUBDIVIDED AS INDICATED THEREON, FOR THE USES AND PURPOSES THEREIN SET FORTH, AND DOES HEREBY ACKNOWLEDGE AND ADOPT THE SAME UNDER THE STYLE AND TITLE THEREON INDICATED.

THIS IS TO FURTHER CERTIFY THAT HOOVER OWNER, LLC, HAS DETERMINED, TO THE BEST OF ITS, KNOWLEDGE, THAT EACH OF THE LOTS DEPICTED ON THE ANNEXED PLAT LIES IN THE FOLLOWING SCHOOL DISTRICT:

ELEMENTARY SCHOOL DISTRICT 35 — HIGH SCHOOL DISTRICT 203

DATED THIS ___ DAY OF _____, A.D., 20_____.

HOOVER OWNER, LLC

BY: _____
MANAGING MEMBER

NOTARY PUBLIC CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

I, _____, A NOTARY PUBLIC, DO HEREBY CERTIFY THAT _____, APPEARED BEFORE ME THIS DAY IN PERSON AND ACKNOWLEDGED THE EXECUTION OF THIS STATEMENT AS HIS FREE AND VOLUNTARY ACT.

GIVEN UNDER MY HAND AND NOTARIAL SEAL THIS __ DAY OF _____ A.D., 20__.

_____
NOTARY PUBLIC

DRAINAGE CERTIFICATE
TO THE BEST OF OUR KNOWLEDGE AND BELIEF, THE DRAINAGE OF SURFACE WATERS WILL NOT BE CHANGED BY THE CONSTRUCTION OF THIS SUBDIVISION OR ANY PART THEREOF, OR, IF SUCH SURFACE WATER DRAINAGE WILL BE CHANGED, REASONABLE PROVISION HAS BEEN MADE FOR COLLECTION AND DIVERSION OF SUCH SURFACE WATERS INTO PUBLIC AREAS, OR DRAINS WHICH THE OWNER HAS A RIGHT TO USE, AND THAT SUCH SURFACE WATERS WILL BE PLANNED FOR IN ACCORDANCE WITH GENERALLY ACCEPTED ENGINEERING PRACTICES SO AS TO REDUCE THE LIKELIHOOD OF DAMAGE TO THE ADJOINING PROPERTY BECAUSE OF THE CONSTRUCTION OF THIS SUBDIVISION.

_____ HOOVER OWNER LLC
OWNER

ITS MANAGER: _____

SIGNED: _____

DATED: _____

_____

NAME: KEVIN C. LEWIS

FIRM: IG CONSULTING, INC.

DATED: _____

SURVEYOR CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

THIS IS TO CERTIFY THAT I, KEVIN C. LEWIS, AN ILLINOIS PROFESSIONAL LAND SURVEYOR NUMBER 3681, HAVE SURVEYED AND SUBDIVIDED THE FOLLOWING DESCRIBED PROPERTY.

PARCEL 1:
THAT PART OF THE SOUTH 6 CHAINS AND 23 LINKS OF THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, WHICH LIES EAST OF THE CENTER LINE OF THE GREEN BAY ROAD (EXCEPTING THAT PORTION AS BEING MORE PARTICULARLY DESCRIBED IN DEED RECORDED AUGUST 22, 2016 AS DOCUMENT NUMBER 1623529020), ALSO THAT PART OF THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, BOUNDED AND DESCRIBED AS FOLLOWS: COMMENCING AT THE INTERSECTION OF THE EAST LINE OF SAID NORTHEAST QUARTER WITH THE NORTH LINE OF THE SOUTH 6.23 CHAINS OF SAID NORTHEAST QUARTER; RUNNING THENCE NORTH ON SAID EAST LINE 3 FEET; THENCE WESTERLY, PARALLEL WITH THE NORTH LINE OF SAID SOUTH 6.23 CHAINS, TO THE CENTER LINE OF GREEN BAY ROAD; THENCE SOUTHEASTERLY, ALONG THE CENTER LINE OF GREEN BAY ROAD, TO THE NORTH LINE OF SAID SOUTH 6.23 CHAINS; THENCE EASTERLY , ALONG THE NORTH LINE OF SAID SOUTH 6.23 CHAINS TO THE PLACE OF BEGINNING, ALL IN COOK COUNTY, ILLINOIS.

PARCEL 2:
THAT PART OF THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, DESCRIBED AS FOLLOWS: BEGINNING AT A POINT IN THE EAST LINE OF SAID NORTHEAST QUARTER, 414.18 FEET NORTH OF THE SOUTHEAST CORNER OF SAID NORTHEAST QUARTER; THENCE NORTH, ALONG THE EAST LINE OF SAID NORTHEAST QUARTER, 366.2 FEET TO THE SOUTH LINE OF THE PROPERTY OF THE FOREST PRESERVE OF COOK COUNTY; THENCE WEST, ALONG THE SOUTH LINE OF THE SAID FOREST PRESERVE OF COOK COUNTY, 568 FEET; THENCE SOUTH, ALONG A LINE 568 FEET WEST OF AND PARALLEL WITH THE SAID EAST LINE OF THE NORTHEAST QUARTER, 350.6 FEET; THENCE SOUTHWESTERLY, ALONG A STRAIGHT LINE, 28.28 FEET TO A POINT ON A LINE 414.18 FEET NORTH OF AND PARALLEL WITH THE SOUTH LINE OF SAID NORTHEAST QUARTER AND 588 FEET WEST OF THE EAST LINE OF SAID NORTHEAST QUARTER; THENCE EAST, ALONG SAID LINE 414.18 FEET NORTH OF THE SOUTH LINE OF SAID NORTHEAST QUARTER, 588 FEET TO THE PLACE OF BEGINNING, IN COOK COUNTY, ILLINOIS.

I ALSO CERTIFY THAT THE PROPERTY IS WITHIN THE CORPORATE LIMITS OF THE VILLAGE GLENCOE, WHICH HAS ADOPTED AN OFFICIAL COMPREHENSIVE PLAN.

I FURTHER CERTIFY THAT BY SCALED MAP LOCATION AND GRAPHIC PLOTTING ONLY, THE PARCELS INCLUDED IN THIS SUBDIVISION ARE LOCATED IN THE "UNSHADED ZONE X" PER FEDERAL EMERGENCY MANAGEMENT AGENCY FLOOD INSURANCE RATE MAP 17031C0094J EFFECTIVE DATE OF AUGUST 19, 2008.

GIVEN UNDER MY HAND AND SEAL THIS _____ DAY OF _____, A.D. 20___.

BY _____
ILLINOIS PROFESSIONAL LAND SURVEYOR NO. 3681
LICENSE EXPIRES NOVEMBER 30, 2020

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

PREPARED FOR: GLENCOE DEVELOPERS LLC | SCALE: 1"=50'
FIELD CREW: D.J. | FIELD WORK:2018 | DRAFTED BY: S.R.M. | CHECKED BY:
FIRM NO. 184-001330

FINAL PLAT OF SUBDIVISION
FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT NUMBER
18557

COPYRIGHT AS DATED © IG CONSULTING, INC.
G:\IG\18\18557\Eng\18557-9P.dwg

FOREST EDGE SUBDIVISION

1801 GREEN BAY ROAD

GLENCOE, ILLINOIS

2019


LEGEND

	EXISTING	PROPOSED
STORM SEWER	——<——<——	——<——<——
SANITARY SEWER	——<——<——<——	——<——<——
WATER MAIN	——W——W——	——W——W——
GAS MAIN	——G——G——G——G——	
TELECOMMUNICATION & ELECTRIC LINE (BURIED)	——TE——TE——TE——TE——	
OVERHEAD ELECTRIC,	——OHW——OHW——OHW——OHW——	
SANITARY MANHOLE	◎	◉
STORM MANHOLE	◎	◉
STORM CATCH BASIN		●
UTILITY MANHOLE	△	
TELEPHONE/UTILITY PEDESTAL	T	
STORM INLET	□	■
UTILITY POLE	—○—	
FIRE HYDRANT		
VALVE VAULT		◑
STREET LIGHT		
TRANSFORMER	TR	▣
ELECTRIC PEDESTAL		⌘
EDGE OF PAVEMENT	———————	———————
CURB & GUTTER	———————	———————
DRAINAGE FLOW		~~~→
EMERGENCY OVERLAND FLOW ROUTE		➡
SPOT GRADE	× 691.18	+ 641.6
TOP OF CURB ELEVATION		+ T/C=642.5
TOP OF PAVEMENT ELEVATION		+ 642.0
TOP OF FOUNDATION ELEVATION		F/F=642.1
ROOT PRUNING		- - - - - -
STAKED SILT FENCE		▬ ▬ ▬
TREE PROTECTION FENCE		——x——x——
CONSTRUCTION FENCE		——○——○——

THE CONTRACTOR MUST CALL J.U.L.I.E FOR THE LOCATION AND STAKING OF EXISTING UNDERGROUND UTILITIES (GAS, ELECTRIC, TELEPHONE, ETC.) AT 1-800-892-0123 48 HOURS PRIOR TO DIGGING.

VILLAGE CONSTRUCTION HOURS OF 7AM-6PM M-F, 9AM-6PM SATURDAY AND NO WORK ON SUNDAYS OR HOLIDAYS.

LOCATION MAP



SECTION 1, TOWNSHIP 42 N, RANGE 12 E

NOTE:
EXISTING WATER, SANITARY SEWER AND STORM SEWER INFORMATION IS BASED ON RECORDS PROVIDED BY THE MUNICIPALITY AND SURVEY DATA DETERMINED BY IG CONSULTING, INC. CONTRACTOR MUST VERIFY LOCATIONS, DEPTHS, MATERIALS AND POTENTIAL CONFLICTS PRIOR TO BIDDING AND CONSTRUCTING THE PROPOSED IMPROVEMENTS. SUCH VERIFICATION SHALL ALSO INCLUDE FACILITIES OWNED AND OPERATED BY VARIOUS UTILITY COMPANIES. ENGINEER MAKES NO REPRESENTATION AS TO THE ACCURACY OR EXISTENCE OF PLAN INFORMATION PROVIDED BY OTHERS.

ENGINEER: KEVIN C. LEWIS _____ DATE _____

ILLINOIS REGISTRATION NO. 062-055368 EXPIRATION DATE: 11-30-2021

THESE PLANS OR ANY PART THEREOF SHALL BE CONSIDERED VOID WITHOUT THE SIGNATURE, SEAL, AND EXPIRATION DATE OF THE SEAL OF THE ENGINEER.

INDEX

1 – COVER SHEET
2 – EXISTING CONDITION & SITE CLEARING PLAN
3 – GEOMETRIC PLAN
4 – LOT GRADING PLAN
5 – MASS GRADING LIMIT
6 – SOIL EROSION CONTROL PLAN
7 – CROSS SECTIONS
8 – CROSS SECTIONS
9 – SITE DEVELOPMENT MANAGEMENT PLAN
10 – UTILITY PLAN
11 – OFF-SITE UTILITY CONNECTION & DETAILS
12 – PLAN & PROFILE, STA. 0+00 TO 5+00
13 – PLAN & PROFILE, STA. 5+00 TO 10+00
14 – PLAN & PROFILE, STA. 10+00 TO 15+00
15 – PLAN & PROFILE, STA. 15+00 TO 15+73
16 – PLAN & PROFILE, OFF-SITE UTILITY CONNECTIONS
17 – PROJECT NOTES AND SPECIFICATIONS
18 – GLENCOE WATER MAIN SPECIFICATIONS
19 – CONSTRUCTION STANDARDS
20 – CONSTRUCTION STANDARDS
21 – CONSTRUCTION STANDARDS
22 – CONSTRUCTION STANDARDS
23 – CONSTRUCTION STANDARDS

ALL ROADWAY CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND ALL AMENDMENTS THERETO AS ADOPTED BY THE STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION (I.D.O.T.).

STORM SEWER, SANITARY SEWER AND WATER MAIN CONSTRUCTION SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS, LATEST ISSUE, AND THE VILLAGE OF GLENCOE SUBDIVISION AND ENGINEERING GUIDE, INCLUDING THE LATEST CONSTRUCTION DETAILS, WHICHEVER IS MORE STRINGENT.

VILLAGE BENCHMARK #296:
NORTHWEST BOLT OF FIRE HYDRANT AT SOUTHWEST CORNER OF WESTLEY ROAD AND FAIRFIELD ROAD, 200'± WEST OF GREENBAY ROAD.
ELEVATION= 646.11

SITE BENCHMARK:
NORTHEAST BONNET BOLT OF FIRE HYDRANT AT THE NORTHEASTERLY CORNER OF #1799 GREENBAY ROAD
ELEVATION = 690.27 NAVD 88 (GEOID12B)

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

COVER SHEET | DESIGN: K.C.L. | DRAFTING: S.R.M | SCALE: NONE | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557

1 of 23

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\01\18\18557\Eng\18557-ts.dwg

NOTE:
1. CONTRACTOR SHALL INVESTIGATE FOR EXISTING STORM SEWER CONNECTIONS AND DISCONNECT ANY FOUND AT THE MAIN.
2. GREEN BAY ROAD DEMOLITION AND IMPROVEMENT SHALL BE DONE SIMULTANEOUSLY.
3. CONTRACTOR SHALL DISCONNECT EXISTING SANITARY SEWER AND WATER SERVICES FOR ALL BUILDINGS AT THE MAINS.

ZONE R-A
FOREST PRESERVE
TURNBULL WOODS

N89°52'17"W 568.00'(D&M)

TEMPORARY CHAIN LINK CONSTRUCTION FENCE
SILT PROTECTION FENCE
TO BE REMOVED

ZONE R-A
FOREST PRESERVE
COUNTY CLERK'S DIVISION

TOTAL WETLANDS: 31,051 S.F. (0.71 ACRES)

LOT B #431 | LOT C #423 | LOT D #415 | #403 | LOT F | #409 | LOT E

ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT

#424 | #414 | #406

NORTHWOOD DRIVE

NORTH GATE MANOR 1st ADDITION
DOC. 16986011

NORTH GATE SUBDIVISION
DOC. 18523477

LOT 1 | LOT H | LOT G | LOT I

S00°01'20"E 350.60'(D&M)

EXISTING WETLAND TO BE MITIGATED AREA=15,488 S.F.

TEMPORARY CHAIN LINK CONSTRUCTION FENCE

S89°41'06"W 382.30'(R&M)

S44°49'53"W 28.36'(R&M)

EXISTING ASPHALT DRIVEWAY TO BE REMOVED

EXISTING UTILITY SERVICES TO BE DISCONNECTED AT MAIN, PLUGGED AND ABANDONED

EXISTING ELECTRIC SERVICES TO BE DISCONNECTED

EXISTING UTILITY SERVICES TO BE DISCONNECTED AT MAIN, PLUGGED AND ABANDONED

EXISTING TO BE REMOVED

EXISTING TO BE REMOVED

TRANSFORMER TO BE REMOVED

EXISTING UTILITY SERVICES TO BE DISCONNECTED AT ENDS, PLUGGED AND ABANDONED

780.36'(R&M) N00°01'20"W

411.18'(D) CHAIN 6.23'

LOT 8 | LOT 9 | LOT 10 | LOT 11 | LOT 12 | LOT 13 | LOT 14 | LOT 15 | LOT 16

#1214 | #1212 | #1206 | #1200 | #1194 | #1188 | #1182 | #1176 | #1201

DUNAS FOREST CREST SUBDIVISION
DOC. 6457807

CAROL LANE

EXISTING 9" PARKWAY TREE TO BE REMOVED. REPLACED WITH 4" REDPOINT MAPLE. (REFER TO LANDSCAPE PLAN FOR PLANTING SPECIFICATIONS AND DETAILS)

EXISTING sanitary manhole rim 677.79 inv 667.07 8" sw (n,s) TO BE REMOVED AS PART OF SANITARY SEWER EXTENSION WORK

EXISTING WETLAND TO BE MITIGATED AREA=11,297 S.F.

EXISTING WETLAND TO BE MITIGATED AREA=7,108 S.F.

WETLAND FLAGGING LOCATED 10/29/2019

WETLAND FLAGGING LOCATED 10/29/2019

ADDITIONAL WETLAND FLAGGING LOCATED 04/01/2020

INCLUDED PARCEL 1

PARCEL 1

R=540.69'
A=27.00'(M)

N29°32'10"W 180.14'(M)

TEMPORARY CHAIN LINK CONSTRUCTION FENCE (TYP.)

191.15'(R&M) N54°46'45"E

159.42'(R&M) S21°40'18"E

SITE BENCHMARK:
N.E. BONNET BOLT ON FIRE HYDRANT.
ELEVATION=690.27 NAVD88 (2001ADJ)

R=175.90'
A=49.30'(M)

R=25.00'
A=35.67'(M)

N51°59'13"E 69.01'(R&M)

R=540.69'
A=36.47'(M)

ZONE R-A
GLENCOE GOLF CLUB

EXISTING FENCE TO BE REMOVED

SAWCUT & REMOVE 560 SF OF CONCRETE SIDEWALK

REMOVE 113 LF OF CONCRETE CURB & GUTTER

GREEN BAY ROAD

WESTLEY ROAD

SUNKEN GARDEN TO BE REMOVED

EXISTING UTILITY SERVICES TO BE DISCONNECTED AT MAIN, PLUGGED AND ABANDONED

SILT PROTECTION FENCE

N89°41'06"E 627.81'(M)

TEMPORARY CHAIN LINK CONSTRUCTION FENCE

N50°31'11"W 164.80'(R&M)

CONTRACTOR SHALL PROTECT COMMUNICATION ANTENNA DURING CONSTRUCTION

UNSUBDIVIDED

LOT 4 | LOT 3 | LOT 2 | LOT 1

ODH'S SUBDIVISION
DOC. 12390488

ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT

#470 | #440 | #1163

SCALE
(IN FEET)
1 inch = 40 ft.

EXISTING CONDITIONS & SITE CLEARING PLAN

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
03/30/20	PER VILLAGE COMMENTS	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gcconsulting.net

EXISTING CONDITIONS & SITE CLEARING PLAN
DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=40' | DATE: 10/28/19
FIRM NO. 184-001330


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557

2 of 23


COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IGV\18\18557\Eng\18557-BP.dwg



TYPICAL STREET CROSS-SECTION

N.T.S.



ZONE R-A

FOREST PRESERVE

TURNBULL WOODS

OUTLOT C
1,622 S.F.
0.04 AC.

N89°52'17"W 568.00'(D&M)

CONCRETE CURTAIN WALL (SEE DETAIL)

OPEN SPACE EASEMENT AREA

35' WEIR WIDTH OVERFLOW = 678.50

OUTLOT D
3,774 S.F.
0.09 AC.

DETENTION BASIN 1
H.W.L.=678.49
(100 YR)

STORMWATER MANAGEMENT AREA

LOT 26
13,091 S.F.
0.30 AC.

LOT 25
13,031 S.F.
0.30 AC.

LOT 27
15,670 S.F.
0.36 AC.

LOT 24
13,364 S.F.
0.31 AC.

LOT 28
16,588 S.F.
0.38 AC.

LOT 23
13,458 S.F.
0.31 AC.

FOREST EDGE DRIVE

PARK
OUTLOT A
20,606 S.F.
0.47 AC.

LOT 29
13,015 S.F.
0.30 AC.

LOT 22
13,078 S.F.
0.30 AC.

LOT 3
16,413 S.F.
0.38 AC.

LOT 21
13,050 S.F.
0.30 AC.

LOT 4
13,259 S.F.
0.30 AC.

LOT 5
13,022 S.F.
0.30 AC.

LOT 6
13,926 S.F.
0.32 AC.

LOT 20
13,008 S.F.
0.30 AC.

LOT 1
27,965 S.F.
0.64 AC.

LOT 10
16,928 S.F.
0.39 AC.

LOT 9
13,888 S.F.
0.32 AC.

LOT 8
15,134 S.F.
0.35 AC.

LOT 7
13,404 S.F.
0.31 AC.

LOT 19
13,193 S.F.
0.30 AC.

LOT 2
18,751 S.F.
0.43 AC.

LOT 18
14,512 S.F.
0.33 AC.

LOT 17
17,764 S.F.
0.41 AC.

LOT 16
14,960 S.F.
0.34 AC.

LOT 11
13,489 S.F.
0.31 AC.

LOT 12
13,574 S.F.
0.31 AC.

LOT 13
13,304 S.F.
0.31 AC.

LOT 14
13,134 S.F.
0.30 AC.

LOT 15
13,040 S.F.
0.30 AC.

OUTLOT B
4,636 S.F.
0.11 AC.

OUTLOT E
4,124 S.F.
0.09 AC.

	AREA (S.F.)	IMPERVIOUS AREA S.F.
PUBLIC R.O.W	65,606	45,035
OUTLOT A	26,606	263
OUTLOT B	4,636	229
OUTLOT C	1,622	0
OUTLOT D	3,774	66
OUTLOT E	4,124	0

LOT NO.	AREA (S.F.)	C-VALUE	MAX. IMPERVIOUS (S.F.)
1	27,965	0.62	7,457
2	18,751	0.65	6,250
3	16,413	0.65	5,471
4	13,259	0.65	4,420
5	13,022	0.65	4,341
6	13,926	0.65	4,642
7	13,404	0.65	4,468
8	15,134	0.65	5,045
9	13,888	0.65	4,629
10	16,928	0.65	5,643
11	13,489	0.65	4,496
12	13,574	0.65	4,525
13	13,304	0.65	4,435
14	13,134	0.65	4,378
15	13,040	0.65	4,347
16	14,960	0.65	4,987
17	17,764	0.65	5,921
18	14,512	0.65	4,837
19	13,193	0.65	4,398
20	13,008	0.65	4,336
21	13,050	0.65	4,350
22	13,078	0.65	4,359
23	13,458	0.65	4,486
24	13,364	0.65	4,455
25	13,031	0.65	4,344
26	13,091	0.65	4,364
27	15,670	0.65	5,223
28	16,588	0.65	5,529
29	13,015	0.65	4,338

S89°41'06"W 382.30'(R&M)

S00°01'20"E 350.60'(D&M)

S44°49'53"W 28.36'(M)

N00°01'20"W 780.38'(R&M) 780.41'(M)

N29°32'10"W 180.14'(M)

N54°46'45"E 191.15'(R&M)

S21°40'18"E 159.42'(R&M)

N50°31'11"W 164.80'(R&M)

627.81'(M) N89°41'06"E

R=540.69' A=27.00'(M)

R=540.69' A=36.47'(M)

R=175.90' A=49.30'(M)

R=25.00' A=35.67'(M) N51°59'13"E 69.07'(R&M)

R=180.00' A=55.60'

R=795.00' A=89.87'

R=25.00' A=40.04'

R=35.00' A=52.91'

R=50.00' A=40.25'

R=78.50' A=35.35'

R=403.93' A=123.93'

R=60.00' A=143.90'

R=38.50' A=37.55'

R=755.00' A=109.61'

R=150.00' A=20.20'

R=35.00'

R=25.00'

R=50.00'

R=150.00'

R=755.00'

R=795.00'

R=180.00'

R=60.00'


R=38.50'

R=403.93'

R=78.50'

R=25.00'

R=35



NOTES:
1. THIS CONCEPTUAL GRADING PLAN IS PROVIDED FOR FUTURE INDIVIDUAL LOT SITE DEVELOPMENT PLANS.
2. THE TOP OF FOUNDATION ELEVATIONS AND THE SITE GRADING MAY BE ADJUSTED TO BEST SAVE THE TREES, HOWEVER SITE DRAINAGE PATTERNS SHALL BE MAINTAINED.
3. THE TREE PROTECTION FENCING MAY BE ADJUSTED AS PART OF EACH LOT GRADING PLAN DESIGN.

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net
FIRM NO. 184-001330

LOT GRADING PLAN | DESIGN: K.C.L. | DRAFTING: S.R.M. | SCALE: 1"=40' | DATE: 10/28/19

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IGV\18\18557\Eng\18557-4P.dwg

PROJECT No. 18557



NOTES:
1. THE MASS GRADING PLAN IS PROVIDED FOR THE CONSTRUCTION OF THE SUBDIVISION ROAD AND INFRASTRUCTURE IMPROVEMENTS.
2. TREE PROTECTION METHODS AND/OR DIRECTIONAL BORING SHALL BE USED TO PROTECT TREES DURING CONSTRUCTION.
3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE LOSS OF ANY TREES IF TREE PROTECTION PROCEDURES ARE NOT USED.
4. CONTRACTOR SHALL CONTACT THE OWNER, ENGINEER OR ARBORIST IF TREE SURVIVABILITY IS IN QUESTION.

REVISIONS

DATE	DESCRIPTION	DRAWN BY
02/20/20	FOR SUBMITTAL	S.R.M.
03/30/20	PER VILLAGE COMMENTS	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

MASS GRADING LIMIT | DESIGN: K.C.L. | DRAFTING: S.R.M. | SCALE: 1"=40' | DATE: 02/20/20

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IGV\18\18557\Eng\18557-MP.dwg

PROJECT No. 18557

SEQUENCE OF CONSTRUCTION

A. THE SITE WILL BE ACCESSED FROM THE LOCATIONS INDICATED ON THIS PLAN, FOR ALL CONSTRUCTION ACTIVITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DAILY INSPECTION TO REMOVE ALL DIRT AND DEBRIS FROM GREEN BAY ROAD, DURING THE COURSE OF CONSTRUCTION.
B. INSTALL SEDIMENT BARRIERS/SILT FENCE DOWN SLOPE FROM CONSTRUCTION ACTIVITIES THAT DISTURB SITE SOIL AS SHOWN ON PLAN.
C. TEMPORARY PARKING OF CONSTRUCTION VEHICLES SHALL BE ON SITE, ONLY AS NECESSARY. STORAGE OF CONSTRUCTION MATERIALS WILL BE ONSITE AND SHALL NOT OBSTRUCT VEHICLE MOVEMENT.
D. STORMWATER DETENTION SHALL BE CONSTRUCTED AS PART OF THE FIRST PHASE OF WORK. GRADE THE PROPOSED IMPROVEMENT AREAS. INSTALL CHAMBER SYSTEM. EXCESS SOIL OVERBURDEN SHALL BE REMOVED AS NECESSARY. ONSITE AND OFFSITE DRAINAGE SHALL NOT BE BLOCKED. DRAINAGE SHALL BE ROUTED TO THE EXISTING CATCH BASINS WITH TEMPORARY FILTER BASKETS INSTALLED DURING CONSTRUCTION. TEMPORARY FILTER BASKETS WILL BE INSTALLED IN ALL EXISTING AND PROPOSED CATCH BASINS SURROUNDING THE CONSTRUCTION AREA. STOCKPILES, IF ANY, SHALL BE PROTECTED WITH PERIMETER SILT FENCING AND MUST BE STABILIZED WITH SEEDING, IF PILES ARE TO REMAIN FOR MORE THAN 14 DAYS. DETENTION BASIN SHALL BE STABILIZED IMMEDIATELY FOLLOWING EXCAVATION. CHAMBER SYSTEM SHALL BE INSPECTED WEEKLY BY THE CONTRACTOR. SILT AND DEBRIS SHALL BE REMOVED, AS NEEDED.
E. INSTALL UNDERGROUND UTILITIES AND FRANCHISE UTILITIES. CONSTRUCT BUILDINGS AND PAVEMENT.
F. VOLUME CONTROL FACILITIES MUST BE INSPECTED EVERY DAY DURING THE COURSE OF CONSTRUCTION. SILT AND DEBRIS SHALL BE REMOVED.
G. TEMPORARY FILTER BASKETS SHALL BE INSTALLED IN ALL CATCH BASINS ALONG WITH LOG TYPE FILTER PROTECTION LOCATED IN PAVED SURFACE AREAS. ALL CATCH BASINS LOCATED IN GRASS (PERVIOUS) AREAS SHALL HAVE TEMPORARY FILTER BASKETS AND MONOFILAMENT FABRIC BARRIER FENCE (INLET PROTECTION) SURROUNDING EACH INLET.
H. A SUMP CONDITION SHALL BE MAINTAINED WHERE THE GROUND SHALL BE KEPT LOWER THAN DRAIN GRATES. SEE DETAILS.
I. CONTRACTOR TO INSTALL AND MAINTAIN TEMPORARY FILTER FABRIC AND STONE IN BRICK PAVER LOCATIONS AT ALL TIMES UNTIL SITE IS FULLY STABILIZED.
J. EXISTING SIDEWALK ALONG GREEN BAY ROAD SHALL BE REPLACED IF CONDITION IS DEFICIENT.

TEMPORARY FILTER BASKETS WITH MONOFILAMENT FABRIC BARRIER FENCE SHALL BE INSTALLED IN VOLUME CONTROL AREAS, PRIOR TO PAVER INSTALLATION. ONCE PAVERS ARE INSTALLED, FILTER BASKETS SHALL REMAIN AND LOG TYPE FILTERS SHALL BE INSTALLED AROUND EACH DRAIN GRATE.

THE PROPOSED DETENTION BASIN SHALL BE STABILIZED WITH EROSION BLANKET AND SEEDED, IMMEDIATELY FOLLOWING EARTHWORK AND TOPSOIL PLACEMENT. EROSION CONTROL BLANKET N.A. GREEN S75BN PR EQUIVALENT.

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gcconsulting.net

SOIL EROSION CONTROL PLAN | DESIGN: K.C.L. | DRAFTING: S.R.M. | SCALE: 1"=40' | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS


COPYRIGHT AS DATED © IG CONSULTING, INC.


G:\IG\18\18557\Eng\18557-SP.dwg


PROJECT No. 18557


SOIL EROSION CONTROL PLAN


SCALE
40 0 20 40 80 160
(IN FEET)
1 inch = 40 ft.

















SCALE: H: 1"=10', V: 1"=10'





PLAN VIEW








SPILLWAY DETAIL











CROSS SECTIONS

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net
FIRM NO. 184-001330


CROSS SECTIONS


DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=10' | DATE: 10/28/19


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS


COPYRIGHT AS DATED © IG CONSULTING, INC.
G:\IG\18\18557\Eng\18557-SP.dwg

PROJECT No. 18557









CROSS SECTIONS

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/10	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

CROSS SECTIONS

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=10' | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\18557-9P.dwg

PROJECT No. 18557

DEVELOPMENT SITE MANAGEMENT NOTES:

OFF-SITE SPECIFICATIONS:
1. NO OFF-SITE PARKING FOR CONTRACTOR AND WORKER VEHICLES SHALL BE ALLOWED.
2. LOADING SHALL TAKE PLACE FROM CONSTRUCTION ENTRANCE AS NOTED ON DRAWING. SPACE SHALL BE MAINTAINED ON-SITE FOR STORAGE AND DELIVERY OF ALL MATERIALS. NO SUCH MATERIALS SHOULD BE STORED ON THE PUBLIC PARKWAY AND/OR RIGHT-OF-WAY AT ANY TIME.
3. DELIVERY ROUTE SHOULD GO THROUGH GREEN BAY ROAD ONLY. ALL ROUTES MUST UTILIZE MAJOR VILLAGE STREETS.

ON-SITE SPECIFICATIONS:
4. CONSTRUCTION ENTRANCE WILL BE MADE OF 8" CRUSHED STONE BASE.
5. ALL EXCAVATION MATERIALS, EXCEPT THAT NEEDED FOR BACKFILL, SHOULD BE LOADED AND REMOVED FROM THE SITE AT THE TIME OF EXCAVATION. EROSION CONTROL MUST BE PROVIDED AROUND SPOILS. ALL SPOILS SHALL BE HAULED OFF-SITE.

GENERAL NOTES:
6. LITTER CONTROL: THE SITE MUST BE KEPT FREE OF ALL LITTER AND DEBRIS AT ALL TIMES ON A DAILY BASIS.
7. GRASS MAINTENANCE: GRASS AND WEEDS ON PRIVATE PROPERTY AND ON THE PARKWAY MUST BE MAINTAINED THROUGHOUT THE ENTIRE CONSTRUCTION PROCESS, INCLUDING THOSE AREAS FENCED FOR TREE PROTECTION.
8. STREET & SIDEWALK CLEANING: ALL HEAVY MUD, GRAVEL AND OTHER DEBRIS LEFT ON SIDEWALK OR STREET MUST BE CLEANED AND REMOVED IMMEDIATELY. STREET AND SIDEWALK MUST BE SWEPT AT END OF WORKING DAY.
9. DUST CONTROL: DUST PARTICLES MUST BE CONTROLLED AT ALL TIMES. NO DRY CUTTING OF BRICK, STONE, OR PAVERS IS PERMITTED.
10. RIGHT-OF-WAY SAFETY AND RESTORATION:
A. TRAFFIC CONTROL IS REQUIRED FOR ANY EXCAVATION OR PERMIT WORK IN THE PUBLIC RIGHT-OF-WAY. AT A MINIMUM, TYPE II BARRICADES ARE REQUIRED. ADVANCED WARNING SIGNS MAY BE REQUIRED BASED ON THE VILLAGE ENGINEER'S REVIEW. NO STREET ACCESS CAN BE CLOSED WITHOUT WRITTEN VILLAGE APPROVAL.
B. NO METAL PLATES MAY BE USED BETWEEN NOVEMBER 15 AND MARCH 15 FOR ANY PAVEMENT OPENING. PLATES MAY BE USED WITH ADEQUATE TRAFFIC CONTROL TO PROTECT OPENING FOR NO MORE THAN 72 HOURS AFTER UTILITY CUT HAS BEEN MADE.
C. TEMPORARY PAVEMENT RESTORATION TO BE:
2-INCH HMA SURFACE
4-INCH HMA BINDER (LIFT 2)
4-INCH HMA BINDER (LIFT 1)
4-INCH AGGREGATE BASE COARSE
D. ANY PUBLIC SIDEWALK OR CURB THAT IS REMOVED AS A RESULT OF A UTILITY CONNECTION WILL BE TEMPORARILY PATCHED (WITH CONCRETE) WITHIN 48 HOURS OF EXCAVATION. NO PUBLIC SIDEWALK WILL BE UNAVAILABLE FOR PUBLIC USE AT ANY TIME EXCEPT WHEN SUCH SIDEWALK IS REMOVED OR REPLACED.
E. ANY TRENCHES IN PUBLIC PARKWAY SHOULD BE BACKFILLED AND JETTED TO ACCELERATE COMPACTION AND SETTLEMENT. THE PARKWAY SHOULD BE FILLED AND LEVELED TO MATCH EXISTING GRADE WITHIN 48 HOURS OF EXCAVATION.

ZONE R-A
FOREST PRESERVE
TURNBULL WOODS
OUTLOT C
ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT
NORTHWOOD DRIVE
#424
#414
#409
#403
#406
LOT E
LOT F
LOT 1
LOT 26
LOT 25
LOT 27
LOT 28
LOT 24
LOT 23
LOT 22
LOT 29
LOT 3
LOT 4
LOT 5
LOT 6
LOT 21
LOT 20
DELIVERY STAGING AREA
LOT 19
LOT 18
LOT 17
LOT 16
LOT 15
LOT 14
LOT 13
LOT 12
LOT 11
LOT 10
LOT 9
LOT 8
LOT 7
LOT 2
PARK
OUTLOT A
FOREST EDGE DRIVE
FOREST EDGE DRIVE
OUTLOT B
OUTLOT D
OUTLOT E
NORTH GATE MANOR 1st ADDITION
DOC. 16986011
NORTH GATE SUBDIVISION
DOC. 18523477
LOT H
LOT G
LOT I
PIN 04-01-200-010
SITE BENCHMARK:
N.E. BONNET BOLT ON FIRE HYDRANT.
ELEVATION=690.27. NAVD88 (GEOID12B)
TEMPORARY CHAIN LINK CONSTRUCTION FENCE
SILT PROTECTION FENCE
CONCRETE CURTAIN WALL
RIP-RAP
35' WEIR WIDTH
OVERFLOW = 678.50
DETENTION BASIN 1
H.W.L.=678.49
(100 YR)
678.49 H.W.L.
THE PROPOSED DETENTION BASIN SHALL BE STABILIZED WITH EROSION BLANKET AND SEEDED, IMMEDIATELY FOLLOWING EARTHWORK AND TOPSOIL PLACEMENT. EROSION CONTROL BLANKET N.A. GREEN 'S75BN PR EQUIVALENT.
ZONE R-A
FOREST PRESERVE
COUNTY CLERK'S DIVISION
TEMPORARY FILTER BASKETS WITH MONOFILAMENT FABRIC BARRIER FENCE SHALL BE INSTALLED IN VOLUME CONTROL AREAS, PRIOR TO PAVER INSTALLATION. ONCE PAVERS ARE INSTALLED, FILTER BASKETS SHALL REMAIN AND LOG TYPE FILTERS SHALL BE INSTALLED AROUND EACH DRAIN GRATE.
CONTRACTOR PARKING LOCATION
PORT-A-POTTY LOCATIONS
DUMPSTER LOCATION
TEMPORARY STOCKPILE LOCATION
CONCRETE WASH OUT AREA
INLET PROTECTION BASKET (TYP.)
TEMPORARY CONSTRUCTION ENTRANCE
GREEN BAY ROAD
WESTLEY ROAD
CAROL LANE
DUNAS FOREST CREST SUBDIVISION DOC. 6452907
ZONE R-A
GLENCOE GOLF CLUB
UNSUBDIVIDED
ODH'S SUBDIVISION
DOC. 12390488
ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT
ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT
#1799
#1214
#1212
#1206
#1201
#1200
#1194
#1188
#1182
#1178
#1163

LEGEND
TREE PROTECTION FENCE
SILT FENCE
CONSTRUCTION FENCE

SCALE
(IN FEET)
1 inch = 40 ft.

SITE DEVELOPMENT MANAGEMENT PLAN

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	FOR SUBMITTAL	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

DESIGN: K.C.L. | DRAFTING: S.R.M. | DATE: 10/28/19
SCALE: 1"=40'
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\01\180\18557\Eng\18557-SP.dwg

PROJECT No. 18557

(A) 15" STM OVER 8" SAN
B/STM=679.43
T/SAN=675.74

(B) 8" WM OVER 24" STM & 8" SANITARY
B/WM=676.50
T/STM=674.16
T/SAN=671.93

(C) 8" WM OVER 24" STM
B/WM=674.00
T/STM=671.95

(D) 8" SAN OVER 24" STM
B/SAN=672.85
T/STM=672.84

(E) 12" STM OVER 8" WM
B/STM=675.58
T/WM=674.08

(F) 18" STM OVER 8" WM
B/STM=674.20
T/WM=672.67

(G) 8" SAN OVER 8" WM
B/SAN=673.31
T/WM=671.81

(H) 15" STM OVER 8" SAN
B/STM=675.88
T/SAN=675.38

(I) 12" STM OVER 8" SAN
B/STM=677.25
T/SAN=676.39

(J) 15" STM OVER 8" WM
B/STM=674.57
T/WM=673.07

(K) 12" STM OVER 8" SAN
B/STM=678.04
T/SAN=677.54

(L) 8" SAN & 12" STM OVER EX. 6" WM
EX. B/WM=671.7±
T/STM=670.2
T/SAN=668.3

(M) 10" STM OVER 8" SAN & 8" WM
B/STM=681.9
T/SAN=675.41
T/WM=681.50

(N) 12" STM OVER 8" SAN
B/STM=676.71
T/SAN=675.90

(O) 10" STM OVER 8" WM
B/STM=677.10
T/WM=675.50

(P) 10" STM OVER 8" WM
B/STM=678.30
T/WM=676.00

(Q) 10" STM OVER 8" SAN
B/STM=678.21
T/SAN=676.38

(R) 10" STM OVER 8" WM
B/STM=682.05
T/WM=681.30

(S) 12" STM OVER 8" SAN
B/STM=677.27
T/SAN=677.15

PROVIDED CHAMBER SYSTEM STORAGE VOLUMES					REQUIRED STORAGE
CHAMBER SYSTEM NO.	STONE QUANTITY CUBIC FEET	STORAGE IN STONE (36%) CUBIC FEET	CHAMBER STORAGE CUBIC FEET	TOTAL VOLUME CUBIC FEET	
1 (902HD)	49,023	17,648	31,708	49,356	
1 (280 HD)	39,054	14,060	16,291	30,351	
2	17,557	6,320	4,520	10,840	
3	23,634	8,508	12,835	21,343	
4	7,907	2,847	2,101	4,948	
5	13,458	4,845	3,619	8,464	
6	9,005	3,242	2,525	5,767	
7	14,388	5,180	4,573	9,752	
SUB-TOTAL				140,821	135,796
DETENTION BASIN 1				5,071	4,446
TOTAL				145,892	140,242

ZONE R-A
FOREST PRESERVE
TURNBULL WOODS

OUTLOT C

LOT 26 T/F=682.5

LOT 27 T/F=682.5

LOT 28 T/F=683.0

LOT 29 T/F=683.5

LOT 3 T/F=684.5

LOT 4 T/F=684.5

LOT 5 T/F=683.5

LOT 6 T/F=682.5

LOT 25 T/F=682.5

LOT 24 T/F=682.0

LOT 23 T/F=682.0

LOT 22 T/F=682.5

LOT 21 T/F=682.8

LOT 20 T/F=682.5

LOT 19 T/F=682.5

LOT 18 T/F=682.5

LOT 17 T/F=683.5

LOT 16 T/F=683.5

LOT 15 T/F=683.5

LOT 14 T/F=684.0

LOT 13 T/F=688.0 L/O=684.0

LOT 12 T/F=688.0

LOT 11 T/F=688.5

LOT 10 T/F=687.5

LOT 9 T/F=686.5

LOT 8 T/F=684.5

LOT 7 T/F=683.5

LOT 2 T/F=688.0

LOT 1 T/F=688.0

PARK

OUTLOT A

FOREST EDGE DRIVE

NORTHWOOD DRIVE

WESTLEY ROAD

GREEN BAY ROAD

CAROL LANE

DETENTION BASIN 1
H.W.L.=678.49
(100 YR)

35' WEIR WIDTH
OVERFLOW = 678.50

OUTLOT D

OUTLOT E

8' WIDE BIOSWALE

SYSTEM 1
CULTEC 902HD/280HD NESTED SYSTEM
1,831 LF 902HD CHAMBERS, 2,683 LF 280HD CHAMBERS
AREA SYSTEM: 15,163 S.F.

SYSTEM 2
261 LF 902HD CHAMBERS
AREA SYSTEM: 2,338 S.F.

SYSTEM 3
74 LF 902HD CHAMBERS
SYSTEM AREA: 6,238 S.F.

SYSTEM 4
121 LF 902HD CHAMBERS,
AREA SYSTEM: 1,062 S.F.

SYSTEM 5
209 LF 902 HD CHAMBER
SYSTEM AREA: 1,940 S.F.

SYSTEM 6
146 LF 902HD CHAMBER
SYSTEM AREA: 1,309 S.F.

SYSTEM 7
264 LF 902HD CHAMBER
SYSTEM AREA: 2,362 S.F

ZONE R-A
FOREST PRESERVE
COUNTY CLERK'S DIVISION
DOC. 1552807

ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT

ODH'S SUBDIVISION
DOC. 12390488

NORTH GATE SUBDIVISION
DOC. 18523477

DUNHAM FOREST CREST SUBDIVISION
DOC. 1552807

ZONE R-A
NCOE GOLF CLUB

UNSUBDIVIDED

PIN 04-01-200-010

SITE BENCHMARK:
N.E. BONNET BOLT ON FIRE HYDRANT.
ELEVATION=690.27 NAVD88 (2001)

NOTE:
1. OFF-SITE SEWERS MAY BE OPEN CUT, AUGER OR DIRECTIONALLY BORE. IF DIRECTIONALLY BORE CONTRACTOR SHALL USE A CERTA-LOK YELOMINE PVC PRESSURE PIPE OR EQUIVALENT MEETING ASTM D2241 AND ASTM D3139.
2. ALL SANITARY MANHOLE SHALL BE 4' IN DIAMETER.
3. STORM SEWER PIPE UNDER PAVEMENT IS ALLOWED TO BE PVC SDR 26 OR STRONGER. HDPE PIPE IS NOT ALLOWED UNDER THE PAVEMENT OR FOR AREAS TO BE MAINTAINED BY THE VILLAGE.
4. AN ANTI-SEEP COLLAR IS SPECIFIED FOR ALL UTILITY TRENCHES EXTENDING FROM OR THROUGH UNDERGROUND DETENTION AREAS INTO HOMES.
5. AN AS-BUILT CERTIFICATION OF THE STORMWATER DETENTION SYSTEM EXCAVATION PRIOR TO BACKFILLING, SHALL BE SUBMITTED TO THE VILLAGE.

SCALE
40 0 20 40 80 160
(IN FEET)
1 inch = 40 ft.

UTILITY PLAN

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
03/30/20	PER VILLAGE COMMENTS	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=40' | DATE: 10/28/19


FIRM NO. 184-001330


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.


G:\GV\P\18557\Cmg\18557-9P.dwg

PROJECT No. 18557







STORM MANHOLE #19 W/RESTRICTOR DETAIL
N.T.S.



CATCH BASIN #18 W/EQUALIZER DETAIL
N.T.S.



STORM MANHOLE #2 W/RESTRICTOR DETAIL
N.T.S.



FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557
11 of 23

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net


OFF-SITE UTILITY PLAN

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=40' | DATE: 10/28/19

REVISIONS


DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

COPYRIGHT AS DATED © IG CONSULTING, INC.
FIRM NO. 184-001330
G:\IG\18\18557\Eng\18557-9P.dwg



PLAN AND PROFILE

SCALE: H: 1"=20', V: 1"=4'



REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.


IGC CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | lg@igcconsulting.net

PLAN & PROFILE
STA: 0+00 TO 5+00

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=20' | DATE: 10/28/19

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No.
18557



REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.


IGC CONSULTING, INC.
CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
CONSULTING
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | lg@lgconsulting.net

PLAN & PROFILE
STA: 5+00 TO 10+00

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=20' | DATE: 10/28/19


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557



PLAN AND PROFILE

SCALE: H: 1"=20', V: 1"=4'



REVISIONS		
DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.


IGC CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

PLAN & PROFILE
STA: 10+00 TO 15+73.39

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=20' | DATE: 10/28/19


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No.
18557



PLAN AND PROFILE

SCALE: H: 1"=20', V: 1"=4'



REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.


IGC CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

PLAN & PROFILE
STA: 10+00 TO 15+73.39

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=20' | DATE: 10/28/19


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No.
18557



PLAN AND PROFILE

SCALE: H: 1"=20', V: 1"=4'



REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
12/13/19	PER LANDSCAPE ARCHITECT COMMENTS	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.

IGC CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

PLAN & PROFILE
STA: 10+00 TO 15+73.39

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=20' | DATE: 10/28/19

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No.
18557

GENERAL

1. CONTRACT DOCUMENTS AS REFERRED TO HEREIN INCLUDE THE CONSTRUCTION CONTRACT, PLANS, SPECIFICATIONS, APPROVED SHOP DRAWINGS, CHANGE ORDERS, AND ANY OTHER DOCUMENTS IDENTIFIED IN THE AGREEMENT BETWEEN OWNER AND CONTRACTOR.
2. UNLESS MODIFIED BY THE CONTRACT DOCUMENTS, ALL WORK PROPOSED HEREIN SHALL COMPLY WITH THE FOLLOWING:
   A. ALL ROADWAY CONSTRUCTION SHALL CONFORM TO THE MOST CURRENT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION DATED JANUARY 1, 1997, AND ALL AMENDMENTS THERETO AS ADOPTED BY THE STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION (I.D.O.T.).
   B. STORM SEWER AND SANITARY SEWER, AND WATER MAIN CONSTRUCTION SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS (SSWS), LATEST EDITION.
   C. ILLINOIS RECOMMENDED STANDARDS FOR SEWAGE WORKS, AS PUBLISHED BY THE I.E.P.A. LATEST EDITION.
   D. THE SUBDIVISION AND OTHER PERTINENT CODES AND STANDARDS OF THE **VILLAGE OF GLENCOE, WHERE APPLICABLE.**
   E. THE NATIONAL ELECTRIC CODE, LATEST EDITION.
   F. THE STANDARD SPECIFICATIONS FOR TRAFFIC CONTROL ITEMS, AS PUBLISHED BY I.D.O.T., LATEST EDITION.
3. THE FOREGOING STANDARD SPECIFICATIONS, SUPPLEMENTAL SPECIFICATIONS AND RECURRING SPECIAL PROVISIONS, CONSTRUCTION PLANS, AND SUBSEQUENT DETAILS ARE ALL TO BE CONSIDERED AS PART OF THE CONTRACT. ANY LABOR, MATERIALS OR ACCESSORIES NECESSARY TO COMPLETE THIS WORK MAY NOT BE SPECIFICALLY NOTED BUT ARE CONSIDERED A PART OF THIS CONTRACT.
4. NO CONSTRUCTION PLANS SHALL BE USED FOR CONSTRUCTION UNLESS SPECIFICALLY MARKED "FOR CONSTRUCTION". PRIOR TO COMMENCEMENT OF CONSTRUCTION, THE CONTRACTOR SHALL CAREFULLY ALL DRAWINGS AND CONDITIONS AFFECTING THEIR WORK WITH THE ACTUAL CONDITIONS AT THE JOB SITE. IF THERE ARE ANY DISCREPANCIES FROM WHAT IS SHOWN ON CONSTRUCTION PLANS, HE/SHE MUST IMMEDIATELY REPORT SAME TO THE ENGINEER BEFORE DOING ANY WORK. OTHERWISE, THE CONTRACTOR SHALL ASSUME FULL RESPONSIBILITY FOR THE EXTENT OF DISAGREEMENT BETWEEN THE CONSTRUCTION PLANS, STANDARD SPECIFICATIONS, AND/OR SPECIAL DETAILS, THE CONTRACTOR SHALL BE ENTITLED TO INSTRUCTIONS FROM THE ENGINEER PRIOR TO PROCEEDING WITH ANY PART OF THE WORK AFFECTED BY OMISSIONS OR DISCREPANCIES. FAILING TO REQUEST SUCH INSTRUCTION, THE CONTRACTOR WILL BE CONSIDERED TO HAVE PROCEEDED AT HIS OWN RISK AND EXPENSE. IN THE EVENT OF ANY DOUBT OR QUESTION ARISING WITH RESPECT TO THE TRUE MEANING OF THE CONSTRUCTION PLANS OR SPECIFICATIONS, THE DECISION OF THE ENGINEER SHALL BE FINAL AND CONCLUSIVE.
5. THE ENGINEER AND OWNER ARE NOT RESPONSIBLE FOR THE CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES OR PROCEDURES, TIME OF PERFORMANCE, PROGRAMS, OR JOBSITE SAFETY PRECAUTIONS AND PROGRAMS. IT IS THE DUTY OF THE CONTRACTOR TO SOLELY RESPONSIBLE FOR EXECUTION OF HIS WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AND SPECIFICATIONS. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR SAFETY ON THE JOB SITE. THE CONTRACTORS SHALL PLAN THEIR WORK BASED ON THEIR OWN BORINGS, EXPLORATIONS, AND OBSERVATIONS TO DETERMINE SOIL CONDITIONS AT LOCATION OF THE PROPOSED WORK.
6. NOTIFICATION OF COMMENCING CONSTRUCTION:
   THE CONTRACTOR SHALL BE RESPONSIBLE FOR HAVING THE UTILITY COMPANIES LOCATE THEIR FACILITIES IN THE FIELD PRIOR TO CONSTRUCTION AND SHALL ALSO BE RESPONSIBLE FOR THE MAINTENANCE AND PRESERVATION OF THESE FACILITIES. THE ENGINEER DOES NOT WARRANT THE LOCATION OF ANY EXISTING UTILITIES SHOWN ON THE PLANS. THE CONTRACTOR SHALL CALL J.U.L.I.E. AT 800-892-0123 SUFFICIENTLY IN ADVANCE OF COMMENCING WORK.
   B. THE CONTRACTOR SHALL NOTIFY THE OWNER, ENGINEER, ALTERNATIVE AND THE AFFECTED GOVERNMENTAL AGENCIES IN WRITING AT LEAST THREE FULL WORKING DAYS PRIOR TO COMMENCEMENT OF CONSTRUCTION. THE CONTRACTOR SHALL NOTIFY ALL NECESSARY TESTING AGENCIES SUFFICIENTLY IN ADVANCE OF CONSTRUCTION.
7. ALL WORK PERFORMED UNDER THIS CONTRACT SHALL BE GUARANTEED AGAINST ALL DEFECTS IN MATERIALS AND WORKMANSHIP OF WHATEVER NATURE BY THE CONTRACTOR AND HIS SURETY FOR A PERIOD OF TWO (2) YEARS FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE MUNICIPALITY, OTHER APPLICABLE GOVERNMENTAL BODY, OR PRIVATE OWNER.
8. BEFORE ACCEPTANCE BY THE OWNER AND FINAL PAYMENT, ALL WORK SHALL BE INSPECTED AND APPROVED BY THE OWNER OR HIS REPRESENTATIVE. FINAL PAYMENT SHALL BE MADE FOR ALL ITEMS OF THE CONTRACT AFTER WORK HAS BEEN APPROVED AND ACCEPTED AND IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.
9. UPON AWARD OF THE CONTRACT AND WHEN REQUIRED BY THE OWNER, THE CONTRACTOR SHALL FURNISH A BOND AND PERFORMANCE BOND IN THE FINAL SUM OF ONE HUNDRED (100) PERCENT TO BE CONSIDERED GUARANTEEING THE COMPLETION OF THE WORK. THE UNDERWRITER SHALL BE ACCEPTABLE TO THE OWNER.
10. OWNER SHALL OBTAIN EASEMENTS AND PERMITS NECESSARY TO FACILITATE CONSTRUCTION OF THE PROPOSED UTILITIES. THE CONTRACTOR, HOWEVER, SHALL FURNISH ALL REQUIRED BONDS AND EVIDENCE OF INSURANCE NECESSARY TO SECURE THESE PERMITS.
11. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS FOR CONSTRUCTION ALONG OR ACROSS EXISTING STREETS OR HIGHWAYS. HE SHALL MAKE ARRANGEMENTS FOR THE PROPER BRACING, SHORING, AND OTHER REQUIRED PROTECTION OF ALL ROADWAYS INVOLVED IN THE WORK. HE/SHE SHALL BE RESPONSIBLE FOR ANY DAMAGE TO THE STREETS OR ROADWAYS AND ASSOCIATED STRUCTURES AND SHALL MAKE REPAIRS AS NECESSARY TO THE SATISFACTION OF THE ENGINEER.
12. EASEMENTS FOR THE EXISTING UTILITIES, BOTH PUBLIC AND PRIVATE, AND UTILITIES WITHIN PUBLIC RIGHT-OF-WAY ARE SHOWN ON THE PLANS ACCORDING TO AVAILABLE RECORDS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING THE EXACT LOCATION IN THE FIELD OF THESE UTILITY LINES AND THEIR PROTECTION FROM DAMAGE DUE TO CONSTRUCTION OPERATIONS. IF ANY NATURE ARE ENCOUNTERED WHICH CONFLICT IN LOCATION WITH NEW CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE ENGINEER IMMEDIATELY SO THAT THE CONFLICT MAY BE RESOLVED.
13. LINE AND GRADE STAKES WILL BE SET ONE TIME AND ONE TIME ONLY BY THE SURVEYOR AT THE OWNER'S EXPENSE. THE CONTRACTOR SHALL NOTIFY THE SURVEYOR THAT STAKES WILL BE NEEDED AT LEAST THREE (3) WORKING DAYS IN ADVANCE OF STARTING THAT WORK. ADDITIONAL NOTIFICATION SHALL BE PROVIDED PRIOR TO THE START OF ANY NEW PROJECT CONSTRUCTION WORK. ANY AND ALL REQUIRED RESTAKING WILL BE PERFORMED BY THE SURVEYOR AT THE EXPENSE OF THAT CONTRACTOR REQUESTING THE RESTAKING. IT SHALL BE THE RESPONSIBILITY OF EACH CONTRACTOR TO PROTECT STAKES PROVIDED FOR HIS USE AND TO REPORT TO THE OWNER'S REPRESENTATIVE IMMEDIATELY ANY INSTANCES OF DESTROYING STAKES AND/OR MONUMENTS PROVIDED. LOT CORNER IRONS ARE TO BE CONSIDERED AS CONTROL STAKES.
14. THE PROPOSED ELEVATIONS SHOWN ON THE PLANS ARE FINISHED SURFACE ELEVATIONS, UNLESS OTHERWISE SPECIFIED.
15. ALL TOP OF FRAMES FOR STORM AND SANITARY SEWERS AND VALVE VAULT COVERS REQUIRING ADJUSTMENT TO MEET FINAL GRADE SHALL HAVE SAME TO BE ADJUSTED BY THE SEWER AND WATER CONTRACTOR, AND THE COST IS TO BE CONSIDERED INCIDENTAL TO THIS CONTRACT.
16. ALL CONTRACTORS SHALL KEEP ACCESS AVAILABLE AT ALL TIMES FOR ALL TYPES OF TRAFFIC. AT NO TIME SHALL ACCESS BE DENIED TO HOMES SURROUNDING THE SITE.
17. ANY EXISTING SIGNS, LIGHT STANDARDS, AND UTILITY POLES WHICH INTERFERE WITH CONSTRUCTION OPERATIONS AND NOT NOTED FOR DISPOSAL SHALL BE REMOVED AND RESET BY THE CONTRACTOR AT HIS OWN EXPENSE. FAILING TO COMPLY TO SUCH INSTRUCTION, THE CONTRACTOR WILL BE CONSIDERED TO HAVE PROCEEDED AT HIS OWN RISK AND EXPENSE. IN THE EVENT OF ANY DOUBT OR QUESTION ARISING WITH RESPECT TO THE TRUE MEANING OF THE CONSTRUCTION PLANS OR SPECIFICATIONS, THE DECISION OF THE ENGINEER SHALL BE FINAL AND CONCLUSIVE.
18. REMOVED EARTH, PAVEMENT, SIDEWALK, CURB AND GUTTER, ETC. SHALL BE DISPOSED OF BY THE RESPECTIVE CONTRACTOR AT HIS OWN EXPENSE AT LOCATIONS APPROVED BY THE ENGINEER. IN-SITE DISPOSAL SHALL BE USED IF FEASIBLE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING AN OFF-SITE DISPOSAL SITE AT HIS OWN EXPENSE, INCLUDING ANY COSTS.
19. ALL FIELD TILE ENCOUNTERED DURING CONSTRUCTION OPERATIONS SHALL BE CONNECTED TO THE PROPOSED STORM SEWER SYSTEM OR EXTENDED TO OUTLET INTO A PROPOSED DRAINAGE WAY. THIS CAN NOT BE ACCOMPLISHED, THEN IT SHALL BE REPAIRED WITH NEW PIPE OF SIMILAR SIZE AND MATERIAL TO THE ORIGINAL LINE AND PUT IN ACCEPTABLE CONDITION. A RECORD OF THE LOCATION OF ALL FIELD TILE OR DRAIN PIPE ENCOUNTERED SHALL BE KEPT BY THE CONTRACTOR AND TRANSMITTED TO THE ENGINEER UPON COMPLETION OF THE PROJECT. THE COST OF THIS WORK SHALL BE CONSIDERED AS INCIDENTAL TO THE CONTRACT, AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
20. WHENEVER, DURING CONSTRUCTION OPERATIONS, ANY LOOSE MATERIAL IS DEPOSITED IN THE FLOW LINE OF GUTTERS, DRAINAGE STRUCTURES, DITCHES, ETC. SUCH THAT THE NATURAL FLOW LINE IS IMPEDED OR OBSTRUCTED, SUCH LOOSE MATERIAL SHALL BE REMOVED AT THE CLOSE OF EACH WORKING DAY BY THE RESPONSIBLE PARTY. AT THE CONCLUSION OF CONSTRUCTION OPERATIONS, ALL DRAINAGE STRUCTURES AND FLOW LINES SHALL BE FREE FROM DIRT AND DEBRIS. THIS WORK SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. DRAINAGE MAY BE ACHIEVED BY DITCHING, PUMPING, OR ANY OTHER ACCEPTABLE METHOD. THE CONTRACTOR'S FAILURE TO PROVIDE THE ABOVE SHALL RESULT IN ANY POSSIBLE ADDED COMPENSATION REQUESTED DUE TO DELAYS OR UNSUITABLE MATERIALS CREATED AS A RESULT THEREOF.
21. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ADEQUATE SIGNS, TRAFFIC CONTROL DEVICES, AND WARNING DEVICES TO INFORM AND PROTECT THE PUBLIC FROM DANGERS INHERENT TO CONSTRUCTION. BARRICADES AND WARNING SIGNS SHALL BE PROVIDED IN ACCORDANCE WITH I.D.O.T. STANDARDS FOR CONSTRUCTION OPERATIONS. ALL ADEQUATE LIGHTING SHALL BE MAINTAINED FROM DUSK TO DAWN AT ALL LOCATIONS WHERE CONSTRUCTION OPERATIONS WARRANT OR AS DESIGNATED BY THE ENGINEER. ALL TRAFFIC CONTROL DEVICES SHALL BE IN FULL COMPLIANCE WITH THE I.D.O.T. MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
22. ALL PERMANENT TYPE PAVEMENTS OR OTHER PERMANENT IMPROVEMENTS WHICH ABUT THE PROPOSED IMPROVEMENTS SHALL BE PROTECTED AND SHALL BE SAWED AS DIRECTED PRIOR TO REMOVAL. ALL ITEMS SO REMOVED SHALL BE REPLACED WITH SIMILAR CONSTRUCTION MATERIALS AND CONSTRUCTION METHODS OR BETTER. NO PAYMENT FOR SAWING SHALL BE INCLUDED IN THE COST FOR REMOVAL OF EACH ITEM, AND REPLACEMENT SHALL BE PAID UNDER THE RESPECTIVE ITEMS IN THE CONTRACT, UNLESS OTHERWISE INDICATED.
23. WHERE OVERHANGING BRANCHES INTERFERE WITH OPERATIONS OF CONSTRUCTION, SAID BRANCHES SHALL BE TRIMMED AS REQUIRED BY SECTION 201.05 OF THE I.D.O.T. STANDARD SPECIFICATIONS, AND THE COST OF SAME SHALL BE INCIDENTAL TO THE CONTRACT. TREES SHALL BE REMOVED ONLY AFTER THE RECEIVING APPROVAL OF THE OWNER. THE OWNER SHALL DESIGNATE THOSE TREES WHICH ARE TO BE REMOVED. ALL TREES WITHIN THE RIGHT-OF-WAY, NOT IN THE LINE OF SEWERS, WATER MAINS, PATHWAYS, SIDEWALKS, AND DRIVEWAYS AS DIRECTED TO PRESERVE TREES. A CONTRACTOR REMOVING TREES WITHOUT OWNER'S APPROVAL WILL BE RESPONSIBLE FOR REPLACEMENT OF SAID TREE(S) AS DIRECTED BY THE OWNER AT CONTRACTOR'S EXPENSE. IF TREES OR SHRUBS ARE TO BE REMOVED, THEY WILL BE PAID FOR IN ACCORDANCE WITH THE SPECIFICATIONS.
24. ALL EXISTING TRAFFIC SIGNS, STREET SIGNS, ETC., WHICH INTERFERE WITH CONSTRUCTION OPERATIONS AND NOT NOTED FOR REMOVAL OR DISPOSAL SHALL BE REMOVED AND RESET BY THE CONTRACTOR AT LOCATIONS AS DESIGNATED BY THE ENGINEER. THIS SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT AND NO ADDITIONAL COMPENSATION SHALL BE ALLOWED. DAMAGE TO THESE ITEMS SHALL BE REPAIRED BY THE CONTRACTOR AT HIS OWN EXPENSE. ALL SIGNS NOT REQUIRED TO BE RESET SHALL BE DELIVERED TO THE MUNICIPALITY AS APPROPRIATE. IN ADDITION, ALL MAIL BOXES THAT INTERFERE WITH CONSTRUCTION SHALL BE SIMILARLY RELOCATED AT NO ADDITIONAL COST IN ACCORDANCE WITH ARTICLES 107.19 AND 107.21 OF THE I.D.O.T. STANDARD SPECIFICATIONS.
25. SPECIAL ATTENTION IS DRAWN TO THE FACT THAT ARTICLE 105.06 OF THE STANDARD SPECIFICATIONS REQUIRES THE CONTRACTOR TO HAVE A COMPETENT SUPERINTENDENT ON THE PROJECT AT ALL TIMES IRRESPECTIVE OF THE AMOUNT OF WORK SUBLET. THE SUPERINTENDENT SHALL BE CAPABLE OF READING AND UNDERSTANDING THE PLANS AND SPECIFICATIONS AND SHALL HAVE THE AUTHORITY TO EXECUTE ORDERS TO EXPEDITE THE PROJECT, AND SHALL BE RESPONSIBLE FOR SCHEDULING AND HAVE CONTROL OF ALL WORK AS THE AGENT OF THE CONTRACTOR. FAILURE TO COMPLY WITH THIS PROVISION WILL RESULT IN SUSPENSION OF WORK AS PROVIDED IN ARTICLE 108.07.
26. THE CONTRACTOR SHALL COLLECT AND REMOVE ALL CONSTRUCTION DEBRIS, EXCESS MATERIALS, TRASH, OIL AND GREASE RESIDUE, MACHINERY, TOOLS, AND OTHER MISCELLANEOUS ITEMS WHICH WERE NOT PRESENT PRIOR TO PROJECT COMMENCEMENT AT NO ADDITIONAL EXPENSE TO THE OWNER. BURNING ON THE SITE IS NOT PERMITTED.
27. ALL EXISTING UTILITIES OR IMPROVEMENTS INCLUDING WALKS, CURBS, PAVEMENTS, AND PAVEMENT PATCHES DAMAGED OR REMOVED DURING CONSTRUCTION SHALL BE PROMPTLY RESTORED TO THEIR RESPECTIVE ORIGINAL CONDITION.
28. HYDRANTS SHALL NOT BE FLUSHED DIRECTLY ON THE ROAD SUBGRADES. WHENEVER POSSIBLE, HOSES SHALL BE USED TO DIRECT THE WATER ON TO LOT AREAS OR THE STORM SEWER SYSTEM (IF AVAILABLE). WHEN HYDRANTS MUST BE FLUSHED, DAMAGE TO THE ROAD SUBGRADE DUE TO EXCESSIVE WATER SATURATION FROM HYDRANT FLUSHING OR FROM LEAKS IN THE WATER DISTRIBUTION SYSTEM SHALL BE THE RESPONSIBILITY OF THE OWNER OF THE SEWER AND WATER CONTRACTOR.
29. ANY DEWATERING OF SEWER AND WATER TRENCHES, AS WELL AS TEMPORARY SHEETING OR BRACING THAT MAY BE REQUIRED, SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR, AND SHALL NOT BE CONSIDERED EXTRA WORK, IN THE EVENT THAT SOFT MATERIALS WITH UNCONFINED COMPRESSIVE STRENGTH LESS THAN 0.5 TSF ARE ENCOUNTERED IN SEWER AND WATER MAIN CONSTRUCTION, THE CONTRACTOR SHALL (UPON APPROVAL OF THE OWNER AND/OR ENGINEER) OVER-EXCAVATE TO A DEPTH OF ONE (1) FOOT BELOW THE BOTTOM OF THE PIPE AND BACKFILL WITH COMPACTED CRUSHED STONE, PROPERLY FORMED TO FIT THE BOTTOM OF THE PIPE.
30. THE CONTRACTOR SHALL PROVIDE ONE MYLAR AND THE REQUIRED QUANTITY OF BLUELINE SETS OF "RECORD DRAWINGS" TO THE ENGINEER PRIOR TO ANY REQUEST FOR FINAL INSPECTION. IF PROVIDED FOR IN THE CONSTRUCTION CONTRACT, SAID PLANS SHALL BE ACCURATELY MARKED TO SHOW ALL LOCATIONS AND DETAILS WHICH INCLUDE VERIFICATION OF ALL BUILDING PADS, TOP OF FOUNDATION, INVERT, RIM AND SPOT GRADE ELEVATIONS, AND INCORPORATE ALL FIELD DESIGN CHANGES APPROVED BY THE ENGINEER.
31. CONTRACTOR SHALL VIDEO TAPE THE WORK AREA PRIOR TO CONSTRUCTION FOR THE PURPOSE OF DOCUMENTING EXISTING CONDITIONS.
32. IT SHALL BE THE RESPONSIBILITY OF THE OWNER OR OTHERS DESIGNATED BY THE OWNER TO ARRANGE FOR PROTECTIVE FENCING AT THE CONSTRUCTION SITE. IG CONSULTING, INC. SHALL NOT BE RESPONSIBLE FOR PROVIDING SPECIFICATIONS, METHODS, SAFETY PRECAUTIONS, OR SEQUENCING OF CONSTRUCTION SITE FENCING OR BARRICADES.

SOIL EROSION CONTROL

1. THIS WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE PROCEDURES AND STANDARDS FOR URBAN SOIL EROSION AND SEDIMENT CONTROL IN ILLINOIS, THE I.E.P.A. STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENTATION CONTROL AND WITH ALL APPLICABLE COUNTY AND LOCAL ORDINANCES AND REGULATIONS.
2. ANY SOIL EROSION CONTROL MEASURES, IN ADDITION TO THOSE OUTLINED IN THESE PLANS AND SPECIFICATIONS, WHICH ARE NECESSARY TO COMPLY WITH FEDERAL, STATE, MUNICIPAL ENGINEER SHALL BE IMPLEMENTED IMMEDIATELY BY THE CONTRACTOR.
3. BEFORE COMMENCING CLEARING AND SITE GRADING WORK, A CONSTRUCTION ENTRANCE SHALL BE INSTALLED AS SHOWN ON THE PLANS. THE CONSTRUCTION ENTRANCE TO THE SITE SHALL BE STABILIZED WITH GRAVEL OR ASPHALTIC SURFACE AS SHOWN ON THE PLANS PRIOR TO ANY WORK ON THE SITE. THE ENTRANCE SHALL BE MAINTAINED PERIODICALLY FOR ITS EFFECTIVENESS TO REMOVE DIRT WHICH COULD LEAVE THE SITE BY CONSTRUCTION VEHICLES. ROADWAYS SHALL BE KEPT CLEAN AT ALL TIMES. CONSTRUCTION VEHICLES ARE LIMITED TO THE CONSTRUCTION ACCESS ROAD NOTED ON THE PLAN (STABILIZED CONSTRUCTION ENTRANCE).
4. STREETS ADJACENT TO THE SITE SHALL BE KEPT FREE OF DIRT, MUD, AND DEBRIS.
5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROPER INSTALLATION AND MAINTENANCE OF ALL TEMPORARY AND PERMANENT EROSION CONTROL DEVICES.
6. THE CONTRACTOR SHALL INSPECT AND DOCUMENT EROSION CONTROL MEASURES ON A WEEKLY BASIS AND WITHIN 24 HOURS AFTER ANY RAINFALL EVENT IN EXCESS OF ONE-HALF INCH.
7. NO SEDIMENT (SOLID OR LIQUID WASTE) SHALL BE ALLOWED TO ENTER THE EXISTING STORM SEWER SYSTEM.
8. ALL STORM SEWER, CATCH BASINS, AND SUMPS PROVIDED WITHIN THIS PROJECT ARE TO BE CLEANED AT THE END OF CONSTRUCTION OF THE PROJECT AND PRIOR TO FINAL ACCEPTANCE. CLEANING MAY ALSO BE REQUIRED DURING THE COURSE OF CONSTRUCTION OF THE PROJECT IF IT IS DETERMINED THAT THE SILT AND DEBRIS TRAPS ARE NOT PROPERLY FUNCTIONING AND THEIR PERFORMANCE IS IMPAIRED.
9. TOPSOIL STOCKPILES SHALL BE LOCATED TO AVOID EROSION OF SAID STOCKPILE ONTO OFF-SITE AREAS, I.E., THE STOCKPILE SHALL BE LOCATED SO THAT AN ON-SITE DRAINAGE SWALE IS LOCATED BETWEEN THE STOCKPILE AND THE DOWNSTREAM OFF-SITE PROPERTY. IF A STOCKPILE IS TO REMAIN IN PLACE FOR MORE THAN TWELVE (12) MONTHS, IT IS REQUIRED THAT THE STOCKPILE BE SEEDED SO AS TO MINIMIZE SOIL EROSION BY BOTH WIND AND WATER.
10. TEMPORARY SOIL STABILIZATION SHALL OCCUR WITHIN SEVEN (7) DAYS AFTER ROUGH GRADING IF A DISTURBED AREA WILL REMAIN IDLE LONGER THAN THIRTY (30) DAYS. PERMANENT SOIL STABILIZATION SHALL BE INSTALLED WITHIN SEVEN (7) DAYS AFTER FINAL GRADE IS REACHED ON ANY PORTION OF THE SITE. PERMANENT VEGETATION IS A GROUND COVER SUFFICIENT ENOUGH TO COVER 80% OF THE SOIL SURFACE AND MATURE ENOUGH TO SURVIVE WINTER WEATHER CONDITIONS.
11. THE TEMPORARY EROSION CONTROL MEASURES SHALL BE PLACED EFFECTIVELY UNTIL ALL THE PERMANENT EROSION CONTROL ITEMS ARE FULLY FUNCTIONING.
12. THE CONTRACTOR SHALL PERFORM SEEDING, MULCHING AND MAINTENANCE EROSION CONTROL MEASURES ARE FULLY FUNCTIONAL AND ACCEPTABLE TO OWNER OR HIS REPRESENTATIVE.
13. UNLESS SOIL EROSION CONTROL ITEMS ARE SPECIFICALLY REFERRED TO AS BID ITEMS (SUCH AS TOPSOIL RESPREAD, SEEDING, ETC.), THEY ARE TO BE CONSIDERED AS INCIDENTAL TO THE COST OF THE CONTRACT.
14. UPON COMPLETION OF TOPSOIL RESPREAD OPERATIONS, ALL DISTURBED AREAS SHALL BE SEEDED AND MULCHED OR LANDSCAPED AS NOTED ON THE PLAN.
15. SEEDING AND MULCHING SHALL BE IN ACCORDANCE WITH SECTIONS 250 AND 251 OF THE STANDARD SPECIFICATIONS. SEED MIXTURE SHALL BE CLASS 1.
16. SODDING SHALL BE IN ACCORDANCE WITH SECTION 252 OF THE I.D.O.T. STANDARD SPECIFICATIONS.

SITE PREPARATION AND EARTHWORK

1. WORK UNDER THIS SECTION SHALL INCLUDE BUT NOT LIMITED TO THE FOLLOWING:
   A. CLEARING AND REMOVAL OF ALL UNDESIRABLE TREES AND OTHER VEGETATIVE GROWTH WITHIN THE CONSTRUCTION AREA. TREE REMOVAL SHALL BE AS DESIGNATED BY THE OWNER AND SHALL BE KEPT TO A MINIMUM. WHERE FEASIBLE AND WHEN PERMITTED BY THE OWNER AND BY THE LOCAL JURISDICTION, TREES AND BRUSH SHALL BE CHIPPED, SAWED, AND BURIED OR SPREAD IN DESIGNATED LOCATIONS ON-SITE. IF ADEQUATE AND APPROPRIATE SPACE IS NOT AVAILABLE FOR ON-SITE BURIAL, THE TREES AND BRUSH SHALL BE DISPOSED OFF-SITE. NO BURNING SHALL BE PERMITTED AS INDICATED, THE CONTRACTOR SHALL COMPLY WITH ALL TREE ORDINANCES, TREES AND SHRUBS DESIGNATED TO BE SAVED SHALL BE PROTECTED FROM HIGH VOLTAGE CONSTRUCTION WITH GUARDS AND THE DRIP LINES. TREES DESIGNATED FOR RELOCATION AND/OR TEMPORARILY STORED FOR TRANSPLANTING SHALL BE PROPERLY BALLED AND BURLAPPED. WHERE REQUIRED BY OWNER, TRUNKS OF DESIGNATED TREES SHALL BE PROTECTED WITH STRAPPED 2" X 6" PLANKING FROM THE BASE TO A HEIGHT OF EIGHT (8) FEET.
   B. STRIPPING OF TOPSOIL FROM ALL STREET, DRIVEWAY, PARKING LOT, RIGHT-OF-WAY, BUILDING PAD, AND OTHER DESIGNATED STRUCTURAL AREAS.
   C. STOCKPILING OF TOPSOIL AT LOCATIONS AS DIRECTED BY THE OWNER. TOPSOIL STOCKPILED FOR FUTURE USE SHALL BE RELATIVELY FREE OF LARGE STONES, ROOTS, WEEDS, BRUSH, STUMPS LARGER THAN TWO (2) INCH DIAMETER, OR OTHER LITTER AND WASTE PRODUCTS INCLUDING EXTRANEOUS MATERIALS HARMFUL TO PLANT GROWTH. TOPSOIL SHALL BE STOCKPILED IN SEQUENCE TO MINIMIZE REHANDLING. FAILURE TO PROPERLY SEQUENCE THE EXCAVATION OPERATIONS SHALL NOT CONSTITUTE A CLAIM FOR ADDITIONAL COMPENSATION. NO MATERIAL SHALL BE STOCKPILED IN FRONT YARDS, DRAINAGE SWALES (FLOOD ROUTING AREAS), IN WETLANDS, IN PROPOSED UTILITY LOCATIONS, IN UTILITY EASEMENTS, OR IN THE RIGHT-OF-WAY. ABSOLUTELY NO MATERIALS WILL BE STOCKPILED OR DISPOSED UNDER THE CANOPIES OF TREES DESIGNATED FOR PROTECTION.
   D. REMOVING UNSUITABLE MATERIALS AS SPECIFIED FROM ROADWAY, DRIVEWAY/PARKING, BUILDING PAD, AND OTHER DESIGNATED AREAS.
   E. DEMOLITION AND REMOVAL OF EXISTING BUILDINGS AND/OR PAVEMENTS INCLUDING OFF-SITE DISPOSAL OF SAME, AT A LEGAL DISPOSAL SITE SELECTED BY THE CONTRACTOR. ON-SITE DISPOSAL WILL ONLY BE ALLOWED IF EXPRESSLY APPROVED BY OWNER IN WRITING.
   F. CLAY CUT AND CLAY FILL WITH COMPACTION WITHIN ROADWAY, DRIVEWAY/PARKING, BUILDING PAD, AND OTHER DESIGNATED AREAS.
   G. EXCAVATION AND GRADING OF THE OPEN SPACE AND/OR YARD AREAS PER PLAN INCLUDING DESIGNATED POND REGRADING, CONSTRUCTION OF BERMS, ETC.
   H. PLACEMENT AND COMPACTION OF CLAY TO STANDARDS AND DETAILS REQUIRED ON THE CONSTRUCTION PLANS TO THE DESIGN SUBGRADE ELEVATIONS. THE CONTRACTOR WILL NOTE THAT THE ELEVATIONS SHOWN ON THE CONSTRUCTION PLANS ARE FINISHED GRADE ELEVATIONS AND THAT PAVEMENT AND/OR TOPSOIL REPLACEMENT THICKNESS MUST BE SUBTRACTED TO DETERMINE SUBGRADE ELEVATIONS.
   I. PLACEMENT AND COMPACTION OF NON-STRUCTURAL FILLS.
   J. IF REQUIRED, REMOVAL FROM SITE AND DISPOSAL OF ANY EXCESS OR UNSUITABLE MATERIAL UPON COMPLETION OF FINISH GRADING.
   K. MOVEMENT AND COMPACTION OF SPOIL MATERIAL FROM THE CONSTRUCTION OF UNDERGROUND UTILITIES.
   L. BACKFILLING OF CURBS AND/OR PAVEMENTS AND SIDEWALK AFTER INSTALLATION OF SAME BY THE PAVING CONTRACTOR.
   M. FINAL SHAPING AND TRIMMING TO THE LINES, GRADES, AND CROSS-SECTION SHOWN IN THESE PLANS; AND TOPSOIL PLACEMENT TO DESIGN FINISHED GRADE ELEVATIONS.
   N. SOIL EROSION CONTROL MEASURE IN ACCORDANCE WITH THE APPLICABLE SPECIFICATIONS, UNLESS SPECIFICALLY EXCLUDED IN THE CONSTRUCTION CONTRACT.

SEWER AND WATER

1. GENERAL
   A. WORK UNDER THIS SECTION SHALL INCLUDE TRENCHING, INSTALLATION OF PIPE, CASTINGS, STRUCTURES, MANHOLES, CATCH BASINS, BUBBLERS, DRAINS, AND TESTING AS SHOWN ON THE CONSTRUCTION PLANS. FITTINGS AND ACCESSORIES NECESSARY TO COMPLETE THE WORK MAY NOT BE SPECIFIED, BUT SHALL BE CONSIDERED AS INCIDENTAL TO THE COST OF THE CONTRACT.
   B. ALL SEWER AND WATER MAIN SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR SEWER AND WATER MAIN CONSTRUCTION IN ILLINOIS, CURRENT EDITION, AND THE STANDARD SPECIFICATIONS AND CONSTRUCTION DETAILS AND ORDINANCES OF THE LOCAL JURISDICTION.
   C. ROUGH GRADING TO WITHIN ONE (1) FOOT OF FINISHED SUBGRADE SHALL BE COMPLETED PRIOR TO COMMENCEMENT OF UNDERGROUND UTILITY INSTALLATION.
   D. ALL UTILITY TRENCHES BENEATH PROPOSED OR EXISTING UTILITIES, PROPOSED OR EXISTING PAVEMENT, DRIVEWAYS, SIDEWALKS AND FOR A DISTANCE OF TWO FEET ON EITHER SIDE OF SAME, AND/OR WHEREVER ELSE SHOWN ON THE CONSTRUCTION PLAN SHALL BE BACKFILLED WITH SELECT GRANULAR BACKFILL (CA-6) AND THOROUGHLY COMPACTED IN ACCORDANCE WITH SPECIFICATIONS.
   E. ALL SANITARY SEWERS, STORM SEWERS, AND SEWER SERVICES SHALL BE INSTALLED ON GRANULAR CRUSHED STONE BEDDING, CLASS I, (I.D.O.T. GRADATION RR-3) CONFORMING TO ASTM D-2321, WITH A MINIMUM THICKNESS EQUAL TO ONE-QUARTER (1/4TH) OF THE OUTSIDE DIAMETER OF THE SEWER PIPE, BUT NOT LESS THAN FOUR (4) INCHES OR MORE THAN EIGHT (8) INCHES. BEDDING SHALL EXTEND UP TO SPRING LINE OF PIPE AS SHOWN ON THE PLANS. IN ALL CASES, FOR PVC SANITARY SEWER, THE BEDDING SHALL EXTEND TO ONE (1) FOOT ABOVE THE TOP OF THE PIPE. BEDDING MATERIAL SHALL CONFORM TO THE REQUIREMENTS OF ASTM C-33 FOR SOUNDNESS AND ASTM C-67 FOR DEGRADATION. COST FOR BEDDING SHALL BE MERGED WITH THE UNIT PRICE BID FOR THE SEWER, WATER MAIN, ETC.
   F. THE UNDERGROUND CONTRACTOR SHALL DISPOSE OF EXCESS EXCAVATED TRENCH MATERIAL WHICH CANNOT BE USED AS FILL AND WHICH IS A HAZARD OR OBSTRUCTION, AND SHALL MAINTAIN AND RESTORE THE SITE TO A WORKABLE

SECTION 2: WATER MAIN

2.1 DESCRIPTION
This work shall consist of furnishing and installing water mains of the required material, size and class together with the necessary fittings, jointing materials and blocking, complete as specified herein and in conformance with the detailed plans.

2.2 MATERIALS
Unless otherwise specified, all materials shall conform to the current AWWA Standards listed below.

a) C-105 Polyethylene Encasement for Ductile Iron Piping.
b) C-153 Ductile Iron Fittings
c) C-151 Ductile Iron Pipe, Centrifugally Cast in Metal Molds or Sand Lined Molds
d) C-909 Class 150 molecularly oriented polyvinyl chloride pipe

Water mains shall be constructed of the materials shown on the plans or specified. Where alternate materials are provided, water mains shall be constructed of the pipe materials selected by the Village at the time of Contract award.

2.3 DUCTILE IRON FITTINGS
Unless otherwise specified, all fittings shall be mechanical joint at all openings. Fittings shall be designed for a minimum working pressure of 250 psi. The cost of all fittings shall be incidental to the Water Main unit price.

Fittings set forth on the plans are for guidance purposes only and are considered a minimum requirement. The Contractor shall provide all fittings required to make a completed installation.

2.4 DUCTILE IRON PIPE
All ductile iron pipes, unless otherwise specified, shall be designed for a maximum working pressure of 350 psi and of a thickness class as specified. All pipes shall be made in standard 18-foot or 20-foot lengths and shall have standard thickness cement lining on the inside.

2.5 STEEL RODS, TURNBUCKLES, BOLTS AND WASHERS
Steel rods shall be S.A.E. 1020 or other steel meeting the approval of the Engineer. Turnbuckles shall be drop forged and conform in dimensions and weights to the latest "Manual of the American Institute of Steel Construction."
Bolts shall be U.S. Standard. Washers may be cast, malleable, or cut steel.

2.6 EXCAVATION AND FOUNDATION
Unless otherwise specified, the trench shall be excavated to a depth which will provide 5.5 feet minimum of cover between the top of the water main and the established finished roadway grade or natural ground, whichever is deeper. The trench for the water main shall be excavated with vertical walls and be a minimum of 24 inches.

Pipe bedding for both Paved Areas and Non-Paved Areas shall be as follows and specified on plans and/or bidding document:

The water main pipe shall be laid on a bedding of compacted 1-inch washed stone with no fines extending the full width of the trench bottom. The bedding shall be placed to a minimum depth of four (4) inches. The bedding stone shall be installed around the water main pipe and full trench width to a thickness above the top of pipe of four (4) inches minimum. The remaining backfill shall be selected materials tamped in place as specified under Section 2.9 or as directed by the Village.

Prior to laying pipe, the bedding materials shall be shaped to provide continuous support for the pipe barrel. Under no circumstances will the pipe be laid on blocks or wedges. Where pipe with a bell or coupling is used, cross trenches shall be excavated to prevent non-uniform loading at joints. The cross trenches shall not be more than two (2) inches wider than the width of the bell or hub.

2.7 LAYING WATER MAIN
All pipe and fittings shall be carefully examined for cracks and other defects just prior to lowering into the trench for installation in final position. Defective pipe or fittings shall be marked and laid aside so as to not be mistakenly used in the improvements. All defective materials shall be removed from the project site upon conclusion of the work day on which they are discovered.

All ductile iron pipes shall be Class 52, cement-lined with push-on joints. The ductile iron water main shall be encased with a polyethylene tube in accordance with AWWA C-105, Method A.

All PVC water mains shall be M.O.P.V.C. Type C 909, Class 150, with push- on joints. A nominal 5" minimum cover is to be provided between the top of the water main and the proposed surface. A tracer wire shall be installed and attached to the PVC main consisting of #10 AWG solid copper THNN. Tracer wire shall have access points in all line valve vaults and hydrant auxiliary valve boxes.

All ductile iron water main shall be installed with serrated bronze wedges in the joints to provide a means of tracing and/or for electrical thawing. Two wedges per joint shall be utilized for 12" or less pipe size.

Bedding shall be in accordance with Section 2.5 of the Specifications, a nominal 5' minimum cover is to be provided between the top of the water main and the proposed surface.
All fittings shall be short-body ductile iron. Bedding, wedges, nominal cover, etc., required for water main shall also apply to fittings.

Before lowering pipe and fittings into the trench, all dirt and foreign matter shall be removed from the pipe interior. After lowering the pipe into the trench and prior to joining the pipe, the bottom worker shall check the joint being made to assure both ends are free of foreign materials picked up during the lowering operation.

As each length of pipe is placed in the trench, the spigot end shall be centered in the bell of the previously installed pipe and forced home. The pipe shall then be installed to the line and grade established by the Village. A tolerance of two
(2) inches in both horizontal and vertical alignment shall be allowed per pipe length on straight runs. The pipe shall be secured in place by tamping approved backfill material around the pipe except at the bell end. Every precaution shall be taken to prevent foreign material from entering the open end of the installed pipe prior to installing the next pipe.
If, for any reason there is a stoppage in the pipe-laying operation, the open end of the last installed pipe shall be sealed by means of a watertight plug. If, upon commencement of work there is water in the trench, the plug shall remain in place until the trench is completely de-watered.

Proper implements, tools and facilities satisfactory to the Village shall be provided and used by the Contractor for efficient execution of work. All pipe, fittings and accessories shall be handled by suitable equipment in a manner to prevent damage to the materials. Under no circumstances shall pipe or accessories be dropped or dumped into the trench.

2.8 BACKFILLING
All trenches and excavation shall be backfilled to finished grade as soon as conditions will permit. The backfill material shall consist of either approved trench backfill aggregate materials if located in Paved Areas or excavated clean material if located in Non-Paved Areas, except that no materials will be allowed that may have any detrimental effect on the pipe, fittings or other appurtenances.
Backfill shall be placed above the bedding stone with clean earthen materials free of clumps and unsuitable materials, except at locations where trench backfill is required. In the event this material is not readily available at all locations, the Contractor shall provide suitable conditioned soil or an approved material for this purpose. Select material shall be placed in the trench and compacted in maximum 2 foot lifts. All select materials shall be compacted to the satisfaction of the Village. No frozen material shall be used as selected backfill. Backfill so placed shall be deposited in the trench in a manner to avoid impact and uneven loading of the water main. After settlement has taken place, the trenches shall be refilled and graded to a finished condition acceptable to the Village.

2.9 TRENCHED BACKFILL PAVED AREAS
Backfill for trenches within the limits of paved areas above the bedding material shall be with aggregate meeting IDOT specifications for Trench Backfill CA-6 or crushed aggregate meeting the gradation requirements for trench backfill material.

2.10 MECHANICAL RESTRAINT JOINTS
Mechanical restraint joints shall be installed according to the manufacturer's specifications. The pipe bells, spigot ends of pipe and pipe gaskets shall be clean and free from particles of sand, dirt or other objectionable matter during jointing. Pipe bolts shall be drawn up uniformly by turning diametrically opposite bolt nuts simultaneously in a manner that the joint gland and rubber gasket are brought to bearing and final seating without warp or eccentricity. All mechanical joints shall be installed with "Mega-Lug" type joint restraint series 1000 as manufactured by Ebba Iron Corp, as specified for ductile iron main or PVC main.

2.11 PUSH-ON JOINTS
Push-on joints shall be installed according to the manufacturer's specifications. The pipe bells, spigot ends of pipe and pipe gaskets shall be clean and free from particles of sand, dirt or other objectionable matter during jointing. Pipe shall be assembled by means of a rotary jack type tool or other approved method. Jointing by the so-called "stabbing" of the pipe spigot into the coupling will not be permitted.

2.12 THRUST BLOCKING AND ANCHORAGE
All tees and bends shall be mechanically restrained and anchored with concrete blocks or poured concrete thrust blocks as specified by the Village and shall be keyed into solid ground at the respective fittings to a depth of not less than three (3) inches and shall extend to solid ground backing in the direction of the thrust, unless otherwise shown or specified on the plans.

Concrete blocking shall extend to a point above the horizontal pipe diameter and in a manner to secure the pipelines from lateral thrust displacement and insure ability to caulk or tighten all the joints. Concrete blocking shall consist of Class X concrete with minimum moisture content to enable tamping in place and molding. Blocking dimensions will be as shown on the plans or as determined in the field by the Village. Fittings at ends of pipelines shall be blocked or harnessed with suitable ties to the pipeline in a manner to permanently anchor the same in place. Plugs shall be blocked in a manner that will facilitate their removal and subsequent extension of the water mains.

Metal harnesses of adequate strength to prevent movement may be used instead of concrete blocking, if permitted by the Village. Steel rods or clamps shall be galvanized or otherwise rustproof treated, as approved by the Village. The cost of metal harnesses shall be incidental to the construction.

2.13 CONNECTIONS TO EXISTING WATER MAINS
Before making any connection to existing water mains, the Contractor shall have all necessary tools, materials, pipe and fittings on hand and sufficient experienced workers available to preclude any unnecessary delay in making the connection due to adverse conditions or mishap. The actual work of cutting into a main or removal of a fitting shall not be done until all measurements, necessary pipe assembly and other specified provisions have been completed. If the connection required shutting down the existing main, the Contractor shall make the necessary arrangements with the Village to accomplish same. In addition, all users to be affected shall be notified 24 hours in advance of water main shutdown by the Village. At no time shall Contractor shut down any water main without the knowledge and consent of the Village.

Temporary blocking capable of withstanding the service pressure shall be provided for all existing valves, fittings and pipe that could be affected by the new construction.

The cost of making connections to existing water mains shall be paid for at the contract unit price per each CUT-IN CONNECTION.

2.14 PRESSURE CONNECTIONS

Pressure connections shall be performed in accordance with Section 46 of the Standard Specifications. The required equipment, labor and material shall be paid for at the contract unit price per each PRESSURE CONNECTION.

2.15 HOUSE SANITARY SEWER AND WATER SERVICES
At all locations where the water main crosses house services, adequate precautions shall be taken by the Contractor to prevent unnecessary and lengthy shutdown of the service. Wherever possible, the water main shall be constructed so as to not damage the services or interfere with their future operation. Any service that is damaged shall be repaired with new material in such a manner that future operation will not be impaired. All work in connection with house services shall conform to the ordinances and requirements of the Village.

Change or adjustment in the line or grade of the pipeline to clear obstructions shall be approved by the Village. All materials required for this purpose shall be furnished by the Village with the work performed by the Contractor and shall be incidental to and included in the contract unit price for water main, unless otherwise specified.

In those instances where house services require adjustment, the work shall be done under the requirements of the Standard Specifications and paid for at the contract unit price per linear foot of SANITARY SERVICE TO BE ADJUSTED.

2.16 HYDROSTATIC TEST
All newly laid water main, fittings, valves and hydrants shall meet the requirements of the following hydrostatic tests before being accepted by the Village.

a) Pressure Test
After completion of the water main, as previously outlines, the main shall be filled with water and the air allowed to escape through hydrants, air release valves, and blow-offs, etc. When the main is free of air, the water pressure shall be raised to 125 pounds per square inch by the addition of water through a force pump and other apparatus. The test pressure shall be maintained for a one-hour period by the addition of water through the pump.

The pipeline, all valves, fittings and hydrants shall be carefully examined during the pressure test to determine if there are any defective pipe, fittings, hydrants or leaking joints. All defective material shall be removed and replaced with sound material and all leaks repaired. The test shall then be repeated until the required results are achieved.

b) Leaking Test
After satisfactory completion of the pressure test, a leakage test shall be conducted. The water pressure in the main shall be raised to minimum pressure of 120 pounds per square inch, unless otherwise specified, by the addition of water to the main. The test pressure shall be maintained in the main for a two (2) hour period. The allowable amount of make-up water to maintain the specified test pressure shall not exceed the following rates for each 1000 feet of pipe.

LEAKAGE IN GPH FOR EACH 1000 FEET OF PIPE

PSI	6"	8"	10"	12"	14"	16"	18"	20"	24"
100	0.45	0.60	0.75	0.90	1.05	1.20	1.35	1.50	1.80
110	.047	0.63	0.79	0.94	1.10	1.26	1.41	1.57	1.89
120	0.49	0.66	0.82	0.99	1.15	1.31	1.48	1.64	1.97
130	0.51	0.68	0.85	1.03	1.20	1.37	1.54	1.71	2.05
140	0.53	0.71	0.89	1.06	1.24	1.42	1.60	1.78	2.13
150	0.55	0.74	0.92	1.10	1.29	1.47	1.65	1.84	2.21

In order to make the above tests, the Contractor shall furnish all apparatus, piping, hose, pump and pressure tank, gauges properly calibrated, a clean barrel or drum to hold water and a five (5) gallon graduated container capable of a gallon or into one-half (½) pints. The Village reserves the right to use Village owned tanks and gauges when considered necessary to check the Contractor's equipment for accuracy.

The above specified tests shall be made on sections not exceeding 2,000 feet in length. Mains which fail to meet the requirements of the initial test shall be repaired and retested until all the requirements have been met. All tests shall be made through one-inch corporation cocks trapped into the main.

2.17 WATER MAIN DISINFECTION
Prior to chlorination and after completion of the pressure test, each pipeline construction section shall be flushed at a minimum water velocity of 2.5 fps in manner and for such length of time as the Village may require to effectively clear the mains, valves, hydrant lead and fittings. Temporary flushing risers shall be provided at the termination of all water mains to assure flushing of the dead ends. All mains and accessories shall be chlorinated under the supervision of the Village by the use of chlorine gas as directed. A proper chlorine concentration shall be introduced into the section of main to be chlorinated by means of one-inch corporation cocks inserted in the top of the new main, in order that the sterilization solution will make proper contact with all interior surfaces, corporation cocks shall be inserted in the top of the new main at the beginning of each pipeline extension and at the ends of any such extension where means of bleeding off water is not available.

The valve controlling water flow from the existing distribution system into the new work shall be opened sufficiently to assure a slow rate of flow into the new pipeline. After regulating the flow from observations at the bleed-off point, the chlorine shall be introduced into the new main at a uniformly proportionate rate until the water in the pipeline has a chlorine content of 50 to 100 ppm and until a heavy chlorine concentration at the bleed-off point is evident.

The Contractor shall exercise every precaution to prevent the chlorine solution from backing up or flowing beyond the limits of the new pipeline extension into the existing distribution system. All valves and hydrants within the limits of the section being chlorinated shall be operated during the application of the chlorine solution. All terminal valves except the feed-in valve shall be kept closed.

On completion of the chlorination process, the feed-in valve shall be tightly shut off and the treated water retained in the line at least 24 hours or longer as may be directed by the Village. After the 24-hour retention period, the pipeline will be checked under the supervision of the Village to make sure the residual chlorine at the extremities of the section shall be not less than 25 ppm.

Following chlorination, all treated water shall be thoroughly flushed from the newly laid pipelines as directed by the Village until the replacement water has normal chlorine content and then samples for testing and analysis shall be taken from a minimum of two locations with sampling cock attached to the 1" corporation cocks in the new line. Quality of water shall meet the requirements of the Illinois Environmental Protection Agency for drinking water for at least two (2) consecutive days, with a minimum of 24 hours between samples, before placing the new pipeline or section in service. Water quality testing and sampling shall be performed by the Village.

Should the initial chlorine treatment fail the approved laboratory analysis of the sampled water, chlorination shall be repeated until approved water quality is obtained from the new pipeline extensions or sections.

If a subcontractor is used for disinfection and/or pressure testing of the new main, they must be approved by the Village prior to testing.

The cost of all labor, materials and equipment necessary to flush and chlorinate the water main shall be incidental to and included in the contract unit price for Water Main.

2.18 ABANDON EXISTING WATER MAIN
The existing water main is to be abandoned after the new main is complete and all services have been transferred. Where the existing main is disconnected from its live sources the ends shall be plugged and the main left in place. Where shown on the plans, the existing line shall be removed, a cut-in sleeve, of the appropriate size and type, shall be installed in its place. Existing valves and their frames removed and filled with backfill material as specified. This work shall be considered included in the contract. The pavement will be repaired with the Class C or D patching item as required by existing street construction or requested by the Engineer.

2.19 RELATION TO SEWERS
Insofar as applicable, the provisions set forth in paragraph 212F of the Technical Policy Statement of the Division of Public Water Supplies, Illinois Environmental Protection Agency, are made a part hereof by reference and shall be adhered to in maintaining horizontal and vertical clearances with sewers paralleling or crossing the pipelines to be installed under this contract. The following horizontal and vertical separations are to be maintained.

a) Horizontal Separation
Whenever possible, a water main must be laid at least ten feet horizontally from any existing or proposed drain or sewer line.

Should local conditions exist which would prevent a lateral separation of ten feet, a water main may be laid closer than ten feet to a storm or sanitary sewer provided that the water main invert is at least 18 inches above the crown of the sewer and is either in a separate trench or in the same trench on an undisturbed earth shelf located to one side of the sewer.

If it is impossible to obtain proper horizontal and vertical separation as described above, both the water main and sewer must be constructed of slip-on or mechanical joint cast or ductile iron pipe, pre-stressed concrete pipe or PVC pipe meeting water main standards and, before backfilling, be pressure tested to the maximum possible expected surcharge head to assure water-tightness.
b) Vertical Separation
Whenever water mains must cross house sewers, storm sewers or sanitary sewers, the water main shall be laid at such an elevation that the invert of the water main is 18 inches above the crown of the sewer measured as the normal distance between the two pipes.

The vertical separation must be maintained for that portion of the water main located within ten feet horizontally of any sewer crossed. If it is impossible to obtain the proper vertical separation as described above or if it is necessary for the water main to pass under a sewer both the water main and sewer must be constructed of slip-on or mechanical joint cast iron pipe, pre-stressed concrete pipe or PVC pipe meeting water main standards. All pipe must extend on each side of the crossing until the normal distance from the water main to the sewer is at least ten feet.

In making such crossings, center a length of water main pipe over the sewer to be crossed so the joints will be equidistant from the sewer and as remote as possible. Where a water main must cross under a sewer, a minimum vertical separation of 18 inches between the invert of the sewer and the crown of the water main shall be maintained, along with means to support the larger-sized sewer lines to prevent their settling and breaking the water main.

b) Water Service Lines
The horizontal and vertical separation between water services lines and all sanitary sewers, storm sewers or any drain must be the same as for water main, as detailed in A. and B. above, except that when minimum horizontal and vertical separation cannot be maintained, water pipe of the types described in A. and B. above must be used for both water and sewer service lines.

2.20 METHOD OF MEASUREMENT
Water main shall be measured for payment in lineal feet along the centerline of the completed water main from center to center of fittings.

2.21 BASIS OF PAYMENT
The work as outlined in Section 2 will be paid for at the contract unit price per lineal foot for WATER MAIN of the diameter and class specified, measured in place unless otherwise specified. This price shall include the cost of all materials, pipe, fittings, adapters, joint materials, blocking and all work and equipment necessary to make a complete and finished installation.

SECTION 3: WATER MAIN INSTALLED BY DIRECTIONAL DRILLING

3.1 DESCRIPTION
This work shall consist of directionally drilling a hole of sufficient size to install the proposed water main as shown on the plans or authorized by the Village.

3.2 DRILLING
A steerable system shall be used to drill a pilot bore hole through the soils in a shallow arc. The pilot hole should be stabilized by filling it with a bentonite based fluid. The pilot hole should then be enlarged by pulling back a reaming tool and carrier pipe to the drill rig location.

If an obstruction is encountered and the obstruction prevents the forward progress of the installation, the Contractor shall promptly advise the Engineer of the condition.
3.3 METHOD OF MEASUREMENT
Directional drilling shall be measured in lineal feet along the centerline and from end-to-end of completed boring.

3.4 BASIS OF PAYMENT
The work will be paid for at the contract unit price per lineal foot for WATER MAIN BY DIRECTIONAL DRILLING for water main of the size specified. This price shall include the cost of all materials, equipment and the work necessary to make a complete and finished installation.

Payment will be made only for the boring that is utilized. Inaccurate bores will be at the Contractor's expense.

If an obstruction prevents forward progress of the installation, and it is determined that extra work such as hand labor and/or special equipment will be required to remove the obstruction, and the contract does not contain a pay item for removal of obstruction, then payment for this extra work will be according to Article 9-4 of the Standard Specifications.

SECTION 4: VALVES

4.1 DESCRIPTION
This work shall consist of furnishing and installing valves of the required material, size and class together with the necessary fittings, jointing materials and blocking completed as specified herein and in conformance with the detailed plans.

4.2 MATERIALS
All materials shall conform to the current AWWA Standards as set forth below, unless otherwise specified.

(a) C-504 – Rubber-Seated Butterfly Valves.

(b) C-509 – Resilient Seated Gate Valves for Water Systems

4.3 BUTTERFLY VALVE
Butterfly valves shall be class 150 B. Valve bodies shall be either cast iron or cast steel or fabricated steel. Valve shafts shall be solid one piece 18-8 stainless steel, Type 302, 303, 304 or 316. Valves shall be 90 degree seating with valve seats of natural gum rubber compound and shall be provided with adjustable mechanical stop to prevent over travel of the valve disc in the open and closed position. Disc materials shall be as called for in the Special Provisions.

Valves shall be equipped with totally enclosed worm gear reducer and bevel gear attachment with 2" square operating nut. Operators shall be capable of seating and unseating the valves under the most adverse conditions (opening against the full design pressure and velocity as specified into a dry system downstream). Operators shall be equipped with a device to hold the valve in a fixed position for an extended period of time.

Where shown or specified on the plans, butterfly valves shall be furnished with hand wheel operators and right-hand or left-hand reducers as indicated so that the operators are in the position shown. Valves which are constructed with segmental retainers or means of adjusting the valve seat for tightness shall be installed so that such retainers or adjusting means is in the position as indicated on the drawings. All valve operators shall close the valve by turning in a clockwise direction. Valves shall be manufactured by The Henry Pratt Company or pre- approved equal.

4.4 RESILIENT SEATED GATE VALVES
All materials shall conform to the current AWWA Standard C-509, Resilient Seated Gate Valves for Water Systems. All gate valves shall be designed for a
200 psi working pressure and tested to a minimum 350 psi hydrostatic pressure. All valves shall have bronze non-rising stems with "O" ring seals. The valves shall close by turning a 2" square operating nut in a clockwise direction. All valves shall be furnished with mechanical joints. Valves shall be manufactured by Mueller or Waterous or pre-approved equal.

4.5 INSERTING VALVES
Inserting valves shall be Mueller or approved equal. The valve shall be installed under pressure, without interruption of service and consist of a two-part cast iron sleeve and valve body. Valve mechanism shall conform to AWWA Standard Specifications for Gate Valves and shall be cast iron body, resilient wedge. Valve stems shall be non-rising type with 2" square operating nut and have positive means to seal the gland. Valves shall close by turning the stem in a clockwise direction and be designed for maximum working pressure of 150 psi.

4.6 TAPPING SLEEVES AND VALVES
Tapping sleeves shall be all stainless manufactured by Cascade, Type CST-Ex or pre-approved equal and tapping valves shall be Mueller or Waterous or pre- approved equal and have mechanical joints sized for the existing pipe. Tapping valves shall conform to AWWA Standard Specification for Gate Valves, insofar as applicable, and shall be of the standard cast iron or ductile iron body, resilient wedge gate type. Valve stems shall be non-rising type with 2" square operating nut and "O" ring seal as specified. Valves shall close by turning the stems in a clockwise direction. The valve shall have an American Standard 125-pound flange on the inlet end and a standard mechanical joint hub on the outlet end. Valve seat opening shall permit full diameter cuts to be made.

4.7 AIR RELEASE VALVES
Air release valves shall be "APCO 200A" or approved equal. Valves shall be furnished with 1" threaded inlet connection and ¾" threaded outlet.

4.8 VALVE BOXES
Valve boxes shall be cast iron manufactured by Tyler, 6850 series or equal. The valve boxes shall be two piece screw type 51-71 inches or approved equal, and lid marked water or approved equal.

4.9 MAIN LINE VALVE INSTALLATION
Mechanical joint valves shall be restrained as specified in Section 2.9 and installed in the pipelines at the locations shown on the plans.

Valves shall be housed in the diameter pre-cast concrete valve vaults in accordance with the requirements shown on the plans and proposal.

4.10 VALVE VAULTS
This work shall be done in accordance with Section 6 of the Standard Specifications insofar as applicable and the following provisions. For valves 4 through 8 inch, a 48" diameter valve vault will be required.

All valve vaults shall be constructed of precast concrete sections. Adjusting rings and cast iron frames shall be sealed with butyl rope. On valve vaults containing gate valves, a concentric cone or flat slab top may be provided. The cone or top shall be placed on the vault so as to place the center of the 24" hole directly over the valve operating nut of the gate valve.

All valves shall be supported by a minimum 8" x 8" x 8" concrete brick or solid block support placed between the valve flange and the vault concrete base.

Each valve vault shall be provided with a 2' deep by 24" diameter drainage sump filled to the invert of the vault with ?" size washed stone.

Where vaults are provided with valve vaults, the valves shall be centered in the vaults. On pipelines of 8" or less in diameter, the connecting pipe nipples shall be not over 6' in length for ductile iron mains. A minimum of 12" clearance will be maintained between the floor and bottom of the pipe. Frame and covers shall be East Jordan Iron Works, Model 1550 or approved equal. Valve vault covers shall have the word "water" cast into the top surface.

4.11 ABANDON EXISTING VALVE VAULT
Abandonment of existing valve vaults shall be performed by removing and disposing of the top cone section or minimum top 2 feet of structure, filling the vault with Class CA-7 aggregate, and restoring the ground over the vault. If the existing vault is made of other materials than precast concrete, the vault walls shall be removed to a point 2 feet below the existing surface. If a valve vault exists in the parkway, the ground above the filled vault shall be filled with native material or CONTRACTOR shall furnish earth. If the valve vault is within pavement, the ground above the filled vault shall be filled with Class CA-7 aggregate to a point at the top surface.
4.12 BASIS OF PAYMENT

The cost of labor and material for installation of each valve and vault including trench backfill and frames and lids will be paid for at the contract unit price per each VALVE VAULT.

SECTION 5: FIRE HYDRANTS

5.1 DESCRIPTION
This work shall consist of furnishing and installing fir hydrants as specified herein and in conformance with the detailed plans.

5.2 MATERIALS
All fire hydrants shall conform to AWWA Standard C-502 unless otherwise specified. Hydrants shall be Waterous, Model WB-67 six-inch with 2-2½ inch nozzles, 1- 4-inch Waterous manufactured integral "Storz" nozzle, 5¼" valve opening, 1½" operating nut pentagon, open clockwise.

5.3 INSTALLATION
Fire hydrants shall be connected with the water mains by means of ductile iron or PVC pipe having an internal diameter of six (6) inches as specified by the Village. The joint at the hydrant shall be a mechanical restraint joint (Mega-Lug type) or a flanged bolted connection in conformity with the standard adopted and in use by the Village.

Each hydrant shall rest in a substantial concrete block foundation with a surface area sufficient to prevent settlement of said hydrant.

There shall be placed for a depth of at least 15 inches below the drip valve to a plan 12 inches above the drip valve, crushed stone conforming to gradation CA-3. Approximately one-third (⅓) cubic yards of crushed stone shall be placed for each hydrant. On top of said crushed stone shall be placed a sheet of 6 mil thickness VisQueen (polyethylene) to prevent infiltration of the earth backfill into the crushed stone. Hardwood or masonry blocking shall be placed between each hydrant and the undisturbed earth end of the trench to prevent the hydrant from being blown off of the connection pipe during testing and until the backfill is sufficiently compacted to serve such purposes. Each hydrant shall be set in a true vertical position and at such height so that the center of the hose or steamer connection will be 18 to 21 inches above finished grade at the hydrant or a shown on the plan. Minimum length of hydrants shall be for 6 foot depth of trench. The top of the valve box for the auxiliary hydrant valve shall be set ½ inch above finished grade of the parkway where the hydrant is located. Inspection and pressure testing of each hydrant will be made by the Village prior to backfilling.
Care shall be used where hydrant connections are to be made to be sure that the trench depth is such that the hydrant will be at the proper grade when connected to said main without the use of special offset fittings.

If hydrant extension sections are required to achieve the specified hydrant exposure, their cost shall be incidental to and include in the contract unit price for fire hydrants.

5.4 BASIS OF PAYMENT
The work as outlined in Section 7 will be paid for at the contract unit price each for FIRE HYDRANTS as specified. This price shall include the cost of fittings, joint materials, blocking, drainage bed and all materials, work and equipment necessary to make a complete and finished installation.

Six-inch auxiliary gate valves and cast iron boxes are required for all hydrants, the cost for furnishing and installing same shall be incidental to and included in the contract unit price for fire hydrants. Auxiliary gate valves and cast iron valve boxes shall be in accordance with Section 6 of this Supplemental Specifications, insofar as applicable.

Hydrant leads shall be paid for at the contract unit price for 6" water main of the class specified.

5.5 REMOVE EXISTING FIRE HYDRANTS
This work shall consist of the removal of existing fire hydrants, as shown on the plans, along with all associated hardware such as auxiliary valves, valve vaults or boxes, pipe and fittings necessary to completely eliminate the appurtenance from the water main.

This work shall be paid for at the contract unit price per each REMOVE EXISTING FIRE HYDRANT, which price shall include the cost of all labor and materials required to complete this item.

SECTION 6: COPPER WATER SERVICE STUBS

6.1 DESCRIPTION
This work shall consist of furnishing and installing copper water tubing, corporation stops, curb stops and curb boxes of the size specified and in conformance with the detailed plans.

6.2 MATERIALS
All materials shall conform to the following standards unless so otherwise specified.

a) Copper Water Tubing, Type K, AWWA Specifications 7S-CR

Nominal Pipe Size	Outside Diameter	Weight Per Foot
¾"	0.875"	0.641#
1"	1.125"	0.839#
1¼"	1.375"	1.040#
1½"	1.625"	1.360#
2"	2.125"	2.060#

b) Corporation stops shall be Mueller B-25000 with 90 degree bend coupling.

c) Curb stops shall be Mueller #H-15154 Mark II Orlseal inverted key, round way.

d) Curb boxes shall be Mueller adjustable cast iron type; Mueller #H-10302 for 1" through 1¼" curb stops, and Mueller #H-10304 for 1½" and 2" curb stops.

e) Terminal markers, 2" x 2" post 4' long with white painted top.

6.3 INSTALLATION
Copper services shall be installed by directional bore or in open cut trenches minimum 5 feet below the centerline elevation of the proposed roadway and shall extend at right angles from the street main to the terminal point. Maximum trench width for installation of the copper services shall be 24 inches.

All taps shall be made after completion of the hydrostatic test and disinfection of the water main and shall be at an angle of 90 degrees above the horizontal diameter of the water main. All 1" and 1" taps to be made on ductile iron main shall be tapped directly into the main (no saddles). Taps larger than 1" made on ductile iron main shall be nylon coated Smith Blair Type 317 or pre-approved equal. All taps made on PVC main shall be Smith Blair Type 325 tapping saddles.
From the connection with the corporation stop, the service line shall be bent in a manner to form a curve from the top of the stop to the bottom of the service trench and in a manner to provide a reasonable amount of slack or extra length in the service line. The corporation stop and service shall then be blocked up in a manner to relieved all stress in the connection with the water main. No splicing of the water service beneath the roadway will be allowed. All copper connections shall be flared. The minimum separation between taps shall be 12 inches.

A cast iron adjustable curb box shall be screwed on and set vertically over the curb stop at the terminal end of each service with the cover of said box set flush with the finished surface. Next to the cast iron box shall be set a 4' long 2" x 2" post with one foot painted white and exposed above the ground.

6.4 REPLACE WATER SERVICE LINE
The water service line size shall be 1 ½ inch diameter from the corporation stop on the new main to a minimum of 6" beyond existing water service box, and shall include new 1 ½ inch curb stop and box and connection to the existing service.

This work shall be paid for at the contract unit price per each, for NEAR SIDE WATER SERVICE or FAR SIDE WATER SERVICE, which price shall include the cost of all labor, materials, and equipment necessary to complete this item.

6.5 CONNECT EXISTING 1 ½ INCH OR 2 INCH COPPER WATER SERVICE LINE
This item shall be in accordance with the requirements of Section 8 of the Supplemental Specifications, with the following addition:

The water service shall be connected to the new corporation stop on the new main at the location shown on the plans. This work shall be included in the price for each NEAR SIDE WATER SERVICE or FAR SIDE WATER SERVICE.

Corporation Stops shall be in accordance with Section 8 of the Supplemental Specifications with the following addition. No size shall be specified. Each stop shall be 1 ½ or 2 inch size to match the line being replaced or connected.

Curb stops and boxes; this item shall be in accordance with Section 8 of the Supplemental Specifications.

All work in connection with the house water services shall conform to the ordinances and regulation of the Village.

6.6 RECORD OF LOCATIONS
The Contractor shall reference and provide an accurate record of the location of the service tap, box location and service size. Complete record shall be given to the Engineer upon completion of the work.

6.7 METHOD OF MEASUREMENT
House water services shall be measured for payment by each complete replacement of water service line from the point of connection with the main to the curb stop.

6.8 BASIS OF PAYMENT
The work as outlined in Section 8 will be paid for at the contract unit price per each for NEAR SIDE WATER SERVICE or FAR SIDE WATER SERVICE. These prices shall include the cost of all copper tubing, fittings, corporation stop, curb stop, cast iron curb box, service saddles, if necessary, tapping, blocking and all materials, work and equipment necessary to make a complete and finished installation.

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 ig@gconsulting.net

1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS


GLENCOE WATER MAIN SPECIFICATIONS

DESIGN: K.C.L. | DRAFTING: S.R.M
SCALE: NONE | DATE: 10/28/19
FIRM NO.: 184-001330

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\Gb\18GB\Xls\18GB18SPEC.xlsm 18557SP.dwg


PROJECT No. 18557



NOTES:
1) GEOTEXTILE FILTER FABRIC SHALL BE PLACED OVER THE CLEARED AREA PRIOR TO PLACING COARSE AGGREGATE.
2) COARSE AGGREGATE (OR CRUSHED CONCRETE) SHALL MEET IDOT GRADATION FOR CA-1 CRUSHED AGGREGATE.
3) STABILIZED CONSTRUCTION ENTRANCE SHALL BE INSTALLED, PRIOR TO ONSET OF CONSTRUCTION OPERATIONS AND SHALL BE MAINTAINED THROUGH THE PROJECT.
4) CONSTRUCTION ENTRANCE SHALL BE REMOVED UPON COMPLETION OF CONSTRUCTION AND ONLY WHEN DIRECTED BY VILLAGE ENGINEER.


* OR TO BUILDING LINE

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
CONSTRUCTION ENTRANCE	SHEET 1 OF 1
	NOT TO SCALE



* IF THE BUILDING IS MULTI-LEVEL OR HAS A STEP FOUNDATION, SHOW PROPOSED TOP OF FOUNDATION AND FINISHED GRADE AT ALL LEVELS.


ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
LOT GRADING	SHEET 1 OF 1
	NOT TO SCALE




NOTES:
WITH TRENCH
1) FILTER BARRIERS SHALL BE PLACED AT THOSE LOCATIONS SHOWN ON THE PLANS INCLUDING STOCK PILE AREAS AND WERE INDICATED BY THE ENGINEERING DIVISION.
2) ATTACH FABRIC TO WIRE MESH WITH HOG RINGS, TO WOOD POSTS WITH NAILS, AND TO STEEL POSTS WITH TIE-WIRES AT TOP AND MID-SECTION.
3) OVERLAP FILTER FABRIC BY 6" AND FOLD AROUND EACH POST ONE FULL TURN WHERE 2 SECTIONS ADJOIN.
4) DRIVE POSTS TIGHTLY TOGETHER AND SECURE TOPS OF POSTS BY TYING OFF WITH CORD OR WIRE TO PREVENT FLOW-THROUGH OF BUILD-UP SEDIMENT AT JOINT.
5) INSPECTION OF SILT FENCES SHALL BE AT LEAST ONE PER WEEK AND AFTER RAIN EVENTS IN EXCESS OF ½". REPAIR OF REPLACEMENT SHALL BE MADE PROMPTLY AS NEEDED.
6) SEDIMENT TRAPPED BY THE FENCE SHALL BE REMOVED (AND PROMPTLY DISPOSED OF) WHENEVER SIGNIFICANT ACCUMULATION OCCURS.
7) BARRIERS SHALL BE MAINTAINED IN PLACE UNTIL COMPLETION OF CONSTRUCTION AND THE UPSLOPE AREA HAS BEEN STABILIZED, AND SHALL BE REMOVED ONLY WHEN DIRECTED BY THE VILLAGE ENGINEER.

WITHOUT TRENCH
1) TOE-IN CAN ALSO BE ACCOMPLISHED BY LAYING THE FABRIC FLAP ON UNTRENCHED GROUND AND PILING AND TAMPING SOIL OVER FLAP AT THE BASE OF STRUCTURE.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SILT FENCE	SHEET 1 OF 1
	NOT TO SCALE




ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SWALE	SHEET 1 OF 1
	NOT TO SCALE




NOTES:
1) FOR PROPOSED STORM SEWER SERVICE ≤ 6", CORE THE PIPE AND USE A BOOT CONNECTION.
2) FOR PROPOSED STORM SEWER SERVICE ≥ 8", A MANHOLE MUST BE INSTALLED.
3) FOR CONNECTING SANITARY SERVICE TO AN EXISTING SANITARY SEWER ≤ 12", REMOVE A SECTION OF PIPE AND INSTALL A TEE OR WYE CONNECTION.
4) FOR CONNECTING SANITARY SEWER SERVICE TO AN EXISTING SANITARY SEWER ≥ 15", CIRCULAR SAW-CUT AND USE A HUB WYE OR TEE SADDLE CONNECTION.
5) FOR PROPOSED STORM OR SANITARY SEWER SERVICES, ENCASE ALL CONNECTIONS IN LOW STRENGTH CONCRETE TO PREVENT THE FITTINGS FROM ROTATING.
6) FOR TRENCHES WITHIN AN EXISTING PAVED SURFACE AREA, FLOWABLE FILL BACKFILL MEETING IDOT'S SPECIFICATIONS CONTROLLED LOW STRENGTH MATERIAL (CLSM) MIX 1 SHALL BE USED.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SANITARY & STORM SERVICE DETAIL	SHEET 1 OF 1
	NOT TO SCALE




MOUNTABLE CURB

COMBINATION CONCRETE CURB AND GUTTER



NOTES:
1) CORE-DRILL CIRCULAR OPENING IN STRUCTURE WALL OF DIAMETER TO FIT THE REQUIRED BOOT SIZE.
2) KOR-N SEAL FLEXIBLE RUBBER BOOT (MANUFACTURED BY NATIONAL POLLUTION CONTROL SYSTEMS, INC. OR AS APPROVED BY VILLAGE ENGINEER SHALL BE USED FOR WATERTIGHT CONNECTION.
3) CUT, SHAPE AND SLOPE NEW INVERT CHANNEL IN THE EXISTING CONCRETE BENCH FOR SMOOTH FLOW FROM NEW CONNECTION.
4) CLEAN EXISTING STRUCTURE AND SEWER PIPE OF ANY DIRT, CONCRETE OR DEBRIS WHICH MAY ACCUMULATE DURING THE CONSTRUCTION PROCESS.


ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PIPE CONNECTION TO STRUCTURE	SHEET 1 OF 1
	NOT TO SCALE



NOTES:
1) MANHOLES MUST CONFORM TO ASTM C-478.
2) MANHOLE SECTIONS TO BE TONGUE AND GROOVED.
3) BENCHES MUST BE PROVIDED IN ALL STORM SEWER MANHOLES.
4) ALL PIPE PENETRATIONS OCCURRING WITHIN (OR BELOW) GROUNDWATER TABLE AND ALL NON-PRECAST OPENINGS SHALL BE CORED, RUBBER BOOTED, AND INTERIOR MORTARED AROUND PIPE. SEE PIPE CONNECTION TO STRUCTURE DETAIL.
5) MASTIC SEALANT OR RUBBER GASKET SEAL MUST BE APPLIED BETWEEN CONCRETE & FLANGE OF FRAME BEFORE LID BOLTS ARE TIGHTENED.
6) INSTALL EXTERNAL CHIMNEY SEAL.


PIPE SIZE (IN.)	DIAMETER "D" (FT.)	THICKNESS "T" (IN.)
12-18	4	4
21-36	5	5
39-60	6	6

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SANITARY MANHOLE	SHEET 1 OF 1
	NOT TO SCALE




NOTE:
THE REQUIRED MANHOLE FRAME AND GRATE ADJUSTMENTS, INCLUDING POURING OF CONCRETE APRON, SHALL BE PERFORMED BEFORE PLACING HOT-MIX ASPHALT SURFACE COURSE.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
STRUCTURE FRAME & GRATE ADJUSTMENT	SHEET 1 OF 1
	NOT TO SCALE




NOTES:
1) MANHOLES MUST CONFORM TO ASTM C-478.
2) MANHOLE SECTIONS TO BE TONGUE AND GROOVED.
3) BENCHES MUST BE PROVIDED IN ALL STORM SEWER MANHOLES.
4) ALL PIPE PENETRATIONS OCCURRING WITHIN (OR BELOW) GROUNDWATER TABLE AND ALL NON-PRECAST OPENINGS SHALL BE CORED, RUBBER BOOTED, AND INTERIOR MORTARED AROUND PIPE. SEE PIPE CONNECTION TO STRUCTURE DETAIL.
5) MASTIC SEALANT OR RUBBER GASKET SEAL MUST BE APPLIED BETWEEN CONCRETE & FLANGE OF FRAME BEFORE LID BOLTS ARE TIGHTENED.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
STORM MANHOLE	SHEET 1 OF 1
	NOT TO SCALE




NOTES:
1) FRAME: TOP FLANGE FABRICATED FROM ¼" FLAT STOCK. BASE RIM FABRICATED FROM 1 ½" X 1½" X ⅛" CHANNEL. ALL STEEL CONFORMING TO ASTM-A36.
2) SEDIMENT BAG: BAG FABRICATED FROM 4 OZ./ SQ.YD. NON-WOVEN POLYPROPYLENE GEOTEXTILE REINFORCED WITH POLYESTER MESH. BAG SECURED TO BASE RIM WITH A STAIN-LESS STEEL STRAP AND LOCK.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
FILTER FOR BEEHIVE (TYPE 8) GRATE & FRAME	SHEET 1 OF 1
	NOT TO SCALE




NOTES:
1) FRAME: TOP FLANGE FABRICATED 1½"x1½"x⅛" ANGLE, BASE RIM FABRICATED FROM 1½"x2"x⅛" CHANNEL. HANDLES AND SUSPENSION BRACKETS FABRICATED FROM 1½"x⅛" FLAT STOCK. ALL STEEL CONFORMING TO ASTM-A36.
2) SEDIMENT BAG: BAG FABRICATED FROM 4 OZ./ SQ.YD. NON-WOVEN POLYPROPYLENE GEOTEXTILE REINFORCED WITH POLYESTER MESH. BAG SECURED TO BASE RIM WITH A STAIN-LESS STEEL STRAP AND LOCK.
3) FILTER FOR OTHER SHAPE GRATES SHALL BE APPROVED IN ADVANCE OF PLACEMENT BY THE VILLAGE ENGINEER.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
FILTER FOR ROUND OPEN (TYPE 1) GRATE & FRAME	SHEET 1 OF 1
	NOT TO SCALE



NOTES:
1) INLET MUST CONFORM TO ASTM C-478.
2) NON-PRECAST OPENINGS SHALL BE CORED, RUBBED BOOTED, AND INTERIOR MORTARED AROUND PIPE. SEE PIPE CONNECTION TO STRUCTURE DETAIL.
3) MAXIMUM DEPTH FROM INVERT OF OUTLET PIPE TO TOP OF FRAME SHALL NOT EXCEED 42 INCHES. IF DESIGN OR CONSTRUCTION REQUIRES DEPTH BEYOND 42 INCHES, STRUCTURE SHALL BE REVISED TO A 48 INCH DIAMETER MANHOLE.
4) BENCHES MUST BE PROVIDED IN ALL INLETS.


ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
INLET TYPE "C"	SHEET 1 OF 1
	NOT TO SCALE



NOTES:
1) MANHOLES MUST CONFORM TO ASTM C-478.
2) MANHOLE SECTIONS TO BE TONGUE AND GROOVED.
3) NON-PRECAST OPENINGS SHALL BE CORED AND RUBBER BOOTED. *
4) MORTAR ALL PIPE PENETRATIONS INSIDE AND OUTSIDE OF STRUCTURE.
5) ALL PIPE PENETRATIONS TO BE CORED, RUBBER BOOTED AND INTERIOR MORTARED. *

* SEE SEWER CONNECTION TO EXISTING MANHOLE DETAIL.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
STORM CATCH BASIN DETAIL TYPE "A" AND TYPE "B"	SHEET 1 OF 1
	NOT TO SCALE



NOTES:
1) CATCH BASIN TO BE CONSTRUCTED OF PRECAST REINFORCED CONCRETE.
2) CATCH BASIN MUST CONFORM TO ASTM C-478.
3) ALL PIPE PENETRATIONS TO BE CORED, RUBBER BOOTED AND INTERIOR MORTARED.
4) MAXIMUM DEPTH FROM INVERT OF OUTLET PIPE TO TOP OF FRAME SHALL NOT EXCEED 42 INCHES. IF DESIGN OR CONSTRUCTION REQUIRES DEPTH BEYOND 42 INCHES, STRUCTURE SHALL BE REVISED TO A 48 INCH DIAMETER TYPE "A" CATCH BASIN.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
STORM CATCH BASIN DETAIL TYPE "C"	SHEET 1 OF 1
	NOT TO SCALE

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

CONSTRUCTION STANDARDS | DESIGN: K.C.L. | DRAFTING: S.R.M | SCALE: NONE | DATE: 10/28/19


FIRM NO. 184-001330

1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED @ IG CONSULTING, INC.


G:\IG\Jobs\18557\Drawings\18557DT.dwg

PROJECT No. 18557



NOTES:
1) ALL MAINS TO HAVE MINIMUM 5'-6" COVER.
2) ALL HYDRANTS TO FACE STREET.
3) DO NOT OBSTRUCT DRAIN HOLES


	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	FIRE HYDRANT DETAIL	SHEET 1 OF 1
		NOT TO SCALE



NOTES:
1) 60" (MIN.) INSIDE DIAMETER FOR ALL PRESSURE CONNECTION VALVES.
2) BACKFILL MATERIAL SHALL BE IDOT CA-7 STONE.
3) TAPPING SLEEVE SHALL BE MUELLER STAINLESS STEEL H-304.
4) BOLTS FOR FITTINGS
   4)1. MECHANICAL JOINT BOLTS & NUTS SHALL BE COMPOSED OF "COR-TEN".
   4)2. ALL OTHER HEXAGONAL BOLTS & NUTS SHALL BE COMPOSED OF STAINLESS STEEL.
5) VALVE VAULT MUST CONFORM TO ASTM C-478.
6) ALL SECTIONS TO BE TONGUE AND GROOVED.
7) NON-PRECAST OPENINGS SHALL BE CORED AND RUBBER BOOTED.*


*SEE PIPE CONNECTIONS TO STRUCTURE DETAIL.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	PRESSURE CONNECTION	SHEET 1 OF 1
		NOT TO SCALE




NOTES:
1) ALL BACKFULL MATERIALS SHALL BE PROPERLY COMPACTED.
2) ALL TRENCH EXCAVATIONS SHALL MEET OSHA REQUIREMENTS.
3) BEDDING MATERIAL FOR PVC PIPE INSTALLATION SHALL COMPLY WITH ASTM D-2321.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	TRENCH DETAIL FOR NON-PAVED AREAS	SHEET 1 OF 1
		NOT TO SCALE



1) TRENCH BACKFILL UNDER A PACED SURFACE OR WITHIN THE ZONE OF INFLUENCE (3' FROM EDGE OF PAVEMENT) SHALL CONSIST OF IDOT CA-7, NO FINES, CRUSHED STONE, GRAVEL, OR CRUSHED GRAVEL. CRUSHED CONCRETE IS NOT ALLOWED.
2) ALL MATERIALS SHALL BE PROPERLY COMPACTED PER SPECIFICATIONS.
3) ALL TRENCH EXCAVATIONS SHALL MEET OSHA REQUIREMENTS.
4) BEDDING MATERIAL FOR PVC PIPE INSTALLATION SHALL COMPLY WITH MWRD STANDARDS, CA11 AND CA13.
5) THE PLACEMENT OF PAVEMENTS SHALL NOT BE ALLOWED WITHOUT PRIOR INSPECTION BY VILLAGE ENGINEERING.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	TRENCH DETAIL FOR PAVED AREAS	SHEET 1 OF 1
		NOT TO SCALE



NOTES:
1) PIPE OPENINGS CAST INTO WALL.
2) PRECAST SECTIONS TO BE JOINTED WITH TONGUE AND GROOVE JOINTS SEALED WITH MASTIC TYPE BITUMINOUS JOINTING COMPOUND.
3) 4' DIA. STRUCTURES FOR UP TO 8" VALVES, 5' DIA. STRUCTURES FOR 10" VALVES AND ABOVE.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	VALVE VAULT DETAIL	SHEET 1 OF 1
		NOT TO SCALE

PROPOSED WATER MAIN ABOVE EXISTING SEWER LINE
WITH 18" MINIMUM VERTICAL SEPARATION

NOTES:
1) OMIT SELECT GRANULAR CRADLE AND GRANULAR BACKFILL TO ONE (1) FOOT OVER TOP OF PIPE AND USE SELECT EXCAVATED MATERIAL (CLASS IV) AND COMPACT FOR 10' ON EITHER SIDE OF SEWER LINE.
2) IF SELECT GRANULAR BACKFILL EXISTS, REMOVE WITHIN WIDTH OF EXISTING SEWER LINE TRENCH AND REPLACE WITH SELECT EXCAVATED MATERIAL (CLASS IV) AND COMPACT.
3) CLASS IV MATERIAL SHALL BE COMPACTED TO 95% OF STANDARD PROCTOR MAXIMUM DENSITY.
4) CONSTRUCT "L" FEET OF PROPOSED SEWER OF WATER MAIN MATERIAL AND PRESSURE TEST, OR USE "L" FEET OF WATER MAIN MATERIAL FOR CASING OF PROPOSED SEWER AND SEAL ENDS OF CASING.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER AND SEWER SEPARATION	SHEET 1 OF 5
		NOT TO SCALE

PROPOSED SEWER LINE BELOW EXISTING WATER MAIN
WITH LESS THAN 18" MINIMUM VERTICAL SEPARATION

NOTES:
1) OMIT SELECT GRANULAR CRADLE AND GRANULAR BACKFILL TO ONE (1) FOOT OVER TOP OF PIPE AND USE SELECT EXCAVATED MATERIAL (CLASS IV) AND COMPACT FOR 10' MIN. ON EITHER SIDE OF SEWER LINE.
2) IF SELECT GRANULAR BACKFILL EXISTS, REMOVE WITHIN WIDTH OF EXISTING SEWER LINE TRENCH AND REPLACE WITH SELECT EXCAVATED MATERIAL (CLASS IV) AND COMPACT.
3) CLASS IV MATERIAL SHALL BE COMPACTED TO 95% OF STANDARD PROCTOR MAXIMUM DENSITY.
4) CONSTRUCT "L" FEET OF PROPOSED SEWER OF WATER MAIN MATERIAL AND PRESSURE TEST, OR USE "L" FEET OF WATER MAIN MATERIAL FOR CASING OF PROPOSED SEWER AND SEAL ENDS OF CASING.
5) PROVIDE ADEQUATE SUPPORT FOR EXISTING WATER MAIN TO PREVENT DAMAGE DUE TO SETTLEMENT OF SEWER TRENCH.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER AND SEWER SEPARATION	SHEET 2 OF 5
		NOT TO SCALE

PROPOSED WATER MAIN ABOVE EXISTING SEWER LINE WITH
LESS THAN 18" MINIMUM VERTICAL SEPARATION

NOTES:
1) OMIT SELECT GRANULAR CRADLE AND GRANULAR BACKFILL TO ONE (1) FOOT OVER TOP OF PIPE AND USE SELECT EXCAVATED MATERIAL (CLASS IV) AND COMPACT FOR 10' ON EITHER SIDE OF SEWER LINE.
2) IF SELECT GRANULAR BACKFILL EXISTS, REMOVE WITHIN WIDTH OF EXISTING SEWER LINE TRENCH AND REPLACE WITH SELECT EXCAVATED MATERIAL (CLASS IV) AND COMPACT.
3) USE CASING FOR PROPOSED WATER MAIN AND SEAL ENDS OF CASING.
4) POINT LOADS SHALL NOT BE ALLOWED BETWEEN WATER MAIN OR WATER MAIN CASING AND SEWER.
5) CLASS IV MATERIAL SHALL BE COMPACTED TO 95% OF STANDARD PROCTOR MAXIMUM DENSITY.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER AND SEWER SEPARATION	SHEET 3 OF 5
		NOT TO SCALE

PROPOSED WATER MAIN BELOW EXISTING SEWER LINE
WITH 18" MINIMUM VERTICAL SEPARATION

NOTES:
1) PROVIDE ADEQUATE SUPPORT FOR EXISTING SEWER LINE TO PREVENT DAMAGE DUE TO SETTLEMENT OF TRENCH.
2) MAINTAIN 18" MINIMUM VERTICAL SEPARATION FOR 10' HORIZONTALLY.
3) USE CASING FOR PROPOSED WATER MAIN AND SEAL ENDS OF CASING. THE CASING PIPE MUST BE A MATERIAL THAT IS APPROVED FOR USE AS WATER MAIN.
4) POINT LOADS SHALL NOT BE ALLOWED BETWEEN WATER MAIN OR WATER MAIN CASING AND SEWER.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER AND SEWER SEPARATION	SHEET 4 OF 5
		NOT TO SCALE

PROPOSED WATER MAIN BELOW EXISTING SEWER LINE
WITH LESS THAN 18" MINIMUM VERTICAL SEPARATION

NOT ALLOWED
MUST MAINTAIN 18" OF VERTICAL SEPARATION

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER AND SEWER SEPARATION	SHEET 5 OF 5
		NOT TO SCALE

NOTES:
1) MAKE EXCAVATION FOR PIPE BELL SO THAT ALL LOADS ARE CARRIED BY PIPE BARREL ONLY.
2) WHERE BOTTOM OF TRENCH IS NOT STABLE, LARGE SIZE CRUSHED STONE OR GRAVEL AS APPROVED BY THE ENGINEER SHALL BE PROVIDED.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER MAIN TRENCH DETAIL	SHEET 1 OF 1
		NOT TO SCALE

NOTES:
1) SERVICE PIPE TO BE WEAVED IN TRENCH TO ALLOW AT LEAST ONE (1) FOOT EXTRA LENGTH IN ITS LENGTH.
2) UPON COMPLETION OF WATER SERVICE CONSTRUCTION ALL BOXES ARE TO BE EXTENDED AND LEFT PROTRUDING 12" ABOVE THE PROPOSED GRADE.
3) SERVICE TAP TO EE MADE AT 45° TO TOP VERTICAL CENTER LINE OF WATER MAIN.
4) GRANULAR BACKFILL TO BE PLACED UNDER PAVEMENT AS SPECIFIED
5) COMPACT ALL TRENCHES.

	ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
	WATER SERVICE DETAIL	SHEET 1 OF 1
		NOT TO SCALE

INLET PROTECTION - PAVED AREAS
DROP-IN PROTECTION

REFERENCE		STANDARD DWG. NO.
Project _____		ILM-5610
Designed _____ Date _____		SHEET 1 OF 1
Checked _____ Date _____		DATE 05-03-13
Approved _____ Date _____		

INLET PROTECTION
LOG TYPE

NOT-TO SCALE

SECTION

NOTES:
0.5 Fence shall be used in combination with drop in filter for inlet protection.
1. 2" x 2" nominal hardwood stakes, 4 foot minimum length, driven into ground approximately 18 inches, stakes driven a minimum width of 12 inches away from the drop inlet.
2. Area inside the log, from edge of fabric to structure, must be stabilized with Erosion Control Blanket, Turf Reinforcement Mat, Geotextile 592 Table 2 Class 2 or CA-7 stone
3. The maximum distance between the stakes should be 4 feet.
4. A maintenance schedule must maintain a sediment accumulation of less than 50% of the height of the log.

REFERENCE		STANDARD DWG. NO.
Project _____		ILM-562
Designed _____ Date _____		SHEET 1 OF 1
Checked _____ Date _____		DATE 11-26-13
Approved _____ Date _____		

INLET PROTECTION MONOFILAMENT FABRIC
BARRIER FENCE

SECTION

NOTES:
1. 2 x 2 nominal hardwood stakes, 4 foot minimum length, driven into ground approximately 18 inches, stakes driven a minimum width of 12 inches away from the drop inlet.
2. Area inside the fence, from edge of fabric to structure, must be stabilized with Erosion Control Blanket, Turf Reinforcement Mat, Geotextile 592 Table 2 Class 2 or CA-7 stone
3. Maximum height of the fabric above the crest of the drop inlet shall be 32". Place the bottom 8 inches of the fabric in a trench and backfill with 6 inches of 95% compacted soil.
4. Stakes must be a maximum of 4 feet apart.
5. A maintenance schedule must maintain a sediment accumulation of less than 50% of the height of the monofilment fabric.
6. Monofilment fabric shall meet the requirement of Material Specification 592 Geotextile Table 1, Class 4.
7. Monofilment fabric shall be secured to each 2" x 2" nominal hardwood stake with a minimum of 4 steel staple fasteners and wood lath. Wood lath shall be a minimum length of 10 inches. Wire fasteners should be used if metal T-Posts are installed in place of hardwood stakes.

REFERENCE		STANDARD DWG. NO.
Project		ILM-531
Designed	Date	SHEET 1 OF 1
Checked	Date	DATE 04-4-13
Approved	Date	

REVISIONS		
DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/19	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

CONSTRUCTION STANDARDS | DESIGN: K.C.L. | DRAFTING: S.R.M | SCALE: NONE | DATE: 10/28/19

FIRM NO. 184-001330


1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\Jobs\18xxx\18557\DT\dwg\18557DT.dwg

PROJECT No. 18557


SQUARES MARKED FOR REMOVAL



NOTE:
RESTORATION IS INCIDENTAL TO CONTRACTORS COST AND DISTURBED AREAS SHOULD BE LIMITED TO AN 18" WIDE STRIP.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 1 OF 9
	NOT TO SCALE


CONTRACTOR DAMAGED ADJACENT SQUARE



NOTES:
1) SAW-CUT AND REMOVE UP TO HALF OF A FOOT TOTAL LARGER WHEN CHIPPED BY CONTRACTOR AT CONTRACTORS COST.
2) REPLACE ADJACENT SQUARE WHEN OVER HALF OF A FOOT LARGER AT CONTRACTORS COST.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 2 OF 9
	NOT TO SCALE


SAFETY



NOTES:
1) LIGHTED TYPE II BARRICADES MUST BE INSTALLED IMMEDIATELY AFTER A BLOCK IS REMOVED.
2) IT IS THE CONTRACTORS RESPONSIBILITY TO KEEP ALL WORKSITES SAFELY BARRICADED AND CLEAN.
3) ALL BARRICADES MUST BE CLEAN, IN GOOD CONDITION, AND LIGHTS MUST BE OPERABLE.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 3 OF 9
	NOT TO SCALE


SITE PREPARATION



NOTES:
1) FORMS SHOULD BE SET TO ENSURE PROPER DRAINAGE AND SAFE SLOPES.
2) FELT EXPANSION JOINT MATERIAL SHALL BE USED AS PRESCRIBED.
3) SIDEWALK SHALL BE PLACED ON LEVEL COURSE OF GRAVEL. THICKNESS MUST BE MAINTAINED.
4) BACKFILL AND RESTORATION SHOULD BE DONE WITHIN 24 HOURS OF POURING CONCRETE. ALL RESTORED AREAS MUST HAVE MOWABLE SLOPES.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 4 OF 9
	NOT TO SCALE


DRIVEWAY SQUARES



NOTES:
1) USE CAUTION WHEN REMOVING SQUARES ADJACENT TO DRIVEWAYS OR OTHER PRIVATE IMPROVEMENTS.
2) MAKE SURE NO VEHICLES WILL BE TRAPPED IF SQUARE IS REMOVED.
3) ATTEMPT TO CONTACT RESIDENT BEFORE REMOVAL.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 5 OF 9
	NOT TO SCALE


ADJACENT SQUARES WITH EXISTING DAMAGE



NOTE:
NOTIFY INSPECTOR OF ALL UNMARKED EXISTING DAMAGE BEFORE PROCEEDING WITH ANY SAW-CUTTING OR REMOVALS.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 6 OF 9
	NOT TO SCALE


ROOTS AND FEATURES



NOTES:
1) APPARENT PLANTINGS, BRICKS, SPRINKLERS, OR OTHER FEATURES IN OR ADJACENT TO THE RIGHT OF WAY SHALL BE PROTECTED FROM DAMAGE OR RESTORED IN KIND.
2) TREE ROOTS OVER 3" SHALL BE CUT OR GROUND UNLESS APPROVED BY THE VILLAGE. SMALLER ROOTS SHALL BE CLEAN CUT OR GROUND.
3) DO NOT DAMAGE OVERHEAD BRANCHES.


ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 7 OF 9
	NOT TO SCALE

UTILITIES



NOTE:
CONTRACTOR SHALL CONTACT J.U.L.I.E. AT 811
CONTRACTOR SHALL NOTIFY THE VILLAGE OF ANY DAMAGE.


ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 8 OF 9
	NOT TO SCALE



CONTRACTION JOINT DETAIL EXPANSION JOINT DETAIL

NOTES:
1) UNLESS OTHERWISE NOTED ON PLANS, CONTRACTION JOINTS TO BE AT 5'-0"
2) EXPANSION JOINTS TO BE 50'-0" O.C. MAX. OR AT BACK OF CURB, CHANGE OF DIRECTION, OTHER WALK, UTILITY APPURTENANCE, OR FACE OF STRUCTURE.
3) PORTLAND CEMENT CONCRETE SHALL CONFORM TO IDOT CLASS SI, MIN. 3,500 PSI (6.1 BAG MIX) AT 14 DAYS, WITH 5% TO 8% AIR ENTRAINMENT. (FLY ASH NOT ALLOWED).
4) A PROTECTIVE COAT OR CONCRETE SEALER WILL BE APPLIED TO ALL NEW CONCRETE SIDEWALKS AND CURB AND GUTTERS IN ACCORDANCE WITH SECTION 420 OF THE IDOT STANDARD SPECIFICATIONS.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
SIDEWALK SQUARE DETAILS	SHEET 9 OF 9
	NOT TO SCALE




TURN DOWN EDGE SIDEWALK

N.T.S.


NOTE: PROVIDE CONTROL JOINTS AT 5' O.C. AND EXPANSION JOINTS AT 25' O.C.

PVMT39

RAMPS IN LANDSCAPED AREA
SETBACK ≤ 5'




RAMPS IN PAVED AREA
SETBACK ≤ 5'




ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PERPENDICULAR CURB RAMPS FOR SIDEWALKS	SHEET 1 OF 4
	NOT TO SCALE

SECTION A-A




SECTION B-B




NOTE:
THE RUNNING SLOPE OF THE CURB RAMP SHALL NOT REQUIRE THE RAMP LENGTH TO EXCEED 15'.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PERPENDICULAR CURB RAMPS FOR SIDEWALKS	SHEET 2 OF 4
	NOT TO SCALE

RAMPS IN LANDSCAPED AREA
SETBACK > 5'




RAMPS IN PAVED AREA
SETBACK > 5'




NOTES:
1) THE RUNNING SLOPE OF THE CURB RAMP SHALL NOT REQUIRE THE RAMP LENGTH TO EXCEED 15'.
2) TURNING SPACE NOT REQUIRED FOR RAMP SLOPES FLATTER THAN 1:20.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PERPENDICULAR CURB RAMPS FOR SIDEWALKS	SHEET 3 OF 4
	NOT TO SCALE

SECTION C-C




ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PERPENDICULAR CURB RAMPS FOR SIDEWALKS	SHEET 4 OF 4
	NOT TO SCALE



NOTES:
1) THE PURPOSE OF TREE PROTECTION FENCING IS TO MINIMIZE CONSTRUCTION ACTIVITIES WITHIN CRITICAL ROOT ZONES OF EXISTING TREES TO REMAIN.
2) CRITICAL ROOT ZONES SHALL BE PROTECTED WITH WELDED WIRE FENCING (CHAIN LINK), 6' HIGH WITH STEEL OR WOODEN POSTS INSTALLED AND SPACED NOT MORE THAN 8' APART.
3) PROTECTIVE TREE FENCING MUST EXTEND TO THE DRIP LINE OF THE TREE (WHICH CAN BE ESTIMATED AT 1 FOOT FOR EVERY 1 INCH OF DBH) BUT IN NO CASE SHALL FENCING BE:
   LESS OF A RADIUS OF 10' FROM TREES UP TO 18" DBH
   LESS OF A RADIUS OF 15' FROM TREES 18" DBH OR LARGER
4) PROTECTIVE TREE FENCING MUST REMAIN INTACT FOR THE ENTIRE DURATION OF THE CONSTRUCTION PROJECT AND MAY NOT BE MOVED OR REMOVED FOR ANY REASON WITHOUT VILLAGE APPROVAL ONLY.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PROTECTIVE TREE FENCING	SHEET 1 OF 1
	NOT TO SCALE



NOTES:
1) THE PURPOSE OF ROOT PRUNING IS TO MAXIMIZE TREE HEALTH FOR TREES WHICH MAY BE IMPACTED BY CONSTRUCTION EQUIPMENT.
2) ROOT PRUNING MUST BE PERFORMED BY A CERTIFIED ARBORIST WITH AT LEAST 5 YEARS EXPERIENCE.
3) ROOT PRUNING MUST BE PERFORMED AS FAR FROM THE PROTECTED TREE AS POSSIBLE BUT STILL BE EFFECTIVE IN PROTECTING FROM EXCAVATION ACTIVITIES.
4) A 4' DEEP ORANGE PLASTIC MESH TREE BARRIER WITH ROBAR SUPPORTS AT POINT OF PRUNING AND CONTINUE COMPLETELY AROUND TREE, PROTECTING THE AREA WITHIN THE DRIP LINE EXTENT OF OUTER BRANCHES.
5) ROOTS TO BE MADE CLEANLY WITH A SHARP ROOT PRUNING TOOL SUCH AS A DOSKO OR VERMEER ROOT PRUNER. CUTTING OR PRUNING OF ROOTS 3" IN DIAMETER OR LARGER IS PROHIBITED.
6) ROOT PRUNING MUST BE TO A DEPTH OF 18-24 INCHES BELOW GRADE.
7) TRENCH SHORING IS REQUIRED IF EXCAVATION OCCURS WITHIN THE DRIP LINE OF THE TREE.
8) 6" EXCAVATION CAUSED PRUNED ROOTS OVER 1.5" IN DIAMETER TO REMAIN EXPOSED FOR MORE THAN 24 HOURS, ROOTS ON THE TREE SIDE MUST BE KEPT MOIST.
9) TREE DIAMETER IS MEASURED AT BREAST HEIGHT (DBH).

FOR TREES < 6" DBH:
ROOTS SHALL NOT BE NO CLOSER TO THE TREE THAN THE DRIP LINE.
FOR TREES > 6" DBH:

TREE DIAMETER	DISTANCE "X"
6"-9"	5' MIN.
10"-14"	10' MIN.
15"-19"	12' MIN.
> 19"	15' MIN.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
ROOT PRUNING DETAIL	SHEET 1 OF 1
	NOT TO SCALE

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

CONSTRUCTION STANDARDS | DESIGN: K.C.L. | DRAFTING: S.R.M | DATE: 10/28/19 | SCALE: NONE

FIRM NO. 184-001330

1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\GIS\Utilities\Projects\1855701.dwg

PROJECT No. 18557

CULTEC Recharger® 902HD Stormwater Chamber

The Recharger® 902HD is a 48" (1219 mm) tall, high capacity chambers. Typically when using this model, fewer chambers are required resulting in less labor and a smaller installation area. The Recharger® 902HD has the side portal internal manifold feature. HVLV® FC-48 Feed Connectors are inserted into the side portals to create the internal manifold.

Recharger 902HD Chamber	
Size (L x W x H)	4.29' x 7.9" x 48" 1.30 m x 1981 mm x 1219 mm
Installed Length	3.67' 1.12 m
Length Adjustment per Row - with two end caps installed	1.03' 0.31 m
Length Adjustment per Row - when not using end caps	0.58' 0.18 m
Chamber Storage	17.31 ft³/ft 1.61 m³/m 63.47 ft³/unit 1.80 m³/unit
Min. Installed Storage	27.06 ft³/ft 2.52 m³/m 99.28 ft³/unit 2.81 m³/unit
Min. Area Required	26.58 ft² 2.47 m²
Chamber Weight	83.2 lbs 37.65 kg
Shipping	15 chambers/skid 1,370 lbs/skid 14 skids/48' flatbed
Min. Center-to-Center Spacing	7.25' 2.21 m
Max. Allowable Cover	8.3' 2.53 m
Max. Allowable O.D. in Side Portal	10" HDPE, 12" PVC 250 mm HDPE, 300 mm PVC
Compatible Feed Connector	HVLV FC-48 Feed Connector

Calculations are based on installed chamber length.
All above values are nominal.
Includes 12" (305 mm) stone above crown of chamber and typical stone surround at 40% void and 6" (152 mm) stone bedding and stone foundation depth as listed in table. Stone void calculated at 40%.

	Stone Foundation Depth		
	6"	12"	18"
	226 mm	305 mm	457 mm
Chamber and Stone Storage Per Chamber	99.28 ft³ 2.81 m³	101.94 ft³ 2.89 m³	107.26 ft³ 3.04 m³
Min. Effective Depth	3.75' 1.75 m	4.00' 1.83 m	4.5' 1.98 m
Stone Required Per Chamber	3.32 yd³ 2.54 m³	3.56 yd³ 2.72 m³	4.05 yd³ 3.06 m³



Recharger 902HD End Cap


Recharger 902HD End Cap	
Size (L x W x H)	9.7" x 78" x 48.5" 246 mm x 1982 mm x 1231 mm
Installed Length	6.2" 157 mm
End Cap Storage	5.34 ft³/ft 0.50 m³/m 2.76 ft³/unit 0.08 m³/unit
Min. Installed Storage	19.38 ft³/ft 1.85 m³/m 10.28 ft³/unit 0.29 m³/unit
End Cap Weight	52.0 lbs 23.58 kg
Shipping	15 end caps/skid 905 lbs/skid 14 skids/48' flatbed
Max. Inlet Opening in End Cap	30" HDPE, 36" PVC 750 mm HDPE, 900 mm PVC

Calculations are based on installed chamber length.
All above values are nominal.
Min. installed storage includes 9" (229 mm) stone base, 12" (305 mm) stone above crown of chamber and typical stone surround at 7.5" (2.21 m) center-to-center spacing.


© CULTEC, Inc., May 2019 SUS902HDV 05-19

CULTEC Recharger® 902HD Stormwater Chamber

Three View Drawing




Typical Interlock Installation




© CULTEC, Inc., May 2019 SUS902HDV 05-19

CULTEC Recharger® 902HD Stormwater Chamber

Plan View Drawing



Typical Cross Section for Traffic Application



© CULTEC, Inc., May 2019 SUS902HDV 05-19

CULTEC Recharger® 902HD Stormwater Chamber

Recharger® 902HD Bare Chamber Storage Volumes

Elevation		Incremental Storage Volume			Cumulative Storage	
in.	mm	ft³/ft	in²/in	ft²	ft²	m²
48	1219	0.028	0.032	0.073	0.002	63.470
47	1194	0.150	0.035	0.183	0.000	63.397
46	1168	0.078	0.037	0.237	0.007	63.213
45	1143	0.128	0.011	0.446	0.012	62.937
44	1118	0.160	0.013	0.587	0.017	62.917
43	1092	0.100	0.019	0.710	0.021	61.930
42	1067	0.020	0.020	0.907	0.023	61.197
41	1041	0.240	0.022	0.882	0.025	60.290
40	1016	0.270	0.025	0.990	0.028	59.510
39	991	0.270	0.025	0.990	0.029	58.520
38	965	0.200	0.027	1.062	0.033	57.530
37	940	0.300	0.028	1.100	0.031	56.467
36	914	0.310	0.029	1.137	0.032	55.367
35	889	0.330	0.031	1.216	0.034	54.230
34	864	0.340	0.032	1.247	0.035	53.020
33	838	0.350	0.033	1.283	0.039	51.773
32	813	0.350	0.033	1.283	0.036	50.490
31	787	0.360	0.033	1.320	0.037	49.207
30	762	0.370	0.034	1.357	0.038	47.887
29	737	0.390	0.035	1.393	0.039	46.530
28	711	0.390	0.036	1.430	0.040	45.137
27	686	0.390	0.036	1.430	0.040	43.707
26	660	0.400	0.037	1.467	0.042	42.277
25	635	0.400	0.037	1.467	0.042	40.810
24	610	0.410	0.038	1.503	0.043	39.343
23	584	0.410	0.038	1.503	0.043	37.840
22	559	0.410	0.038	1.503	0.043	36.337
21	533	0.410	0.038	1.503	0.044	34.833
20	508	0.420	0.039	1.540	0.044	33.293
19	483	0.420	0.039	1.540	0.044	31.753
18	457	0.430	0.040	1.577	0.045	30.213
17	432	0.430	0.040	1.577	0.045	28.637
16	406	0.440	0.041	1.613	0.046	27.060
15	381	0.440	0.041	1.613	0.046	25.447
14	356	0.450	0.042	1.650	0.047	23.833
13	330	0.450	0.042	1.650	0.047	22.183
12	305	0.450	0.042	1.650	0.047	20.533
11	279	0.450	0.042	1.650	0.047	18.883
10	254	0.460	0.043	1.687	0.048	17.233
9	229	0.460	0.043	1.687	0.048	15.547
8	203	0.460	0.043	1.687	0.048	13.860
7	178	0.460	0.043	1.687	0.048	12.173
6	152	0.470	0.044	1.723	0.049	10.487
5	127	0.470	0.044	1.723	0.049	8.763
4	102	0.480	0.045	1.760	0.050	7.040
3	76	0.480	0.045	1.760	0.050	5.280
2	51	0.480	0.045	1.760	0.050	3.520
1	25	0.480	0.045	1.760	0.050	1.760
Total		17.310	1.608	63.476	1.767	63.470

Calculations are based on installed chamber length of 3.67' (1.12 m).

Recharger® 902HD Bare End Cap Storage Volumes

Elevation		Incremental Storage Volume			Cumulative Storage	
in.	mm	ft³/ft	in²/in	ft²	ft²	m²
48	1219	0.039	0.004	0.100	0.0006	2.716
47	1154	0.058	0.005	0.030	0.0000	2.736
46	1168	0.058	0.005	0.030	0.0000	2.760
45	1143	0.077	0.007	0.040	0.0011	2.673
44	1118	0.097	0.009	0.050	0.0014	2.639
43	1092	0.077	0.007	0.040	0.0011	2.589
42	1067	0.097	0.009	0.050	0.0014	2.549
41	1041	0.097	0.009	0.050	0.0014	2.498
40	1016	0.097	0.009	0.050	0.0014	2.448
39	991	0.097	0.009	0.050	0.0014	2.398
38	965	0.097	0.009	0.050	0.0014	2.348
37	940	0.116	0.011	0.060	0.0017	2.299
36	914	0.097	0.009	0.050	0.0014	2.239
35	889	0.097	0.009	0.050	0.0014	2.189
34	864	0.116	0.011	0.060	0.0017	2.139
33	838	0.097	0.009	0.050	0.0014	2.079
32	813	0.097	0.009	0.050	0.0014	2.029
31	787	0.116	0.011	0.060	0.0017	1.979
30	762	0.097	0.009	0.050	0.0014	1.919
29	737	0.135	0.013	0.070	0.0020	1.869
28	711	0.097	0.009	0.050	0.0014	1.799
27	686	0.116	0.011	0.060	0.0017	1.749
26	660	0.116	0.011	0.060	0.0017	1.689
25	635	0.097	0.009	0.050	0.0014	1.629
24	609	0.116	0.011	0.060	0.0017	1.579
23	584	0.116	0.011	0.060	0.0017	1.519
22	559	0.135	0.013	0.070	0.0020	1.459
21	533	0.116	0.011	0.060	0.0017	1.389
20	508	0.116	0.011	0.060	0.0017	1.329
19	483	0.116	0.011	0.060	0.0017	1.269
18	457	0.116	0.011	0.060	0.0017	1.209
17	432	0.116	0.011	0.060	0.0017	1.149
16	406	0.135	0.013	0.070	0.0020	1.089
15	381	0.116	0.011	0.060	0.0017	1.019
14	356	0.116	0.011	0.060	0.0017	0.959
13	330	0.116	0.011	0.060	0.0017	0.899
12	305	0.135	0.013	0.070	0.0020	0.839
11	279	0.116	0.011	0.060	0.0017	0.779
10	254	0.135	0.013	0.070	0.0020	0.719
9	229	0.135	0.013	0.070	0.0020	0.649
8	203	0.135	0.013	0.070	0.0020	0.579
7	178	0.135	0.013	0.070	0.0020	0.509
6	152	0.116	0.011	0.060	0.0017	0.439
5	127	0.135	0.013	0.070	0.0020	0.379
4	102	0.135	0.013	0.070	0.0020	0.309
3	76	0.135	0.014	0.080	0.0023	0.239
2	51	0.135	0.013	0.070	0.0020	0.159
1	25	0.155	0.014	0.080	0.0023	0.089
Total		3.330	0.446	3.750	0.0765	2.708

Calculations are based on installed chamber length of 6.2" (157 mm).

© CULTEC, Inc., May 2019 SUS902HDV 05-19

CULTEC Recharger® 902HD Stormwater Chamber

CULTEC Recharger® 902HD Specifications

GENERAL

CULTEC Recharger® 902HD chambers are designed for underground stormwater management. The chambers may be used for retention, recharging, detention or controlling the flow of on-site stormwater runoff.

CHAMBER PARAMETERS

1. The chambers shall be manufactured in the U.S.A. or Canada by CULTEC, Inc. of Brookfield, CT (cultec.com, 203-775-4416).
2. Chambers shall be designed and tested in accordance with ASTM F2787 "Standard Practice for Structural Design of Thermoplastic Corrugated Wall Stormwater Collection Chambers".
3. The chamber shall be designed to withstand the AASHTO design truck load and live and dead load factors as defined by AASHTO LRFD Section 12.12 when installed according to CULTEC's recommended installation instructions.
4. The chamber shall be structural foam injection molded of blue virgin high molecular weight impact-modified polypropylene.
5. The chamber shall be arched in shape.
6. The chamber shall be open-bottomed.
7. The chamber shall be joined using an interlocking overlapping rib method. Connections must be fully shouldered overlapping ribs, having no separate couplings.
8. The nominal chamber dimensions of the CULTEC Recharger® 902HD shall be 48 inches (1219 mm) tall, 78 inches (1981 mm) wide and 4.25 feet (1.30m) long. The installed length of a joined Recharger 902HD shall be 3.67 feet (1.12 m).
9. Multiple chambers may be connected to form different length rows. Each row shall begin and end with a separately formed CULTEC Recharger® 902HD End Cap. Maximum inlet opening on the end cap is 30 inches (750 mm) HDPE or 36 inches (900 mm) PVC.
10. The chamber shall have two side portals to accept CULTEC HVLV® FC-48 Field Connectors to create an internal manifold. Maximum allowable pipe size in the side portal is 10 inches (250 mm) HDPE and 12 inches (300 mm) PVC.
11. The nominal chamber dimensions of the CULTEC HVLV™ FC-48 Feed Connector shall be 12 inches (305 mm) tall, 16 inches (406 mm) wide and 49 inches (1245 mm) long.
12. The nominal storage volume of the Recharger 902HD chamber shall be 17.31 ft³/ ft (1.61 m³ / m) - without stone. The nominal storage volume of a joined Recharger 902HD shall be 63.47 ft³ / unit (1.80 m³ / unit) - without stone.
13. The nominal storage volume of the HVLV™ FC-48 Feed Connector shall be 0.913 ft³ / ft (0.085 m³ / m) - without stone.
14. The Recharger 902HD chamber shall have 5 corrugations.
15. The chamber shall be capable of accepting a 6 inch (150 mm) inspection port opening at the top center of each chamber, centered on the crest.
16. The units may be trimmed to custom lengths by cutting back to any corrugation.
17. The chamber shall be manufactured in a facility employing CULTEC's Quality Control and Assurance Procedures.
18. Maximum allowable cover over the top of the chamber shall be 8.3 feet (2.53 m).

END CAP PARAMETERS

1. The CULTEC Recharger® 902HD End Cap (refe rred to as 'end cap') shall be manufactured in the U.S.A. by CULTEC, Inc. of Brookfield, CT (cultec.com, 203-775-4416).
2. The end cap shall be twin-sheet thermoformed of virgin high molecular weight polyethylene.
3. The end cap shall be joined at the beginning and end of each row of chambers using an interlocking overlapping rib method. Connections must be fully shouldered overlapping ribs, having no separate couplings.
4. The nominal dimensions of the end cap shall be 48.5 inches (1231 mm) tall, 78 inches (1982 mm) wide and 9.7 inches (246 mm) long. When joined with a Recharger 902HD chamber, the installed length of the end cap shall be 6.2 inches (157 mm).
5. The nominal storage volume of the end cap shall be 5.34 ft³/ ft (0.50 m³ / m) - without stone. The nominal storage volume of an interlocked end cap shall be 2.76 ft³ / unit (0.08 m³ / unit) - without stone.
6. Maximum inlet opening on the end cap is 30 inches (750 mm) HDPE or 36 inches (900 mm) PVC.
7. The end cap shall provide resistance to the loads and load factors as defined in the AASHTO LRFD Bridge Design Specifications Section 12.12.

© CULTEC, Inc., May 2019 SUS902HDV 05-19

CULTEC Recharger® 280HD Stormwater Chamber

The Recharger® 280HD is a 26.5" (673 mm) tall, mid-size chamber and is typically used for installations with depth restrictions or when a larger infiltrative area is required. The Recharger® 280HD has the side portal internal manifold feature. HVLV® FC-24 Feed Connectors are inserted into the side portals to create the internal manifold.

Size (L x W x H)	8' x 47" x 26.5" 2.44 m x 1194 mm x 673 mm
Installed Length	7' 2.13 m
Length Adjustment per Row	1' 0.30 m
Chamber Storage	6.68 ft³/ft 0.56 m³/m 42.55 ft³/unit 1.21 m³/unit
Min. Installed Storage	8.21 ft³/ft 0.66 m³/m 64.68 ft³/unit 1.83 m³/unit
Min. Area Required	30.33 ft² 2.82 m²
Chamber Weight	64.0 lbs 29.03 kg
Shipping	35 chambers/skid 2,345 lbs/skid 12 skids/48' flatbed
Min. Center-to-Center Spacing	4.33' 1.32 m
Max. Allowable Cover	12' 3.66 m
Max. Inlet Opening in End Wall	21" HDPE, PVC 525 mm HDPE, PVC
Max. Allowable O.D. in Side Portal	10" HDPE, 12" PVC 250 mm HDPE, 300 mm PVC
Compatible Feed Connector	HVLV FC-24 Feed Connector

Calculations are based on installed chamber length.
All above values are nominal.
Min. installed storage includes 6" (152 mm) stone base, 6" (152 mm) stone above crown of chamber and typical stone surround at 12" (305 mm) center-to-center spacing.

	Stone Foundation Depth		
	6"	12"	18"
	152 mm	305 mm	457 mm
Chamber and Stone Storage Per Chamber	44.46 ft³ 1.83 m³	70.53 ft³ 2.00 m³	76.59 ft³ 2.17 m³
Min. Effective Depth	3.21' 0.98 m	3.71' 1.13 m	4.21' 1.28 m
Stone Required Per Chamber	2.03 yd³ 1.55 m³	2.59 yd³ 1.98 m³	3.15 yd³ 2.41 m³

Calculations are based on installed chamber length.
Min. installed storage includes 6" (152 mm) stone above crown of chamber and typical stone surround at 12" (305 mm) center-to-center spacing and stone foundation depth as listed in table. Stone void calculated at 40%.



Recharger® 280HD Bare Chamber Storage Volumes

Elevation		Incremental Storage Volume			Cumulative Storage	
in.	mm	ft³/ft	in²/in	ft²	ft²	m²
26.5	686	0.859	0.080	0.556	0.000	42.553
26	660	0.018	0.092	0.126	0.004	42.553
25	635	0.047	0.084	0.329	0.009	42.427
24	609	0.109	0.069	0.756	0.020	42.098
23	584	0.154	0.012	0.938	0.027	41.342
22	559	0.139	0.075	1.513	0.032	40.404
21	533	0.179	0.017	1.253	0.035	39.347
20	508	0.191	0.016	1.363	0.035	38.094
19	483	0.229	0.019	1.463	0.041	36.729
18	457	0.231	0.021	1.547	0.044	35.266
17	432	0.252	0.022	1.624	0.048	33.719
16	406	0.241	0.022	1.697	0.048	32.095
15	381	0.249	0.023	1.743	0.049	30.398
14	356	0.253	0.024	1.847	0.052	28.655
13	330	0.267	0.025	1.869	0.053	26.824
12	305	0.271	0.025	1.892	0.054	24.955
11	279	0.275	0.026	1.925	0.055	23.059
10	254	0.279	0.026	1.953	0.055	21.133
9	229	0.287	0.027	2.009	0.057	19.180
8	203	0.292	0.027	2.044	0.058	17.171
7	178	0.294	0.027	2.056	0.058	15.127
6	152	0.305	0.028	2.135	0.061	13.043
5	127	0.306	0.028	2.142	0.061	10.934
4	102	0.318	0.029	2.226	0.063	8.792
3	76	0.319	0.029	2.233	0.063	6.636
2	51	0.312	0.029	2.184	0.062	4.466
1	25	0.326	0.030	2.282	0.065	2.282
Total		6.674	0.563	43.559	1.268	42.553


Calculations are based on installed chamber length.

Visit www.cultec.com/downloads.html for Product Downloads and CAD details.


© CULTEC, Inc., May 2019 SUS280HD 05-19

CULTEC Recharger® 280HD Stormwater Chamber

Three View Drawing




Typical Interlock Installation




© CULTEC, Inc., May 2019 SUS280HD 05-19

CULTEC Recharger® 280HD Stormwater Chamber

Plan View Drawing



Typical Cross Section for Traffic Application



© CULTEC, Inc., May 2019 SUS280HD 05-19

CULTEC Recharger® 280HD Stormwater Chamber


CULTEC Recharger® 280HD Specifications

GENERAL

CULTEC Recharger® 280HD chambers are designed for underground stormwater management. The chambers may be used for retention, recharging, detention or controlling the flow of on-site stormwater runoff.

CHAMBER PARAMETERS

1. The chambers shall be manufactured in the U.S.A. by CULTEC, Inc. of Brookfield, CT (cultec.com, 203-775-4416).
2. The chamber shall be vacuum thermoformed of polyethylene with a black interior and blue exterior.
3. The chamber shall be arched in shape.
4. The chamber shall be open-bottomed.
5. The chamber shall be joined using an interlocking overlapping rib method. Connections must be fully shouldered overlapping ribs, having no separate couplings or separate end walls.
6. The nominal chamber dimensions of the CULTEC Recharger® 280HD shall be 26.5 inches (673 mm) tall, 47 inches (1194 mm) wide and 8 feet (2.44 m) long. The installed length of a joined Recharger® 280HD shall be 7 feet (2.13 m).
7. Maximum inlet opening on the chamber end wall is 21 inches (525 mm) HDPE, PVC.
8. The chamber shall have two side portals to accept CULTEC HVLV® FC-24 Feed Connectors to create an internal manifold. Maximum allowable O.D. in the side portal is 10 inches (250 mm) HDPE, 12 inches (300 mm) PVC.
9. The nominal chamber dimensions of the CULTEC HVLV® FC-24 Feed Connector shall be 12 inches (305 mm) tall, 16 inches (406 mm) wide and 24.2 inches (614 mm) long.
10. The nominal storage volume of the Recharger® 280HD chamber shall be 6.079 ft³ / ft (0.565 m³ / m) - without stone. The nominal storage volume of a single Recharger 280HD Stand Alone unit shall be 46.63 ft³ (1.38 m³) - without stone. The nominal storage volume of a joined Recharger® 280HD Intermediate unit shall be 42.553 ft³ (1.205 m³) - without stone. The nominal storage volume of the length adjustment amount per run shall be 6.08 ft³ (0.56 m³) - without stone.
11. The nominal storage volume of the HVLV® FC-24 Feed Connector shall be 0.913 ft³ / ft (0.085 m³ / m) - without stone.
12. The Recharger® 280HD chamber shall have seventy-two discharge holes bored into the sidewalls of the unit's core to promote lateral conveyance of water.
13. The Recharger® 280HD chamber shall have 15 corrugations.
14. The end wall of the chamber, when present, shall be an integral part of the continuously formed unit. Separate end plates cannot be used with this unit.
15. The Recharger® 280HD Stand Alone unit must be formed as a whole chamber having two fully formed integral end walls and having no separate end plates or separate end walls.
16. The Recharger® 280HD Starter unit must be formed as a whole chamber having one fully formed integral end wall and one partially formed integral end wall with a lower transfer opening of 9 inches (229 mm) high x 35 inches (889 mm) wide.
17. The Recharger® 280HD Intermediate unit must be formed as a whole chamber having one fully open end wall and one partially formed integral end wall with a lower transfer opening of 9 inches (229 mm) high x 35 inches (889 mm) wide.
18. The Recharger® 280HD End unit must be formed




NOTES:
1. PRECAST CONC. FLARED END SECTIONS SHALL CONFORM TO THE APPLICABLE REQUIREMENTS OF A.S.T.M. DESIGNATION C-76, CLASS III, WALL "B" REINFORCED CONC. PIPE.
2. USE STANDARD REINFORCEMENT FOR CIRCULAR, CLASS III, WALL "B" REINFORCED CONC. PIPE.
3. THE END BLOCK SHALL BE PLACED PRIOR TO THE INSTALLATION OF THE FLARED END SECTION. THE END BLOCK SHALL BE BACKFILLED IN ACCORDANCE WITH ART. 502.11 OF THE STANDARD SPECIFICATIONS, COST INCIDENTAL TO END SECTION.

DIMENSION CHART

PIPE DIA.	WALL	A	B	C	D	E	G	R	SLOPE
12"	2"	4"	4'0"	2'7/8"	6'7/8"	2'0"	2"	9"	3:1
15"	2 1/4"	6"	2'3"	3'10"	6'1"	2'6"	2 1/4"	11"	3:1
18"	2 1/2"	9"	2'3"	3'10"	6'1"	3'0"	2 1/2"	12"	3:1
21"	2 3/4"	9"	2'11"	3'2"	6'1"	3'6"	2 3/4"	13"	3:1
24"	3"	9 1/2"	3'7 1/2"	2'6"	6' 1 1/2"	4'0"	3"	14"	3:1
27"	3 1/4"	10 1/2"	4'0"	2' 1 1/2"	6' 1 1/2"	4'6"	3 1/4"	14 1/2"	3:1
30"	3 1/2"	1'0"	4'6"	1' 7 3/4"	6' 1 3/4"	5'0"	3 1/2"	15"	3:1
33"	3 3/4"	1' 1 1/2"	4'10 1/2"	3' 3 1/4"	8' 1 3/4"	5'6"	3 3/4"	17 1/2"	3:1
36"	4"	1'3"	5'3"	2' 10 3/4"	8' 1 3/4"	6'0"	4"	20"	3:1
42"	4 1/2"	1'9"	5'3"	2'11"	8'2"	6'6"	4 1/2"	22"	3:1
48"	5"	2'0"	6'0"	2'2"	8'2"	7'0"	5"	22"	3:1
54"	5 1/2"	2'3"	5'5"	2'11"	8'4"	7'6"	5 1/2"	24"	2.4:1

PRECAST REINFORCED CONCRETE FLARED END SECTION

ST58.DWG



	APRON SIZE	V-BAR e	H-BAR SIZE	NO. H-BARS	BOLT DIA.	"A" DIM.
	INCHES				INCHES	
ARCH PIPE OPENING	18	1/2	5/8 ø	3	1/2	5
	24	5/8	3/4 ø	4	1/2	7
	30	5/8	3/4 ø	4	1/2	7 1/2
	36	3/4	1 ø	4	1/2	10 1/2
	42	3/4	1 ø	4	3/4	11
	48	3/4	1.5 PIPE	4	3/4	12
	54	3/4	1.5 PIPE	4	3/4	12
	60	3/4	1.5 PIPE	5	3/4	14
	72	3/4	1.5 PIPE	5	3/4	14
	84	3/4	1.5 PIPE	6	3/4	15
ROUND PIPE OPENING	12	1/2	5/8 ø	3	1/2	4
	15	1/2	5/8 ø	3	1/2	4 1/2
	18	1/2	5/8 ø	4	1/2	4 1/2
	21	1/2	5/8 ø	4	1/2	5
	24	5/8	3/4 ø	4	1/2	5
	27	5/8	3/4 ø	4	1/2	5 1/2
	30	5/8	3/4 ø	4	1/2	5 1/2
	36	3/4	1 ø	4	3/4	8
	42	3/4	1 ø	4	3/4	8
	48	3/4	1 ø	5	3/4	8
	54	3/4	1.5 PIPE	5	3/4	8
	60	3/4	1.5 PIPE	6	3/4	8
	66	3/4	1.5 PIPE	6	3/4	8
	72	3/4	1.5 PIPE	6	3/4	9
	84	3/4	1.5 PIPE	7	3/4	10
	90	3/4	1.5 PIPE	7	3/4	14


NOTES: 1. BARS & PLATES ARE HOT-ROLLED STEEL.
2. BARS, PLATES & PIPE ARE FINISHED WITH 2 COATS OF ALUMINUM PAINT.
3. BOLTS ARE GALVANIZED
4. SEE STD. PLATES A-10 & A-11 FOR APRON DIMENSIONS.
5. TRASH GUARDS MAY DIFFERENT DIAMETER BARS ARE AVAILABLE, SPECIAL ORDER.

TRASH GUARDS FOR F.E.S.

ST59.DWG

R-3502 Series
Inlet for Roll Type Curb

Heavy Duty



Catalog No.	A	B	C	E	F	G	H	I	J	K	L	M	N	O	P
	Dimensions in inches														
R-3502-A *	22	1 3/4	20 1/4	36	10	1 7/8	1	13 7/8	8 7/8	4	1 3/4	3	23	36	15 5/8
R-3502-B	21 1/2	1 3/4	20 1/4	36	10	1 7/8	1	14	8	4	2 3/4	3	22	36	13 5/8


* Frame furnished in two pieces as shown on *R-3502-D2*.

CATALOG NUMBER	GRATE TYPE	SQ. FT. OPEN	WEIR PERIMETER LINEAL FEET
R-3502-A	A	1.4	4.1
R-3502-B	A	1.4	4.2

■ Note: When specifying/ordering grates, refer to "Choosing the Proper Inlet Grate" on pages 125-126. For a complete listing of FREE OPEN AREAS and WEIR PERIMETERS of all NEENAH grates, refer to pages 327-332.

R-2560 Series
Inlet Frame, Beehive Grate

Suitable for drainage in circumstances where clogging of a flat grating is a problem. Excellent for roadside or earth ditch inlets.



Illustrating R-2560-E

CATALOG NUMBER	GRATE TYPE	SQ. FT. OPEN	WEIR PERIMETER LINEAL FEET
R-2560-A	Beehive	1.3	3.1
R-2560-C	Beehive	0.7	4.7
R-2560-C1	Beehive	0.7	5.5
R-2560-C2	Beehive	0.7	3.6
R-2560-D	Beehive	1.9	5.3
R-2560-D1	Beehive	1.2	5.8
R-2560-D2	Beehive	1.2	5.8
R-2560-D3	Beehive	1.2	5.8
R-2560-D4	Beehive	1.9	5.1
R-2560-D7	Beehive	1.3	5.3
R-2560-D8	Beehive	1.3	5.3
R-2560-E	Beehive	1.2	4.0
R-2560-EA	Beehive	1.2	6.2
R-2560-EB	Beehive	1.8	6.7
R-2560-E7	Beehive	1.8	6.2
R-2560-E8	Beehive	2.9	6.2
R-2560-E9	Beehive	1.2	6.2
R-2560-E7	Beehive	1.2	6.2
R-2560-E8	Beehive	1.8	6.2
R-2560-E9	Beehive	1.2	6.2
R-2560-EA	Beehive	1.8	6.2
R-2560-EB	Beehive	1.5	6.4

Catalog No.	A	B	C	E	F	G	Frame/Lid
	Dimensions in inches						
R-2560-A	12	1	11	19	4	3 1/4	R-1791-A
R-2560-C	18 1/4	1 1/4	16 3/4	30	9	4	R-1900-A
R-2560-C1	22	1 1/2	20 15/32	27 9/16	3 15/16	4 1/2	R-1690
R-2560-C2	22	1 1/2	20 1/2	28 1/4	6	4 1/2	R-1761
R-2560-D	22	1 1/2	20	35	9	4 1/2	R-1710
R-2560-D1	22	1 1/2	20 15/32	27 9/16	3 15/16	7	R-1690
R-2560-D3	22	1 1/2	20 1/2	28 1/4	6	7	R-1761
R-2560-D3	22	1 1/2	20	35	9	7	R-1710
R-2560-D5	22 3/4	1 1/2	21 1/4	34	4	4 1/2	R-1647-A
R-2560-D6	22 3/4	1 1/2	21	34	9	4 1/2	R-1713
R-2560-D7	22 3/4	1 1/2	21 1/4	34	4	7	R-1647-A
R-2560-D8	22 3/4	1 1/2	21	34	9	7	R-1713
R-2560-E	23	1 1/2	21 1/16	35 7/16	8 7/8	7	R-1550-A
R-2560-E1	25 3/4	7/8	24	35 7/16	7	6	R-1733
R-2560-E2	25 3/4	7/8	24	35 7/16	7	9	R-1733
R-2560-E5	25 3/4	7/8	24 1/8	35 1/2	8	6	R-1733-A
R-2560-E6	25 3/4	7/8	24 1/8	35 1/2	8	9	R-1733-A
R-2560-E7	25 3/4	7/8	24 1/8	35 1/2	9	6	R-1733-B
R-2560-E8	25 3/4	7/8	24 1/8	35 1/2	9	9	R-1733-B
R-2560-E9	25 3/4	7/8	24 1/8	35 1/2	10	6	R-1733-C
R-2560-E10	25 3/4	7/8	24 1/8	35 1/2	10	9	R-1733-C
R-2560-EA	25 3/4	7/8	24 1/8	35 7/16	4	6	R-1733-1
R-2560-EB	25 3/4	7/8	24 1/8	35 7/16	4	9	R-1733-1
R-2560-G	32	1 1/2	30	46	7	4	R-1740-B

R-2586 Series
Angle Frame, Grate



Illustrating R-2586-A with Type E Grate

CATALOG NUMBER	GRATE TYPE	SQ. FT. OPEN	WEIR PERIMETER LINEAL FEET
R-2586-A	E	3.4	3.8
R-2586-B	G	3.5	4.2
R-2586-C	E	3.5	4.2
R-2586-D	G	3.8	5.2
R-2586-E	G	3.8	5.1
R-2586-F	G	3.8	5.4
R-2586-G	G	1.8	5.8
R-2586-H	G	1.3	6.0
R-2586-K	G	1.3	5.2
R-2586-M	G	1.8	7.0
R-2586-N	G	1.7	7.9
R-2586-O	G	1.9	9.4

Type G

Catalog No.	A	B	C	E	F	G	H	Type	Duty
	Dimensions in inches								
R-2586-A	14 1/4	3/4	13	16	1 1/2	3/4	1	E	Light
R-2586-B *	18	1	13 1/2	18 1/4	1 5/8	1 1/8	1	G	Heavy
R-2586-C **	18	3/4	16	18 1/4	1 1/4	7/8	3/4	E	Light
R-2586-D * **	19 3/4	1	17 1/2	21 3/4	1 5/8	1	3/4	G	Light
R-2586-E **	19 1/2	1 1/2	16	21 1/4	2	3/4	3/4	G	Light
R-2586-F *	20 1/2	3/4	18 3/4	23	1 1/4	1	1	G	Light
R-2586-G **	22 1/4	1 1/2	20 3/8	24 3/8	2 1/4	1 1/4	1	G	Heavy
R-2586-H **	22 3/4	1 3/4	20 1/2	25 1/2	3	1 1/2	1	E	Heavy
R-2586-K	24	3/4	21 3/4	26	1 1/4	1/2	1/2	G	Light
R-2586-M	26 5/8	3/4	24	28 1/4	1 3/8	7/8	11/16	G	Light
R-2586-N	38	1	27 1/2	33	1 3/4	1 1/4	1	G	Light
R-2586-O	32	1	30	34	2 1/4	1 1/4	1	G	Light

* Furnished standard with machined horizontal bearing surfaces. All others have as-cast surfaces.
** Cast integral frame anchors available if specified.

Eco-Optiloc™



NATURAL — RIVER BLEND — STANDARD 10 1/16" x 10 7/16" x 3 1/16" 26cm x 26cm x 8cm SPECIAL ORDER

Stones & Bundling	Unit Thickness	SqFt/ Bundle	SqFt/ Section	SqFt/ Stone	Sections/ Bundle	LnFt/Sec (Soldier)	SqFt/LnFt (Soldier)	LnFt/Bdl (Soldier)	Units/ SqFt	Lbs/ Bundle	Lbs/ Section	Units/ Bundle
Standard	3 1/8" (8cm)	84.4	-	-	-	-	-	-	-	2868	-	-

Notes: Most standard colors are available but are special order only and subject to minimum quantities. Contact your representative for details. This product is optimized for mechanical installation. Product is available in full bundles only. All measurements are nominal. Contact Unilock for information.

TAPCO Safe travels.

Custom Sign Proof for Production Date 7/18/2019

current sign design version A



Customer:	Village of Glencoe
Customer #:	C9622
Sales order #:	SO Q1912781
Sales person:	Richard B
File name:	Q1912781 .fs

By checking "Approves for Production" and signing below, customer agrees to purchase sign as it appears on this artwork proof. Once this approval is received by TAPCO production will begin and any changes and/or cancellations will not be possible.

Customer... date & signature

... approves for production 7/18/19 Ray Irby

... requests changes / additions (please describe below)

P 262.814.7000 | F 414.354.5480 | www.tapconet.com | 5100 W. Brown Deer Road, Brown Deer, WI 53223

NOTE:
1. STREET NAME SIGNS CAN BE MOUNTED ON TOP OF STOP SIGN OR NO OUTLET SIGN.
2. ALL STOP SIGNS ANN STREET NAME POSTS SHOULD BE 2-3/8" GALVANIZED STEEL ROUND POSTS, SCHEDULE 5 WITH BLACK POWDER COATING. NO PARKING SIGNS ARE TO BE U-CHANNEL POSTS.
3. CONTRACTOR SHALL CONTACT TAPCO AND PROVIDE A PROOF FOR STAFF REVIEW PRIOR TO ORDERING.

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gconsulting.net

CONSTRUCTION STANDARDS

DESIGN: K.C.L. | DRAFTING: S.R.M

SCALE: NONE | DATE: 10/28/19

FIRM NO. 184-001330

1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

C:\IG\08\18557\Dwg\18557DT.dwg

PROJECT No. 18557

LEGEND

PROPERTY LINE

EX. TREES TO REMAIN

NEW PROPOSED PARKWAY TREES

* SEE SHEET 13 FOR DETAILED PLANTING LIST

FOREST PRESERVE
TURNBULL WOODS

FOREST PRESERVE

ZONE R-A
FOREST PRESERV
COUNTY CLERK'S

ZONE R-A
GLENCOE GOLF CLUB

ZONE R-B
SINGLE FAMILY
RESIDENTIAL DISTRIC

NORTH GATE SUBDIVISION
DOC. 18523477

DUNAS FOREST CREST SUBDIVISION
DOC. 6452607

ESTATE ROAD

GREEN BAY ROAD

WESTLEY ROAD

NORTHWOOD DRIVE

TRIST

OUTLOT A

OUTLOT B

OUTLOT C

DETENTION
E. 1.0 AC.

STORM SERVICE (TYP.)

PROPOSED ELECTRIC LINE (TYP.)

PERMEABLE PAVERS FOR BMP CONTROL

PROPOSED STREET LIGHT (TYP.)

PROPOSED ELECTRIC MAIN (TYP.)

35' WEIR WIDTH
OVERFLOW = 678.50

(1) QBS 6" CAL
(2) QBS 6" CAL
(3) UAP 6" CAL
(2) ARR 6" CAL
(4) KCT 6" CAL
(2) QRS 6" CAL
(2) ATM 6" CAL
(5) PAE 6" CAL
(3) ATM 6" CAL
(5) ATT 6" CAL
(4) ARR 5" CAL
(1) GTP 6" CAL
(2) KCT 6" CAL
(2) PAE 6" CAL

SCALE

40 0 20 40 80 160

(IN FEET)
1 inch = 40 ft.

LANDSCAPE PLANS

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | g@gconsulting.net

PROPOSED STREET TREES

DESIGN: B.J. | DRAFTING: D.O.

SCALE: 1"=40' | DATE: 02-21-2020

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © G CONSULTING, INC.

S:\ARA — CAD\2019\1913 — Hoover Estate\Master Plan\Sheets\L1.00 Proposed Street Trees.dwg

PROJECT No. 18557

LEGEND

- PROPERTY LINE
- EX. TREES TO REMAIN
- NEW PROPOSED STREET TREES
- NEW PROPOSED SHADE TREES
- NEW PROPOSED COLUMNAR TREES

* SEE SHEET 13 FOR DETAILED PLANTING LIST

FOREST PRESERVE
TURNBULL WOODS

FOREST PRESERVE

ZONE R-A
FOREST PRESERVE
COUNTY CLERK'S DIVISION

ZONE R-B
SINGLE FAMILY
RESIDENTIAL DISTRICT

NORTHWOOD DRIVE

NORTH GATE SUBDIVISION
DOC. 18523477

DUNAS FOREST CREST SUBDIVISION
DOC. 6452807

CAROL LANE

ESTATE ROAD

GREEN BAY ROAD

WESTLEY ROAD

UNSUBDIVIDED

OUTLOT A

OUTLOT E

#403 #409 #414 #406 #1799 #1214 #1212 #1201 #1206 #1200 #1194 #1188 #1185 #1179 #1173 #1182 #1178 #1176 #1169

LOT F LOT E LOT H LOT G LOT 1 LOT 2 LOT 3 LOT 4 LOT 5 LOT 6 LOT 7 LOT 8 LOT 9 LOT 10 LOT 11 LOT 12 LOT 13 LOT 14 LOT 15 LOT 16 LOT 17 LOT 18 LOT 19 LOT 20 LOT 21 LOT 22 LOT 23 LOT 24 LOT 25 LOT 26 LOT 27 LOT 28 LOT 29 LOT 8 LOT 9 LOT 10 LOT 11 LOT 12 LOT 13 LOT 14 LOT 15 LOT 16 LOT 17

(1) CBF 8" CAL. (4) ATH 6" CAL. (3) LTA 5" CAL. (3) QUK 6" CAL. (6) QRS 6" CAL. (4) RB 5" CAL. (5) QUK 6" CAL. (4) UAP 6" CAL. (2) CBF 5" CAL. (5) QMP 6" CAL. (6) QRS 6" CAL. (1) QBS 6" CAL. (5) LTA 5" CAL. (2) ARR 8" CAL. (1) QBS 6" CAL. (3) UAP 6" CAL. (2) ARR 6" CAL. (4) KCT 6" CAL. (4) ARR 6" CAL. (3) QRS 6" CAL. (2) QRS 5" CAL. (1) KCT 5" CAL. (2) ATH 6" CAL. (2) QBS 6" CAL. (2) QBS 6" CAL. (3) PAE 6" CAL. (4) KCT 6" CAL. (3) BBM 6" CAL. (2) QBS 6" CAL. (5) KCT 6" CAL. (3) BBM 6" CAL. (1) QBS 6" CAL. (5) ATH 6" CAL. (3) ATH 6" CAL. (5) ATH 6" CAL. (4) ARR 5" CAL. (1) QMP 6" CAL. (2) QBS 6" CAL. (3) QBS 6" CAL. (1) UAP 5" CAL. (1) PAE 6" CAL. (8) ARM 6" CAL. (2) ARR 8" CAL. (1) ARM 6" CAL. (3) ARM 6" CAL. (3) ARM 6" CAL. (7) ARA 6" CAL. (6) RPO 6" CAL. (1) QMP 6" CAL. (2) ARR 4" CAL. (8) ARA 6" CAL. (0) QRS 6" CAL. (1) CBF 6" CAL. (6) ARM 6" CAL. (1) CBF 6" CAL. (3) UAP 6" CAL. (2) ARR 6" CAL. (1) QBS 6" CAL.

SANITARY SERVICE (TYP.) WATER SERVICE (TYP.) STORM SERVICE (TYP.) PROPOSED ELECTRIC LINE (TYP.) PERMEABLE PAVERS FOR BMP CONTROL PROPOSED STREET LIGHT (TYP.) PROPOSED ELECTRIC MAIN (TYP.) SANITARY SERVICE (TYP.) WATER SERVICE (TYP.) 8' WIDE BIOSWALE

SCALE
40 0 20 40 80 160
(IN FEET)
1 inch = 40 ft.

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE:	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 ig@igconsulting.net

PROPOSED SITE TREES

DESIGN: B.J. | DRAFTING: D.O.
SCALE: 1"=40' | DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA — CAD\2019\1913 — Hoover Estate\Master Plan\Sheets\L1.01 Proposed Site Trees.dwg

PROJECT No. 18557

LEGEND

PROPERTY LINE

NEW 6' ORNAMENTAL FENCE
SEE SHEET 10 FOR DETAIL

NEW 6' BOARD ON BOARD FENCE
SEE SHEET 10 FOR DETAIL



1 TYPICAL BOARD ON BOARD WOOD FENCE
SCALE: NTS



2 TYPICAL ORNAMENTAL FENCE
SCALE: NTS

SCALE
40 0 20 40 80 160
(IN FEET)
1 inch = 40 ft.

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net
PERIMETER FENCING

DESIGN: B.J. | DRAFTING: D.O.
SCALE: 1"=40' | DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA -- CAD\2019\1913 -- Hoover Estate\Master Plan\Sheets\L1.02 Perimeter Fencing.dwg

PROJECT No.
18557

LOT 26
LOT 27
LOT 25
LOT 24
LOT 4
OUTLOT A
SANITARY SERVICE (TYP.)
WATER SER (TYP.)
WOODLAND PLANTING
(2) ARR 5"CAL.
(1) UAP 6"CAL.
(3) UAP 6" CAL.
(1) QBS 6" CAL.
(5) LTA 5"CAL.
(2) ARR 6" CAL.
(4) KCT 6"CAL.
(4) ARR 6"CAL.
(1) QRS 6"CAL.
(3) QRS 6"CAL.
(2) QRS 6"CAL.
(1) KCT 5"CAL.
(2) QBS 6"CAL.
(2) ATM 6"CAL.
(2) QBS 6"CAL.
(5) PAE 6"CAL.

LEGEND

- PROPERTY LINE
- EXISTING TREES TO REMAIN WITH TAG NUMBER
- PROPOSED STREET TREES
- PROPOSED SHADE TREES
- WOODLAND PLANTING
- SOD
- PROPOSED CONTOUR LINES
- PROPOSED STREET LIGHTS

* SEE SHEET 13 FOR DETAILED PLANTING LIST

PLANT MATERIAL

WOODLAND PLANTING

VIRGINIA BLUESTEM



WHITE TRILLIUM



BLOOD ROOT PLANT



HIPATICA



YELLOW TRILLIUM



MAYFLOWER PLANT



SOLOMAN'S SEAL



MAYAPPLE PLANT



TROUT LILY



NARCISS MIX







SHADE TREES

PRINCETON ELM



RED POINT MAPLE



KENTUCKY COFFEE TREE



SCALE

1/16" 0 8' 16' 32' 64'

1/16 inch = 1 ft

NORTH

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE:	DESCRIPTION	DRWN. BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1729 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net
FIRM NO. 184-001330

ENLARGEMENT PLAN
OUTLOT A

DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557

4 of 13

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA — CAD\2019\19-3 — Hoover Estate\Master Plan\Sheets\L1.03 Enlargement Plan Outlot A.dwg



LEGEND

- PROPERTY LINE
- EXISTING TREE TO REMAIN WITH TAG NUMBER
- PROPOSED STREET TREES
- PROPOSED SHADE TREE
- SOD
- PROPOSED CONTOUR LINES
- PROPOSED STREET LIGHTS

* SEE SHEET 13 FOR DETAILED PLANTING LIST

PLANT MATERIAL

CAREX PENSYLVANICA



NARCISSUS



AMERICAN SENTRY LINDEN



TULIP TREE



SCALE

1/16" 0' 8' 16' 32' 64'

1/16 inch = 1 ft

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

ENLARGEMENT PLAN
OUTLOT C

DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA — CAD\2019\19-3 — Hoover Estate\Master Plan\Sheets\LI-04 Enlargement Plan Outlot C.dwg

PROJECT No. 18557

PRESERVE

35' WEIR WIDTH
OVERFLOW = 678.50

(3) QWK
6" CAL.

(10) QRS
6" CAL.

DETENTION BASIN
HYDRO SEEDED WITH
RTF FESCUE SEED MIX

LOW MOW GRASS
(HYDRO SEEDED)
SEE SHEET 13 FOR
DETAILED PLANTING LIST

6' BOARD ON BOARD
FENCE

8' WIDE HYDO SEEDED
BIOSWALE TYP
SEE SHEET 13 FOR
DETAILED PLANTING
LIST

(7) CBF
6" CAL.

HYDRO SEEDED WITH RTF
FESCUE SEED MIX

(5) ARM
6" CAL.

(1) UAP
6" CAL.

(3) UAP
6" CAL.

(2) ARR
6" CAL.

(4) ARR
6" CAL.

(1) QRS
6" CAL.

(3) QRS
6" CAL.

(2) QRS
6" OAK.

(1) KCT

SANITARY SERVICE
(TYP.)

WATER SERVICE
(TYP.)

LOT 25

LOT 24

LOT 23

LOT 22

LOT 21

DETENTION BASIN

MATCH LINE A: SEE MATCH LINE B ON SHEET 7

LEGEND

- PROPERTY LINE
- EXISTING TREE TO REMAIN WITH TAG NUMBER
- PROPOSED STREET TREES
- PROPOSED COLUMNAR TREES
- PROPOSED SHADE TREE
- HYDRO SEEDED BIOSWALE TYPICAL
- LOW MOW GRASS (HYDRO SEEDED)
- HYDRO SEEDED WITH RTF FESCUE SEED MIX
- S.O.D
- PROPOSED CONTOUR LINES
- PROPOSED STREET LIGHTS

*SEE SHEET 13 FOR DETAIL PLANTING LIST

PLANT MATERIAL

BIOSWALE PLANTING TYPICAL

HELIANTHUS GROSSESERRATUS



ASTER WOODS LIGHT BLUE



ELYMUS CANADENSIS



CAREX STIPATA



SCHIZACHYRIUM SCOPARIUM



LIATRIS SPICATATTT



COLUMNAR TREES

URBAN PINNACLE OAK



ARMSTRONG GOLD MAPLE



CARPINUS BETULUS 'FRANS FONTAINE'



STREET SPIRE OAK



SCALE

1/16" 0 8' 16' 32' 64'

1/16 inch = 1 ft

NORTH

Jacobs/Ryan Associates
Landscape Architects

1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE:	DESCRIPTION	DRWN. BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.

CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

ENLARGEMENT PLAN
OUTLOT D

DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS


PROJECT No.
18557

6 of 13

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA — CAD\2019\19-13 — Hoover Estate\Master Plan\Sheets\L1.05 Enlargement Plan Outlot D.dwg

MATCH LINE B: SEE MATCH LINE A SHEET 6



MATCH LINE C: SEE MATCH LINE D ON SHEET 8

LEGEND

- PROPERTY LINE
- EXISTING TREE TO REMAIN WITH TAG NUMBER
- PROPOSED STREET TREES
- PROPOSED COLUMNAR TREES
- PROPOSED SHADE TREE
- HYDRO SEEDED BIOSWALE TYPICAL
- LOW MOW GRASS (HYDRO SEEDED)
- HYDRO SEEDED WITH RTF FESCUE SEED MIX
- S.O.D
- PROPOSED CONTOUR LINES
- PROPOSED STREET LIGHTS

*SEE SHEET 13 FOR DETAIL PLANTING LIST

PLANT MATERIAL

BIOSWALE PLANTING TYPICAL

HELIANTHUS GROSSESERRATUS



ASTER WOODS LIGHT BLUE



ELYMUS CANADENSIS



CAREX STIPATA



SCHIZACHYRIUM SCOPARIUM



LIATRIS SPICATATTT



COLUMNAR TREES

URBAN PINNACLE OAK



ARMSTRONG GOLD MAPLE



REGAL PRINCE OAK



SCALE

1/16" 0 8" 16" 32" 64"

1/16 inch = 1 ft

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gcensulting.net

ENLARGEMENT PLAN
OUTLOT F

DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020
FIRM NO. 184-001330


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\IRA — CAD\2019\1913 — Hoover Estate\Master Plan\Sheets\L1.06 Enlargement Plan Outlot F.dwg

PROJECT No. 18557

MATCH LINE D: SEE MATCH LINE C ON SHEET 7



LEGEND

- PROPERTY LINE
- EXISTING TREE TO REMAIN WITH TAG NUMBER
- PROPOSED STREET TREES
- PROPOSED COLUMNAR TREES
- PROPOSED SHADE TREES
- HYDRO SEEDED BIOSWALE TYPICAL
- LOW MOW GRASS (HYDRO SEEDED)
- HYDRO SEEDED WITH RTF FESCUE SEED MIX
- S.O.D
- PROPOSED CONTOUR LINES
- PROPOSED STREET LIGHTS

*SEE SHEET 13 FOR DETAIL PLANTING LIST

PLANT MATERIAL

BIOSWALE PLANTING TYPICAL

HELIANTHUS GROSSESERRATUS



ASTER WOODS LIGHT BLUE



CAREX STIPATA



ELYMUS CANADENSIS



SCHIZACHYRIUM SCOPARIUM



LIATRIS SPICATATTT



COLUMNAR TREES

URBAN PINNACLE OAK



ARMSTRONG GOLD MAPLE



KINDRED SPIRIT OAK



REGAL PRINCE OAK



SCALE

1/16" 0 8' 16' 32' 64'

1/16 inch = 1 ft

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net

ENLARGEMENT PLAN
OUTLOT E


DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\IRA — CAD\2019\1913 — Hoover Estate\Master Plan\Sheets\L1.07 Enlargement Plan Outlot E.dwg

PROJECT No. 18557



LEGEND

- PROPERTY LINE
- EXISTING TREE TO REMAIN WITH TAG NUMBER
- PROPOSED STREET TREES
- PROPOSED SHADE TREES
- PROPOSED COLUMNAR TREES
- PLANTING MIX
- S.O.D
- PROPOSED CONTOUR LINES

*SEE SHEET 13 FOR DETAIL PLANTING LIST

SCALE
1/8" 0 4' 8' 16' 32'
1/8 Inch = 1 ft

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IGCONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net


ENTRANCE ENLARGEMENT PLAN
DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS


COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA -- CAD\2019\1813 -- Hoover Estate\Master Plan\Sheets\L1.08 Entrance Enlargement Plan.dwg

PROJECT No. 18557




1 TYPICAL METAL ORNAMENTAL FENCE
SCALE: NTS



2 TYPICAL BOARD ON BOARD FENCE
SCALE: NTS

NOTE: SEE CIVIL PLANS FOR
TRANSFORMER LOCATIONS



3 TYPICAL TRANSFORMER LANDSCAPE PLANTING
SCALE: NTS

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net

SITE DETAILS
DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020
FIRM NO. 184-001330


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.


S:\JRA -- CAD\2019\1913 -- Hoover Estate\Master Plan\Sheets\L2.00 Site Details.dwg

PROJECT No.
18557


Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217




1 COLUMNAR TREE PLANTING DETAIL SECTION I
SCALE: 1/4" = 1'-0"



2 COLUMNAR TREE PLANTING DETAIL SCECTION G
SCALE: 1/4" = 1'-0"



3 SECTION THROUGH BIOSWALE @ SECTION I
SCALE: 1/4" = 1'-0"



4 SECTION THROUGH PARKWAY TYP.
SCALE: 1/4" = 1'-0"

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO


IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net

SITE SECTIONS
DESIGN: B.J. DRAFTING: D.O.
SCALE: 1"=40' DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.
S:\JRA — CAD\2019\1913 — Hoover Estate\Master Plan\Sheets\L2.01 Site Sections.dwg

PROJECT No. 18557




NOTES:

- PRIOR TO MEASURING CALIPER OF NURSERY GROWN TREES, SCRAPE BACK SOIL WHICH MAY BE ON STRUCTURAL ROOTS. EXPOSE ROOT FLARE IF POSSIBLE. TREES UNDER 3" IN CALIPER MAY NOT HAVE EVIDENT ROOT FLARE.
- DEPTH OF ROOT FLARE OR STRUCTURAL ROOTS MAY BE LOCATED USING A METAL PROBE.
- TREE SHALL EXHIBIT A WELL BALANCED HEAD W/ STRONG LATERAL BRANCHING REPRESENTATIVE OF THE SPECIES.
- LATERAL BRANCHING TO BE STRONG AND 360° AROUND.

FOR TREES UP TO AND INCLUDING 4" CALIPER, MEASURE 6" ABOVE TOPMOST STRUCTURAL ROOTS. FOR TREES ABOVE 4" CALIPER, MEASURE 12" ABOVE THE ROOT FLARE.

FINISHED BALL DIAMETER SHALL CONFORM TO MINIMUM ANSI Z60.1 STANDARDS OR GREATER DUE TO SPECIFIC WEATHER OR GROWING CONDITIONS. TYPICAL 11"/CALIPER INCH MINIMUM.

1 TREE PLANTING DETAIL
SCALE: 3/8" = 1'-0"



DIAMETER OF BALL SHALL BE 11"/CAL OR GREATER, DUE TO SOIL OR SEASONAL CONDITIONS.

BALL DIAMETER IS MEASURED AT WIDEST DIMENSION OF BALL AFTER EXCESS SOIL HAS BEEN REMOVED FROM ABOVE STRUCTURAL ROOTS.

LANDSCAPE ARCHITECT AND/ OR LANDSCAPE CONTRACTOR SHALL VERIFY HOW OR IF TREES HAVE BEEN ROOT PRUNED.


TOP OF ROOT BALL / ROOT FLARE NOT ALWAYS PRESENT ON TREES LESS THAN 2 1/2" CAL.

SHOULDER OF ROOT BALL

"STRUCTURAL ROOTS" - ROOTS WITHIN THE SHOULDER OF THE ROOT BALL

SIDE ANGLE OF BALL BETWEEN 21°-30°

2 SECTION THROUGH ROOT BALL
SCALE: 3/8" = 1'-0"



NOTES:

- SPECIFIED TURN BUCKLE, GUY CABLE, AND WIRE. NOTE SUPPORT APPURTENANCES TO BE USED ONLY IF TREE FAILS TO REMAIN PLUMB.
- USE OF LOW PROFILE BASKET WILL PERMIT BASKET BURLAP AND TWINE TO REMAIN INTACT THROUGH 1 YR GUARANTEE PERIOD.
- IT SHALL BE THE RESPONSIBILITY OF THE INSTALLING LANDSCAPE CONTRACTOR TO CONFIRM AND ATTEST THAT THE BURLAP ON THE TOP OF THE BALL AND TWINE HAS BEEN REMOVED AND/OR DETERIORATED AT THE END OF THE GUARANTEE PERIOD. IF BURLAP AND TWINE REMAIN, IT SHALL BE REMOVED.
- NO SYNTHETIC BURLAP OR TWINE SHALL BE PERMITTED.
- NO MULTIPLE LAYERS OF BURLAP OR TWINE SHALL BE PERMITTED OUTSIDE TREE BASKET.
- LIFT TREE FROM BOTTOM OF ROOT BALL USING EITHER BALL CHAIN AND/OR STRAPS. DO NOT LIFT TREE BY WIRES OF BASKET OR TRUNK.
- KEEP TREE IN A PLUMB AND STRAIGHT POSITION THROUGHOUT ESTABLISHMENT PERIOD. ADD SPECIFIED CABLE SUPPORTS ONLY IF TREE DOES NOT REMAIN PLUMB.

MULCH ENTIRE PLANT PIT WITH 3" OF TRIPLE GROUND HARDWOOD BARK. KEEP MULCH A MINIMUM OF 6" AWAY FROM TRUNK AND ROOT FLARE.


SHOULDER OF ROOT BALL

SPECIFIED PLANTING MIX

ROUGHEN SIDES OF PIT

SET BALL ON STABLE SUBGRADE TO MINIMIZE SETTLEMENT

3 SHADE TREE PLANTING WITH LOW PROFILE BRACKET
SCALE: 3/8" = 1'-0"



FOR CONTAINER SHRUBS: GENTLY REMOVE PLASTIC CONTAINER BEFORE PLANTING BEING CAREFUL TO KEEP ROOT SYSTEN INTACT.

TRIANGULATE SHRUBS IN MASS PLANTING UNLESS OTHERWISE DIRECTED BY LANDSCAPE ARCHITECT

IF DIRECTED BY LANDSCAPE ARCHITECT, PRUNE SHRUBS AFTER PLANTING. RETAIN NATURAL CHARACTER AND GENERAL SHAPE OF SHRUB.

SET CROWN OF SHRUBS SO AFTER SETTLEMENT OF SOIL AROUND BALL, THE TOP OF THE BALL IS 1" ABOVE THE ADJACENT FINISHED GRADE. DO NOT PILE EXCESS SOIL FROM PLANTING OPERATIONS AROUND AND UP ON ROOT ZONE.


SET SHRUBS PLUMB AND STRAIGHT

2" DEPTH LAYER TRIPLE GROUND HARDWOOD BARK MULCH

SPECIFIED SOIL MIX, SEE NOTES

EXISTING SUBGRADE


4 SHRUB PLANTING DETAIL
SCALE: 1" = 1'-0"




NOTES:

- LOCATE TOP OF ROOT BALL AND ROOT FLARE 2" ABOVE FINISHED GRADE, DEPENDING ON TREE SIZE AND SITE CONDITIONS.
- SUPPORT APPURTENANCES TO BE USED ONLY IF TREE FAILS TO REMAIN PLUMB.
- PRUNE TREES AFTER PLANTING AND AT DIRECTION OF THE LANDSCAPE ARCHITECT.


5 COLUMNAR TREE PLANTING DETAIL TYPICAL
SCALE: 3/8" = 1'-0"



6 DRUM LACING DETAIL
SCALE: 1/2" = 1'-0"



7 LOW PROFILE PACKAGE
SCALE: 1/2" = 1'-0"



8 PERENNIAL PLANTING DETAIL
SCALE: 1" = 1'-0"

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net

PLANTING DETAILS

DESIGN: B.J. DRAFTING: D.O.

SCALE: 1"=40' DATE: 02-21-2020

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\IRA --- CAD\2019\19-13 --- Hoover Estate\Master Plan\Sheets\L3.00 Planting Details.dwg

PROJECT No. 18557

PLANTING GENERAL NOTES:

1. PROVIDE ALL SHADE TREES AS SPECIMEN QUALITY, WELL MATCHED, WELL SHAPED, LIMBED UP 7'-0" MIN. ABOVE GROUND UNLESS NOTED OTHERWISE ON DRAWINGS.
2. ALL DEPOSITS AND DOWN PAYMENTS FOR PLANT MATERIAL SHALL BE THE RESPONSIBILITY OF THE LANDSCAPE CONTRACTOR.
3. PRIOR TO MEASURING CALIPER AND CLEAR TRUNK HEIGHT, NURSERY MUST REMOVE ANY EXCESS SOIL, WHICH MIGHT BE PLACED UPON THE TOP OF THE STRUCTURAL ROOTS.
4. BALL SIZE SHALL FOLLOW, AT A MINIMUM, THE ANSI 2010 SPECIFICATIONS BUT PREFERABLY 11" WIDTH FOR EVERY 1" OF CALIPER AND 2/3 DEPTH OF THE BALL DIAMETER. SEASONAL DIGGING AND SPECIFIC WEATHER CONDITIONS MAY REQUIRE UNIQUE DIGGING PROCEDURES. LANDSCAPE CONTRACTOR IS TO COORDINATE DIGGING AND HANDLING OF TREES BASED ON SEASONAL REQUIREMENTS.
5. IF TREES ARE MECHANICALLY DUG, "LOW PROFILE" BASKETS MUST BE USED. TREES MAY BE SUPPLIED IN "HIGH PROFILE" BASKETS IF THE FOLLOWING TASKS ARE PREFORMED AFTER SETTING TREE IN THE PLANTING PIT. ALL TOP LOOPS AND RINGS EXTENDING OVER THE SHOULDER OF THE BALL SHALL REMOVED AND THE TOP OF BALL ROPES SHALL BE RETIED TO THE BASKET.
6. ALL TREES LABELED "SPRING DIG ONLY" SHALL BE DUG IN THE NURSERY AT THE MOST HORTICULTURALLY APPROPRIATE TIME (I.E. PRIOR TO LEAF OUT) AND HELD AT THE NURSERY UNTIL DELIVERY TO THE SITE FOR PLANTING. IF THE SITE IS NOT READY FOR "SPRING ONLY" PLANTS.
7. NOTIFY LANDSCAPE ARCHITECT IF PRE-DUG TREES AND OTHER PLANTING MATERIAL CANNOT BE PLANTED IN SEASONAL CONDITIONS AS OUTLINED IN SPECIFICATIONS. LANDSCAPE CONTRACTOR WILL PAY ALL ASSOCIATED COSTS TO HOLD AND MAINTAIN TREES AT THE NURSERY UNTIL SEASONAL CONDITIONS PERMIT. PLANTS HELD AT THE NURSERY WILL REQUIRE MAINTENANCE INCLUDING, BUT NOT LIMITED TO, WATERING, SPRAYING FOR INSECTS, MULCHING, AND IF REQUIRED, REWRAPPING OF THE BALL. HOLDING YARD NURSERY WILL KEEP LANDSCAPE ARCHITECT INFORMED AS TO MAINTENANCE TASKS PERFORMED.
8. QUANTITIES OF PLANTS INDICATED ON THE PLANT LIST ARE INCLUDED FOR CONVENIENCE ONLY. IN THE EVENT THAT DISCREPANCIES OCCUR, THE ACTUAL PLANT DESIGNATIONS AS SHOWN ON THE DRAWINGS SHALL GOVERN.
9. TREES SHALL BE SET STRAIGHT AND PLUMB IN THE PLANTING PIT. THE TOP OF THE BALL SHALL BE TWO INCHES (2") ABOVE SURROUNDING FINISHED GRADE. NO STAKING OR GUYING IS ANTICIPATED, HOWEVER IF THE TREE IS UNABLE TO MAINTAIN PLUMB DURING THE GUARANTEE PERIOD THE LANDSCAPE CONTRACTOR SHALL STAKE AND OR GUY THE TREE AS SPECIFIED.
10. LANDSCAPE CONTRACTOR SHALL NOT PLACE PLANTING SOIL ON THE TOP OF THE BALL DURING BACKFILLING OPERATIONS. SISAL TWINE ON THE TOP OF THE BALL SHALL BE LEFT IN PLACE DURING THE GUARANTEE PERIOD. IF NOT FULLY ROTTED SHALL BE REMOVED PRIOR TO FINAL ACCEPTANCE. IT IS THE RESPONSIBILITY OF THE INSTALLING CONTRACTOR TO CUT AND REMOVE ALL BURLAP AND TWINE REMAINING ON TOP OF ROOT BALL AT THE END OF THE GUARANTEE PERIOD.
11. LANDSCAPE CONTRACTOR SHALL KEEP GATOR BAGS FILLED THROUGHOUT PERIODS OF DROUGHT. BAGS SHALL BE REMOVED AT THE END OF GUARANTEE PERIOD.
12. NURSERIES SHALL PROVIDE CERTIFICATION THAT ALL PLANT MATERIAL SUPPLIED FOR THE PROJECT HAVE BEEN GROWN, HARVESTED, SHIPPED, AND HELD PER SPECIFICATIONS.
13. GENERAL CONTRACTOR SHALL PROVIDE INFORMATION ON THE NURSERY OF ORIGIN FOR ALL TREES AND SHRUBS.
14. TREE WRAP TAPE IS TO BE BURLAP SEAMED ALONG BOTH OUTSIDE EDGES, AT LEAST 10 OZ. IN WEIGHT, MINIMUM OF 6" WIDTH, AS SUPPLIED BY GEMPLER'S (800.382.8473). ALL PURPOSE BURLAP IS NOT ACCEPTABLE. BURLAP WRAP TO BE PROVIDED ON FALL INSTALLED TREES.
15. ALL INVASIVE WEEDS OR GRASSES SHALL BE REMOVED FROM TOP OF ROOT BALL PRIOR TO BACKFILLING.

SOIL NOTES:

1. EXCAVATE FILL AND DISPOSE OF EXCESS FILL MATERIAL LEGALLY OFF SITE FOR ALL PLANTERS.
2. REMOVE ALL CONCRETE CHUNKS, STONES, GARBAGE, WOOD, AND OTHER DEBRIS AND CONFIRM THAT SUBGRADE ELEVATIONS HAVE BEEN MET PRIOR TO INSTALLING PLANTING SOIL MIX.
3. SOIL MIX AT CENTER OF PARKWAY PLANTINGS SHALL BE MOUNDED 4" ABOVE CURB AT CENTER OF PARKWAY. SOIL MIX DEPTH FOR TREES SHALL BE TO BOTTOM OF ROOTBALL WHICH MAY BE 30-36" TOTAL DEPTH, DEPENDING ON ACTUAL SIZE OF ROOTBALL.
4. PLANTING SOIL MIX FOR SODDED AREAS SHALL BE THREE PARTS TOPSOIL, ONE PART SAND AND ONE PART PINE BARK FINES. TOP SOIL MIX DEPTH SHALL BE 6" FOR SOD.
5. ENHANCED PLANTING SOIL MIX FOR TREE PITS AND PLANTERS: 'TERRAVIVA CHATEAU SOIL MIX'. MIXTURE OF SHALE, SAND AND BARK FINES WILL BE PREMIXED BEFORE FINAL MIXTURE WITH TOPSOIL DONE ON SITE.

GENERAL PLANTED BIOSWALE MAINTENANCE AND CARE

1. WATERING: FOR THE FIRST THREE WEEKS AFTER PLANTING, WATER THE BIOSWALE ONCE PER WEEK. IT IS NOT NECESSARY TO WATER DURING A GIVEN WEEK IF ONE INCH OF RAIN ACCUMULATES.
2. WATER THE BIOSWALE DURING PERIODS OF DROUGHT IN MID-SUMMER, IF NEEDED.
3. WEEDING: USING A FIELD GUIDE, IDENTIFY WHAT IS A WEED VERSUS WHAT IS A BIOSWALE PLANT. REMOVE IDENTIFIED WEEDS. TIP: YOU MAY WANT TO MARK BIOSWALE PLANTS WITH A SMALL PLANTING STAKES UNTIL THEY ARE ESTABLISHED.
4. MULCH: UNTIL THE BIOSWALE PLANTS ARE ESTABLISHED, MULCHING THE EDGE / SLOPE OF THE BIOSWALE INTERIOR WILL DISCOURAGE WEED GROWTH AND SOIL EROSION.
5. SEDIMENTATION: IT IS ALWAYS BEST TO PROTECT THE BIOSWALE FROM THE POSSIBILITY OF SILT ENTERING THE BIOSWALE BE DILIGENT, CONDITIONS CHANGE. IF BIOSWALE DOES HAVE SEDIMENT BUILD UP, AN EASY REMEDY IS TO DIG SMALL PITS IN THE SWALE AND REMOVE THE SOIL. OVER TIME THESE WILL NATURALLY FILL IN AND THE PLANTS GROW OVER. THIS IS LESS INVASIVE THAN TRYING TO SKIM OFF LARGER AREAS AND DISTURBS THE PLANT COMMUNITY LESS. IN SEVERE CASE IT MAY BE NECESSARY TO RE-DIG THE ENTIRE BASIN.

LIST OF PRE-APPROVED NURSERIES:

SHADE AND ORNAMENTAL TREES:
1) Doty Nurseries (630) 365-9063
2) Gro Horticultural Enterprises (847) 669-8658
3) Hinsdale Nurseries (630) 323-1411
4) Johnson's Nursery, Inc. (262) 252-4980
5) Kaneville Tree Farms, Inc. (630) 557-2793
6) Mariani Plants (262) 857-6529
7) Spring Grove Nursery (815) 448-2097
8) Wilson Nurseries (847) 683-3700

SHRUBS:
1) Hinsdale Nurseries (630) 323-1411
2) Johnson's Nursery, Inc. (262) 252-4980
3) Mariani Plants (866) 627-4264
4) Midwest Groundcovers (847) 742-1780
5) Wilson Nurseries (847) 683-3700

PERENNIALS & BULBS:
1) Hinsdale Nurseries (630) 323-1411
2) Hoffie Nursery (815) 923-2518
3) Johnson's Nursery, Inc. (262) 252-4980
4) Klehm's Song Sparrow Farm and Nursery (608) 883-2356
5) Mariani Plants (866) 627-4264
6) Midwest Groundcovers (847) 742-1780
7) Possibility Place Nursery (708) 534-3988
8) Twixwood Nursery (269) 471-7408

WATER DISTRIBUTION GENERAL NOTES:

1. FIELD LOCATE ALL UTILITIES A MINIMUM OF 48 HOURS PRIOR TO THE START OF CONSTRUCTION. FOR UTILITY LOCATION CALL DIGGER AT (1-312-744-7000). ANY DISCREPANCIES WITH THE DRAWING SHALL BE REPORTED TO THE ARCHITECT OF RECORD IMMEDIATELY.
2. HOSE BIBS SHALL BE LOCATED TO ENSURE ALL LANDSCAPE AREAS HAVE ADEQUATE WATER SUPPLY FOR PLANT ESTABLISHMENT. WATER TRUCK IS ACCEPTABLE DURING CONSTRUCTION.
3. THE IRRIGATION SYSTEM SHOULD HAVE 55 TO 60 LBS OF STATIC PRESSURE PRIOR TO ANY IRRIGATION EQUIPMENT AND BACKFLOW PREVENTOR BEING INSTALLED. 40 PSI IS THE MINIMUM WATER SUPPLY REQUIRED AT THE POINT OF CONNECTION AT THE DOWNSTREAM SIDE OF THE BACKFLOW PREVENTOR. CONTRACTOR TO PROVIDE A BOOSTER PUMP ASSEMBLY IF NEEDED TO MAINTAIN PRESSURE AND PROVIDE PROPER OPERATION.

TREE PROTECTION NOTES:

1. CONSTRUCTION FENCING IS TO BE INSTALLED AS SHOWN ON DOCUMENTS SO AS TO PROTECT TREES DURING CONSTRUCTION. FENCING SHALL NOT BE REMOVED DURING CONSTRUCTION NOR SHALL CONSTRUCTION MATERIALS BE LOCATED WITHIN THE PROTECTION FENCING ENCLOSURE.
2. EXISTING CONDITIONS SHOWN OF THE DRAWINGS MAY NOT BE AN EXACT REPRESENTATION OF THE CONDITIONS THE CONTRACTOR MAY ENCOUNTER. THE OWNER, ENGINEER AND LANDSCAPE ARCHITECT SHALL NOT BE RESPONSIBLE FOR INTERPRETATIONS AND CONCLUSIONS DRAWN THEREFROM.
3. CONTRACTOR SHALL COMPLETELY REMOVE AND LEGALLY DISPOSE, OFF SITE, OF ALL VEGETATION LABELED TO BE REMOVED. ALL GREEN ASH TREES SHALL BE REMOVED AND DISPOSED ACCORDING TO ILLINOIS CODES.
4. IF CONSTRUCTION IS TO OCCUR WITHIN THE ROOT ZONE TREES LABELED "TO REMAIN", CONTRACTOR SHALL PERFORM PLANT CARE, AND CROWN REDUCTION PRUNING TO COMPENSATE FOR LOSS OF ROOTS. CONSTRUCTION WITHIN THE ROOT ZONE OF TREES "TO REMAIN" SHALL BE ADDRESSED BY ROOT PRUNING, AUGURING OR AIR SPADING, AS NEEDED. ALL SUCH WORK TO BE DONE WITH THE CONSULTATION/SUPERVISION OF A CERTIFIED ARBORIST.
5. CONTRACTOR SHALL REPLACE ALL PLANTS "TO REMAIN" INCLUDING THOSE WITH MAJOR BRANCHES BROKEN± TRUNKS DAMAGED, OR HAVE DIED AS A RESULT OF CONSTRUCTION TAKING PLACE IN THEIR ROOT ZONES.

VILLAGE CODE
PRIORITY ONE TREES
FOR EACH PRIORITY ONE TREE, THE VILLAGE ARBORIST SHALL DETERMINE WHETHER THE CUTTING OR DESTRUCTION OF THE PRIORITY ONE TREE CAN BE AVOIDED BY A REASONABLE MODIFICATION TO THE TREE IMPACT ACTIVITY.

1801 Green Bay Road : Plant Schedule

Key	Totals	Botanical Name	Common Name	Size and Root	Spacing	Comments
SHADE TREES						
ATM	14	Tilia americana 'McKSentry'	American Sentry® linden	6" cal.	on plans	spring dig only, specimen selected
QBS	13	Quercus bicolor	Swamp White Oak	6" cal.	on plans	spring dig only, specimen selected
ARR	8	Acer rubrum 'Redpointe'	Redpointe' Red Maple	6" cal.	on plans	spring dig only, specimen selected
ARR	6	Acer rubrum 'Redpointe'	Redpointe' Red Maple	5" cal.	on plans	spring dig only, specimen selected
ARR	2	Acer rubrum 'Redpointe'	Redpointe' Red Maple	4" cal.	on plans	spring dig only, specimen selected
KCT	12	Gymnocladus dioicus 'espresso'	Kentucky Coffee tree	6" cal.	on plans	spring dig only, specimen selected
KCT	1	Gymnocladus dioicus 'espresso'	Kentucky Coffee tree	5" cal.	on plans	spring dig only, specimen selected
UAP	15	Ulmus americana 'Princeton'	Princeton Elm	6" cal.	on plans	spring dig only, specimen selected
UAP	1	Ulmus americana 'Princeton'	Princeton Elm	5" cal.	on plans	spring dig only, specimen selected
ARM	20	Acer x freemanii 'Armstrong Gold'	Armstrong Gold Maple	6" cal.	on plans	spring dig only, specimen selected
RPO	6	Quercus × warei 'Long'	Regal Prince Oak	6" cal.	on plans	spring dig only, specimen selected
QWK	14	Quercus x warei 'Nadler'	Kindred Spirit Hybrid Oak	6" cal.	on plans	spring dig only, specimen selected
QMP	6	Quercus macrocarpa 'JFS-KW3' PP 22815	Urban Pinnacle® Bur Oak	6" cal.	on plans	spring dig only, specimen selected
CBF	14	Carpinus betulus 'Frans Fontaine'	Columnar Hornbeam	6" cal.	on plans	spring dig only, specimen selected
CBF	14	Carpinus betulus 'Frans Fontaine'	Columnar Hornbeam	5" cal.	on plans	spring dig only, specimen selected
QRS	17	Quercus robur x alba 'JFS-KW1QX'	Streetspire Oak	6" cal.	on plans	spring dig only, specimen selected
PAE	8	Platanus acerifolia 'Morton Circle'	Exclamation London Planetree	6" cal.	on plans	spring dig only, specimen selected
RB	4	Betula nigra 'Fargo"	River Birch Fargo Multi stem	5" cal.	on plans	spring dig only, specimen selected
LTA	8	Liriodendron tulipifera 'Arnold'	Tulip Tree	5" cal.	on plans	spring dig only, specimen selected
SSM	6	Acer miyabei 'Morton'	State Street Miyabe's maple	6" cal.	on plans	spring dig only, specimen selected
SHRUBS						
HTS	29	Hydrangea serrata 'Mak20'	Hydrangea tuff stuff	#5/ 36"x36"	on plans	specimen quality
SBT	on plan	Spiraea betulifolia 'Tor'	Tor Spirea	#5/ 36"x36"	on plans	plant 15 /trasformer
PLANTING MIX						
Mix A (205 sft)						
Spring		Actaea racemosa	Black cohosh			
		Narcissus 'King Alfred'	Trumpet daffodil			
Summer		Begonia Dragon Wing® Pink	Begonia Pink	# 4.5	12" oc.	
Fall		Chrysanthemum yellow	Yellow Daisy Mums	#1 gal	12"oc.	
Winter		Evergreen Boughes				
Mix B (1205 sft)		Allium 'Chivette'	Chives	#1qt		
		Rudbeckia 'American Gold Rush'	Black-eyed Susan	#1qt		
		Pennisetum alopecuroides 'Ginger Love'	Fountain grass	#1qt		
		Lobelia siphilitica	blue cardinal flower	#1qt		
		Amsonia 'blue star'		#1qt		
		Hosta Thread grass		#1qt		

NOTE: 189 TREES PLANTED TOTALING TO 1096 CALIPER INCHES

NOTE: "SPECIES OF TREES MAY BE SUBSTITUTED AS AVAILABILITY ALLOWS"
"ALL VARIETIES SHALL BE TREES ON THE APPROVED VILLAGE LIST"

1801 Green Bay Road : Plant Schedule	
BIOSWALE (5315 SQF)	
Botanical Name	Common Name
Agropyron elongatum	Tall Wheatgrass
Alisma subcordatum	American Water Plantain
Symphyotrichum lanceolatum	Aster lanceolatus
Bidens cernua	Nodding Beggarticks
Bouteloua hirsuta	Hairy Grama
Carex stipata	Awlfruit Sedge
Carex vulpinoidea	Fox sedge
Eleocharis obtusa	Blunt spikerush
Elymus canadensis	Canada Wild Rye
Pascopyrum smithii	Western Wheatgrass
Helianthus grosseserratus	Sawtooth Sunflower
Panicum virgatum	Switchgrass
Schizachyrium scoparium	Little Bluestem
Bolboschoenus fluviatilis	River Bulrush
Schoenoplectus tabernaemontani	Softstem Bulrush
Spartina pectinata	Prairie Cordgrass
Verbena hastata	American blue vervain
Eleocharis erythropoda	Bald Spikerush
Solidago sempervirens	Seaside Goldenrod
Juncus effusus	Common Rush

1801 Green Bay Road : Plant Schedule
LOW MOW GRASS (SEED TYPE)
Common Name
Janeston Chewing Fescne
Quatro Sheep Fescue
Sealink Slender Fescue
Sword Hard Fescue
Aurora Fescue
Kent Creeping Red Fescue
*plant in early spring at the rate of 10 lbs/1000sf

Jacobs/Ryan Associates
Landscape Architects
1527 North Sandburg Terrace Chicago, Illinois 60610 (312) 664-3217

REVISIONS

DATE	DESCRIPTION	DRAWN BY
2-21-20	ISSUE FOR REVIEW	DO
4-17-20	PER VILLAGE COMMENTS	DO
6-8-20	PER VILLAGE COMMENTS	DO

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE, WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net

PLANTING DETAILS

DESIGN: B.J. | DRAFTING: D.O.
SCALE: 1"=40' | DATE: 02-21-2020
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

S:\JRA -- CAD\2019\1913 -- Hoover Estate\Master Plan\Sheets\L3.01 Planting Notes.dwg

PROJECT No. 18557

TREE REMOVAL & PRESERVATION PLAN

1801 GREEN BAY ROAD

GLENCOE, ILLINOIS

2019


LEGEND

EXISTING		PROPOSED
	STORM SEWER	
	SANITARY SEWER	
W W	WATER MAIN	
	GAS MAIN	
	ELECTRIC LINE (BURIED)	
OHW OHW OHW OHW	OVERHEAD ELECTRIC,	
	SANITARY MANHOLE	
	STORM MANHOLE	
	STORM CATCH BASIN	
	UTILITY MANHOLE	
T	TELEPHONE/UTILITY PEDESTAL	
	STORM INLET	
	UTILITY POLE	
	FIRE HYDRANT	
	VALVE VAULT	
	STREET LIGHT	
TR	TRANSFORMER	
	ELECTRIC PEDESTAL	
	EDGE OF PAVEMENT	
	CURB & GUTTER	
	DRAINAGE FLOW	
	EMERGENCY OVERLAND FLOW ROUTE	
× 691.18	SPOT GRADE	
	TOP OF CURB ELEVATION	
	TOP OF PAVEMENT ELEVATION	
	TOP OF FOUNDATION ELEVATION	
	ROOT PRUNING	
	STAKED SILT FENCE	
x x	TREE PROTECTION FENCE	
	CONSTRUCTION FENCE	

THE CONTRACTOR MUST CALL J.U.L.I.E FOR THE LOCATION AND STAKING OF EXISTING UNDERGROUND UTILITIES (GAS, ELECTRIC, TELEPHONE, ETC.) AT 1-800-892-0123 48 HOURS PRIOR TO DIGGING.

VILLAGE CONSTRUCTION HOURS OF 7AM-6PM M-F, 9AM-6PM SATURDAY AND NO WORK ON SUNDAYS OR HOLIDAYS.

LOCATION MAP



SECTION 1, TOWNSHIP 42 N, RANGE 12 E

NOTE:
EXISTING WATER, SANITARY SEWER AND STORM SEWER INFORMATION IS BASED ON RECORDS PROVIDED BY THE MUNICIPALITY AND SURVEY DATA DETERMINED BY IG CONSULTING, INC. CONTRACTOR MUST VERIFY LOCATIONS, DEPTHS, MATERIALS AND POTENTIAL CONFLICTS PRIOR TO BIDDING AND CONSTRUCTING THE PROPOSED IMPROVEMENTS. SUCH VERIFICATION SHALL ALSO INCLUDE FACILITIES OWNED AND OPERATED BY VARIOUS UTILITY COMPANIES. ENGINEER MAKES NO REPRESENTATION AS TO THE ACCURACY OR EXISTENCE OF PLAN INFORMATION PROVIDED BY OTHERS.

INDEX

1 – COVER SHEET
2 – EXISTING CONDITIONS
3 – TREE INVENTORY & SPECIFICATIONS
4 – TREE INVENTORY & SPECIFICATIONS
5 – TREE REMOVAL PLAN
6 – TREE PRESERVATION PLAN
7 – CONSTRUCTION STANDARDS

ALL ROADWAY CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND ALL AMENDMENTS THERETO AS ADOPTED BY THE STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION (I.D.O.T.).

STORM SEWER, SANITARY SEWER AND WATER MAIN CONSTRUCTION SHALL CONFORM TO THE STANDARD SPECIFICATIONS FOR WATER AND SEWER MAIN CONSTRUCTION IN ILLINOIS, LATEST ISSUE, AND THE VILLAGE OF GLENCOE SUBDIVISION AND ENGINEERING GUIDE, INCLUDING THE LATEST CONSTRUCTION DETAILS, WHICHEVER IS MORE STRINGENT.

VILLAGE BENCHMARK #296:
NORTHWEST BOLT OF FIRE HYDRANT AT SOUTHWEST CORNER OF WESTLEY ROAD AND FAIRFIELD ROAD, 200'± WEST OF GREENBAY ROAD.
ELEVATION= 646.11

SITE BENCHMARK:
NORTHEAST BONNET BOLT OF FIRE HYDRANT AT THE NORTHEASTERLY CORNER OF #1799 GREENBAY ROAD
ELEVATION = 690.27 NAVD 88 (GEOID12B)

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

COVER SHEET | DESIGN: K.C.L. | DRAFTING: S.R.M | SCALE: NONE | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\01\18\18557\Eng\18557-ts.dwg

PROJECT No. 18557

ZONE R-A
FOREST PRESERVE
TURNBULL WOODS

ZONE R-A
FOREST PRESERVE
COUNTY CLERK'S DIVISION

ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT

LOT B #431
LOT C #423
LOT D #415
#403
LOT F
#409
LOT E
#424
LOT 1
#414
NORTH GATE MANOR 1st ADDITION
DOC. 16986011
#406
NORTH GATE SUBDIVISION
DOC. 18523477
LOT I
LOT H
LOT G

NORTHWOOD DRIVE

N89°52'17"W 568.00'(D&M)

S00°01'20"E 350.60'(D&M)

S89°41'06"W 382.30'(R&M)

S44°49'53"W 18.36'(R&M) 18.36'(M)

N29°32'10"W 180.14'(M)

191.15'(R&M) N54°46'45"E

159.42'(R&M) S21°40'18"E

R=540.69' A=27.00'(M)

R=175.90' A=49.30'(M)

R=25.00' A=35.67'(M) N51°59'13"E 69.01'(R&M)

R=540.69' A=36.47'(M)

164.80'(R&M) N50°31'11"W

627.81'(M) N89°41'06"E

780.38'(R&M) N00°01'20"W

PARCEL 1

UNSUBDIVIDED

ZONE R-A
GLENCOE GOLF CLUB

WESTLEY ROAD

GREEN BAY ROAD

ODH'S SUBDIVISION
DOC. 12390488

LOT 4 LOT 3 LOT 2 LOT 1

LOT 8 LOT 9 LOT 10 LOT 11 LOT 12 LOT 13 LOT 14 LOT 15 LOT 16

#1214 #1212 #1206 #1201 #1200 #1194 #1188 #1182 #1178

CAROL LANE

DUNAS FOREST CREST SUBDIVISION
DOC. 6457807

INCLUDED PARCEL 1

ADDITIONAL WETLAND FLAGGING LOCATED 04/01/2020

WETLAND FLAGGING LOCATED 10/29/2019

WETLAND FLAGGING LOCATED 10/23/2019

5 FT. PUBLIC UTILITY EASEMENT PER DOCUMENT R134411 & 7571980 TO BE VACATED

20 FT. EASEMENT TO BE VACATED

NORTH LINE OF THE SOUTH 6.23 CHAINS (411.18 FEET) OF THE NORTHEAST QUARTER OF SECTION 1-42-12

414.18 FEET NORTH OF AND PARALLEL TO THE SOUTH LINE OF THE NORTHEAST QUARTER OF SECTION 1-42-12

SITE BENCHMARK:
NLE BONNET BOLT ON FIRE HYDRANT.
ELEVATION=690.27 NAVD88 (GEOID12B)

TREE LEGEND

- EXISTING TREE 8 INCHES AND GREATER
- HIGH VALUE TREES
- EXISTING TREES 6 AND 7 INCHES

SCALE
40 0 20 40 80 160
(IN FEET)
1 inch = 40 ft.

EXISTING CONDITIONS

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/20/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/05/20	FOR SUBMITTAL	S.R.M.
02/19/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

EXISTING CONDITIONS | DESIGN: K.C.L. | DRAFTING: S.R.M. | SCALE: 1"=40' | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\18557-4P.dwg

PROJECT No. 18557

Tag No.	Size (")	Common Name	Village Code classification	Cond	Form	Action Code	Notes
1201	18	Black Locust		3	2		
1202	7	Black Cherry	R	6	6	X	Dead
1203	18	Ash	R	6	6	X	Topped at 10'
1204	17	Black Locust		2	2		
1205	6	Buckthorn	R	3	3	X	
1206	9	Black Locust		2	3		
1207	7	Buckthorn	R	3	3	X	
1208	18	Shagbark Hickory	HR	4	4	X	Trunk Rot
1209	20	Siberian Elm		4	3	X	Encroaching onto nearby tree
1210	7	Ash	R	6	6	X	Dead
1211	8	Ash	R	6	6	X	Dead
1212	9	Ash	R	6	6	X	Dead
1213	12	American Elm	H	2	3		
1214	7	American Elm		2	3		
1215	7	Ash	R	6	6	X	Dead
1216	13	Eastern White Pine	H	2	2	RP	
1217	30	White Oak	H	1	1	RP	
1218	14	Ash	R	6	6	X	Dead
1219	14	Buckthorn	R	3	3	X	Multi stem trunk: 7,7
1220	9	Buckthorn	R	4	3	X	Trunk Rot
1221	10	Ash	R	6	6	X	Dead
1222	29	White Oak	H	2	3	RP	
1223	27	White Oak	H	2	2		Trunk rot, basal rot
1224	6	Black Locust		3	4		
1225	15	Linden	HR	5	3	X	Trunk rot, basal rot
1226	9	Buckthorn	R	3	4	X	
1227	6	Buckthorn	R	5	5	X	Girdled roots
1228	15	Black Locust		2	2		
1229	12	Black Locust		2	2		
1230	7	Black Locust		3	3		
1231	14	Eastern White Pine	H	2	2		
1232	17	Eastern White Pine	H	3	3		
1233	10	Eastern White Pine	H	3	4	X	Lean
1234	9	Shagbark Hickory	H	2	2		
1235	6	Hawthorne		5	5	R	
1236	17	Shagbark Hickory	H	2	3	R	
1237	7	Ash	R	6	6	X	Dead
1238	18	Buckthorn	R	3	3	X	Multi stem trunk: 18" at base
1239	31	White Oak	H	3	2		
1240	16	Eastern White Pine	HR	3	5	R	Lean > 40°
1241	25	Ash	R	6	6	X	Topped at 15' dead
1242	19	Northern Red Oak	HR	4	4	R	Multi stem trunk: 10,9 Dead
1243	7	Buckthorn	R	3	3	X	
1244	16	Black Locust		2	2		
1245	15	Black Locust		3	3		
1246	13	American Elm	H	3	3		
1247	7	Walnut		1	1		
1248	8	Shagbark Hickory	H	1	2		
1249	21	Shagbark Hickory	H	1	1		
1250	12	Dogwood		2	2		Multi stem trunk: 6,6
1251	31	White Oak	H	1	1		
1252	38	White Oak	H	2	2		
1253	22	White Oak	H	2	2		
1254	23	White Oak	H	2	3		
1255	30	Northern Red Oak	H	1	3		
1256	20	White Oak	H	2	2		
1257	19	White Oak	H	2	2		
1258	26	White Oak	H	2	2		
1259	31	White Oak	H	2	2		
1260	19	Red Pine		2	2	R	
1261	16	Red Pine		2	3	R	
1262	17	Eastern White Pine	H	3	3	R	
1263	37	Burr Oak	HR	3	3	X	Trunk Rot
1264	8	Fir		3	3		
1265	21	Shagbark Hickory	H	1	1		
1266	44	Swamp White Oak	H	3	2	RP	Old lightning strike
1267	22	Shagbark Hickory	H	1	1		
1268	18	Shagbark Hickory	H	1	1	RP	
1269	18	Shagbark Hickory	H	1	1		
1270	40	Swamp White Oak	H	1	1		
1271	38	White Oak	HR	3	2	X	Fruiting bodies along root zone
1272	15	White Poplar	R	2	3		
1273	40	Swamp White Oak	HR	4	3	R	Basal rot
1274	34	White Poplar	R	2	3	R	
1275	17	Eastern White Pine	H	2	3	R	
1276	21	Eastern White Pine	H	2	2	R	
1277	13	Crabapple		3	3		Multi stem trunk: 10,9,6
1278	7	Magnolia		2	3	R	
1279	14	Dead/Dying	R	6	6	X	
1280	13	Dead/Dying	R	6	6	X	
1281	14	Sugar Maple	H	2	3		
1282	11	Eastern Red Cedar		3	3		
1283	11	Eastern Red Cedar		3	3		
1284	7	Eastern Red Cedar		3	3		
1285	16	Eastern Red Cedar		3	3		Multi stem trunk: 6,9
1286	12	Sugar Maple	H	2	3	R	
1287	7	American Elm		3	4	R	
1288	7	Sugar Maple		2	3	R	
1289	14	Sugar Maple	H	2	2	R	
1290	7	Sugar Maple		2	3	R	
1291	7	Sugar Maple		3	3	R	
1292	32	White Oak	H	5	3	RP	
1293	16	Norway Spruce		2	3		
1294	20	Shagbark Hickory	H	2	2		
1295	24	Shagbark Hickory	H	2	2		
1296	6	Ornamental Cherry		1	1		
1297	18	Buckthorn	R	3	3	X	Multi stem trunk: 18" at base
1298	10	Buckthorn	R	3	3	X	
1299	32	White Oak	H	1	2	R	
1300	31	Northern Red Oak	H	2	2	R	
1301	25	Sugar Maple	H	2	2	R	
1302	7	Sugar Maple		2	3	R	
1303	10	Sugar Maple	H	2	4	R	Trunk Damage
1304	7	Sugar Maple		2	3	R	
1305	7	Sugar Maple		3	3	R	
1306	11	Sugar Maple	H	3	3	RP	
1307	54	American Elm	H	2	3	RP	Multi stem trunk: 20,19,15 Included Bark
1308	26	Swamp White Oak	H	1	1	RP	
1309	25	Sugar Maple	H	3	3	R	Multi stem trunk: 25" at base
1310	18	Shagbark Hickory	H	2	3		
1311	23	White Oak	H	2	2		
1312	11	Sugar Maple	H	3	3	RP	

Tag No.	Size (")	Common Name	Village Code classification	Cond	Form	Action Code	Notes
1313	7	Birch		3	3		
1314	10	Sugar Maple	H	3	4		
1315	9	Sugar Maple	H	3	4		
1316	33	Swamp White Oak	H	2	2	R	
1317	18	White Oak	H	2	2		
1318	21	White Oak	H	2	3	R	
1319	24	White Oak	H	1	1	R	
1320	19	Swamp White Oak	H	2	2	RP	
1321	7	Sugar Maple		2	2		
1322	8	Northern Red Oak	H	2	3		
1323	15	White Oak	H	2	1		
1324	19	Northern Red Oak	H	2	3		
1325	15	White Oak	H	2	3		
1326	10	Northern Red Oak	H	3	2		
1327	9	Northern Red Oak	H	1	1		
1328	10	Northern Red Oak	H	2	3		
1329	28	Swamp White Oak	H	1	1		
1330	9	American Elm	H	3	3		
1331	21	Swamp White Oak	H	2	2		
1332	28	Swamp White Oak	H	2	2	RP	
1333	13	Swamp White Oak	H	5	5	R	Canopy damage
1334	31	Swamp White Oak	H	4	2	R	
1335	42	Swamp White Oak	H	2	2	R	
1336	14	Swamp White Oak	H	2	3	R	
1337	29	Swamp White Oak	H	2	2	R	
1338	22	Swamp White Oak	H	2	3	RP	
1339	41	Swamp White Oak	H	2	3	RP	
1340	18	White Oak	H	2	3		
1341	22	White Oak	H	1	2		
1342	17	White Oak	H	2	2		
1343	22	White Oak	H	2	3		
1344	10	Northern Red Oak	H	3	3		
1345	8	Northern Red Oak	H	3	3		
1346	10	Northern Red Oak	H	3	3		
1347	13	Northern Red Oak	H	3	3		
1348	17	Northern Red Oak	H	3	3		
1349	14	Northern Red Oak	H	2	3		
1350	13	Northern Red Oak	H	3	3		
1351	7	Sugar Maple		3	4		
1352	16	Shagbark Hickory	H	2	3	RP	
1353	12	Swamp White Oak	H	2	4	R	
1354	24	Norway Spruce		2	3	R	Multi stem trunk: 13,11
1355	16	Northern Red Oak	H	3	3		
1356	13	Norway Spruce		2	2		
1357	12	Northern Red Oak	H	3	3		
1358	15	Pin Oak	H	2	1		
1359	6	Swamp White Oak		2	3	R	
1360	30	Swamp White Oak	H	1	1	R	
1361	26	Swamp White Oak	HR	5	3	R	Trunk split, trunk rot
1362	21	Swamp White Oak	H	2	3	R	
1363	7	Northern Red Oak		2	3		
1364	24	White Oak	H	1	1		
1365	10	Black Locust		3	4		
1366	11	Swamp White Oak	H	2	3		
1367	16	White Oak	H	2	2		
1368	14	Swamp White Oak	H	1	1		
1369	12	Northern Red Oak	H	2	3		
1370	9	Northern Red Oak	H	2	3		
1371	15	Northern Red Oak	H	2	3		
1372	9	Northern Red Oak	H	2	3		
1373	8	Northern Red Oak	H	2	3		
1374	10	Black Cherry		5	5	X	Lean, basal rot, root zone failure
1375	24	White Oak	H	1	1	RP	
1376	29	Swamp White Oak	H	2	1	RP	
1377	19	Sugar Maple	HR	2	4	R	Lean, girdled roots
1378	16	Northern Red Oak	H	2	2	R	
1379	9	Sugar Maple	H	2	2	R	Root zone failure
1380	30	White Oak	H	1	2		
1381	21	Eastern White Pine	H	2	3		
1382	17	Shagbark Hickory	H	2	3	X	Trunk Damage
1383	24	Shagbark Hickory	H	2	3		
1384	26	Norway Maple		4	5	X	Trunk Rot
1385	43	White Oak	H	2	3	RP	
1386	28	White Oak	H	1	1		
1387	10	Northern Red Oak	H	2	3		
1388	21	White Oak	H	2	2	RP	
1389	18	White Oak	H	1	1	RP	
1390	6	Sugar Maple		2	3	R	
1391	23	Swamp White Oak	H	1	1	R	
1392	22	White Oak	H	2	3	R	
1393	13	White Oak	H	2	1	R	
1394	34	Northern Red Oak	H	2	2	R	
1395	16	White Oak	H	3	3	R	
1396	26	Northern Red Oak	H	2	2	RP	
1397	27	White Oak	H	1	2	RP	
1398	7	Eastern White Cedar		3	3		
1399	28	White Oak	H	2	2		
1400	20	White Oak	H	2	2		
1401	10	Eastern White Pine	H	2	2		
1402	18	White Oak	H	1	1		
1403	22	White Oak	H	2	3		
1404	21	White Oak	H	2	2		
1405	21	White Oak	H	2	3		
1406	28	White Oak	H	3	3		
1407	25	Swamp White Oak	H	2	2		
1408	15	White Oak	H	1	1		
1409	21	White Oak	H	1	1		
1410	25	Northern Red Oak	H	2	3		
1411	16	White Oak	H	2	2		
1412	13	White Oak	H	3	3		
1413	19	White Oak	H	2	2		
1414	19	White Oak	H	2	2		
1415	15	White Oak	H	2	3		
1416	26	White Oak	H	2	2		
1417	13	Norway Maple		3	3		Multi stem trunk: 8.5
1418	17	White Oak	H	3	3		
1419	17	White Oak	H	2	2		
1420	17	White Oak	H	2	3		
1421	18	Catalpa	H	3	3		
1422	14	Northern Red Oak	H	2	3		
1423	16	Northern Red Oak	H	2	3		
1424	23	Norway Maple		1	1		
1425	35	Swamp White Oak	H	2	1		
1426	31	Swamp White Oak	H	2	2		
1427	30	Swamp White Oak	H	2	2		
1428	26	Swamp White Oak	H	2	3		

Tag No.	Size (")	Common Name	Village Code classification	Cond	Form	Action Code	Notes
1429	27	Swamp White Oak	HR	5	3	X	Trunk Rot
1430	7	Shagbark Hickory		2	2	*	
1431	15	Swamp White Oak	H	3	3		
1432	25	Swamp White Oak	H	2	2		
1433	26	Swamp White Oak	H	2	3		
1434	6	Dead	R	6	6	X	
1435	6	Norway Maple		2	3		
1436	10	Norway Maple		3	3		
1437	21	White Oak	H	2	2	RP	
1438	17	White Oak	H	2	2		
1439	17	White Oak	H	2	2		
1488	19	White Oak	H	2	2	RP	
1489	9	Eastern White Pine	H	2	2		
1490	19	Shagbark Hickory	H	2	2	R	
1491	7	Buckthorn	R	3	3	X	
2501	15	White Oak	H	2	2		
2502	26	White Oak	HR	5	3	X	Trunk Rot
2503	11	Northern Red Oak	H	3	3		
2504	14	Black Spruce		1	2		
2505	18	Black Spruce		1	1		
2506	26	White Oak	H	2	2		
2507	14	White Oak	H	2	2		
2508	8	Northern Red Oak	H	3	2		
2509	8	Norway Spruce		2	2		
2510	29	White Oak	H	2	2		
2511	22	White Oak	H	2	3		
2512	22	White Oak	H	2	2		
2513	13	Swamp White Oak	H	3	3		
2514	20	White Oak	H	2	2		
2515	19	White Oak	H	2	2		
2516	6	White Oak		3	3		
2517	24	White Oak	H	2	3		
2518	7	Northern Red Oak		2	3		
2519	10	Northern Red Oak	H	3	3		
2520	14	Northern Red Oak	H	2	2		
2521	16	Northern Red Oak	H	2	2		
2522	14	Northern Red Oak	H	3	3		
2523	19	White Oak	H	3	2		
2524	16	White Oak	H	3	3		
2525	16	Northern Red Oak	H	3	3		
2526	15	White Oak	H	3	3		
2527	7	Northern Red Oak		3	3		
2528	8	Northern Red Oak	H	2	3		
2529	18	White Oak	H	2	3		
2530	6	Northern Red Oak		2	2		
2531	6	Northern Red Oak		2	2		
2532	22	White Oak	H	2	3		
2533	19	Northern Red Oak	H	3	3		
2534	6	Northern Red Oak		3	3		
2535	18	Black Spruce		1	1		
2536	20	White Oak	H	2	2		
2537	12	Northern Red Oak	H	2	3		
2538	23	White Oak	H	2	2		
2539	18	White Oak	H	3	3		
2540	11	Northern Red Oak	H	2	3		
2541	14	Black Spruce		2	1		
2542	10	Dead/Dying	R	6	6	X	
2543	9	Dead	R	6	6	X	High risk tree, overhanging adjacent back yard
2544	6	Buckthorn	R	3	3	X	
2545	10	American Elm	H	3	3		
2546	6	Dead	R	6	6	X	
2547	7	Sugar Maple		2	3		
2548	8	Dead	R	6	6	X	
2549	11	Dead	R	6	6	X	High Risk Tree, Leaning over adjacent front yar
2550	17	Northern Red Oak	H	3	3		
2551	8	Dead	R	6	6	X	
2552	6	Dead	R	6	6	X	
2553	10	Dead	R	6	6	X	
2554	9	Buckthorn	R	3	3	X	
2555	7	Buckthorn	R	3	3	X	
2556	12	Dead	R	6	6	X	High risk, imminent fall barber
2557	8	Dead	R	6	6	X	
2558	10	American Elm	H	3	2		
2559	7	Buckthorn	R	4	5	X	
2560	11	Dead	R	6	6	X	
2561	12	Dead	R	6	6	X	
2562	18	American Elm	H	4	4		Growing into fence
2563	9	Buckthorn	R	3	3	X	
2564	10	Dead/Dying	R	6	6	X	Barber char high risk to property
2565	12	Dead/Dying	R	6	6	X	
2566	7	White Walnut		2	2		
2567	18	Shagbark Hickory	H	2	3		
2568	7	Hawthorne		4	4		Fruiting Bodies on Trunk
2569	8	Shagbark Hickory	H	1	1		
2570	13	Norway Maple		3	3		
2571	11	Norway Maple		3	3		
2572	7	Shagbark Hickory		2	1		
2573	18	Norway Maple		3	3		Multi stem trunk: 10,8
2574	9	Norway Maple		3	3		
2575	7	Norway Maple		3	3		
2576	10	Norway Maple		3	3		
2577	24	Swamp White Oak	H	2	2		
2578	21	Swamp White Oak	H	2	2		
2579	6	Shagbark Hickory		1	1		
2580	29	Swamp White Oak	H	2	2	RP	
2581	11	Black Locust		3	4		
2582	8	Black Locust		3	3		
2583	6	Buckthorn	R	3	3	X	
2584	7	Dead/Dying	R	6	6	X	
2585	7	Dead/Dying	R	6	6	X	
2586	8	Buckthorn	R	6	6	X	Fallen
2587	7	Buckthorn	R	4	3	X	
2588	6	Buckthorn	R	5	3	X	Leaning >30°
2589	8	Dead/Dying	R	6	6	X	
2590	6	Dead/Dying	R	6	6	X	
2591	7	Dead/Dying	R	6	6	X	
2592	6	Buckthorn	R	3	3	X	
2593	8	Buckthorn	R	3	3	X	
2594	11	Buckthorn	R	5	5	X	Trunk Rot
2595	6	Buckthorn	R	4	3	X	
2596	6	Dead/Dying	R	6	6	X	
2597	32	White Oak	H	2	1	RP	
2598	7	Buckthorn	R	3	3	X	
2599	10	Buckthorn	R	4	4	X	Gone
2600	9	Buckthorn	R	4	5	X	Fallen
2601	17	White Oak	H	2	3		

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/19	FOR SUBMITTAL	S.R.M.
02/05/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

TREE INVENTORY & SPECIFICATIONS

DESIGN: K.C.L. | DRAFTING: S.R.M
SCALE: NONE | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\JOBS\18557\Eng\cad\2017\18557-treelist-v2017.dwg

PROJECT No. 18557

Tag No.	Size (")	Common Name	Village Code classification	Cond	Form	Action Code	Notes
2602	6	Boxelder	R	3	3		
2603	28	White Oak	H	2	3		
2604	16	White Oak	H	2	3		
2605	28	Swamp White Oak	H	2	2		
2606	6	Buckthorn	R	3	3	X	
2607	11	Black Locust		3	4		
2608	7	Black Locust		5	5		Trunk rot/leaning
2609	6	Buckthorn	R	3	3	X	
2610	14	White Oak	H	2	2		
2611	23	Swamp White Oak	H	2	3		
2612	7	Buckthorn	R	3	3	X	
2613	10	Norway Maple		2	2		
2614	11	Buckthorn	R	4	4	X	Trimmed to single
2615	8	Buckthorn	R	4	4	X	
2616	7	Buckthorn	R	5	5	X	Topped @ 5'
2617	9	Buckthorn	R	5	5	X	Topped @ 7'
2618	6	Buckthorn	R	3	3	X	
2619	10	Buckthorn	R	4	4	X	
2620	9	Buckthorn	R	4	3	X	
2621	8	Buckthorn	R	3	3	X	
2622	9	Buckthorn	R	4	4	X	
2623	16	Black Locust		4	3	X	Trunk Rot
2624	6	Buckthorn	R	5	5	X	
2625	22	White Oak	H	2	2		
2626	12	Buckthorn	R	4	3	X	Multi stem trunk: 6,6
2627	8	Buckthorn	R	4	3	X	
2628	6	Buckthorn	R	4	3	X	
2629	8	Buckthorn	R	4	3	X	
2630	16	Black Locust		2	2		
2631	6	Buckthorn	R	3	3	X	
2632	6	Buckthorn	R	4	3	X	
2633	18	White Oak	H	2	3		
2634	9	Buckthorn	R	4	3	X	
2635	10	Black Locust		5	4	X	Fruiting bodies at +/- 20'
2636	9	Buckthorn	R	3	3	X	
2637	10	Buckthorn	R	4	3	X	
2638	9	Buckthorn	R	4	3	X	
2639	12	Black Locust	R	6	6	X	Dead, leaning against nearby tree, high risk tree
2640	12	Black Locust	R	6	6	X	Dead/Dying
2641	15	Black Locust		4	3	X	Fruiting Bodies on trunk at 30
2642	11	Black Locust		4	4	X	Trunk Rot
2643	6	Buckthorn	R	3	3	X	
2644	6	Buckthorn	R	4	3	X	
2645	7	Buckthorn	R	3	3	X	
2646	20	Black Locust		2	2		
2647	7	Buckthorn	R	4	3	X	
2648	8	Buckthorn	R	4	4	X	
2649	11	Buckthorn	R	4	4	X	Multi stem trunk: 6,5
2650	12	Buckthorn	R	4	4	X	Multi stem trunk: 8,4
2651	17	Black Locust		4	3		
2652	30	White Oak	H	2	3		
2653	9	Buckthorn	R	4	3	X	
2654	13	Dead	R	6	6	X	High risk tree, leaning tree over entrance
2655	13	Dead	R	6	6	X	
2656	6	Buckthorn	R	3	3	X	
2657	7	Buckthorn	R	3	3	X	
2658	6	Dead	R	6	6	X	
2659	21	Norway Maple		3	3		
2660	13	Black Locust		4	3		
2661	7	Buckthorn	R	3	3	X	
2662	22	Swamp White Oak	H	2	2		
2663	9	Buckthorn	R	3	3	X	
2665	6	Buckthorn	R	3	3	X	
2666	7	Buckthorn	R	3	3	X	
2667	7	Buckthorn	R	5	4	X	Leaning/trunk rot
2668	8	Buckthorn	R	4	3	X	
2669	6	Buckthorn	R	4	4	X	
2670	23	Swamp White Oak	H	2	2		
2671	11	Dead/Dying	R	6	6	X	
2672	14	Buckthorn	R	6	6	X	Multi stem trunk: 9,5 Fallen
2673	7	Buckthorn	R	3	3	X	
2674	23	White Oak	H	3	3		
2675	6	Buckthorn	R	4	3	X	
2676	22	Dead/Dying	R	6	6	X	Multi stem trunk: 12,10
2677	20	Buckthorn	R	3	3	X	Multi stem trunk: 10,6,4
2678	15	White Oak	H	2	2		
2679	7	Buckthorn	R	4	3	X	
2680	22	White Oak	H	2	2		
2681	9	Buckthorn	R	3	3	X	Gone
2682	23	White Oak	H	3	2		
2683	7	Buckthorn	R	3	3	X	
2684	13	Linden	R	2	1		
2685	22	White Oak	H	2	2		
2686	14	Norway Maple		2	2		
2687	24	White Oak	H	2	2		
2688	7	Buckthorn	R	3	3	X	
2689	7	Buckthorn	R	4	3	X	
2690	7	Buckthorn	R	3	3	X	
2691	7	Siberian Elm		2	3		
2692	26	White Oak	H	2	2		
2693	28	White Oak	H	3	3		
2694	6	Buckthorn	R	3	3	X	
2695	6	Buckthorn	R	4	3	X	
2696	12	Buckthorn	R	3	3	X	Multi stem trunk: 7,5
2697	7	Buckthorn	R	3	3	X	
2698	7	Buckthorn	R	3	4	X	
2699	9	Buckthorn	R	3	3	X	
2700	11	Shagbark Hickory	H	1	1	RP	
2701	7	Walnut		2	2		
2702	18	White Oak	H	3	2	*	
2703	23	Swamp White Oak	H	3	3	*	
2704	17	White Oak	H	3	3	*	
2705	12	Dead/Dying	R	6	6	X	
2706	14	Norway Maple		3	4		Growing into fence
2707	11	Norway Maple		3	3		
2708	9	Norway Maple		3	4		
2709	22	Norway Maple		3	3	*	Multi stem trunk: 13,9
2710	20	White Oak	H	2	2	*	
2711	17	Dead/Dying	R	6	6	X	
2712	22	Sugar Maple	H	4	4	*	Multi stem trunk: 8,6,6
2713	22	White Oak	H	2	2		
2714	18	White Oak	H	2	2		
2715	22	White Oak	H	2	2		
2716	16	White Oak	H	2	2		
2717	10	Norway Maple		4	4	X	Encroaching onto nearby tree
2718	24	White Oak	H	2	2		

Tag No.	Size (")	Common Name	Village Code classification	Cond	Form	Action Code	Notes
2719	6	Shagbark Hickory		2	2		
2720	10	Black Locust		3	3		
2721	16	White Oak	H	3	3		
2722	21	White Oak	H	2	2		
2723	17	White Oak	H	2	3		
2724	23	White Oak	H	1	1		
2725	9	Black Locust		3	3		
2726	20	White Oak	H	2	2		
2727	14	Black Locust		3	3		
2728	23	Black Locust		3	3		
2729	26	Swamp White Oak	H	2	3		
2730	7	Northern Red Oak		2	2		
2731	20	White Oak	H	2	2		
2732	11	Northern Red Oak	H	3	3		
2733	18	White Oak	H	3	3		
2734	13	Norway Spruce		2	3		
2735	9	Northern Red Oak	H	2	3		
2736	20	White Oak	H	1	1		
2737	8	Northern Red Oak	HR	4	5	X	Leaning
2738	10	Northern Red Oak	H	3	3		
2739	13	Northern Red Oak	H	3	3		
2740	9	Northern Red Oak	H	3	3		
2741	6	Northern Red Oak		3	3		
2742	22	White Oak	H	3	3		
2743	19	White Oak	H	2	2		
2744	16	White Oak	H	2	2		
2745	22	White Oak	H	3	2		
2746	7	Shagbark Hickory		2	2	R	
2747	16	Buckthorn	R	3	3	X	Multi stem trunk: 8,8
2748	13	Black Spruce		3	3		
2749	10	Norway Spruce		2	4		
2750	17	White Oak	H	2	2		
2751	17	White Oak	H	2	2		
2752	19	White Oak	H	2	2		
2753	9	Northern Red Oak	H	3	3		
2754	20	Northern Red Oak	H	3	3		
2755	30	Northern Red Oak	H	3	2		
2818	8	Norway Maple		3	3		
2819	12	Black Locust		4	4		
2820	10	Black Locust		4	4		
2821	6	Dead	R	6	6	X	
2822	18	Black Locust		5	4	X	Trunk Damage
2823	15	Black Locust		5	4	X	Trunk Damage, Basal Rot
2824	18	Black Locust		5	4	X	Trunk Damage
2825	7	Buckthorn	R	4	4	X	
2826	8	Black Locust		3	3		
2827	6	Buckthorn	R	3	3	X	
2828	9	Black Locust		3	3		
2829	10	Black Locust		3	2		
2830	8	Dead/Dying	R	6	6	X	
2831	9	Dead	R	6	6	X	
2832	15	Dead/Dying	R	6	6	X	
2833	8	Norway Maple		3	3		
2834	12	Dead	R	6	6	X	
2835	6	Norway Maple		3	4		
2836	8	Dead	R	6	6	X	
2837	15	Eastern White Pine	H	3	3		
2838	7	Black Locust	R	3	3	X	
2839	8	Dead	R	5	5	X	
2840	9	Eastern White Pine	H	3	3		
2841	20	Dead	R	6	6	X	
2842	7	American Elm	H	3	3		
2843	10	Norway Maple		3	2		
2844	13	Norway Maple		3	3		
2845	12	Norway Maple		3	3		
2846	12	Black Locust		3	3		
2847	7	Black Locust	R	3	3	X	
2848	7	Black Locust	R	3	4	X	
2849	10	Eastern White Pine	H	3	3		
2850	10	Dead	R	6	6	X	
2851	10	Eastern White Pine	H	2	3		
2852	7	Eastern White Pine	H	4	4	X	
2853	20	Eastern White Pine	H	3	3		
2854	15	Norway Maple		3	3		
2855	10	Norway Maple		3	3		
2856	7	Norway Maple		3	3		
2857	7	Norway Maple		3	3		
2858	13	Dead	R	6	6	X	
2859	8	Shagbark Hickory	H	3	3	X	
2860	18	Eastern White Pine	H	2	2		
2861	6	Shagbark Hickory	H	2	3	X	
2862	7	Buckthorn	R	3	4	X	
2863	36	White Oak	H	2	2		
2864	25	White Oak	H	2	2		
2865	24	White Oak	H	3	2		
2866	18	Dead	R	6	6	X	High risk tree, leaning over adjacent property
2867	6	Sugar Maple		3	3		
2868	29	White Oak	H	2	2		
2869	8	Buckthorn	R	5	4	X	Trunk rot
2870	30	White Oak	H	3	2		
2871	15	Shagbark Hickory	H	2	2		
2872	27	White Oak	H	3	3		
2873	7	Buckthorn	R	3	3	X	
2874	17	Shagbark Hickory	HR	6	6	X	Major Trunk Damage
2875	9	Northern Red Oak	H	2	3		
2876	17	Shagbark Hickory	H	2	3		
2877	27	Swamp White Oak	H	2	2		
2878	28	White Oak	H	3	2		
2879	7	Buckthorn	R	3	4	X	
2880	8	Dead	R	6	6	X	
2881	6	Dead	R	6	6	X	
2882	7	Shagbark Hickory		2	2		
2883	8	Shagbark Hickory	H	2	3		
2884	10	Norway Maple		3	4		
2885	28	White Poplar	R	3	3		
2886	13	Dead	R	6	6	X	
2887	8	Boxelder	R	4	5	X	Poor form
2888	39	Swamp White Oak	H	2	2		
2889	7	American Elm		4	4		
2890	39	Swamp White Oak	H	3	3		
2891	6	American Elm		3	3		
2892	7	American Elm		3	4		
2893	9	Dead/Dying	R	6	6	X	High risk tree to fence
2894	15	Shagbark Hickory	H	2	2		
2895	17	Dead/Dying	R	6	6	X	
2896	7	Dead/Dying	R	6	6	X	

Tag No.	Size (")	Common Name	Village Code classification	Cond	Form	Action Code	Notes
2897	6	Eastern White Pine		3	4		
2898	13	Buckthorn	R	3	4	X	Multi stem trunk: 7,6
2899	34	White Oak	H	3	2		
2900	14	Eastern White Pine	H	3	3		
2901	12	Black Locust		4	3	*	
2902	7	Dead/Dying	R	6	6	X	Topped at 20'
2903	8	Dead/Dying	R	6	6	X	
2904	12	Dead/Dying	R	6	6	X	
2905	7	Dead/Dying	R	6	6	X	
2906	18	Dead/Dying	R	6	6	X	
2907	18	Dead/Dying	R	6	6	X	
2908	17	Shagbark Hickory	H	2	2	*	
2909	6	Buckthorn	R	3	4	X	
2910	7	Dead	R	6	6	X	
2911	12	Dead	R	6	6	X	
2912	7	Buckthorn	R	4	4	X	
2913	16	Dead/Dying	R	6	6	X	
2914	13	Dead/Dying	R	6	6	X	
2915	11	Dead/Dying	R	6	6	X	
2916	6	Eastern White Pine		3	3		
2917	10	Buckthorn	R	3	4	X	
2918	18	Shagbark Hickory	H	2	2		
2919	12	Boxelder	R	3	4		
2920	41	White Oak	H	2	2		
2921	7	Black Locust		3	2	*	
2922	17	Boxelder	R	5	4	*	Multi stem trunk: 11,6
2923	7	Buckthorn	R	3	4	X	
2924	6	Dead	R	6	6	X	
2925	14	Black Locust		2	2	*	
2926	11	Shagbark Hickory	H	2	2	*	
2927	8	Dead/Dying	R	6	6	X	High risk tree, leaning over adjacent property
2928	9	Buckthorn	R	3	4	X	
2929	7	Boxelder	R	4	4	*	
2930	9	Buckthorn	R	3	3	X	
2931	7	Buckthorn	R	3	3	X	
2932	14	Boxelder	R	3	3	*	
2933	8	Dead/Dying	R	6	6	X	
2934	6	Buckthorn	R	3	4	X	
2935	12	Dead/Dying	R	6	6	X	
2936	15	Buckthorn	R	3	4	X	Multi stem trunk: 8,7
2937	10	Buckthorn	R	3	4	X	
2938	8	Black Locust		3	3	*	
2939	14	Black Locust		3	3	*	
2940	10	Boxelder	R	5	5	X	
2941	8	Dead	R	6	6	X	
2942	10	Dead	R	6	6	X	
2943	7	Dead	R	6	6	X	
2944	14	Dead	R	6	6	X	
2945	14	Dead/Dying	R	6	6	X	
2946	14	Dead/Dying	R	6	6	X	
2947	13	Dead	R	6	6	X	
2948	8	Dead	R	6	6	X	
2949	9	Dead	R	6	6	X	
2950	8	American Elm	H	3	3	*	
2951	6	Dead/Dying	R	6	6	X	
2952	6	Boxelder	R	3	3	*	
2953	7	Sugar Maple		3	3		
2954	7	Boxelder	R	3	4		
2955	33	White Oak	H	3	2	*	
2956	7	Boxelder	R	3	3	*	
2957	7	Boxelder	R	3	3	*	
2958	15	Northern Red Oak	H	2	3	RP	
2959	7	Boxelder	R	3	4	*	
2960	9	Dead	R	6	6	X	
2961	9	Dead	R	6	6	X	
2962	6	Shagbark Hickory		3	3	*	
2963	12	American Elm	H	3	3		
2964	8	American Elm	H	3	4		
2965	16	Boxelder	R	3	4		
2966	8	White Spruce		4	4		
2967	17	Norway Spruce		1	2		
2968	18	Norway Spruce		1	1		
2969	11	Norway Spruce		1	1		
2970	27	Norway Spruce		1	1		
2971	17	Norway Spruce		1	1		
2972	18	Norway Spruce		1	1		
2973	13	Norway Spruce		1	1		
2974	16	Norway Spruce		1	1	RP	
2975	6	Buckthorn	R	3	3	X	
2976	7	Buckthorn	R	4	4	X	
2977	8	Buckthorn	R	3	4	X	
2978	18	Norway Maple		3	3	RP	
2979	17	Norway Maple		2	2	RP	
2980	12	Siberian Elm		4	4		
2981	5	Norway Maple		3	3	*	
2982	42	Cottonwood	R	5	2	X	Gone
2983	6	Boxelder	R	3	3	*	
2984	12	Shagbark Hickory	H	3	3	*	
2985	28	Swamp White Oak	H	3	3	RP	
2986	7	Boxelder	R	3	3		
2987	44	Swamp White Oak	H	3	2	RP	
2988	6	Dead	R	6	6	X	
2989	8	Dead	R	6	6	X	
2990	11	Norway Maple		3	3		
2991	25	White Oak	H	2	2		
2992	19	Shagbark Hickory	H	2	2		
2993	37	White Oak	H	2	2	*	
2994	13	Norway Maple		3	3		
2995	23	Dead	R	6	6	X	Multi stem trunk: 13,10
2996	11	Norway Maple		3	3		
2997	10	Norway Maple		4	4		
2998	25	Norway Maple		3	3	X	Multi stem trunk: 16,9
2999	26	Black Locust		5	4	X	Trunk Rot
3000	35	Swamp White Oak	H	2	2		
3001	8	Dead	R	6	6	X	Fallen

Code	Description
1	Specimen
2	Good
3	Average
4	Fair
5	Poor
6	Dead

Action Code
X
R
*
RP

Classification Code

H
HR
R

The condition of the trees shall be based on a six (6) point scale with one (1) being the best and six (6) being the wo

Removal Description
Inch diameter to be removed based on condition &/or species
Inch diameter to be removed based on road alignment option
Inch diameter to be removed based on subdivision improvements
Tree to remain
Root Prune

Village Classification Description
Heritage Tree
Heritage Tree to be removed due to Poor or Hazardous Condition
Removable Tree
Non-Heritage Tree

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/19	FOR SUBMITTAL	S.R.M.
02/05/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH: (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH: (262) 878-6200 | ig@igconsulting.net
FIRM NO. 184-001330

TREE INVENTORY & SPECIFICATIONS

DESIGN: K.C.L.
DRAFTING: S.R.M
SCALE: NONE
DATE: 10/28/19

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.
G:\IG\18\1855\Eng\cad\2017\1855-treelist-~2017.dwg

PROJECT No. 18557

ZONE R-A
FOREST PRESERVE
TURNBULL WOODS

OUTLOT C

35' WEIR WIDTH
OVERFLOW = 678.50

OUTLOT D

DESENTION BASIN 1
H.W.L.=678.49
(100 YR)

SYSTEM 3
747 LF 902HD CHAMBERS
SYSTEM AREA: 6,238 S.F.

ZONE R-A
FOREST PRESERVE
COUNTY CLERK'S DIVISION

LOT 26
LOT 25
LOT 27
LOT 28
LOT 24
LOT 23
LOT 22
LOT 29
LOT 3
LOT 4
LOT 5
LOT 6
LOT 21
LOT 20

FOREST EDGE DRIVE

PARK
OUTLOT A

SYSTEM 6
146 LF 902HD CHAMBER
SYSTEM AREA: 1,309 S.F.

SYSTEM 4
121 LF 902HD CHAMBERS,
AREA SYSTEM: 1,062 S.F.

SYSTEM 2
261 LF 902HD CHAMBERS
AREA SYSTEM: 2,338 S.F.

LOT 19
SYSTEM 5
209 LF 902 HD CHAMBER
SYSTEM AREA: 1,940 S.F.

SYSTEM 1
CULTEC 902HD/208HD TIERED SYSTEM
1,831 LF 902HD CHAMBERS, 2,683 LF 280HD CHAMBERS
AREA SYSTEM: 15,163 S.F.

LOT 18
LOT 17
LOT 16
LOT 15
LOT 14
LOT 13
LOT 12
LOT 11
LOT 10
LOT 9
LOT 8
LOT 7
LOT 2
LOT 1

OUTLOT E

DUNHAM FOREST CREST SUBDIVISION
DOC. 1252807

CAROL LANE

ZONE R-B
SINGLE FAMILY
RESIDENTIAL DISTRICT

LOT 8
LOT 9
LOT 10
LOT 11
LOT 12
LOT 13
LOT 14
LOT 15
LOT 16

#1214
#1212
#1206
#1201
#1200
#1194
#1188
#1182
#1178

LOT B #431
LOT C #423
LOT D #415
#403
LOT F
#409
LOT E
ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT
#424
LOT 1
NORTHWOOD DRIVE
#414
NORTH GATE MANOR 1st ADDITION
DOC. 16986011
#406
NORTH GATE SUBDIVISION
DOC. 18523477
LOT H
LOT G
LOT I
#1805

PIN 04-01-200-010

SITE BENCHMARK:
N.E. BONNET BOLT ON FIRE HYDRANT.
ELEVATION=690.27 NAVD88 (GEOID12B)

ZONE R-A
GLENCOE GOLF CLUB

#1799

WESTLEY ROAD

GREEN BAY ROAD

OUTLOT B

FOREST EDGE DRIVE

UNSUBDIVIDED

ODH'S SUBDIVISION
DOC. 12390488
ZONE R-B
SINGLE FAMILY RESIDENTIAL DISTRICT

#1163

TREE LEGEND

6"-7"	>8"	
●	⊗	TREES TO BE REMOVED – DEAD/DYING/POOR/REMOVABLE
●	⊗	HIGH VALUE TREES TO BE REMOVED – ROAD AND SIDEWALK CONSTRUCTION
●	⊗	TREES TO BE REMOVED – ROAD AND SIDEWALK CONSTRUCTION
●	⊗	TREES TO BE REMOVED – SUBDIVISION IMPROVEMENTS

SCALE
40 0 20 40 80 160
(IN FEET)
1 inch = 40 ft.

TREE REMOVAL PLAN

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/20/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/04/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
03/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@gcconsulting.net

DESIGN: K.C.L.	DRAFTING: S.R.M.
SCALE: 1"=40'	DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\VS\18\18557\Eng\18557-RP.dwg

PROJECT No. 18557

TREE PRESERVATION PLAN

DO NOT DISTURBED AREA WITH TREE PROTECTION FENCE

ROOT PRUNNING

TREE LEGEND

- EXISTING TREE 8 INCHES AND MORE
- HIGH VALUE TREES
- EXISITNG TREES 7 INCHES OR LESS

SCALE

(IN FEET)
1 inch = 40 ft.

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/20/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/04/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=40' | DATE: 10/28/19
FIRM NO. 184-001330


FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\18557-grp.dwg


PROJECT No. 18557

6 of 7




NOTES:
1) THE PURPOSE OF TREE PROTECTION FENCING IS TO MINIMIZE CONSTRUCTION ACTIVITIES WITHIN CRITICAL ROOT ZONES OF EXISTING TREES TO REMAIN.
2) PROTECTIVE TREE FENCING MUST BE WIRE MESH OR WELDED WIRE FENCING (CHAIN LINK), 6' HIGH WITH STEEL OR WOODEN POSTS INSTALLED AND SPACED NOT MORE THAN 8' APART.
3) PROTECTIVE TREE FENCING MUST EXTEND TO THE DRIP LINE OF THE TREE (WHICH CAN BE ESTIMATED AT 1 FOOT FOR EVERY 1 INCH OF DBH) BUT IN NO CASE SHALL FENCING BE:
   LESS OF A RADIUS OF 10' FROM TREES UP TO 18" DBH
   LESS OF A RADIUS OF 15' FROM TREES 18" IN DBH OR LARGER
4) PROTECTIVE TREE FENCING MUST REMAIN INTACT FOR THE ENTIRE DURATION OF THE CONSTRUCTION PROJECT AND MAY NOT BE MOVED OR REMOVED FOR ANY REASON WITHOUT VILLAGE APPROVAL ONLY.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
PROTECTIVE TREE FENCING	SHEET 1 OF 1
	NOT TO SCALE




NOTES:
1) THE PURPOSE OF TREE BANDING AND BOARDING IS TO PROTECT TREE TRUNKS WHICH MAY BE EXPOSED TO CONSTRUCTION EQUIPMENT, SUCH AS AT DRIVEWAYS AND PARKWAYS.
2) EXISTING VEGETATION WHICH IS TO REMAIN IN PLACE SHALL BE PROTECTED AGAINST UNNECESSARY CUTTING, BREAKING, OR SKINNING OF ROOTS, SKINNING AND BRUISING OF BARK, SMOTHERING BY STOCKPILING OF CONSTRUCTION MATERIALS OR EXCAVATED MATERIALS WITHIN THE DRIP LINE, EXCESS FOOT OR VEHICULAR TRAFFIC OR PARKING OF VEHICLES WITHIN THE DRIP LINE.
3) BANDING IS USED TO PROTECT TREE TRUNKS ONLY.
4) 2X4, 2X6, OR 1X6 WOOD PLANKS MUST BE ERECTED VERTICALLY AND CONTINUOUSLY AROUND THE TRUNK, FASTENED WITH METAL WIRE OR BINDING.
5) NO NAILS MAY BE USED ON THE TREE.
6) EXISTING VEGETATION WHICH IS TO REMAIN IN PLACE SHALL BE WATERED AS REQUIRED TO MAINTAIN ITS HEALTH DURING THE COURSE OF CONSTRUCTION OPERATIONS.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
TREE BANDING AND BOARDING DETAIL	SHEET 1 OF 1
	NOT TO SCALE




ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
DIRECTIONAL BORING DETAIL AT EXISTING TREE	SHEET 1 OF 1
	NOT TO SCALE



NOTE:
BRIDGING CONSISTS OF 5"-8" MULCH OR WASHED STONE OVER SHEETS OF EXTERIOR PLYWOOD, CONCRETE BEAMS, AND GEOTEXTILE FABRIC THAT COVERS THE CRITICAL ROOT ZONE.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
TREE ROOT BRIDGING DETAIL	SHEET 1 OF 1
	NOT TO SCALE



NOTES:
1) THE PURPOSE OF ROOT PRUNING IS TO MAXIMIZE TREE HEALTH FOR TREE WHICH MAY BE IMPACTED BY CONSTRUCTION EQUIPMENT.
2) ROOT PRUNING MUST BE PERFORMED BY A CERTIFIED ARBORIST PRIOR TO EXCAVATION ACTIVITIES.
3) ROOT PRUNING MUST BE PERFORMED AS FAR FROM THE PROTECTED TREE AS POSSIBLE BUT STILL BE EFFECTIVE IN PROTECTING FROM EXCAVATION ACTIVITIES.
4) INSTALL ORANGE PLASTIC MESH TREE BARRIER WITH REBAR SUPPORTS AT POINT OF PRUNING AND CONTINUE COMPLETELY AROUND TREE, PROTECTING THE AREA WITHIN THE DRIP LINE (EXTENT OF OUTER BRANCHES)
5) CUTS ARE TO BE MADE CLEANLY WITH A SHARP ROOT PRUNING TOOL SUCH AS A DOSCO OR VERMEER ROOT PRUNER. CUTTING OR PRUNING OF ROOTS 2" IN DIAMETER OR LARGER IS PROHIBITED.
6) ROOT PRUNING MUST BE TO A DEPTH OF 18-24 INCHES BELOW GRADE.
7) HAND DIGGING IS REQUIRED IF EXCAVATION OCCURS WITHIN THE DRIP LINE OF THE TREE.
8) IF EXCAVATION CAUSED PRUNED ROOTS OVER 1.5" IN DIAMETER TO REMAIN EXPOSED FOR MORE THAN 24 HOURS, ROOTS ON THE TREE SIDE MUST BE KEPT MOIST.
9) TREE DIAMETER IS MEASURED AT BREAST HEIGHT (DBH).

FOR TREES < 6" DBH:
TRENCHING SHALL BE NO CLOSER TO THE TREE THAN THE DRIP LINE.
FOR TREES > 6" DBH:

TREE DIAMETER	DISTANCE "A"
6"-9"	5' MIN.
10"-14"	10' MIN.
15"-19"	12' MIN.
> 19"	15' MIN.

ENGINEERING AND SPECIFICATIONS MANUAL	JULY 2018
ROOT PRUNING DETAIL	SHEET 1 OF 1
	NOT TO SCALE

REVISIONS

DATE	DESCRIPTION	DRAWN BY
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/04/20	FOR SUBMITTAL	S.R.M.
04/17/20	PER VILLAGE COMMENTS	S.R.M.
05/08/20	PER VILLAGE COMMENTS	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

CONSTRUCTION STANDARDS | DESIGN: K.C.L. | DRAFTING: S.R.M | SCALE: NONE | DATE: 10/28/19

FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\cad2017\185570T-TREE-PLAN.dwg

PROJECT No. 18557

STORMWATER MANAGEMENT REPORT

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD,
GLENCOE, IL
(IG #18557)

Prepared for:
Glencoe Developers, LLC
707 Skokie Blvd, Suite 100
Northbrook, IL 60062

Prepared by:
IG Consulting, Inc.
300 Marquardt Drive
Wheeling, Il 60090

May 8, 2020

SUMMARY

IG Consulting, Inc. was engaged by Glencoe Developers, LLC to evaluate the existing and proposed storm water conditions for the property situated at 1801 Green Bay Road in Glencoe, Illinois and to prepare a stormwater management plan for a 29-unit residential community the developer intends to construct on the property. A copy of the proposed subdivision plan is attached as Exhibit "A".

EXISTING CONDITIONS

The property is situated in the northeast corner of Cook County Illinois. The surface of the property gently slopes to the east and is tributary to Lake Michigan. The highest ground on the property is along Green Bay Road. Water flows across the surface in two general directions. The northerly watersheds discharge toward the Turnbull Woods Forest Preserve property, along the north property line and at a point near the north end of the east property line. The southerly watershed drains toward Carol Lane at the east property line. The watersheds and these drainage flows are depicted on Exhibit "B".

IG Consulting performed a Critical Duration Analysis of various storm events, including events having a 1% chance (commonly called 100 year storm) of occurring, as requested by the Village staff. Exhibit B shows the 1-hour event generated the highest discharge rate for each sub-watershed the property. Sub-watershed A discharges 3.56 CFS, sub-watershed B discharges 8.77 CFS, and sub-watershed C discharges 11.49 CFS, as shown in Appendix "D". A summary of the Critical Duration Analysis is included as Table 1.

The Village of Glencoe initiated a study of the Terrace Court Basin area in 2014 and installed a storm sewer in Park Place in 2016 to help alleviate stormwater concerns raised by residents in the area. The existing watershed contributing to the Terrace Court basin area, and factored into the storm sewer design and installation, included the southerly 5.2 acres of the subject property flowing into the storm sewer at the intersection of Carol Lane and Park Place unrestricted in any way.

PROPOSED CONDITIONS/STORM WATER DETENTION

The proposed development will follow the current local, county, state and federal guidelines regarding storm water management and discharge from the subject property. Accordingly, we are proposing two storm water discharge points from the subject property that would collect proportional areas of the property in drainage swales and roadway gutters and direct the water into private and public storm sewer pipes. Those pipes would then discharge into a below grade chamber system embedded in stone and a surface basin that would temporarily hold the water and release it at a restricted rate. The basins would be sized to limit the overall discharge from the site to 3.30 CFS (approximately 19% of the current peak discharge). The proposed watersheds are depicted on Exhibit "C". The detention system will be a combination of an above ground detention basin in the northeast corner and a prefabricated, below ground chamber system in the northeast and southeast corners of the site, including the use of the prefabricated chamber system in select areas throughout the site.

Area "D" is a 1.04-acre sub-watershed that drains north to Turnbull Woods. A portion of the area will remain undeveloped and considered a preservation area. Areas in "D" that will be *developed* and unrestricted (not tributary to storm water detention), will be part of a swap of on-site property that will remain undeveloped. By MWRD regulation, if the unrestricted area is planted with deep rooted vegetation and in an easement to remain undisturbed, it can be considered unrestricted area that will not impact the total allowable release rate for the site.

Also, a proposed berm constructed along the east property line will be unrestricted on the east side of the berm. The berm will be planted and placed in an easement as protected area from development, to avoid impact to the allowable release rate. The release rate for the development was calculated as follows:

Site Area: 527,076 SF (12.10 Acres)
Undetained Developed Area: 27,150 SF**
Undetained Undeveloped Area: Planted with native planting (West Berm) and area to remain undeveloped (undisturbed) in a Preservation Easement (Rear yards of Lots 16 thru 29): 20,956 SF

**MWRD will allow on-site, undetained, developed areas to be swapped for on-site, undisturbed areas tributary to proposed detention.
On-Site Undisturbed Areas tributary to detention for Swap: The park area and two areas at the entrance into the subdivision: 27,363 SF. See exhibit for details.

527,076 **Total Site Area**
– 20, 956 **Undetained Undeveloped Area**
– 27, 150 **Undetained Developed Area in Swap**
= 478, 970 SF (11.00 Acres)

Therefore, the stormwater detention calculations are based on a net 11.00-acre development.
11.00 (0.30 cfs/Acre (North Branch Watershed)) = 3.30 CFS (Total Allowable Release Rate)

DESIGNED STORAGE VOLUME:
The proposed conditions were modeled using HydroCad Software, and Custom Prizmatic Storage for rock void volumes, including stormwater modeling with the Cultec arch pipe system. 2019 Bulletin 70 Rainfall data was used to detain sufficient storm water on site, while limiting the combined release rate to 3.30 cfs (11.00 acres x 0.30 cfs/acre).

In order to establish the required detention volume for the proposed project, the site was first modeled to provide the required detention for the 100-year storm event at the allowable release rate for just the subject property. Then, the offsite tributary area flowing from Northwood Drive, the existing residence on Green Bay Road and the northerly rear yards of Kelling Lane were incorporated creating a second model. In the second model, the internal weir to Turnbull Woods was lowered to allow the offsite bypass flow over the weir, while maintaining the required storage volume. The internal weir draining to Carol Lane was raised to direct the Kelling Lane bypass flow to drain through the detention system and discharge into Turnbull Woods, further reducing the flow to the Carol Lane storm sewer system. Please see Table 2, Page 17 for the specific flow rates in both iterations.

The resulting storage volume **required** for the development is **140,242 cubic feet**. The system as shown in Appendix A utilized a north surface basin containing 4,446 cf, of required storage and the below ground chamber system providing 135,796 cubic feet of required storage. A calculation was provided from HydroCad's technical reference manual for custom Prizmatic volume modeling.

The underground detention system is comprised of 2,683 LF of 280 HD chamber, 3,505 LF of 902 HD chamber within 45,407 sf of gravel bedding. The total amount of stone provided for the chamber system is 174,027 cubic feet. With a 36% void ratio, the total available storage is 62,650 cubic feet. Total storage in chambers is 78,172 cubic feet. The total provided detention storage in the chamber system is 140,821 cubic feet. Total provided storage for the North Basin is 5,071 cubic feet, with a total combined storage **provided** of **145,892 cubic feet**.

Release rate to the Northeast (Turnbull Woods): 1.40 cfs @ HWL of 678.36 and release rate to southeast (Carol Lane): 1.52 cfs @ HWL of 678.34, at the 18th hour. Total allowable release rate is 2.92 cfs. With ByPass, the release rate to Turnbull Woods is 8.39 cfs @ HWL of 678.49 and to Carol Lane 1.53 cfs @ HWL 678.50, at the 18th hour. Drain down time is 23 hours for the north detention basin and 82 hours for the below ground detention chamber system. Drain down calculations are provided in the Appendix A of this report.

BYPASS

Storm water entering the site from Northwood Drive and 1799 Green Bay Road will bypass through the development to the proposed detention system. To manage the bypass flow through the detention system and out to Turnbull Woods, the restrictor will remain a 6.5-inch diameter orifice and the 6 foot wide internal weir plate will be set to elevation 678.00, allowing bypass overflow. See tables 1 and 2 for information. To the south, existing flow from ODH Subdivision occurs at the 1-hour event at 2.31 cfs, for a combined total of 5.87 cfs to Carol Lane. At the 1-hour event, a proposed combined bypass/restrictor flow is 1.08cfs to Carol Lane.

At the 18-hour event, the existing runoff discharge to Carol lane is 2.08cfs. Proposed combined discharge at the 18-hour event will be 1.53cfs, to the Carol Lane storm sewer. An internal plate will be installed with a 4.5-inch diameter orifice and the top of the plate will be set at elevation 678.60 to control bypass flow to Turnbull Woods. Bypass flows are shown in Tables 1 and 2.

VOLUME CONTROL

The storm water chambers are designed to meet water quality discharge Retention-Volume Control (Initial 1" flow of water is filtered or treated to remove sediment and debris). The Prefabricated chamber system will provide the necessary volume control and detention for the development. Storm water captured throughout the site will pass through the chamber system, prior to release to the public sewer system. According to Section 5.3.3, *Volume Control Practices, in the MWRD's Watershed Management Ordinance, Technical Guidance Manual,* volume control practices provide water quality enhancements through filtration of pollutants such as fine sediment, nutrients, bacteria and organic materials from initial (first flush) storm water runoff. Furthermore, the manual states when detention is required for development, credit for retention-based practices may be applied toward the detention requirements. Flows through Contech's Separator Rows within the chamber system and filtration through open graded stone below the chambers will provide necessary volume control and detention for the development. The storm water chamber system will be constructed in the rear lots, from the northeast to the southeast corner of the site, including select areas. The system would be accessed via easements along the side yards of the lots within the subdivision. In addition, chambers will be constructed underneath low points in the street with permeable pavers, providing water quality/volume control and storm water detention. Total Impervious Area for the Site: 5.57 Ac. (242,629 s.f.)
242,629 * 0.083 = 20,138.00 cubic feet (0.462 Acre Feet) of Volume Control.

DISCHARGE DESIGN:

Two primary discharge restrictors from the detention system are proposed along the east line of the property. The southerly restrictor will be a 4.5" diameter hole in an internal weir plate of a storm manhole. It will discharge into a 12 " diameter pipe to a proposed manhole in Carol Lane and then continue in a 12" diameter pipe to the 30" storm sewer at Park Place. The northerly restrictor consists of a plate with a 6.5" diameter orifice, The plate is an internal wall of the restrictor manhole flowing into a 18" pipe and an energy dissipater on the surface at the property line.

OVERFLOW CONDITIONS:

In the event a storm event exceeds the capacity of the detention storage, two overflow weirs have been incorporated into the design. A six foot wide internal overflow weir at elevation 678.60 will be installed in the storm manhole with the southerly restrictor. A six foot wide internal overflow weir at elevation 678.00 will be installed in the manhole for the northerly restrictor.

A 35-foot wide weir at elevation 678.50 is incorporated into the berm of the north surface basin.

In addition, an internal weir will be placed inside a manhole at elevation 677.80, with a 1.50-inch orifice at invert elevation 673.50 to regulate flow between the above ground basin to the northeast and the chamber system, including flows to the two northeast and southeast restrictor manholes.

EROSION CONTROL

Soil erosion control will be managed during construction activities, with the use of perimeter silt fence, at the start of construction. The north detention basin will be stabilized with topsoil, blanket and seed, immediately following the completion of earthwork. Temporary filter baskets will be installed in catch basins. Combination silt fence surrounding catch basins with filter baskets will be installed in grass areas, Filter logs will be placed around inlet structures with temporary filter baskets, in paver brick locations. An energy dissipator with down-stream rip-rap will be installed at the northeast restrictor catch basin. Site and off-site bypass discharges enter the northeast restrictor catch basin, then into the Turnbull Woods Forest Preserve.

SANITARY SEWER

8-inch and 6-inch PVC, SDR 26 sanitary sewer will be installed to service the 29 lots. State requirements for sewer separation, material types and crossings are met, for protection of surrounding utilities. Two connections will be made to service the development. The proposed 8-inch sewer will discharge to an existing 8-inch sewer in Green Bay Road. Another proposed 8-inch sewer will discharge east, between lots 17 and 18 and between lots 14 and 15 on Carol Lane. The 8-inch sewer will connect to an existing 8-inch sewer in Carol Lane.

CONCLUSION:

The design proposes to collect the storm water and release it to both the northeast (Turnbull Woods) and southeast (Park Place). This plan will maintain flow to Turnbull Woods and will reduce the

primary flow to the Park Place sewer by over 60%. The design directs the majority of the overland flow from the site away from the existing neighboring residential properties.

While there will be an increase in impervious area on the subject property as a result of its development, the overall peak rate of stormwater runoff will actually decrease to less than 20% of the existing peak flow due to the temporary detention of stormwater in the basins the developer will be constructing on the property. Storm water will be released at a controlled and restricted rate into the Village's Terrace Court Basin storm sewer system. Storm sewer and swale sizing calculations are found in Appendix A of this report.

:\IG\18\18557\Stormwater Management Report-5-13-20Rev.doc

EXHIBIT A

FINAL PLAT OF SUBDIVISION

FOREST EDGE SUBDIVISION

OF

BEING A SUBDIVISION IN THE NORTH QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, COOK COUNTY, ILLINOIS.

EXISTING PINS:
PARCEL 1 = 04-01-200-011
PARCEL 2 = 04-01-200-006

SEND TAX BILL TO:

NAME: _____

ADDRESS: _____

CITY: _____

STATE: _____

TOTAL SUBDIVISION AREA = 12.11 ACRES

RIGHT OF WAY DEDICATION = 1.51 ACRES

SCALE

50 0 25 50 100 200

(IN FEET)
1 inch = 50 ft.

ALL DISTANCES IN FEET AND DECIMAL PARTS THEREOF.
NO DIMENSIONS TO BE ASSUMED FROM SCALING.

COMPARE YOUR DESCRIPTION AND SITE MARKINGS WITH THIS PLAT AND AT ONCE REPORT ANY DISCREPANCIES WHICH YOU MAY FIND.

REFER TO TITLE REPORT FOR ANY EASEMENTS, COVENANTS OR RESTRICTIONS THAT MAY EXIST BUT ARE NOT SHOWN HEREON.

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\18557-SP.dwg

REVISED: 06/08/20
REVISED: 04/17/20
REVISED: 02/20/20
REVISED: 02/19/20
PREPARED: 01/17/20

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

PREPARED FOR: GLENCOE DEVELOPERS LLC | SCALE: 1"=50' | DRAFTED BY: S.R.M. | CHECKED BY:
FIELD CREW: D.J. | FIELD WORK: 2018 | FIRM NO. 184-001330

FINAL PLAT OF SUBDIVISION
FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT NUMBER
18557

FINAL PLAT OF SUBDIVISION
FOREST EDGE SUBDIVISION
OF

BEING A SUBDIVISION IN THE NORTH QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, COOK COUNTY, ILLINOIS.

REVISED: 06/08/20
REVISED: 04/17/20
REVISED: 02/20/20
REVISED: 02/19/20
PREPARED: 01/17/20

PRESIDENT AND BOARD OF TRUSTEES CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

APPROVED AND RIGHT OF WAY DEDICATION HEREBY ACCEPTED, BY THE PRESIDENT AND BOARD OF TRUSTEES OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS

THIS _____ DAY OF _____ A.D., 20__.

_____
VILLAGE PRESIDENT

_____
ATTEST: VILLAGE TREASURER

VILLAGE ENGINEER CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

APPROVED BY THE VILLAGE ENGINEER OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS

THIS _____ DAY OF _____ A.D., 20__.

_____
VILLAGE ENGINEER

PLAN COMMISSION CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

RECOMMENDED BY THE PLAN COMMISSION OF THE VILLAGE OF GLENCOE, ILLINOIS

THIS _____ DAY OF _____ A.D., 20__.

_____
CHAIRMAN

_____
SECRETARY

EASEMENT FOR STORM SEWER

A PERMANENT AND PERPETUAL NON-EXCLUSIVE EASEMENT IS HEREBY GRANTED TO THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS (" VILLAGE"), TO SURVEY, CONSTRUCT, RECONSTRUCT, USE, OPERATE, MAINTAIN, TEST, INSPECT, REPAIR, REPLACE, ALTER, REMOVE OR ABANDON IN PLACE STORM SEWER MAINS, TOGETHER WITH RELATED ATTACHMENTS, EQUIPMENT AND APPURTENANCES THERETO, IN, UPON, UNDER, ALONG AND ACROSS THE AREAS DESIGNATED "STORM SEWER EASEMENT" ON THIS SUBDIVISION PLAT. THE OWNERS OF THE PROPERTY SUBDIVIDED ON THIS PLAT OR ANY PART THEREOF HEREBY RESERVE THE RIGHT TO USE THE AREAS DESIGNATED "STORM SEWER EASEMENT" AND THE ADJACENT PROPERTY IN ANY MANNER THAT WILL NOT PREVENT OR INTERFERE WITH THE EXERCISE BY THE VILLAGE OF THE RIGHTS HEREBY GRANTED; PROVIDED, HOWEVER, THAT THE OWNERS SHALL NOT IN ANY MANNER DISTURB, DAMAGE, DESTROY, INJURE, OBSTRUCT OR PERMIT TO BE OBSTRUCTED THE "STORM SEWER EASEMENT" AT ANY TIME WHATSOEVER WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF THE VILLAGE'S VILLAGE MANAGER.

PUBLIC UTILITY & ACCESS EASEMENT

A PERMANENT AND PERPETUAL NON-EXCLUSIVE EASEMENT IS HEREBY GRANTED TO THE VILLAGE, NORTH SHORE GAS COMPANY, COMCAST CABLE, COMMONWEALTH EDISON COMPANY, AT&T AND WIDE OPEN WEST, THEIR SUCCESSORS AND ASSIGNS, IN ALL AREAS DESIGNATED "PUBLIC UTILITY & ACCESS EASEMENT ON THIS SUBDIVISION PLAT, SAID EASEMENTS SHALL BE FOR THE INSTALLATION, MAINTENANCE, RELOCATION, RENEWAL AND REMOVAL OF PUBLIC UTILITIES, DRAINAGE FACILITIES AND RELATED APPURTENANCES, IN, UNDER, ACROSS, ALONG AND/OR UPON THE SO DESIGNATED PROPERTY. IT SHALL INCLUDE THE RIGHT TO ENTER THE SUBDIVIDED PROPERTY AND SUCH AREAS FOR ALL SUCH PURPOSES, AND THE RIGHT, WITHOUT LIABILITY, TO CUT, TRIM, ALTER AND/OR REMOVE ANY VEGETATION, ROOTS, STRUCTURES OR DEVICES WITHIN THE DESIGNATED EASEMENT PROPERTY AS MAY BE REASONABLY REQUIRED INCIDENT TO THE RIGHT HEREIN GIVEN.

WITHOUT PRIOR WRITTEN CONSENT OF THE GRANTEES, NO BUILDINGS, STRUCTURES OR OTHER OBSTRUCTION SHALL BE CONSTRUCTED, PLANTED OR PLACED IN ANY SUCH EASEMENT AREAS, NOR SHALL ANY OTHER USES BE MADE THEREOF WHICH WILL INTERFERE WITH THE EASEMENTS GRANTED HEREBY. SUCH EASEMENTS SHALL FURTHER BE FOR THE PURPOSE OF SERVING ALL AREAS SHOWN ON THIS PLAT AS WELL AS OTHER PROPERTY, WHETHER OR NOT CONTIGUOUS THERETO, WITH GAS, ELECTRIC, TELEPHONE, FIBER-OPTIC AND/OR CABLE TV, WATERMAINS, SANITARY AND STORM SEWERS.

SUCH EASEMENTS SHALL SURVIVE THE VACATION BY PROPER AUTHORITY OF ANY STREET AND OTHER PUBLIC WAY AND PLACE SHOWN ON THIS PLAT, UNLESS OTHERWISE EXPRESSLY MENTIONED IN AN ORDINANCE OF VACATION.

EMERGENCY & PEDESTRIAN ACCESS EASEMENT

A PERMANENT AND PERPETUAL NON-EXCLUSIVE EASEMENT IS HEREBY RESERVED FOR AND GRANTED TO THE VILLAGE ON, OVER, UPON AND ACROSS, THOSE AREAS DEPICTED ON THE PLAT AS "EMERGENCY & PEDESTRIAN EASEMENT" FOR MUNICIPAL EMERGENCY VEHICULAR USE AND PUBLIC PEDESTRIAN USE, BICYCLE USE (NON-MOTORIZED VEHICLES), AND ACCESS, AND FOR THE VILLAGE TO IMPROVE, INSTALL, CONSTRUCT, RENEW, CLEAR, RECONSTRUCT, REPLACE, REMOVE, REPAIR, ALTER, INSPECT, OPERATE, AND MAINTAIN SAME.

RESTRICTIVE COVENANTS AND EASEMENT FOR STORM WATER MANAGEMENT AREA

1. THE AREA OF THE PROPERTY DESIGNATED ON THIS PLAT AS "STORM WATER MANAGEMENT AREA" SHALL BE CONTINUOUSLY MAINTAINED IN A FIRST RATE MANNER BY FOREST EDGE SUBDIVISION HOMEOWNERS' ASSOCIATION (THE "ASSOCIATION") AND AN EASEMENT ON, UNDER AND ABOVE THE STORM WATER MANAGEMENT AREA IS HEREBY GRANTED TO, AND FOR THE USE AND BENEFIT OF, ALL OF THE LOTS IN THIS SUBDIVISION AND THE HOMEOWNERS' ASSOCIATION FOR THE SOLE PURPOSE OF STORM WATER DETENTION AND DRAINAGE.

2. NO CHANGE SHALL BE MADE IN THE FINISHED GRADE OF THE LAND WITHIN THE STORM WATER MANAGEMENT AREA, NOR SHALL ANY CONSTRUCTION OF ANY KIND WHATSOEVER BE ERECTED OR PERMITTED TO EXIST WITHIN THE STORM WATER MANAGEMENT AREA THAT MIGHT MATERIALLY IMPEDE STORM WATER DRAINAGE THEREIN OR MATERIALLY REDUCE THE STORM WATER DETENTION CAPACITY THEREOF. TREES, SHRUBS, FENCES AND NORMAL LANDSCAPE PLANTING ASIDE FROM THOSE DEPICTED IN THE FINAL ENGINEERING AND LANDSCAPE PLANS FOR THE FOREST EDGE SUBDIVISION SHALL BE PERMITTED WITHIN THE STORM WATER MANAGEMENT AREA ONLY WITH THE PRIOR WRITTEN APPROVAL OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS (THE "VILLAGE").

3. IN THE EVENT THE VILLAGE DETERMINES, IN ITS SOLE AND ABSOLUTE DISCRETION, THAT PRIOR MAINTENANCE OF THE STORM WATER MANAGEMENT AREA, AS REQUIRED BY THE DECLARATION FOR THE FOREST EDGE SUBDIVISION, IS NOT PERFORMED AT ANY TIME, THE VILLAGE, AFTER TEN (10) DAYS PRIOR WRITTEN NOTICE TO THE ASSOCIATION, MAY, BUT SHALL NOT BE OBLIGATED TO, ENTER UPON THE STORM WATER MANAGEMENT AREA FOR THE PURPOSE OF PERFORMING MAINTENANCE WORK ON AND TO THE STORM WATER MANAGEMENT AREA.

4. IN THE EVENT THAT THE VILLAGE SHALL CAUSE TO BE PERFORMED ANY WORK PURSUANT TO THESE PARAGRAPHS, THE VILLAGE SHALL HAVE THE RIGHT TO CHARGE THE ASSOCIATION AN AMOUNT SUFFICIENT TO DEFRAY THE ENTIRE COST OF SUCH WORK OR ACTION, INCLUDING ADMINISTRATIVE COSTS, EITHER BEFORE OR AFTER SUCH COST IS INCURRED. IF THE AMOUNT SO CHARGED IS NOT PAID BY THE ASSOCIATION WITHIN THIRTY (30) DAYS FOLLOWING A DEMAND IN WRITING BY THE VILLAGE FOR SUCH PAYMENT, SUCH CHARGE, TOGETHER WITH INTEREST AND COSTS OF COLLECTION, SHALL BECOME A LIEN UPON THE STORM WATER MANAGEMENT AREA AND LOTS 1-29 IN THIS SUBDIVISION AND THE VILLAGE SHALL HAVE THE RIGHT TO COLLECT SUCH CHARGE, WITH INTEREST AND COSTS, AND TO ENFORCE SUCH LIEN AS IN FORECLOSURE PROCEEDINGS AS PERMITTED BY LAW.

5. NOTHING IN THESE PARAGRAPHS SHALL BE CONSTRUED TO CONSTITUTE A DEDICATION OF ANY PORTION OF THE STORM WATER MANAGEMENT AREA TO, OR AN ACCEPTANCE THEREOF BY, THE VILLAGE.

6. THE VILLAGE SHALL BE UNDER NO OBLIGATION TO EXERCISE THE RIGHTS GRANTED IN THESE PARAGRAPHS EXCEPT AS IT SHALL DETERMINE TO BE IN ITS BEST INTEREST. NO FAILURE TO EXERCISE AT ANY TIME ANY RIGHT HEREIN GRANTED TO THE VILLAGE SHALL BE CONSTRUED AS A WAIVER OF THAT OR ANY OTHER RIGHTS.

7. THESE COVENANTS SHALL RUN WITH THE LAND IN THE SUBDIVISION SHOWN ON THIS PLAT, AND SHALL BE BINDING UPON AND INURE TO THE BENEFIT OF THE OWNERS OF ALL LOTS OF RECORD THEREIN, THEIR RESPECTIVE SUCCESSORS, ASSIGNS AND GRANTEES AND ALL PARTIES CLAIMING BY, THROUGH AND UNDER THEM. ENFORCEMENT OF THESE COVENANTS MAY BE SOUGHT BY THE OWNERS OF ANY LOTS OF RECORD IN THIS SUBDIVISION, ANY PERSON WITH AN INTEREST IN ANY OF SAID LOTS OF RECORD, OR THE VILLAGE OF GLENCOE BY ANY PROCEEDING AT LAW OR IN EQUITY AGAINST ANY PERSON OR PERSONS VIOLATING OR ATTEMPTING TO VIOLATE ANY COVENANT, EITHER TO RESTRAIN VIOLATION, TO COMPEL AFFIRMATIVE ACTION, OR TO RECOVER DAMAGES, AND AGAINST THE LAND TO ENFORCE ANY LIEN CREATED BY THESE COVENANTS.

OPEN SPACE COVENANT AND EASEMENT

THE AREA OF THE PROPERTY DESIGNATED ON THIS PLAT AS "OPEN SPACE EASEMENT AREA" SHALL BE CONTINUOUSLY MAINTAINED AS OPEN SPACE IN ITS NATURAL CONDITION BY FOREST EDGE SUBDIVISION HOMEOWNERS' ASSOCIATION (THE "ASSOCIATION"). NO MANMADE STRUCTURE OF ANY KIND SHALL BE CONSTRUCTED THEREON NOR SHALL ANY GRADING BE PERMITTED EXCEPT FOR THOSE IMPROVEMENTS WHICH ARE INCLUDED IN THE APPROVED PLANS AND SPECIFICATIONS FOR THE SUBDIVISION.

EASEMENT FOR STORM WATER DRAINAGE:

A PERMANENT AND PERPETUAL NON-INCLUSIVE EASEMENT IS HEREBY GRANTED TO THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS ("VILLAGE"), ITS SUCCESSORS AND ASSIGNS, AND TO, AND FOR THE USE AND BENEFIT OF, THE OWNERS OF ALL OF THE LOTS IN THIS SUBDIVISION, FOR THE SOLE PURPOSE OF OVERLAND STORM WATER DRAINAGE, IN, UPON, ALONG AND ACROSS THE AREAS DESIGNATED "EASEMENT FOR STORM WATER DRAINAGE" ON THIS SUBDIVISION PLAT. NO CHANGE SHALL BE MADE IN THE FINISHED GRADE OF THE LAND WITHIN ANY "EASEMENT FOR STORM WATER DRAINAGE," AND NO CONSTRUCTION OF ANY KIND WHATSOEVER SHALL BE ERECTED OR PERMITTED TO EXIST WITHIN ANY "EASEMENT FOR STORM WATER DRAINAGE" THAT MIGHT MATERIALLY REDUCE THE STORM WATER DRAINAGE CAPACITY THEREOF. TREES, SHRUBS, FENCES, AND NORMAL LANDSCAPE PLANTING SHALL BE PERMITTED WITHIN ANY "EASEMENT FOR STORM WATER DRAINAGE" ONLY WITH THE PRIOR WRITTEN APPROVAL OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE. EACH OWNER OF A LOT WITH ANY "EASEMENT FOR STORM WATER DRAINAGE" LOCATED ON IT SHALL MAINTAIN A GRASS COVER ON THE SURFACE OF THAT PORTION OF SUCH LOT LOCATED WITHIN THE "EASEMENT FOR STORM WATER DRAINAGE," AND SHALL KEEP SUCH GRASS AND LANDSCAPING IN A FIRST-CLASS AND TRIMMED CONDITION. THE OWNERS OF LOTS ON WHICH ANY "EASEMENT FOR STORM WATER DRAINAGE" IS LOCATED SHALL NOT IN ANY MANNER DAMAGE, DESTROY, INJURE, OBSTRUCT, OR PERMIT TO BE OBSTRUCTED THE "EASEMENT FOR STORM WATER DRAINAGE" AT ANY TIME WHATSOEVER WITHOUT THE EXPRESS PRIOR WRITTEN CONSENT OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE.

BIOSWALE EASEMENT:

THE AREA OF THE PROPERTY DESIGNATED ON THIS PLAT AS "BIOSWALE EASEMENT" SHALL BE CONTINUOUSLY MAINTAINED IN A FIRST RATE MANNER BY FOREST EDGE SUBDIVISION HOMEOWNERS' ASSOCIATION (THE "ASSOCIATION") AND AN EASEMENT ON, UNDER AND ABOVE THE STORM WATER MANAGEMENT AREA IS HEREBY GRANTED TO, AND FOR THE USE AND BENEFIT OF, ALL OF THE LOTS IN THIS SUBDIVISION AND THE HOMEOWNERS' ASSOCIATION FOR THE SOLE PURPOSE OF STORM WATER DRAINAGE. NO CHANGE SHALL BE MADE IN THE FINISHED GRADE OF THE LAND WITHIN THE BIOSWALE EASEMENT, NOR SHALL ANY CONSTRUCTION OF ANY KIND WHATSOEVER BE ERECTED OR PERMITTED TO EXIST WITHIN THE BIOSWALE EASEMENT THAT MIGHT MATERIALLY IMPEDE STORM WATER DRAINAGE THEREIN. TREES, SHRUBS, FENCES AND NORMAL LANDSCAPE PLANTING ASIDE FROM THOSE DEPICTED IN THE FINAL ENGINEERING AND LANDSCAPE PLANS FOR THE FOREST EDGE SUBDIVISION SHALL BE PERMITTED WITHIN THE BIOSWALE EASEMENT ONLY WITH THE PRIOR WRITTEN APPROVAL OF THE VILLAGE MANAGER OF THE VILLAGE OF GLENCOE, COOK COUNTY, ILLINOIS.

OWNER'S CERTIFICATE
STATE OF ILLINOIS}
COUNTY OF COOK}S.S.

THIS IS TO CERTIFY THAT HOOVER OWNER, LLC, A DELAWARE LIMITED LIABILITY COMPANY, IS THE OWNER OF THE LAND DESCRIBED IN THE ANNEXED PLAT, AND THAT IT HAS CAUSED THE SAME TO BE SURVEYED AND SUBDIVIDED AS INDICATED THEREON, FOR THE USES AND PURPOSES THEREIN SET FORTH, AND DOES HEREBY ACKNOWLEDGE AND ADOPT THE SAME UNDER THE STYLE AND TITLE THEREON INDICATED.

THIS IS TO FURTHER CERTIFY THAT HOOVER OWNER, LLC, HAS DETERMINED, TO THE BEST OF ITS, KNOWLEDGE, THAT EACH OF THE LOTS DEPICTED ON THE ANNEXED PLAT LIES IN THE FOLLOWING SCHOOL DISTRICT:

ELEMENTARY SCHOOL DISTRICT 35 — HIGH SCHOOL DISTRICT 203

DATED THIS ___ DAY OF _____, A.D., 20_____.

HOOVER OWNER, LLC

BY: _____
MANAGING MEMBER

NOTARY PUBLIC CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

I, _____, A NOTARY PUBLIC, DO HEREBY CERTIFY THAT _____, APPEARED BEFORE ME THIS DAY IN PERSON AND ACKNOWLEDGED THE EXECUTION OF THIS STATEMENT AS HIS FREE AND VOLUNTARY ACT.

GIVEN UNDER MY HAND AND NOTARIAL SEAL THIS __ DAY OF _____ A.D., 20__.

_____
NOTARY PUBLIC

DRAINAGE CERTIFICATE
TO THE BEST OF OUR KNOWLEDGE AND BELIEF, THE DRAINAGE OF SURFACE WATERS WILL NOT BE CHANGED BY THE CONSTRUCTION OF THIS SUBDIVISION OR ANY PART THEREOF, OR, IF SUCH SURFACE WATER DRAINAGE WILL BE CHANGED, REASONABLE PROVISION HAS BEEN MADE FOR COLLECTION AND DIVERSION OF SUCH SURFACE WATERS INTO PUBLIC AREAS, OR DRAINS WHICH THE OWNER HAS A RIGHT TO USE, AND THAT SUCH SURFACE WATERS WILL BE PLANNED FOR IN ACCORDANCE WITH GENERALLY ACCEPTED ENGINEERING PRACTICES SO AS TO REDUCE THE LIKELIHOOD OF DAMAGE TO THE ADJOINING PROPERTY BECAUSE OF THE CONSTRUCTION OF THIS SUBDIVISION.

_____ HOOVER OWNER LLC
OWNER

ITS MANAGER: _____

SIGNED: _____

DATED: _____

_____

NAME: KEVIN C. LEWIS

FIRM: IG CONSULTING, INC.

DATED: _____

SURVEYOR CERTIFICATE
STATE OF ILLINOIS}
}S.S.
COUNTY OF COOK}

THIS IS TO CERTIFY THAT I, KEVIN C. LEWIS, AN ILLINOIS PROFESSIONAL LAND SURVEYOR NUMBER 3681, HAVE SURVEYED AND SUBDIVIDED THE FOLLOWING DESCRIBED PROPERTY.

PARCEL 1:
THAT PART OF THE SOUTH 6 CHAINS AND 23 LINKS OF THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, WHICH LIES EAST OF THE CENTER LINE OF THE GREEN BAY ROAD (EXCEPTING THAT PORTION AS BEING MORE PARTICULARLY DESCRIBED IN DEED RECORDED AUGUST 22, 2016 AS DOCUMENT NUMBER 1623529020), ALSO THAT PART OF THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, BOUNDED AND DESCRIBED AS FOLLOWS: COMMENCING AT THE INTERSECTION OF THE EAST LINE OF SAID NORTHEAST QUARTER WITH THE NORTH LINE OF THE SOUTH 6.23 CHAINS OF SAID NORTHEAST QUARTER; RUNNING THENCE NORTH ON SAID EAST LINE 3 FEET; THENCE WESTERLY, PARALLEL WITH THE NORTH LINE OF SAID SOUTH 6.23 CHAINS, TO THE CENTER LINE OF GREEN BAY ROAD; THENCE SOUTHEASTERLY, ALONG THE CENTER LINE OF GREEN BAY ROAD, TO THE NORTH LINE OF SAID SOUTH 6.23 CHAINS; THENCE EASTERLY , ALONG THE NORTH LINE OF SAID SOUTH 6.23 CHAINS TO THE PLACE OF BEGINNING, ALL IN COOK COUNTY, ILLINOIS.

PARCEL 2:
THAT PART OF THE NORTHEAST QUARTER OF SECTION 1, TOWNSHIP 42 NORTH, RANGE 12 EAST OF THE THIRD PRINCIPAL MERIDIAN, DESCRIBED AS FOLLOWS: BEGINNING AT A POINT IN THE EAST LINE OF SAID NORTHEAST QUARTER, 414.18 FEET NORTH OF THE SOUTHEAST CORNER OF SAID NORTHEAST QUARTER; THENCE NORTH, ALONG THE EAST LINE OF SAID NORTHEAST QUARTER, 366.2 FEET TO THE SOUTH LINE OF THE PROPERTY OF THE FOREST PRESERVE OF COOK COUNTY; THENCE WEST, ALONG THE SOUTH LINE OF THE SAID FOREST PRESERVE OF COOK COUNTY, 568 FEET; THENCE SOUTH, ALONG A LINE 568 FEET WEST OF AND PARALLEL WITH THE SAID EAST LINE OF THE NORTHEAST QUARTER, 350.6 FEET; THENCE SOUTHWESTERLY, ALONG A STRAIGHT LINE, 28.28 FEET TO A POINT ON A LINE 414.18 FEET NORTH OF AND PARALLEL WITH THE SOUTH LINE OF SAID NORTHEAST QUARTER AND 588 FEET WEST OF THE EAST LINE OF SAID NORTHEAST QUARTER; THENCE EAST, ALONG SAID LINE 414.18 FEET NORTH OF THE SOUTH LINE OF SAID NORTHEAST QUARTER, 588 FEET TO THE PLACE OF BEGINNING, IN COOK COUNTY, ILLINOIS.

I ALSO CERTIFY THAT THE PROPERTY IS WITHIN THE CORPORATE LIMITS OF THE VILLAGE GLENCOE, WHICH HAS ADOPTED AN OFFICIAL COMPREHENSIVE PLAN.

I FURTHER CERTIFY THAT BY SCALED MAP LOCATION AND GRAPHIC PLOTTING ONLY, THE PARCELS INCLUDED IN THIS SUBDIVISION ARE LOCATED IN THE "UNSHADED ZONE X" PER FEDERAL EMERGENCY MANAGEMENT AGENCY FLOOD INSURANCE RATE MAP 17031C0094J EFFECTIVE DATE OF AUGUST 19, 2008.

GIVEN UNDER MY HAND AND SEAL THIS _____ DAY OF _____, A.D. 20___.

BY _____
ILLINOIS PROFESSIONAL LAND SURVEYOR NO. 3681
LICENSE EXPIRES NOVEMBER 30, 2020

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net


PREPARED FOR: GLENCOE DEVELOPERS LLC | SCALE: 1"=50'
FIELD CREW: D.J. | FIELD WORK:2018 | DRAFTED BY: S.R.M. | CHECKED BY:
FIRM NO. 184-001330

FINAL PLAT OF SUBDIVISION
FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT NUMBER
18557

COPYRIGHT AS DATED © IG CONSULTING, INC.
G:\IG\18\18557\Eng\18557-9P.dwg

EXHIBIT B



REVISIONS		
DATE	DESCRIPTION	DRAWN BY
06/03/19	VILLAGE REVIEW	S.R.M.
07/22/19	REVISED ENTRANCE	S.R.M.
07/29/19	FOR SUBMITTAL	S.R.M.
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net

EXISTING TRIBUTARY EXHIBIT | DESIGN: K.C.L | DRAFTING: S.R.M. | SCALE: 1"=40' | DATE: 05/06/2019

FIRM NO. 184-001330

1801 GREEN BAY ROAD SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

PROJECT No. 18557

1 of 1

COPYRIGHT AS DATED © IG CONSULTING, INC.

C:\IG\18557\Engr\18557-EP.dwg

TABLE 1

100 Year Critical Duration Analysis Existing Conditions Table 1									
100 Year Event Storm Duration	Existing Discharge Rate Area "A" (1.60 Ac.) CFS	Existing Discharge Rate Area "B" (3.60 Ac.) CFS	Existing Discharge Rate Area "C" (5.90 Ac.) CFS	Existing Runoff Total 11.10 Acres (ABC) CFS	Existing Discharge Rate Area "D" (1.00 Ac.) CFS	Existing Runoff Total offsite (2.20 Ac.) & Area "C" (5.90 Ac.) CFS	Offsite Bypass 2.20 Acres (0.60 Ac+1.60 Ac) CFS	Turnbull North Runoff (1.80 Ac) CFS	ODH Subdivision Bypass Runoff (0.55 Ac) CFS
1 Hr	3.56	8.77	11.49	23.82	2.92	17.90	6.41	6.39	2.31
2 Hr	3.33	8.03	11.30	22.66	2.41	16.88	5.58	5.12	1.76
3 Hr	2.90	6.90	10.19	19.99	1.95	15.04	4.85	4.26	1.50
6Hr	2.01	4.73	7.51	14.25	1.38	10.93	3.42	3.05	1.07
12Hr	1.67	3.85	6.21	11.73	1.05	8.74	2.53	2.06	0.67
18Hr	1.50	3.44	5.54	10.48	0.95	7.74	2.20	1.81	0.58
24Hr**	1.23	2.80	4.55	8.58	0.77	6.34	1.79	1.46	0.47
48Hr	0.72	1.63	2.66	5.01	0.45	3.70	1.04	0.84	0.27
72Hr	0.51	1.17	1.91	3.59	0.32	2.66	0.75	0.60	0.19
120Hr	0.34	0.77	1.26	2.37	0.22	1.74	0.48	0.40	0.12
240Hr	0.21	0.47	0.77	1.45	0.13	1.06	0.29	0.24	0.08

EXHIBIT C

PROPOSED TRIBUTARY EXHIBIT C

SCALE: 1 inch = 40 ft. (IN FEET)

'D₂'
A=1.04 acres
Q_{MAX} = 5.31 cfs

Q_{MAX} = 11.17 C.F.S.

'D₃'
A=1.8 acres
Q_{MAX} = 5.86 cfs

'C₂'
A=0.60 acres
Q_{MAX} = 1.74 cfs

'C₃'
A=0.6 acres
Q_{MAX} = 2.50 cfs

A=3.5 acres
PARK
OUTLOT A

A=7.5 acres

A=0.55 acres

PROPOSED OVERLAND FLOW ROUTE (TYP.)

OUTLOT D $Q_{MAX\ 'FPD'}$ = 19.56 C.F.S.

$Q_{MAX\ 'NORTH'}$ = 8.39 C.F.S.

$Q_{MAX\ 'SOUTH'}$ = 1.53 C.F.S.

Q_{MAX} CAROL

FOREST PRESERVE
TIMBER BULL WOODS

FOREST PRESERVE
COUNTY CLERK'S DIVISION

OUTLOT C

OUTLOT B

OUTLOT E

FOREST EDGE DRIVE

NORTHWOOD DRIVE

GREEN BAY ROAD

WESTLEY ROAD

CAROL LANE

PROPOSED STREET

LOT 1 T/F=688.0
LOT 2 T/F=688.0
LOT 3 T/F=684.5
LOT 4 T/F=684.5
LOT 5 T/F=683.5
LOT 6 T/F=682.5
LOT 7 T/F=683.5
LOT 8 T/F=684.5
LOT 9 T/F=686.5
LOT 10 T/F=687.5
LOT 11 T/F=688.5
LOT 12 T/F=688.0
LOT 13 T/F=688.0
LOT 14 T/F=684.0
LOT 15 T/F=683.5
LOT 16 T/F=683.5
LOT 17 T/F=683.5
LOT 18 T/F=682.5
LOT 19 T/F=682.5
LOT 20 T/F=682.5
LOT 21 T/F=682.5
LOT 22 T/F=682.5
LOT 23 T/F=682.0
LOT 24 T/F=682.0
LOT 25 T/F=682.5
LOT 26 T/F=682.5
LOT 27 T/F=682.5
LOT 28 T/F=683.0
LOT 29 T/F=683.5

PIN 04-01-200-010

NORTH GATE MANOR 1st ADDITION DOC. 16986011

NORTH GATE SUBDIVISION DOC. 1852347

DUNAS FOREST CREST SUBDIVISION DOC. 6452807

UNSUBDIVIDED ODH'S SUBDIVISION DOC. 1830406

GLENCOE GOLF CLUB

OPEN SPACE EASEMENT AREA

STORM SEWER EASEMENT

STORMWATER MANAGEMENT AREA

DETENTION BASIN

10' EMERGENCY & PEDESTRIAN ACCESS EASEMENT & PUBLIC

4' WIDE BIOSWALE

PROPOSED PERMEABLE PAVERS FOR BMP CONTROL (TYP.)

INSTALL TURN DOWN EDGE SIDEWALK WHERE APPLICABLE.

SITE BENCHMARK:
N.E. BONNET BOLT ON FIRE HYDRANT
ELEVATION=690.27 NAVD88 (GEOID18)

REVISIONS		
DATE	DESCRIPTION	DRAWN BY
06/03/19	VILLAGE REVIEW	S.R.M.
07/22/19	REVISED ENTRANCE	S.R.M.
07/29/19	FOR SUBMITTAL	S.R.M.
12/06/19	FOR SUBMITTAL	S.R.M.
01/17/20	FOR SUBMITTAL	S.R.M.
02/20/20	FOR SUBMITTAL	S.R.M.
04/17/20	FOR SUBMITTAL	S.R.M.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH (262) 878-6200 | ig@igconsulting.net

DESIGN: K.C.L. | DRAFTING: S.R.M.
SCALE: 1"=40' | DATE: 05/06/2019
FIRM NO. 184-001330

FOREST EDGE SUBDIVISION
1801 GREEN BAY ROAD
GLENCOE, ILLINOIS

COPYRIGHT AS DATED © IG CONSULTING, INC.

G:\IG\18\18557\Eng\18557-9P.dwg

PROJECT No. 18557

1 of 1

TABLE 2

100 Year Critical Duration Analysis For Proposed Development and Bypass Flows					100-Year Critical Duration Analysis For Proposed Development				
100 Year Event Storm Duration	Prop. Development 100Yr HWL North Elevation	Prop. Development 100 Yr HWL South Elevation	Prop. Development Release Rate CFS Turnbull Woods	Prop. Development Release Rate CFS Carol Lane	Prop Development Release Rate North CFS	Prop development Release Rate South CFS	Prop. Development Release Rate 11.00 Acres CFS	Prop. Development 100 Yr HWL North Elevation	Prop Development 100 Yr HWL South Elevation
1 Hr	678.38	674.34	6.18	1.08	1.45	1.05	2.50	678.48	674.10
2 Hr**	678.34	676.50	5.35	1.34	1.42	1.28	2.70	678.40	675.98
3 Hr	678.28	677.53	4.41	1.44	1.38	1.36	2.74	678.32	676.73
6Hr	678.23	678.24	3.54	1.51	1.33	1.44	2.77	678.22	677.56
12Hr	678.33	678.35	5.24	1.52	1.35	1.51	2.86	678.24	678.23
18Hr*	678.49	678.50	8.39	1.53	1.40	1.52	2.92	678.36	678.34
24Hr	678.42	678.42	6.91	1.53	1.26	1.49	2.75	678.07	678.07
48Hr	678.20	678.19	3.05	1.50	1.17	1.39	2.56	677.88	677.04
72Hr	677.87	676.67	1.16	1.35	1.06	1.26	2.32	677.69	675.76
120Hr	677.48	674.55	0.94	1.11	0.68	1.05	1.73	677.15	674.08
240Hr	677.00	673.01	0.54	0.89	0.37	0.85	1.22	676.89	672.74

2-YEAR AND 10-YEAR EVENT CALCULATIONS

2-Year Critical Duration Analysis For Proposed Development and Bypass Flows					10-Year Critical Duration Analysis For Proposed Development and Bypass Flows			
100 Year Event Storm Duration	Prop. Development 2 Yr HWL North Elevation	Prop. Development 2 Yr HWL South Elevation	Prop. Development Release Rate CFS Turnbull Woods	Prop. Development Release Rate CFS Carol Lane	Prop Development 10-Yr HWL North Elevation	Prop development 10 Yr HWL South Elevation CFS	Prop. Development Release Rate CFS Turnbull Woods	Prop. Development Release Rate CFS Carol Lane
1 Hr	677.86	670.95	1.16	0.46	678.13	671.97	2.20	0.71
2 Hr**	677.90	671.24	1.18	0.55	678.12	672.66	2.09	0.83
3 Hr	677.89	671.36	1.17	0.58	678.09	672.87	1.81	0.87
6Hr	677.82	671.49	1.14	0.61	678.02	673.16	1.30	0.92
12Hr	677.78	671.67	1.12	0.65	677.98	673.51	1.22	0.97
18Hr	677.74	671.79	1.09	0.67	677.96	673.64	1.21	0.99
24Hr*	677.52	671.77	0.96	0.67	677.92	673.51	1.19	0.97
48Hr	677.07	671.78	0.61	0.67	677.76	673.18	1.10	0.92
72Hr	676.93	671.59	0.43	0.63	677.29	672.83	0.80	0.87
120Hr	676.82	671.28	0.27	0.56	676.99	672.26	0.52	0.77
240Hr	676.73	671.01	0.15	0.48	676.84	671.66	0.30	0.64

APPENDIX A

STORMWATER CALCULATIONS

DRAW DOWN TIME

Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.20	117	676.62	0.15	0.05	0.10	0.00
4.00	0.42	291	676.81	0.37	0.26	0.11	0.00
5.00	0.63	473	676.93	0.55	0.44	0.11	0.00
6.00	0.96	948	677.16	0.80	0.69	0.11	0.00
7.00	1.11	1,459	677.37	0.98	0.86	0.12	0.00
8.00	1.39	2,052	677.60	1.13	1.01	0.12	0.00
9.00	1.87	2,888	677.89	1.82	1.17	0.65	0.00
10.00	2.38	3,040	677.94	2.34	1.20	1.14	0.00
11.00	4.21	3,398	678.05	4.13	1.48	2.65	0.00
12.00	4.92	3,511	678.09	4.94	1.77	3.17	0.00
13.00	**3.50**	**3,354**	**678.04**	**3.07**	**1.39**	**1.68**	0.00
14.00	**5.30**	**4,554**	**678.39**	**7.84**	**6.38**	**1.46**	0.00
15.00	3.54	3,955	678.22	3.39	3.39	0.00	0.00
16.00	1.23	3,511	678.09	1.77	1.77	0.00	0.00
17.00	2.58	3,466	678.07	1.65	1.65	0.00	0.00
18.00	1.09	3,215	677.99	1.23	1.23	0.00	0.00
19.00	0.05	1,289	677.30	0.81	0.81	0.00	0.00
20.00	0.04	133	676.65	0.07	0.07	0.00	0.00
21.00	0.03	105	676.60	0.03	0.03	0.00	0.00
22.00	0.00	87	676.54	0.01	0.01	0.01	0.00
→ 23.00	0.00	76	676.20	0.00	0.00	0.00	0.00
24.00	0.00	72	675.90	0.00	0.00	0.00	0.00

DRAW DOWN TIME

Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.84	2,667	670.30	0.18	0.18	0.00	0.00
6.00	1.77	9,285	670.85	0.43	0.43	0.00	0.00
8.00	2.49	20,426	671.37	0.58	0.58	0.00	0.00
10.00	**5.22**	42,795	672.36	0.78	0.78	0.00	0.00
12.00	**11.67**	**101,118**	**675.67**	**1.24**	**1.24**	**0.00**	**0.00**
14.00	5.42	**135,970**	**678.36**	**4.55**	**1.52**	**3.03**	**0.00**
16.00	2.11	133,889	678.13	1.50	1.50	0.00	0.00
18.00	1.84	132,782	678.01	1.49	1.49	0.00	0.00
20.00	0.00	123,905	677.23	1.46	1.41	0.04	0.00
22.00	0.01	113,812	676.52	1.34	1.34	0.00	0.00
24.00	0.00	104,431	675.90	1.27	1.27	0.00	0.00
26.00	0.00	95,564	675.20	1.19	1.19	0.00	0.00
28.00	0.00	87,300	674.54	1.11	1.11	0.00	0.00
30.00	0.00	79,540	674.08	1.05	1.05	0.00	0.00
32.00	0.00	72,176	673.71	1.00	1.00	0.01	0.00
34.00	0.00	65,170	673.37	0.95	0.95	0.00	0.00
36.00	0.00	58,507	673.06	0.90	0.90	0.00	0.00
38.00	0.00	52,178	672.78	0.86	0.86	0.00	0.00
40.00	0.00	46,177	672.51	0.81	0.81	0.00	0.00
42.00	0.00	40,498	672.26	0.77	0.77	0.00	0.00
44.00	0.00	35,141	672.03	0.72	0.72	0.00	0.00
46.00	0.00	30,111	671.80	0.68	0.68	0.00	0.00
48.00	0.00	25,408	671.59	0.63	0.63	0.00	0.00
50.00	0.00	21,030	671.40	0.59	0.59	0.00	0.00
52.00	0.00	16,979	671.22	0.54	0.54	0.00	0.00
54.00	0.00	13,264	671.04	0.49	0.49	0.00	0.00
56.00	0.00	9,897	670.88	0.44	0.44	0.00	0.00
58.00	0.00	6,884	670.72	0.39	0.39	0.00	0.00
60.00	0.00	4,441	670.48	0.29	0.29	0.00	0.00
62.00	0.00	2,729	670.31	0.18	0.18	0.00	0.00
64.00	0.00	1,786	670.20	0.09	0.09	0.00	0.00
66.00	0.00	1,292	670.14	0.05	0.05	0.00	0.00
68.00	0.00	1,002	670.11	0.03	0.03	0.00	0.00
70.00	0.00	814	670.09	0.02	0.02	0.00	0.00
72.00	0.00	684	670.08	0.02	0.02	0.00	0.00
74.00	0.00	589	670.07	0.01	0.01	0.00	0.00
76.00	0.00	516	670.06	0.01	0.01	0.00	0.00
78.00	0.00	459	670.05	0.01	0.01	0.00	0.00
80.00	0.00	414	670.05	0.01	0.01	0.00	0.00
→ 82.00	0.00	376	670.04	0.00	0.00	0.00	0.00
84.00	0.00	345	670.04	0.00	0.00	0.00	0.00
86.00	0.00	318	670.04	0.00	0.00	0.00	0.00
88.00	0.00	295	670.03	0.00	0.00	0.00	0.00
90.00	0.00	275	670.03	0.00	0.00	0.00	0.00
92.00	0.00	258	670.03	0.00	0.00	0.00	0.00
94.00	0.00	242	670.03	0.00	0.00	0.00	0.00
96.00	0.00	229	670.03	0.00	0.00	0.00	0.00
98.00	0.00	217	670.02	0.00	0.00	0.00	0.00
100.00	0.00	206	670.02	0.00	0.00	0.00	0.00

STORM SEWER CALCUATION - 1801 Green Bay Road

FREQUENCY: 10 & 100

RUNOFF COEFF "C": 0.73

SEWER ROUGH. COEFF. RCP 0.013 PVC 0.009

STATION		DRAINAGE AREA			A X C		FLOW TIME			RAINFALL INTENSITY	TOTAL RUNOFF	SEWER	PIPE	PIPE	MANNING'S	PIPE	VEL.	CAP	Design Sewer Capacity
FROM	TO	INCREMENT FT2	INCREMENT AC	TOTAL AC	INCREMENT	TOTAL	TO UPPER END MIN	INSECTION MIN	T/C MIN	I IN/HR	Q = C.I.A. CFS	LENGTH FT	DIA IN	Material RCP	COFF.	SLOPE %	FPS	CFS	(%)
SOUTH																			
Y.D. #12A	C.B. #12	8,761	0.20	0.20	0.15	0.15	11.53	0.00	11.53	10.53	1.55	54	10	PVC	0.009	1.00	5.80	3.16	48.85%
C.B. #12	C.B. #11	12,812	0.29	0.50	0.21	0.36	11.53	0.16	11.69	10.44	3.77	22	12	RCP	0.013	1.20	4.97	3.90	96.71%
C.B. #11	C.B. #9B	8,996	0.21	0.70	0.15	0.51	11.69	0.07	11.76	10.41	5.33	100	15	RCP	0.013	1.00	5.26	6.46	82.56%
Y.D. #9C	STM MH #9B	6,893	0.16	0.16	0.12	0.12	10.30	0.00	10.30	11.16	1.29	0	10	PVC	0.009	1.00	5.80	3.16	40.73%
STM MH #9B	C.B. #9	0	0.00	0.86	0.00	0.63	11.64	0.32	11.96	10.30	6.47	125	15	RCP	0.013	1.00	5.27	6.47	99.90%
C.B. #10	C.B. #9	17,376	0.40	0.40	0.29	0.29	10.30	0.00	10.30	11.16	3.25	22	15	RCP	0.013	1.00	5.26	6.46	50.31%
Y.D. #9A	C.B. #9	5,604	0.13	0.13	0.09	0.09	5.46	0.00	5.46	12.18	1.14	30	10	PVC	0.009	1.00	5.80	3.16	36.14%
C.B. #9	C.B. #7	13,783	0.32	1.70	0.23	1.24	12.08	0.39	12.47	10.08	12.54	145	21	RCP	0.013	1.00	6.59	15.85	79.13%
C.B. #8	SYSTEM 5	17,960	0.41	0.41	0.30	0.30	6.00	0.00	6.00	12.00	3.61	N/A	N/A	-	-	-	-	-	-
C.B. #7	C.B. #6	16,976	0.39	2.51	0.28	1.83	12.47	0.36	12.83	9.94	18.18	117	24	RCP	0.013	0.75	6.24	19.59	92.82%
C.B. #6	C.B. #3	0	0.00	2.51	0.00	1.83	12.83	0.31	13.14	9.64	18.00	155	24	RCP	0.013	0.75	6.24	19.59	91.88%
C.B. #3	SYSTEM 4	0	0.00	2.51	0.00	1.83	13.14	0.41	13.55	9.69	17.75	4	24	RCP	0.013	0.75	6.24	19.59	90.63%
NORTH A																			
Y.D. #35A	C.B. #35	5,349	0.12	0.12	0.09	0.09	10.19	0.00	10.19	6.69	0.60	102	10	PVC	0.009	1.00	5.80	3.16	18.95%
C.B. #36	C.B. #35	7,038	0.16	0.16	0.12	0.12	5.00	0.00	5.00	7.44	0.88	22	12	RCP	0.013	0.50	3.21	2.52	34.83%
C.B. #35	C.B. #34	18,561	0.43	0.71	0.31	0.43	10.19	0.29	10.48	6.61	2.83	87	12	RCP	0.013	1.25	5.07	3.98	71.14%
C.B. #34	C.B. #33	0	0.00	0.71	0.00	0.43	10.48	0.25	10.73	6.52	2.80	67	12	RCP	0.013	1.25	5.07	3.98	70.22%
C.B. #33A	C.B. #33	10,821	0.25	0.25	0.18	0.18	6.36	0.00	6.36	7.30	1.32	22	12	RCP	0.013	1.00	4.54	3.56	37.16%
C.B. #33	C.B. #32	20,781	0.48	1.44	0.35	1.05	10.73	0.22	10.95	6.43	6.74	56	15	RCP	0.013	1.50	6.45	7.91	85.19%
C.B. #32	MH #31	2,406	0.06	1.49	0.04	1.09	5.99	0.31	6.30	7.15	7.78	88	15	RCP	0.013	1.50	6.45	7.91	98.38%
NORTH B																			
Y.D. #45A	C.B. #45	13,039	0.30	0.30	0.22	0.22	9.50	0.00	9.50	6.83	1.49	40	10	PVC	0.009	1.00	5.80	3.16	47.16%
C.B. #45	C.B. #44	19,709	0.45	0.75	0.33	0.55	9.50	0.11	9.61	6.81	3.74	22	12	RCP	0.013	1.25	5.07	3.98	93.83%
C.B. #44	C.B. #43	4,491	0.10	0.85	0.08	0.62	9.61	0.09	9.70	6.80	4.24	55	15	RCP	0.013	1.00	5.26	6.46	65.69%
C.B. #43	C.B. #42	0	0.00	0.85	0.00	0.62	9.70	0.17	9.87	6.79	4.24	72	15	RCP	0.013	1.00	5.26	6.46	65.60%
C.B. #41	C.B. #42	17,513	0.40	0.40	0.29	0.29	9.77	0.00	9.77	6.80	2.00	22	12	RCP	0.013	0.50	3.21	2.52	79.22%
C.B. #42	C.B. #38	8,624	0.20	1.45	0.14	1.06	9.87	0.23	10.10	6.74	7.16	112	15	RCP	0.013	1.25	5.89	7.22	99.12%
C.B. #40	C.B. #39	3,602	0.08	0.08	0.06	0.06	5.00	0.00	5.00	7.44	0.45	22	12	RCP	0.013	0.50	3.21	2.52	17.83%
C.B. #39	C.B. #38	7,295	0.17	0.25	0.12	0.18	5.00	0.09	5.09	7.40	1.35	76	12	RCP	0.013	1.00	4.54	3.56	37.93%
C.B. #38	C.B. #16	0	0.00	1.71	0.00	1.24	10.10	0.32	10.42	6.63	8.25	135	18	RCP	0.013	1.00	5.94	10.50	78.56%
NORTH C																			
C.B. #30	C.B. #29	29,092	0.67	0.67	0.49	0.49	12.27	0.00	12.27	10.14	4.94	90	12	RCP	0.013	2.00	6.42	5.04	98.12%
C.B. #29	C.B. #28	29,734	0.68	1.35	0.50	0.99	12.27	0.23	12.50	10.04	9.90	94	18	RCP	0.013	1.00	5.94	10.50	94.23%
C.B. #28	C.B. #27	14,209	0.33	1.68	0.24	1.22	12.79	0.26	13.05	9.86	12.07	70	18	RCP	0.013	1.50	7.28	12.87	93.81%
C.B. #27	C.B. #26	17,904	0.41	2.09	0.30	1.52	13.33	0.16	13.49	9.71	14.80	120	21	RCP	0.013	1.50	8.07	19.41	76.25%
C.B. #26	C.B. #25	0	0.00	2.09	0.00	1.52	13.74	0.25	13.99	9.55	14.55	150	21	RCP	0.013	1.50	8.07	19.41	75.00%
C.B. #25	SYSTEM 6	19,976	0.46	2.55	0.33	1.86	14.28	0.31	14.59	9.39	17.45	3	21	RCP	0.013	1.25	7.37	17.72	98.52%
C.B. #23	SYSTEM 6	152,724	3.51	3.51	2.56	2.56	21.48	0.00	21.48	7.50	19.20	N/A	24	RCP	0.013	0.75	6.24	19.59	97.98%
C.B. #22	SYSTEM 6	152,724	3.51	3.51	2.56	2.56	21.48	0.00	21.48	7.50	19.20	N/A	24	RCP	0.013	0.75	6.24	19.59	97.98%
EAST INLETS											MAX INLET CAP.								
C.B. #3	SYSTEM 4	-	-	-	-	-	-	-	-	-	6.23	N/A	24	RCP	0.013	1.00	7.20	22.62	27.54%
C.B. #13	SYSTEM 4	-	-	-	-	-	-	-	-	-	6.23	N/A	24	RCP	0.013	1.00	7.20	22.62	27.54%
C.B. #14	SYSTEM 4	-	-	-	-	-	-	-	-	-	6.23	N/A	24	RCP	0.013	1.00	7.20	22.62	27.54%
Y.D. #15	SYSTEM 4	-	-	-	-	-	-	-	-	-	2.08	N/A	10	PVC	0.009	1.00	5.80	3.16	65.72%
Y.D. #16A	SYSTEM 4	-	-	-	-	-	-	-	-	-	2.08	N/A	10	PVC	0.009	1.00	5.80	3.16	65.72%
C.B. #18	SYSTEM 4	-	-	-	-	-	-	-	-	-	6.23	N/A	24	RCP	0.013	1.00	7.20	22.62	27.54%

INLET CAPACITY CALCULATION - 1800 Green Bay Road

Selected Inlets		
Model	Inlet Area (S.F.)	
R-2540	1.10	Circular C.B.
R-2560-EB	1.80	Beehive
R-2560-D8	1.30	Beehive
R-3038-A	1.50	Gutter/Curb
R-3502-D2	1.90	Gutter/Curb barrier?
R-3503-A	1.30	Gutter/Curb
R-3502	1.40	ROAD
R-2586-H	1.30	Y.D.
R-3337-A	1.10	Gutter

RUNOFF COEFF "C":	0.73
INLET COEFF "C":	0.61
GRAV. CONSTANT "G":	32.2
MAX. HEAD "H":	0.5

RAIN EVENT	STRUCTURE	AREA FT2	AREA AC	TIME OF CONCENTRATION MIN	RAINFALL INTENSITY (I) IN/HR	RUNOFF (Q) CFS	INLET AREA (A) FT2	MAX. POSSIBLE FLOW CFS	INLET FLOW CHECK OK/NOT OK	HEAD @ FLOW USED H (FT)	CHECK OK/NOT OK
100	C.B. #30	29,092	0.67	10.70	10.82	5.28	1.80	6.23	OK	0.36	OK
100	C.B. #29	29,734	0.68	13.37	9.7	4.83	1.80	6.23	OK	0.30	OK
100	C.B. #28	14,209	0.33	10.70	10.82	2.58	1.80	6.23	OK	0.09	OK
100	C.B. #27	15,242	0.35	8.15	11.6	2.96	1.80	6.23	OK	0.11	OK
100	C.B. #25	25,608	0.59	10.57	11	4.72	1.80	6.23	OK	0.29	OK
100	C.B. #23	13,135	0.30	5.00	12.36	2.72	1.40	4.85	OK	0.16	OK
100	C.B. #22	15,444	0.35	5.00	12.36	3.20	1.40	4.85	OK	0.22	OK
100	Y.D. #12A	8,761	0.20	11.53	10.53	1.55	1.30	4.50	OK	0.06	OK
100	C.B. #12	12,812	0.29	14.78	9.35	2.01	1.40	4.85	OK	0.09	OK
100	C.B. #11	8,996	0.21	7.50	7	1.06	1.40	4.85	OK	0.02	OK
100	Y.D. #9C	6,893	0.16	11.06	10.74	1.24	1.30	4.50	OK	0.04	OK
100	Y.D. #9A	5,604	0.13	5.46	12.18	1.14	1.30	4.50	OK	0.03	OK
100	C.B. #9	13,818	0.32	11.64	10.46	2.42	1.40	4.85	OK	0.12	OK
100	C.B. #8	17,960	0.41	6.00	12	3.61	1.40	4.85	OK	0.28	OK
100	C.B. #7	16,940	0.39	7.85	11.65	3.31	1.40	4.85	OK	0.23	OK
100	C.B. #10	17,376	0.40	10.30	11.16	3.25	1.40	4.85	OK	0.22	OK
100	C.B. #5	32,330	0.74	8.78	11.5	6.23	1.80	6.23	NOT OK	0.50	NOT OK
100	C.B. #4	15,605	0.36	13.15	9.85	2.58	1.80	6.23	OK	0.09	OK
10	Y.D. #45A	13,039	0.30	9.50	6.83	1.49	1.30	4.50	OK	0.06	OK
10	C.B. #45	19,495	0.45	11.42	6.31	2.06	1.40	4.85	OK	0.09	OK
10	C.B. #44	4,491	0.10	5.00	7.44	0.56	1.40	4.85	OK	0.01	OK
10	C.B. #42	8,624	0.20	7.43	7.03	1.02	1.40	4.85	OK	0.02	OK
10	C.B. #41	14,931	0.34	9.77	6.75	1.69	1.40	4.85	OK	0.06	OK
10	C.B. #40	3,602	0.08	5.00	7.44	0.45	1.40	4.85	OK	0.00	OK
10	C.B. #39	7,295	0.17	5.00	7.44	0.91	1.40	4.85	OK	0.02	OK
10	C.B. #36	7,038	0.16	5.00	7.44	0.88	1.40	4.85	OK	0.02	OK
10	Y.D. #35A	5,349	0.12	10.19	6.71	0.60	1.30	4.50	OK	0.01	OK
10	C.B. #35	18,561	0.43	15.13	5.55	1.73	1.40	4.85	OK	0.06	OK

10	C.B. #33	20,781	0.48	5.00	7.44	2.59	1.40	4.85	OK	0.14	OK
10	C.B. #32	2,406	0.06	5.00	7.44	0.30	1.40	4.85	OK	0.00	OK
10	C.B. #33A	10,821	0.25	6.36	7.15	1.30	1.40	4.85	OK	0.04	OK
100	C.B. #3						1.80	6.23	OK	0.00	OK
100	C.B. #13						1.80	6.23	OK	0.00	OK
100	C.B. #14						1.80	6.23	OK	0.00	OK
100	Y.D. #?						1.30	4.50	OK	0.00	OK
100	Y.D. #?						1.30	4.50	OK	0.00	OK
100	C.B. #18						1.80	6.23	OK	0.00	OK
100	TRIB TOTAL	242,070	5.56	24.00	7.07	28.68		33.92			
100 Q	C.B. #39/#40	78,977	1.81	14.28	9.47	12.53					
10	C.B. #13		0.25	10.65	6.48	1.20					
10	C.B. #14	11,058	0.20	10.47	6.605	0.95					
10	C.B. #15	8,625	0.18	12.68	6.29	0.82					
10	C.B. #16	7,752	0.17	9.62	6.81	0.84					
10/100	Y.D. EAST	7,390	0.25	10.65	10.95	2.03	0.6	2.08	OK	0.48	OK
Y.D. #s	13, 14, 15, 16	11,058									

Custom Storage

Custom storage may be defined in three ways:

1) Direct entry of *cumulative* (total) storage at various elevations, which requires no further calculations.

2) Entry of *incremental* storage, that is, the volume of horizontal sections across the pond. These sections are summed by the program to produce the cumulative storage.

3) Entry of *surface areas* at various elevations, from which HydroCAD determines the incremental (and cumulative) storage at each elevation.


The third option is often the most convenient, since it uses readily available data, such as the surface area at each contour elevation. The actual storage calculation is based on the selected *pond shape*, as described below.

Custom Prismatic Storage

Each stage is taken as a horizontal section of a prism. This provides accurate volumes for four-sided ponds when zero, one or two (opposing) sides of the pond are sloping, and the other sides are vertical. The traditional "average area" method accurately determines the volume of these shapes.

$$V = h \frac{A_1 + A_2}{2} \qquad \text{Eq. 30}$$

V=Volume of section
h=Height of section
A_1=Area of bottom of section
A_2=Area of top of section



Since the aspect ratio of prismatic shapes is undefined, the wetted area cannot be determined, making this shape incompatible with exfiltration calculations. One of the other shapes should be selected when wetted area is required.

PROVIDED CHAMBER SYSTEM STORAGE VOLUMES					REQUIRED STORAGE VOLUMES
CHAMBER SYSTEM NO.	STONE QUANTITY CUBIC FEET	STORAGE IN STONE (36%) CUBIC FEET	CHAMBER STORAGE CUBIC FEET	TOTAL VOLUME CUBIC FEET	
1 (902HD)	49,023	17,648	31,708	49,356	
1 (280 HD)	39,054	14,060	16,291	30,351	
2	17,557	6,320	4,520	10,840	
3	23,634	8,508	12,835	21,343	
4	7,907	2,847	2,101	4,948	
5	13,458	4,845	3,619	8,464	
6	9,005	3,242	2,525	5,767	
7	14,388	5,180	4,573	9,752	
SUB–TOTAL				140,821	135,796
DETENTION BASIN 1				5,071	4,446
TOTAL				**145,892**	**140,242**

STORM SEWER TRIBUTARY EXHIBIT

SCALE: 1 inch = 40 ft. (IN FEET)

FOREST EDGE SUBDIVISION

1801 GREEN BAY ROAD

GLENCOE, ILLINOIS

PROJECT No. 18557

1 of 1

COPYRIGHT AS DATED © IG CONSULTING, INC.

IG CONSULTING, INC.
CONSULTING CIVIL ENGINEERS, PLANNERS & LAND SURVEYORS
300 MARQUARDT DRIVE WHEELING, ILLINOIS 60090 PH. (847) 215-1133 | FAX (847) 215-1177
1129 MAIN STREET UNION GROVE, WISCONSIN 53182 PH. (262) 878-6200 | ig@igconsulting.net
FIRM NO. 184-001330

STORM SEWER TRIBUTARY EXHIBIT	DESIGN: K.C.L.	DRAFTING: S.R.M.
	SCALE: 1"=40'	DATE: 02/20/20

REVISIONS

DATE	DESCRIPTION	DRAWN BY
04/17/20	PER VILLAGE COMMENTS	S.R.M.

G:\IG\18\18557\Eng\18557-9P.dwg

CAPACITY CALCULATION FOR SWALE-M

100yr FLOW - ONSITE TRIBUTARY AREA

A = 1.49 (acres)

C = 0.73

i_{100} = 8.23 in/hr BASED ON A 18.3min T_C

Q_{100} = CiA
= 8.97 cfs to swale

Q_{swale} = VA

where A = 6.0 sf

$$V = \frac{1.49 (R^{2/3})(S^{1/2})}{n}$$

where $R = \frac{A}{P}$

slope, S= 1.5 %
wetted perimeter P= 10.25 ft.
Manning's n_{grass}= 0.080

V= 1.60 f/s

Q_{swale} = VA
= 9.58 cfs > 8.97 cfs OK

Mannings Formula

$Q = (1.486/n)AR_h^{2/3}S^{1/2}$


R = A/P

A = cross sectional area

P= wetted perimeter

S = slope of channel

n = Manning's roughness coefficie



$V = (1.49/n)R_h^{2/3}S^{1/2}$

Q = V x A

	INPUT
z (sideslope)=	4
z (sideslope)=	4
b (btm width, ft)=	2
d (depth, ft)=	1
S (slope, ft/ft)	0.015
n_{low} =	0.08
n_{high} =	0.08

Clear Data Entry Cells

Depth, ft	Area, sf	Wetted	Hydrauli	Velocity,	Low N Flow, cfs	High N Velocity, fps	High N Flow, cfs
1	6.0	10.25	0.59	1.59	9.55	1.59	9.55

T = 10

Dm = 0.600

IG Consulting, Inc.
CONSULTING CIVIL ENGINEERS & SURVEYORS
300 Marquardt Drive, Wheeling, IL 60090 847-215-1133

SWALE CAPACITY CALCULATION (SWALE-M)
1801 GREENBAY
Project: 1801 GREENBAY RD
GLENCOE
Date: 17-Apr-20
IG No. 18557

CAPACITY CALCULATION FOR SWALE-N

100yr FLOW - ONSITE TRIBUTARY AREA

A = 3.95 (acres)

C = 0.73

i_{100} = 7.07 in/hr BASED ON A 24min T_C

Q_{100} = CiA
= 20.37 cfs to swale

Q_{swale} = VA

where A = 12.0 sf

$$V = \frac{1.49 (R^{2/3})(S^{1/2})}{n}$$

where $R = \frac{A}{P}$

slope, S= 1.5 %
wetted perimeter P= 16.25 ft.
Manning's n_{grass}= 0.080

V= 1.86 f/s

Q_{swale} = VA
= 22.37 cfs > 20.37 cfs OK

Mannings Formula

$Q = (1.486/n)AR_h^{2/3}S^{1/2}$


R = A/P

A = cross sectional area

P= wetted perimeter

S = slope of channel

n = Manning's roughness coefficie



$V = (1.49/n)R_h^{2/3}S^{1/2}$

Q = V x A

	INPUT
z (sideslope)=	4
z (sideslope)=	4
b (btm width, ft)=	8
d (depth, ft)=	1
S (slope, ft/ft)	0.015
n_{low} =	0.08
n_{high} =	0.08

Clear Data Entry Cells

Depth, ft	Area, sf	Wetted	Hydrauli	Velocity,	Low N Flow, cfs	High N Velocity, fps	High N Flow, cfs		
1	12.0	16.25	0.74	1.86	22.31	1.86	22.31	T =	16
								Dm =	0.750

IG Consulting, Inc.
CONSULTING CIVIL ENGINEERS & SURVEYORS
300 Marquardt Drive, Wheeling, IL 60090 847-215-1133

SWALE CAPACITY CALCULATION (SWALE-N)
1801 GREENBAY
Project: 1801 GREENBAY RD
GLENCOE
Date: 17-Apr-20
IG No. 18557

CAPACITY CALCULATION FOR SWALE-P

100yr FLOW - ONSITE TRIBUTARY AREA

A = 3.00 (acres)

C = 0.73

i_{100} = 7.07 in/hr BASED ON A 24min T_C

Q_{100} = CiA
= 15.50 cfs to swale

Q_{swale} = VA

where A = 10.0 sf

$$V = \frac{1.49 (R^{2/3})(S^{1/2})}{n}$$

where $R = \frac{A}{P}$

slope, S= 1.2 %
wetted perimeter P= 14.25 ft.
Manning's n_{grass}= 0.080

V= 1.61 f/s

Q_{swale} = VA
= 16.11 cfs > 15.50 cfs OK

Mannings Formula

$Q = (1.486/n)AR_h^{2/3}S^{1/2}$


R = A/P

A = cross sectional area

P= wetted perimeter

S = slope of channel

n = Manning's roughness coefficie



$V = (1.49/n)R_h^{2/3}S^{1/2}$

Q = V x A


	INPUT
z (sideslope)=	4
z (sideslope)=	4
b (btm width, ft)=	6
d (depth, ft)=	1
S (slope, ft/ft)	0.012
n_{low} =	0.08
n_{high} =	0.08

Clear Data Entry Cells

Depth, ft	Area, sf	Wetted	Hydrauli	Velocity,	Low N Flow, cfs	High N Velocity, fps	High N Flow, cfs		
1	10.0	14.25	0.70	1.61	16.07	1.61	16.07	T =	14
								Dm =	0.714

IG Consulting, Inc.
CONSULTING CIVIL ENGINEERS & SURVEYORS
300 Marquardt Drive, Wheeling, IL 60090 847-215-1133

SWALE CAPACITY CALCULATION (SWALE-P)
1801 GREENBAY
Project: 1801 GREENBAY RD
GLENCOE
Date: 17-Apr-20
IG No. 18557



Subcat Reach Pond Link

Routing Diagram for D_Detention 11.00 Ac_Cultec_4-19-20_6REV
Prepared by {enter your company name here}, Printed 4/21/2020
HydroCAD® 10.00-25 s/n 00783 © 2019 HydroCAD Software Solutions LLC

Summary for Subcatchment 1S: North Property


Runoff = 13.68 cfs @ 0.44 hrs, Volume= 0.674 af, Depth= 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	4.03	2.31	4.53
0.02	0.05	0.00	0.00	1.06	4.03	2.31	4.32
0.04	0.21	0.00	0.00	1.08	4.03	2.31	4.09
0.06	0.46	0.00	0.00	1.10	4.03	2.31	3.86
0.08	0.72	0.04	0.00	1.12	4.03	2.31	3.60
0.10	1.00	0.13	0.02	1.14	4.03	2.31	3.32
0.12	1.25	0.25	0.09	1.16	4.03	2.31	3.00
0.14	1.46	0.36	0.27	1.18	4.03	2.31	2.68
0.16	1.63	0.45	0.61	1.20	4.03	2.31	2.36
0.18	1.78	0.55	1.19	1.22	4.03	2.31	2.05
0.20	1.93	0.65	2.03	1.24	4.03	2.31	1.76
0.22	2.08	0.75	3.15	1.26	4.03	2.31	1.49
0.24	2.21	0.84	4.48	1.28	4.03	2.31	1.25
0.26	2.34	0.94	5.93	1.30	4.03	2.31	1.03
0.28	2.46	1.03	7.39	1.32	4.03	2.31	0.85
0.30	2.56	1.10	8.80	1.34	4.03	2.31	0.71
0.32	2.66	1.18	10.09	1.36	4.03	2.31	0.59
0.34	2.75	1.25	11.24	1.38	4.03	2.31	0.49
0.36	2.83	1.31	12.18	1.40	4.03	2.31	0.41
0.38	2.90	1.37	12.91	1.42	4.03	2.31	0.34
0.40	2.97	1.42	13.36	1.44	4.03	2.31	0.29
0.42	3.04	1.48	13.63	1.46	4.03	2.31	0.24
0.44	3.10	1.53	**13.68**	1.48	4.03	2.31	0.20
0.46	3.17	1.58	13.61	1.50	4.03	2.31	0.16
0.48	3.22	1.63	13.42	1.52	4.03	2.31	0.14
0.50	3.28	1.67	13.14	1.54	4.03	2.31	0.11
0.52	3.32	1.71	12.79	1.56	4.03	2.31	0.09
0.54	3.36	1.74	12.37	1.58	4.03	2.31	0.08
0.56	3.39	1.77	11.95	1.60	4.03	2.31	0.06
0.58	3.43	1.80	11.48	1.62	4.03	2.31	0.05
0.60	3.46	1.83	11.02	1.64	4.03	2.31	0.04
0.62	3.49	1.85	10.52	1.66	4.03	2.31	0.03
0.64	3.53	1.88	10.01	1.68	4.03	2.31	0.03
0.66	3.56	1.91	9.49	1.70	4.03	2.31	0.02
0.68	3.59	1.93	8.96	1.72	4.03	2.31	0.02
0.70	3.62	1.96	8.45	1.74	4.03	2.31	0.01
0.72	3.66	1.99	7.96	1.76	4.03	2.31	0.01
0.74	3.69	2.02	7.52	1.78	4.03	2.31	0.01
0.76	3.72	2.05	7.10	1.80	4.03	2.31	0.01
0.78	3.75	2.07	6.75	1.82	4.03	2.31	0.00
0.80	3.79	2.10	6.43	1.84	4.03	2.31	0.00
0.82	3.82	2.13	6.18	1.86	4.03	2.31	0.00
0.84	3.85	2.16	5.96	1.88	4.03	2.31	0.00
0.86	3.88	2.18	5.78	1.90	4.03	2.31	0.00
0.88	3.91	2.21	5.64	1.92	4.03	2.31	0.00
0.90	3.93	2.22	5.51	1.94	4.03	2.31	0.00
0.92	3.94	2.24	5.41	1.96	4.03	2.31	0.00
0.94	3.96	2.25	5.30	1.98	4.03	2.31	0.00
0.96	3.98	2.27	5.19	2.00	4.03	2.31	0.00
0.98	4.00	2.29	5.05				
1.00	**4.03**	**2.31**	4.90				
1.02	4.03	2.31	4.72				

Summary for Subcatchment 7S: South Property


Runoff = 25.34 cfs @ 0.56 hrs, Volume= 1.445 af, Depth> 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	4.03	2.31	11.94
0.02	0.05	0.00	0.00	1.06	4.03	2.31	11.56
0.04	0.21	0.00	0.00	1.08	4.03	2.31	11.19
0.06	0.46	0.00	0.00	1.10	4.03	2.31	10.78
0.08	0.72	0.04	0.00	1.12	4.03	2.31	10.34
0.10	1.00	0.13	0.00	1.14	4.03	2.31	9.91
0.12	1.25	0.25	0.06	1.16	4.03	2.31	9.42
0.14	1.46	0.36	0.17	1.18	4.03	2.31	8.92
0.16	1.63	0.45	0.38	1.20	4.03	2.31	8.40
0.18	1.78	0.55	0.74	1.22	4.03	2.31	7.82
0.20	1.93	0.65	1.31	1.24	4.03	2.31	7.25
0.22	2.08	0.75	2.07	1.26	4.03	2.31	6.66
0.24	2.21	0.84	3.07	1.28	4.03	2.31	6.08
0.26	2.34	0.94	4.40	1.30	4.03	2.31	5.53
0.28	2.46	1.03	5.97	1.32	4.03	2.31	4.99
0.30	2.56	1.10	7.74	1.34	4.03	2.31	4.48
0.32	2.66	1.18	9.70	1.36	4.03	2.31	4.00
0.34	2.75	1.25	11.73	1.38	4.03	2.31	3.56
0.36	2.83	1.31	13.77	1.40	4.03	2.31	3.16
0.38	2.90	1.37	15.78	1.42	4.03	2.31	2.79
0.40	2.97	1.42	17.70	1.44	4.03	2.31	2.44
0.42	3.04	1.48	19.42	1.46	4.03	2.31	2.14
0.44	3.10	1.53	20.99	1.48	4.03	2.31	1.89
0.46	3.17	1.58	22.35	1.50	4.03	2.31	1.67
0.48	3.22	1.63	23.45	1.52	4.03	2.31	1.47
0.50	3.28	1.67	24.32	1.54	4.03	2.31	1.29
0.52	3.32	1.71	24.85	1.56	4.03	2.31	1.14
0.54	3.36	1.74	25.18	1.58	4.03	2.31	1.01
0.56	3.39	1.77	**25.34**	1.60	4.03	2.31	0.89
0.58	3.43	1.80	25.19	1.62	4.03	2.31	0.78
0.60	3.46	1.83	24.93	1.64	4.03	2.31	0.68
0.62	3.49	1.85	24.55	1.66	4.03	2.31	0.60
0.64	3.53	1.88	24.04	1.68	4.03	2.31	0.53
0.66	3.56	1.91	23.47	1.70	4.03	2.31	0.46
0.68	3.59	1.93	22.78	1.72	4.03	2.31	0.41
0.70	3.62	1.96	22.04	1.74	4.03	2.31	0.36
0.72	3.66	1.99	21.28	1.76	4.03	2.31	0.31
0.74	3.69	2.02	20.45	1.78	4.03	2.31	0.28
0.76	3.72	2.05	19.65	1.80	4.03	2.31	0.24
0.78	3.75	2.07	18.86	1.82	4.03	2.31	0.21
0.80	3.79	2.10	18.06	1.84	4.03	2.31	0.18
0.82	3.82	2.13	17.33	1.86	4.03	2.31	0.16
0.84	3.85	2.16	16.63	1.88	4.03	2.31	0.14
0.86	3.88	2.18	15.97	1.90	4.03	2.31	0.12
0.88	3.91	2.21	15.37	1.92	4.03	2.31	0.11
0.90	3.93	2.22	14.80	1.94	4.03	2.31	0.09
0.92	3.94	2.24	14.30	1.96	4.03	2.31	0.08
0.94	3.96	2.25	13.84	1.98	4.03	2.31	0.07
0.96	3.98	2.27	13.40	2.00	4.03	2.31	0.06
0.98	4.00	2.29	13.03				
1.00	**4.03**	**2.31**	12.64				
1.02	4.03	2.31	12.29				

Summary for Pond 3P: Southeast Chambers

Inflow	=	36.70 cfs @	0.53 hrs, Volume=	1.937 af
Outflow	=	1.05 cfs @	1.60 hrs, Volume=	0.125 af, Atten= 97%, Lag= 63.6 min
Primary	=	1.05 cfs @	1.60 hrs, Volume=	0.125 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 674.10' @ 1.60 hrs Surf.Area= 31,290 sf Storage= 79,881 cf

Plug-Flow detention time= 56.5 min calculated for 0.125 af (6% of inflow)
Center-of-Mass det. time= 31.3 min (75.7 - 44.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.05 cfs @ 1.60 hrs HW=674.10' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.05 cfs @ 9.53 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.05	0.00	0	670.00	0.00	0.00	0.00	0.00
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.15	0.27	12	670.00	0.00	0.00	0.00	0.00
0.20	1.41	128	670.01	0.00	0.00	0.00	0.00
0.25	3.84	529	670.06	0.01	0.01	0.00	0.00
0.30	7.86	1,482	670.17	0.07	0.07	0.00	0.00
0.35	14.94	3,260	670.36	0.22	0.22	0.00	0.00
0.40	26.28	6,763	670.71	0.38	0.38	0.00	0.00
0.45	33.09	11,966	670.98	0.47	0.47	0.00	0.00
0.50	**36.18**	18,092	671.27	0.55	0.55	0.00	0.00
0.55	**36.64**	24,560	671.55	0.62	0.62	0.00	0.00
0.60	35.35	30,965	671.84	0.68	0.68	0.00	0.00
0.65	33.06	37,049	672.11	0.74	0.74	0.00	0.00
0.70	30.14	42,662	672.36	0.78	0.78	0.00	0.00
0.75	26.97	47,715	672.58	0.82	0.82	0.00	0.00
0.80	23.96	52,199	672.78	0.86	0.86	0.00	0.00
0.85	21.42	56,167	672.96	0.89	0.89	0.00	0.00
0.90	19.41	59,711	673.12	0.91	0.91	0.00	0.00
0.95	17.86	62,923	673.27	0.93	0.93	0.00	0.00
1.00	16.59	65,876	673.40	0.95	0.95	0.00	0.00
1.05	15.34	68,601	673.53	0.97	0.97	0.00	0.00
1.10	13.92	71,086	673.65	0.99	0.99	0.00	0.00
1.15	12.28	73,297	673.76	1.01	1.01	0.00	0.00
1.20	10.38	75,191	673.86	1.02	1.02	0.00	0.00
1.25	8.29	76,724	673.94	1.03	1.03	0.00	0.00
1.30	6.28	77,882	674.00	1.04	1.04	0.00	0.00
1.35	4.57	78,697	674.04	1.04	1.04	0.00	0.00
1.40	3.27	79,230	674.07	1.05	1.05	0.00	0.00
1.45	2.41	79,565	674.09	1.05	1.05	0.00	0.00
1.50	1.78	79,760	674.10	1.05	1.05	0.00	0.00
1.55	1.33	79,856	674.10	1.05	1.05	0.00	0.00
1.60	0.99	**79,880**	**674.10**	**1.05**	**1.05**	0.00	0.00
1.65	0.75	79,851	674.10	1.05	1.05	0.00	0.00
1.70	0.57	79,784	674.10	1.05	1.05	0.00	0.00
1.75	0.44	79,687	674.09	1.05	1.05	0.00	0.00
1.80	0.35	79,571	674.09	1.05	1.05	0.00	0.00
1.85	0.28	79,439	674.08	1.05	1.05	0.00	0.00
1.90	0.23	79,296	674.07	1.05	1.05	0.00	0.00
1.95	0.19	79,145	674.06	1.05	1.05	0.00	0.00
2.00	0.00	78,989	674.05	1.05	1.05	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	13.68 cfs @	0.44 hrs,	Volume=	0.674 af
Outflow	=	13.32 cfs @	0.49 hrs,	Volume=	0.660 af, Atten= 3%, Lag= 3.2 min
Primary	=	1.45 cfs @	0.49 hrs,	Volume=	0.167 af
Secondary	=	11.86 cfs @	0.49 hrs,	Volume=	0.493 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 678.48' @ 0.49 hrs Surf.Area= 3,656 sf Storage= 4,884 cf

Plug-Flow detention time= 10.0 min calculated for 0.660 af (98% of inflow)
Center-of-Mass det. time= 9.1 min (47.3 - 38.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.45 cfs @ 0.49 hrs HW=678.48' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 1.45 cfs @ 6.30 fps)
└2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=11.86 cfs @ 0.49 hrs HW=678.48' TW=671.23' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.68 fps)
└5=**Sharp-Crested Rectangular Weir** (Weir Controls 11.73 cfs @ 2.93 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.05	0.00	0	670.75	0.00	0.00	0.00	0.00
0.10	0.02	0	670.78	0.00	0.00	0.00	0.00
0.15	0.42	21	672.27	0.00	0.00	0.00	0.00
0.20	2.03	178	676.71	0.23	0.13	0.10	0.00
0.25	5.20	680	677.04	0.68	0.57	0.11	0.00
0.30	8.80	1,729	677.48	1.05	0.93	0.12	0.00
0.35	11.74	3,298	678.02	3.43	1.24	2.19	0.00
0.40	**13.36**	4,416	678.35	9.98	1.40	8.58	0.00
0.45	**13.68**	**4,814**	**678.46**	**12.79**	**1.44**	**11.35**	0.00
0.50	13.14	**4,884**	**678.48**	**13.31**	**1.45**	**11.86**	0.00
0.55	12.16	4,815	678.46	12.80	1.44	11.35	0.00
0.60	11.02	4,684	678.43	11.85	1.43	10.42	0.00
0.65	9.74	4,524	678.38	10.71	1.41	9.31	0.00
0.70	8.45	4,343	678.33	9.48	1.39	8.10	0.00
0.75	7.31	4,161	678.28	8.28	1.36	6.92	0.00
0.80	6.43	3,996	678.23	7.24	1.34	5.90	0.00
0.85	5.87	3,867	678.19	6.46	1.32	5.13	0.00
0.90	5.51	3,775	678.17	5.92	1.31	4.61	0.00
0.95	5.24	3,710	678.15	5.55	1.30	4.25	0.00
1.00	4.90	3,655	678.13	5.24	1.29	3.95	0.00
1.05	4.42	3,586	678.11	4.87	1.28	3.59	0.00
1.10	3.86	3,498	678.08	4.41	1.27	3.14	0.00
1.15	3.16	3,390	678.05	3.86	1.25	2.61	0.00
1.20	2.36	3,251	678.01	3.21	1.23	1.98	0.00
1.25	1.62	3,092	677.95	2.54	1.21	1.33	0.00
1.30	1.03	2,927	677.90	1.94	1.18	0.76	0.00
1.35	0.65	2,769	677.85	1.49	1.15	0.33	0.00
1.40	0.41	2,621	677.80	1.24	1.13	0.11	0.00
1.45	0.26	2,462	677.75	1.21	1.10	0.11	0.00
1.50	0.16	2,287	677.68	1.17	1.06	0.11	0.00
1.55	0.10	2,103	677.62	1.13	1.02	0.11	0.00
1.60	0.06	1,918	677.55	1.09	0.98	0.11	0.00
1.65	0.04	1,734	677.48	1.04	0.93	0.11	0.00
1.70	0.02	1,555	677.41	1.00	0.89	0.11	0.00
1.75	0.01	1,383	677.34	0.95	0.84	0.11	0.00
1.80	0.01	1,218	677.27	0.89	0.79	0.11	0.00
1.85	0.00	1,062	677.21	0.84	0.73	0.10	0.00
1.90	0.00	916	677.14	0.78	0.68	0.10	0.00
1.95	0.00	779	677.08	0.72	0.62	0.10	0.00
2.00	0.00	654	677.02	0.66	0.56	0.10	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 11.35 cfs @ 0.60 hrs, Volume= 0.918 af, Depth= 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.10	0.00	0.00
0.10	0.40	0.00	0.00
0.15	0.81	0.07	0.01
0.20	1.23	0.23	0.22
0.25	1.61	0.45	1.13
0.30	1.91	0.63	3.16
0.35	2.15	0.80	5.88
0.40	2.38	0.97	8.39
0.45	2.60	1.14	10.07
0.50	2.81	1.30	10.90
0.55	3.00	1.45	11.25
0.60	3.16	1.58	**11.35**
0.65	3.31	1.70	11.22
0.70	3.44	1.81	10.86
0.75	3.56	1.91	10.28
0.80	3.66	2.00	9.59
0.85	3.77	2.08	8.89
0.90	3.87	2.17	8.19
0.95	3.96	2.25	7.57
1.00	4.04	2.32	7.06
1.05	4.11	2.38	6.62
1.10	4.17	2.43	6.19
1.15	4.22	2.48	5.69
1.20	4.27	2.52	5.12
1.25	4.32	2.56	4.56
1.30	4.37	2.61	4.08
1.35	4.42	2.65	3.74
1.40	4.47	2.70	3.51
1.45	4.52	2.74	3.37
1.50	4.57	2.79	3.28
1.55	4.62	2.83	3.23
1.60	4.67	2.88	3.20
1.65	4.72	2.92	3.18
1.70	4.77	2.97	3.17
1.75	4.81	3.01	3.17
1.80	4.84	3.03	3.15
1.85	4.87	3.06	3.07
1.90	4.89	3.08	2.87
1.95	4.93	3.11	2.58
2.00	**4.97**	**3.15**	2.30
2.05	4.97	3.15	2.13
2.10	4.97	3.15	2.02
2.15	4.97	3.15	1.80
2.20	4.97	3.15	1.41
2.25	4.97	3.15	0.98
2.30	4.97	3.15	0.63
2.35	4.97	3.15	0.39
2.40	4.97	3.15	0.25
2.45	4.97	3.15	0.16
2.50	4.97	3.15	0.10
2.55	4.97	3.15	0.06
2.60	4.97	3.15	0.04
2.65	4.97	3.15	0.02
2.70	4.97	3.15	0.01
2.75	4.97	3.15	0.01
2.80	4.97	3.15	0.00
2.85	4.97	3.15	0.00
2.90	4.97	3.15	0.00
2.95	4.97	3.15	0.00
3.00	4.97	3.15	0.00

Summary for Subcatchment 7S: South Property


Runoff = 22.41 cfs @ 0.72 hrs, Volume= 1.967 af, Depth> 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.10	0.00	0.00
0.10	0.40	0.00	0.00
0.15	0.81	0.07	0.00
0.20	1.23	0.23	0.13
0.25	1.61	0.45	0.71
0.30	1.91	0.63	2.21
0.35	2.15	0.80	4.90
0.40	2.38	0.97	8.57
0.45	2.60	1.14	12.52
0.50	2.81	1.30	16.07
0.55	3.00	1.45	18.87
0.60	3.16	1.58	20.80
0.65	3.31	1.70	21.90
0.70	3.44	1.81	**22.35**
0.75	3.56	1.91	**22.30**
0.80	3.66	2.00	21.82
0.85	3.77	2.08	21.01
0.90	3.87	2.17	19.96
0.95	3.96	2.25	18.81
1.00	4.04	2.32	17.65
1.05	4.11	2.38	16.56
1.10	4.17	2.43	15.55
1.15	4.22	2.48	14.55
1.20	4.27	2.52	13.52
1.25	4.32	2.56	12.44
1.30	4.37	2.61	11.36
1.35	4.42	2.65	10.34
1.40	4.47	2.70	9.45
1.45	4.52	2.74	8.74
1.50	4.57	2.79	8.19
1.55	4.62	2.83	7.79
1.60	4.67	2.88	7.50
1.65	4.72	2.92	7.29
1.70	4.77	2.97	7.14
1.75	4.81	3.01	7.04
1.80	4.84	3.03	6.95
1.85	4.87	3.06	6.85
1.90	4.89	3.08	6.67
1.95	4.93	3.11	6.37
2.00	**4.97**	**3.15**	5.97
2.05	4.97	3.15	5.54
2.10	4.97	3.15	5.14
2.15	4.97	3.15	4.73
2.20	4.97	3.15	4.25
2.25	4.97	3.15	3.65
2.30	4.97	3.15	2.99
2.35	4.97	3.15	2.34
2.40	4.97	3.15	1.76
2.45	4.97	3.15	1.28
2.50	4.97	3.15	0.93
2.55	4.97	3.15	0.68
2.60	4.97	3.15	0.50
2.65	4.97	3.15	0.37
2.70	4.97	3.15	0.27
2.75	4.97	3.15	0.20
2.80	4.97	3.15	0.14
2.85	4.97	3.15	0.10
2.90	4.97	3.15	0.07
2.95	4.97	3.15	0.05
3.00	4.97	3.15	0.04

Summary for Pond 3P: Southeast Chambers

Inflow	=	32.04 cfs @	0.69 hrs, Volume=	2.613 af
Outflow	=	1.28 cfs @	2.46 hrs, Volume=	0.227 af, Atten= 96%, Lag= 106.3 min
Primary	=	1.28 cfs @	2.46 hrs, Volume=	0.227 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 675.98' @ 2.46 hrs Surf.Area= 46,816 sf Storage= 105,647 cf

Plug-Flow detention time= 85.6 min calculated for 0.226 af (9% of inflow)
Center-of-Mass det. time= 47.1 min (112.5 - 65.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.28 cfs @ 2.46 hrs HW=675.98' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.28 cfs @ 11.59 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.13	6	670.00	0.00	0.00	0.00	0.00
0.30	2.31	302	670.03	0.00	0.00	0.00	0.00
0.40	8.69	2,045	670.23	0.12	0.12	0.00	0.00
0.50	23.34	7,281	670.76	0.40	0.40	0.00	0.00
0.60	**30.51**	16,924	671.21	0.54	0.54	0.00	0.00
0.70	**32.04**	28,057	671.71	0.66	0.66	0.00	0.00
0.80	30.54	39,170	672.21	0.76	0.76	0.00	0.00
0.90	27.35	49,397	672.65	0.84	0.84	0.00	0.00
1.00	23.83	58,357	673.06	0.90	0.90	0.00	0.00
1.10	20.82	66,100	673.41	0.96	0.96	0.00	0.00
1.20	17.86	72,771	673.74	1.00	1.00	0.00	0.00
1.30	14.67	78,311	674.02	1.04	1.04	0.00	0.00
1.40	12.02	82,753	674.26	1.07	1.07	0.00	0.00
1.50	10.38	86,393	674.48	1.10	1.10	0.00	0.00
1.60	9.52	89,573	674.71	1.13	1.13	0.00	0.00
1.70	9.10	92,514	674.94	1.16	1.16	0.00	0.00
1.80	8.89	95,333	675.18	1.19	1.19	0.00	0.00
1.90	8.49	98,053	675.41	1.21	1.21	0.00	0.00
2.00	7.39	100,508	675.62	1.24	1.24	0.00	0.00
2.10	6.18	102,512	675.78	1.26	1.26	0.00	0.00
2.20	4.94	104,095	675.88	1.27	1.27	0.00	0.00
2.30	3.17	105,134	675.95	1.28	1.28	0.00	0.00
2.40	1.84	**105,679**	**675.97**	**1.28**	**1.28**	0.00	0.00
2.50	1.01	**105,630**	**675.98**	**1.28**	**1.28**	0.00	0.00
2.60	0.58	105,455	675.97	1.28	1.28	0.00	0.00
2.70	0.34	105,160	675.95	1.28	1.28	0.00	0.00
2.80	0.21	104,799	675.92	1.27	1.27	0.00	0.00
2.90	0.14	104,403	675.90	1.27	1.27	0.00	0.00
3.00	0.00	103,989	675.87	1.27	1.27	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	11.35 cfs @	0.60 hrs,	Volume=	0.918 af
Outflow	=	11.26 cfs @	0.65 hrs,	Volume=	0.905 af, Atten= 1%, Lag= 2.9 min
Primary	=	1.42 cfs @	0.65 hrs,	Volume=	0.258 af
Secondary	=	9.85 cfs @	0.65 hrs,	Volume=	0.647 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 678.40' @ 0.65 hrs Surf.Area= 3,578 sf Storage= 4,601 cf

Plug-Flow detention time= 11.8 min calculated for 0.905 af (99% of inflow)
Center-of-Mass det. time= 10.6 min (70.3 - 59.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.42 cfs @ 0.65 hrs HW=678.40' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.42 cfs @ 6.16 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=9.84 cfs @ 0.65 hrs HW=678.40' TW=671.44' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.60 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 9.71 cfs @ 2.73 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond 8P: North System




Pond 8P: North System



Pond 8P: North System

Stage-Area-Storage



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.22	11	671.55	0.00	0.00	0.00	0.00
0.30	3.16	386	676.88	0.47	0.36	0.11	0.00
0.40	8.39	2,109	677.62	1.14	1.02	0.12	0.00
0.50	10.90	4,216	678.30	8.63	1.37	7.26	0.00
0.60	**11.35**	**4,582**	**678.40**	**11.12**	**1.42**	**9.71**	0.00
0.70	10.86	**4,579**	**678.40**	**11.10**	**1.42**	**9.69**	0.00
0.80	9.59	4,438	678.36	10.12	1.40	8.72	0.00
0.90	8.19	4,236	678.30	8.77	1.37	7.39	0.00
1.00	7.06	4,043	678.25	7.53	1.35	6.18	0.00
1.10	6.19	3,891	678.20	6.60	1.33	5.27	0.00
1.20	5.12	3,727	678.15	5.64	1.30	4.34	0.00
1.30	4.08	3,535	678.09	4.59	1.28	3.32	0.00
1.40	3.51	3,383	678.05	3.82	1.25	2.56	0.00
1.50	3.28	3,301	678.02	3.43	1.24	2.19	0.00
1.60	3.20	3,264	678.01	3.26	1.23	2.02	0.00
1.70	3.17	3,250	678.01	3.19	1.23	1.96	0.00
1.80	3.15	3,246	678.00	3.17	1.23	1.94	0.00
1.90	2.87	3,219	678.00	3.05	1.23	1.82	0.00
2.00	2.30	3,122	677.96	2.63	1.21	1.42	0.00
2.10	2.02	3,021	677.93	2.24	1.20	1.04	0.00
2.20	1.41	2,916	677.90	1.87	1.18	0.69	0.00
2.30	0.63	2,707	677.83	1.32	1.14	0.18	0.00
2.40	0.25	2,423	677.73	1.17	1.09	0.08	0.00
2.50	0.10	2,077	677.61	1.09	1.02	0.08	0.00
2.60	0.04	1,722	677.48	1.00	0.93	0.07	0.00
2.70	0.01	1,385	677.34	0.91	0.84	0.07	0.00
2.80	0.00	1,077	677.21	0.81	0.74	0.07	0.00
2.90	0.00	805	677.09	0.70	0.63	0.06	0.00
3.00	0.00	574	676.98	0.58	0.51	0.06	0.00


Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**


Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.08	4.92	3.10	2.40
0.04	0.03	0.00	0.00	2.12	4.95	3.13	2.39
0.08	0.13	0.00	0.00	2.16	4.98	3.16	2.38
0.12	0.28	0.00	0.00	2.20	5.01	3.18	2.37
0.16	0.50	0.00	0.00	2.24	5.04	3.21	2.36
0.20	0.74	0.05	0.01	2.28	5.07	3.24	2.36
0.24	0.99	0.13	0.11	2.32	5.10	3.26	2.36
0.28	1.23	0.24	0.45	2.36	5.13	3.29	2.36
0.32	1.48	0.37	1.21	2.40	5.16	3.32	2.36
0.36	1.70	0.50	2.46	2.44	5.19	3.34	2.36
0.40	1.90	0.63	4.06	2.48	5.22	3.37	2.36
0.44	2.07	0.74	5.77	2.52	5.25	3.40	2.37
0.48	2.22	0.85	7.29	2.56	5.28	3.42	2.37
0.52	2.36	0.95	8.41	2.60	5.30	3.45	2.37
0.56	2.50	1.06	9.06	2.64	5.32	3.47	2.36
0.60	2.63	1.16	9.34	2.68	5.34	3.49	2.34
0.64	2.77	1.26	**9.39**	2.72	5.36	3.50	2.29
0.68	2.89	1.36	9.35	2.76	5.37	3.51	2.18
0.72	3.02	1.46	9.27	2.80	5.39	3.53	2.04
0.76	3.13	1.56	9.19	2.84	5.40	3.54	1.86
0.80	3.25	1.65	9.11	2.88	5.42	3.56	1.70
0.84	3.35	1.73	9.01	2.92	5.44	3.57	1.56
0.88	3.45	1.82	8.87	2.96	5.46	3.60	1.46
0.92	3.54	1.89	8.68	3.00	**5.49**	**3.62**	1.42
0.96	3.62	1.96	8.43	3.04	5.49	3.62	1.44
1.00	3.70	2.03	8.12	3.08	5.49	3.62	1.48
1.04	3.78	2.10	7.77	3.12	5.49	3.62	1.46
1.08	3.85	2.16	7.40	3.16	5.49	3.62	1.32
1.12	3.92	2.22	7.04	3.20	5.49	3.62	1.09
1.16	3.99	2.27	6.71	3.24	5.49	3.62	0.82
1.20	4.05	2.33	6.39	3.28	5.49	3.62	0.58
1.24	4.11	2.38	6.09	3.32	5.49	3.62	0.40
1.28	4.17	2.43	5.79	3.36	5.49	3.62	0.28
1.32	4.23	2.48	5.52	3.40	5.49	3.62	0.19
1.36	4.28	2.54	5.28	3.44	5.49	3.62	0.13
1.40	4.34	2.58	5.07	3.48	5.49	3.62	0.09
1.44	4.39	2.63	4.92	3.52	5.49	3.62	0.06
1.48	4.44	2.67	4.79	3.56	5.49	3.62	0.04
1.52	4.49	2.71	4.66	3.60	5.49	3.62	0.03
1.56	4.53	2.75	4.51	3.64	5.49	3.62	0.02
1.60	4.56	2.78	4.33	3.68	5.49	3.62	0.01
1.64	4.60	2.81	4.12	3.72	5.49	3.62	0.01
1.68	4.62	2.84	3.88	3.76	5.49	3.62	0.01
1.72	4.65	2.86	3.62	3.80	5.49	3.62	0.00
1.76	4.68	2.89	3.36	3.84	5.49	3.62	0.00
1.80	4.71	2.92	3.11	3.88	5.49	3.62	0.00
1.84	4.74	2.94	2.90	3.92	5.49	3.62	0.00
1.88	4.77	2.97	2.73	3.96	5.49	3.62	0.00
1.92	4.80	3.00	2.61	4.00	5.49	3.62	0.00
1.96	4.83	3.02	2.53				
2.00	4.86	3.05	2.47				
2.04	4.89	3.08	2.43				


Subcatchment 7S: South Property




Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.08	4.92	3.10	5.67
0.04	0.03	0.00	0.00	2.12	4.95	3.13	5.52
0.08	0.13	0.00	0.00	2.16	4.98	3.16	5.42
0.12	0.28	0.00	0.00	2.20	5.01	3.18	5.33
0.16	0.50	0.00	0.00	2.24	5.04	3.21	5.26
0.20	0.74	0.05	0.01	2.28	5.07	3.24	5.21
0.24	0.99	0.13	0.06	2.32	5.10	3.26	5.18
0.28	1.23	0.24	0.28	2.36	5.13	3.29	5.15
0.32	1.48	0.37	0.79	2.40	5.16	3.32	5.12
0.36	1.70	0.50	1.80	2.44	5.19	3.34	5.11
0.40	1.90	0.63	3.37	2.48	5.22	3.37	5.10
0.44	2.07	0.74	5.49	2.52	5.25	3.40	5.09
0.48	2.22	0.85	7.97	2.56	5.28	3.42	5.09
0.52	2.36	0.95	10.54	2.60	5.30	3.45	5.08
0.56	2.50	1.06	12.95	2.64	5.32	3.47	5.08
0.60	2.63	1.16	14.97	2.68	5.34	3.49	5.07
0.64	2.77	1.26	16.49	2.72	5.36	3.50	5.03
0.68	2.89	1.36	17.55	2.76	5.37	3.51	4.95
0.72	3.02	1.46	18.24	2.80	5.39	3.53	4.82
0.76	3.13	1.56	18.61	2.84	5.40	3.54	4.63
0.80	3.25	1.65	18.80	2.88	5.42	3.56	4.38
0.84	3.35	1.73	**18.88**	2.92	5.44	3.57	4.12
0.88	3.45	1.82	**18.89**	2.96	5.46	3.60	3.86
0.92	3.54	1.89	18.79	3.00	**5.49**	**3.62**	3.64
0.96	3.62	1.96	18.59	3.04	5.49	3.62	3.47
1.00	3.70	2.03	18.29	3.08	5.49	3.62	3.36
1.04	3.78	2.10	17.90	3.12	5.49	3.62	3.28
1.08	3.85	2.16	17.39	3.16	5.49	3.62	3.18
1.12	3.92	2.22	16.80	3.20	5.49	3.62	3.00
1.16	3.99	2.27	16.18	3.24	5.49	3.62	2.72
1.20	4.05	2.33	15.55	3.28	5.49	3.62	2.38
1.24	4.11	2.38	14.90	3.32	5.49	3.62	2.01
1.28	4.17	2.43	14.25	3.36	5.49	3.62	1.64
1.32	4.23	2.48	13.63	3.40	5.49	3.62	1.30
1.36	4.28	2.54	13.04	3.44	5.49	3.62	1.01
1.40	4.34	2.58	12.49	3.48	5.49	3.62	0.78
1.44	4.39	2.63	11.98	3.52	5.49	3.62	0.61
1.48	4.44	2.67	11.53	3.56	5.49	3.62	0.48
1.52	4.49	2.71	11.14	3.60	5.49	3.62	0.37
1.56	4.53	2.75	10.76	3.64	5.49	3.62	0.29
1.60	4.56	2.78	10.39	3.68	5.49	3.62	0.23
1.64	4.60	2.81	10.00	3.72	5.49	3.62	0.17
1.68	4.62	2.84	9.60	3.76	5.49	3.62	0.14
1.72	4.65	2.86	9.15	3.80	5.49	3.62	0.10
1.76	4.68	2.89	8.66	3.84	5.49	3.62	0.08
1.80	4.71	2.92	8.16	3.88	5.49	3.62	0.06
1.84	4.74	2.94	7.66	3.92	5.49	3.62	0.05
1.88	4.77	2.97	7.19	3.96	5.49	3.62	0.04
1.92	4.80	3.00	6.76	4.00	5.49	3.62	0.03
1.96	4.83	3.02	6.40				
2.00	4.86	3.05	6.10				
2.04	4.89	3.08	5.86				


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.01	0	670.00	0.00	0.00	0.00	0.00
0.30	0.56	37	670.00	0.00	0.00	0.00	0.00
0.40	3.48	562	670.06	0.01	0.01	0.00	0.00
0.50	9.39	2,594	670.29	0.17	0.17	0.00	0.00
0.60	21.64	7,653	670.77	0.41	0.41	0.00	0.00
0.70	25.86	16,068	671.17	0.53	0.53	0.00	0.00
0.80	**26.61**	25,327	671.59	0.63	0.63	0.00	0.00
0.90	**26.40**	34,659	672.01	0.72	0.72	0.00	0.00
1.00	25.35	43,775	672.41	0.79	0.79	0.00	0.00
1.10	23.36	52,344	672.79	0.86	0.86	0.00	0.00
1.20	20.98	60,095	673.14	0.91	0.91	0.00	0.00
1.30	18.63	66,966	673.46	0.96	0.96	0.00	0.00
1.40	16.53	73,004	673.75	1.00	1.00	0.00	0.00
1.50	14.94	78,343	674.02	1.04	1.04	0.00	0.00
1.60	13.67	83,159	674.28	1.08	1.08	0.00	0.00
1.70	12.18	87,484	674.55	1.11	1.11	0.00	0.00
1.80	10.38	91,211	674.84	1.15	1.15	0.00	0.00
1.90	8.68	94,276	675.09	1.18	1.18	0.00	0.00
2.00	7.50	96,785	675.30	1.20	1.20	0.00	0.00
2.10	6.85	98,942	675.48	1.22	1.22	0.00	0.00
2.20	6.52	100,909	675.65	1.24	1.24	0.00	0.00
2.30	6.36	102,779	675.79	1.26	1.26	0.00	0.00
2.40	6.28	104,601	675.91	1.27	1.27	0.00	0.00
2.50	6.25	106,398	676.03	1.29	1.29	0.00	0.00
2.60	6.24	108,183	676.14	1.30	1.30	0.00	0.00
2.70	6.20	109,961	676.26	1.31	1.31	0.00	0.00
2.80	5.85	111,685	676.38	1.32	1.32	0.00	0.00
2.90	4.99	113,199	676.48	1.33	1.33	0.00	0.00
3.00	4.09	114,374	676.56	1.34	1.34	0.00	0.00
3.10	3.67	115,287	676.62	1.35	1.35	0.00	0.00
3.20	3.26	116,080	676.67	1.35	1.35	0.00	0.00
3.30	2.26	116,624	676.71	1.36	1.36	0.00	0.00
3.40	1.36	**116,814**	**676.72**	**1.36**	**1.36**	0.00	0.00
3.50	0.74	116,714	676.72	1.36	1.36	0.00	0.00
3.60	0.42	116,441	676.70	1.36	1.36	0.00	0.00
3.70	0.25	116,077	676.67	1.35	1.35	0.00	0.00
3.80	0.15	115,662	676.65	1.35	1.35	0.00	0.00
3.90	0.09	115,221	676.62	1.35	1.35	0.00	0.00
4.00	0.00	114,764	676.58	1.35	1.35	0.00	0.00


Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**


Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.01	0	670.76	0.00	0.00	0.00	0.00
0.30	0.77	61	675.11	0.07	0.00	0.07	0.00
0.40	4.06	643	677.02	0.67	0.56	0.11	0.00
0.50	7.90	2,383	677.72	1.20	1.08	0.12	0.00
0.60	**9.34**	4,123	678.27	8.04	1.36	6.68	0.00
0.70	**9.31**	**4,318**	**678.32**	**9.31**	**1.38**	**7.93**	0.00
0.80	9.11	**4,301**	**678.32**	**9.20**	**1.38**	**7.82**	0.00
0.90	8.78	4,262	678.31	8.94	1.38	7.56	0.00
1.00	8.12	4,184	678.29	8.42	1.37	7.06	0.00
1.10	7.22	4,056	678.25	7.61	1.35	6.26	0.00
1.20	6.39	3,918	678.21	6.76	1.33	5.43	0.00
1.30	5.65	3,788	678.17	6.00	1.31	4.69	0.00
1.40	5.07	3,673	678.14	5.34	1.30	4.04	0.00
1.50	4.73	3,593	678.11	4.90	1.28	3.62	0.00
1.60	4.33	3,528	678.09	4.55	1.27	3.28	0.00
1.70	3.75	3,434	678.06	4.07	1.26	2.81	0.00
1.80	3.11	3,311	678.02	3.47	1.24	2.23	0.00
1.90	2.67	3,192	677.99	2.93	1.22	1.71	0.00
2.00	2.47	3,116	677.96	2.61	1.21	1.40	0.00
2.10	2.39	3,078	677.95	2.46	1.20	1.25	0.00
2.20	2.37	3,062	677.95	2.39	1.20	1.19	0.00
2.30	2.36	3,056	677.94	2.37	1.20	1.16	0.00
2.40	2.36	3,055	677.94	2.36	1.20	1.16	0.00
2.50	2.36	3,056	677.94	2.36	1.20	1.16	0.00
2.60	2.37	3,058	677.94	2.36	1.20	1.16	0.00
2.70	2.32	3,056	677.94	2.36	1.20	1.16	0.00
2.80	2.04	3,023	677.93	2.23	1.20	1.03	0.00
2.90	1.62	2,934	677.90	1.91	1.18	0.73	0.00
3.00	1.42	2,837	677.87	1.61	1.16	0.45	0.00
3.10	1.49	2,799	677.86	1.51	1.16	0.35	0.00
3.20	1.09	2,759	677.85	1.41	1.15	0.26	0.00
3.30	0.48	2,588	677.79	1.18	1.12	0.06	0.00
3.40	0.19	2,295	677.69	1.12	1.06	0.06	0.00
3.50	0.08	1,952	677.56	1.04	0.99	0.05	0.00
3.60	0.03	1,609	677.43	0.95	0.90	0.05	0.00
3.70	0.01	1,288	677.30	0.86	0.81	0.05	0.00
3.80	0.00	997	677.18	0.75	0.71	0.04	0.00
3.90	0.00	743	677.06	0.64	0.60	0.04	0.00
4.00	0.00	528	676.96	0.52	0.48	0.04	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 7.00 cfs @ 0.91 hrs, Volume= 1.310 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.13	0.00	0.00
0.30	0.52	0.01	0.00
0.45	1.05	0.15	0.51
0.60	1.59	0.43	3.07
0.75	2.09	0.75	5.85
0.90	2.47	1.03	**6.99**
1.05	2.78	1.28	6.52
1.20	3.09	1.52	5.95
1.35	3.37	1.75	5.71
1.50	3.64	1.97	5.53
1.65	3.88	2.18	5.32
1.80	4.09	2.37	4.93
1.95	4.28	2.53	4.41
2.10	4.45	2.68	3.96
2.25	4.60	2.82	3.61
2.40	4.74	2.94	3.29
2.55	4.87	3.06	2.98
2.70	5.00	3.18	2.81
2.85	5.12	3.29	2.76
3.00	5.23	3.38	2.59
3.15	5.32	3.46	2.30
3.30	5.39	3.53	1.97
3.45	5.46	3.59	1.65
3.60	5.52	3.65	1.47
3.75	5.59	3.71	1.42
3.90	5.65	3.77	1.41
4.05	5.72	3.83	1.41
4.20	5.78	3.89	1.41
4.35	5.85	3.95	1.41
4.50	5.91	4.01	1.41
4.65	5.98	4.07	1.41
4.80	6.04	4.13	1.42
4.95	6.11	4.19	1.42
5.10	6.17	4.25	1.42
5.25	6.23	4.30	1.41
5.40	6.27	4.34	1.24
5.55	6.30	4.37	0.95
5.70	6.33	4.40	0.78
5.85	6.37	4.44	0.75
6.00	**6.43**	**4.49**	0.90
6.15	6.43	4.49	0.93
6.30	6.43	4.49	0.32
6.45	6.43	4.49	0.08
6.60	6.43	4.49	0.02
6.75	6.43	4.49	0.00
6.90	6.43	4.49	0.00
7.05	6.43	4.49	0.00
7.20	6.43	4.49	0.00
7.35	6.43	4.49	0.00
7.50	6.43	4.49	0.00
7.65	6.43	4.49	0.00
7.80	6.43	4.49	0.00
7.95	6.43	4.49	0.00

Summary for Subcatchment 7S: South Property


Runoff = 13.92 cfs @ 1.04 hrs, Volume= 2.808 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.13	0.00	0.00
0.30	0.52	0.01	0.00
0.45	1.05	0.15	0.34
0.60	1.59	0.43	3.16
0.75	2.09	0.75	8.41
0.90	2.47	1.03	12.68
1.05	2.78	1.28	**13.91**
1.20	3.09	1.52	13.27
1.35	3.37	1.75	12.61
1.50	3.64	1.97	12.18
1.65	3.88	2.18	11.76
1.80	4.09	2.37	11.16
1.95	4.28	2.53	10.24
2.10	4.45	2.68	9.23
2.25	4.60	2.82	8.36
2.40	4.74	2.94	7.61
2.55	4.87	3.06	6.91
2.70	5.00	3.18	6.36
2.85	5.12	3.29	6.07
3.00	5.23	3.38	5.83
3.15	5.32	3.46	5.36
3.30	5.39	3.53	4.74
3.45	5.46	3.59	4.06
3.60	5.52	3.65	3.49
3.75	5.59	3.71	3.20
3.90	5.65	3.77	3.08
4.05	5.72	3.83	3.04
4.20	5.78	3.89	3.02
4.35	5.85	3.95	3.02
4.50	5.91	4.01	3.02
4.65	5.98	4.07	3.03
4.80	6.04	4.13	3.03
4.95	6.11	4.19	3.04
5.10	6.17	4.25	3.04
5.25	6.23	4.30	3.03
5.40	6.27	4.34	2.88
5.55	6.30	4.37	2.45
5.70	6.33	4.40	1.97
5.85	6.37	4.44	1.71
6.00	**6.43**	**4.49**	1.76
6.15	6.43	4.49	2.00
6.30	6.43	4.49	1.41
6.45	6.43	4.49	0.60
6.60	6.43	4.49	0.24
6.75	6.43	4.49	0.09
6.90	6.43	4.49	0.04
7.05	6.43	4.49	0.01
7.20	6.43	4.49	0.00
7.35	6.43	4.49	0.00
7.50	6.43	4.49	0.00
7.65	6.43	4.49	0.00
7.80	6.43	4.49	0.00
7.95	6.43	4.49	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	19.42 cfs @	1.01 hrs,	Volume=	3.512 af
Outflow	=	1.47 cfs @	6.69 hrs,	Volume=	0.756 af, Atten= 92%, Lag= 340.8 min
Primary	=	1.44 cfs @	6.31 hrs,	Volume=	0.751 af
Secondary	=	0.04 cfs @	7.27 hrs,	Volume=	0.005 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Peak Elev= 677.56' @ 6.31 hrs Surf.Area= 46,993 sf Storage= 128,202 cf

Plug-Flow detention time= 227.6 min calculated for 0.753 af (21% of inflow)
Center-of-Mass det. time= 141.8 min (285.7 - 143.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.44 cfs @ 6.31 hrs HW=677.56' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.44 cfs @ 13.08 fps)


Secondary OutFlow Max=0.04 cfs @ 7.27 hrs HW=677.24' TW=676.71' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Orifice Controls 0.04 cfs @ 3.50 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.30	0.00	0	670.00	0.00	0.00	0.00	0.00
0.60	3.27	718	670.08	0.02	0.02	0.00	0.00
0.90	**18.05**	10,330	670.90	0.45	0.45	0.00	0.00
1.20	**18.04**	30,128	671.80	0.68	0.68	0.00	0.00
1.50	16.47	47,914	672.59	0.82	0.82	0.00	0.00
1.80	14.95	64,122	673.32	0.94	0.94	0.00	0.00
2.10	12.07	77,840	673.99	1.04	1.04	0.00	0.00
2.40	9.79	88,550	674.63	1.12	1.12	0.00	0.00
2.70	8.00	96,920	675.31	1.20	1.20	0.00	0.00
3.00	7.29	103,875	675.86	1.27	1.27	0.00	0.00
3.30	5.69	109,659	676.24	1.31	1.31	0.00	0.00
3.60	3.91	113,441	676.49	1.34	1.34	0.00	0.00
3.90	3.35	115,849	676.66	1.35	1.35	0.00	0.00
4.20	3.28	117,951	676.80	1.37	1.37	0.00	0.00
4.50	3.28	120,007	676.95	1.38	1.38	0.00	0.00
4.80	3.29	122,056	677.09	1.40	1.40	0.00	0.00
5.10	3.30	124,100	677.24	1.41	1.41	0.00	0.00
5.40	3.09	126,103	677.40	1.43	1.43	0.00	0.00
5.70	2.00	127,341	677.49	1.44	1.44	0.00	0.00
6.00	1.78	127,731	677.52	1.44	1.44	0.00	0.00
6.30	1.41	**128,200**	**677.56**	1.44	**1.44**	0.00	0.00
6.60	0.24	127,425	677.50	**1.47**	1.44	0.03	0.00
6.90	0.04	125,967	677.39	**1.47**	1.43	0.04	0.00
7.20	0.00	124,407	677.27	1.46	1.41	**0.04**	0.00
7.50	0.00	122,839	677.15	1.44	1.40	**0.04**	0.00
7.80	0.00	121,286	677.04	1.43	1.39	0.04	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	7.00 cfs @	0.91 hrs, Volume=	1.315 af
Outflow	=	6.95 cfs @	0.97 hrs, Volume=	1.313 af, Atten= 1%, Lag= 3.3 min
Primary	=	1.33 cfs @	0.97 hrs, Volume=	0.608 af
Secondary	=	5.62 cfs @	0.97 hrs, Volume=	0.704 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Peak Elev= 678.22' @ 0.97 hrs Surf.Area= 3,391 sf Storage= 3,949 cf

Plug-Flow detention time= 18.8 min calculated for 1.313 af (100% of inflow)
Center-of-Mass det. time= 18.2 min (163.2 - 145.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.33 cfs @ 0.97 hrs HW=678.22' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 1.33 cfs @ 5.79 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=5.61 cfs @ 0.97 hrs HW=678.22' TW=671.11' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.39 fps)
└—5=**Sharp-Crested Rectangular Weir** (Weir Controls 5.48 cfs @ 2.22 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.30	0.00	0	670.75	0.00	0.00	0.00	0.00
0.60	3.07	665	677.03	0.68	0.57	0.11	0.00
0.90	**6.99**	**3,907**	**678.21**	**6.70**	**1.33**	**5.37**	0.00
1.20	5.95	**3,803**	**678.17**	**6.09**	**1.31**	**4.77**	0.00
1.50	5.53	3,717	678.15	5.59	1.30	4.29	0.00
1.80	4.93	3,626	678.12	5.08	1.29	3.79	0.00
2.10	3.96	3,440	678.06	4.11	1.26	2.85	0.00
2.40	3.29	3,298	678.02	3.41	1.24	2.17	0.00
2.70	2.81	3,177	677.98	2.87	1.22	1.64	0.00
3.00	2.59	3,135	677.97	2.68	1.21	1.46	0.00
3.30	1.97	2,997	677.92	2.14	1.19	0.95	0.00
3.60	1.47	2,823	677.87	1.58	1.16	0.41	0.00
3.90	1.41	2,763	677.85	1.42	1.15	0.27	0.00
4.20	1.41	2,759	677.85	1.41	1.15	0.26	0.00
4.50	1.41	2,762	677.85	1.41	1.15	0.26	0.00
4.80	1.42	2,765	677.85	1.41	1.15	0.26	0.00
5.10	1.42	2,769	677.85	1.42	1.15	0.26	0.00
5.40	1.24	2,745	677.84	1.36	1.15	0.21	0.00
5.70	0.78	2,498	677.76	1.13	1.10	0.03	0.00
6.00	0.90	2,151	677.64	1.05	1.03	0.02	0.00
6.30	0.32	1,924	677.55	0.98	0.98	0.00	0.00
6.60	0.05	1,120	677.23	0.75	0.75	0.00	0.00
6.90	0.04	488	676.94	0.45	0.45	0.00	0.00
7.20	0.04	204	676.74	0.16	0.16	0.00	0.00
7.50	0.04	132	676.65	0.07	0.07	0.00	0.00
7.80	0.04	115	676.62	0.05	0.05	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 4.39 cfs @ 5.20 hrs, Volume= 1.593 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.05	0.00	0.00
0.60	0.11	0.00	0.00
0.80	0.20	0.00	0.00
1.00	0.30	0.00	0.00
1.20	0.41	0.00	0.00
1.40	0.54	0.01	0.03
1.60	0.65	0.03	0.18
1.80	0.75	0.05	0.34
2.00	0.85	0.08	0.45
2.20	0.95	0.11	0.55
2.40	1.05	0.15	0.64
2.60	1.16	0.20	0.74
2.80	1.29	0.26	0.92
3.00	1.43	0.34	1.15
3.20	1.59	0.43	1.40
3.40	1.75	0.53	1.62
3.60	1.92	0.64	1.82
3.80	2.11	0.77	2.04
4.00	2.32	0.92	2.39
4.20	2.56	1.10	2.81
4.40	2.82	1.30	3.25
4.60	3.10	1.53	3.63
4.80	3.39	1.77	3.99
5.00	3.69	2.02	4.30
5.20	3.98	2.27	**4.39**
5.40	4.26	2.51	4.36
5.60	4.52	2.74	4.28
5.80	4.76	2.96	4.01
6.00	4.97	3.15	3.67
6.20	5.17	3.32	3.31
6.40	5.34	3.48	3.03
6.60	5.50	3.63	2.77
6.80	5.65	3.77	2.52
7.00	5.79	3.89	2.35
7.20	5.92	4.01	2.22
7.40	6.04	4.13	2.09
7.60	6.15	4.23	1.95
7.80	6.25	4.33	1.82
8.00	6.35	4.42	1.69
8.20	6.44	4.50	1.55
8.40	6.52	4.57	1.42
8.60	6.59	4.65	1.30
8.80	6.67	4.72	1.25
9.00	6.74	4.79	1.25
9.20	6.82	4.85	1.23
9.40	6.88	4.91	1.14
9.60	6.93	4.96	1.01
9.80	6.98	5.01	0.89
10.00	7.03	5.06	0.84
10.20	7.08	5.11	0.84
10.40	7.13	5.15	0.84
10.60	7.18	5.20	0.84
10.80	7.23	5.25	0.84
11.00	7.28	5.29	0.82
11.20	7.32	5.33	0.73
11.40	7.35	5.36	0.60
11.60	7.38	5.38	0.49
11.80	7.41	5.42	0.54
12.00	**7.46**	**5.46**	0.67
12.20	7.46	5.46	0.47
12.40	7.46	5.46	0.08
12.60	7.46	5.46	0.01
12.80	7.46	5.46	0.00
13.00	7.46	5.46	0.00
13.20	7.46	5.46	0.00
13.40	7.46	5.46	0.00
13.60	7.46	5.46	0.00
13.80	7.46	5.46	0.00
14.00	7.46	5.46	0.00
14.20	7.46	5.46	0.00
14.40	7.46	5.46	0.00
14.60	7.46	5.46	0.00
14.80	7.46	5.46	0.00
15.00	7.46	5.46	0.00

Summary for Subcatchment 7S: South Property


Runoff = 9.36 cfs @ 5.39 hrs, Volume= 3.415 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.05	0.00	0.00
0.60	0.11	0.00	0.00
0.80	0.20	0.00	0.00
1.00	0.30	0.00	0.00
1.20	0.41	0.00	0.00
1.40	0.54	0.01	0.02
1.60	0.65	0.03	0.22
1.80	0.75	0.05	0.55
2.00	0.85	0.08	0.82
2.20	0.95	0.11	1.05
2.40	1.05	0.15	1.26
2.60	1.16	0.20	1.46
2.80	1.29	0.26	1.75
3.00	1.43	0.34	2.18
3.20	1.59	0.43	2.69
3.40	1.75	0.53	3.19
3.60	1.92	0.64	3.64
3.80	2.11	0.77	4.10
4.00	2.32	0.92	4.71
4.20	2.56	1.10	5.52
4.40	2.82	1.30	6.43
4.60	3.10	1.53	7.30
4.80	3.39	1.77	8.10
5.00	3.69	2.02	8.83
5.20	3.98	2.27	**9.27**
5.40	4.26	2.51	**9.35**
5.60	4.52	2.74	9.27
5.80	4.76	2.96	8.90
6.00	4.97	3.15	8.27
6.20	5.17	3.32	7.54
6.40	5.34	3.48	6.86
6.60	5.50	3.63	6.27
6.80	5.65	3.77	5.71
7.00	5.79	3.89	5.27
7.20	5.92	4.01	4.94
7.40	6.04	4.13	4.64
7.60	6.15	4.23	4.35
7.80	6.25	4.33	4.07
8.00	6.35	4.42	3.79
8.20	6.44	4.50	3.50
8.40	6.52	4.57	3.21
8.60	6.59	4.65	2.93
8.80	6.67	4.72	2.75
9.00	6.74	4.79	2.70
9.20	6.82	4.85	2.67
9.40	6.88	4.91	2.55
9.60	6.93	4.96	2.32
9.80	6.98	5.01	2.05
10.00	7.03	5.06	1.87
10.20	7.08	5.11	1.81
10.40	7.13	5.15	1.80
10.60	7.18	5.20	1.80
10.80	7.23	5.25	1.80
11.00	7.28	5.29	1.79
11.20	7.32	5.33	1.67
11.40	7.35	5.36	1.43
11.60	7.38	5.38	1.17
11.80	7.41	5.42	1.11
12.00	**7.46**	**5.46**	1.29
12.20	7.46	5.46	1.31
12.40	7.46	5.46	0.54
12.60	7.46	5.46	0.16
12.80	7.46	5.46	0.04
13.00	7.46	5.46	0.01
13.20	7.46	5.46	0.00
13.40	7.46	5.46	0.00
13.60	7.46	5.46	0.00
13.80	7.46	5.46	0.00
14.00	7.46	5.46	0.00
14.20	7.46	5.46	0.00
14.40	7.46	5.46	0.00
14.60	7.46	5.46	0.00
14.80	7.46	5.46	0.00
15.00	7.46	5.46	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	12.47 cfs @	5.34 hrs,	Volume=	4.184 af
Outflow	=	3.67 cfs @	9.68 hrs,	Volume=	1.478 af, Atten= 71%, Lag= 260.6 min
Primary	=	1.51 cfs @	9.88 hrs,	Volume=	1.251 af
Secondary	=	2.16 cfs @	9.68 hrs,	Volume=	0.227 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Peak Elev= 678.23' @ 9.88 hrs Surf.Area= 47,068 sf Storage= 134,811 cf

Plug-Flow detention time= 330.8 min calculated for 1.477 af (35% of inflow)
Center-of-Mass det. time= 206.4 min (587.1 - 380.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.51 cfs @ 9.88 hrs HW=678.23' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.51 cfs @ 13.66 fps)


Secondary OutFlow Max=1.65 cfs @ 9.68 hrs HW=678.22' TW=678.21' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Weir Controls 1.64 cfs @ 0.66 fps)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.52 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.50	0.00	0	670.00	0.00	0.00	0.00	0.00
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
1.50	0.09	20	670.00	0.00	0.00	0.00	0.00
2.00	0.93	980	670.11	0.03	0.03	0.00	0.00
2.50	1.46	2,951	670.33	0.20	0.20	0.00	0.00
3.00	2.29	5,702	670.61	0.34	0.34	0.00	0.00
3.50	3.54	10,224	670.90	0.45	0.45	0.00	0.00
4.00	5.65	17,013	671.22	0.54	0.54	0.00	0.00
4.50	8.96	29,027	671.75	0.67	0.67	0.00	0.00
5.00	**11.80**	46,422	672.52	0.81	0.81	0.00	0.00
5.50	**12.42**	67,001	673.46	0.96	0.96	0.00	0.00
6.00	10.79	86,437	674.48	1.10	1.10	0.00	0.00
6.50	8.31	101,446	675.70	1.25	1.25	0.00	0.00
7.00	6.47	112,339	676.42	1.33	1.33	0.00	0.00
7.50	5.38	120,543	676.99	1.39	1.39	0.00	0.00
8.00	4.36	126,786	677.45	1.43	1.43	0.00	0.00
8.50	3.30	131,104	677.83	1.47	1.47	0.00	0.00
9.00	3.17	133,067	678.04	2.20	1.49	0.71	0.00
9.50	3.73	**134,431**	**678.19**	**1.50**	**1.50**	**0.00**	0.00
10.00	1.87	**134,782**	**678.23**	**3.38**	**1.51**	**1.87**	0.00
10.50	3.37	134,453	678.19	1.50	1.50	0.00	0.00
11.00	1.79	134,292	678.18	3.02	1.50	1.51	0.00
11.50	1.29	133,600	678.10	1.50	1.50	0.00	0.00
12.00	1.29	132,238	677.95	1.83	1.48	0.35	0.00
12.50	0.29	130,858	677.80	1.49	1.47	0.02	0.00
13.00	0.01	128,342	677.57	1.49	1.45	0.04	0.00
13.50	0.00	125,682	677.36	1.47	1.42	0.05	0.00
14.00	0.00	123,053	677.17	1.45	1.40	0.04	0.00
14.50	0.00	120,470	676.98	1.42	1.39	0.04	0.00
15.00	0.00	117,935	676.80	1.39	1.37	0.03	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	4.39 cfs @	5.20 hrs,	Volume=	1.820 af
Outflow	=	4.39 cfs @	5.28 hrs,	Volume=	1.818 af, Atten= 0%, Lag= 4.9 min
Primary	=	1.35 cfs @	9.86 hrs,	Volume=	1.048 af
Secondary	=	3.12 cfs @	5.28 hrs,	Volume=	0.770 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Peak Elev= 678.24' @ 9.86 hrs Surf.Area= 3,417 sf Storage= 4,035 cf

Plug-Flow detention time= 24.2 min calculated for 1.818 af (100% of inflow)
Center-of-Mass det. time= 23.6 min (431.0 - 407.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.35 cfs @ 9.86 hrs HW=678.24' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.35 cfs @ 5.84 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=3.12 cfs @ 5.28 hrs HW=678.08' TW=673.04' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.23 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 2.99 cfs @ 1.79 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.50	0.00	0	670.75	0.00	0.00	0.00	0.00
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
1.50	0.10	25	672.53	0.00	0.00	0.00	0.00
2.00	0.45	249	676.78	0.32	0.22	0.11	0.00
2.50	0.69	480	676.94	0.55	0.45	0.11	0.00
3.00	1.15	881	677.13	0.77	0.66	0.11	0.00
3.50	1.72	1,820	677.51	1.07	0.96	0.12	0.00
4.00	2.39	2,983	677.92	2.13	1.19	0.94	0.00
4.50	3.45	3,275	678.01	3.32	1.24	2.09	0.00
5.00	**4.30**	3,464	678.07	**4.23**	1.27	**2.97**	0.00
5.50	**4.33**	3,487	678.08	**4.35**	1.27	**3.08**	0.00
6.00	3.67	3,373	678.04	3.77	1.25	2.52	0.00
6.50	2.90	3,205	677.99	2.98	1.23	1.75	0.00
7.00	2.35	3,071	677.95	2.41	1.20	1.20	0.00
7.50	2.02	2,983	677.92	2.07	1.19	0.88	0.00
8.00	1.69	2,891	677.89	1.74	1.17	0.57	0.00
8.50	1.35	2,784	677.85	1.39	1.15	0.24	0.00
9.00	1.96	3,364	678.04	1.72	1.25	0.47	0.00
9.50	1.08	**3,873**	**678.20**	2.61	**1.32**	1.29	0.00
10.00	2.71	**3,924**	**678.21**	1.33	**1.33**	0.00	0.00
10.50	0.84	3,926	678.21	2.90	1.33	1.57	0.00
11.00	2.34	3,748	678.16	1.31	1.31	0.00	0.00
11.50	0.53	3,523	678.09	1.27	1.27	0.00	0.00
12.00	1.01	3,051	677.94	1.20	1.20	0.00	0.00
12.50	0.06	2,185	677.65	1.04	1.04	0.00	0.00
13.00	0.04	753	677.07	0.61	0.61	0.00	0.00
13.50	0.05	192	676.73	0.15	0.15	0.00	0.00
14.00	0.04	121	676.63	0.05	0.05	0.00	0.00
14.50	0.04	110	676.61	0.04	0.04	0.00	0.00
15.00	0.00	103	676.60	0.03	0.03	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 3.74 cfs @ 11.86 hrs, Volume= 1.936 af, Depth> 6.64"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.01 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06" x 8

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.50	0.04	0.00	0.00
1.00	0.15	0.00	0.00
1.50	0.29	0.00	0.00
2.00	0.42	0.00	0.00
2.50	0.56	0.01	0.07
3.00	0.70	0.04	0.18
3.50	0.83	0.07	0.26
4.00	0.97	0.12	0.34
4.50	1.10	0.18	0.40
5.00	1.25	0.25	0.50
5.50	1.43	0.34	0.65
6.00	1.61	0.44	0.74
6.50	1.79	0.56	0.80
7.00	1.97	0.68	0.85
7.50	2.16	0.81	0.91
8.00	2.37	0.96	1.07
8.50	2.60	1.13	1.25
9.00	2.86	1.34	1.43
9.50	3.15	1.57	1.62
10.00	3.46	1.83	1.82
10.50	3.87	2.17	2.44
11.00	4.39	2.63	3.26
11.50	4.96	3.14	**3.59**
12.00	5.53	3.66	**3.69**
12.50	6.01	4.10	3.13
13.00	6.40	4.46	2.55
13.50	6.71	4.75	2.06
14.00	6.96	4.99	1.65
14.50	7.15	5.17	1.32
15.00	7.32	5.33	1.10
15.50	7.46	5.46	0.94
16.00	7.60	5.59	0.91
16.50	7.73	5.72	0.89
17.00	7.84	5.82	0.73
17.50	7.94	5.92	0.67
18.00	8.06	6.03	0.83
18.50	8.10	6.07	0.30
19.00	8.21	6.18	0.76
19.50	8.35	6.31	0.92
20.00	8.48	6.44	0.92
20.50	8.62	6.57	0.92
21.00	**8.76**	**6.70**	0.92

Summary for Subcatchment 7S: South Property


Runoff = 7.96 cfs @ 11.98 hrs, Volume= 4.129 af, Depth> 6.61"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.01 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06" x 8

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.50	0.04	0.00	0.00
1.00	0.15	0.00	0.00
1.50	0.29	0.00	0.00
2.00	0.42	0.00	0.00
2.50	0.56	0.01	0.10
3.00	0.70	0.04	0.33
3.50	0.83	0.07	0.52
4.00	0.97	0.12	0.68
4.50	1.10	0.18	0.82
5.00	1.25	0.25	1.00
5.50	1.43	0.34	1.31
6.00	1.61	0.44	1.55
6.50	1.79	0.56	1.69
7.00	1.97	0.68	1.79
7.50	2.16	0.81	1.91
8.00	2.37	0.96	2.21
8.50	2.60	1.13	2.58
9.00	2.86	1.34	2.98
9.50	3.15	1.57	3.38
10.00	3.46	1.83	3.79
10.50	3.87	2.17	4.85
11.00	4.39	2.63	6.58
11.50	4.96	3.14	**7.55**
12.00	5.53	3.66	**7.95**
12.50	6.01	4.10	7.01
13.00	6.40	4.46	5.73
13.50	6.71	4.75	4.66
14.00	6.96	4.99	3.72
14.50	7.15	5.17	2.98
15.00	7.32	5.33	2.45
15.50	7.46	5.46	2.08
16.00	7.60	5.59	1.96
16.50	7.73	5.72	1.94
17.00	7.84	5.82	1.65
17.50	7.94	5.92	1.41
18.00	8.06	6.03	1.70
18.50	8.10	6.07	0.69
19.00	8.21	6.18	1.40
19.50	8.35	6.31	1.94
20.00	8.48	6.44	1.98
20.50	8.62	6.57	1.98
21.00	**8.76**	**6.70**	1.98

Summary for Pond 3P: Southeast Chambers

Inflow	=	10.44 cfs @	11.93 hrs, Volume=	4.940 af
Outflow	=	4.35 cfs @	15.15 hrs, Volume=	1.908 af, Atten= 58%, Lag= 193.2 min
Primary	=	1.52 cfs @	15.74 hrs, Volume=	1.481 af
Secondary	=	2.83 cfs @	15.15 hrs, Volume=	0.427 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.01 hrs
Peak Elev= 678.34' @ 15.74 hrs Surf.Area= 47,080 sf Storage= 135,796 cf

Plug-Flow detention time= 366.5 min calculated for 1.907 af (39% of inflow)
Center-of-Mass det. time= 161.5 min (899.3 - 737.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.52 cfs @ 15.74 hrs HW=678.34' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.52 cfs @ 13.75 fps)


Secondary OutFlow Max=2.17 cfs @ 15.15 hrs HW=678.31' TW=678.29' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Weir Controls 2.16 cfs @ 0.72 fps)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.57 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.50	0.00	0	670.00	0.00	0.00	0.00	0.00
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
1.50	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.50	0.13	53	670.01	0.00	0.00	0.00	0.00
3.00	0.43	580	670.06	0.01	0.01	0.00	0.00
3.50	0.62	1,471	670.16	0.06	0.06	0.00	0.00
4.00	0.79	2,545	670.28	0.16	0.16	0.00	0.00
4.50	0.93	3,713	670.41	0.25	0.25	0.00	0.00
5.00	1.11	5,009	670.54	0.31	0.31	0.00	0.00
5.50	1.42	6,642	670.70	0.38	0.38	0.00	0.00
6.00	1.66	8,711	670.82	0.42	0.42	0.00	0.00
6.50	1.80	11,032	670.94	0.46	0.46	0.00	0.00
7.00	1.91	13,508	671.05	0.50	0.50	0.00	0.00
7.50	2.02	16,107	671.18	0.53	0.53	0.00	0.00
8.00	2.33	19,005	671.31	0.56	0.56	0.00	0.00
8.50	2.70	22,472	671.46	0.60	0.60	0.00	0.00
9.00	3.10	26,561	671.64	0.64	0.64	0.00	0.00
9.50	3.54	31,295	671.85	0.69	0.69	0.00	0.00
10.00	4.40	37,253	672.12	0.74	0.74	0.00	0.00
10.50	5.97	44,869	672.45	0.80	0.80	0.00	0.00
11.00	8.52	56,338	672.96	0.89	0.89	0.00	0.00
11.50	**9.86**	71,404	673.67	0.99	0.99	0.00	0.00
12.00	**10.41**	87,896	674.58	1.11	1.11	0.00	0.00
12.50	8.98	103,426	675.84	1.26	1.26	0.00	0.00
13.00	7.13	115,561	676.64	1.35	1.35	0.00	0.00
13.50	5.59	124,532	677.28	1.42	1.42	0.00	0.00
14.00	4.25	130,740	677.79	1.47	1.47	0.00	0.00
14.50	3.60	133,828	678.12	2.50	1.50	1.00	0.00
15.00	4.50	135,148	678.27	**2.76**	1.51	**1.25**	0.00
15.50	2.08	**135,763**	**678.34**	**4.16**	**1.52**	**2.64**	0.00
16.00	5.07	**135,634**	**678.33**	1.52	**1.52**	0.00	0.00
16.50	1.94	135,736	678.34	4.10	1.52	2.58	0.00
17.00	4.07	135,263	678.28	1.51	1.51	0.00	0.00
17.50	1.41	134,472	678.20	3.02	1.50	1.52	0.00
18.00	2.49	133,730	678.11	1.68	1.50	0.19	0.00
18.50	0.69	132,547	677.98	1.95	1.48	0.46	0.00
19.00	1.40	131,098	677.83	1.57	1.47	0.10	0.00
19.50	1.94	131,353	677.85	1.73	1.47	0.26	0.00
20.00	1.98	131,588	677.88	1.88	1.47	0.41	0.00
20.50	1.98	131,852	677.91	1.80	1.48	0.33	0.00
21.00	0.00	132,160	677.94	1.82	1.48	0.34	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	3.88 cfs @	15.15 hrs, Volume=	2.362 af
Outflow	=	4.52 cfs @	15.68 hrs, Volume=	2.293 af, Atten= 0%, Lag= 31.9 min
Primary	=	1.40 cfs @	15.72 hrs, Volume=	1.480 af
Secondary	=	3.12 cfs @	15.68 hrs, Volume=	0.813 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.01 hrs
Peak Elev= 678.36' @ 15.72 hrs Surf.Area= 3,535 sf Storage= 4,446 cf

Plug-Flow detention time= 25.9 min calculated for 2.292 af (97% of inflow)
Center-of-Mass det. time= 12.2 min (792.2 - 780.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.40 cfs @ 15.72 hrs HW=678.36' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.40 cfs @ 6.07 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=3.43 cfs @ 15.68 hrs HW=678.36' TW=678.33' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.89 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 3.42 cfs @ 1.04 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.50	0.00	0	670.75	0.00	0.00	0.00	0.00
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
1.50	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.50	0.07	43	673.81	0.03	0.00	0.03	0.00
3.00	0.18	107	676.61	0.14	0.04	0.10	0.00
3.50	0.26	172	676.70	0.23	0.12	0.10	0.00
4.00	0.34	233	676.77	0.30	0.20	0.11	0.00
4.50	0.40	289	676.81	0.37	0.26	0.11	0.00
5.00	0.50	356	676.86	0.44	0.33	0.11	0.00
5.50	0.65	487	676.94	0.56	0.45	0.11	0.00
6.00	0.74	641	677.02	0.66	0.56	0.11	0.00
6.50	0.80	777	677.08	0.73	0.62	0.11	0.00
7.00	0.85	900	677.14	0.78	0.67	0.11	0.00
7.50	0.91	1,020	677.19	0.83	0.72	0.11	0.00
8.00	1.07	1,238	677.28	0.91	0.79	0.11	0.00
8.50	1.25	1,595	677.43	1.02	0.90	0.12	0.00
9.00	1.43	2,072	677.61	1.13	1.01	0.12	0.00
9.50	1.62	2,667	677.82	1.29	1.13	0.16	0.00
10.00	1.82	2,875	677.88	1.78	1.17	0.61	0.00
10.50	2.44	3,034	677.94	2.32	1.20	1.12	0.00
11.00	3.26	3,239	678.00	3.16	1.23	1.93	0.00
11.50	3.59	3,326	678.03	3.56	1.24	2.31	0.00
12.00	3.69	3,363	678.04	3.72	1.25	2.47	0.00
12.50	3.13	3,257	678.01	3.20	1.23	1.97	0.00
13.00	2.55	3,124	677.96	2.61	1.21	1.40	0.00
13.50	2.06	3,002	677.93	2.13	1.19	0.94	0.00
14.00	1.65	2,884	677.89	1.70	1.17	0.53	0.00
14.50	2.32	3,631	678.12	1.90	1.29	0.61	0.00
15.00	**2.34**	4,201	678.29	3.42	1.37	2.05	0.00
15.50	**3.58**	**4,286**	**678.32**	**1.38**	**1.38**	**0.00**	0.00
16.00	0.91	**4,440**	**678.36**	**4.50**	**1.40**	**3.10**	0.00
16.50	3.47	4,277	678.31	1.38	1.38	0.00	0.00
17.00	0.73	4,268	678.31	3.79	1.38	2.42	0.00
17.50	2.19	3,815	678.18	1.32	1.32	0.00	0.00
18.00	1.02	3,629	678.12	2.08	1.29	0.79	0.00
18.50	0.76	3,147	677.97	1.22	1.22	0.00	0.00
19.00	0.86	2,493	677.76	1.10	1.10	0.00	0.00
19.50	1.18	2,387	677.72	1.08	1.08	0.00	0.00
20.00	1.33	2,703	677.83	1.14	1.14	0.00	0.00
20.50	1.25	2,912	677.90	1.18	1.18	0.00	0.00
21.00	0.00	3,032	677.94	1.20	1.20	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 3.02 cfs @ 15.77 hrs, Volume= 2.034 af, Depth> 6.97"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.01 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57" x 8

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.50	0.02	0.00	0.00
1.00	0.09	0.00	0.00
1.50	0.20	0.00	0.00
2.00	0.30	0.00	0.00
2.50	0.41	0.00	0.00
3.00	0.52	0.01	0.04
3.50	0.63	0.02	0.11
4.00	0.74	0.05	0.17
4.50	0.85	0.08	0.22
5.00	0.96	0.12	0.27
5.50	1.07	0.16	0.31
6.00	1.17	0.21	0.34
6.50	1.29	0.27	0.40
7.00	1.42	0.34	0.49
7.50	1.57	0.42	0.58
8.00	1.71	0.51	0.62
8.50	1.86	0.60	0.66
9.00	2.00	0.70	0.69
9.50	2.15	0.80	0.71
10.00	2.30	0.90	0.76
10.50	2.46	1.03	0.86
11.00	2.64	1.16	0.97
11.50	2.84	1.32	1.07
12.00	3.05	1.48	1.18
12.50	3.27	1.67	1.30
13.00	3.51	1.87	1.41
13.50	3.78	2.09	1.59
14.00	4.11	2.38	2.06
14.50	4.52	2.75	2.56
15.00	4.97	3.15	2.82
15.50	5.43	3.57	**2.96**
16.00	5.88	3.98	**2.94**
16.50	6.28	4.35	2.58
17.00	6.61	4.66	2.20
17.50	6.89	4.93	1.90
18.00	7.13	5.15	1.60
18.50	7.34	5.35	1.35
19.00	7.51	5.51	1.15
19.50	7.65	5.65	0.97
20.00	7.78	5.77	0.86
20.50	7.90	5.88	0.76
21.00	8.00	5.98	0.73
21.50	8.11	6.09	0.73
22.00	8.22	6.18	0.70
22.50	8.31	6.27	0.60
23.00	8.38	6.34	0.51
23.50	8.47	6.43	0.58
24.00	8.57	6.52	0.69
24.50	8.59	6.54	0.19
25.00	8.66	6.61	0.46
25.50	8.77	6.71	0.72
26.00	8.87	6.82	0.74
26.50	8.98	6.92	0.74
27.00	**9.09**	**7.03**	0.74

Summary for Subcatchment 7S: South Property


Runoff = 6.45 cfs @ 15.85 hrs, Volume= 4.343 af, Depth> 6.95"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.01 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57" x 8

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.50	0.02	0.00	0.00
1.00	0.09	0.00	0.00
1.50	0.20	0.00	0.00
2.00	0.30	0.00	0.00
2.50	0.41	0.00	0.00
3.00	0.52	0.01	0.06
3.50	0.63	0.02	0.20
4.00	0.74	0.05	0.34
4.50	0.85	0.08	0.45
5.00	0.96	0.12	0.55
5.50	1.07	0.16	0.64
6.00	1.17	0.21	0.72
6.50	1.29	0.27	0.83
7.00	1.42	0.34	1.01
7.50	1.57	0.42	1.21
8.00	1.71	0.51	1.32
8.50	1.86	0.60	1.39
9.00	2.00	0.70	1.46
9.50	2.15	0.80	1.51
10.00	2.30	0.90	1.59
10.50	2.46	1.03	1.79
11.00	2.64	1.16	2.01
11.50	2.84	1.32	2.25
12.00	3.05	1.48	2.48
12.50	3.27	1.67	2.73
13.00	3.51	1.87	2.97
13.50	3.78	2.09	3.27
14.00	4.11	2.38	4.16
14.50	4.52	2.75	5.23
15.00	4.97	3.15	5.95
15.50	5.43	3.57	**6.27**
16.00	5.88	3.98	**6.38**
16.50	6.28	4.35	5.71
17.00	6.61	4.66	4.90
17.50	6.89	4.93	4.22
18.00	7.13	5.15	3.58
18.50	7.34	5.35	3.01
19.00	7.51	5.51	2.57
19.50	7.65	5.65	2.16
20.00	7.78	5.77	1.90
20.50	7.90	5.88	1.68
21.00	8.00	5.98	1.58
21.50	8.11	6.09	1.57
22.00	8.22	6.18	1.54
22.50	8.31	6.27	1.34
23.00	8.38	6.34	1.13
23.50	8.47	6.43	1.20
24.00	8.57	6.52	1.42
24.50	8.59	6.54	0.49
25.00	8.66	6.61	0.84
25.50	8.77	6.71	1.45
26.00	8.87	6.82	1.58
26.50	8.98	6.92	1.58
27.00	**9.09**	**7.03**	1.58

Summary for Pond 3P: Southeast Chambers

Inflow	=	8.23 cfs @	15.85 hrs, Volume=	4.913 af
Outflow	=	2.55 cfs @	19.97 hrs, Volume=	1.994 af, Atten= 69%, Lag= 246.9 min
Primary	=	1.49 cfs @	20.01 hrs, Volume=	1.858 af
Secondary	=	1.06 cfs @	19.97 hrs, Volume=	0.136 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.00 hrs, dt= 0.01 hrs
Peak Elev= 678.07' @ 20.01 hrs Surf.Area= 47,049 sf Storage= 133,290 cf

Plug-Flow detention time= 436.6 min calculated for 1.994 af (41% of inflow)
Center-of-Mass det. time= 181.5 min (1,125.9 - 944.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.49 cfs @ 20.01 hrs HW=678.07' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.49 cfs @ 13.51 fps)


Secondary OutFlow Max=0.93 cfs @ 19.97 hrs HW=678.06' TW=678.05' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Weir Controls 0.93 cfs @ 0.59 fps)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.50 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
3.00	0.06	27	670.00	0.00	0.00	0.00	0.00
4.00	0.44	989	670.11	0.03	0.03	0.00	0.00
5.00	0.66	2,642	670.30	0.17	0.17	0.00	0.00
6.00	0.83	4,471	670.48	0.29	0.29	0.00	0.00
7.00	1.12	6,669	670.70	0.38	0.38	0.00	0.00
8.00	1.43	9,845	670.88	0.44	0.44	0.00	0.00
9.00	1.57	13,550	671.06	0.50	0.50	0.00	0.00
10.00	1.70	17,520	671.24	0.55	0.55	0.00	0.00
11.00	2.13	22,315	671.46	0.60	0.60	0.00	0.00
12.00	2.60	28,541	671.73	0.66	0.66	0.00	0.00
13.00	3.09	36,267	672.08	0.73	0.73	0.00	0.00
14.00	4.95	46,875	672.54	0.82	0.82	0.00	0.00
15.00	**7.53**	66,791	673.45	0.96	0.96	0.00	0.00
16.00	**8.12**	91,658	674.87	1.15	1.15	0.00	0.00
17.00	5.96	112,748	676.45	1.33	1.33	0.00	0.00
18.00	4.06	125,744	677.37	1.43	1.43	0.00	0.00
19.00	2.57	132,049	677.93	**1.82**	1.48	**0.34**	0.00
20.00	1.90	**133,275**	**678.06**	**1.49**	**1.49**	**0.00**	0.00
21.00	1.58	**132,585**	**677.99**	1.87	**1.49**	0.38	0.00
22.00	1.54	131,627	677.88	1.80	1.48	0.32	0.00
23.00	1.13	130,625	677.78	1.50	1.47	0.03	0.00
24.00	1.42	129,624	677.69	1.50	1.46	0.04	0.00
25.00	0.84	127,238	677.48	1.48	1.44	0.04	0.00
26.00	1.58	126,784	677.45	1.47	1.43	0.03	0.00
27.00	0.00	127,205	677.48	1.47	1.44	0.03	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	3.02 cfs @	15.77 hrs, Volume=	2.170 af
Outflow	=	3.02 cfs @	15.83 hrs, Volume=	2.145 af, Atten= 0%, Lag= 3.1 min
Primary	=	1.26 cfs @	20.04 hrs, Volume=	1.573 af
Secondary	=	1.79 cfs @	15.83 hrs, Volume=	0.572 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.00 hrs, dt= 0.01 hrs
Peak Elev= 678.07' @ 20.04 hrs Surf.Area= 3,240 sf Storage= 3,446 cf

Plug-Flow detention time= 25.6 min calculated for 2.145 af (99% of inflow)
Center-of-Mass det. time= 18.2 min (985.2 - 967.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.26 cfs @ 20.04 hrs HW=678.06' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.26 cfs @ 5.48 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=1.79 cfs @ 15.83 hrs HW=677.99' TW=674.53' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.95 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 1.68 cfs @ 1.47 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.04	23	672.40	0.00	0.00	0.00	0.00
4.00	0.17	114	676.62	0.15	0.04	0.10	0.00
5.00	0.27	189	676.72	0.25	0.14	0.11	0.00
6.00	0.34	252	676.78	0.33	0.22	0.11	0.00
7.00	0.49	363	676.86	0.45	0.34	0.11	0.00
8.00	0.62	526	676.96	0.59	0.48	0.11	0.00
9.00	0.69	630	677.01	0.66	0.55	0.11	0.00
10.00	0.76	740	677.06	0.71	0.60	0.11	0.00
11.00	0.97	1,058	677.21	0.84	0.73	0.11	0.00
12.00	1.18	1,584	677.42	1.01	0.90	0.12	0.00
13.00	1.41	2,305	677.69	1.18	1.06	0.12	0.00
14.00	2.06	2,935	677.90	1.97	1.18	0.79	0.00
15.00	**2.82**	3,155	677.97	**2.80**	1.22	**1.58**	0.00
16.00	**2.94**	3,199	677.99	**2.97**	1.22	**1.74**	0.00
17.00	2.20	3,030	677.93	2.25	1.20	1.06	0.00
18.00	1.60	2,860	677.88	1.65	1.17	0.48	0.00
19.00	1.49	2,995	677.92	1.19	1.19	0.00	0.00
20.00	0.86	**3,404**	**678.05**	1.26	**1.26**	0.00	0.00
21.00	1.12	**3,180**	**677.98**	1.22	**1.22**	0.00	0.00
22.00	1.02	2,799	677.86	1.16	1.16	0.00	0.00
23.00	0.54	1,669	677.46	0.92	0.92	0.00	0.00
24.00	0.73	1,054	677.20	0.73	0.73	0.00	0.00
25.00	0.50	463	676.93	0.43	0.43	0.00	0.00
26.00	0.77	938	677.15	0.69	0.69	0.00	0.00
27.00	0.00	1,102	677.22	0.75	0.75	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.72 cfs @ 41.20 hrs, Volume= 2.116 af, Depth> 7.26"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28" x 8

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	26.00	2.84	1.32	0.42
0.50	0.00	0.00	0.00	26.50	2.92	1.38	0.44
1.00	0.02	0.00	0.00	27.00	2.99	1.44	0.44
1.50	0.04	0.00	0.00	27.50	3.07	1.50	0.42
2.00	0.07	0.00	0.00	28.00	3.14	1.56	0.40
2.50	0.10	0.00	0.00	28.50	3.20	1.61	0.38
3.00	0.15	0.00	0.00	29.00	3.26	1.66	0.36
3.50	0.20	0.00	0.00	29.50	3.33	1.71	0.38
4.00	0.25	0.00	0.00	30.00	3.40	1.77	0.40
4.50	0.30	0.00	0.00	30.50	3.47	1.83	0.43
5.00	0.36	0.00	0.00	31.00	3.54	1.90	0.46
5.50	0.42	0.00	0.00	31.50	3.63	1.97	0.49
6.00	0.48	0.00	0.02	32.00	3.72	2.04	0.54
6.50	0.54	0.01	0.04	32.50	3.81	2.13	0.59
7.00	0.60	0.02	0.06	33.00	3.92	2.22	0.65
7.50	0.66	0.03	0.08	33.50	4.04	2.32	0.70
8.00	0.72	0.04	0.09	34.00	4.16	2.42	0.74
8.50	0.77	0.05	0.10	34.50	4.28	2.53	0.75
9.00	0.82	0.07	0.10	35.00	4.40	2.64	0.75
9.50	0.86	0.08	0.10	35.50	4.52	2.74	0.76
10.00	0.90	0.10	0.10	36.00	4.64	2.85	0.76
10.50	0.95	0.11	0.12	36.50	4.77	2.96	0.79
11.00	1.00	0.13	0.14	37.00	4.90	3.08	0.85
11.50	1.05	0.15	0.16	37.50	5.04	3.21	0.90
12.00	1.11	0.18	0.18	38.00	5.19	3.35	0.96
12.50	1.17	0.21	0.19	38.50	5.35	3.49	1.02
13.00	1.23	0.24	0.20	39.00	5.53	3.65	1.14
13.50	1.29	0.27	0.21	39.50	5.72	3.83	1.28
14.00	1.35	0.30	0.22	40.00	5.94	4.04	1.42
14.50	1.41	0.33	0.23	40.50	6.18	4.26	1.56
15.00	1.47	0.36	0.24	41.00	6.44	4.50	**1.70**
15.50	1.53	0.40	0.25	41.50	6.69	4.74	**1.71**
16.00	1.60	0.43	0.25	42.00	6.95	4.98	1.69
16.50	1.66	0.47	0.26	42.50	7.20	5.21	1.67
17.00	1.72	0.51	0.26	43.00	7.44	5.45	1.64
17.50	1.78	0.55	0.27	43.50	7.68	5.67	1.60
18.00	1.84	0.59	0.28	44.00	7.91	5.89	1.50
18.50	1.90	0.63	0.28	44.50	8.11	6.08	1.39
19.00	1.96	0.67	0.29	45.00	8.30	6.27	1.28
19.50	2.02	0.71	0.29	45.50	8.47	6.43	1.17
20.00	2.08	0.75	0.29	46.00	8.64	6.59	1.09
20.50	2.14	0.79	0.30	46.50	8.80	6.74	1.09
21.00	2.20	0.83	0.30	47.00	8.96	6.90	1.09
21.50	2.26	0.88	0.31	47.50	9.12	7.05	1.10
22.00	2.32	0.92	0.31	48.00	9.28	7.21	1.10
22.50	2.38	0.97	0.31	48.50	9.28	7.21	0.08
23.00	2.44	1.01	0.32	49.00	9.30	7.22	0.09
23.50	2.50	1.06	0.32	49.50	9.32	7.24	0.14
24.00	2.56	1.10	0.32	50.00	**9.35**	**7.27**	0.20
24.50	2.62	1.15	0.34				
25.00	2.69	1.20	0.36				
25.50	2.76	1.26	0.39				

Summary for Subcatchment 7S: South Property


Runoff = 3.67 cfs @ 41.40 hrs, Volume= 4.531 af, Depth> 7.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28" x 8

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	26.00	2.84	1.32	0.88
0.50	0.00	0.00	0.00	26.50	2.92	1.38	0.94
1.00	0.02	0.00	0.00	27.00	2.99	1.44	0.95
1.50	0.04	0.00	0.00	27.50	3.07	1.50	0.91
2.00	0.07	0.00	0.00	28.00	3.14	1.56	0.86
2.50	0.10	0.00	0.00	28.50	3.20	1.61	0.82
3.00	0.15	0.00	0.00	29.00	3.26	1.66	0.77
3.50	0.20	0.00	0.00	29.50	3.33	1.71	0.79
4.00	0.25	0.00	0.00	30.00	3.40	1.77	0.85
4.50	0.30	0.00	0.00	30.50	3.47	1.83	0.90
5.00	0.36	0.00	0.00	31.00	3.54	1.90	0.96
5.50	0.42	0.00	0.00	31.50	3.63	1.97	1.03
6.00	0.48	0.00	0.03	32.00	3.72	2.04	1.13
6.50	0.54	0.01	0.07	32.50	3.81	2.13	1.24
7.00	0.60	0.02	0.12	33.00	3.92	2.22	1.36
7.50	0.66	0.03	0.16	33.50	4.04	2.32	1.48
8.00	0.72	0.04	0.19	34.00	4.16	2.42	1.58
8.50	0.77	0.05	0.20	34.50	4.28	2.53	1.60
9.00	0.82	0.07	0.21	35.00	4.40	2.64	1.61
9.50	0.86	0.08	0.21	35.50	4.52	2.74	1.62
10.00	0.90	0.10	0.21	36.00	4.64	2.85	1.63
10.50	0.95	0.11	0.24	36.50	4.77	2.96	1.67
11.00	1.00	0.13	0.28	37.00	4.90	3.08	1.79
11.50	1.05	0.15	0.32	37.50	5.04	3.21	1.91
12.00	1.11	0.18	0.37	38.00	5.19	3.35	2.03
12.50	1.17	0.21	0.41	38.50	5.35	3.49	2.16
13.00	1.23	0.24	0.43	39.00	5.53	3.65	2.37
13.50	1.29	0.27	0.45	39.50	5.72	3.83	2.67
14.00	1.35	0.30	0.47	40.00	5.94	4.04	2.97
14.50	1.41	0.33	0.49	40.50	6.18	4.26	3.28
15.00	1.47	0.36	0.51	41.00	6.44	4.50	**3.59**
15.50	1.53	0.40	0.52	41.50	6.69	4.74	**3.67**
16.00	1.60	0.43	0.54	42.00	6.95	4.98	3.62
16.50	1.66	0.47	0.55	42.50	7.20	5.21	3.58
17.00	1.72	0.51	0.56	43.00	7.44	5.45	3.53
17.50	1.78	0.55	0.58	43.50	7.68	5.67	3.47
18.00	1.84	0.59	0.59	44.00	7.91	5.89	3.27
18.50	1.90	0.63	0.60	44.50	8.11	6.08	3.04
19.00	1.96	0.67	0.61	45.00	8.30	6.27	2.80
19.50	2.02	0.71	0.62	45.50	8.47	6.43	2.56
20.00	2.08	0.75	0.63	46.00	8.64	6.59	2.36
20.50	2.14	0.79	0.64	46.50	8.80	6.74	2.34
21.00	2.20	0.83	0.65	47.00	8.96	6.90	2.34
21.50	2.26	0.88	0.66	47.50	9.12	7.05	2.35
22.00	2.32	0.92	0.66	48.00	9.28	7.21	2.35
22.50	2.38	0.97	0.67	48.50	9.28	7.21	0.47
23.00	2.44	1.01	0.68	49.00	9.30	7.22	0.17
23.50	2.50	1.06	0.69	49.50	9.32	7.24	0.28
24.00	2.56	1.10	0.69	50.00	**9.35**	**7.27**	0.40
24.50	2.62	1.15	0.71				
25.00	2.69	1.20	0.77				
25.50	2.76	1.26	0.82				

Summary for Pond 3P: Southeast Chambers

Inflow	=	4.22 cfs @	41.35 hrs, Volume=	5.009 af
Outflow	=	1.39 cfs @	48.32 hrs, Volume=	2.370 af, Atten= 67%, Lag= 418.1 min
Primary	=	1.39 cfs @	48.32 hrs, Volume=	2.370 af
Secondary	=	0.01 cfs @	49.20 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.00 hrs, dt= 0.01 hrs
Peak Elev= 677.04' @ 48.32 hrs Surf.Area= 46,934 sf Storage= 121,254 cf

Plug-Flow detention time= 484.1 min calculated for 2.369 af (47% of inflow)
Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.39 cfs @ 48.32 hrs HW=677.04' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.39 cfs @ 12.60 fps)


Secondary OutFlow Max=0.01 cfs @ 49.20 hrs HW=676.81' TW=676.78' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.81 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
3.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.00	0	670.00	0.00	0.00	0.00	0.00
5.00	0.00	0	670.00	0.00	0.00	0.00	0.00
6.00	0.03	16	670.00	0.00	0.00	0.00	0.00
7.00	0.18	380	670.04	0.00	0.00	0.00	0.00
8.00	0.27	1,142	670.13	0.04	0.04	0.00	0.00
9.00	0.31	1,940	670.22	0.11	0.11	0.00	0.00
10.00	0.31	2,548	670.29	0.16	0.16	0.00	0.00
11.00	0.38	3,106	670.35	0.21	0.21	0.00	0.00
12.00	0.47	3,802	670.42	0.26	0.26	0.00	0.00
13.00	0.54	4,647	670.50	0.30	0.30	0.00	0.00
14.00	0.58	5,513	670.59	0.34	0.34	0.00	0.00
15.00	0.61	6,379	670.67	0.37	0.37	0.00	0.00
16.00	0.64	7,245	670.75	0.40	0.40	0.00	0.00
17.00	0.67	8,138	670.80	0.42	0.42	0.00	0.00
18.00	0.69	9,069	670.84	0.43	0.43	0.00	0.00
19.00	0.72	10,031	670.89	0.44	0.44	0.00	0.00
20.00	0.74	11,013	670.93	0.46	0.46	0.00	0.00
21.00	0.75	12,012	670.98	0.47	0.47	0.00	0.00
22.00	0.77	13,020	671.03	0.49	0.49	0.00	0.00
23.00	0.78	14,033	671.08	0.50	0.50	0.00	0.00
24.00	0.80	15,049	671.13	0.52	0.52	0.00	0.00
25.00	0.87	16,139	671.18	0.53	0.53	0.00	0.00
26.00	0.99	17,549	671.24	0.55	0.55	0.00	0.00
27.00	1.06	19,283	671.32	0.57	0.57	0.00	0.00
28.00	0.97	20,863	671.39	0.58	0.58	0.00	0.00
29.00	0.88	22,062	671.44	0.60	0.60	0.00	0.00
30.00	0.95	23,146	671.49	0.61	0.61	0.00	0.00
31.00	1.07	24,575	671.56	0.62	0.62	0.00	0.00
32.00	1.24	26,412	671.64	0.64	0.64	0.00	0.00
33.00	1.47	28,931	671.75	0.66	0.66	0.00	0.00
34.00	1.69	32,197	671.89	0.69	0.69	0.00	0.00
35.00	1.72	35,795	672.06	0.73	0.73	0.00	0.00
36.00	1.74	39,353	672.21	0.76	0.76	0.00	0.00
37.00	1.90	43,037	672.37	0.79	0.79	0.00	0.00
38.00	2.15	47,423	672.57	0.82	0.82	0.00	0.00
39.00	2.49	52,627	672.80	0.86	0.86	0.00	0.00
40.00	3.09	59,467	673.11	0.91	0.91	0.00	0.00
41.00	**4.10**	68,856	673.55	0.97	0.97	0.00	0.00
42.00	**4.15**	80,269	674.12	1.05	1.05	0.00	0.00
43.00	4.01	91,013	674.82	1.14	1.14	0.00	0.00
44.00	3.64	100,697	675.63	1.24	1.24	0.00	0.00
45.00	2.97	108,028	676.13	1.30	1.30	0.00	0.00
46.00	2.43	112,893	676.46	1.33	1.33	0.00	0.00
47.00	2.40	116,719	676.72	1.36	1.36	0.00	0.00
48.00	2.40	**120,421**	**676.98**	**1.39**	**1.39**	0.00	0.00
49.00	0.17	**118,894**	**676.87**	**1.37**	**1.37**	**0.00**	0.00
50.00	0.00	115,011	676.60	1.35	1.35	**0.00**	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	1.72 cfs @	41.20 hrs, Volume=	2.117 af
Outflow	=	1.71 cfs @	41.33 hrs, Volume=	2.112 af, Atten= 0%, Lag= 7.4 min
Primary	=	1.17 cfs @	41.36 hrs, Volume=	1.634 af
Secondary	=	0.55 cfs @	41.33 hrs, Volume=	0.478 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.00 hrs, dt= 0.01 hrs
Peak Elev= 677.88' @ 41.36 hrs Surf.Area= 3,040 sf Storage= 2,853 cf

Plug-Flow detention time= 23.5 min calculated for 2.112 af (100% of inflow)
Center-of-Mass det. time= 21.7 min (2,177.2 - 2,155.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.17 cfs @ 41.36 hrs HW=677.88' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 1.17 cfs @ 5.07 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.55 cfs @ 41.33 hrs HW=677.88' TW=673.73' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.81 fps)
└—5=**Sharp-Crested Rectangular Weir** (Weir Controls 0.43 cfs @ 0.92 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.00	0	670.75	0.00	0.00	0.00	0.00
4.00	0.00	0	670.75	0.00	0.00	0.00	0.00
5.00	0.00	0	670.75	0.00	0.00	0.00	0.00
6.00	0.02	12	671.63	0.00	0.00	0.00	0.00
7.00	0.06	52	674.47	0.06	0.00	0.06	0.00
8.00	0.09	69	675.68	0.09	0.00	0.09	0.00
9.00	0.10	77	676.24	0.10	0.00	0.10	0.00
10.00	0.10	77	676.27	0.10	0.00	0.10	0.00
11.00	0.14	101	676.59	0.13	0.03	0.10	0.00
12.00	0.18	130	676.65	0.17	0.07	0.10	0.00
13.00	0.20	152	676.68	0.20	0.10	0.10	0.00
14.00	0.22	164	676.70	0.22	0.11	0.10	0.00
15.00	0.24	178	676.71	0.23	0.13	0.10	0.00
16.00	0.25	190	676.72	0.25	0.14	0.11	0.00
17.00	0.26	200	676.73	0.26	0.16	0.11	0.00
18.00	0.28	209	676.74	0.27	0.17	0.11	0.00
19.00	0.29	217	676.75	0.28	0.18	0.11	0.00
20.00	0.29	224	676.76	0.29	0.19	0.11	0.00
21.00	0.30	230	676.76	0.30	0.20	0.11	0.00
22.00	0.31	236	676.77	0.31	0.20	0.11	0.00
23.00	0.32	241	676.77	0.32	0.21	0.11	0.00
24.00	0.32	247	676.78	0.32	0.22	0.11	0.00
25.00	0.36	275	676.80	0.35	0.24	0.11	0.00
26.00	0.42	322	676.84	0.40	0.30	0.11	0.00
27.00	0.44	357	676.86	0.44	0.33	0.11	0.00
28.00	0.40	325	676.84	0.41	0.30	0.11	0.00
29.00	0.36	287	676.81	0.36	0.26	0.11	0.00
30.00	0.40	309	676.83	0.39	0.28	0.11	0.00
31.00	0.46	356	676.86	0.44	0.33	0.11	0.00
32.00	0.54	431	676.91	0.51	0.40	0.11	0.00
33.00	0.65	552	676.97	0.61	0.50	0.11	0.00
34.00	0.74	716	677.05	0.70	0.59	0.11	0.00
35.00	0.75	803	677.09	0.74	0.63	0.11	0.00
36.00	0.76	833	677.11	0.75	0.64	0.11	0.00
37.00	0.85	929	677.15	0.79	0.68	0.11	0.00
38.00	0.96	1,169	677.25	0.88	0.77	0.11	0.00
39.00	1.14	1,517	677.40	0.99	0.88	0.12	0.00
40.00	1.42	2,236	677.67	1.17	1.05	0.12	0.00
41.00	**1.70**	**2,841**	**677.87**	**1.68**	**1.16**	**0.51**	0.00
42.00	**1.69**	**2,848**	**677.88**	**1.69**	**1.17**	**0.52**	0.00
43.00	1.64	2,836	677.87	1.65	1.16	0.48	0.00
44.00	1.50	2,796	677.86	1.52	1.16	0.37	0.00
45.00	1.28	2,705	677.83	1.31	1.14	0.17	0.00
46.00	1.09	2,518	677.77	1.17	1.11	0.07	0.00
47.00	1.09	2,322	677.70	1.13	1.07	0.06	0.00
48.00	1.10	2,256	677.67	1.10	1.05	0.05	0.00
49.00	0.09	376	676.87	0.35	0.35	0.00	0.00
50.00	0.00	205	676.74	0.18	0.16	0.02	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.23 cfs @ 61.56 hrs, Volume= 2.280 af, Depth> 7.82"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85" x 8

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.01	0.00	0.00
2.00	0.03	0.00	0.00
3.00	0.07	0.00	0.00
4.00	0.13	0.00	0.00
5.00	0.19	0.00	0.00
6.00	0.26	0.00	0.00
7.00	0.34	0.00	0.00
8.00	0.43	0.00	0.00
9.00	0.51	0.00	0.02
10.00	0.60	0.02	0.04
11.00	0.68	0.03	0.06
12.00	0.76	0.05	0.07
13.00	0.84	0.07	0.08
14.00	0.90	0.09	0.07
15.00	0.96	0.12	0.08
16.00	1.02	0.14	0.10
17.00	1.10	0.17	0.12
18.00	1.18	0.21	0.14
19.00	1.27	0.25	0.15
20.00	1.35	0.30	0.16
21.00	1.44	0.34	0.17
22.00	1.52	0.39	0.17
23.00	1.61	0.44	0.18
24.00	1.69	0.49	0.19
25.00	1.78	0.55	0.19
26.00	1.86	0.60	0.20
27.00	1.95	0.66	0.20
28.00	2.03	0.72	0.21
29.00	2.12	0.78	0.21
30.00	2.21	0.84	0.22
31.00	2.29	0.90	0.22
32.00	2.38	0.96	0.22
33.00	2.46	1.03	0.23
34.00	2.55	1.09	0.23
35.00	2.63	1.16	0.23
36.00	2.72	1.22	0.23
37.00	2.81	1.29	0.25
38.00	2.91	1.37	0.28
39.00	3.01	1.46	0.30
40.00	3.12	1.55	0.32
41.00	3.23	1.63	0.30
42.00	3.33	1.72	0.28
43.00	3.42	1.79	0.26
44.00	3.51	1.87	0.27
45.00	3.60	1.95	0.29
46.00	3.71	2.03	0.32
47.00	3.82	2.13	0.34
48.00	3.94	2.24	0.39
49.00	4.09	2.36	0.44
50.00	4.24	2.50	0.50
51.00	4.41	2.65	0.53
52.00	4.58	2.80	0.54
53.00	4.75	2.95	0.54
54.00	4.93	3.11	0.54
55.00	5.10	3.27	0.59
56.00	5.30	3.45	0.64
57.00	5.51	3.64	0.69
58.00	5.74	3.85	0.76
59.00	6.00	4.09	0.89
60.00	6.30	4.37	1.03
61.00	6.65	4.70	**1.17**
62.00	7.01	5.04	**1.22**
63.00	7.37	5.38	1.20
64.00	7.73	5.72	1.18
65.00	8.07	6.05	1.15
66.00	8.39	6.35	1.05
67.00	8.68	6.63	0.95
68.00	8.94	6.87	0.84
69.00	9.17	7.10	0.78
70.00	9.39	7.32	0.78
71.00	9.62	7.54	0.78
72.00	9.85	7.76	0.78
73.00	9.86	7.76	0.04
74.00	9.88	7.79	0.09
75.00	**9.92**	**7.83**	0.15

Summary for Subcatchment 7S: South Property


Runoff = 2.62 cfs @ 61.74 hrs, Volume= 4.882 af, Depth> 7.81"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85" x 8

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.01	0.00	0.00
2.00	0.03	0.00	0.00
3.00	0.07	0.00	0.00
4.00	0.13	0.00	0.00
5.00	0.19	0.00	0.00
6.00	0.26	0.00	0.00
7.00	0.34	0.00	0.00
8.00	0.43	0.00	0.00
9.00	0.51	0.00	0.04
10.00	0.60	0.02	0.09
11.00	0.68	0.03	0.13
12.00	0.76	0.05	0.15
13.00	0.84	0.07	0.16
14.00	0.90	0.09	0.16
15.00	0.96	0.12	0.16
16.00	1.02	0.14	0.20
17.00	1.10	0.17	0.24
18.00	1.18	0.21	0.29
19.00	1.27	0.25	0.32
20.00	1.35	0.30	0.34
21.00	1.44	0.34	0.35
22.00	1.52	0.39	0.37
23.00	1.61	0.44	0.38
24.00	1.69	0.49	0.40
25.00	1.78	0.55	0.41
26.00	1.86	0.60	0.42
27.00	1.95	0.66	0.43
28.00	2.03	0.72	0.44
29.00	2.12	0.78	0.45
30.00	2.21	0.84	0.46
31.00	2.29	0.90	0.47
32.00	2.38	0.96	0.48
33.00	2.46	1.03	0.48
34.00	2.55	1.09	0.49
35.00	2.63	1.16	0.50
36.00	2.72	1.22	0.50
37.00	2.81	1.29	0.54
38.00	2.91	1.37	0.59
39.00	3.01	1.46	0.65
40.00	3.12	1.55	0.69
41.00	3.23	1.63	0.66
42.00	3.33	1.72	0.61
43.00	3.42	1.79	0.57
44.00	3.51	1.87	0.57
45.00	3.60	1.95	0.62
46.00	3.71	2.03	0.67
47.00	3.82	2.13	0.73
48.00	3.94	2.24	0.83
49.00	4.09	2.36	0.94
50.00	4.24	2.50	1.05
51.00	4.41	2.65	1.14
52.00	4.58	2.80	1.15
53.00	4.75	2.95	1.16
54.00	4.93	3.11	1.16
55.00	5.10	3.27	1.24
56.00	5.30	3.45	1.36
57.00	5.51	3.64	1.47
58.00	5.74	3.85	1.60
59.00	6.00	4.09	1.88
60.00	6.30	4.37	2.17
61.00	6.65	4.70	**2.47**
62.00	7.01	5.04	**2.62**
63.00	7.37	5.38	2.57
64.00	7.73	5.72	2.52
65.00	8.07	6.05	2.48
66.00	8.39	6.35	2.29
67.00	8.68	6.63	2.06
68.00	8.94	6.87	1.84
69.00	9.17	7.10	1.66
70.00	9.39	7.32	1.66
71.00	9.62	7.54	1.67
72.00	9.85	7.76	1.67
73.00	9.86	7.76	0.09
74.00	9.88	7.79	0.19
75.00	**9.92**	**7.83**	0.30

Summary for Pond 3P: Southeast Chambers

Inflow	=	2.74 cfs @	61.74 hrs, Volume=	5.420 af
Outflow	=	1.26 cfs @	72.27 hrs, Volume=	3.282 af, Atten= 54%, Lag= 631.5 min
Primary	=	1.26 cfs @	72.27 hrs, Volume=	3.282 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.01 hrs
Peak Elev= 675.76' @ 72.27 hrs Surf.Area= 46,791 sf Storage= 102,225 cf

Plug-Flow detention time= 517.7 min calculated for 3.281 af (61% of inflow)
Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.26 cfs @ 72.27 hrs HW=675.76' (Free Discharge)
└─**1=Orifice/Grate** (Orifice Controls 1.26 cfs @ 11.37 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├─**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└─**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└─**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.00	0	670.00	0.00	0.00	0.00	0.00
6.00	0.00	0	670.00	0.00	0.00	0.00	0.00
8.00	0.00	0	670.00	0.00	0.00	0.00	0.00
10.00	0.13	413	670.05	0.01	0.01	0.00	0.00
12.00	0.22	1,521	670.17	0.07	0.07	0.00	0.00
14.00	0.24	2,403	670.27	0.15	0.15	0.00	0.00
16.00	0.29	2,941	670.33	0.20	0.20	0.00	0.00
18.00	0.39	3,774	670.42	0.25	0.25	0.00	0.00
20.00	0.44	4,779	670.52	0.30	0.30	0.00	0.00
22.00	0.47	5,728	670.61	0.35	0.35	0.00	0.00
24.00	0.50	6,627	670.70	0.38	0.38	0.00	0.00
26.00	0.53	7,490	670.77	0.40	0.40	0.00	0.00
28.00	0.55	8,387	670.81	0.42	0.42	0.00	0.00
30.00	0.56	9,317	670.85	0.43	0.43	0.00	0.00
32.00	0.58	10,262	670.90	0.45	0.45	0.00	0.00
34.00	0.59	11,212	670.94	0.46	0.46	0.00	0.00
36.00	0.61	12,155	670.99	0.48	0.48	0.00	0.00
38.00	0.70	13,310	671.04	0.49	0.49	0.00	0.00
40.00	0.80	15,088	671.13	0.52	0.52	0.00	0.00
42.00	0.72	16,777	671.21	0.54	0.54	0.00	0.00
44.00	0.67	17,750	671.25	0.55	0.55	0.00	0.00
46.00	0.78	18,971	671.31	0.56	0.56	0.00	0.00
48.00	0.94	20,935	671.40	0.58	0.58	0.00	0.00
50.00	1.16	24,156	671.54	0.62	0.62	0.00	0.00
52.00	1.26	28,438	671.73	0.66	0.66	0.00	0.00
54.00	1.27	32,660	671.92	0.70	0.70	0.00	0.00
56.00	1.47	37,227	672.12	0.74	0.74	0.00	0.00
58.00	1.72	43,137	672.38	0.79	0.79	0.00	0.00
60.00	**2.29**	51,617	672.75	0.85	0.85	0.00	0.00
62.00	**2.73**	63,642	673.30	0.94	0.94	0.00	0.00
64.00	2.64	75,943	673.90	1.02	1.02	0.00	0.00
66.00	2.39	86,694	674.50	1.10	1.10	0.00	0.00
68.00	1.93	94,024	675.07	1.17	1.17	0.00	0.00
70.00	1.74	98,231	675.42	1.22	1.22	0.00	0.00
72.00	1.74	**101,877**	**675.73**	**1.25**	**1.25**	0.00	0.00
74.00	0.26	**96,273**	**675.25**	**1.20**	**1.20**	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	1.23 cfs @	61.56 hrs, Volume=	2.279 af
Outflow	=	1.18 cfs @	63.56 hrs, Volume=	2.277 af, Atten= 4%, Lag= 120.3 min
Primary	=	1.06 cfs @	63.86 hrs, Volume=	1.738 af
Secondary	=	0.12 cfs @	62.88 hrs, Volume=	0.538 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.01 hrs
Peak Elev= 677.69' @ 63.86 hrs Surf.Area= 2,836 sf Storage= 2,301 cf

Plug-Flow detention time= 20.4 min calculated for 2.276 af (100% of inflow)
Center-of-Mass det. time= 18.8 min (3,231.9 - 3,213.1)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.06 cfs @ 63.86 hrs HW=677.69' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 1.06 cfs @ 4.62 fps)
└2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.12 cfs @ 62.88 hrs HW=677.68' TW=673.56' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.76 fps)
└5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
4.00	0.00	0	670.75	0.00	0.00	0.00	0.00
6.00	0.00	0	670.75	0.00	0.00	0.00	0.00
8.00	0.00	0	670.76	0.00	0.00	0.00	0.00
10.00	0.04	46	674.07	0.04	0.00	0.04	0.00
12.00	0.07	59	675.00	0.07	0.00	0.07	0.00
14.00	0.07	62	675.18	0.08	0.00	0.08	0.00
16.00	0.10	73	676.00	0.09	0.00	0.09	0.00
18.00	0.14	103	676.60	0.13	0.03	0.10	0.00
20.00	0.16	120	676.63	0.16	0.05	0.10	0.00
22.00	0.17	132	676.65	0.17	0.07	0.10	0.00
24.00	0.19	141	676.66	0.19	0.08	0.10	0.00
26.00	0.20	149	676.68	0.20	0.09	0.10	0.00
28.00	0.21	155	676.68	0.21	0.10	0.10	0.00
30.00	0.22	160	676.69	0.21	0.11	0.10	0.00
32.00	0.22	167	676.70	0.22	0.12	0.10	0.00
34.00	0.23	173	676.71	0.23	0.12	0.10	0.00
36.00	0.23	177	676.71	0.23	0.13	0.10	0.00
38.00	0.28	209	676.74	0.27	0.17	0.11	0.00
40.00	0.32	247	676.78	0.32	0.22	0.11	0.00
42.00	0.28	220	676.75	0.29	0.18	0.11	0.00
44.00	0.27	200	676.73	0.26	0.16	0.11	0.00
46.00	0.32	238	676.77	0.31	0.21	0.11	0.00
48.00	0.39	301	676.82	0.38	0.27	0.11	0.00
50.00	0.50	400	676.89	0.48	0.37	0.11	0.00
52.00	0.54	459	676.92	0.54	0.43	0.11	0.00
54.00	0.54	467	676.93	0.54	0.43	0.11	0.00
56.00	0.64	566	676.98	0.62	0.51	0.11	0.00
58.00	0.76	759	677.07	0.72	0.61	0.11	0.00
60.00	**1.03**	1,305	677.31	0.93	0.81	0.11	0.00
62.00	**1.22**	**2,111**	**677.62**	**1.14**	**1.02**	**0.12**	0.00
64.00	1.18	**2,301**	**677.69**	**1.18**	**1.06**	**0.12**	0.00
66.00	1.05	2,107	677.62	1.13	1.02	0.10	0.00
68.00	0.84	1,435	677.36	0.94	0.85	0.09	0.00
70.00	0.78	1,001	677.18	0.79	0.71	0.08	0.00
72.00	0.78	987	677.18	0.78	0.71	0.07	0.00
74.00	0.09	96	676.57	0.09	0.02	0.07	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.80 cfs @ 102.38 hrs, Volume= 2.569 af, Depth> 8.81"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66" x 8

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.28	0.00	0.00
12.00	0.39	0.00	0.00
14.00	0.50	0.00	0.01
16.00	0.61	0.02	0.03
18.00	0.72	0.04	0.05
20.00	0.83	0.07	0.05
22.00	0.92	0.10	0.05
24.00	1.00	0.13	0.05
26.00	1.08	0.17	0.06
28.00	1.17	0.21	0.08
30.00	1.28	0.26	0.10
32.00	1.39	0.32	0.11
34.00	1.50	0.38	0.11
36.00	1.61	0.44	0.12
38.00	1.72	0.51	0.12
40.00	1.83	0.58	0.13
42.00	1.94	0.66	0.13
44.00	2.05	0.73	0.14
46.00	2.17	0.81	0.14
48.00	2.28	0.89	0.14
50.00	2.39	0.97	0.14
52.00	2.50	1.05	0.15
54.00	2.61	1.14	0.15
56.00	2.72	1.23	0.15
58.00	2.83	1.31	0.15
60.00	2.94	1.40	0.16
62.00	3.06	1.49	0.17
64.00	3.19	1.60	0.19
66.00	3.33	1.72	0.21
68.00	3.47	1.84	0.20
70.00	3.60	1.95	0.19
72.00	3.72	2.04	0.17
74.00	3.84	2.15	0.18
76.00	3.97	2.26	0.20
78.00	4.11	2.38	0.23
80.00	4.27	2.52	0.26
82.00	4.45	2.68	0.30
84.00	4.66	2.87	0.35
86.00	4.89	3.07	0.35
88.00	5.11	3.27	0.36
90.00	5.33	3.47	0.36
92.00	5.56	3.69	0.39
94.00	5.82	3.93	0.44
96.00	6.11	4.19	0.48
98.00	6.43	4.50	0.58
100.00	6.82	4.86	0.68
102.00	7.27	5.29	**0.79**
104.00	7.75	5.74	**0.79**
106.00	8.21	6.18	0.77
108.00	8.66	6.61	0.76
110.00	9.08	7.01	0.68
112.00	9.45	7.37	0.60
114.00	9.77	7.68	0.52
116.00	10.07	7.97	0.51
118.00	10.36	8.26	0.51
120.00	10.66	8.54	0.51
122.00	10.67	8.56	0.04
124.00	10.71	8.59	0.08
126.00	10.77	8.65	0.12
128.00	10.85	8.73	0.15
130.00	**10.94**	**8.82**	0.17

Summary for Subcatchment 7S: South Property


Runoff = 1.72 cfs @ 102.53 hrs, Volume= 5.501 af, Depth> 8.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66" x 8

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.28	0.00	0.00
12.00	0.39	0.00	0.00
14.00	0.50	0.00	0.03
16.00	0.61	0.02	0.07
18.00	0.72	0.04	0.10
20.00	0.83	0.07	0.11
22.00	0.92	0.10	0.12
24.00	1.00	0.13	0.11
26.00	1.08	0.17	0.14
28.00	1.17	0.21	0.17
30.00	1.28	0.26	0.21
32.00	1.39	0.32	0.23
34.00	1.50	0.38	0.24
36.00	1.61	0.44	0.25
38.00	1.72	0.51	0.26
40.00	1.83	0.58	0.27
42.00	1.94	0.66	0.28
44.00	2.05	0.73	0.29
46.00	2.17	0.81	0.30
48.00	2.28	0.89	0.30
50.00	2.39	0.97	0.31
52.00	2.50	1.05	0.32
54.00	2.61	1.14	0.32
56.00	2.72	1.23	0.33
58.00	2.83	1.31	0.33
60.00	2.94	1.40	0.34
62.00	3.06	1.49	0.37
64.00	3.19	1.60	0.41
66.00	3.33	1.72	0.46
68.00	3.47	1.84	0.44
70.00	3.60	1.95	0.40
72.00	3.72	2.04	0.37
74.00	3.84	2.15	0.39
76.00	3.97	2.26	0.44
78.00	4.11	2.38	0.48
80.00	4.27	2.52	0.56
82.00	4.45	2.68	0.65
84.00	4.66	2.87	0.73
86.00	4.89	3.07	0.76
88.00	5.11	3.27	0.76
90.00	5.33	3.47	0.77
92.00	5.56	3.69	0.84
94.00	5.82	3.93	0.93
96.00	6.11	4.19	1.02
98.00	6.43	4.50	1.22
100.00	6.82	4.86	1.45
102.00	7.27	5.29	**1.68**
104.00	7.75	5.74	**1.69**
106.00	8.21	6.18	1.66
108.00	8.66	6.61	1.62
110.00	9.08	7.01	1.47
112.00	9.45	7.37	1.29
114.00	9.77	7.68	1.12
116.00	10.07	7.97	1.08
118.00	10.36	8.26	1.09
120.00	10.66	8.54	1.09
122.00	10.67	8.56	0.07
124.00	10.71	8.59	0.16
126.00	10.77	8.65	0.26
128.00	10.85	8.73	0.31
130.00	**10.94**	**8.82**	0.35

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.83 cfs @ 102.53 hrs,	Volume=	6.421 af
Outflow	=	1.05 cfs @ 120.20 hrs,	Volume=	5.130 af, Atten= 43%, Lag= 1,060.1 min
Primary	=	1.05 cfs @ 120.20 hrs,	Volume=	5.130 af
Secondary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.01 hrs
Peak Elev= 674.08' @ 120.20 hrs Surf.Area= 31,284 sf Storage= 79,413 cf

Plug-Flow detention time= 576.4 min calculated for 5.130 af (80% of inflow)
Center-of-Mass det. time= 130.6 min (5,381.3 - 5,250.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.05 cfs @ 120.20 hrs HW=674.08' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.05 cfs @ 9.50 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
15.00	0.07	252	670.03	0.00	0.00	0.00	0.00
20.00	0.17	1,846	670.21	0.10	0.10	0.00	0.00
25.00	0.18	2,474	670.28	0.16	0.16	0.00	0.00
30.00	0.30	3,318	670.37	0.23	0.23	0.00	0.00
35.00	0.35	4,511	670.49	0.29	0.29	0.00	0.00
40.00	0.37	5,390	670.58	0.33	0.33	0.00	0.00
45.00	0.40	6,103	670.65	0.36	0.36	0.00	0.00
50.00	0.41	6,703	670.70	0.38	0.38	0.00	0.00
55.00	0.43	7,218	670.75	0.40	0.40	0.00	0.00
60.00	0.44	7,740	670.78	0.41	0.41	0.00	0.00
65.00	0.54	8,972	670.84	0.43	0.43	0.00	0.00
70.00	0.51	10,743	670.92	0.46	0.46	0.00	0.00
75.00	0.52	11,255	670.95	0.46	0.46	0.00	0.00
80.00	0.66	13,150	671.04	0.49	0.49	0.00	0.00
85.00	0.86	17,739	671.25	0.55	0.55	0.00	0.00
90.00	0.87	22,927	671.48	0.61	0.61	0.00	0.00
95.00	1.09	29,012	671.75	0.67	0.67	0.00	0.00
100.00	**1.56**	39,483	672.22	0.76	0.76	0.00	0.00
105.00	**1.79**	56,316	672.96	0.89	0.89	0.00	0.00
110.00	1.58	70,428	673.62	0.99	0.99	0.00	0.00
115.00	1.19	76,670	673.93	1.03	1.03	0.00	0.00
120.00	1.19	**79,337**	**674.07**	**1.05**	**1.05**	0.00	0.00
125.00	0.31	**65,628**	**673.39**	**0.95**	**0.95**	0.00	0.00
130.00	0.00	56,257	672.96	0.89	0.89	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.80 cfs @ 102.38 hrs,	Volume=	2.569 af
Outflow	=	0.79 cfs @ 103.59 hrs,	Volume=	2.566 af, Atten= 1%, Lag= 72.5 min
Primary	=	0.68 cfs @ 103.59 hrs,	Volume=	1.646 af
Secondary	=	0.11 cfs @ 103.59 hrs,	Volume=	0.920 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.01 hrs
Peak Elev= 677.15' @ 103.59 hrs Surf.Area= 2,246 sf Storage= 926 cf

Plug-Flow detention time= 14.9 min calculated for 2.566 af (100% of inflow)
Center-of-Mass det. time= 12.3 min (5,382.3 - 5,370.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908

Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


Primary OutFlow Max=0.68 cfs @ 103.59 hrs HW=677.15' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 0.68 cfs @ 2.96 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Secondary OutFlow Max=0.11 cfs @ 103.59 hrs HW=677.15' TW=672.75' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 9.12 fps)
└—**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System

Hydrograph




Pond 8P: North System

Stage-Discharge



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
15.00	0.02	41	673.71	0.02	0.00	0.02	0.00
20.00	0.05	51	674.38	0.05	0.00	0.05	0.00
25.00	0.06	52	674.46	0.06	0.00	0.06	0.00
30.00	0.10	76	676.15	0.10	0.00	0.10	0.00
35.00	0.11	92	676.56	0.11	0.01	0.10	0.00
40.00	0.13	100	676.59	0.13	0.02	0.10	0.00
45.00	0.14	105	676.60	0.14	0.03	0.10	0.00
50.00	0.14	111	676.62	0.14	0.04	0.10	0.00
55.00	0.15	116	676.62	0.15	0.05	0.10	0.00
60.00	0.16	121	676.63	0.16	0.05	0.10	0.00
65.00	0.20	152	676.68	0.20	0.10	0.10	0.00
70.00	0.19	143	676.67	0.19	0.08	0.10	0.00
75.00	0.19	147	676.67	0.19	0.09	0.10	0.00
80.00	0.26	198	676.73	0.26	0.15	0.11	0.00
85.00	0.35	274	676.80	0.35	0.24	0.11	0.00
90.00	0.36	280	676.80	0.36	0.25	0.11	0.00
95.00	0.46	369	676.87	0.45	0.35	0.11	0.00
100.00	**0.68**	**631**	**677.01**	**0.66**	**0.55**	**0.11**	0.00
105.00	**0.78**	**910**	**677.14**	**0.79**	**0.67**	**0.11**	0.00
110.00	0.68	728	677.06	0.70	0.59	0.11	0.00
115.00	0.51	434	676.91	0.51	0.40	0.10	0.00
120.00	0.51	438	676.91	0.51	0.41	0.10	0.00
125.00	0.10	76	676.21	0.10	0.00	0.10	0.00
130.00	0.00	127	676.64	0.16	0.06	0.10	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.48 cfs @ 204.42 hrs, Volume= 3.083 af, Depth>10.57"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65" x 8

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.09	0.00	0.00
15.00	0.20	0.00	0.00
20.00	0.34	0.00	0.00
25.00	0.49	0.00	0.01
30.00	0.66	0.03	0.02
35.00	0.82	0.07	0.04
40.00	0.98	0.12	0.04
45.00	1.12	0.18	0.04
50.00	1.23	0.24	0.04
55.00	1.36	0.30	0.05
60.00	1.52	0.39	0.07
65.00	1.68	0.49	0.07
70.00	1.84	0.59	0.08
75.00	2.01	0.70	0.08
80.00	2.17	0.82	0.08
85.00	2.34	0.94	0.09
90.00	2.50	1.06	0.09
95.00	2.67	1.18	0.09
100.00	2.83	1.31	0.09
105.00	3.00	1.44	0.09
110.00	3.16	1.58	0.10
115.00	3.33	1.71	0.10
120.00	3.49	1.85	0.10
125.00	3.67	2.00	0.11
130.00	3.87	2.17	0.13
135.00	4.08	2.36	0.13
140.00	4.28	2.53	0.11
145.00	4.45	2.68	0.11
150.00	4.63	2.84	0.12
155.00	4.83	3.02	0.14
160.00	5.07	3.23	0.16
165.00	5.34	3.49	0.19
170.00	5.67	3.78	0.21
175.00	6.00	4.09	0.22
180.00	6.33	4.39	0.22
185.00	6.68	4.72	0.25
190.00	7.08	5.10	0.28
195.00	7.53	5.53	0.34
200.00	8.10	6.07	**0.42**
205.00	8.77	6.72	**0.48**
210.00	9.47	7.39	0.47
215.00	10.15	8.04	0.46
220.00	10.78	8.66	0.41
225.00	11.32	9.18	0.34
230.00	11.77	9.63	0.30
235.00	12.21	10.06	0.30
240.00	12.65	10.49	0.30
245.00	12.67	10.51	0.03
250.00	**12.74**	**10.58**	0.06

Summary for Subcatchment 7S: South Property


Runoff = 1.04 cfs @ 204.56 hrs, Volume= 6.606 af, Depth>10.57"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.01 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65" x 8

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.09	0.00	0.00
15.00	0.20	0.00	0.00
20.00	0.34	0.00	0.00
25.00	0.49	0.00	0.02
30.00	0.66	0.03	0.05
35.00	0.82	0.07	0.07
40.00	0.98	0.12	0.09
45.00	1.12	0.18	0.08
50.00	1.23	0.24	0.09
55.00	1.36	0.30	0.11
60.00	1.52	0.39	0.14
65.00	1.68	0.49	0.15
70.00	1.84	0.59	0.16
75.00	2.01	0.70	0.17
80.00	2.17	0.82	0.18
85.00	2.34	0.94	0.18
90.00	2.50	1.06	0.19
95.00	2.67	1.18	0.19
100.00	2.83	1.31	0.20
105.00	3.00	1.44	0.20
110.00	3.16	1.58	0.20
115.00	3.33	1.71	0.21
120.00	3.49	1.85	0.21
125.00	3.67	2.00	0.24
130.00	3.87	2.17	0.27
135.00	4.08	2.36	0.27
140.00	4.28	2.53	0.25
145.00	4.45	2.68	0.22
150.00	4.63	2.84	0.26
155.00	4.83	3.02	0.29
160.00	5.07	3.23	0.35
165.00	5.34	3.49	0.41
170.00	5.67	3.78	0.46
175.00	6.00	4.09	0.46
180.00	6.33	4.39	0.46
185.00	6.68	4.72	0.53
190.00	7.08	5.10	0.60
195.00	7.53	5.53	0.72
200.00	8.10	6.07	**0.89**
205.00	8.77	6.72	**1.03**
210.00	9.47	7.39	1.00
215.00	10.15	8.04	0.97
220.00	10.78	8.66	0.87
225.00	11.32	9.18	0.74
230.00	11.77	9.63	0.65
235.00	12.21	10.06	0.65
240.00	12.65	10.49	0.65
245.00	12.67	10.51	0.06
250.00	**12.74**	**10.58**	0.13

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.14 cfs @ 204.56 hrs, Volume=	8.210 af
Outflow	=	0.85 cfs @ 224.86 hrs, Volume=	7.619 af, Atten= 26%, Lag= 1,218.2 min
Primary	=	0.85 cfs @ 224.86 hrs, Volume=	7.619 af
Secondary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.01 hrs
Peak Elev= 672.74' @ 224.86 hrs Surf.Area= 30,976 sf Storage= 51,223 cf

Plug-Flow detention time= 530.9 min calculated for 7.619 af (93% of inflow)
Center-of-Mass det. time= 216.5 min (10,419.5 - 10,203.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L Inside #15** Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.85 cfs @ 224.86 hrs HW=672.74' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.85 cfs @ 7.69 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
15.00	0.00	0	670.00	0.00	0.00	0.00	0.00
20.00	0.00	0	670.00	0.00	0.00	0.00	0.00
25.00	0.02	67	670.01	0.00	0.00	0.00	0.00
30.00	0.07	823	670.09	0.02	0.02	0.00	0.00
35.00	0.11	1,606	670.18	0.08	0.08	0.00	0.00
40.00	0.13	2,030	670.23	0.11	0.11	0.00	0.00
45.00	0.12	2,129	670.24	0.12	0.12	0.00	0.00
50.00	0.13	2,107	670.24	0.12	0.12	0.00	0.00
55.00	0.17	2,362	670.26	0.15	0.15	0.00	0.00
60.00	0.21	2,756	670.31	0.18	0.18	0.00	0.00
65.00	0.23	3,078	670.34	0.21	0.21	0.00	0.00
70.00	0.24	3,296	670.37	0.23	0.23	0.00	0.00
75.00	0.25	3,507	670.39	0.24	0.24	0.00	0.00
80.00	0.26	3,692	670.41	0.25	0.25	0.00	0.00
85.00	0.27	3,860	670.42	0.26	0.26	0.00	0.00
90.00	0.28	4,017	670.44	0.27	0.27	0.00	0.00
95.00	0.28	4,161	670.45	0.27	0.27	0.00	0.00
100.00	0.29	4,293	670.47	0.28	0.28	0.00	0.00
105.00	0.29	4,415	670.48	0.29	0.29	0.00	0.00
110.00	0.30	4,527	670.49	0.29	0.29	0.00	0.00
115.00	0.30	4,629	670.50	0.30	0.30	0.00	0.00
120.00	0.31	4,723	670.51	0.30	0.30	0.00	0.00
125.00	0.34	5,025	670.54	0.32	0.32	0.00	0.00
130.00	0.37	5,583	670.59	0.34	0.34	0.00	0.00
135.00	0.38	6,144	670.65	0.36	0.36	0.00	0.00
140.00	0.35	6,132	670.65	0.36	0.36	0.00	0.00
145.00	0.33	5,761	670.61	0.35	0.35	0.00	0.00
150.00	0.36	5,742	670.61	0.35	0.35	0.00	0.00
155.00	0.39	6,162	670.65	0.36	0.36	0.00	0.00
160.00	0.45	6,941	670.73	0.39	0.39	0.00	0.00
165.00	0.52	8,342	670.81	0.42	0.42	0.00	0.00
170.00	0.56	10,374	670.90	0.45	0.45	0.00	0.00
175.00	0.57	12,193	670.99	0.48	0.48	0.00	0.00
180.00	0.57	13,649	671.06	0.50	0.50	0.00	0.00
185.00	0.63	15,303	671.14	0.52	0.52	0.00	0.00
190.00	0.70	17,724	671.25	0.55	0.55	0.00	0.00
195.00	0.82	21,046	671.40	0.59	0.59	0.00	0.00
200.00	**0.99**	26,392	671.64	0.64	0.64	0.00	0.00
205.00	**1.14**	33,678	671.96	0.71	0.71	0.00	0.00
210.00	1.11	40,651	672.27	0.77	0.77	0.00	0.00
215.00	1.08	46,189	672.51	0.81	0.81	0.00	0.00
220.00	0.98	**50,036**	**672.68**	**0.84**	**0.84**	0.00	0.00
225.00	0.85	**51,221**	**672.74**	**0.85**	**0.85**	0.00	0.00
230.00	0.75	50,127	672.69	0.84	0.84	0.00	0.00
235.00	0.76	48,684	672.62	0.83	0.83	0.00	0.00
240.00	0.76	47,440	672.57	0.82	0.82	0.00	0.00
245.00	0.09	35,384	672.04	0.72	0.72	0.00	0.00
250.00	0.00	25,753	671.61	0.63	0.63	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.48 cfs @ 204.42 hrs, Volume=	3.083 af
Outflow	=	0.48 cfs @ 204.87 hrs, Volume=	3.082 af, Atten= 0%, Lag= 26.9 min
Primary	=	0.37 cfs @ 204.87 hrs, Volume=	1.477 af
Secondary	=	0.11 cfs @ 204.87 hrs, Volume=	1.605 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.01 hrs
Peak Elev= 676.89' @ 204.87 hrs Surf.Area= 1,620 sf Storage= 397 cf

Plug-Flow detention time= 13.5 min calculated for 3.082 af (100% of inflow)
Center-of-Mass det. time= 11.8 min (10,516.6 - 10,504.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.37 cfs @ 204.87 hrs HW=676.89' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 0.37 cfs @ 2.12 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 204.87 hrs HW=676.89' TW=671.95' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.78 fps)
└—**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
15.00	0.00	0	670.75	0.00	0.00	0.00	0.00
20.00	0.00	0	670.75	0.00	0.00	0.00	0.00
25.00	0.01	35	673.23	0.00	0.00	0.00	0.00
30.00	0.02	42	673.71	0.02	0.00	0.02	0.00
35.00	0.04	44	673.92	0.04	0.00	0.04	0.00
40.00	0.04	46	674.02	0.04	0.00	0.04	0.00
45.00	0.04	46	674.00	0.04	0.00	0.04	0.00
50.00	0.04	46	674.03	0.04	0.00	0.04	0.00
55.00	0.05	50	674.35	0.05	0.00	0.05	0.00
60.00	0.07	57	674.81	0.07	0.00	0.07	0.00
65.00	0.07	60	675.03	0.07	0.00	0.07	0.00
70.00	0.08	62	675.21	0.08	0.00	0.08	0.00
75.00	0.08	65	675.36	0.08	0.00	0.08	0.00
80.00	0.08	67	675.51	0.08	0.00	0.08	0.00
85.00	0.09	68	675.64	0.09	0.00	0.09	0.00
90.00	0.09	70	675.76	0.09	0.00	0.09	0.00
95.00	0.09	72	675.87	0.09	0.00	0.09	0.00
100.00	0.09	73	675.97	0.09	0.00	0.09	0.00
105.00	0.09	74	676.06	0.09	0.00	0.09	0.00
110.00	0.10	76	676.15	0.09	0.00	0.09	0.00
115.00	0.10	77	676.22	0.10	0.00	0.10	0.00
120.00	0.10	78	676.29	0.10	0.00	0.10	0.00
125.00	0.11	90	676.55	0.11	0.01	0.10	0.00
130.00	0.13	100	676.59	0.13	0.02	0.10	0.00
135.00	0.13	100	676.59	0.13	0.02	0.10	0.00
140.00	0.11	93	676.56	0.11	0.01	0.10	0.00
145.00	0.11	83	676.53	0.10	0.00	0.10	0.00
150.00	0.12	96	676.57	0.12	0.02	0.10	0.00
155.00	0.14	104	676.60	0.14	0.03	0.10	0.00
160.00	0.16	124	676.64	0.16	0.06	0.10	0.00
165.00	0.19	146	676.67	0.19	0.09	0.10	0.00
170.00	0.21	160	676.69	0.21	0.11	0.10	0.00
175.00	0.22	162	676.69	0.22	0.11	0.10	0.00
180.00	0.22	163	676.70	0.22	0.11	0.10	0.00
185.00	0.25	187	676.72	0.25	0.14	0.11	0.00
190.00	0.28	213	676.75	0.28	0.17	0.11	0.00
195.00	0.34	257	676.79	0.33	0.23	0.11	0.00
200.00	**0.42**	**329**	**676.84**	**0.41**	**0.30**	**0.11**	0.00
205.00	**0.48**	**401**	**676.89**	**0.48**	**0.37**	**0.11**	0.00
210.00	0.47	387	676.88	0.47	0.36	0.11	0.00
215.00	0.46	372	676.87	0.46	0.35	0.11	0.00
220.00	0.41	326	676.84	0.41	0.30	0.11	0.00
225.00	0.34	270	676.80	0.35	0.24	0.11	0.00
230.00	0.30	231	676.77	0.30	0.20	0.11	0.00
235.00	0.30	232	676.77	0.30	0.20	0.11	0.00
240.00	0.30	232	676.77	0.30	0.20	0.11	0.00
245.00	0.03	43	673.81	0.03	0.00	0.03	0.00
250.00	0.00	54	674.62	0.06	0.00	0.06	0.00

Stage-Discharge for Pond 8P: North System


Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	5.62	1.30	4.31	0.00
678.35	9.91	1.39	8.51	0.00
678.55	15.18	1.48	13.70	0.00
678.75	27.96	2.72	19.77	5.47
678.95	**52.16**	**5.83**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

APPENDIX B

BYPASS CALCULATIONS



Subcat Reach Pond Link

Routing Diagram for D_ByPass_Detention 11.00 Ac_Cultec_5-7-20_6AREV

Prepared by {enter your company name here}, Printed 5/13/2020

HydroCAD® 10.00-25 s/n 00783 © 2019 HydroCAD Software Solutions LLC

Summary for Subcatchment 1S: North Property


Runoff = 13.68 cfs @ 0.44 hrs, Volume= 0.674 af, Depth= 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.06	4.03	2.31	4.32
0.02	0.05	0.00	0.00	1.08	4.03	2.31	4.09
0.04	0.21	0.00	0.00	1.10	4.03	2.31	3.86
0.06	0.46	0.00	0.00	1.12	4.03	2.31	3.60
0.08	0.72	0.04	0.00	1.14	4.03	2.31	3.32
0.10	1.00	0.13	0.02	1.16	4.03	2.31	3.00
0.12	1.25	0.25	0.09	1.18	4.03	2.31	2.68
0.14	1.46	0.36	0.27	1.20	4.03	2.31	2.36
0.16	1.63	0.45	0.61	1.22	4.03	2.31	2.05
0.18	1.78	0.55	1.19	1.24	4.03	2.31	1.76
0.20	1.93	0.65	2.03	1.26	4.03	2.31	1.49
0.22	2.08	0.75	3.15	1.28	4.03	2.31	1.25
0.24	2.21	0.84	4.48	1.30	4.03	2.31	1.03
0.26	2.34	0.94	5.93	1.32	4.03	2.31	0.85
0.28	2.46	1.03	7.39	1.34	4.03	2.31	0.71
0.30	2.56	1.10	8.80	1.36	4.03	2.31	0.59
0.32	2.66	1.18	10.09	1.38	4.03	2.31	0.49
0.34	2.75	1.25	11.24	1.40	4.03	2.31	0.41
0.36	2.83	1.31	12.18	1.42	4.03	2.31	0.34
0.38	2.90	1.37	12.91	1.44	4.03	2.31	0.29
0.40	2.97	1.42	13.36	1.46	4.03	2.31	0.24
0.42	3.04	1.48	13.63	1.48	4.03	2.31	0.20
0.44	3.10	1.53	**13.68**	1.50	4.03	2.31	0.16
0.46	3.17	1.58	13.61	1.52	4.03	2.31	0.14
0.48	3.22	1.63	13.42	1.54	4.03	2.31	0.11
0.50	3.28	1.67	13.14	1.56	4.03	2.31	0.09
0.52	3.32	1.71	12.79	1.58	4.03	2.31	0.08
0.54	3.36	1.74	12.37	1.60	4.03	2.31	0.06
0.56	3.39	1.77	11.95	1.62	4.03	2.31	0.05
0.58	3.43	1.80	11.48	1.64	4.03	2.31	0.04
0.60	3.46	1.83	11.02	1.66	4.03	2.31	0.03
0.62	3.49	1.85	10.52	1.68	4.03	2.31	0.03
0.64	3.53	1.88	10.01	1.70	4.03	2.31	0.02
0.66	3.56	1.91	9.49	1.72	4.03	2.31	0.02
0.68	3.59	1.93	8.96	1.74	4.03	2.31	0.01
0.70	3.62	1.96	8.45	1.76	4.03	2.31	0.01
0.72	3.66	1.99	7.96	1.78	4.03	2.31	0.01
0.74	3.69	2.02	7.52	1.80	4.03	2.31	0.01
0.76	3.72	2.05	7.10	1.82	4.03	2.31	0.00
0.78	3.75	2.07	6.75	1.84	4.03	2.31	0.00
0.80	3.79	2.10	6.43	1.86	4.03	2.31	0.00
0.82	3.82	2.13	6.18	1.88	4.03	2.31	0.00
0.84	3.85	2.16	5.96	1.90	4.03	2.31	0.00
0.86	3.88	2.18	5.78	1.92	4.03	2.31	0.00
0.88	3.91	2.21	5.64	1.94	4.03	2.31	0.00
0.90	3.93	2.22	5.51	1.96	4.03	2.31	0.00
0.92	3.94	2.24	5.41	1.98	4.03	2.31	0.00
0.94	3.96	2.25	5.30	2.00	4.03	2.31	0.00
0.96	3.98	2.27	5.19				
0.98	4.00	2.29	5.05				
1.00	**4.03**	**2.31**	4.90				
1.02	4.03	2.31	4.72				
1.04	4.03	2.31	4.53				

Summary for Subcatchment 7S: South Property


Runoff = 25.34 cfs @ 0.56 hrs, Volume= 1.445 af, Depth> 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.02	0.05	0.00	0.00
0.04	0.21	0.00	0.00
0.06	0.46	0.00	0.00
0.08	0.72	0.04	0.00
0.10	1.00	0.13	0.00
0.12	1.25	0.25	0.06
0.14	1.46	0.36	0.17
0.16	1.63	0.45	0.38
0.18	1.78	0.55	0.74
0.20	1.93	0.65	1.31
0.22	2.08	0.75	2.07
0.24	2.21	0.84	3.07
0.26	2.34	0.94	4.40
0.28	2.46	1.03	5.97
0.30	2.56	1.10	7.74
0.32	2.66	1.18	9.70
0.34	2.75	1.25	11.73
0.36	2.83	1.31	13.77
0.38	2.90	1.37	15.78
0.40	2.97	1.42	17.70
0.42	3.04	1.48	19.42
0.44	3.10	1.53	20.99
0.46	3.17	1.58	22.35
0.48	3.22	1.63	23.45
0.50	3.28	1.67	24.32
0.52	3.32	1.71	24.85
0.54	3.36	1.74	25.18
0.56	3.39	1.77	**25.34**
0.58	3.43	1.80	25.19
0.60	3.46	1.83	24.93
0.62	3.49	1.85	24.55
0.64	3.53	1.88	24.04
0.66	3.56	1.91	23.47
0.68	3.59	1.93	22.78
0.70	3.62	1.96	22.04
0.72	3.66	1.99	21.28
0.74	3.69	2.02	20.45
0.76	3.72	2.05	19.65
0.78	3.75	2.07	18.86
0.80	3.79	2.10	18.06
0.82	3.82	2.13	17.33
0.84	3.85	2.16	16.63
0.86	3.88	2.18	15.97
0.88	3.91	2.21	15.37
0.90	3.93	2.22	14.80
0.92	3.94	2.24	14.30
0.94	3.96	2.25	13.84
0.96	3.98	2.27	13.40
0.98	4.00	2.29	13.03
1.00	**4.03**	**2.31**	12.64
1.02	4.03	2.31	12.29
1.04	4.03	2.31	11.94
1.06	4.03	2.31	11.56
1.08	4.03	2.31	11.19
1.10	4.03	2.31	10.78
1.12	4.03	2.31	10.34
1.14	4.03	2.31	9.91
1.16	4.03	2.31	9.42
1.18	4.03	2.31	8.92
1.20	4.03	2.31	8.40
1.22	4.03	2.31	7.82
1.24	4.03	2.31	7.25
1.26	4.03	2.31	6.66
1.28	4.03	2.31	6.08
1.30	4.03	2.31	5.53
1.32	4.03	2.31	4.99
1.34	4.03	2.31	4.48
1.36	4.03	2.31	4.00
1.38	4.03	2.31	3.56
1.40	4.03	2.31	3.16
1.42	4.03	2.31	2.79
1.44	4.03	2.31	2.44
1.46	4.03	2.31	2.14
1.48	4.03	2.31	1.89
1.50	4.03	2.31	1.67
1.52	4.03	2.31	1.47
1.54	4.03	2.31	1.29
1.56	4.03	2.31	1.14
1.58	4.03	2.31	1.01
1.60	4.03	2.31	0.89
1.62	4.03	2.31	0.78
1.64	4.03	2.31	0.68
1.66	4.03	2.31	0.60
1.68	4.03	2.31	0.53
1.70	4.03	2.31	0.46
1.72	4.03	2.31	0.41
1.74	4.03	2.31	0.36
1.76	4.03	2.31	0.31
1.78	4.03	2.31	0.28
1.80	4.03	2.31	0.24
1.82	4.03	2.31	0.21
1.84	4.03	2.31	0.18
1.86	4.03	2.31	0.16
1.88	4.03	2.31	0.14
1.90	4.03	2.31	0.12
1.92	4.03	2.31	0.11
1.94	4.03	2.31	0.09
1.96	4.03	2.31	0.08
1.98	4.03	2.31	0.07
2.00	4.03	2.31	0.06

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 3.23 cfs @ 0.69 hrs, Volume= 0.214 af, Depth> 2.14"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.02	0.05	0.00	0.00
0.04	0.21	0.00	0.00
0.06	0.46	0.00	0.00
0.08	0.72	0.02	0.00
0.10	1.00	0.10	0.00
0.12	1.25	0.20	0.00
0.14	1.46	0.29	0.00
0.16	1.63	0.38	0.01
0.18	1.78	0.47	0.03
0.20	1.93	0.56	0.06
0.22	2.08	0.65	0.09
0.24	2.21	0.74	0.15
0.26	2.34	0.83	0.21
0.28	2.46	0.91	0.30
0.30	2.56	0.99	0.40
0.32	2.66	1.06	0.53
0.34	2.75	1.12	0.68
0.36	2.83	1.18	0.85
0.38	2.90	1.24	1.04
0.40	2.97	1.29	1.23
0.42	3.04	1.34	1.44
0.44	3.10	1.39	1.64
0.46	3.17	1.44	1.85
0.48	3.22	1.49	2.04
0.50	3.28	1.53	2.24
0.52	3.32	1.57	2.42
0.54	3.36	1.60	2.59
0.56	3.39	1.62	2.73
0.58	3.43	1.65	2.86
0.60	3.46	1.68	2.97
0.62	3.49	1.70	3.07
0.64	3.53	1.73	3.14
0.66	3.56	1.76	3.19
0.68	3.59	1.78	**3.22**
0.70	3.62	1.81	**3.23**
0.72	3.66	1.84	3.22
0.74	3.69	1.86	3.19
0.76	3.72	1.89	3.16
0.78	3.75	1.92	3.10
0.80	3.79	1.94	3.04
0.82	3.82	1.97	2.97
0.84	3.85	2.00	2.90
0.86	3.88	2.02	2.83
0.88	3.91	2.04	2.75
0.90	3.93	2.06	2.68
0.92	3.94	2.07	2.60
0.94	3.96	2.09	2.53
0.96	3.98	2.10	2.46
0.98	4.00	2.12	2.39
1.00	**4.03**	**2.15**	2.32
1.02	4.03	2.15	2.26
1.04	4.03	2.15	2.20
1.06	4.03	2.15	2.14
1.08	4.03	2.15	2.07
1.10	4.03	2.15	2.02
1.12	4.03	2.15	1.96
1.14	4.03	2.15	1.90
1.16	4.03	2.15	1.83
1.18	4.03	2.15	1.77
1.20	4.03	2.15	1.71
1.22	4.03	2.15	1.64
1.24	4.03	2.15	1.57
1.26	4.03	2.15	1.50
1.28	4.03	2.15	1.43
1.30	4.03	2.15	1.35
1.32	4.03	2.15	1.28
1.34	4.03	2.15	1.20
1.36	4.03	2.15	1.12
1.38	4.03	2.15	1.05
1.40	4.03	2.15	0.98
1.42	4.03	2.15	0.91
1.44	4.03	2.15	0.84
1.46	4.03	2.15	0.77
1.48	4.03	2.15	0.71
1.50	4.03	2.15	0.65
1.52	4.03	2.15	0.60
1.54	4.03	2.15	0.55
1.56	4.03	2.15	0.50
1.58	4.03	2.15	0.45
1.60	4.03	2.15	0.41
1.62	4.03	2.15	0.38
1.64	4.03	2.15	0.34
1.66	4.03	2.15	0.31
1.68	4.03	2.15	0.29
1.70	4.03	2.15	0.26
1.72	4.03	2.15	0.24
1.74	4.03	2.15	0.22
1.76	4.03	2.15	0.20
1.78	4.03	2.15	0.18
1.80	4.03	2.15	0.17
1.82	4.03	2.15	0.15
1.84	4.03	2.15	0.14
1.86	4.03	2.15	0.13
1.88	4.03	2.15	0.12
1.90	4.03	2.15	0.11
1.92	4.03	2.15	0.10
1.94	4.03	2.15	0.09
1.96	4.03	2.15	0.08
1.98	4.03	2.15	0.07
2.00	4.03	2.15	0.06

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 2.31 cfs @ 0.34 hrs, Volume= 0.098 af, Depth= 2.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.02	0.05	0.00	0.00
0.04	0.21	0.00	0.00
0.06	0.46	0.00	0.00
0.08	0.72	0.02	0.00
0.10	1.00	0.10	0.01
0.12	1.25	0.20	0.06
0.14	1.46	0.29	0.19
0.16	1.63	0.38	0.44
0.18	1.78	0.47	0.78
0.20	1.93	0.56	1.15
0.22	2.08	0.65	1.50
0.24	2.21	0.74	1.78
0.26	2.34	0.83	1.99
0.28	2.46	0.91	2.13
0.30	2.56	0.99	2.23
0.32	2.66	1.06	2.29
0.34	2.75	1.12	**2.31**
0.36	2.83	1.18	2.29
0.38	2.90	1.24	2.23
0.40	2.97	1.29	2.16
0.42	3.04	1.34	2.06
0.44	3.10	1.39	1.96
0.46	3.17	1.44	1.86
0.48	3.22	1.49	1.76
0.50	3.28	1.53	1.67
0.52	3.32	1.57	1.59
0.54	3.36	1.60	1.52
0.56	3.39	1.62	1.44
0.58	3.43	1.65	1.36
0.60	3.46	1.68	1.26
0.62	3.49	1.70	1.16
0.64	3.53	1.73	1.07
0.66	3.56	1.76	0.98
0.68	3.59	1.78	0.91
0.70	3.62	1.81	0.86
0.72	3.66	1.84	0.83
0.74	3.69	1.86	0.80
0.76	3.72	1.89	0.78
0.78	3.75	1.92	0.77
0.80	3.79	1.94	0.76
0.82	3.82	1.97	0.76
0.84	3.85	2.00	0.75
0.86	3.88	2.02	0.75
0.88	3.91	2.04	0.75
0.90	3.93	2.06	0.75
0.92	3.94	2.07	0.74
0.94	3.96	2.09	0.71
0.96	3.98	2.10	0.68
0.98	4.00	2.12	0.63
1.00	**4.03**	**2.15**	0.58
1.02	4.03	2.15	0.54
1.04	4.03	2.15	0.51
1.06	4.03	2.15	0.49
1.08	4.03	2.15	0.44
1.10	4.03	2.15	0.38
1.12	4.03	2.15	0.31
1.14	4.03	2.15	0.24
1.16	4.03	2.15	0.17
1.18	4.03	2.15	0.12
1.20	4.03	2.15	0.09
1.22	4.03	2.15	0.07
1.24	4.03	2.15	0.05
1.26	4.03	2.15	0.03
1.28	4.03	2.15	0.02
1.30	4.03	2.15	0.02
1.32	4.03	2.15	0.01
1.34	4.03	2.15	0.01
1.36	4.03	2.15	0.01
1.38	4.03	2.15	0.00
1.40	4.03	2.15	0.00
1.42	4.03	2.15	0.00
1.44	4.03	2.15	0.00
1.46	4.03	2.15	0.00
1.48	4.03	2.15	0.00
1.50	4.03	2.15	0.00
1.52	4.03	2.15	0.00
1.54	4.03	2.15	0.00
1.56	4.03	2.15	0.00
1.58	4.03	2.15	0.00
1.60	4.03	2.15	0.00
1.62	4.03	2.15	0.00
1.64	4.03	2.15	0.00
1.66	4.03	2.15	0.00
1.68	4.03	2.15	0.00
1.70	4.03	2.15	0.00
1.72	4.03	2.15	0.00
1.74	4.03	2.15	0.00
1.76	4.03	2.15	0.00
1.78	4.03	2.15	0.00
1.80	4.03	2.15	0.00
1.82	4.03	2.15	0.00
1.84	4.03	2.15	0.00
1.86	4.03	2.15	0.00
1.88	4.03	2.15	0.00
1.90	4.03	2.15	0.00
1.92	4.03	2.15	0.00
1.94	4.03	2.15	0.00
1.96	4.03	2.15	0.00
1.98	4.03	2.15	0.00
2.00	4.03	2.15	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	35.84 cfs @	0.55 hrs,	Volume=	2.038 af
Outflow	=	1.08 cfs @	1.59 hrs,	Volume=	0.129 af, Atten= 97%, Lag= 62.7 min
Primary	=	1.08 cfs @	1.59 hrs,	Volume=	0.129 af
Secondary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 674.34' @ 1.59 hrs Surf.Area= 31,344 sf Storage= 84,157 cf

Plug-Flow detention time= 57.4 min calculated for 0.128 af (6% of inflow)
Center-of-Mass det. time= 30.8 min (75.5 - 44.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.08 cfs @ 1.59 hrs HW=674.34' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.08 cfs @ 9.81 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.05	0.00	0	670.00	0.00	0.00	0.00	0.00
0.10	0.01	0	670.00	0.00	0.00	0.00	0.00
0.15	0.57	27	670.00	0.00	0.00	0.00	0.00
0.20	2.56	253	670.03	0.00	0.00	0.00	0.00
0.25	5.73	919	670.10	0.03	0.03	0.00	0.00
0.30	10.09	2,237	670.25	0.13	0.13	0.00	0.00
0.35	17.86	4,432	670.48	0.29	0.29	0.00	0.00
0.40	27.74	8,396	670.81	0.42	0.42	0.00	0.00
0.45	32.69	13,701	671.06	0.50	0.50	0.00	0.00
0.50	35.25	19,699	671.34	0.57	0.57	0.00	0.00
0.55	**35.83**	26,000	671.62	0.64	0.64	0.00	0.00
0.60	34.87	32,280	671.90	0.70	0.70	0.00	0.00
0.65	32.92	38,299	672.17	0.75	0.75	0.00	0.00
0.70	30.40	43,912	672.41	0.79	0.79	0.00	0.00
0.75	27.65	49,042	672.64	0.83	0.83	0.00	0.00
0.80	25.01	53,675	672.84	0.87	0.87	0.00	0.00
0.85	22.73	57,850	673.03	0.90	0.90	0.00	0.00
0.90	20.87	61,640	673.21	0.92	0.92	0.00	0.00
0.95	19.35	65,117	673.37	0.95	0.95	0.00	0.00
1.00	17.99	68,330	673.52	0.97	0.97	0.00	0.00
1.05	16.68	71,298	673.66	0.99	0.99	0.00	0.00
1.10	15.19	74,018	673.80	1.01	1.01	0.00	0.00
1.15	13.45	76,446	673.92	1.03	1.03	0.00	0.00
1.20	11.52	78,545	674.03	1.04	1.04	0.00	0.00
1.25	9.45	80,280	674.12	1.06	1.06	0.00	0.00
1.30	7.43	81,643	674.20	1.06	1.06	0.00	0.00
1.35	5.58	82,652	674.25	1.07	1.07	0.00	0.00
1.40	4.04	83,348	674.29	1.08	1.08	0.00	0.00
1.45	2.82	83,788	674.32	1.08	1.08	0.00	0.00
1.50	1.93	84,032	674.33	1.08	1.08	0.00	0.00
1.55	1.33	**84,137**	**674.34**	**1.08**	**1.08**	0.00	0.00
1.60	0.99	**84,156**	**674.34**	**1.08**	**1.08**	0.00	0.00
1.65	0.75	84,121	674.34	1.08	1.08	0.00	0.00
1.70	0.57	84,048	674.33	1.08	1.08	0.00	0.00
1.75	0.44	83,946	674.33	1.08	1.08	0.00	0.00
1.80	0.35	83,823	674.32	1.08	1.08	0.00	0.00
1.85	0.28	83,686	674.31	1.08	1.08	0.00	0.00
1.90	0.23	83,538	674.30	1.08	1.08	0.00	0.00
1.95	0.19	83,382	674.30	1.08	1.08	0.00	0.00
2.00	0.00	83,220	674.29	1.08	1.08	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	15.47 cfs @	0.47 hrs, Volume=	0.888 af
Outflow	=	15.43 cfs @	0.50 hrs, Volume=	0.860 af, Atten= 0%, Lag= 1.6 min
Primary	=	6.18 cfs @	0.50 hrs, Volume=	0.364 af
Secondary	=	9.26 cfs @	0.50 hrs, Volume=	0.495 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 678.38' @ 0.50 hrs Surf.Area= 3,554 sf Storage= 4,516 cf

Plug-Flow detention time= 7.9 min calculated for 0.856 af (96% of inflow)
Center-of-Mass det. time= 6.5 min (48.3 - 41.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=6.17 cfs @ 0.50 hrs HW=678.38' (Free Discharge)
- **1=Orifice/Grate** (Orifice Controls 1.41 cfs @ 6.11 fps)
- **2=Sharp-Crested Rectangular Weir** (Weir Controls 4.77 cfs @ 2.11 fps)


Secondary OutFlow Max=9.25 cfs @ 0.50 hrs HW=678.38' TW=671.33' (Dynamic Tailwater)
- **4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.57 fps)
- **5=Sharp-Crested Rectangular Weir** (Weir Controls 9.12 cfs @ 2.67 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
- **3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.05	0.00	0	670.75	0.00	0.00	0.00	0.00
0.10	0.02	0	670.78	0.00	0.00	0.00	0.00
0.15	0.43	22	672.29	0.00	0.00	0.00	0.00
0.20	2.08	181	676.71	0.24	0.13	0.10	0.00
0.25	5.37	700	677.04	0.69	0.58	0.11	0.00
0.30	9.20	1,793	677.50	1.07	0.95	0.12	0.00
0.35	12.50	3,433	678.06	4.38	1.56	2.81	0.00
0.40	14.59	4,311	678.32	12.96	5.08	7.88	0.00
0.45	**15.42**	4,486	678.37	15.05	6.01	9.05	0.00
0.50	**15.37**	**4,516**	**678.38**	**15.43**	**6.17**	**9.25**	0.00
0.55	14.82	4,489	678.37	15.10	6.03	9.07	0.00
0.60	13.99	4,430	678.36	14.38	5.71	8.67	0.00
0.65	12.91	4,350	678.33	13.43	5.29	8.14	0.00
0.70	11.68	4,252	678.31	12.27	4.78	7.49	0.00
0.75	10.48	4,144	678.27	11.06	4.25	6.81	0.00
0.80	9.47	4,044	678.25	9.98	3.79	6.19	0.00
0.85	8.73	3,962	678.22	9.12	3.42	5.69	0.00
0.90	8.19	3,900	678.20	8.48	3.16	5.33	0.00
0.95	7.74	3,851	678.19	8.00	2.95	5.04	0.00
1.00	7.23	3,802	678.17	7.53	2.76	4.76	0.00
1.05	6.59	3,743	678.16	6.96	2.53	4.43	0.00
1.10	5.87	3,671	678.13	6.31	2.28	4.03	0.00
1.15	5.02	3,586	678.11	5.57	1.99	3.58	0.00
1.20	4.06	3,479	678.08	4.71	1.68	3.03	0.00
1.25	3.16	3,358	678.04	3.85	1.40	2.45	0.00
1.30	2.38	3,231	678.00	3.12	1.23	1.89	0.00
1.35	1.81	3,097	677.96	2.55	1.21	1.34	0.00
1.40	1.39	2,968	677.91	2.07	1.19	0.88	0.00
1.45	1.06	2,849	677.88	1.69	1.17	0.52	0.00
1.50	0.82	2,739	677.84	1.41	1.15	0.27	0.00
1.55	0.62	2,631	677.80	1.24	1.13	0.11	0.00
1.60	0.48	2,511	677.76	1.21	1.10	0.11	0.00
1.65	0.37	2,372	677.71	1.19	1.08	0.11	0.00
1.70	0.28	2,220	677.66	1.15	1.05	0.11	0.00
1.75	0.22	2,061	677.60	1.12	1.01	0.11	0.00
1.80	0.17	1,899	677.54	1.08	0.98	0.11	0.00
1.85	0.14	1,736	677.48	1.04	0.94	0.11	0.00
1.90	0.11	1,574	677.42	1.00	0.89	0.10	0.00
1.95	0.08	1,415	677.36	0.95	0.85	0.10	0.00
2.00	0.00	1,260	677.29	0.90	0.80	0.10	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 11.35 cfs @ 0.60 hrs, Volume= 0.918 af, Depth= 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.10	0.00	0.00
0.10	0.40	0.00	0.00
0.15	0.81	0.07	0.01
0.20	1.23	0.23	0.22
0.25	1.61	0.45	1.13
0.30	1.91	0.63	3.16
0.35	2.15	0.80	5.88
0.40	2.38	0.97	8.39
0.45	2.60	1.14	10.07
0.50	2.81	1.30	10.90
0.55	3.00	1.45	11.25
0.60	3.16	1.58	**11.35**
0.65	3.31	1.70	11.22
0.70	3.44	1.81	10.86
0.75	3.56	1.91	10.28
0.80	3.66	2.00	9.59
0.85	3.77	2.08	8.89
0.90	3.87	2.17	8.19
0.95	3.96	2.25	7.57
1.00	4.04	2.32	7.06
1.05	4.11	2.38	6.62
1.10	4.17	2.43	6.19
1.15	4.22	2.48	5.69
1.20	4.27	2.52	5.12
1.25	4.32	2.56	4.56
1.30	4.37	2.61	4.08
1.35	4.42	2.65	3.74
1.40	4.47	2.70	3.51
1.45	4.52	2.74	3.37
1.50	4.57	2.79	3.28
1.55	4.62	2.83	3.23
1.60	4.67	2.88	3.20
1.65	4.72	2.92	3.18
1.70	4.77	2.97	3.17
1.75	4.81	3.01	3.17
1.80	4.84	3.03	3.15
1.85	4.87	3.06	3.07
1.90	4.89	3.08	2.87
1.95	4.93	3.11	2.58
2.00	**4.97**	**3.15**	2.30
2.05	4.97	3.15	2.13
2.10	4.97	3.15	2.02
2.15	4.97	3.15	1.80
2.20	4.97	3.15	1.41
2.25	4.97	3.15	0.98
2.30	4.97	3.15	0.63
2.35	4.97	3.15	0.39
2.40	4.97	3.15	0.25
2.45	4.97	3.15	0.16
2.50	4.97	3.15	0.10
2.55	4.97	3.15	0.06
2.60	4.97	3.15	0.04
2.65	4.97	3.15	0.02
2.70	4.97	3.15	0.01
2.75	4.97	3.15	0.01
2.80	4.97	3.15	0.00
2.85	4.97	3.15	0.00
2.90	4.97	3.15	0.00
2.95	4.97	3.15	0.00
3.00	4.97	3.15	0.00

Summary for Subcatchment 7S: South Property


Runoff = 22.41 cfs @ 0.72 hrs, Volume= 1.967 af, Depth> 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.10	0.00	0.00
0.10	0.40	0.00	0.00
0.15	0.81	0.07	0.00
0.20	1.23	0.23	0.13
0.25	1.61	0.45	0.71
0.30	1.91	0.63	2.21
0.35	2.15	0.80	4.90
0.40	2.38	0.97	8.57
0.45	2.60	1.14	12.52
0.50	2.81	1.30	16.07
0.55	3.00	1.45	18.87
0.60	3.16	1.58	20.80
0.65	3.31	1.70	21.90
0.70	3.44	1.81	**22.35**
0.75	3.56	1.91	**22.30**
0.80	3.66	2.00	21.82
0.85	3.77	2.08	21.01
0.90	3.87	2.17	19.96
0.95	3.96	2.25	18.81
1.00	4.04	2.32	17.65
1.05	4.11	2.38	16.56
1.10	4.17	2.43	15.55
1.15	4.22	2.48	14.55
1.20	4.27	2.52	13.52
1.25	4.32	2.56	12.44
1.30	4.37	2.61	11.36
1.35	4.42	2.65	10.34
1.40	4.47	2.70	9.45
1.45	4.52	2.74	8.74
1.50	4.57	2.79	8.19
1.55	4.62	2.83	7.79
1.60	4.67	2.88	7.50
1.65	4.72	2.92	7.29
1.70	4.77	2.97	7.14
1.75	4.81	3.01	7.04
1.80	4.84	3.03	6.95
1.85	4.87	3.06	6.85
1.90	4.89	3.08	6.67
1.95	4.93	3.11	6.37
2.00	**4.97**	**3.15**	5.97
2.05	4.97	3.15	5.54
2.10	4.97	3.15	5.14
2.15	4.97	3.15	4.73
2.20	4.97	3.15	4.25
2.25	4.97	3.15	3.65
2.30	4.97	3.15	2.99
2.35	4.97	3.15	2.34
2.40	4.97	3.15	1.76
2.45	4.97	3.15	1.28
2.50	4.97	3.15	0.93
2.55	4.97	3.15	0.68
2.60	4.97	3.15	0.50
2.65	4.97	3.15	0.37
2.70	4.97	3.15	0.27
2.75	4.97	3.15	0.20
2.80	4.97	3.15	0.14
2.85	4.97	3.15	0.10
2.90	4.97	3.15	0.07
2.95	4.97	3.15	0.05
3.00	4.97	3.15	0.04

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 3.02 cfs @ 0.87 hrs, Volume= 0.295 af, Depth> 2.95"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.10	0.00	0.00
0.10	0.40	0.00	0.00
0.15	0.81	0.04	0.00
0.20	1.23	0.19	0.01
0.25	1.61	0.37	0.03
0.30	1.91	0.55	0.10
0.35	2.15	0.70	0.25
0.40	2.38	0.86	0.48
0.45	2.60	1.02	0.82
0.50	2.81	1.17	1.21
0.55	3.00	1.31	1.62
0.60	3.16	1.44	2.01
0.65	3.31	1.55	2.36
0.70	3.44	1.66	2.64
0.75	3.56	1.76	2.85
0.80	3.66	1.84	2.97
0.85	3.77	1.93	**3.02**
0.90	3.87	2.01	**3.02**
0.95	3.96	2.09	2.96
1.00	4.04	2.16	2.88
1.05	4.11	2.21	2.78
1.10	4.17	2.26	2.65
1.15	4.22	2.31	2.53
1.20	4.27	2.35	2.40
1.25	4.32	2.39	2.26
1.30	4.37	2.43	2.11
1.35	4.42	2.48	1.97
1.40	4.47	2.52	1.83
1.45	4.52	2.56	1.70
1.50	4.57	2.61	1.58
1.55	4.62	2.65	1.47
1.60	4.67	2.69	1.39
1.65	4.72	2.74	1.32
1.70	4.77	2.78	1.26
1.75	4.81	2.82	1.22
1.80	4.84	2.85	1.19
1.85	4.87	2.87	1.16
1.90	4.89	2.89	1.13
1.95	4.93	2.92	1.09
2.00	**4.97**	**2.96**	1.05
2.05	4.97	2.96	1.00
2.10	4.97	2.96	0.95
2.15	4.97	2.96	0.89
2.20	4.97	2.96	0.83
2.25	4.97	2.96	0.76
2.30	4.97	2.96	0.68
2.35	4.97	2.96	0.59
2.40	4.97	2.96	0.50
2.45	4.97	2.96	0.42
2.50	4.97	2.96	0.35
2.55	4.97	2.96	0.28
2.60	4.97	2.96	0.22
2.65	4.97	2.96	0.17
2.70	4.97	2.96	0.14
2.75	4.97	2.96	0.11
2.80	4.97	2.96	0.09
2.85	4.97	2.96	0.07
2.90	4.97	2.96	0.05
2.95	4.97	2.96	0.04
3.00	4.97	2.96	0.03

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 1.76 cfs @ 0.42 hrs, Volume= 0.136 af, Depth= 2.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.10	0.00	0.00
0.10	0.40	0.00	0.00
0.15	0.81	0.04	0.01
0.20	1.23	0.19	0.14
0.25	1.61	0.37	0.62
0.30	1.91	0.55	1.26
0.35	2.15	0.70	1.66
0.40	2.38	0.86	**1.75**
0.45	2.60	1.02	**1.75**
0.50	2.81	1.17	1.75
0.55	3.00	1.31	1.73
0.60	3.16	1.44	1.68
0.65	3.31	1.55	1.58
0.70	3.44	1.66	1.45
0.75	3.56	1.76	1.32
0.80	3.66	1.84	1.21
0.85	3.77	1.93	1.11
0.90	3.87	2.01	1.02
0.95	3.96	2.09	0.97
1.00	4.04	2.16	0.93
1.05	4.11	2.21	0.87
1.10	4.17	2.26	0.78
1.15	4.22	2.31	0.68
1.20	4.27	2.35	0.58
1.25	4.32	2.39	0.52
1.30	4.37	2.43	0.50
1.35	4.42	2.48	0.49
1.40	4.47	2.52	0.48
1.45	4.52	2.56	0.48
1.50	4.57	2.61	0.48
1.55	4.62	2.65	0.48
1.60	4.67	2.69	0.48
1.65	4.72	2.74	0.48
1.70	4.77	2.78	0.48
1.75	4.81	2.82	0.48
1.80	4.84	2.85	0.47
1.85	4.87	2.87	0.41
1.90	4.89	2.89	0.34
1.95	4.93	2.92	0.29
2.00	**4.97**	**2.96**	0.28
2.05	4.97	2.96	0.31
2.10	4.97	2.96	0.26
2.15	4.97	2.96	0.14
2.20	4.97	2.96	0.06
2.25	4.97	2.96	0.03
2.30	4.97	2.96	0.01
2.35	4.97	2.96	0.01
2.40	4.97	2.96	0.00
2.45	4.97	2.96	0.00
2.50	4.97	2.96	0.00
2.55	4.97	2.96	0.00
2.60	4.97	2.96	0.00
2.65	4.97	2.96	0.00
2.70	4.97	2.96	0.00
2.75	4.97	2.96	0.00
2.80	4.97	2.96	0.00
2.85	4.97	2.96	0.00
2.90	4.97	2.96	0.00
2.95	4.97	2.96	0.00
3.00	4.97	2.96	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	32.02 cfs @	0.71 hrs,	Volume=	2.801 af
Outflow	=	1.34 cfs @	2.46 hrs,	Volume=	0.236 af, Atten= 96%, Lag= 105.0 min
Primary	=	1.34 cfs @	2.46 hrs,	Volume=	0.236 af
Secondary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 676.50' @ 2.46 hrs Surf.Area= 46,874 sf Storage= 113,551 cf

Plug-Flow detention time= 86.7 min calculated for 0.235 af (8% of inflow)
Center-of-Mass det. time= 46.2 min (112.5 - 66.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.34 cfs @ 2.46 hrs HW=676.50' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.34 cfs @ 12.10 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.27	13	670.00	0.00	0.00	0.00	0.00
0.30	3.57	522	670.06	0.01	0.01	0.00	0.00
0.40	10.45	2,823	670.32	0.19	0.19	0.00	0.00
0.50	24.62	8,787	670.83	0.43	0.43	0.00	0.00
0.60	30.46	18,580	671.29	0.56	0.56	0.00	0.00
0.70	**32.01**	29,682	671.78	0.67	0.67	0.00	0.00
0.80	**30.85**	40,827	672.28	0.77	0.77	0.00	0.00
0.90	28.07	51,225	672.74	0.85	0.85	0.00	0.00
1.00	24.92	60,501	673.15	0.92	0.92	0.00	0.00
1.10	22.03	68,659	673.54	0.97	0.97	0.00	0.00
1.20	19.09	75,762	673.89	1.02	1.02	0.00	0.00
1.30	16.04	81,756	674.20	1.07	1.07	0.00	0.00
1.40	13.52	86,704	674.50	1.10	1.10	0.00	0.00
1.50	11.89	90,876	674.81	1.14	1.14	0.00	0.00
1.60	10.98	94,575	675.11	1.18	1.18	0.00	0.00
1.70	10.50	98,013	675.40	1.21	1.21	0.00	0.00
1.80	10.22	101,306	675.68	1.25	1.25	0.00	0.00
1.90	9.66	104,461	675.90	1.27	1.27	0.00	0.00
2.00	8.53	107,307	676.09	1.29	1.29	0.00	0.00
2.10	7.31	109,713	676.24	1.31	1.31	0.00	0.00
2.20	5.80	111,640	676.37	1.32	1.32	0.00	0.00
2.30	3.76	112,926	676.46	1.33	1.33	0.00	0.00
2.40	1.95	**113,487**	**676.50**	**1.34**	**1.34**	0.00	0.00
2.50	1.00	**113,525**	**676.50**	**1.34**	**1.34**	0.00	0.00
2.60	0.57	113,326	676.49	1.33	1.33	0.00	0.00
2.70	0.33	113,008	676.47	1.33	1.33	0.00	0.00
2.80	0.20	112,624	676.44	1.33	1.33	0.00	0.00
2.90	0.13	112,205	676.41	1.33	1.33	0.00	0.00
3.00	0.00	111,767	676.38	1.32	1.32	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	13.59 cfs @	0.67 hrs, Volume=	1.213 af
Outflow	=	13.57 cfs @	0.68 hrs, Volume=	1.191 af, Atten= 0%, Lag= 1.1 min
Primary	=	5.35 cfs @	0.68 hrs, Volume=	0.492 af
Secondary	=	8.22 cfs @	0.68 hrs, Volume=	0.699 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 678.34' @ 0.68 hrs Surf.Area= 3,511 sf Storage= 4,362 cf

Plug-Flow detention time= 9.3 min calculated for 1.191 af (98% of inflow)
Center-of-Mass det. time= 7.7 min (71.2 - 63.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=5.35 cfs @ 0.68 hrs HW=678.34' (Free Discharge)
- **1=Orifice/Grate** (Orifice Controls 1.39 cfs @ 6.03 fps)
- **2=Sharp-Crested Rectangular Weir** (Weir Controls 3.96 cfs @ 1.98 fps)


Secondary OutFlow Max=8.22 cfs @ 0.68 hrs HW=678.34' TW=671.71' (Dynamic Tailwater)
- **4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.52 fps)
- **5=Sharp-Crested Rectangular Weir** (Weir Controls 8.09 cfs @ 2.55 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
- **3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.22	12	671.57	0.00	0.00	0.00	0.00
0.30	3.26	397	676.89	0.48	0.37	0.11	0.00
0.40	8.87	2,204	677.65	1.16	1.04	0.12	0.00
0.50	12.11	4,143	678.27	11.05	4.25	6.80	0.00
0.60	**13.36**	**4,325**	**678.33**	**13.13**	**5.16**	**7.98**	0.00
0.70	**13.50**	**4,361**	**678.34**	**13.56**	**5.34**	**8.21**	0.00
0.80	12.56	4,301	678.32	12.84	5.03	7.81	0.00
0.90	11.21	4,188	678.29	11.55	4.46	7.09	0.00
1.00	9.94	4,069	678.25	10.24	3.90	6.34	0.00
1.10	8.85	3,965	678.22	9.14	3.43	5.71	0.00
1.20	7.52	3,843	678.19	7.91	2.92	4.99	0.00
1.30	6.20	3,700	678.14	6.57	2.38	4.19	0.00
1.40	5.34	3,588	678.11	5.58	2.00	3.58	0.00
1.50	4.86	3,517	678.09	5.00	1.79	3.22	0.00
1.60	4.58	3,475	678.07	4.67	1.67	3.00	0.00
1.70	4.43	3,451	678.07	4.48	1.61	2.87	0.00
1.80	4.34	3,437	678.06	4.38	1.57	2.80	0.00
1.90	4.00	3,408	678.05	4.16	1.50	2.65	0.00
2.00	3.35	3,326	678.03	3.61	1.34	2.27	0.00
2.10	2.97	3,246	678.00	3.15	1.24	1.92	0.00
2.20	2.24	3,143	677.97	2.70	1.22	1.48	0.00
2.30	1.30	2,940	677.91	1.93	1.18	0.75	0.00
2.40	0.76	2,721	677.83	1.33	1.14	0.19	0.00
2.50	0.44	2,498	677.76	1.17	1.10	0.07	0.00
2.60	0.26	2,213	677.66	1.11	1.05	0.06	0.00
2.70	0.15	1,899	677.54	1.04	0.98	0.06	0.00
2.80	0.09	1,583	677.42	0.95	0.90	0.06	0.00
2.90	0.06	1,281	677.30	0.86	0.81	0.06	0.00
3.00	0.00	1,002	677.18	0.76	0.71	0.05	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 9.39 cfs @ 0.64 hrs, Volume= 1.056 af, Depth= 3.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.12	4.95	3.13	2.39
0.04	0.03	0.00	0.00	2.16	4.98	3.16	2.38
0.08	0.13	0.00	0.00	2.20	5.01	3.18	2.37
0.12	0.28	0.00	0.00	2.24	5.04	3.21	2.36
0.16	0.50	0.00	0.00	2.28	5.07	3.24	2.36
0.20	0.74	0.05	0.01	2.32	5.10	3.26	2.36
0.24	0.99	0.13	0.11	2.36	5.13	3.29	2.36
0.28	1.23	0.24	0.45	2.40	5.16	3.32	2.36
0.32	1.48	0.37	1.21	2.44	5.19	3.34	2.36
0.36	1.70	0.50	2.46	2.48	5.22	3.37	2.36
0.40	1.90	0.63	4.06	2.52	5.25	3.40	2.37
0.44	2.07	0.74	5.77	2.56	5.28	3.42	2.37
0.48	2.22	0.85	7.29	2.60	5.30	3.45	2.37
0.52	2.36	0.95	8.41	2.64	5.32	3.47	2.36
0.56	2.50	1.06	9.06	2.68	5.34	3.49	2.34
0.60	2.63	1.16	9.34	2.72	5.36	3.50	2.29
0.64	2.77	1.26	**9.39**	2.76	5.37	3.51	2.18
0.68	2.89	1.36	9.35	2.80	5.39	3.53	2.04
0.72	3.02	1.46	9.27	2.84	5.40	3.54	1.86
0.76	3.13	1.56	9.19	2.88	5.42	3.56	1.70
0.80	3.25	1.65	9.11	2.92	5.44	3.57	1.56
0.84	3.35	1.73	9.01	2.96	5.46	3.60	1.46
0.88	3.45	1.82	8.87	3.00	**5.49**	**3.62**	1.42
0.92	3.54	1.89	8.68	3.04	5.49	3.62	1.44
0.96	3.62	1.96	8.43	3.08	5.49	3.62	1.48
1.00	3.70	2.03	8.12	3.12	5.49	3.62	1.46
1.04	3.78	2.10	7.77	3.16	5.49	3.62	1.32
1.08	3.85	2.16	7.40	3.20	5.49	3.62	1.09
1.12	3.92	2.22	7.04	3.24	5.49	3.62	0.82
1.16	3.99	2.27	6.71	3.28	5.49	3.62	0.58
1.20	4.05	2.33	6.39	3.32	5.49	3.62	0.40
1.24	4.11	2.38	6.09	3.36	5.49	3.62	0.28
1.28	4.17	2.43	5.79	3.40	5.49	3.62	0.19
1.32	4.23	2.48	5.52	3.44	5.49	3.62	0.13
1.36	4.28	2.54	5.28	3.48	5.49	3.62	0.09
1.40	4.34	2.58	5.07	3.52	5.49	3.62	0.06
1.44	4.39	2.63	4.92	3.56	5.49	3.62	0.04
1.48	4.44	2.67	4.79	3.60	5.49	3.62	0.03
1.52	4.49	2.71	4.66	3.64	5.49	3.62	0.02
1.56	4.53	2.75	4.51	3.68	5.49	3.62	0.01
1.60	4.56	2.78	4.33	3.72	5.49	3.62	0.01
1.64	4.60	2.81	4.12	3.76	5.49	3.62	0.01
1.68	4.62	2.84	3.88	3.80	5.49	3.62	0.00
1.72	4.65	2.86	3.62	3.84	5.49	3.62	0.00
1.76	4.68	2.89	3.36	3.88	5.49	3.62	0.00
1.80	4.71	2.92	3.11	3.92	5.49	3.62	0.00
1.84	4.74	2.94	2.90	3.96	5.49	3.62	0.00
1.88	4.77	2.97	2.73	4.00	5.49	3.62	0.00
1.92	4.80	3.00	2.61				
1.96	4.83	3.02	2.53				
2.00	4.86	3.05	2.47				
2.04	4.89	3.08	2.43				
2.08	4.92	3.10	2.40				

Summary for Subcatchment 7S: South Property


Runoff = 18.89 cfs @ 0.87 hrs, Volume= 2.263 af, Depth> 3.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.12	4.95	3.13	5.52
0.04	0.03	0.00	0.00	2.16	4.98	3.16	5.42
0.08	0.13	0.00	0.00	2.20	5.01	3.18	5.33
0.12	0.28	0.00	0.00	2.24	5.04	3.21	5.26
0.16	0.50	0.00	0.00	2.28	5.07	3.24	5.21
0.20	0.74	0.05	0.01	2.32	5.10	3.26	5.18
0.24	0.99	0.13	0.06	2.36	5.13	3.29	5.15
0.28	1.23	0.24	0.28	2.40	5.16	3.32	5.12
0.32	1.48	0.37	0.79	2.44	5.19	3.34	5.11
0.36	1.70	0.50	1.80	2.48	5.22	3.37	5.10
0.40	1.90	0.63	3.37	2.52	5.25	3.40	5.09
0.44	2.07	0.74	5.49	2.56	5.28	3.42	5.09
0.48	2.22	0.85	7.97	2.60	5.30	3.45	5.08
0.52	2.36	0.95	10.54	2.64	5.32	3.47	5.08
0.56	2.50	1.06	12.95	2.68	5.34	3.49	5.07
0.60	2.63	1.16	14.97	2.72	5.36	3.50	5.03
0.64	2.77	1.26	16.49	2.76	5.37	3.51	4.95
0.68	2.89	1.36	17.55	2.80	5.39	3.53	4.82
0.72	3.02	1.46	18.24	2.84	5.40	3.54	4.63
0.76	3.13	1.56	18.61	2.88	5.42	3.56	4.38
0.80	3.25	1.65	18.80	2.92	5.44	3.57	4.12
0.84	3.35	1.73	**18.88**	2.96	5.46	3.60	3.86
0.88	3.45	1.82	**18.89**	3.00	**5.49**	**3.62**	3.64
0.92	3.54	1.89	18.79	3.04	5.49	3.62	3.47
0.96	3.62	1.96	18.59	3.08	5.49	3.62	3.36
1.00	3.70	2.03	18.29	3.12	5.49	3.62	3.28
1.04	3.78	2.10	17.90	3.16	5.49	3.62	3.18
1.08	3.85	2.16	17.39	3.20	5.49	3.62	3.00
1.12	3.92	2.22	16.80	3.24	5.49	3.62	2.72
1.16	3.99	2.27	16.18	3.28	5.49	3.62	2.38
1.20	4.05	2.33	15.55	3.32	5.49	3.62	2.01
1.24	4.11	2.38	14.90	3.36	5.49	3.62	1.64
1.28	4.17	2.43	14.25	3.40	5.49	3.62	1.30
1.32	4.23	2.48	13.63	3.44	5.49	3.62	1.01
1.36	4.28	2.54	13.04	3.48	5.49	3.62	0.78
1.40	4.34	2.58	12.49	3.52	5.49	3.62	0.61
1.44	4.39	2.63	11.98	3.56	5.49	3.62	0.48
1.48	4.44	2.67	11.53	3.60	5.49	3.62	0.37
1.52	4.49	2.71	11.14	3.64	5.49	3.62	0.29
1.56	4.53	2.75	10.76	3.68	5.49	3.62	0.23
1.60	4.56	2.78	10.39	3.72	5.49	3.62	0.17
1.64	4.60	2.81	10.00	3.76	5.49	3.62	0.14
1.68	4.62	2.84	9.60	3.80	5.49	3.62	0.10
1.72	4.65	2.86	9.15	3.84	5.49	3.62	0.08
1.76	4.68	2.89	8.66	3.88	5.49	3.62	0.06
1.80	4.71	2.92	8.16	3.92	5.49	3.62	0.05
1.84	4.74	2.94	7.66	3.96	5.49	3.62	0.04
1.88	4.77	2.97	7.19	4.00	5.49	3.62	0.03
1.92	4.80	3.00	6.76				
1.96	4.83	3.02	6.40				
2.00	4.86	3.05	6.10				
2.04	4.89	3.08	5.86				
2.08	4.92	3.10	5.67				

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 2.66 cfs @ 1.04 hrs, Volume= 0.342 af, Depth> 3.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.04	0.03	0.00	0.00
0.08	0.13	0.00	0.00
0.12	0.28	0.00	0.00
0.16	0.50	0.00	0.00
0.20	0.74	0.03	0.00
0.24	0.99	0.09	0.00
0.28	1.23	0.19	0.01
0.32	1.48	0.30	0.03
0.36	1.70	0.43	0.08
0.40	1.90	0.54	0.16
0.44	2.07	0.65	0.29
0.48	2.22	0.75	0.47
0.52	2.36	0.84	0.69
0.56	2.50	0.94	0.95
0.60	2.63	1.04	1.22
0.64	2.77	1.14	1.48
0.68	2.89	1.23	1.73
0.72	3.02	1.33	1.96
0.76	3.13	1.42	2.15
0.80	3.25	1.51	2.30
0.84	3.35	1.59	2.43
0.88	3.45	1.67	2.52
0.92	3.54	1.74	2.58
0.96	3.62	1.81	2.63
1.00	3.70	1.87	2.65
1.04	3.78	1.94	**2.66**
1.08	3.85	2.00	2.64
1.12	3.92	2.06	2.62
1.16	3.99	2.11	2.58
1.20	4.05	2.16	2.53
1.24	4.11	2.21	2.46
1.28	4.17	2.26	2.40
1.32	4.23	2.31	2.32
1.36	4.28	2.36	2.24
1.40	4.34	2.41	2.17
1.44	4.39	2.46	2.09
1.48	4.44	2.50	2.01
1.52	4.49	2.54	1.94
1.56	4.53	2.57	1.88
1.60	4.56	2.60	1.81
1.64	4.60	2.63	1.75
1.68	4.62	2.66	1.69
1.72	4.65	2.68	1.63
1.76	4.68	2.71	1.56
1.80	4.71	2.73	1.50
1.84	4.74	2.76	1.43
1.88	4.77	2.79	1.36
1.92	4.80	2.81	1.29
1.96	4.83	2.84	1.22
2.00	4.86	2.86	1.16
2.04	4.89	2.89	1.10
2.08	4.92	2.92	1.05
2.12	4.95	2.94	1.01
2.16	4.98	2.97	0.97
2.20	5.01	2.99	0.94
2.24	5.04	3.02	0.91
2.28	5.07	3.05	0.89
2.32	5.10	3.07	0.87
2.36	5.13	3.10	0.86
2.40	5.16	3.12	0.85
2.44	5.19	3.15	0.84
2.48	5.22	3.18	0.83
2.52	5.25	3.20	0.82
2.56	5.28	3.23	0.82
2.60	5.30	3.25	0.81
2.64	5.32	3.27	0.81
2.68	5.34	3.29	0.80
2.72	5.36	3.30	0.80
2.76	5.37	3.32	0.79
2.80	5.39	3.33	0.78
2.84	5.40	3.34	0.77
2.88	5.42	3.36	0.75
2.92	5.44	3.38	0.73
2.96	5.46	3.40	0.70
3.00	**5.49**	**3.42**	0.67
3.04	5.49	3.42	0.64
3.08	5.49	3.42	0.61
3.12	5.49	3.42	0.59
3.16	5.49	3.42	0.56
3.20	5.49	3.42	0.54
3.24	5.49	3.42	0.51
3.28	5.49	3.42	0.48
3.32	5.49	3.42	0.44
3.36	5.49	3.42	0.40
3.40	5.49	3.42	0.36
3.44	5.49	3.42	0.31
3.48	5.49	3.42	0.27
3.52	5.49	3.42	0.23
3.56	5.49	3.42	0.19
3.60	5.49	3.42	0.16
3.64	5.49	3.42	0.13
3.68	5.49	3.42	0.11
3.72	5.49	3.42	0.09
3.76	5.49	3.42	0.08
3.80	5.49	3.42	0.06
3.84	5.49	3.42	0.05
3.88	5.49	3.42	0.04
3.92	5.49	3.42	0.04
3.96	5.49	3.42	0.03
4.00	5.49	3.42	0.03

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 1.50 cfs @ 0.49 hrs, Volume= 0.157 af, Depth= 3.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.12	4.95	2.94	0.36
0.04	0.03	0.00	0.00	2.16	4.98	2.97	0.36
0.08	0.13	0.00	0.00	2.20	5.01	2.99	0.36
0.12	0.28	0.00	0.00	2.24	5.04	3.02	0.36
0.16	0.50	0.00	0.00	2.28	5.07	3.05	0.36
0.20	0.74	0.03	0.00	2.32	5.10	3.07	0.36
0.24	0.99	0.09	0.06	2.36	5.13	3.10	0.36
0.28	1.23	0.19	0.24	2.40	5.16	3.12	0.36
0.32	1.48	0.30	0.55	2.44	5.19	3.15	0.36
0.36	1.70	0.43	0.90	2.48	5.22	3.18	0.36
0.40	1.90	0.54	1.21	2.52	5.25	3.20	0.36
0.44	2.07	0.65	1.42	2.56	5.28	3.23	0.36
0.48	2.22	0.75	**1.50**	2.60	5.30	3.25	0.36
0.52	2.36	0.84	**1.49**	2.64	5.32	3.27	0.36
0.56	2.50	0.94	1.44	2.68	5.34	3.29	0.34
0.60	2.63	1.04	1.40	2.72	5.36	3.30	0.31
0.64	2.77	1.14	1.38	2.76	5.37	3.32	0.27
0.68	2.89	1.23	1.37	2.80	5.39	3.33	0.24
0.72	3.02	1.33	1.35	2.84	5.40	3.34	0.21
0.76	3.13	1.42	1.34	2.88	5.42	3.36	0.20
0.80	3.25	1.51	1.32	2.92	5.44	3.38	0.19
0.84	3.35	1.59	1.30	2.96	5.46	3.40	0.20
0.88	3.45	1.67	1.26	3.00	**5.49**	**3.42**	0.22
0.92	3.54	1.74	1.21	3.04	5.49	3.42	0.25
0.96	3.62	1.81	1.14	3.08	5.49	3.42	0.24
1.00	3.70	1.87	1.08	3.12	5.49	3.42	0.17
1.04	3.78	1.94	1.02	3.16	5.49	3.42	0.09
1.08	3.85	2.00	0.97	3.20	5.49	3.42	0.05
1.12	3.92	2.06	0.93	3.24	5.49	3.42	0.03
1.16	3.99	2.11	0.88	3.28	5.49	3.42	0.01
1.20	4.05	2.16	0.84	3.32	5.49	3.42	0.01
1.24	4.11	2.21	0.80	3.36	5.49	3.42	0.00
1.28	4.17	2.26	0.76	3.40	5.49	3.42	0.00
1.32	4.23	2.31	0.73	3.44	5.49	3.42	0.00
1.36	4.28	2.36	0.71	3.48	5.49	3.42	0.00
1.40	4.34	2.41	0.71	3.52	5.49	3.42	0.00
1.44	4.39	2.46	0.70	3.56	5.49	3.42	0.00
1.48	4.44	2.50	0.68	3.60	5.49	3.42	0.00
1.52	4.49	2.54	0.65	3.64	5.49	3.42	0.00
1.56	4.53	2.57	0.61	3.68	5.49	3.42	0.00
1.60	4.56	2.60	0.57	3.72	5.49	3.42	0.00
1.64	4.60	2.63	0.53	3.76	5.49	3.42	0.00
1.68	4.62	2.66	0.49	3.80	5.49	3.42	0.00
1.72	4.65	2.68	0.44	3.84	5.49	3.42	0.00
1.76	4.68	2.71	0.41	3.88	5.49	3.42	0.00
1.80	4.71	2.73	0.38	3.92	5.49	3.42	0.00
1.84	4.74	2.76	0.37	3.96	5.49	3.42	0.00
1.88	4.77	2.79	0.36	4.00	5.49	3.42	0.00
1.92	4.80	2.81	0.36				
1.96	4.83	2.84	0.36				
2.00	4.86	2.86	0.36				
2.04	4.89	2.89	0.36				
2.08	4.92	2.92	0.36				

Summary for Pond 3P: Southeast Chambers

Inflow	=	27.20 cfs @	0.84 hrs,	Volume=	3.223 af
Outflow	=	1.45 cfs @	4.00 hrs,	Volume=	0.344 af, Atten= 95%, Lag= 189.4 min
Primary	=	1.44 cfs @	3.40 hrs,	Volume=	0.344 af
Secondary	=	0.02 cfs @	4.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Peak Elev= 677.53' @ 3.40 hrs Surf.Area= 46,989 sf Storage= 127,835 cf

Plug-Flow detention time= 116.1 min calculated for 0.344 af (11% of inflow)
Center-of-Mass det. time= 61.7 min (149.0 - 87.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.44 cfs @ 3.40 hrs HW=677.53' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.44 cfs @ 13.05 fps)


Secondary OutFlow Max=0.12 cfs @ 4.00 hrs HW=677.35' TW=0.00' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.37 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.01	0	670.00	0.00	0.00	0.00	0.00
0.30	0.95	71	670.01	0.00	0.00	0.00	0.00
0.40	4.69	857	670.10	0.02	0.02	0.00	0.00
0.50	10.89	3,374	670.37	0.23	0.23	0.00	0.00
0.60	22.64	9,107	670.84	0.43	0.43	0.00	0.00
0.70	26.09	17,687	671.25	0.55	0.55	0.00	0.00
0.80	**27.11**	27,059	671.67	0.65	0.65	0.00	0.00
0.90	**27.07**	36,593	672.09	0.73	0.73	0.00	0.00
1.00	26.12	45,957	672.50	0.81	0.81	0.00	0.00
1.10	24.31	54,818	672.90	0.88	0.88	0.00	0.00
1.20	22.11	62,931	673.27	0.93	0.93	0.00	0.00
1.30	19.89	70,222	673.61	0.98	0.98	0.00	0.00
1.40	17.90	76,721	673.94	1.03	1.03	0.00	0.00
1.50	16.35	82,553	674.25	1.07	1.07	0.00	0.00
1.60	15.00	87,855	674.58	1.11	1.11	0.00	0.00
1.70	13.46	92,638	674.95	1.16	1.16	0.00	0.00
1.80	11.67	96,806	675.30	1.20	1.20	0.00	0.00
1.90	10.02	100,322	675.60	1.24	1.24	0.00	0.00
2.00	8.84	103,293	675.83	1.26	1.26	0.00	0.00
2.10	8.15	105,908	676.00	1.28	1.28	0.00	0.00
2.20	7.77	108,316	676.15	1.30	1.30	0.00	0.00
2.30	7.57	110,611	676.30	1.32	1.32	0.00	0.00
2.40	7.46	112,842	676.45	1.33	1.33	0.00	0.00
2.50	7.41	115,038	676.60	1.35	1.35	0.00	0.00
2.60	7.39	117,216	676.75	1.36	1.36	0.00	0.00
2.70	7.30	119,376	676.90	1.38	1.38	0.00	0.00
2.80	6.83	121,454	677.05	1.39	1.39	0.00	0.00
2.90	5.88	123,282	677.18	1.41	1.41	0.00	0.00
3.00	4.94	124,742	677.29	1.42	1.42	0.00	0.00
3.10	4.46	125,932	677.38	1.43	1.43	0.00	0.00
3.20	3.82	126,947	677.46	1.43	1.43	0.00	0.00
3.30	2.53	127,630	677.52	1.44	1.44	0.00	0.00
3.40	1.33	**127,832**	**677.53**	1.44	**1.44**	0.00	0.00
3.50	0.72	127,693	677.52	1.44	1.44	0.00	0.00
3.60	0.39	127,381	677.50	1.44	1.44	0.00	0.00
3.70	0.21	126,975	677.46	1.43	1.43	0.00	0.00
3.80	0.10	126,516	677.43	1.44	1.43	0.01	0.00
3.90	0.05	126,025	677.39	1.45	1.43	0.02	0.00
4.00	0.00	125,519	677.35	**1.45**	1.42	**0.02**	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	11.44 cfs @	0.83 hrs, Volume=	1.398 af
Outflow	=	11.44 cfs @	0.85 hrs, Volume=	1.378 af, Atten= 0%, Lag= 1.6 min
Primary	=	4.41 cfs @	0.85 hrs, Volume=	0.574 af
Secondary	=	7.02 cfs @	0.85 hrs, Volume=	0.804 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Peak Elev= 678.28' @ 0.85 hrs Surf.Area= 3,458 sf Storage= 4,177 cf

Plug-Flow detention time= 10.9 min calculated for 1.378 af (99% of inflow)
Center-of-Mass det. time= 9.1 min (94.0 - 84.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=4.41 cfs @ 0.85 hrs HW=678.28' (Free Discharge)
- **1=Orifice/Grate** (Orifice Controls 1.37 cfs @ 5.92 fps)
- **2=Sharp-Crested Rectangular Weir** (Weir Controls 3.05 cfs @ 1.80 fps)


Secondary OutFlow Max=7.02 cfs @ 0.85 hrs HW=678.28' TW=671.90' (Dynamic Tailwater)
- **4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.46 fps)
- **5=Sharp-Crested Rectangular Weir** (Weir Controls 6.89 cfs @ 2.41 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
- **3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.01	0	670.76	0.00	0.00	0.00	0.00
0.30	0.79	62	675.21	0.08	0.00	0.08	0.00
0.40	4.22	664	677.03	0.68	0.57	0.11	0.00
0.50	8.48	2,508	677.76	1.23	1.10	0.12	0.00
0.60	10.56	4,057	678.25	10.12	3.85	6.27	0.00
0.70	11.16	4,143	678.27	11.05	4.25	6.80	0.00
0.80	**11.41**	**4,172**	**678.28**	**11.38**	**4.39**	**6.99**	0.00
0.90	**11.33**	**4,174**	**678.28**	**11.39**	**4.40**	**7.00**	0.00
1.00	10.76	4,134	678.27	10.95	4.20	6.74	0.00
1.10	9.86	4,055	678.25	10.10	3.84	6.26	0.00
1.20	8.92	3,967	678.22	9.16	3.44	5.72	0.00
1.30	8.01	3,878	678.20	8.26	3.06	5.20	0.00
1.40	7.24	3,793	678.17	7.43	2.73	4.71	0.00
1.50	6.71	3,732	678.15	6.85	2.49	4.36	0.00
1.60	6.15	3,675	678.14	6.33	2.29	4.04	0.00
1.70	5.41	3,598	678.11	5.66	2.03	3.63	0.00
1.80	4.61	3,502	678.08	4.88	1.75	3.13	0.00
1.90	3.99	3,412	678.06	4.20	1.51	2.68	0.00
2.00	3.63	3,349	678.04	3.76	1.38	2.38	0.00
2.10	3.42	3,309	678.02	3.51	1.31	2.20	0.00
2.20	3.31	3,283	678.02	3.36	1.28	2.08	0.00
2.30	3.24	3,268	678.01	3.27	1.26	2.01	0.00
2.40	3.21	3,260	678.01	3.22	1.25	1.97	0.00
2.50	3.19	3,256	678.01	3.20	1.25	1.95	0.00
2.60	3.18	3,254	678.01	3.18	1.24	1.94	0.00
2.70	3.13	3,251	678.01	3.16	1.24	1.92	0.00
2.80	2.82	3,219	678.00	3.01	1.23	1.78	0.00
2.90	2.36	3,134	677.97	2.64	1.21	1.42	0.00
3.00	2.09	3,042	677.94	2.27	1.20	1.07	0.00
3.10	2.09	3,003	677.93	2.13	1.19	0.94	0.00
3.20	1.62	2,956	677.91	1.95	1.18	0.77	0.00
3.30	0.94	2,799	677.86	1.48	1.16	0.32	0.00
3.40	0.55	2,602	677.79	1.15	1.12	0.03	0.00
3.50	0.32	2,356	677.71	1.10	1.07	0.03	0.00
3.60	0.19	2,065	677.60	1.03	1.01	0.02	0.00
3.70	0.11	1,760	677.49	0.95	0.94	0.01	0.00
3.80	0.08	1,464	677.38	0.86	0.86	0.00	0.00
3.90	0.06	1,191	677.26	0.78	0.78	0.00	0.00
4.00	0.00	943	677.16	0.69	0.69	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 7.00 cfs @ 0.92 hrs, Volume= 1.310 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.10	0.06	0.00	0.00
0.20	0.23	0.00	0.00
0.30	0.52	0.01	0.00
0.40	0.87	0.08	0.14
0.50	1.23	0.23	1.17
0.60	1.59	0.43	3.07
0.70	1.93	0.65	5.04
0.80	2.23	0.85	6.47
0.90	2.47	1.03	**6.99**
1.00	2.68	1.19	**6.77**
1.10	2.89	1.36	6.28
1.20	3.09	1.52	5.94
1.30	3.28	1.67	5.77
1.40	3.46	1.83	5.65
1.50	3.64	1.97	5.53
1.60	3.80	2.12	5.40
1.70	3.95	2.25	5.21
1.80	4.09	2.37	4.93
1.90	4.22	2.48	4.59
2.00	4.34	2.58	4.24
2.10	4.45	2.68	3.96
2.20	4.55	2.77	3.72
2.30	4.65	2.86	3.50
2.40	4.74	2.94	3.29
2.50	4.83	3.02	3.07
2.60	4.91	3.10	2.90
2.70	5.00	3.18	2.81
2.80	5.08	3.25	2.78
2.90	5.16	3.32	2.72
3.00	5.23	3.38	2.59
3.10	5.29	3.44	2.41
3.20	5.34	3.49	2.20
3.30	5.39	3.53	1.97
3.40	5.43	3.57	1.75
3.50	5.48	3.61	1.57
3.60	5.52	3.65	1.47
3.70	5.56	3.69	1.43
3.80	5.61	3.73	1.41
3.90	5.65	3.77	1.41
4.00	5.69	3.81	1.41
4.10	5.74	3.85	1.41
4.20	5.78	3.89	1.41
4.30	5.82	3.93	1.41
4.40	5.87	3.97	1.41
4.50	5.91	4.01	1.41
4.60	5.95	4.05	1.41
4.70	6.00	4.09	1.41
4.80	6.04	4.13	1.42
4.90	6.08	4.17	1.42
5.00	6.13	4.21	1.42
5.10	6.17	4.25	1.42
5.20	6.21	4.29	1.42
5.30	6.24	4.32	1.37
5.40	6.27	4.34	1.24
5.50	6.29	4.36	1.05
5.60	6.31	4.38	0.87
5.70	6.33	4.40	0.78
5.80	6.36	4.42	0.74
5.90	6.39	4.45	0.77
6.00	**6.43**	**4.49**	0.90
6.10	6.43	4.49	1.02
6.20	6.43	4.49	0.73
6.30	6.43	4.49	0.32
6.40	6.43	4.49	0.13
6.50	6.43	4.49	0.05
6.60	6.43	4.49	0.02
6.70	6.43	4.49	0.01
6.80	6.43	4.49	0.00
6.90	6.43	4.49	0.00
7.00	6.43	4.49	0.00
7.10	6.43	4.49	0.00
7.20	6.43	4.49	0.00
7.30	6.43	4.49	0.00
7.40	6.43	4.49	0.00
7.50	6.43	4.49	0.00
7.60	6.43	4.49	0.00
7.70	6.43	4.49	0.00
7.80	6.43	4.49	0.00
7.90	6.43	4.49	0.00
8.00	6.43	4.49	0.00

Summary for Subcatchment 7S: South Property


Runoff = 13.93 cfs @ 1.04 hrs, Volume= 2.808 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.10	0.06	0.00	0.00
0.20	0.23	0.00	0.00
0.30	0.52	0.01	0.00
0.40	0.87	0.08	0.09
0.50	1.23	0.23	0.88
0.60	1.59	0.43	3.16
0.70	1.93	0.65	6.58
0.80	2.23	0.85	10.11
0.90	2.47	1.03	12.69
1.00	2.68	1.19	**13.83**
1.10	2.89	1.36	**13.79**
1.20	3.09	1.52	13.27
1.30	3.28	1.67	12.80
1.40	3.46	1.83	12.46
1.50	3.64	1.97	12.18
1.60	3.80	2.12	11.91
1.70	3.95	2.25	11.59
1.80	4.09	2.37	11.16
1.90	4.22	2.48	10.58
2.00	4.34	2.58	9.90
2.10	4.45	2.68	9.23
2.20	4.55	2.77	8.64
2.30	4.65	2.86	8.11
2.40	4.74	2.94	7.61
2.50	4.83	3.02	7.14
2.60	4.91	3.10	6.70
2.70	5.00	3.18	6.36
2.80	5.08	3.25	6.15
2.90	5.16	3.32	6.01
3.00	5.23	3.38	5.83
3.10	5.29	3.44	5.54
3.20	5.34	3.49	5.17
3.30	5.39	3.53	4.74
3.40	5.43	3.57	4.28
3.50	5.48	3.61	3.84
3.60	5.52	3.65	3.49
3.70	5.56	3.69	3.27
3.80	5.61	3.73	3.15
3.90	5.65	3.77	3.08
4.00	5.69	3.81	3.05
4.10	5.74	3.85	3.03
4.20	5.78	3.89	3.02
4.30	5.82	3.93	3.02
4.40	5.87	3.97	3.02
4.50	5.91	4.01	3.02
4.60	5.95	4.05	3.03
4.70	6.00	4.09	3.03
4.80	6.04	4.13	3.03
4.90	6.08	4.17	3.03
5.00	6.13	4.21	3.04
5.10	6.17	4.25	3.04
5.20	6.21	4.29	3.04
5.30	6.24	4.32	3.01
5.40	6.27	4.34	2.88
5.50	6.29	4.36	2.62
5.60	6.31	4.38	2.27
5.70	6.33	4.40	1.97
5.80	6.36	4.42	1.77
5.90	6.39	4.45	1.69
6.00	**6.43**	**4.49**	1.76
6.10	6.43	4.49	1.96
6.20	6.43	4.49	1.92
6.30	6.43	4.49	1.42
6.40	6.43	4.49	0.82
6.50	6.43	4.49	0.44
6.60	6.43	4.49	0.24
6.70	6.43	4.49	0.13
6.80	6.43	4.49	0.07
6.90	6.43	4.49	0.04
7.00	6.43	4.49	0.02
7.10	6.43	4.49	0.01
7.20	6.43	4.49	0.00
7.30	6.43	4.49	0.00
7.40	6.43	4.49	0.00
7.50	6.43	4.49	0.00
7.60	6.43	4.49	0.00
7.70	6.43	4.49	0.00
7.80	6.43	4.49	0.00
7.90	6.43	4.49	0.00
8.00	6.43	4.49	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.91 cfs @ 1.26 hrs, Volume= 0.428 af, Depth= 4.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.10	0.06	0.00	0.00
0.20	0.23	0.00	0.00
0.30	0.52	0.00	0.00
0.40	0.87	0.06	0.00
0.50	1.23	0.18	0.03
0.60	1.59	0.36	0.16
0.70	1.93	0.56	0.44
0.80	2.23	0.75	0.85
0.90	2.47	0.92	1.28
1.00	2.68	1.07	1.62
1.10	2.89	1.23	1.83
1.20	3.09	1.38	**1.91**
1.30	3.28	1.53	**1.91**
1.40	3.46	1.68	1.89
1.50	3.64	1.82	1.87
1.60	3.80	1.96	1.85
1.70	3.95	2.08	1.82
1.80	4.09	2.20	1.78
1.90	4.22	2.31	1.72
2.00	4.34	2.41	1.64
2.10	4.45	2.50	1.55
2.20	4.55	2.59	1.46
2.30	4.65	2.68	1.37
2.40	4.74	2.76	1.29
2.50	4.83	2.83	1.21
2.60	4.91	2.91	1.14
2.70	5.00	2.99	1.08
2.80	5.08	3.06	1.02
2.90	5.16	3.13	0.98
3.00	5.23	3.19	0.95
3.10	5.29	3.24	0.92
3.20	5.34	3.29	0.87
3.30	5.39	3.33	0.82
3.40	5.43	3.37	0.75
3.50	5.48	3.41	0.69
3.60	5.52	3.45	0.63
3.70	5.56	3.49	0.57
3.80	5.61	3.53	0.54
3.90	5.65	3.57	0.51
4.00	5.69	3.61	0.50
4.10	5.74	3.65	0.49
4.20	5.78	3.68	0.48
4.30	5.82	3.72	0.48
4.40	5.87	3.76	0.48
4.50	5.91	3.80	0.48
4.60	5.95	3.84	0.48
4.70	6.00	3.88	0.48
4.80	6.04	3.92	0.48
4.90	6.08	3.96	0.48
5.00	6.13	4.00	0.48
5.10	6.17	4.04	0.48
5.20	6.21	4.08	0.48
5.30	6.24	4.11	0.48
5.40	6.27	4.13	0.47
5.50	6.29	4.15	0.45
5.60	6.31	4.17	0.41
5.70	6.33	4.19	0.37
5.80	6.36	4.21	0.33
5.90	6.39	4.24	0.30
6.00	**6.43**	**4.28**	0.29
6.10	6.43	4.28	0.29
6.20	6.43	4.28	0.30
6.30	6.43	4.28	0.28
6.40	6.43	4.28	0.22
6.50	6.43	4.28	0.15
6.60	6.43	4.28	0.10
6.70	6.43	4.28	0.06
6.80	6.43	4.28	0.04
6.90	6.43	4.28	0.02
7.00	6.43	4.28	0.02
7.10	6.43	4.28	0.01
7.20	6.43	4.28	0.01
7.30	6.43	4.28	0.00
7.40	6.43	4.28	0.00
7.50	6.43	4.28	0.00
7.60	6.43	4.28	0.00
7.70	6.43	4.28	0.00
7.80	6.43	4.28	0.00
7.90	6.43	4.28	0.00
8.00	6.43	4.28	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 1.07 cfs @ 0.81 hrs, Volume= 0.196 af, Depth= 4.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.10	0.06	0.00	0.00
0.20	0.23	0.00	0.00
0.30	0.52	0.00	0.00
0.40	0.87	0.06	0.06
0.50	1.23	0.18	0.37
0.60	1.59	0.36	0.72
0.70	1.93	0.56	0.98
0.80	2.23	0.75	**1.07**
0.90	2.47	0.92	**1.03**
1.00	2.68	1.07	0.92
1.10	2.89	1.23	0.87
1.20	3.09	1.38	0.85
1.30	3.28	1.53	0.84
1.40	3.46	1.68	0.83
1.50	3.64	1.82	0.81
1.60	3.80	1.96	0.79
1.70	3.95	2.08	0.75
1.80	4.09	2.20	0.69
1.90	4.22	2.31	0.64
2.00	4.34	2.41	0.60
2.10	4.45	2.50	0.56
2.20	4.55	2.59	0.53
2.30	4.65	2.68	0.50
2.40	4.74	2.76	0.47
2.50	4.83	2.83	0.44
2.60	4.91	2.91	0.42
2.70	5.00	2.99	0.42
2.80	5.08	3.06	0.42
2.90	5.16	3.13	0.40
3.00	5.23	3.19	0.37
3.10	5.29	3.24	0.34
3.20	5.34	3.29	0.30
3.30	5.39	3.33	0.27
3.40	5.43	3.37	0.23
3.50	5.48	3.41	0.22
3.60	5.52	3.45	0.22
3.70	5.56	3.49	0.22
3.80	5.61	3.53	0.22
3.90	5.65	3.57	0.22
4.00	5.69	3.61	0.22
4.10	5.74	3.65	0.22
4.20	5.78	3.68	0.22
4.30	5.82	3.72	0.22
4.40	5.87	3.76	0.22
4.50	5.91	3.80	0.22
4.60	5.95	3.84	0.22
4.70	6.00	3.88	0.22
4.80	6.04	3.92	0.22
4.90	6.08	3.96	0.22
5.00	6.13	4.00	0.22
5.10	6.17	4.04	0.22
5.20	6.21	4.08	0.22
5.30	6.24	4.11	0.19
5.40	6.27	4.13	0.16
5.50	6.29	4.15	0.13
5.60	6.31	4.17	0.11
5.70	6.33	4.19	0.11
5.80	6.36	4.21	0.11
5.90	6.39	4.24	0.14
6.00	**6.43**	**4.28**	0.17
6.10	6.43	4.28	0.14
6.20	6.43	4.28	0.03
6.30	6.43	4.28	0.01
6.40	6.43	4.28	0.00
6.50	6.43	4.28	0.00
6.60	6.43	4.28	0.00
6.70	6.43	4.28	0.00
6.80	6.43	4.28	0.00
6.90	6.43	4.28	0.00
7.00	6.43	4.28	0.00
7.10	6.43	4.28	0.00
7.20	6.43	4.28	0.00
7.30	6.43	4.28	0.00
7.40	6.43	4.28	0.00
7.50	6.43	4.28	0.00
7.60	6.43	4.28	0.00
7.70	6.43	4.28	0.00
7.80	6.43	4.28	0.00
7.90	6.43	4.28	0.00
8.00	6.43	4.28	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	20.08 cfs @	1.03 hrs,	Volume=	3.863 af
Outflow	=	3.21 cfs @	5.40 hrs,	Volume=	1.006 af, Atten= 84%, Lag= 262.0 min
Primary	=	1.51 cfs @	5.31 hrs,	Volume=	0.787 af
Secondary	=	1.70 cfs @	5.40 hrs,	Volume=	0.219 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.00 hrs, dt= 0.01 hrs
Peak Elev= 678.24' @ 5.31 hrs Surf.Area= 47,068 sf Storage= 134,868 cf

Plug-Flow detention time= 230.8 min calculated for 1.006 af (26% of inflow)
Center-of-Mass det. time= 147.5 min (291.5 - 144.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.51 cfs @ 5.31 hrs HW=678.24' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.51 cfs @ 13.66 fps)


Secondary OutFlow Max=1.74 cfs @ 5.40 hrs HW=678.24' TW=678.23' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Weir Controls 1.73 cfs @ 0.67 fps)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.53 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.20	0.00	0	670.00	0.00	0.00	0.00	0.00
0.40	0.15	11	670.00	0.00	0.00	0.00	0.00
0.60	3.98	1,090	670.12	0.04	0.04	0.00	0.00
0.80	14.47	6,601	670.69	0.38	0.38	0.00	0.00
1.00	**20.03**	19,343	671.32	0.57	0.57	0.00	0.00
1.20	**19.12**	33,109	671.94	0.70	0.70	0.00	0.00
1.40	18.09	45,937	672.50	0.81	0.81	0.00	0.00
1.60	17.32	58,086	673.04	0.90	0.90	0.00	0.00
1.80	16.19	69,547	673.58	0.98	0.98	0.00	0.00
2.00	14.34	79,870	674.10	1.05	1.05	0.00	0.00
2.20	12.56	88,778	674.65	1.12	1.12	0.00	0.00
2.40	11.08	96,472	675.27	1.20	1.20	0.00	0.00
2.60	9.76	103,098	675.81	1.26	1.26	0.00	0.00
2.80	8.99	108,898	676.19	1.30	1.30	0.00	0.00
3.00	8.47	114,263	676.55	1.34	1.34	0.00	0.00
3.20	7.42	119,055	676.88	1.38	1.38	0.00	0.00
3.40	5.99	122,921	677.16	1.40	1.40	0.00	0.00
3.60	4.73	125,746	677.37	1.43	1.43	0.00	0.00
3.80	4.17	127,889	677.54	1.44	1.44	0.00	0.00
4.00	4.00	129,777	677.70	1.46	1.46	0.00	0.00
4.20	3.82	131,568	677.88	1.47	1.47	0.00	0.00
4.40	3.88	132,953	678.03	2.17	1.49	0.68	0.00
4.60	3.57	133,949	678.14	2.59	1.50	1.09	0.00
4.80	3.25	134,473	678.20	2.50	1.50	0.99	0.00
5.00	3.26	134,724	678.22	3.02	1.51	1.51	0.00
5.20	3.26	**134,842**	**678.24**	3.16	**1.51**	1.65	0.00
5.40	3.04	**134,846**	**678.24**	**3.21**	**1.51**	**1.70**	0.00
5.60	2.39	134,559	678.21	3.01	1.51	1.51	0.00
5.80	1.88	134,060	678.15	2.56	1.50	1.06	0.00
6.00	1.93	133,684	678.11	2.19	1.50	0.70	0.00
6.20	1.95	133,616	678.10	2.21	1.50	0.71	0.00
6.40	0.82	133,064	678.04	2.06	1.49	0.57	0.00
6.60	0.24	132,010	677.92	1.88	1.48	0.40	0.00
6.80	0.07	130,874	677.80	1.49	1.47	0.02	0.00
7.00	0.02	129,833	677.70	1.49	1.46	0.03	0.00
7.20	0.00	128,770	677.61	1.49	1.45	0.04	0.00
7.40	0.00	127,702	677.52	1.48	1.44	0.04	0.00
7.60	0.00	126,637	677.44	1.48	1.43	0.04	0.00
7.80	0.00	125,576	677.36	1.47	1.42	0.05	0.00
8.00	0.00	124,521	677.28	1.46	1.42	0.05	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	8.43 cfs @	0.96 hrs,	Volume=	1.957 af
Outflow	=	8.41 cfs @	1.00 hrs,	Volume=	1.953 af, Atten= 0%, Lag= 2.0 min
Primary	=	3.54 cfs @	5.30 hrs,	Volume=	1.093 af
Secondary	=	5.28 cfs @	1.00 hrs,	Volume=	0.860 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.00 hrs, dt= 0.01 hrs
Peak Elev= 678.23' @ 5.30 hrs Surf.Area= 3,403 sf Storage= 3,988 cf

Plug-Flow detention time= 15.8 min calculated for 1.953 af (100% of inflow)
Center-of-Mass det. time= 15.3 min (183.1 - 167.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=3.54 cfs @ 5.30 hrs HW=678.23' (Free Discharge)
- **1=Orifice/Grate** (Orifice Controls 1.34 cfs @ 5.81 fps)
- **2=Sharp-Crested Rectangular Weir** (Weir Controls 2.20 cfs @ 1.61 fps)


Secondary OutFlow Max=5.28 cfs @ 1.00 hrs HW=678.20' TW=671.31' (Dynamic Tailwater)
- **4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.37 fps)
- **5=Sharp-Crested Rectangular Weir** (Weir Controls 5.15 cfs @ 2.17 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
- **3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.20	0.00	0	670.75	0.00	0.00	0.00	0.00
0.40	0.15	11	671.54	0.00	0.00	0.00	0.00
0.60	3.24	755	677.07	0.72	0.61	0.11	0.00
0.80	**7.31**	3,527	678.09	5.10	1.82	3.29	0.00
1.00	**8.39**	3,892	678.20	**8.41**	3.12	**5.28**	0.00
1.20	7.85	3,843	678.19	7.92	2.92	4.99	0.00
1.40	7.54	3,808	678.18	7.58	2.79	4.80	0.00
1.60	7.24	3,777	678.17	7.29	2.67	4.62	0.00
1.80	6.71	3,727	678.15	6.82	2.48	4.34	0.00
2.00	5.88	3,638	678.12	6.01	2.16	3.85	0.00
2.20	5.18	3,552	678.10	5.29	1.89	3.40	0.00
2.40	4.58	3,477	678.08	4.68	1.68	3.00	0.00
2.60	4.04	3,403	678.05	4.13	1.49	2.63	0.00
2.80	3.80	3,361	678.04	3.83	1.40	2.43	0.00
3.00	3.55	3,329	678.03	3.62	1.35	2.27	0.00
3.20	3.07	3,257	678.01	3.19	1.25	1.95	0.00
3.40	2.50	3,145	677.97	2.69	1.22	1.47	0.00
3.60	2.09	3,027	677.93	2.22	1.20	1.02	0.00
3.80	1.95	2,968	677.91	2.00	1.19	0.81	0.00
4.00	1.90	2,948	677.91	1.92	1.18	0.73	0.00
4.20	1.89	2,955	677.91	1.77	1.18	0.58	0.00
4.40	2.57	3,321	678.03	1.97	1.33	0.64	0.00
4.60	2.98	3,671	678.13	2.60	2.28	0.33	0.00
4.80	2.89	3,859	678.19	2.99	2.99	0.00	0.00
5.00	3.40	3,944	678.22	3.34	3.34	0.00	0.00
5.20	3.54	**3,982**	**678.23**	3.51	**3.51**	0.00	0.00
5.40	3.41	**3,976**	**678.23**	3.48	**3.48**	0.00	0.00
5.60	2.79	3,866	678.19	3.02	3.02	0.00	0.00
5.80	2.13	3,694	678.14	2.36	2.36	0.00	0.00
6.00	1.88	3,573	678.10	1.95	1.95	0.00	0.00
6.20	1.74	3,545	678.10	1.87	1.87	0.00	0.00
6.40	0.91	3,335	678.03	1.36	1.36	0.00	0.00
6.60	0.51	2,935	677.90	1.18	1.18	0.00	0.00
6.80	0.06	2,345	677.70	1.07	1.07	0.00	0.00
7.00	0.04	1,661	677.45	0.92	0.92	0.00	0.00
7.20	0.04	1,090	677.22	0.74	0.74	0.00	0.00
7.40	0.04	649	677.02	0.56	0.56	0.00	0.00
7.60	0.05	356	676.86	0.33	0.33	0.00	0.00
7.80	0.05	211	676.74	0.17	0.17	0.00	0.00
8.00	0.00	150	676.68	0.09	0.09	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 4.39 cfs @ 5.20 hrs, Volume= 1.593 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.05	0.00	0.00
0.60	0.11	0.00	0.00
0.80	0.20	0.00	0.00
1.00	0.30	0.00	0.00
1.20	0.41	0.00	0.00
1.40	0.54	0.01	0.03
1.60	0.65	0.03	0.18
1.80	0.75	0.05	0.34
2.00	0.85	0.08	0.45
2.20	0.95	0.11	0.55
2.40	1.05	0.15	0.64
2.60	1.16	0.20	0.74
2.80	1.29	0.26	0.92
3.00	1.43	0.34	1.15
3.20	1.59	0.43	1.40
3.40	1.75	0.53	1.62
3.60	1.92	0.64	1.82
3.80	2.11	0.77	2.04
4.00	2.32	0.92	2.39
4.20	2.56	1.10	2.81
4.40	2.82	1.30	3.25
4.60	3.10	1.53	3.63
4.80	3.39	1.77	3.99
5.00	3.69	2.02	4.30
5.20	3.98	2.27	**4.39**
5.40	4.26	2.51	4.36
5.60	4.52	2.74	4.28
5.80	4.76	2.96	4.01
6.00	4.97	3.15	3.67
6.20	5.17	3.32	3.31
6.40	5.34	3.48	3.03
6.60	5.50	3.63	2.77
6.80	5.65	3.77	2.52
7.00	5.79	3.89	2.35
7.20	5.92	4.01	2.22
7.40	6.04	4.13	2.09
7.60	6.15	4.23	1.95
7.80	6.25	4.33	1.82
8.00	6.35	4.42	1.69
8.20	6.44	4.50	1.55
8.40	6.52	4.57	1.42
8.60	6.59	4.65	1.30
8.80	6.67	4.72	1.25
9.00	6.74	4.79	1.25
9.20	6.82	4.85	1.23
9.40	6.88	4.91	1.14
9.60	6.93	4.96	1.01
9.80	6.98	5.01	0.89
10.00	7.03	5.06	0.84
10.20	7.08	5.11	0.84
10.40	7.13	5.15	0.84
10.60	7.18	5.20	0.84
10.80	7.23	5.25	0.84
11.00	7.28	5.29	0.82
11.20	7.32	5.33	0.73
11.40	7.35	5.36	0.60
11.60	7.38	5.38	0.49
11.80	7.41	5.42	0.54
12.00	**7.46**	**5.46**	0.67
12.20	7.46	5.46	0.47
12.40	7.46	5.46	0.08
12.60	7.46	5.46	0.01
12.80	7.46	5.46	0.00
13.00	7.46	5.46	0.00
13.20	7.46	5.46	0.00
13.40	7.46	5.46	0.00
13.60	7.46	5.46	0.00
13.80	7.46	5.46	0.00
14.00	7.46	5.46	0.00
14.20	7.46	5.46	0.00
14.40	7.46	5.46	0.00
14.60	7.46	5.46	0.00
14.80	7.46	5.46	0.00
15.00	7.46	5.46	0.00

Summary for Subcatchment 7S: South Property


Runoff = 9.36 cfs @ 5.39 hrs, Volume= 3.415 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.05	0.00	0.00
0.60	0.11	0.00	0.00
0.80	0.20	0.00	0.00
1.00	0.30	0.00	0.00
1.20	0.41	0.00	0.00
1.40	0.54	0.01	0.02
1.60	0.65	0.03	0.22
1.80	0.75	0.05	0.55
2.00	0.85	0.08	0.82
2.20	0.95	0.11	1.05
2.40	1.05	0.15	1.26
2.60	1.16	0.20	1.46
2.80	1.29	0.26	1.75
3.00	1.43	0.34	2.18
3.20	1.59	0.43	2.69
3.40	1.75	0.53	3.19
3.60	1.92	0.64	3.64
3.80	2.11	0.77	4.10
4.00	2.32	0.92	4.71
4.20	2.56	1.10	5.52
4.40	2.82	1.30	6.43
4.60	3.10	1.53	7.30
4.80	3.39	1.77	8.10
5.00	3.69	2.02	8.83
5.20	3.98	2.27	**9.27**
5.40	4.26	2.51	**9.35**
5.60	4.52	2.74	9.27
5.80	4.76	2.96	8.90
6.00	4.97	3.15	8.27
6.20	5.17	3.32	7.54
6.40	5.34	3.48	6.86
6.60	5.50	3.63	6.27
6.80	5.65	3.77	5.71
7.00	5.79	3.89	5.27
7.20	5.92	4.01	4.94
7.40	6.04	4.13	4.64
7.60	6.15	4.23	4.35
7.80	6.25	4.33	4.07
8.00	6.35	4.42	3.79
8.20	6.44	4.50	3.50
8.40	6.52	4.57	3.21
8.60	6.59	4.65	2.93
8.80	6.67	4.72	2.75
9.00	6.74	4.79	2.70
9.20	6.82	4.85	2.67
9.40	6.88	4.91	2.55
9.60	6.93	4.96	2.32
9.80	6.98	5.01	2.05
10.00	7.03	5.06	1.87
10.20	7.08	5.11	1.81
10.40	7.13	5.15	1.80
10.60	7.18	5.20	1.80
10.80	7.23	5.25	1.80
11.00	7.28	5.29	1.79
11.20	7.32	5.33	1.67
11.40	7.35	5.36	1.43
11.60	7.38	5.38	1.17
11.80	7.41	5.42	1.11
12.00	**7.46**	**5.46**	1.29
12.20	7.46	5.46	1.31
12.40	7.46	5.46	0.54
12.60	7.46	5.46	0.16
12.80	7.46	5.46	0.04
13.00	7.46	5.46	0.01
13.20	7.46	5.46	0.00
13.40	7.46	5.46	0.00
13.60	7.46	5.46	0.00
13.80	7.46	5.46	0.00
14.00	7.46	5.46	0.00
14.20	7.46	5.46	0.00
14.40	7.46	5.46	0.00
14.60	7.46	5.46	0.00
14.80	7.46	5.46	0.00
15.00	7.46	5.46	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.43 cfs @ 5.60 hrs, Volume= 0.523 af, Depth= 5.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.05	0.00	0.00
0.60	0.11	0.00	0.00
0.80	0.20	0.00	0.00
1.00	0.30	0.00	0.00
1.20	0.41	0.00	0.00
1.40	0.54	0.00	0.00
1.60	0.65	0.01	0.01
1.80	0.75	0.03	0.03
2.00	0.85	0.05	0.07
2.20	0.95	0.08	0.11
2.40	1.05	0.12	0.14
2.60	1.16	0.16	0.17
2.80	1.29	0.21	0.21
3.00	1.43	0.28	0.26
3.20	1.59	0.36	0.33
3.40	1.75	0.45	0.41
3.60	1.92	0.56	0.48
3.80	2.11	0.68	0.55
4.00	2.32	0.82	0.64
4.20	2.56	0.99	0.75
4.40	2.82	1.18	0.88
4.60	3.10	1.39	1.02
4.80	3.39	1.62	1.15
5.00	3.69	1.86	1.27
5.20	3.98	2.10	1.37
5.40	4.26	2.34	1.42
5.60	4.52	2.57	**1.43**
5.80	4.76	2.77	1.41
6.00	4.97	2.96	1.34
6.20	5.17	3.13	1.24
6.40	5.34	3.29	1.14
6.60	5.50	3.43	1.04
6.80	5.65	3.56	0.95
7.00	5.79	3.69	0.87
7.20	5.92	3.81	0.81
7.40	6.04	3.92	0.76
7.60	6.15	4.02	0.71
7.80	6.25	4.12	0.67
8.00	6.35	4.20	0.62
8.20	6.44	4.29	0.58
8.40	6.52	4.36	0.53
8.60	6.59	4.43	0.49
8.80	6.67	4.50	0.45
9.00	6.74	4.57	0.43
9.20	6.82	4.63	0.43
9.40	6.88	4.69	0.41
9.60	6.93	4.74	0.39
9.80	6.98	4.79	0.35
10.00	7.03	4.84	0.31
10.20	7.08	4.88	0.30
10.40	7.13	4.93	0.29
10.60	7.18	4.98	0.28
10.80	7.23	5.02	0.28
11.00	7.28	5.07	0.28
11.20	7.32	5.10	0.27
11.40	7.35	5.13	0.25
11.60	7.38	5.16	0.21
11.80	7.41	5.19	0.18
12.00	**7.46**	**5.23**	0.19
12.20	7.46	5.23	0.21
12.40	7.46	5.23	0.15
12.60	7.46	5.23	0.06
12.80	7.46	5.23	0.03
13.00	7.46	5.23	0.01
13.20	7.46	5.23	0.00
13.40	7.46	5.23	0.00
13.60	7.46	5.23	0.00
13.80	7.46	5.23	0.00
14.00	7.46	5.23	0.00
14.20	7.46	5.23	0.00
14.40	7.46	5.23	0.00
14.60	7.46	5.23	0.00
14.80	7.46	5.23	0.00
15.00	7.46	5.23	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.67 cfs @ 5.08 hrs, Volume= 0.240 af, Depth= 5.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.05	0.00	0.00
0.60	0.11	0.00	0.00
0.80	0.20	0.00	0.00
1.00	0.30	0.00	0.00
1.20	0.41	0.00	0.00
1.40	0.54	0.00	0.00
1.60	0.65	0.01	0.03
1.80	0.75	0.03	0.05
2.00	0.85	0.05	0.06
2.20	0.95	0.08	0.08
2.40	1.05	0.12	0.09
2.60	1.16	0.16	0.11
2.80	1.29	0.21	0.14
3.00	1.43	0.28	0.18
3.20	1.59	0.36	0.22
3.40	1.75	0.45	0.25
3.60	1.92	0.56	0.28
3.80	2.11	0.68	0.32
4.00	2.32	0.82	0.38
4.20	2.56	0.99	0.45
4.40	2.82	1.18	0.52
4.60	3.10	1.39	0.57
4.80	3.39	1.62	0.63
5.00	3.69	1.86	**0.67**
5.20	3.98	2.10	**0.67**
5.40	4.26	2.34	0.66
5.60	4.52	2.57	0.64
5.80	4.76	2.77	0.59
6.00	4.97	2.96	0.53
6.20	5.17	3.13	0.48
6.40	5.34	3.29	0.44
6.60	5.50	3.43	0.40
6.80	5.65	3.56	0.37
7.00	5.79	3.69	0.35
7.20	5.92	3.81	0.33
7.40	6.04	3.92	0.31
7.60	6.15	4.02	0.29
7.80	6.25	4.12	0.27
8.00	6.35	4.20	0.25
8.20	6.44	4.29	0.23
8.40	6.52	4.36	0.21
8.60	6.59	4.43	0.19
8.80	6.67	4.50	0.19
9.00	6.74	4.57	0.19
9.20	6.82	4.63	0.19
9.40	6.88	4.69	0.17
9.60	6.93	4.74	0.14
9.80	6.98	4.79	0.13
10.00	7.03	4.84	0.13
10.20	7.08	4.88	0.13
10.40	7.13	4.93	0.13
10.60	7.18	4.98	0.13
10.80	7.23	5.02	0.13
11.00	7.28	5.07	0.12
11.20	7.32	5.10	0.10
11.40	7.35	5.13	0.08
11.60	7.38	5.16	0.07
11.80	7.41	5.19	0.09
12.00	**7.46**	**5.23**	0.11
12.20	7.46	5.23	0.02
12.40	7.46	5.23	0.00
12.60	7.46	5.23	0.00
12.80	7.46	5.23	0.00
13.00	7.46	5.23	0.00
13.20	7.46	5.23	0.00
13.40	7.46	5.23	0.00
13.60	7.46	5.23	0.00
13.80	7.46	5.23	0.00
14.00	7.46	5.23	0.00
14.20	7.46	5.23	0.00
14.40	7.46	5.23	0.00
14.60	7.46	5.23	0.00
14.80	7.46	5.23	0.00
15.00	7.46	5.23	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	13.73 cfs @	5.39 hrs,	Volume=	4.504 af
Outflow	=	4.29 cfs @	7.85 hrs,	Volume=	1.799 af, Atten= 69%, Lag= 147.7 min
Primary	=	1.52 cfs @	7.84 hrs,	Volume=	1.283 af
Secondary	=	2.77 cfs @	7.85 hrs,	Volume=	0.515 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Peak Elev= 678.35' @ 7.84 hrs Surf.Area= 47,081 sf Storage= 135,876 cf

Plug-Flow detention time= 303.0 min calculated for 1.797 af (40% of inflow)
Center-of-Mass det. time= 191.6 min (563.9 - 372.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.52 cfs @ 7.84 hrs HW=678.35' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.52 cfs @ 13.76 fps)


Secondary OutFlow Max=2.78 cfs @ 7.85 hrs HW=678.35' TW=678.33' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Weir Controls 2.77 cfs @ 0.85 fps)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.69 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.50	0.00	0	670.00	0.00	0.00	0.00	0.00
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
1.50	0.11	22	670.00	0.00	0.00	0.00	0.00
2.00	0.99	1,053	670.12	0.03	0.03	0.00	0.00
2.50	1.56	3,148	670.35	0.22	0.22	0.00	0.00
3.00	2.47	6,117	670.65	0.36	0.36	0.00	0.00
3.50	3.80	11,022	670.94	0.46	0.46	0.00	0.00
4.00	6.74	19,630	671.34	0.57	0.57	0.00	0.00
4.50	10.18	33,650	671.96	0.71	0.71	0.00	0.00
5.00	**13.05**	53,195	672.82	0.86	0.86	0.00	0.00
5.50	**13.69**	75,929	673.90	1.02	1.02	0.00	0.00
6.00	12.07	97,514	675.36	1.21	1.21	0.00	0.00
6.50	9.56	114,622	676.57	1.34	1.34	0.00	0.00
7.00	7.63	127,505	677.51	1.44	1.44	0.00	0.00
7.50	5.94	**135,201**	**678.28**	**3.22**	**1.51**	**1.71**	0.00
8.00	4.04	**135,812**	**678.35**	**4.24**	**1.52**	**2.72**	0.00
8.50	3.26	135,253	678.28	3.64	1.51	2.12	0.00
9.00	2.89	134,711	678.22	3.05	1.51	1.55	0.00
9.50	2.60	134,451	678.19	2.84	1.50	1.34	0.00
10.00	2.00	133,834	678.13	2.34	1.50	0.84	0.00
10.50	1.93	133,444	678.08	2.04	1.49	0.55	0.00
11.00	1.91	133,321	678.07	2.02	1.49	0.53	0.00
11.50	1.37	132,899	678.02	2.03	1.49	0.54	0.00
12.00	1.41	131,957	677.92	1.71	1.48	0.23	0.00
12.50	0.29	130,807	677.80	1.49	1.47	0.02	0.00
13.00	0.01	128,296	677.57	1.48	1.45	0.04	0.00
13.50	0.00	125,639	677.36	1.47	1.42	0.05	0.00
14.00	0.00	123,012	677.16	1.45	1.40	0.04	0.00
14.50	0.00	120,429	676.98	1.42	1.39	0.04	0.00
15.00	0.00	117,895	676.80	1.39	1.37	0.03	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	5.79 cfs @	5.31 hrs,	Volume=	2.632 af
Outflow	=	5.79 cfs @	5.39 hrs,	Volume=	2.630 af, Atten= 0%, Lag= 4.9 min
Primary	=	5.24 cfs @	7.82 hrs,	Volume=	1.780 af
Secondary	=	3.71 cfs @	5.36 hrs,	Volume=	0.850 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.01 hrs
Peak Elev= 678.33' @ 7.82 hrs Surf.Area= 3,505 sf Storage= 4,342 cf

Plug-Flow detention time= 18.1 min calculated for 2.628 af (100% of inflow)
Center-of-Mass det. time= 17.7 min (429.4 - 411.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=5.24 cfs @ 7.82 hrs HW=678.33' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.39 cfs @ 6.02 fps)
└**2=Sharp-Crested Rectangular Weir** (Weir Controls 3.86 cfs @ 1.96 fps)


Secondary OutFlow Max=3.71 cfs @ 5.36 hrs HW=678.12' TW=673.57' (Dynamic Tailwater)
└**4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.26 fps)
└**5=Sharp-Crested Rectangular Weir** (Weir Controls 3.59 cfs @ 1.91 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.50	0.00	0	670.75	0.00	0.00	0.00	0.00
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
1.50	0.10	25	672.54	0.00	0.00	0.00	0.00
2.00	0.52	277	676.80	0.35	0.25	0.11	0.00
2.50	0.84	599	677.00	0.64	0.53	0.11	0.00
3.00	1.41	1,190	677.26	0.89	0.78	0.11	0.00
3.50	2.17	2,520	677.77	1.23	1.11	0.12	0.00
4.00	3.03	3,173	677.98	2.87	1.22	1.65	0.00
4.50	4.39	3,421	678.06	4.29	1.53	2.76	0.00
5.00	**5.58**	3,578	678.11	**5.52**	1.97	**3.54**	0.00
5.50	**5.76**	3,610	678.12	**5.77**	2.07	**3.70**	0.00
6.00	5.01	3,529	678.09	5.09	1.82	3.26	0.00
6.50	3.99	3,395	678.05	4.05	1.48	2.58	0.00
7.00	3.23	3,277	678.01	3.28	1.27	2.01	0.00
7.50	4.47	**4,147**	**678.28**	5.41	**4.27**	1.14	0.00
8.00	5.03	**4,315**	**678.32**	5.10	**5.10**	0.00	0.00
8.50	3.99	4,115	678.27	4.12	4.12	0.00	0.00
9.00	3.23	3,931	678.21	3.29	3.29	0.00	0.00
9.50	2.81	3,838	678.18	2.90	2.90	0.00	0.00
10.00	1.99	3,622	678.12	2.11	2.11	0.00	0.00
10.50	1.67	3,490	678.08	1.71	1.71	0.00	0.00
11.00	1.64	3,444	678.07	1.59	1.59	0.00	0.00
11.50	1.30	3,293	678.02	1.29	1.29	0.00	0.00
12.00	1.09	2,962	677.91	1.19	1.19	0.00	0.00
12.50	0.15	2,260	677.67	1.05	1.05	0.00	0.00
13.00	0.05	843	677.11	0.65	0.65	0.00	0.00
13.50	0.05	211	676.74	0.17	0.17	0.00	0.00
14.00	0.04	123	676.63	0.06	0.06	0.00	0.00
14.50	0.04	110	676.61	0.04	0.04	0.00	0.00
15.00	0.00	103	676.60	0.03	0.03	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 3.74 cfs @ 11.86 hrs, Volume= 1.760 af, Depth= 6.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	10.60	3.97	2.26	2.60
0.20	0.01	0.00	0.00	10.80	4.17	2.44	2.94
0.40	0.02	0.00	0.00	11.00	4.39	2.63	3.26
0.60	0.05	0.00	0.00	11.20	4.62	2.83	3.43
0.80	0.10	0.00	0.00	11.40	4.85	3.04	3.54
1.00	0.15	0.00	0.00	11.60	5.08	3.25	3.63
1.20	0.20	0.00	0.00	11.80	5.31	3.46	**3.72**
1.40	0.26	0.00	0.00	12.00	5.53	3.66	**3.69**
1.60	0.31	0.00	0.00	12.20	5.74	3.85	3.49
1.80	0.37	0.00	0.00	12.40	5.92	4.02	3.26
2.00	0.42	0.00	0.00	12.60	6.10	4.18	3.00
2.20	0.48	0.00	0.01	12.80	6.25	4.33	2.76
2.40	0.53	0.01	0.05	13.00	6.40	4.46	2.55
2.60	0.59	0.01	0.09	13.20	6.53	4.59	2.35
2.80	0.64	0.02	0.14	13.40	6.65	4.70	2.15
3.00	0.70	0.04	0.18	13.60	6.76	4.80	1.96
3.20	0.75	0.05	0.21	13.80	6.86	4.90	1.79
3.40	0.80	0.06	0.25	14.00	6.96	4.99	1.65
3.60	0.86	0.08	0.28	14.20	7.04	5.07	1.51
3.80	0.91	0.10	0.31	14.40	7.12	5.14	1.38
4.00	0.97	0.12	0.34	14.60	7.19	5.21	1.25
4.20	1.02	0.14	0.36	14.80	7.26	5.27	1.17
4.40	1.08	0.16	0.39	15.00	7.32	5.33	1.10
4.60	1.13	0.19	0.41	15.20	7.38	5.39	1.03
4.80	1.19	0.22	0.44	15.40	7.43	5.44	0.96
5.00	1.25	0.25	0.50	15.60	7.49	5.49	0.92
5.20	1.32	0.28	0.55	15.80	7.54	5.54	0.92
5.40	1.39	0.32	0.62	16.00	7.60	5.59	0.91
5.60	1.46	0.36	0.68	16.20	7.65	5.64	0.92
5.80	1.54	0.40	0.71	16.40	7.70	5.69	0.91
6.00	1.61	0.44	0.74	16.60	7.75	5.74	0.86
6.20	1.68	0.49	0.77	16.80	7.80	5.78	0.80
6.40	1.75	0.53	0.79	17.00	7.84	5.82	0.73
6.60	1.83	0.58	0.81	17.20	7.87	5.86	0.66
6.80	1.90	0.63	0.83	17.40	7.91	5.90	0.65
7.00	1.97	0.68	0.85	17.60	7.96	5.94	0.70
7.20	2.05	0.73	0.87	17.80	8.01	5.98	0.77
7.40	2.12	0.78	0.89	18.00	**8.06**	**6.03**	0.83
7.60	2.20	0.83	0.94	18.20	8.06	6.03	0.55
7.80	2.28	0.89	1.00	18.40	8.06	6.03	0.10
8.00	2.37	0.96	1.07	18.60	8.06	6.03	0.02
8.20	2.46	1.03	1.14	18.80	8.06	6.03	0.00
8.40	2.55	1.10	1.21	19.00	8.06	6.03	0.00
8.60	2.65	1.17	1.28	19.20	8.06	6.03	0.00
8.80	2.76	1.25	1.36	19.40	8.06	6.03	0.00
9.00	2.86	1.34	1.43	19.60	8.06	6.03	0.00
9.20	2.98	1.43	1.51	19.80	8.06	6.03	0.00
9.40	3.09	1.52	1.58	20.00	8.06	6.03	0.00
9.60	3.21	1.62	1.66	20.20	8.06	6.03	0.00
9.80	3.33	1.72	1.74	20.40	8.06	6.03	0.00
10.00	3.46	1.83	1.82	20.60	8.06	6.03	0.00
10.20	3.61	1.95	1.99	20.80	8.06	6.03	0.00
10.40	3.78	2.09	2.28	21.00	8.06	6.03	0.00

Summary for Subcatchment 7S: South Property


Runoff = 7.96 cfs @ 11.97 hrs, Volume= 3.772 af, Depth= 6.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	10.60	3.97	2.26	5.19
0.20	0.01	0.00	0.00	10.80	4.17	2.44	5.88
0.40	0.02	0.00	0.00	11.00	4.39	2.63	6.59
0.60	0.05	0.00	0.00	11.20	4.62	2.83	7.11
0.80	0.10	0.00	0.00	11.40	4.85	3.04	7.43
1.00	0.15	0.00	0.00	11.60	5.08	3.25	7.66
1.20	0.20	0.00	0.00	11.80	5.31	3.46	**7.86**
1.40	0.26	0.00	0.00	12.00	5.53	3.66	**7.95**
1.60	0.31	0.00	0.00	12.20	5.74	3.85	7.70
1.80	0.37	0.00	0.00	12.40	5.92	4.02	7.26
2.00	0.42	0.00	0.00	12.60	6.10	4.18	6.75
2.20	0.48	0.00	0.01	12.80	6.25	4.33	6.21
2.40	0.53	0.01	0.06	13.00	6.40	4.46	5.73
2.60	0.59	0.01	0.15	13.20	6.53	4.59	5.29
2.80	0.64	0.02	0.24	13.40	6.65	4.70	4.87
3.00	0.70	0.04	0.33	13.60	6.76	4.80	4.44
3.20	0.75	0.05	0.41	13.80	6.86	4.90	4.05
3.40	0.80	0.06	0.48	14.00	6.96	4.99	3.72
3.60	0.86	0.08	0.55	14.20	7.04	5.07	3.42
3.80	0.91	0.10	0.62	14.40	7.12	5.14	3.13
4.00	0.97	0.12	0.68	14.60	7.19	5.21	2.85
4.20	1.02	0.14	0.74	14.80	7.26	5.27	2.62
4.40	1.08	0.16	0.80	15.00	7.32	5.33	2.45
4.60	1.13	0.19	0.85	15.20	7.38	5.39	2.30
4.80	1.19	0.22	0.91	15.40	7.43	5.44	2.15
5.00	1.25	0.25	1.00	15.60	7.49	5.49	2.03
5.20	1.32	0.28	1.11	15.80	7.54	5.54	1.98
5.40	1.39	0.32	1.24	16.00	7.60	5.59	1.96
5.60	1.46	0.36	1.37	16.20	7.65	5.64	1.96
5.80	1.54	0.40	1.48	16.40	7.70	5.69	1.96
6.00	1.61	0.44	1.55	16.60	7.75	5.74	1.90
6.20	1.68	0.49	1.61	16.80	7.80	5.78	1.79
6.40	1.75	0.53	1.66	17.00	7.84	5.82	1.65
6.60	1.83	0.58	1.71	17.20	7.87	5.86	1.51
6.80	1.90	0.63	1.75	17.40	7.91	5.90	1.41
7.00	1.97	0.68	1.79	17.60	7.96	5.94	1.45
7.20	2.05	0.73	1.83	17.80	8.01	5.98	1.56
7.40	2.12	0.78	1.87	18.00	**8.06**	**6.03**	1.70
7.60	2.20	0.83	1.95	18.20	8.06	6.03	1.58
7.80	2.28	0.89	2.07	18.40	8.06	6.03	0.64
8.00	2.37	0.96	2.21	18.60	8.06	6.03	0.19
8.20	2.46	1.03	2.36	18.80	8.06	6.03	0.05
8.40	2.55	1.10	2.51	19.00	8.06	6.03	0.01
8.60	2.65	1.17	2.66	19.20	8.06	6.03	0.00
8.80	2.76	1.25	2.82	19.40	8.06	6.03	0.00
9.00	2.86	1.34	2.98	19.60	8.06	6.03	0.00
9.20	2.98	1.43	3.14	19.80	8.06	6.03	0.00
9.40	3.09	1.52	3.30	20.00	8.06	6.03	0.00
9.60	3.21	1.62	3.46	20.20	8.06	6.03	0.00
9.80	3.33	1.72	3.63	20.40	8.06	6.03	0.00
10.00	3.46	1.83	3.79	20.60	8.06	6.03	0.00
10.20	3.61	1.95	4.04	20.80	8.06	6.03	0.00
10.40	3.78	2.09	4.54	21.00	8.06	6.03	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.23 cfs @ 12.09 hrs, Volume= 0.580 af, Depth= 5.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	10.60	3.97	2.09	0.74
0.20	0.01	0.00	0.00	10.80	4.17	2.27	0.84
0.40	0.02	0.00	0.00	11.00	4.39	2.46	0.95
0.60	0.05	0.00	0.00	11.20	4.62	2.65	1.05
0.80	0.10	0.00	0.00	11.40	4.85	2.85	1.12
1.00	0.15	0.00	0.00	11.60	5.08	3.05	1.16
1.20	0.20	0.00	0.00	11.80	5.31	3.26	1.20
1.40	0.26	0.00	0.00	12.00	5.53	3.46	**1.23**
1.60	0.31	0.00	0.00	12.20	5.74	3.64	**1.22**
1.80	0.37	0.00	0.00	12.40	5.92	3.81	1.17
2.00	0.42	0.00	0.00	12.60	6.10	3.97	1.11
2.20	0.48	0.00	0.00	12.80	6.25	4.12	1.03
2.40	0.53	0.00	0.00	13.00	6.40	4.25	0.95
2.60	0.59	0.01	0.00	13.20	6.53	4.37	0.88
2.80	0.64	0.01	0.01	13.40	6.65	4.48	0.81
3.00	0.70	0.02	0.02	13.60	6.76	4.59	0.74
3.20	0.75	0.03	0.04	13.80	6.86	4.68	0.68
3.40	0.80	0.04	0.05	14.00	6.96	4.77	0.62
3.60	0.86	0.06	0.06	14.20	7.04	4.84	0.57
3.80	0.91	0.07	0.07	14.40	7.12	4.92	0.52
4.00	0.97	0.09	0.08	14.60	7.19	4.98	0.48
4.20	1.02	0.11	0.09	14.80	7.26	5.04	0.44
4.40	1.08	0.13	0.10	15.00	7.32	5.10	0.41
4.60	1.13	0.15	0.11	15.20	7.38	5.16	0.38
4.80	1.19	0.17	0.12	15.40	7.43	5.21	0.36
5.00	1.25	0.20	0.13	15.60	7.49	5.26	0.33
5.20	1.32	0.23	0.15	15.80	7.54	5.31	0.32
5.40	1.39	0.26	0.16	16.00	7.60	5.36	0.31
5.60	1.46	0.30	0.18	16.20	7.65	5.41	0.31
5.80	1.54	0.33	0.20	16.40	7.70	5.46	0.31
6.00	1.61	0.37	0.21	16.60	7.75	5.51	0.31
6.20	1.68	0.41	0.23	16.80	7.80	5.55	0.29
6.40	1.75	0.46	0.24	17.00	7.84	5.59	0.27
6.60	1.83	0.50	0.24	17.20	7.87	5.62	0.25
6.80	1.90	0.54	0.25	17.40	7.91	5.66	0.23
7.00	1.97	0.59	0.26	17.60	7.96	5.70	0.23
7.20	2.05	0.63	0.27	17.80	8.01	5.75	0.24
7.40	2.12	0.68	0.27	18.00	**8.06**	**5.80**	0.26
7.60	2.20	0.73	0.28	18.20	8.06	5.80	0.26
7.80	2.28	0.79	0.30	18.40	8.06	5.80	0.18
8.00	2.37	0.85	0.32	18.60	8.06	5.80	0.08
8.20	2.46	0.91	0.34	18.80	8.06	5.80	0.03
8.40	2.55	0.98	0.36	19.00	8.06	5.80	0.01
8.60	2.65	1.05	0.39	19.20	8.06	5.80	0.00
8.80	2.76	1.13	0.41	19.40	8.06	5.80	0.00
9.00	2.86	1.21	0.43	19.60	8.06	5.80	0.00
9.20	2.98	1.29	0.46	19.80	8.06	5.80	0.00
9.40	3.09	1.38	0.49	20.00	8.06	5.80	0.00
9.60	3.21	1.48	0.51	20.20	8.06	5.80	0.00
9.80	3.33	1.57	0.54	20.40	8.06	5.80	0.00
10.00	3.46	1.68	0.56	20.60	8.06	5.80	0.00
10.20	3.61	1.80	0.60	20.80	8.06	5.80	0.00
10.40	3.78	1.94	0.65	21.00	8.06	5.80	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.58 cfs @ 11.80 hrs, Volume= 0.266 af, Depth= 5.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	10.60	3.97	2.09	0.42
0.20	0.01	0.00	0.00	10.80	4.17	2.27	0.48
0.40	0.02	0.00	0.00	11.00	4.39	2.46	0.52
0.60	0.05	0.00	0.00	11.20	4.62	2.65	0.53
0.80	0.10	0.00	0.00	11.40	4.85	2.85	0.55
1.00	0.15	0.00	0.00	11.60	5.08	3.05	0.57
1.20	0.20	0.00	0.00	11.80	5.31	3.26	**0.58**
1.40	0.26	0.00	0.00	12.00	5.53	3.46	0.55
1.60	0.31	0.00	0.00	12.20	5.74	3.64	0.52
1.80	0.37	0.00	0.00	12.40	5.92	3.81	0.48
2.00	0.42	0.00	0.00	12.60	6.10	3.97	0.44
2.20	0.48	0.00	0.00	12.80	6.25	4.12	0.41
2.40	0.53	0.00	0.00	13.00	6.40	4.25	0.38
2.60	0.59	0.01	0.01	13.20	6.53	4.37	0.35
2.80	0.64	0.01	0.02	13.40	6.65	4.48	0.32
3.00	0.70	0.02	0.02	13.60	6.76	4.59	0.29
3.20	0.75	0.03	0.03	13.80	6.86	4.68	0.26
3.40	0.80	0.04	0.03	14.00	6.96	4.77	0.24
3.60	0.86	0.06	0.04	14.20	7.04	4.84	0.22
3.80	0.91	0.07	0.04	14.40	7.12	4.92	0.20
4.00	0.97	0.09	0.05	14.60	7.19	4.98	0.19
4.20	1.02	0.11	0.05	14.80	7.26	5.04	0.17
4.40	1.08	0.13	0.05	15.00	7.32	5.10	0.16
4.60	1.13	0.15	0.06	15.20	7.38	5.16	0.15
4.80	1.19	0.17	0.06	15.40	7.43	5.21	0.14
5.00	1.25	0.20	0.07	15.60	7.49	5.26	0.14
5.20	1.32	0.23	0.08	15.80	7.54	5.31	0.14
5.40	1.39	0.26	0.09	16.00	7.60	5.36	0.14
5.60	1.46	0.30	0.10	16.20	7.65	5.41	0.14
5.80	1.54	0.33	0.10	16.40	7.70	5.46	0.14
6.00	1.61	0.37	0.11	16.60	7.75	5.51	0.13
6.20	1.68	0.41	0.11	16.80	7.80	5.55	0.12
6.40	1.75	0.46	0.12	17.00	7.84	5.59	0.11
6.60	1.83	0.50	0.12	17.20	7.87	5.62	0.10
6.80	1.90	0.54	0.12	17.40	7.91	5.66	0.10
7.00	1.97	0.59	0.12	17.60	7.96	5.70	0.11
7.20	2.05	0.63	0.13	17.80	8.01	5.75	0.12
7.40	2.12	0.68	0.13	18.00	**8.06**	**5.80**	0.14
7.60	2.20	0.73	0.14	18.20	8.06	5.80	0.02
7.80	2.28	0.79	0.15	18.40	8.06	5.80	0.00
8.00	2.37	0.85	0.16	18.60	8.06	5.80	0.00
8.20	2.46	0.91	0.17	18.80	8.06	5.80	0.00
8.40	2.55	0.98	0.19	19.00	8.06	5.80	0.00
8.60	2.65	1.05	0.20	19.20	8.06	5.80	0.00
8.80	2.76	1.13	0.21	19.40	8.06	5.80	0.00
9.00	2.86	1.21	0.22	19.60	8.06	5.80	0.00
9.20	2.98	1.29	0.23	19.80	8.06	5.80	0.00
9.40	3.09	1.38	0.24	20.00	8.06	5.80	0.00
9.60	3.21	1.48	0.26	20.20	8.06	5.80	0.00
9.80	3.33	1.57	0.27	20.40	8.06	5.80	0.00
10.00	3.46	1.68	0.28	20.60	8.06	5.80	0.00
10.20	3.61	1.80	0.32	20.80	8.06	5.80	0.00
10.40	3.78	1.94	0.37	21.00	8.06	5.80	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	11.71 cfs @	11.93 hrs,	Volume=	5.001 af
Outflow	=	11.15 cfs @	13.57 hrs,	Volume=	2.277 af, Atten= 5%, Lag= 98.6 min
Primary	=	1.53 cfs @	13.56 hrs,	Volume=	1.507 af
Secondary	=	9.62 cfs @	13.57 hrs,	Volume=	0.770 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Peak Elev= 678.50' @ 13.56 hrs Surf.Area= 47,097 sf Storage= 137,169 cf

Plug-Flow detention time= 326.5 min calculated for 2.275 af (45% of inflow)
Center-of-Mass det. time= 176.1 min (871.0 - 695.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.53 cfs @ 13.56 hrs HW=678.49' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.53 cfs @ 13.88 fps)


Secondary OutFlow Max=7.72 cfs @ 13.57 hrs HW=678.48' TW=678.31' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Weir Controls 7.70 cfs @ 1.94 fps)
└**4=Orifice/Grate** (Orifice Controls 0.02 cfs @ 1.97 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
0.40	0.00	0	670.00	0.00	0.00	0.00	0.00
0.80	0.00	0	670.00	0.00	0.00	0.00	0.00
1.20	0.00	0	670.00	0.00	0.00	0.00	0.00
1.60	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.40	0.07	23	670.00	0.00	0.00	0.00	0.00
2.80	0.36	319	670.04	0.00	0.00	0.00	0.00
3.20	0.54	942	670.11	0.03	0.03	0.00	0.00
3.60	0.70	1,751	670.20	0.09	0.09	0.00	0.00
4.00	0.84	2,667	670.30	0.18	0.18	0.00	0.00
4.40	0.96	3,649	670.40	0.25	0.25	0.00	0.00
4.80	1.08	4,711	670.51	0.30	0.30	0.00	0.00
5.20	1.31	5,939	670.63	0.35	0.35	0.00	0.00
5.60	1.58	7,461	670.76	0.40	0.40	0.00	0.00
6.00	1.77	9,285	670.85	0.43	0.43	0.00	0.00
6.40	1.89	11,277	670.95	0.46	0.46	0.00	0.00
6.80	1.99	13,381	671.05	0.49	0.49	0.00	0.00
7.20	2.08	15,578	671.15	0.52	0.52	0.00	0.00
7.60	2.21	17,870	671.26	0.55	0.55	0.00	0.00
8.00	2.49	20,426	671.37	0.58	0.58	0.00	0.00
8.40	2.81	23,380	671.50	0.61	0.61	0.00	0.00
8.80	3.55	26,983	671.66	0.65	0.65	0.00	0.00
9.20	4.11	31,531	671.86	0.69	0.69	0.00	0.00
9.60	4.66	36,801	672.10	0.74	0.74	0.00	0.00
10.00	5.22	42,795	672.36	0.78	0.78	0.00	0.00
10.40	6.50	49,831	672.67	0.84	0.84	0.00	0.00
10.80	8.69	59,426	673.11	0.91	0.91	0.00	0.00
11.20	10.50	71,956	673.70	1.00	1.00	0.00	0.00
11.60	**11.30**	86,165	674.46	1.10	1.10	0.00	0.00
12.00	**11.67**	101,118	675.67	1.24	1.24	0.00	0.00
12.40	10.60	115,451	676.63	1.35	1.35	0.00	0.00
12.80	9.05	127,667	677.52	1.44	1.44	0.00	0.00
13.20	5.64	**135,564**	**678.32**	**4.47**	**1.52**	**2.95**	0.00
13.60	9.02	**136,428**	**678.41**	**3.89**	**1.53**	**2.37**	0.00
14.00	3.96	136,021	678.37	5.47	1.52	3.95	0.00
14.40	3.33	135,595	678.32	5.95	1.52	4.43	0.00
14.80	2.79	135,049	678.26	4.11	1.51	2.59	0.00
15.20	2.45	134,486	678.20	1.51	1.51	0.00	0.00
15.60	2.17	134,086	678.15	1.50	1.50	0.00	0.00
16.00	2.11	133,887	678.13	1.50	1.50	0.00	0.00
16.40	2.10	133,790	678.12	1.50	1.50	0.00	0.00
16.80	1.90	133,637	678.10	1.50	1.50	0.00	0.00
17.20	1.60	133,259	678.06	1.49	1.49	0.00	0.00
17.60	1.56	132,824	678.01	1.49	1.49	0.00	0.00
18.00	1.84	132,782	678.01	1.49	1.49	0.00	0.00
18.40	0.64	132,310	677.96	2.06	1.48	0.57	0.00
18.80	0.05	130,256	677.74	1.49	1.46	0.02	0.00
19.20	0.00	128,144	677.56	1.48	1.44	0.04	0.00
19.60	0.00	126,015	677.39	1.47	1.43	0.05	0.00
20.00	0.00	123,905	677.23	1.46	1.41	0.04	0.00
20.40	0.00	121,822	677.08	1.44	1.40	0.04	0.00
20.80	0.00	119,769	676.93	1.41	1.38	0.03	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	12.37 cfs @	13.57 hrs, Volume=	3.110 af
Outflow	=	12.66 cfs @	13.60 hrs, Volume=	3.108 af, Atten= 0%, Lag= 1.8 min
Primary	=	8.40 cfs @	13.60 hrs, Volume=	2.144 af
Secondary	=	4.53 cfs @	13.52 hrs, Volume=	0.964 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Peak Elev= 678.49' @ 13.60 hrs Surf.Area= 3,660 sf Storage= 4,899 cf

Plug-Flow detention time= 18.6 min calculated for 3.108 af (100% of inflow)
Center-of-Mass det. time= 18.2 min (758.4 - 740.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=8.09 cfs @ 13.60 hrs HW=678.47' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.45 cfs @ 6.28 fps)
└**2=Sharp-Crested Rectangular Weir** (Weir Controls 6.64 cfs @ 2.38 fps)


Secondary OutFlow Max=5.43 cfs @ 13.52 hrs HW=678.47' TW=678.41' (Dynamic Tailwater)
└**4=Orifice/Grate** (Orifice Controls 0.02 cfs @ 1.24 fps)
└**5=Sharp-Crested Rectangular Weir** (Weir Controls 5.41 cfs @ 1.37 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.40	0.00	0	670.75	0.00	0.00	0.00	0.00
0.80	0.00	0	670.75	0.00	0.00	0.00	0.00
1.20	0.00	0	670.75	0.00	0.00	0.00	0.00
1.60	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.40	0.05	21	672.27	0.00	0.00	0.00	0.00
2.80	0.15	83	676.53	0.10	0.00	0.10	0.00
3.20	0.25	152	676.68	0.20	0.10	0.10	0.00
3.60	0.34	222	676.76	0.29	0.19	0.11	0.00
4.00	0.42	291	676.81	0.37	0.26	0.11	0.00
4.40	0.49	357	676.86	0.44	0.33	0.11	0.00
4.80	0.56	426	676.90	0.51	0.40	0.11	0.00
5.20	0.70	536	676.96	0.60	0.49	0.11	0.00
5.60	0.86	719	677.05	0.70	0.59	0.11	0.00
6.00	0.96	948	677.16	0.80	0.69	0.11	0.00
6.40	1.03	1,163	677.25	0.88	0.77	0.11	0.00
6.80	1.08	1,362	677.33	0.95	0.83	0.11	0.00
7.20	1.13	1,553	677.41	1.00	0.89	0.12	0.00
7.60	1.22	1,750	677.49	1.06	0.94	0.12	0.00
8.00	1.39	2,052	677.60	1.13	1.01	0.12	0.00
8.40	1.57	2,489	677.76	1.22	1.10	0.12	0.00
8.80	1.77	2,846	677.87	1.69	1.17	0.53	0.00
9.20	1.97	2,921	677.90	1.92	1.18	0.74	0.00
9.60	2.17	2,982	677.92	2.13	1.19	0.94	0.00
10.00	2.38	3,040	677.94	2.34	1.20	1.14	0.00
10.40	2.93	3,158	677.98	2.81	1.22	1.59	0.00
10.80	3.78	3,330	678.03	3.68	1.35	2.33	0.00
11.20	4.48	3,441	678.06	4.43	1.58	2.85	0.00
11.60	4.80	3,487	678.08	4.77	1.70	3.07	0.00
12.00	4.92	3,511	678.09	4.94	1.77	3.17	0.00
12.40	4.43	3,454	678.07	4.48	1.62	2.87	0.00
12.80	3.79	3,369	678.04	3.85	1.42	2.43	0.00
13.20	**6.18**	4,219	678.30	4.62	4.62	**0.00**	0.00
13.60	**5.07**	**4,889**	**678.48**	**12.64**	**8.35**	**4.29**	0.00
14.00	6.22	4,492	678.37	6.04	6.04	0.00	0.00
14.40	6.34	4,149	678.28	4.28	4.28	0.00	0.00
14.80	4.20	3,853	678.19	2.96	2.96	0.00	0.00
15.20	1.41	3,786	678.17	2.70	2.70	0.00	0.00
15.60	1.26	3,629	678.12	2.13	2.13	0.00	0.00
16.00	1.23	3,511	678.09	1.77	1.77	0.00	0.00
16.40	1.22	3,485	678.08	1.70	1.70	0.00	0.00
16.80	1.09	3,447	678.07	1.60	1.60	0.00	0.00
17.20	0.92	3,349	678.04	1.38	1.38	0.00	0.00
17.60	0.93	3,228	678.00	1.23	1.23	0.00	0.00
18.00	1.09	3,215	677.99	1.23	1.23	0.00	0.00
18.40	0.85	3,037	677.94	1.20	1.20	0.00	0.00
18.80	0.06	1,902	677.54	0.98	0.98	0.00	0.00
19.20	0.04	796	677.09	0.63	0.63	0.00	0.00
19.60	0.05	248	676.78	0.22	0.22	0.00	0.00
20.00	0.04	133	676.65	0.07	0.07	0.00	0.00
20.40	0.04	115	676.62	0.05	0.05	0.00	0.00
20.80	0.03	108	676.61	0.04	0.04	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 3.02 cfs @ 15.78 hrs, Volume= 1.903 af, Depth= 6.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.13	0.00	0.00
1.60	0.22	0.00	0.00
2.00	0.30	0.00	0.00
2.40	0.39	0.00	0.00
2.80	0.48	0.00	0.01
3.20	0.57	0.01	0.07
3.60	0.65	0.03	0.12
4.00	0.74	0.05	0.17
4.40	0.83	0.07	0.21
4.80	0.91	0.10	0.25
5.20	1.00	0.13	0.29
5.60	1.09	0.17	0.32
6.00	1.17	0.21	0.34
6.40	1.27	0.25	0.39
6.80	1.37	0.31	0.46
7.20	1.48	0.37	0.53
7.60	1.60	0.43	0.59
8.00	1.71	0.51	0.62
8.40	1.83	0.58	0.65
8.80	1.94	0.66	0.67
9.20	2.06	0.74	0.70
9.60	2.18	0.82	0.72
10.00	2.30	0.90	0.76
10.40	2.43	1.00	0.84
10.80	2.57	1.11	0.92
11.20	2.72	1.22	1.01
11.60	2.88	1.35	1.10
12.00	3.05	1.48	1.18
12.40	3.22	1.63	1.28
12.80	3.41	1.79	1.37
13.20	3.61	1.95	1.46
13.60	3.84	2.15	1.67
14.00	4.11	2.38	2.06
14.40	4.44	2.67	2.46
14.80	4.79	2.98	2.76
15.20	5.15	3.31	2.88
15.60	5.52	3.65	**2.99**
16.00	5.88	3.98	**2.94**
16.40	6.20	4.28	2.65
16.80	6.48	4.54	2.35
17.20	6.73	4.77	2.07
17.60	6.95	4.98	1.84
18.00	7.13	5.15	1.60
18.40	7.30	5.31	1.39
18.80	7.44	5.45	1.23
19.20	7.57	5.57	1.07
19.60	7.68	5.67	0.95
20.00	7.78	5.77	0.86
20.40	7.87	5.86	0.78
20.80	7.96	5.94	0.73
21.20	8.05	6.02	0.73
21.60	8.13	6.11	0.73
22.00	8.22	6.18	0.70
22.40	8.29	6.25	0.62
22.80	8.35	6.31	0.54
23.20	8.42	6.37	0.53
23.60	8.49	6.44	0.60
24.00	**8.57**	**6.52**	0.69
24.40	8.57	6.52	0.08
24.80	8.57	6.52	0.00
25.20	8.57	6.52	0.00
25.60	8.57	6.52	0.00
26.00	8.57	6.52	0.00
26.40	8.57	6.52	0.00
26.80	8.57	6.52	0.00

Summary for Subcatchment 7S: South Property


Runoff = 6.44 cfs @ 15.86 hrs, Volume= 4.077 af, Depth= 6.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.13	0.00	0.00
1.60	0.22	0.00	0.00
2.00	0.30	0.00	0.00
2.40	0.39	0.00	0.00
2.80	0.48	0.00	0.01
3.20	0.57	0.01	0.12
3.60	0.65	0.03	0.23
4.00	0.74	0.05	0.34
4.40	0.83	0.07	0.43
4.80	0.91	0.10	0.51
5.20	1.00	0.13	0.59
5.60	1.09	0.17	0.66
6.00	1.17	0.21	0.72
6.40	1.27	0.25	0.80
6.80	1.37	0.31	0.93
7.20	1.48	0.37	1.09
7.60	1.60	0.43	1.24
8.00	1.71	0.51	1.32
8.40	1.83	0.58	1.38
8.80	1.94	0.66	1.43
9.20	2.06	0.74	1.48
9.60	2.18	0.82	1.52
10.00	2.30	0.90	1.59
10.40	2.43	1.00	1.75
10.80	2.57	1.11	1.92
11.20	2.72	1.22	2.10
11.60	2.88	1.35	2.29
12.00	3.05	1.48	2.48
12.40	3.22	1.63	2.68
12.80	3.41	1.79	2.87
13.20	3.61	1.95	3.07
13.60	3.84	2.15	3.40
14.00	4.11	2.38	4.16
14.40	4.44	2.67	5.02
14.80	4.79	2.98	5.76
15.20	5.15	3.31	6.09
15.60	5.52	3.65	**6.33**
16.00	5.88	3.98	**6.38**
16.40	6.20	4.28	5.86
16.80	6.48	4.54	5.23
17.20	6.73	4.77	4.60
17.60	6.95	4.98	4.09
18.00	7.13	5.15	3.58
18.40	7.30	5.31	3.11
18.80	7.44	5.45	2.74
19.20	7.57	5.57	2.40
19.60	7.68	5.67	2.09
20.00	7.78	5.77	1.90
20.40	7.87	5.86	1.73
20.80	7.96	5.94	1.59
21.20	8.05	6.02	1.57
21.60	8.13	6.11	1.57
22.00	8.22	6.18	1.54
22.40	8.29	6.25	1.38
22.80	8.35	6.31	1.21
23.20	8.42	6.37	1.11
23.60	8.49	6.44	1.24
24.00	**8.57**	**6.52**	1.42
24.40	8.57	6.52	0.52
24.80	8.57	6.52	0.04
25.20	8.57	6.52	0.00
25.60	8.57	6.52	0.00
26.00	8.57	6.52	0.00
26.40	8.57	6.52	0.00
26.80	8.57	6.52	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.00 cfs @ 15.93 hrs, Volume= 0.628 af, Depth= 6.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.13	0.00	0.00
1.60	0.22	0.00	0.00
2.00	0.30	0.00	0.00
2.40	0.39	0.00	0.00
2.80	0.48	0.00	0.00
3.20	0.57	0.00	0.00
3.60	0.65	0.01	0.02
4.00	0.74	0.03	0.03
4.40	0.83	0.05	0.05
4.80	0.91	0.07	0.06
5.20	1.00	0.10	0.07
5.60	1.09	0.13	0.09
6.00	1.17	0.16	0.10
6.40	1.27	0.20	0.11
6.80	1.37	0.25	0.12
7.20	1.48	0.30	0.15
7.60	1.60	0.37	0.17
8.00	1.71	0.43	0.19
8.40	1.83	0.50	0.20
8.80	1.94	0.57	0.21
9.20	2.06	0.64	0.22
9.60	2.18	0.72	0.22
10.00	2.30	0.80	0.23
10.40	2.43	0.89	0.25
10.80	2.57	0.99	0.28
11.20	2.72	1.10	0.31
11.60	2.88	1.22	0.34
12.00	3.05	1.35	0.37
12.40	3.22	1.49	0.40
12.80	3.41	1.64	0.43
13.20	3.61	1.80	0.46
13.60	3.84	1.99	0.50
14.00	4.11	2.22	0.60
14.40	4.44	2.49	0.73
14.80	4.79	2.80	0.86
15.20	5.15	3.12	0.93
15.60	5.52	3.45	**0.98**
16.00	5.88	3.78	**1.00**
16.40	6.20	4.07	0.95
16.80	6.48	4.33	0.85
17.20	6.73	4.55	0.76
17.60	6.95	4.75	0.67
18.00	7.13	4.93	0.59
18.40	7.30	5.08	0.51
18.80	7.44	5.22	0.45
19.20	7.57	5.34	0.40
19.60	7.68	5.44	0.35
20.00	7.78	5.54	0.31
20.40	7.87	5.62	0.28
20.80	7.96	5.71	0.26
21.20	8.05	5.79	0.25
21.60	8.13	5.87	0.25
22.00	8.22	5.95	0.25
22.40	8.29	6.02	0.23
22.80	8.35	6.08	0.20
23.20	8.42	6.14	0.18
23.60	8.49	6.20	0.19
24.00	**8.57**	**6.28**	0.22
24.40	8.57	6.28	0.14
24.80	8.57	6.28	0.03
25.20	8.57	6.28	0.00
25.60	8.57	6.28	0.00
26.00	8.57	6.28	0.00
26.40	8.57	6.28	0.00
26.80	8.57	6.28	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.47 cfs @ 15.70 hrs, Volume= 0.288 af, Depth= 6.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.13	0.00	0.00
1.60	0.22	0.00	0.00
2.00	0.30	0.00	0.00
2.40	0.39	0.00	0.00
2.80	0.48	0.00	0.00
3.20	0.57	0.00	0.01
3.60	0.65	0.01	0.01
4.00	0.74	0.03	0.02
4.40	0.83	0.05	0.03
4.80	0.91	0.07	0.03
5.20	1.00	0.10	0.04
5.60	1.09	0.13	0.04
6.00	1.17	0.16	0.05
6.40	1.27	0.20	0.06
6.80	1.37	0.25	0.07
7.20	1.48	0.30	0.08
7.60	1.60	0.37	0.09
8.00	1.71	0.43	0.09
8.40	1.83	0.50	0.09
8.80	1.94	0.57	0.10
9.20	2.06	0.64	0.10
9.60	2.18	0.72	0.11
10.00	2.30	0.80	0.11
10.40	2.43	0.89	0.13
10.80	2.57	0.99	0.14
11.20	2.72	1.10	0.15
11.60	2.88	1.22	0.17
12.00	3.05	1.35	0.18
12.40	3.22	1.49	0.20
12.80	3.41	1.64	0.21
13.20	3.61	1.80	0.22
13.60	3.84	1.99	0.27
14.00	4.11	2.22	0.33
14.40	4.44	2.49	0.39
14.80	4.79	2.80	0.43
15.20	5.15	3.12	0.45
15.60	5.52	3.45	**0.46**
16.00	5.88	3.78	**0.44**
16.40	6.20	4.07	0.40
16.80	6.48	4.33	0.35
17.20	6.73	4.55	0.31
17.60	6.95	4.75	0.27
18.00	7.13	4.93	0.24
18.40	7.30	5.08	0.21
18.80	7.44	5.22	0.18
19.20	7.57	5.34	0.16
19.60	7.68	5.44	0.14
20.00	7.78	5.54	0.13
20.40	7.87	5.62	0.12
20.80	7.96	5.71	0.11
21.20	8.05	5.79	0.11
21.60	8.13	5.87	0.11
22.00	8.22	5.95	0.11
22.40	8.29	6.02	0.09
22.80	8.35	6.08	0.08
23.20	8.42	6.14	0.08
23.60	8.49	6.20	0.10
24.00	**8.57**	**6.28**	0.11
24.40	8.57	6.28	0.00
24.80	8.57	6.28	0.00
25.20	8.57	6.28	0.00
25.60	8.57	6.28	0.00
26.00	8.57	6.28	0.00
26.40	8.57	6.28	0.00
26.80	8.57	6.28	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	9.46 cfs @	15.85 hrs, Volume=	5.294 af
Outflow	=	9.37 cfs @	17.67 hrs, Volume=	2.608 af, Atten= 1%, Lag= 109.1 min
Primary	=	1.53 cfs @	17.66 hrs, Volume=	1.912 af
Secondary	=	7.84 cfs @	17.67 hrs, Volume=	0.696 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.00 hrs, dt= 0.02 hrs
Peak Elev= 678.42' @ 17.66 hrs Surf.Area= 47,088 sf Storage= 136,494 cf

Plug-Flow detention time= 391.4 min calculated for 2.606 af (49% of inflow)
Center-of-Mass det. time= 204.7 min (1,117.9 - 913.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.53 cfs @ 17.66 hrs HW=678.42' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.53 cfs @ 13.81 fps)


Secondary OutFlow Max=6.28 cfs @ 17.67 hrs HW=678.41' TW=678.27' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Weir Controls 6.26 cfs @ 1.76 fps)
└**4=Orifice/Grate** (Orifice Controls 0.02 cfs @ 1.78 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
3.00	0.06	26	670.00	0.00	0.00	0.00	0.00
4.00	0.46	1,029	670.12	0.03	0.03	0.00	0.00
5.00	0.70	2,763	670.31	0.18	0.18	0.00	0.00
6.00	0.87	4,707	670.51	0.30	0.30	0.00	0.00
7.00	1.19	7,070	670.74	0.40	0.40	0.00	0.00
8.00	1.52	10,513	670.91	0.45	0.45	0.00	0.00
9.00	1.67	14,528	671.10	0.51	0.51	0.00	0.00
10.00	1.82	18,837	671.30	0.56	0.56	0.00	0.00
11.00	2.28	24,049	671.53	0.62	0.62	0.00	0.00
12.00	2.81	30,806	671.83	0.68	0.68	0.00	0.00
13.00	3.85	40,430	672.26	0.77	0.77	0.00	0.00
14.00	5.85	53,829	672.85	0.87	0.87	0.00	0.00
15.00	**8.73**	77,412	673.97	1.03	1.03	0.00	0.00
16.00	**9.34**	106,297	676.02	1.28	1.28	0.00	0.00
17.00	7.05	**131,222**	**677.84**	**1.47**	**1.47**	**0.00**	0.00
18.00	3.82	**135,959**	**678.36**	**6.77**	**1.52**	**5.25**	0.00
19.00	2.75	134,845	678.24	4.92	1.51	3.41	0.00
20.00	2.03	133,894	678.13	1.50	1.50	0.00	0.00
21.00	1.69	133,100	678.04	2.66	1.49	1.17	0.00
22.00	1.64	132,794	678.01	1.49	1.49	0.00	0.00
23.00	1.21	131,633	677.88	1.72	1.48	0.25	0.00
24.00	1.53	130,768	677.79	1.49	1.47	0.03	0.00
25.00	0.01	127,467	677.50	1.48	1.44	0.05	0.00
26.00	0.00	122,200	677.10	1.44	1.40	0.04	0.00
27.00	0.00	117,112	676.75	1.39	1.36	0.02	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	10.30 cfs @	17.67 hrs, Volume=	3.227 af
Outflow	=	10.57 cfs @	17.70 hrs, Volume=	3.225 af, Atten= 0%, Lag= 1.8 min
Primary	=	6.91 cfs @	17.70 hrs, Volume=	2.295 af
Secondary	=	3.89 cfs @	17.62 hrs, Volume=	0.930 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.00 hrs, dt= 0.02 hrs
Peak Elev= 678.42' @ 17.70 hrs Surf.Area= 3,591 sf Storage= 4,648 cf

Plug-Flow detention time= 20.7 min calculated for 3.222 af (100% of inflow)
Center-of-Mass det. time= 20.3 min (981.8 - 961.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=6.70 cfs @ 17.70 hrs HW=678.41' (Free Discharge)
- **1=Orifice/Grate** (Orifice Controls 1.42 cfs @ 6.16 fps)
- **2=Sharp-Crested Rectangular Weir** (Weir Controls 5.28 cfs @ 2.19 fps)


Secondary OutFlow Max=4.66 cfs @ 17.62 hrs HW=678.41' TW=678.34' (Dynamic Tailwater)
- **4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 1.19 fps)
- **5=Sharp-Crested Rectangular Weir** (Weir Controls 4.64 cfs @ 1.30 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
- **3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.04	22	672.35	0.00	0.00	0.00	0.00
4.00	0.20	132	676.65	0.17	0.07	0.10	0.00
5.00	0.34	237	676.77	0.31	0.21	0.11	0.00
6.00	0.44	333	676.84	0.42	0.31	0.11	0.00
7.00	0.63	488	676.94	0.56	0.45	0.11	0.00
8.00	0.81	785	677.08	0.73	0.62	0.11	0.00
9.00	0.90	1,033	677.20	0.84	0.72	0.11	0.00
10.00	0.99	1,254	677.29	0.91	0.80	0.11	0.00
11.00	1.26	1,765	677.49	1.06	0.94	0.12	0.00
12.00	1.55	2,659	677.81	1.28	1.13	0.15	0.00
13.00	1.86	2,893	677.89	1.83	1.17	0.66	0.00
14.00	2.66	3,099	677.96	2.57	1.21	1.36	0.00
15.00	3.72	3,334	678.03	3.70	1.35	2.35	0.00
16.00	3.94	3,379	678.05	3.96	1.44	2.52	0.00
17.00	**3.01**	**3,236**	**678.00**	**3.05**	**1.23**	**1.82**	0.00
18.00	**7.45**	**4,290**	**678.32**	**4.98**	**4.98**	**0.00**	0.00
19.00	4.99	3,931	678.21	3.29	3.29	0.00	0.00
20.00	1.17	3,513	678.09	1.78	1.78	0.00	0.00
21.00	2.15	3,361	678.04	1.41	1.41	0.00	0.00
22.00	0.95	3,216	677.99	1.23	1.23	0.00	0.00
23.00	0.95	2,822	677.87	1.16	1.16	0.00	0.00
24.00	0.93	2,027	677.59	1.00	1.00	0.00	0.00
25.00	0.06	388	676.88	0.36	0.36	0.00	0.00
26.00	0.04	116	676.62	0.05	0.05	0.00	0.00
27.00	0.00	101	676.59	0.03	0.03	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.72 cfs @ 41.20 hrs, Volume= 2.102 af, Depth= 7.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.02	0.00	0.00
2.00	0.07	0.00	0.00
3.00	0.15	0.00	0.00
4.00	0.25	0.00	0.00
5.00	0.36	0.00	0.00
6.00	0.48	0.00	0.02
7.00	0.60	0.02	0.06
8.00	0.72	0.04	0.09
9.00	0.82	0.07	0.10
10.00	0.90	0.10	0.10
11.00	1.00	0.13	0.14
12.00	1.11	0.18	0.18
13.00	1.23	0.24	0.20
14.00	1.35	0.30	0.22
15.00	1.47	0.36	0.24
16.00	1.60	0.43	0.25
17.00	1.72	0.51	0.26
18.00	1.84	0.59	0.28
19.00	1.96	0.67	0.29
20.00	2.08	0.75	0.29
21.00	2.20	0.83	0.30
22.00	2.32	0.92	0.31
23.00	2.44	1.01	0.32
24.00	2.56	1.10	0.32
25.00	2.69	1.20	0.36
26.00	2.84	1.32	0.42
27.00	2.99	1.44	0.44
28.00	3.14	1.56	0.40
29.00	3.26	1.66	0.36
30.00	3.40	1.77	0.40
31.00	3.54	1.90	0.46
32.00	3.72	2.04	0.54
33.00	3.92	2.22	0.65
34.00	4.16	2.42	0.74
35.00	4.40	2.64	0.75
36.00	4.64	2.85	0.76
37.00	4.90	3.08	0.85
38.00	5.19	3.35	0.96
39.00	5.53	3.65	1.14
40.00	5.94	4.04	1.42
41.00	6.44	4.50	**1.70**
42.00	6.95	4.98	**1.69**
43.00	7.44	5.45	1.64
44.00	7.91	5.89	1.50
45.00	8.30	6.27	1.28
46.00	8.64	6.59	1.09
47.00	8.96	6.90	1.09
48.00	**9.28**	**7.21**	1.10
49.00	9.28	7.21	0.00
50.00	9.28	7.21	0.00

Summary for Subcatchment 7S: South Property


Runoff = 3.67 cfs @ 41.40 hrs, Volume= 4.504 af, Depth= 7.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.02	0.00	0.00
2.00	0.07	0.00	0.00
3.00	0.15	0.00	0.00
4.00	0.25	0.00	0.00
5.00	0.36	0.00	0.00
6.00	0.48	0.00	0.03
7.00	0.60	0.02	0.12
8.00	0.72	0.04	0.19
9.00	0.82	0.07	0.21
10.00	0.90	0.10	0.21
11.00	1.00	0.13	0.28
12.00	1.11	0.18	0.37
13.00	1.23	0.24	0.43
14.00	1.35	0.30	0.47
15.00	1.47	0.36	0.51
16.00	1.60	0.43	0.54
17.00	1.72	0.51	0.56
18.00	1.84	0.59	0.59
19.00	1.96	0.67	0.61
20.00	2.08	0.75	0.63
21.00	2.20	0.83	0.65
22.00	2.32	0.92	0.66
23.00	2.44	1.01	0.68
24.00	2.56	1.10	0.69
25.00	2.69	1.20	0.77
26.00	2.84	1.32	0.88
27.00	2.99	1.44	0.95
28.00	3.14	1.56	0.86
29.00	3.26	1.66	0.77
30.00	3.40	1.77	0.85
31.00	3.54	1.90	0.96
32.00	3.72	2.04	1.13
33.00	3.92	2.22	1.36
34.00	4.16	2.42	1.58
35.00	4.40	2.64	1.61
36.00	4.64	2.85	1.63
37.00	4.90	3.08	1.79
38.00	5.19	3.35	2.03
39.00	5.53	3.65	2.37
40.00	5.94	4.04	2.97
41.00	6.44	4.50	**3.59**
42.00	6.95	4.98	**3.62**
43.00	7.44	5.45	3.53
44.00	7.91	5.89	3.27
45.00	8.30	6.27	2.80
46.00	8.64	6.59	2.36
47.00	8.96	6.90	2.34
48.00	**9.28**	**7.21**	2.35
49.00	9.28	7.21	0.02
50.00	9.28	7.21	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.58 cfs @ 41.56 hrs, Volume= 0.696 af, Depth= 6.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.02	0.00	0.00
2.00	0.07	0.00	0.00
3.00	0.15	0.00	0.00
4.00	0.25	0.00	0.00
5.00	0.36	0.00	0.00
6.00	0.48	0.00	0.00
7.00	0.60	0.01	0.01
8.00	0.72	0.02	0.02
9.00	0.82	0.05	0.03
10.00	0.90	0.07	0.03
11.00	1.00	0.10	0.04
12.00	1.11	0.14	0.05
13.00	1.23	0.19	0.06
14.00	1.35	0.24	0.07
15.00	1.47	0.30	0.07
16.00	1.60	0.37	0.08
17.00	1.72	0.43	0.08
18.00	1.84	0.50	0.09
19.00	1.96	0.58	0.09
20.00	2.08	0.65	0.09
21.00	2.20	0.73	0.10
22.00	2.32	0.82	0.10
23.00	2.44	0.90	0.10
24.00	2.56	0.99	0.10
25.00	2.69	1.08	0.11
26.00	2.84	1.19	0.13
27.00	2.99	1.31	0.14
28.00	3.14	1.42	0.13
29.00	3.26	1.52	0.12
30.00	3.40	1.62	0.13
31.00	3.54	1.74	0.15
32.00	3.72	1.89	0.17
33.00	3.92	2.06	0.21
34.00	4.16	2.25	0.24
35.00	4.40	2.46	0.25
36.00	4.64	2.67	0.25
37.00	4.90	2.90	0.27
38.00	5.19	3.15	0.31
39.00	5.53	3.45	0.36
40.00	5.94	3.83	0.45
41.00	6.44	4.28	**0.55**
42.00	6.95	4.76	**0.57**
43.00	7.44	5.22	0.56
44.00	7.91	5.65	0.53
45.00	8.30	6.03	0.45
46.00	8.64	6.34	0.38
47.00	8.96	6.65	0.37
48.00	**9.28**	**6.96**	0.37
49.00	9.28	6.96	0.02
50.00	9.28	6.96	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.27 cfs @ 41.03 hrs, Volume= 0.319 af, Depth= 6.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.02	0.00	0.00
2.00	0.07	0.00	0.00
3.00	0.15	0.00	0.00
4.00	0.25	0.00	0.00
5.00	0.36	0.00	0.00
6.00	0.48	0.00	0.00
7.00	0.60	0.01	0.01
8.00	0.72	0.02	0.01
9.00	0.82	0.05	0.01
10.00	0.90	0.07	0.01
11.00	1.00	0.10	0.02
12.00	1.11	0.14	0.02
13.00	1.23	0.19	0.03
14.00	1.35	0.24	0.03
15.00	1.47	0.30	0.03
16.00	1.60	0.37	0.04
17.00	1.72	0.43	0.04
18.00	1.84	0.50	0.04
19.00	1.96	0.58	0.04
20.00	2.08	0.65	0.04
21.00	2.20	0.73	0.04
22.00	2.32	0.82	0.05
23.00	2.44	0.90	0.05
24.00	2.56	0.99	0.05
25.00	2.69	1.08	0.06
26.00	2.84	1.19	0.06
27.00	2.99	1.31	0.07
28.00	3.14	1.42	0.06
29.00	3.26	1.52	0.05
30.00	3.40	1.62	0.06
31.00	3.54	1.74	0.07
32.00	3.72	1.89	0.08
33.00	3.92	2.06	0.10
34.00	4.16	2.25	0.11
35.00	4.40	2.46	0.12
36.00	4.64	2.67	0.12
37.00	4.90	2.90	0.13
38.00	5.19	3.15	0.15
39.00	5.53	3.45	0.18
40.00	5.94	3.83	0.22
41.00	6.44	4.28	**0.27**
42.00	6.95	4.76	**0.26**
43.00	7.44	5.22	0.25
44.00	7.91	5.65	0.23
45.00	8.30	6.03	0.20
46.00	8.64	6.34	0.17
47.00	8.96	6.65	0.17
48.00	**9.28**	**6.96**	0.17
49.00	9.28	6.96	0.00
50.00	9.28	6.96	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	5.02 cfs @ 41.40 hrs,	Volume=	5.654 af
Outflow	=	4.58 cfs @ 47.01 hrs,	Volume=	2.792 af, Atten= 9%, Lag= 336.6 min
Primary	=	1.50 cfs @ 48.04 hrs,	Volume=	2.515 af
Secondary	=	3.07 cfs @ 47.01 hrs,	Volume=	0.277 af
Tertiary	=	0.00 cfs @ 0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.00 hrs, dt= 0.02 hrs
Peak Elev= 678.19' @ 48.04 hrs Surf.Area= 47,063 sf Storage= 134,407 cf

Plug-Flow detention time= 498.1 min calculated for 2.792 af (49% of inflow)
Center-of-Mass det. time= 34.1 min (2,194.2 - 2,160.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.50 cfs @ 48.04 hrs HW=678.19' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.50 cfs @ 13.62 fps)


Secondary OutFlow Max=2.45 cfs @ 47.01 hrs HW=678.17' TW=678.13' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Weir Controls 2.43 cfs @ 1.10 fps)
└**4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 1.06 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
3.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.00	0	670.00	0.00	0.00	0.00	0.00
5.00	0.00	0	670.00	0.00	0.00	0.00	0.00
6.00	0.03	15	670.00	0.00	0.00	0.00	0.00
7.00	0.19	395	670.04	0.01	0.01	0.00	0.00
8.00	0.30	1,223	670.14	0.05	0.05	0.00	0.00
9.00	0.32	2,065	670.23	0.12	0.12	0.00	0.00
10.00	0.33	2,693	670.30	0.18	0.18	0.00	0.00
11.00	0.40	3,266	670.36	0.22	0.22	0.00	0.00
12.00	0.50	4,004	670.44	0.27	0.27	0.00	0.00
13.00	0.57	4,907	670.53	0.31	0.31	0.00	0.00
14.00	0.61	5,838	670.62	0.35	0.35	0.00	0.00
15.00	0.65	6,775	670.71	0.39	0.39	0.00	0.00
16.00	0.68	7,725	670.78	0.41	0.41	0.00	0.00
17.00	0.71	8,723	670.83	0.42	0.42	0.00	0.00
18.00	0.73	9,762	670.87	0.44	0.44	0.00	0.00
19.00	0.76	10,833	670.93	0.46	0.46	0.00	0.00
20.00	0.78	11,927	670.98	0.47	0.47	0.00	0.00
21.00	0.80	13,038	671.03	0.49	0.49	0.00	0.00
22.00	0.82	14,159	671.09	0.50	0.50	0.00	0.00
23.00	0.83	15,286	671.14	0.52	0.52	0.00	0.00
24.00	0.85	16,418	671.19	0.53	0.53	0.00	0.00
25.00	0.93	17,632	671.25	0.55	0.55	0.00	0.00
26.00	1.05	19,191	671.32	0.57	0.57	0.00	0.00
27.00	1.12	21,095	671.40	0.59	0.59	0.00	0.00
28.00	1.03	22,834	671.48	0.60	0.60	0.00	0.00
29.00	0.93	24,166	671.54	0.62	0.62	0.00	0.00
30.00	1.02	25,380	671.59	0.63	0.63	0.00	0.00
31.00	1.14	26,965	671.66	0.65	0.65	0.00	0.00
32.00	1.32	28,990	671.75	0.67	0.67	0.00	0.00
33.00	1.57	31,751	671.87	0.69	0.69	0.00	0.00
34.00	1.81	35,316	672.03	0.72	0.72	0.00	0.00
35.00	1.84	39,237	672.21	0.76	0.76	0.00	0.00
36.00	1.86	43,121	672.38	0.79	0.79	0.00	0.00
37.00	2.04	47,151	672.55	0.82	0.82	0.00	0.00
38.00	2.30	51,938	672.77	0.85	0.85	0.00	0.00
39.00	2.74	57,620	673.02	0.90	0.90	0.00	0.00
40.00	3.86	66,267	673.42	0.96	0.96	0.00	0.00
41.00	**4.89**	78,408	674.02	1.04	1.04	0.00	0.00
42.00	**4.95**	92,420	674.93	1.16	1.16	0.00	0.00
43.00	4.80	105,570	675.97	1.28	1.28	0.00	0.00
44.00	4.36	117,541	676.78	1.36	1.36	0.00	0.00
45.00	3.58	126,828	677.45	1.43	1.43	0.00	0.00
46.00	3.07	132,648	677.99	2.10	1.49	0.62	0.00
47.00	2.51	134,334	678.18	**4.28**	1.50	**2.77**	0.00
48.00	4.35	**134,162**	**678.16**	1.98	**1.50**	0.48	0.00
49.00	0.02	**130,083**	**677.73**	1.49	**1.46**	0.03	0.00
50.00	0.00	124,767	677.29	1.46	1.42	0.05	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	4.54 cfs @	47.01 hrs, Volume=	3.075 af
Outflow	=	4.87 cfs @	48.00 hrs, Volume=	3.072 af, Atten= 0%, Lag= 59.4 min
Primary	=	3.05 cfs @	48.00 hrs, Volume=	2.241 af
Secondary	=	1.89 cfs @	46.88 hrs, Volume=	0.831 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.00 hrs, dt= 0.02 hrs
Peak Elev= 678.20' @ 48.00 hrs Surf.Area= 3,369 sf Storage= 3,874 cf

Plug-Flow detention time= 22.2 min calculated for 3.070 af (100% of inflow)
Center-of-Mass det. time= 21.4 min (2,241.6 - 2,220.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=2.97 cfs @ 48.00 hrs HW=678.19' (Free Discharge)
- **1=Orifice/Grate** (Orifice Controls 1.32 cfs @ 5.74 fps)
- **2=Sharp-Crested Rectangular Weir** (Weir Controls 1.65 cfs @ 1.46 fps)


Secondary OutFlow Max=2.23 cfs @ 46.88 hrs HW=678.18' TW=678.15' (Dynamic Tailwater)
- **4=Orifice/Grate** (Orifice Controls 0.01 cfs @ 0.90 fps)
- **5=Sharp-Crested Rectangular Weir** (Weir Controls 2.22 cfs @ 0.98 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
- **3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.00	0	670.75	0.00	0.00	0.00	0.00
4.00	0.00	0	670.75	0.00	0.00	0.00	0.00
5.00	0.00	0	670.75	0.00	0.00	0.00	0.00
6.00	0.02	12	671.61	0.00	0.00	0.00	0.00
7.00	0.07	55	674.69	0.06	0.00	0.06	0.00
8.00	0.11	82	676.53	0.10	0.00	0.10	0.00
9.00	0.12	97	676.58	0.12	0.02	0.10	0.00
10.00	0.13	99	676.58	0.12	0.02	0.10	0.00
11.00	0.17	124	676.64	0.16	0.06	0.10	0.00
12.00	0.23	162	676.69	0.22	0.11	0.10	0.00
13.00	0.26	197	676.73	0.26	0.15	0.11	0.00
14.00	0.29	217	676.75	0.28	0.18	0.11	0.00
15.00	0.31	233	676.77	0.31	0.20	0.11	0.00
16.00	0.33	250	676.78	0.32	0.22	0.11	0.00
17.00	0.35	266	676.79	0.34	0.24	0.11	0.00
18.00	0.36	281	676.81	0.36	0.25	0.11	0.00
19.00	0.38	294	676.81	0.37	0.27	0.11	0.00
20.00	0.39	305	676.82	0.38	0.28	0.11	0.00
21.00	0.40	316	676.83	0.40	0.29	0.11	0.00
22.00	0.41	325	676.84	0.41	0.30	0.11	0.00
23.00	0.42	333	676.85	0.42	0.31	0.11	0.00
24.00	0.43	341	676.85	0.43	0.32	0.11	0.00
25.00	0.48	376	676.87	0.46	0.35	0.11	0.00
26.00	0.55	449	676.92	0.53	0.42	0.11	0.00
27.00	0.58	515	676.95	0.58	0.47	0.11	0.00
28.00	0.53	473	676.93	0.55	0.44	0.11	0.00
29.00	0.48	410	676.89	0.49	0.38	0.11	0.00
30.00	0.53	431	676.91	0.51	0.40	0.11	0.00
31.00	0.60	509	676.95	0.58	0.47	0.11	0.00
32.00	0.71	629	677.01	0.66	0.55	0.11	0.00
33.00	0.85	875	677.13	0.77	0.66	0.11	0.00
34.00	0.98	1,203	677.27	0.90	0.78	0.11	0.00
35.00	1.00	1,419	677.36	0.96	0.85	0.12	0.00
36.00	1.01	1,518	677.40	0.99	0.88	0.12	0.00
37.00	1.12	1,677	677.46	1.04	0.92	0.12	0.00
38.00	1.27	2,084	677.61	1.14	1.02	0.12	0.00
39.00	1.50	2,687	677.82	1.32	1.14	0.19	0.00
40.00	1.87	2,895	677.89	1.84	1.17	0.67	0.00
41.00	2.25	3,011	677.93	2.23	1.19	1.04	0.00
42.00	2.26	3,024	677.93	2.26	1.20	1.07	0.00
43.00	2.20	3,014	677.93	2.20	1.19	1.01	0.00
44.00	2.03	2,975	677.92	2.05	1.19	0.86	0.00
45.00	1.73	2,896	677.89	1.76	1.17	0.58	0.00
46.00	2.09	3,210	677.99	1.76	1.23	**0.53**	0.00
47.00	**4.24**	3,569	678.10	1.94	1.94	**0.00**	0.00
48.00	1.95	**3,870**	**678.19**	**4.87**	**3.03**	1.83	0.00
49.00	0.04	1,801	677.51	0.95	0.95	0.00	0.00
50.00	0.00	156	676.69	0.10	0.10	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.22 cfs @ 61.56 hrs, Volume= 2.263 af, Depth= 7.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.01	0.00	0.00
2.00	0.03	0.00	0.00
3.00	0.07	0.00	0.00
4.00	0.13	0.00	0.00
5.00	0.19	0.00	0.00
6.00	0.26	0.00	0.00
7.00	0.34	0.00	0.00
8.00	0.43	0.00	0.00
9.00	0.51	0.00	0.02
10.00	0.60	0.02	0.04
11.00	0.68	0.03	0.06
12.00	0.76	0.05	0.07
13.00	0.84	0.07	0.08
14.00	0.90	0.09	0.07
15.00	0.96	0.12	0.08
16.00	1.02	0.14	0.10
17.00	1.10	0.17	0.12
18.00	1.18	0.21	0.14
19.00	1.27	0.25	0.15
20.00	1.35	0.30	0.16
21.00	1.44	0.34	0.17
22.00	1.52	0.39	0.17
23.00	1.61	0.44	0.18
24.00	1.69	0.49	0.19
25.00	1.78	0.55	0.19
26.00	1.86	0.60	0.20
27.00	1.95	0.66	0.20
28.00	2.03	0.72	0.21
29.00	2.12	0.78	0.21
30.00	2.21	0.84	0.22
31.00	2.29	0.90	0.22
32.00	2.38	0.96	0.22
33.00	2.46	1.03	0.23
34.00	2.55	1.09	0.23
35.00	2.63	1.16	0.23
36.00	2.72	1.22	0.23
37.00	2.81	1.29	0.25
38.00	2.91	1.37	0.28
39.00	3.01	1.46	0.30
40.00	3.12	1.55	0.32
41.00	3.23	1.63	0.30
42.00	3.33	1.72	0.28
43.00	3.42	1.79	0.26
44.00	3.51	1.87	0.27
45.00	3.60	1.95	0.29
46.00	3.71	2.03	0.32
47.00	3.82	2.13	0.34
48.00	3.94	2.24	0.39
49.00	4.09	2.36	0.44
50.00	4.24	2.50	0.50
51.00	4.41	2.65	0.53
52.00	4.58	2.80	0.54
53.00	4.75	2.95	0.54
54.00	4.93	3.11	0.54
55.00	5.10	3.27	0.59
56.00	5.30	3.45	0.64
57.00	5.51	3.64	0.69
58.00	5.74	3.85	0.76
59.00	6.00	4.09	0.89
60.00	6.30	4.37	1.03
61.00	6.65	4.70	**1.17**
62.00	7.01	5.04	**1.22**
63.00	7.37	5.38	1.20
64.00	7.73	5.72	1.18
65.00	8.07	6.05	1.15
66.00	8.39	6.35	1.05
67.00	8.68	6.63	0.95
68.00	8.94	6.87	0.84
69.00	9.17	7.10	0.78
70.00	9.39	7.32	0.78
71.00	9.62	7.54	0.78
72.00	**9.85**	**7.76**	0.78
73.00	9.85	7.76	0.00
74.00	9.85	7.76	0.00
75.00	9.85	7.76	0.00

Summary for Subcatchment 7S: South Property


Runoff = 2.62 cfs @ 61.74 hrs, Volume= 4.848 af, Depth= 7.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.01	0.00	0.00
2.00	0.03	0.00	0.00
3.00	0.07	0.00	0.00
4.00	0.13	0.00	0.00
5.00	0.19	0.00	0.00
6.00	0.26	0.00	0.00
7.00	0.34	0.00	0.00
8.00	0.43	0.00	0.00
9.00	0.51	0.00	0.04
10.00	0.60	0.02	0.09
11.00	0.68	0.03	0.13
12.00	0.76	0.05	0.15
13.00	0.84	0.07	0.16
14.00	0.90	0.09	0.16
15.00	0.96	0.12	0.16
16.00	1.02	0.14	0.20
17.00	1.10	0.17	0.24
18.00	1.18	0.21	0.29
19.00	1.27	0.25	0.32
20.00	1.35	0.30	0.34
21.00	1.44	0.34	0.35
22.00	1.52	0.39	0.37
23.00	1.61	0.44	0.38
24.00	1.69	0.49	0.40
25.00	1.78	0.55	0.41
26.00	1.86	0.60	0.42
27.00	1.95	0.66	0.43
28.00	2.03	0.72	0.44
29.00	2.12	0.78	0.45
30.00	2.21	0.84	0.46
31.00	2.29	0.90	0.47
32.00	2.38	0.96	0.48
33.00	2.46	1.03	0.48
34.00	2.55	1.09	0.49
35.00	2.63	1.16	0.50
36.00	2.72	1.22	0.50
37.00	2.81	1.29	0.54
38.00	2.91	1.37	0.59
39.00	3.01	1.46	0.65
40.00	3.12	1.55	0.69
41.00	3.23	1.63	0.66
42.00	3.33	1.72	0.61
43.00	3.42	1.79	0.57
44.00	3.51	1.87	0.57
45.00	3.60	1.95	0.62
46.00	3.71	2.03	0.67
47.00	3.82	2.13	0.73
48.00	3.94	2.24	0.83
49.00	4.09	2.36	0.94
50.00	4.24	2.50	1.05
51.00	4.41	2.65	1.14
52.00	4.58	2.80	1.15
53.00	4.75	2.95	1.16
54.00	4.93	3.11	1.16
55.00	5.10	3.27	1.24
56.00	5.30	3.45	1.36
57.00	5.51	3.64	1.47
58.00	5.74	3.85	1.60
59.00	6.00	4.09	1.88
60.00	6.30	4.37	2.17
61.00	6.65	4.70	**2.47**
62.00	7.01	5.04	**2.62**
63.00	7.37	5.38	2.57
64.00	7.73	5.72	2.52
65.00	8.07	6.05	2.48
66.00	8.39	6.35	2.29
67.00	8.68	6.63	2.06
68.00	8.94	6.87	1.84
69.00	9.17	7.10	1.66
70.00	9.39	7.32	1.66
71.00	9.62	7.54	1.67
72.00	**9.85**	**7.76**	1.67
73.00	9.85	7.76	0.01
74.00	9.85	7.76	0.00
75.00	9.85	7.76	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.41 cfs @ 62.00 hrs, Volume= 0.750 af, Depth= 7.50"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.01	0.00	0.00
2.00	0.03	0.00	0.00
3.00	0.07	0.00	0.00
4.00	0.13	0.00	0.00
5.00	0.19	0.00	0.00
6.00	0.26	0.00	0.00
7.00	0.34	0.00	0.00
8.00	0.43	0.00	0.00
9.00	0.51	0.00	0.00
10.00	0.60	0.01	0.01
11.00	0.68	0.02	0.01
12.00	0.76	0.03	0.02
13.00	0.84	0.05	0.02
14.00	0.90	0.07	0.02
15.00	0.96	0.08	0.02
16.00	1.02	0.11	0.03
17.00	1.10	0.13	0.03
18.00	1.18	0.17	0.04
19.00	1.27	0.20	0.04
20.00	1.35	0.24	0.05
21.00	1.44	0.28	0.05
22.00	1.52	0.33	0.05
23.00	1.61	0.37	0.06
24.00	1.69	0.42	0.06
25.00	1.78	0.47	0.06
26.00	1.86	0.52	0.06
27.00	1.95	0.57	0.06
28.00	2.03	0.63	0.07
29.00	2.12	0.68	0.07
30.00	2.21	0.74	0.07
31.00	2.29	0.80	0.07
32.00	2.38	0.86	0.07
33.00	2.46	0.92	0.07
34.00	2.55	0.98	0.07
35.00	2.63	1.04	0.07
36.00	2.72	1.10	0.08
37.00	2.81	1.17	0.08
38.00	2.91	1.24	0.09
39.00	3.01	1.32	0.10
40.00	3.12	1.41	0.11
41.00	3.23	1.49	0.10
42.00	3.33	1.57	0.10
43.00	3.42	1.64	0.09
44.00	3.51	1.72	0.09
45.00	3.60	1.79	0.09
46.00	3.71	1.88	0.10
47.00	3.82	1.97	0.11
48.00	3.94	2.07	0.13
49.00	4.09	2.19	0.14
50.00	4.24	2.33	0.16
51.00	4.41	2.47	0.18
52.00	4.58	2.62	0.18
53.00	4.75	2.77	0.18
54.00	4.93	2.92	0.18
55.00	5.10	3.08	0.19
56.00	5.30	3.25	0.21
57.00	5.51	3.44	0.23
58.00	5.74	3.65	0.25
59.00	6.00	3.88	0.29
60.00	6.30	4.16	0.34
61.00	6.65	4.48	0.38
62.00	7.01	4.82	**0.41**
63.00	7.37	5.15	0.41
64.00	7.73	5.49	0.40
65.00	8.07	5.81	0.39
66.00	8.39	6.11	0.37
67.00	8.68	6.39	0.33
68.00	8.94	6.63	0.30
69.00	9.17	6.85	0.27
70.00	9.39	7.07	0.26
71.00	9.62	7.29	0.26
72.00	**9.85**	**7.50**	0.26
73.00	9.85	7.50	0.01
74.00	9.85	7.50	0.00
75.00	9.85	7.50	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.19 cfs @ 61.42 hrs, Volume= 0.344 af, Depth= 7.50"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.00	0.01	0.00	0.00
2.00	0.03	0.00	0.00
3.00	0.07	0.00	0.00
4.00	0.13	0.00	0.00
5.00	0.19	0.00	0.00
6.00	0.26	0.00	0.00
7.00	0.34	0.00	0.00
8.00	0.43	0.00	0.00
9.00	0.51	0.00	0.00
10.00	0.60	0.01	0.00
11.00	0.68	0.02	0.01
12.00	0.76	0.03	0.01
13.00	0.84	0.05	0.01
14.00	0.90	0.07	0.01
15.00	0.96	0.08	0.01
16.00	1.02	0.11	0.01
17.00	1.10	0.13	0.02
18.00	1.18	0.17	0.02
19.00	1.27	0.20	0.02
20.00	1.35	0.24	0.02
21.00	1.44	0.28	0.02
22.00	1.52	0.33	0.02
23.00	1.61	0.37	0.03
24.00	1.69	0.42	0.03
25.00	1.78	0.47	0.03
26.00	1.86	0.52	0.03
27.00	1.95	0.57	0.03
28.00	2.03	0.63	0.03
29.00	2.12	0.68	0.03
30.00	2.21	0.74	0.03
31.00	2.29	0.80	0.03
32.00	2.38	0.86	0.03
33.00	2.46	0.92	0.03
34.00	2.55	0.98	0.03
35.00	2.63	1.04	0.03
36.00	2.72	1.10	0.03
37.00	2.81	1.17	0.04
38.00	2.91	1.24	0.04
39.00	3.01	1.32	0.05
40.00	3.12	1.41	0.05
41.00	3.23	1.49	0.05
42.00	3.33	1.57	0.04
43.00	3.42	1.64	0.04
44.00	3.51	1.72	0.04
45.00	3.60	1.79	0.04
46.00	3.71	1.88	0.05
47.00	3.82	1.97	0.05
48.00	3.94	2.07	0.06
49.00	4.09	2.19	0.07
50.00	4.24	2.33	0.08
51.00	4.41	2.47	0.08
52.00	4.58	2.62	0.08
53.00	4.75	2.77	0.08
54.00	4.93	2.92	0.08
55.00	5.10	3.08	0.09
56.00	5.30	3.25	0.10
57.00	5.51	3.44	0.11
58.00	5.74	3.65	0.12
59.00	6.00	3.88	0.14
60.00	6.30	4.16	0.16
61.00	6.65	4.48	**0.18**
62.00	7.01	4.82	**0.19**
63.00	7.37	5.15	0.19
64.00	7.73	5.49	0.18
65.00	8.07	5.81	0.18
66.00	8.39	6.11	0.16
67.00	8.68	6.39	0.15
68.00	8.94	6.63	0.13
69.00	9.17	6.85	0.12
70.00	9.39	7.07	0.12
71.00	9.62	7.29	0.12
72.00	**9.85**	**7.50**	0.12
73.00	9.85	7.50	0.00
74.00	9.85	7.50	0.00
75.00	9.85	7.50	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	3.28 cfs @	61.80 hrs, Volume=	5.872 af
Outflow	=	1.35 cfs @	72.25 hrs, Volume=	3.484 af, Atten= 59%, Lag= 627.1 min
Primary	=	1.35 cfs @	72.25 hrs, Volume=	3.484 af
Secondary	=	0.00 cfs @	73.58 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.02 hrs
Peak Elev= 676.67' @ 72.25 hrs Surf.Area= 46,894 sf Storage= 116,087 cf

Plug-Flow detention time= 535.9 min calculated for 3.484 af (59% of inflow)
Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.35 cfs @ 72.25 hrs HW=676.67' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.35 cfs @ 12.26 fps)


Secondary OutFlow Max=0.00 cfs @ 73.58 hrs HW=676.31' TW=676.31' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.00	0	670.00	0.00	0.00	0.00	0.00
6.00	0.00	0	670.00	0.00	0.00	0.00	0.00
8.00	0.00	0	670.00	0.00	0.00	0.00	0.00
10.00	0.14	433	670.05	0.01	0.01	0.00	0.00
12.00	0.25	1,645	670.18	0.08	0.08	0.00	0.00
14.00	0.27	2,618	670.29	0.17	0.17	0.00	0.00
16.00	0.32	3,210	670.36	0.22	0.22	0.00	0.00
18.00	0.41	4,055	670.44	0.27	0.27	0.00	0.00
20.00	0.46	5,109	670.55	0.32	0.32	0.00	0.00
22.00	0.50	6,124	670.65	0.36	0.36	0.00	0.00
24.00	0.53	7,098	670.74	0.40	0.40	0.00	0.00
26.00	0.56	8,082	670.79	0.41	0.41	0.00	0.00
28.00	0.58	9,120	670.84	0.43	0.43	0.00	0.00
30.00	0.60	10,189	670.90	0.45	0.45	0.00	0.00
32.00	0.61	11,272	670.95	0.46	0.46	0.00	0.00
34.00	0.63	12,356	671.00	0.48	0.48	0.00	0.00
36.00	0.64	13,432	671.05	0.49	0.49	0.00	0.00
38.00	0.74	14,735	671.11	0.51	0.51	0.00	0.00
40.00	0.85	16,710	671.20	0.54	0.54	0.00	0.00
42.00	0.76	18,588	671.29	0.56	0.56	0.00	0.00
44.00	0.71	19,700	671.34	0.57	0.57	0.00	0.00
46.00	0.83	21,083	671.40	0.59	0.59	0.00	0.00
48.00	1.00	23,268	671.50	0.61	0.61	0.00	0.00
50.00	1.24	26,807	671.65	0.64	0.64	0.00	0.00
52.00	1.34	31,487	671.86	0.69	0.69	0.00	0.00
54.00	1.36	36,110	672.07	0.73	0.73	0.00	0.00
56.00	1.57	41,120	672.29	0.77	0.77	0.00	0.00
58.00	1.84	47,590	672.57	0.82	0.82	0.00	0.00
60.00	**2.45**	56,843	672.99	0.89	0.89	0.00	0.00
62.00	**3.27**	71,303	673.66	0.99	0.99	0.00	0.00
64.00	3.13	86,821	674.51	1.11	1.11	0.00	0.00
66.00	2.73	99,979	675.57	1.23	1.23	0.00	0.00
68.00	2.04	107,944	676.13	1.30	1.30	0.00	0.00
70.00	1.85	112,110	676.40	1.33	1.33	0.00	0.00
72.00	1.85	**115,774**	**676.65**	**1.35**	**1.35**	**0.00**	0.00
74.00	0.00	**108,742**	**676.18**	**1.30**	**1.30**	**0.00**	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	1.63 cfs @	61.78 hrs, Volume=	3.013 af
Outflow	=	1.63 cfs @	61.83 hrs, Volume=	3.011 af, Atten= 0%, Lag= 3.1 min
Primary	=	1.16 cfs @	61.89 hrs, Volume=	2.332 af
Secondary	=	0.47 cfs @	61.80 hrs, Volume=	0.679 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.02 hrs
Peak Elev= 677.87' @ 61.89 hrs Surf.Area= 3,030 sf Storage= 2,824 cf

Plug-Flow detention time= 23.3 min calculated for 3.011 af (100% of inflow)
Center-of-Mass det. time= 22.7 min (3,238.0 - 3,215.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.16 cfs @ 61.89 hrs HW=677.87' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.16 cfs @ 5.04 fps)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.47 cfs @ 61.80 hrs HW=677.87' TW=673.58' (Dynamic Tailwater)
└**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.97 fps)
└**5=Sharp-Crested Rectangular Weir** (Weir Controls 0.35 cfs @ 0.86 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
4.00	0.00	0	670.75	0.00	0.00	0.00	0.00
6.00	0.00	0	670.75	0.00	0.00	0.00	0.00
8.00	0.00	0	670.76	0.00	0.00	0.00	0.00
10.00	0.05	49	674.23	0.05	0.00	0.05	0.00
12.00	0.09	70	675.77	0.09	0.00	0.09	0.00
14.00	0.10	76	676.20	0.10	0.00	0.10	0.00
16.00	0.12	94	676.57	0.12	0.01	0.10	0.00
18.00	0.18	131	676.65	0.17	0.07	0.10	0.00
20.00	0.21	153	676.68	0.20	0.10	0.10	0.00
22.00	0.23	169	676.70	0.22	0.12	0.10	0.00
24.00	0.24	184	676.72	0.24	0.14	0.10	0.00
26.00	0.26	197	676.73	0.26	0.15	0.11	0.00
28.00	0.27	207	676.74	0.27	0.17	0.11	0.00
30.00	0.28	216	676.75	0.28	0.18	0.11	0.00
32.00	0.29	224	676.76	0.29	0.19	0.11	0.00
34.00	0.30	230	676.76	0.30	0.20	0.11	0.00
36.00	0.31	236	676.77	0.31	0.20	0.11	0.00
38.00	0.37	282	676.81	0.36	0.25	0.11	0.00
40.00	0.43	341	676.85	0.43	0.32	0.11	0.00
42.00	0.38	305	676.82	0.39	0.28	0.11	0.00
44.00	0.35	271	676.80	0.35	0.24	0.11	0.00
46.00	0.42	329	676.84	0.41	0.31	0.11	0.00
48.00	0.52	420	676.90	0.50	0.39	0.11	0.00
50.00	0.66	584	676.99	0.63	0.52	0.11	0.00
52.00	0.72	737	677.06	0.71	0.60	0.11	0.00
54.00	0.73	766	677.08	0.72	0.61	0.11	0.00
56.00	0.85	954	677.16	0.80	0.69	0.11	0.00
58.00	1.01	1,333	677.32	0.94	0.82	0.11	0.00
60.00	**1.37**	**2,293**	**677.69**	**1.18**	**1.06**	**0.12**	0.00
62.00	**1.63**	**2,824**	**677.87**	**1.63**	**1.16**	**0.47**	0.00
64.00	1.58	2,809	677.86	1.58	1.16	0.42	0.00
66.00	1.42	2,759	677.85	1.44	1.15	0.29	0.00
68.00	1.14	2,592	677.79	1.20	1.12	0.08	0.00
70.00	1.04	2,060	677.60	1.08	1.01	0.06	0.00
72.00	1.04	1,956	677.56	1.04	0.99	0.06	0.00
74.00	0.00	76	676.19	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.80 cfs @ 102.38 hrs, Volume= 2.492 af, Depth= 8.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.28	0.00	0.00
12.00	0.39	0.00	0.00
14.00	0.50	0.00	0.01
16.00	0.61	0.02	0.03
18.00	0.72	0.04	0.05
20.00	0.83	0.07	0.05
22.00	0.92	0.10	0.05
24.00	1.00	0.13	0.05
26.00	1.08	0.17	0.06
28.00	1.17	0.21	0.08
30.00	1.28	0.26	0.10
32.00	1.39	0.32	0.11
34.00	1.50	0.38	0.11
36.00	1.61	0.44	0.12
38.00	1.72	0.51	0.12
40.00	1.83	0.58	0.13
42.00	1.94	0.66	0.13
44.00	2.05	0.73	0.14
46.00	2.17	0.81	0.14
48.00	2.28	0.89	0.14
50.00	2.39	0.97	0.14
52.00	2.50	1.05	0.15
54.00	2.61	1.14	0.15
56.00	2.72	1.23	0.15
58.00	2.83	1.31	0.15
60.00	2.94	1.40	0.16
62.00	3.06	1.49	0.17
64.00	3.19	1.60	0.19
66.00	3.33	1.72	0.21
68.00	3.47	1.84	0.20
70.00	3.60	1.95	0.19
72.00	3.72	2.04	0.17
74.00	3.84	2.15	0.18
76.00	3.97	2.26	0.20
78.00	4.11	2.38	0.23
80.00	4.27	2.52	0.26
82.00	4.45	2.68	0.30
84.00	4.66	2.87	0.35
86.00	4.89	3.07	0.35
88.00	5.11	3.27	0.36
90.00	5.33	3.47	0.36
92.00	5.56	3.69	0.39
94.00	5.82	3.93	0.44
96.00	6.11	4.19	0.48
98.00	6.43	4.50	0.58
100.00	6.82	4.86	0.68
102.00	7.27	5.29	**0.79**
104.00	7.75	5.74	**0.79**
106.00	8.21	6.18	0.77
108.00	8.66	6.61	0.76
110.00	9.08	7.01	0.68
112.00	9.45	7.37	0.60
114.00	9.77	7.68	0.52
116.00	10.07	7.97	0.51
118.00	10.36	8.26	0.51
120.00	**10.66**	**8.54**	0.51
122.00	10.66	8.54	0.00
124.00	10.66	8.54	0.00
126.00	10.66	8.54	0.00
128.00	10.66	8.54	0.00
130.00	10.66	8.54	0.00

Summary for Subcatchment 7S: South Property


Runoff = 1.72 cfs @ 102.58 hrs, Volume= 5.340 af, Depth= 8.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.28	0.00	0.00
12.00	0.39	0.00	0.00
14.00	0.50	0.00	0.03
16.00	0.61	0.02	0.07
18.00	0.72	0.04	0.10
20.00	0.83	0.07	0.11
22.00	0.92	0.10	0.12
24.00	1.00	0.13	0.11
26.00	1.08	0.17	0.14
28.00	1.17	0.21	0.17
30.00	1.28	0.26	0.21
32.00	1.39	0.32	0.23
34.00	1.50	0.38	0.24
36.00	1.61	0.44	0.25
38.00	1.72	0.51	0.26
40.00	1.83	0.58	0.27
42.00	1.94	0.66	0.28
44.00	2.05	0.73	0.29
46.00	2.17	0.81	0.30
48.00	2.28	0.89	0.30
50.00	2.39	0.97	0.31
52.00	2.50	1.05	0.32
54.00	2.61	1.14	0.32
56.00	2.72	1.23	0.33
58.00	2.83	1.31	0.33
60.00	2.94	1.40	0.34
62.00	3.06	1.49	0.37
64.00	3.19	1.60	0.41
66.00	3.33	1.72	0.46
68.00	3.47	1.84	0.44
70.00	3.60	1.95	0.40
72.00	3.72	2.04	0.37
74.00	3.84	2.15	0.39
76.00	3.97	2.26	0.44
78.00	4.11	2.38	0.48
80.00	4.27	2.52	0.56
82.00	4.45	2.68	0.65
84.00	4.66	2.87	0.73
86.00	4.89	3.07	0.76
88.00	5.11	3.27	0.76
90.00	5.33	3.47	0.77
92.00	5.56	3.69	0.84
94.00	5.82	3.93	0.93
96.00	6.11	4.19	1.02
98.00	6.43	4.50	1.22
100.00	6.82	4.86	1.45
102.00	7.27	5.29	**1.68**
104.00	7.75	5.74	**1.69**
106.00	8.21	6.18	1.66
108.00	8.66	6.61	1.62
110.00	9.08	7.01	1.47
112.00	9.45	7.37	1.29
114.00	9.77	7.68	1.12
116.00	10.07	7.97	1.08
118.00	10.36	8.26	1.09
120.00	**10.66**	**8.54**	1.09
122.00	10.66	8.54	0.00
124.00	10.66	8.54	0.00
126.00	10.66	8.54	0.00
128.00	10.66	8.54	0.00
130.00	10.66	8.54	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.27 cfs @ 102.74 hrs, Volume= 0.828 af, Depth= 8.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.28	0.00	0.00
12.00	0.39	0.00	0.00
14.00	0.50	0.00	0.00
16.00	0.61	0.01	0.01
18.00	0.72	0.02	0.01
20.00	0.83	0.05	0.01
22.00	0.92	0.07	0.02
24.00	1.00	0.10	0.02
26.00	1.08	0.13	0.02
28.00	1.17	0.16	0.02
30.00	1.28	0.21	0.03
32.00	1.39	0.26	0.03
34.00	1.50	0.31	0.03
36.00	1.61	0.37	0.04
38.00	1.72	0.44	0.04
40.00	1.83	0.50	0.04
42.00	1.94	0.57	0.04
44.00	2.05	0.64	0.04
46.00	2.17	0.71	0.04
48.00	2.28	0.79	0.05
50.00	2.39	0.86	0.05
52.00	2.50	0.94	0.05
54.00	2.61	1.02	0.05
56.00	2.72	1.10	0.05
58.00	2.83	1.19	0.05
60.00	2.94	1.27	0.05
62.00	3.06	1.36	0.06
64.00	3.19	1.46	0.06
66.00	3.33	1.57	0.07
68.00	3.47	1.69	0.07
70.00	3.60	1.79	0.06
72.00	3.72	1.89	0.06
74.00	3.84	1.99	0.06
76.00	3.97	2.09	0.07
78.00	4.11	2.21	0.07
80.00	4.27	2.35	0.09
82.00	4.45	2.51	0.10
84.00	4.66	2.69	0.11
86.00	4.89	2.88	0.12
88.00	5.11	3.08	0.12
90.00	5.33	3.28	0.12
92.00	5.56	3.49	0.13
94.00	5.82	3.72	0.15
96.00	6.11	3.98	0.16
98.00	6.43	4.28	0.19
100.00	6.82	4.64	0.23
102.00	7.27	5.06	**0.26**
104.00	7.75	5.51	**0.27**
106.00	8.21	5.94	0.26
108.00	8.66	6.37	0.26
110.00	9.08	6.77	0.23
112.00	9.45	7.12	0.21
114.00	9.77	7.43	0.18
116.00	10.07	7.71	0.17
118.00	10.36	8.00	0.17
120.00	**10.66**	**8.28**	0.17
122.00	10.66	8.28	0.00
124.00	10.66	8.28	0.00
126.00	10.66	8.28	0.00
128.00	10.66	8.28	0.00
130.00	10.66	8.28	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.12 cfs @ 102.22 hrs, Volume= 0.380 af, Depth= 8.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.28	0.00	0.00
12.00	0.39	0.00	0.00
14.00	0.50	0.00	0.00
16.00	0.61	0.01	0.00
18.00	0.72	0.02	0.01
20.00	0.83	0.05	0.01
22.00	0.92	0.07	0.01
24.00	1.00	0.10	0.01
26.00	1.08	0.13	0.01
28.00	1.17	0.16	0.01
30.00	1.28	0.21	0.01
32.00	1.39	0.26	0.01
34.00	1.50	0.31	0.02
36.00	1.61	0.37	0.02
38.00	1.72	0.44	0.02
40.00	1.83	0.50	0.02
42.00	1.94	0.57	0.02
44.00	2.05	0.64	0.02
46.00	2.17	0.71	0.02
48.00	2.28	0.79	0.02
50.00	2.39	0.86	0.02
52.00	2.50	0.94	0.02
54.00	2.61	1.02	0.02
56.00	2.72	1.10	0.02
58.00	2.83	1.19	0.02
60.00	2.94	1.27	0.02
62.00	3.06	1.36	0.03
64.00	3.19	1.46	0.03
66.00	3.33	1.57	0.03
68.00	3.47	1.69	0.03
70.00	3.60	1.79	0.03
72.00	3.72	1.89	0.03
74.00	3.84	1.99	0.03
76.00	3.97	2.09	0.03
78.00	4.11	2.21	0.03
80.00	4.27	2.35	0.04
82.00	4.45	2.51	0.05
84.00	4.66	2.69	0.05
86.00	4.89	2.88	0.05
88.00	5.11	3.08	0.05
90.00	5.33	3.28	0.06
92.00	5.56	3.49	0.06
94.00	5.82	3.72	0.07
96.00	6.11	3.98	0.07
98.00	6.43	4.28	0.09
100.00	6.82	4.64	0.11
102.00	7.27	5.06	**0.12**
104.00	7.75	5.51	**0.12**
106.00	8.21	5.94	0.12
108.00	8.66	6.37	0.12
110.00	9.08	6.77	0.11
112.00	9.45	7.12	0.09
114.00	9.77	7.43	0.08
116.00	10.07	7.71	0.08
118.00	10.36	8.00	0.08
120.00	**10.66**	**8.28**	0.08
122.00	10.66	8.28	0.00
124.00	10.66	8.28	0.00
126.00	10.66	8.28	0.00
128.00	10.66	8.28	0.00
130.00	10.66	8.28	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.96 cfs @ 102.58 hrs,	Volume=	6.603 af
Outflow	=	1.11 cfs @ 120.18 hrs,	Volume=	5.372 af, Atten= 43%, Lag= 1,055.9 min
Primary	=	1.11 cfs @ 120.18 hrs,	Volume=	5.372 af
Secondary	=	0.01 cfs @ 124.47 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.02 hrs
Peak Elev= 674.55' @ 120.18 hrs Surf.Area= 31,393 sf Storage= 87,474 cf

Plug-Flow detention time= 597.1 min calculated for 5.372 af (81% of inflow)
Center-of-Mass det. time= 204.3 min (5,370.2 - 5,165.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=1.11 cfs @ 120.18 hrs HW=674.55' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 1.11 cfs @ 10.06 fps)


Secondary OutFlow Max=0.00 cfs @ 124.47 hrs HW=673.71' TW=673.71' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	0.00	**0.00**
14.00	0.03	63	670.01	0.00	0.00	0.00	0.00
18.00	0.16	1,316	670.15	0.05	0.05	0.00	0.00
22.00	0.19	2,430	670.27	0.15	0.15	0.00	0.00
26.00	0.22	2,798	670.31	0.19	0.19	0.00	0.00
30.00	0.32	3,651	670.40	0.25	0.25	0.00	0.00
34.00	0.36	4,631	670.50	0.30	0.30	0.00	0.00
38.00	0.38	5,423	670.58	0.33	0.33	0.00	0.00
42.00	0.40	6,101	670.65	0.36	0.36	0.00	0.00
46.00	0.42	6,697	670.70	0.38	0.38	0.00	0.00
50.00	0.44	7,226	670.75	0.40	0.40	0.00	0.00
54.00	0.45	7,767	670.78	0.41	0.41	0.00	0.00
58.00	0.46	8,337	670.81	0.42	0.42	0.00	0.00
62.00	0.50	9,009	670.84	0.43	0.43	0.00	0.00
66.00	0.59	10,556	670.91	0.45	0.45	0.00	0.00
70.00	0.53	12,089	670.99	0.48	0.48	0.00	0.00
74.00	0.53	12,543	671.01	0.48	0.48	0.00	0.00
78.00	0.62	13,757	671.07	0.50	0.50	0.00	0.00
82.00	0.80	16,515	671.19	0.53	0.53	0.00	0.00
86.00	0.92	21,126	671.40	0.59	0.59	0.00	0.00
90.00	0.93	25,640	671.60	0.63	0.63	0.00	0.00
94.00	1.11	30,754	671.83	0.68	0.68	0.00	0.00
98.00	1.42	38,229	672.16	0.75	0.75	0.00	0.00
102.00	**1.92**	50,849	672.72	0.85	0.85	0.00	0.00
106.00	**1.89**	65,683	673.40	0.95	0.95	0.00	0.00
110.00	1.68	77,643	673.98	1.04	1.04	0.00	0.00
114.00	1.30	83,817	674.32	1.08	1.08	0.00	0.00
118.00	1.26	**86,282**	**674.47**	**1.10**	**1.10**	0.00	0.00
122.00	0.00	**81,406**	**674.18**	**1.06**	**1.06**	**0.00**	0.00
126.00	0.00	66,857	673.45	0.96	0.96	**0.00**	0.00
130.00	0.00	53,701	672.85	0.87	0.87	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	1.07 cfs @ 102.52 hrs,	Volume=	3.321 af
Outflow	=	1.05 cfs @ 104.35 hrs,	Volume=	3.320 af, Atten= 2%, Lag= 110.2 min
Primary	=	0.94 cfs @ 104.35 hrs,	Volume=	2.435 af
Secondary	=	0.12 cfs @ 104.35 hrs,	Volume=	0.884 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.02 hrs
Peak Elev= 677.48' @ 104.35 hrs Surf.Area= 2,612 sf Storage= 1,743 cf

Plug-Flow detention time= 18.1 min calculated for 3.320 af (100% of inflow)
Center-of-Mass det. time= 17.6 min (5,335.1 - 5,317.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.94 cfs @ 104.35 hrs HW=677.48' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.94 cfs @ 4.07 fps)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.12 cfs @ 104.35 hrs HW=677.48' TW=673.13' (Dynamic Tailwater)
└**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.54 fps)
└**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
└**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
14.00	0.01	35	673.22	0.00	0.00	0.00	0.00
18.00	0.06	52	674.48	0.06	0.00	0.06	0.00
22.00	0.07	59	674.97	0.07	0.00	0.07	0.00
26.00	0.08	65	675.42	0.08	0.00	0.08	0.00
30.00	0.13	98	676.58	0.12	0.02	0.10	0.00
34.00	0.15	111	676.62	0.14	0.04	0.10	0.00
38.00	0.16	123	676.64	0.16	0.06	0.10	0.00
42.00	0.17	133	676.65	0.17	0.07	0.10	0.00
46.00	0.18	140	676.66	0.18	0.08	0.10	0.00
50.00	0.19	145	676.67	0.19	0.09	0.10	0.00
54.00	0.20	150	676.68	0.20	0.09	0.10	0.00
58.00	0.20	154	676.68	0.20	0.10	0.10	0.00
62.00	0.23	171	676.70	0.23	0.12	0.10	0.00
66.00	0.28	215	676.75	0.28	0.18	0.11	0.00
70.00	0.25	192	676.73	0.25	0.15	0.11	0.00
74.00	0.25	184	676.72	0.24	0.14	0.10	0.00
78.00	0.30	227	676.76	0.30	0.19	0.11	0.00
82.00	0.40	316	676.83	0.40	0.29	0.11	0.00
86.00	0.47	388	676.88	0.47	0.36	0.11	0.00
90.00	0.48	395	676.88	0.48	0.37	0.11	0.00
94.00	0.58	503	676.95	0.57	0.46	0.11	0.00
98.00	0.77	777	677.08	0.73	0.62	0.11	0.00
102.00	**1.05**	**1,506**	**677.39**	**0.99**	**0.87**	**0.12**	0.00
106.00	**1.04**	**1,708**	**677.47**	**1.05**	**0.93**	**0.12**	0.00
110.00	0.92	1,425	677.36	0.96	0.85	0.11	0.00
114.00	0.70	811	677.10	0.73	0.63	0.10	0.00
118.00	0.68	707	677.05	0.68	0.58	0.09	0.00
122.00	0.00	48	674.19	0.00	0.00	0.00	0.00
126.00	0.00	39	673.50	0.00	0.00	0.00	0.00
130.00	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.48 cfs @ 204.42 hrs, Volume= 3.058 af, Depth=10.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.09	0.00	0.00
14.00	0.18	0.00	0.00
18.00	0.28	0.00	0.00
22.00	0.40	0.00	0.00
26.00	0.53	0.01	0.01
30.00	0.66	0.03	0.02
34.00	0.79	0.06	0.03
38.00	0.92	0.10	0.04
42.00	1.04	0.15	0.04
46.00	1.14	0.19	0.04
50.00	1.23	0.24	0.04
54.00	1.33	0.29	0.05
58.00	1.45	0.35	0.06
62.00	1.58	0.43	0.07
66.00	1.71	0.51	0.07
70.00	1.84	0.59	0.08
74.00	1.98	0.68	0.08
78.00	2.11	0.77	0.08
82.00	2.24	0.86	0.08
86.00	2.37	0.96	0.09
90.00	2.50	1.06	0.09
94.00	2.64	1.16	0.09
98.00	2.77	1.26	0.09
102.00	2.90	1.37	0.09
106.00	3.03	1.47	0.09
110.00	3.16	1.58	0.10
114.00	3.29	1.69	0.10
118.00	3.43	1.80	0.10
122.00	3.56	1.91	0.10
126.00	3.71	2.03	0.11
130.00	3.87	2.17	0.13
134.00	4.04	2.32	0.13
138.00	4.20	2.46	0.12
142.00	4.35	2.59	0.11
146.00	4.48	2.71	0.11
150.00	4.63	2.84	0.12
154.00	4.79	2.98	0.13
158.00	4.97	3.14	0.15
162.00	5.17	3.33	0.17
166.00	5.41	3.54	0.20
170.00	5.67	3.78	0.21
174.00	5.93	4.03	0.22
178.00	6.19	4.27	0.22
182.00	6.46	4.52	0.23
186.00	6.75	4.80	0.25
190.00	7.08	5.10	0.28
194.00	7.43	5.44	0.32
198.00	7.86	5.84	0.38
202.00	8.35	6.32	**0.45**
206.00	8.91	6.85	**0.48**
210.00	9.47	7.39	0.47
214.00	10.01	7.91	0.46
218.00	10.53	8.42	0.43
222.00	11.00	8.88	0.38
226.00	11.41	9.28	0.33
230.00	11.77	9.63	0.30
234.00	12.12	9.97	0.30
238.00	**12.47**	**10.31**	0.30
242.00	**12.65**	**10.49**	0.00
246.00	12.65	10.49	0.00
250.00	12.65	10.49	0.00

Summary for Subcatchment 7S: South Property


Runoff = 1.04 cfs @ 204.56 hrs, Volume= 6.554 af, Depth=10.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.09	0.00	0.00
14.00	0.18	0.00	0.00
18.00	0.28	0.00	0.00
22.00	0.40	0.00	0.00
26.00	0.53	0.01	0.02
30.00	0.66	0.03	0.05
34.00	0.79	0.06	0.07
38.00	0.92	0.10	0.08
42.00	1.04	0.15	0.09
46.00	1.14	0.19	0.08
50.00	1.23	0.24	0.09
54.00	1.33	0.29	0.11
58.00	1.45	0.35	0.13
62.00	1.58	0.43	0.15
66.00	1.71	0.51	0.16
70.00	1.84	0.59	0.16
74.00	1.98	0.68	0.17
78.00	2.11	0.77	0.17
82.00	2.24	0.86	0.18
86.00	2.37	0.96	0.18
90.00	2.50	1.06	0.19
94.00	2.64	1.16	0.19
98.00	2.77	1.26	0.19
102.00	2.90	1.37	0.20
106.00	3.03	1.47	0.20
110.00	3.16	1.58	0.20
114.00	3.29	1.69	0.21
118.00	3.43	1.80	0.21
122.00	3.56	1.91	0.22
126.00	3.71	2.03	0.25
130.00	3.87	2.17	0.27
134.00	4.04	2.32	0.28
138.00	4.20	2.46	0.26
142.00	4.35	2.59	0.23
146.00	4.48	2.71	0.23
150.00	4.63	2.84	0.26
154.00	4.79	2.98	0.28
158.00	4.97	3.14	0.32
162.00	5.17	3.33	0.37
166.00	5.41	3.54	0.43
170.00	5.67	3.78	0.46
174.00	5.93	4.03	0.46
178.00	6.19	4.27	0.46
182.00	6.46	4.52	0.49
186.00	6.75	4.80	0.54
190.00	7.08	5.10	0.60
194.00	7.43	5.44	0.68
198.00	7.86	5.84	0.82
202.00	8.35	6.32	**0.96**
206.00	8.91	6.85	**1.03**
210.00	9.47	7.39	1.00
214.00	10.01	7.91	0.98
218.00	10.53	8.42	0.92
222.00	11.00	8.88	0.82
226.00	11.41	9.28	0.71
230.00	11.77	9.63	0.65
234.00	12.12	9.97	0.65
238.00	**12.47**	**10.31**	0.65
242.00	**12.65**	**10.49**	0.00
246.00	12.65	10.49	0.00
250.00	12.65	10.49	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.16 cfs @ 204.78 hrs, Volume= 1.021 af, Depth=10.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.09	0.00	0.00
14.00	0.18	0.00	0.00
18.00	0.28	0.00	0.00
22.00	0.40	0.00	0.00
26.00	0.53	0.00	0.00
30.00	0.66	0.01	0.01
34.00	0.79	0.04	0.01
38.00	0.92	0.07	0.01
42.00	1.04	0.11	0.01
46.00	1.14	0.15	0.01
50.00	1.23	0.19	0.01
54.00	1.33	0.23	0.02
58.00	1.45	0.29	0.02
62.00	1.58	0.36	0.02
66.00	1.71	0.43	0.02
70.00	1.84	0.51	0.02
74.00	1.98	0.59	0.02
78.00	2.11	0.67	0.03
82.00	2.24	0.76	0.03
86.00	2.37	0.85	0.03
90.00	2.50	0.94	0.03
94.00	2.64	1.04	0.03
98.00	2.77	1.14	0.03
102.00	2.90	1.24	0.03
106.00	3.03	1.34	0.03
110.00	3.16	1.44	0.03
114.00	3.29	1.54	0.03
118.00	3.43	1.65	0.03
122.00	3.56	1.76	0.03
126.00	3.71	1.88	0.04
130.00	3.87	2.01	0.04
134.00	4.04	2.15	0.04
138.00	4.20	2.29	0.04
142.00	4.35	2.42	0.04
146.00	4.48	2.53	0.04
150.00	4.63	2.66	0.04
154.00	4.79	2.80	0.04
158.00	4.97	2.96	0.05
162.00	5.17	3.14	0.06
166.00	5.41	3.35	0.07
170.00	5.67	3.58	0.07
174.00	5.93	3.82	0.07
178.00	6.19	4.06	0.07
182.00	6.46	4.31	0.08
186.00	6.75	4.58	0.09
190.00	7.08	4.88	0.09
194.00	7.43	5.21	0.11
198.00	7.86	5.61	0.13
202.00	8.35	6.08	**0.15**
206.00	8.91	6.61	**0.16**
210.00	9.47	7.14	0.16
214.00	10.01	7.66	0.16
218.00	10.53	8.16	0.15
222.00	11.00	8.62	0.13
226.00	11.41	9.01	0.11
230.00	11.77	9.36	0.10
234.00	12.12	9.70	0.10
238.00	**12.47**	**10.04**	0.10
242.00	**12.65**	**10.21**	0.00
246.00	12.65	10.21	0.00
250.00	12.65	10.21	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.08 cfs @ 204.21 hrs, Volume= 0.468 af, Depth=10.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.02 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.09	0.00	0.00
14.00	0.18	0.00	0.00
18.00	0.28	0.00	0.00
22.00	0.40	0.00	0.00
26.00	0.53	0.00	0.00
30.00	0.66	0.01	0.00
34.00	0.79	0.04	0.00
38.00	0.92	0.07	0.01
42.00	1.04	0.11	0.01
46.00	1.14	0.15	0.01
50.00	1.23	0.19	0.01
54.00	1.33	0.23	0.01
58.00	1.45	0.29	0.01
62.00	1.58	0.36	0.01
66.00	1.71	0.43	0.01
70.00	1.84	0.51	0.01
74.00	1.98	0.59	0.01
78.00	2.11	0.67	0.01
82.00	2.24	0.76	0.01
86.00	2.37	0.85	0.01
90.00	2.50	0.94	0.01
94.00	2.64	1.04	0.01
98.00	2.77	1.14	0.01
102.00	2.90	1.24	0.01
106.00	3.03	1.34	0.01
110.00	3.16	1.44	0.01
114.00	3.29	1.54	0.01
118.00	3.43	1.65	0.01
122.00	3.56	1.76	0.02
126.00	3.71	1.88	0.02
130.00	3.87	2.01	0.02
134.00	4.04	2.15	0.02
138.00	4.20	2.29	0.02
142.00	4.35	2.42	0.02
146.00	4.48	2.53	0.02
150.00	4.63	2.66	0.02
154.00	4.79	2.80	0.02
158.00	4.97	2.96	0.02
162.00	5.17	3.14	0.03
166.00	5.41	3.35	0.03
170.00	5.67	3.58	0.03
174.00	5.93	3.82	0.03
178.00	6.19	4.06	0.03
182.00	6.46	4.31	0.04
186.00	6.75	4.58	0.04
190.00	7.08	4.88	0.04
194.00	7.43	5.21	0.05
198.00	7.86	5.61	0.06
202.00	8.35	6.08	**0.07**
206.00	8.91	6.61	**0.07**
210.00	9.47	7.14	0.07
214.00	10.01	7.66	0.07
218.00	10.53	8.16	0.07
222.00	11.00	8.62	0.06
226.00	11.41	9.01	0.05
230.00	11.77	9.36	0.05
234.00	12.12	9.70	0.05
238.00	**12.47**	**10.04**	0.05
242.00	**12.65**	**10.21**	0.00
246.00	12.65	10.21	0.00
250.00	12.65	10.21	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.22 cfs @ 204.56 hrs,	Volume=	8.721 af
Outflow	=	0.89 cfs @ 225.23 hrs,	Volume=	8.092 af, Atten= 27%, Lag= 1,240.6 min
Primary	=	0.89 cfs @ 225.23 hrs,	Volume=	8.092 af
Secondary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.02 hrs
Peak Elev= 673.01' @ 225.23 hrs Surf.Area= 31,038 sf Storage= 57,307 cf

Plug-Flow detention time= 552.9 min calculated for 8.092 af (93% of inflow)
Center-of-Mass det. time= 239.6 min (10,352.0 - 10,112.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)**Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.60'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.89 cfs @ 225.23 hrs HW=673.01' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.89 cfs @ 8.09 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
└**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
20.00	0.00	0	670.00	0.00	0.00	0.00	0.00
30.00	0.08	883	670.10	0.02	0.02	0.00	0.00
40.00	0.14	2,194	670.25	0.13	0.13	0.00	0.00
50.00	0.14	2,279	670.26	0.14	0.14	0.00	0.00
60.00	0.24	3,031	670.34	0.21	0.21	0.00	0.00
70.00	0.27	3,811	670.42	0.26	0.26	0.00	0.00
80.00	0.29	4,286	670.47	0.28	0.28	0.00	0.00
90.00	0.30	4,595	670.50	0.30	0.30	0.00	0.00
100.00	0.31	4,835	670.52	0.31	0.31	0.00	0.00
110.00	0.32	5,030	670.54	0.32	0.32	0.00	0.00
120.00	0.33	5,192	670.56	0.32	0.32	0.00	0.00
130.00	0.40	6,035	670.64	0.36	0.36	0.00	0.00
140.00	0.37	6,639	670.70	0.38	0.38	0.00	0.00
150.00	0.38	6,219	670.66	0.36	0.36	0.00	0.00
160.00	0.48	7,542	670.77	0.41	0.41	0.00	0.00
170.00	0.60	11,565	670.96	0.47	0.47	0.00	0.00
180.00	0.60	15,347	671.14	0.52	0.52	0.00	0.00
190.00	0.75	19,980	671.35	0.57	0.57	0.00	0.00
200.00	**1.06**	29,589	671.78	0.67	0.67	0.00	0.00
210.00	**1.19**	45,298	672.47	0.80	0.80	0.00	0.00
220.00	1.04	**55,827**	**672.94**	**0.88**	**0.88**	0.00	0.00
230.00	0.80	**56,310**	**672.96**	**0.89**	**0.89**	0.00	0.00
240.00	0.80	53,712	672.85	0.87	0.87	0.00	0.00
250.00	0.00	27,456	671.68	0.65	0.65	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.68	1.54	15.13	0.00
678.80	**24.77**	**1.56**	**21.42**	**1.79**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	0.65 cfs @ 204.42 hrs,	Volume=	4.080 af
Outflow	=	0.64 cfs @ 205.24 hrs,	Volume=	4.079 af, Atten= 0%, Lag= 49.1 min
Primary	=	0.54 cfs @ 205.24 hrs,	Volume=	2.379 af
Secondary	=	0.11 cfs @ 205.24 hrs,	Volume=	1.700 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.02 hrs
Peak Elev= 677.00' @ 205.24 hrs Surf.Area= 2,084 sf Storage= 605 cf

Plug-Flow detention time= 13.8 min calculated for 4.079 af (100% of inflow)
Center-of-Mass det. time= 13.0 min (10,509.8 - 10,496.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.50'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.54 cfs @ 205.24 hrs HW=677.00' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.54 cfs @ 2.41 fps)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 205.24 hrs HW=677.00' TW=672.15' (Dynamic Tailwater)
└**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.93 fps)
└**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
└**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
20.00	0.00	0	670.75	0.00	0.00	0.00	0.00
30.00	0.03	43	673.79	0.03	0.00	0.03	0.00
40.00	0.05	50	674.32	0.05	0.00	0.05	0.00
50.00	0.05	50	674.35	0.05	0.00	0.05	0.00
60.00	0.09	69	675.69	0.09	0.00	0.09	0.00
70.00	0.10	79	676.40	0.10	0.00	0.10	0.00
80.00	0.11	88	676.55	0.11	0.01	0.10	0.00
90.00	0.12	94	676.56	0.12	0.01	0.10	0.00
100.00	0.12	97	676.58	0.12	0.02	0.10	0.00
110.00	0.13	100	676.59	0.13	0.02	0.10	0.00
120.00	0.13	102	676.59	0.13	0.03	0.10	0.00
130.00	0.17	130	676.65	0.17	0.06	0.10	0.00
140.00	0.15	118	676.63	0.15	0.05	0.10	0.00
150.00	0.16	123	676.63	0.16	0.06	0.10	0.00
160.00	0.22	161	676.69	0.21	0.11	0.10	0.00
170.00	0.29	219	676.75	0.29	0.18	0.11	0.00
180.00	0.29	222	676.76	0.29	0.18	0.11	0.00
190.00	0.37	292	676.81	0.37	0.26	0.11	0.00
200.00	**0.56**	**473**	**676.93**	**0.55**	**0.44**	**0.11**	0.00
210.00	**0.63**	**582**	**676.99**	**0.63**	**0.52**	**0.11**	0.00
220.00	0.54	474	676.93	0.55	0.44	0.11	0.00
230.00	0.41	324	676.84	0.41	0.30	0.11	0.00
240.00	0.41	325	676.84	0.41	0.30	0.11	0.00
250.00	0.00	39	673.50	0.00	0.00	0.00	0.00


Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	24.61	9.86	13.70	1.05
678.75	46.70	15.13	19.77	11.80
678.95	**76.77**	**21.27**	**26.68**	**28.82**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

2-YEAR AND 10-YEAR EVENT CALCULATIONS



Subcat Reach Pond Link

Routing Diagram for D_ByPass_Detention 11.00 Ac_Cultec_4-19-20_6REV
Prepared by {enter your company name here}, Printed 4/21/2020
HydroCAD® 10.00-25 s/n 00783 © 2019 HydroCAD Software Solutions LLC

Summary for Subcatchment 1S: North Property


Runoff = 2.27 cfs @ 0.53 hrs, Volume= 0.122 af, Depth= 0.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=1.57"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	1.57	0.42	1.15
0.02	0.02	0.00	0.00	1.06	1.57	0.42	1.10
0.04	0.08	0.00	0.00	1.08	1.57	0.42	1.05
0.06	0.18	0.00	0.00	1.10	1.57	0.42	0.99
0.08	0.28	0.00	0.00	1.12	1.57	0.42	0.93
0.10	0.39	0.00	0.00	1.14	1.57	0.42	0.86
0.12	0.49	0.00	0.00	1.16	1.57	0.42	0.78
0.14	0.57	0.01	0.00	1.18	1.57	0.42	0.70
0.16	0.63	0.02	0.01	1.20	1.57	0.42	0.61
0.18	0.69	0.03	0.02	1.22	1.57	0.42	0.53
0.20	0.75	0.05	0.05	1.24	1.57	0.42	0.46
0.22	0.81	0.07	0.11	1.26	1.57	0.42	0.39
0.24	0.86	0.08	0.20	1.28	1.57	0.42	0.32
0.26	0.91	0.10	0.32	1.30	1.57	0.42	0.27
0.28	0.96	0.12	0.48	1.32	1.57	0.42	0.22
0.30	1.00	0.13	0.67	1.34	1.57	0.42	0.18
0.32	1.04	0.15	0.88	1.36	1.57	0.42	0.15
0.34	1.07	0.16	1.10	1.38	1.57	0.42	0.13
0.36	1.10	0.17	1.32	1.40	1.57	0.42	0.11
0.38	1.13	0.19	1.54	1.42	1.57	0.42	0.09
0.40	1.16	0.20	1.73	1.44	1.57	0.42	0.07
0.42	1.18	0.21	1.90	1.46	1.57	0.42	0.06
0.44	1.21	0.22	2.03	1.48	1.57	0.42	0.05
0.46	1.23	0.24	2.13	1.50	1.57	0.42	0.04
0.48	1.26	0.25	2.20	1.52	1.57	0.42	0.04
0.50	1.28	0.26	2.24	1.54	1.57	0.42	0.03
0.52	1.29	0.27	**2.26**	1.56	1.57	0.42	0.02
0.54	1.31	0.27	**2.26**	1.58	1.57	0.42	0.02
0.56	1.32	0.28	2.25	1.60	1.57	0.42	0.02
0.58	1.34	0.29	2.22	1.62	1.57	0.42	0.01
0.60	1.35	0.29	2.19	1.64	1.57	0.42	0.01
0.62	1.36	0.30	2.13	1.66	1.57	0.42	0.01
0.64	1.37	0.31	2.07	1.68	1.57	0.42	0.01
0.66	1.39	0.32	1.99	1.70	1.57	0.42	0.01
0.68	1.40	0.32	1.91	1.72	1.57	0.42	0.00
0.70	1.41	0.33	1.83	1.74	1.57	0.42	0.00
0.72	1.42	0.34	1.75	1.76	1.57	0.42	0.00
0.74	1.44	0.34	1.67	1.78	1.57	0.42	0.00
0.76	1.45	0.35	1.60	1.80	1.57	0.42	0.00
0.78	1.46	0.36	1.54	1.82	1.57	0.42	0.00
0.80	1.47	0.36	1.48	1.84	1.57	0.42	0.00
0.82	1.49	0.37	1.44	1.86	1.57	0.42	0.00
0.84	1.50	0.38	1.40	1.88	1.57	0.42	0.00
0.86	1.51	0.39	1.38	1.90	1.57	0.42	0.00
0.88	1.52	0.39	1.35	1.92	1.57	0.42	0.00
0.90	1.53	0.40	1.34	1.94	1.57	0.42	0.00
0.92	1.54	0.40	1.32	1.96	1.57	0.42	0.00
0.94	1.54	0.40	1.30	1.98	1.57	0.42	0.00
0.96	1.55	0.41	1.29	2.00	1.57	0.42	0.00
0.98	1.56	0.41	1.26				
1.00	**1.57**	**0.42**	1.23				
1.02	1.57	0.42	1.19				

Summary for Subcatchment 7S: South Property


Runoff = 4.29 cfs @ 0.66 hrs, Volume= 0.262 af, Depth> 0.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=1.57"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	1.57	0.42	2.83
0.02	0.02	0.00	0.00	1.06	1.57	0.42	2.77
0.04	0.08	0.00	0.00	1.08	1.57	0.42	2.70
0.06	0.18	0.00	0.00	1.10	1.57	0.42	2.61
0.08	0.28	0.00	0.00	1.12	1.57	0.42	2.52
0.10	0.39	0.00	0.00	1.14	1.57	0.42	2.43
0.12	0.49	0.00	0.00	1.16	1.57	0.42	2.32
0.14	0.57	0.01	0.00	1.18	1.57	0.42	2.21
0.16	0.63	0.02	0.00	1.20	1.57	0.42	2.09
0.18	0.69	0.03	0.01	1.22	1.57	0.42	1.95
0.20	0.75	0.05	0.03	1.24	1.57	0.42	1.81
0.22	0.81	0.07	0.07	1.26	1.57	0.42	1.67
0.24	0.86	0.08	0.12	1.28	1.57	0.42	1.52
0.26	0.91	0.10	0.20	1.30	1.57	0.42	1.39
0.28	0.96	0.12	0.32	1.32	1.57	0.42	1.25
0.30	1.00	0.13	0.47	1.34	1.57	0.42	1.13
0.32	1.04	0.15	0.67	1.36	1.57	0.42	1.01
0.34	1.07	0.16	0.90	1.38	1.57	0.42	0.90
0.36	1.10	0.17	1.17	1.40	1.57	0.42	0.80
0.38	1.13	0.19	1.47	1.42	1.57	0.42	0.70
0.40	1.16	0.20	1.78	1.44	1.57	0.42	0.62
0.42	1.18	0.21	2.11	1.46	1.57	0.42	0.54
0.44	1.21	0.22	2.44	1.48	1.57	0.42	0.48
0.46	1.23	0.24	2.75	1.50	1.57	0.42	0.42
0.48	1.26	0.25	3.05	1.52	1.57	0.42	0.37
0.50	1.28	0.26	3.32	1.54	1.57	0.42	0.33
0.52	1.29	0.27	3.56	1.56	1.57	0.42	0.29
0.54	1.31	0.27	3.77	1.58	1.57	0.42	0.26
0.56	1.32	0.28	3.96	1.60	1.57	0.42	0.23
0.58	1.34	0.29	4.08	1.62	1.57	0.42	0.20
0.60	1.35	0.29	4.18	1.64	1.57	0.42	0.18
0.62	1.36	0.30	4.25	1.66	1.57	0.42	0.15
0.64	1.37	0.31	4.28	1.68	1.57	0.42	0.14
0.66	1.39	0.32	**4.28**	1.70	1.57	0.42	0.12
0.68	1.40	0.32	4.25	1.72	1.57	0.42	0.11
0.70	1.41	0.33	4.20	1.74	1.57	0.42	0.09
0.72	1.42	0.34	4.13	1.76	1.57	0.42	0.08
0.74	1.44	0.34	4.04	1.78	1.57	0.42	0.07
0.76	1.45	0.35	3.95	1.80	1.57	0.42	0.06
0.78	1.46	0.36	3.85	1.82	1.57	0.42	0.05
0.80	1.47	0.36	3.74	1.84	1.57	0.42	0.05
0.82	1.49	0.37	3.64	1.86	1.57	0.42	0.04
0.84	1.50	0.38	3.54	1.88	1.57	0.42	0.04
0.86	1.51	0.39	3.44	1.90	1.57	0.42	0.03
0.88	1.52	0.39	3.36	1.92	1.57	0.42	0.03
0.90	1.53	0.40	3.27	1.94	1.57	0.42	0.02
0.92	1.54	0.40	3.20	1.96	1.57	0.42	0.02
0.94	1.54	0.40	3.13	1.98	1.57	0.42	0.02
0.96	1.55	0.41	3.07	2.00	1.57	0.42	0.02
0.98	1.56	0.41	3.01				
1.00	**1.57**	**0.42**	2.95				
1.02	1.57	0.42	2.89				

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.50 cfs @ 0.80 hrs, Volume= 0.035 af, Depth> 0.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=1.57"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	1.57	0.35	0.43
0.02	0.02	0.00	0.00	1.06	1.57	0.35	0.43
0.04	0.08	0.00	0.00	1.08	1.57	0.35	0.42
0.06	0.18	0.00	0.00	1.10	1.57	0.35	0.41
0.08	0.28	0.00	0.00	1.12	1.57	0.35	0.40
0.10	0.39	0.00	0.00	1.14	1.57	0.35	0.40
0.12	0.49	0.00	0.00	1.16	1.57	0.35	0.39
0.14	0.57	0.00	0.00	1.18	1.57	0.35	0.38
0.16	0.63	0.01	0.00	1.20	1.57	0.35	0.37
0.18	0.69	0.02	0.00	1.22	1.57	0.35	0.35
0.20	0.75	0.03	0.00	1.24	1.57	0.35	0.34
0.22	0.81	0.04	0.00	1.26	1.57	0.35	0.33
0.24	0.86	0.06	0.00	1.28	1.57	0.35	0.31
0.26	0.91	0.07	0.01	1.30	1.57	0.35	0.30
0.28	0.96	0.08	0.01	1.32	1.57	0.35	0.28
0.30	1.00	0.10	0.02	1.34	1.57	0.35	0.27
0.32	1.04	0.11	0.03	1.36	1.57	0.35	0.25
0.34	1.07	0.12	0.04	1.38	1.57	0.35	0.23
0.36	1.10	0.13	0.05	1.40	1.57	0.35	0.22
0.38	1.13	0.15	0.07	1.42	1.57	0.35	0.20
0.40	1.16	0.16	0.08	1.44	1.57	0.35	0.19
0.42	1.18	0.17	0.11	1.46	1.57	0.35	0.17
0.44	1.21	0.18	0.13	1.48	1.57	0.35	0.16
0.46	1.23	0.19	0.16	1.50	1.57	0.35	0.15
0.48	1.26	0.20	0.18	1.52	1.57	0.35	0.13
0.50	1.28	0.21	0.21	1.54	1.57	0.35	0.12
0.52	1.29	0.21	0.24	1.56	1.57	0.35	0.11
0.54	1.31	0.22	0.27	1.58	1.57	0.35	0.10
0.56	1.32	0.23	0.30	1.60	1.57	0.35	0.09
0.58	1.34	0.23	0.33	1.62	1.57	0.35	0.08
0.60	1.35	0.24	0.36	1.64	1.57	0.35	0.08
0.62	1.36	0.25	0.39	1.66	1.57	0.35	0.07
0.64	1.37	0.25	0.41	1.68	1.57	0.35	0.06
0.66	1.39	0.26	0.43	1.70	1.57	0.35	0.06
0.68	1.40	0.26	0.45	1.72	1.57	0.35	0.05
0.70	1.41	0.27	0.46	1.74	1.57	0.35	0.05
0.72	1.42	0.28	0.48	1.76	1.57	0.35	0.04
0.74	1.44	0.28	0.49	1.78	1.57	0.35	0.04
0.76	1.45	0.29	0.49	1.80	1.57	0.35	0.04
0.78	1.46	0.30	0.50	1.82	1.57	0.35	0.03
0.80	1.47	0.30	**0.50**	1.84	1.57	0.35	0.03
0.82	1.49	0.31	0.50	1.86	1.57	0.35	0.03
0.84	1.50	0.31	0.50	1.88	1.57	0.35	0.03
0.86	1.51	0.32	0.49	1.90	1.57	0.35	0.02
0.88	1.52	0.33	0.49	1.92	1.57	0.35	0.02
0.90	1.53	0.33	0.48	1.94	1.57	0.35	0.02
0.92	1.54	0.33	0.47	1.96	1.57	0.35	0.02
0.94	1.54	0.34	0.47	1.98	1.57	0.35	0.02
0.96	1.55	0.34	0.46	2.00	1.57	0.35	0.01
0.98	1.56	0.35	0.46				
1.00	**1.57**	**0.35**	0.45				
1.02	1.57	0.35	0.44				

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.33 cfs @ 0.42 hrs, Volume= 0.016 af, Depth= 0.35"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=1.57"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	1.57	0.35	0.12
0.02	0.02	0.00	0.00	1.06	1.57	0.35	0.12
0.04	0.08	0.00	0.00	1.08	1.57	0.35	0.11
0.06	0.18	0.00	0.00	1.10	1.57	0.35	0.09
0.08	0.28	0.00	0.00	1.12	1.57	0.35	0.08
0.10	0.39	0.00	0.00	1.14	1.57	0.35	0.06
0.12	0.49	0.00	0.00	1.16	1.57	0.35	0.04
0.14	0.57	0.00	0.00	1.18	1.57	0.35	0.03
0.16	0.63	0.01	0.00	1.20	1.57	0.35	0.02
0.18	0.69	0.02	0.01	1.22	1.57	0.35	0.02
0.20	0.75	0.03	0.02	1.24	1.57	0.35	0.01
0.22	0.81	0.04	0.05	1.26	1.57	0.35	0.01
0.24	0.86	0.06	0.08	1.28	1.57	0.35	0.01
0.26	0.91	0.07	0.12	1.30	1.57	0.35	0.00
0.28	0.96	0.08	0.17	1.32	1.57	0.35	0.00
0.30	1.00	0.10	0.21	1.34	1.57	0.35	0.00
0.32	1.04	0.11	0.25	1.36	1.57	0.35	0.00
0.34	1.07	0.12	0.28	1.38	1.57	0.35	0.00
0.36	1.10	0.13	0.31	1.40	1.57	0.35	0.00
0.38	1.13	0.15	0.32	1.42	1.57	0.35	0.00
0.40	1.16	0.16	0.33	1.44	1.57	0.35	0.00
0.42	1.18	0.17	**0.33**	1.46	1.57	0.35	0.00
0.44	1.21	0.18	0.33	1.48	1.57	0.35	0.00
0.46	1.23	0.19	0.33	1.50	1.57	0.35	0.00
0.48	1.26	0.20	0.32	1.52	1.57	0.35	0.00
0.50	1.28	0.21	0.31	1.54	1.57	0.35	0.00
0.52	1.29	0.21	0.31	1.56	1.57	0.35	0.00
0.54	1.31	0.22	0.30	1.58	1.57	0.35	0.00
0.56	1.32	0.23	0.29	1.60	1.57	0.35	0.00
0.58	1.34	0.23	0.28	1.62	1.57	0.35	0.00
0.60	1.35	0.24	0.26	1.64	1.57	0.35	0.00
0.62	1.36	0.25	0.25	1.66	1.57	0.35	0.00
0.64	1.37	0.25	0.23	1.68	1.57	0.35	0.00
0.66	1.39	0.26	0.21	1.70	1.57	0.35	0.00
0.68	1.40	0.26	0.20	1.72	1.57	0.35	0.00
0.70	1.41	0.27	0.19	1.74	1.57	0.35	0.00
0.72	1.42	0.28	0.18	1.76	1.57	0.35	0.00
0.74	1.44	0.28	0.18	1.78	1.57	0.35	0.00
0.76	1.45	0.29	0.18	1.80	1.57	0.35	0.00
0.78	1.46	0.30	0.18	1.82	1.57	0.35	0.00
0.80	1.47	0.30	0.18	1.84	1.57	0.35	0.00
0.82	1.49	0.31	0.18	1.86	1.57	0.35	0.00
0.84	1.50	0.31	0.18	1.88	1.57	0.35	0.00
0.86	1.51	0.32	0.18	1.90	1.57	0.35	0.00
0.88	1.52	0.33	0.18	1.92	1.57	0.35	0.00
0.90	1.53	0.33	0.18	1.94	1.57	0.35	0.00
0.92	1.54	0.33	0.18	1.96	1.57	0.35	0.00
0.94	1.54	0.34	0.17	1.98	1.57	0.35	0.00
0.96	1.55	0.34	0.16	2.00	1.57	0.35	0.00
0.98	1.56	0.35	0.15				
1.00	**1.57**	**0.35**	0.14				
1.02	1.57	0.35	0.13				

Summary for Pond 3P: Southeast Chambers

Inflow	=	4.62 cfs @	0.64 hrs, Volume=	0.300 af
Outflow	=	0.46 cfs @	1.54 hrs, Volume=	0.051 af, Atten= 90%, Lag= 53.9 min
Primary	=	0.46 cfs @	1.54 hrs, Volume=	0.051 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 670.95' @ 1.54 hrs Surf.Area= 28,220 sf Storage= 11,255 cf

Plug-Flow detention time= 53.0 min calculated for 0.051 af (17% of inflow)
Center-of-Mass det. time= 28.6 min (79.4 - 50.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.46 cfs @ 1.54 hrs HW=670.95' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.46 cfs @ 4.19 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.05	0.00	0	670.00	0.00	0.00	0.00	0.00
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.15	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.05	2	670.00	0.00	0.00	0.00	0.00
0.25	0.26	24	670.00	0.00	0.00	0.00	0.00
0.30	0.79	105	670.01	0.00	0.00	0.00	0.00
0.35	1.44	291	670.03	0.00	0.00	0.00	0.00
0.40	2.22	604	670.07	0.01	0.01	0.00	0.00
0.45	3.04	1,060	670.12	0.04	0.04	0.00	0.00
0.50	3.75	1,650	670.18	0.08	0.08	0.00	0.00
0.55	4.28	2,347	670.26	0.14	0.14	0.00	0.00
0.60	**4.56**	3,110	670.35	0.21	0.21	0.00	0.00
0.65	**4.62**	3,897	670.43	0.26	0.26	0.00	0.00
0.70	4.51	4,673	670.50	0.30	0.30	0.00	0.00
0.75	4.30	5,414	670.58	0.33	0.33	0.00	0.00
0.80	4.04	6,107	670.65	0.36	0.36	0.00	0.00
0.85	3.79	6,749	670.71	0.38	0.38	0.00	0.00
0.90	3.58	7,344	670.76	0.40	0.40	0.00	0.00
0.95	3.52	7,912	670.79	0.41	0.41	0.00	0.00
1.00	3.45	8,467	670.81	0.42	0.42	0.00	0.00
1.05	3.32	9,004	670.84	0.43	0.43	0.00	0.00
1.10	3.09	9,510	670.86	0.44	0.44	0.00	0.00
1.15	2.74	9,962	670.88	0.44	0.44	0.00	0.00
1.20	2.32	10,345	670.90	0.45	0.45	0.00	0.00
1.25	1.87	10,648	670.92	0.45	0.45	0.00	0.00
1.30	1.51	10,876	670.93	0.46	0.46	0.00	0.00
1.35	1.19	11,042	670.94	0.46	0.46	0.00	0.00
1.40	0.92	11,153	670.94	0.46	0.46	0.00	0.00
1.45	0.70	11,218	670.94	0.46	0.46	0.00	0.00
1.50	0.54	**11,249**	**670.95**	**0.46**	**0.46**	0.00	0.00
1.55	0.43	**11,254**	**670.95**	**0.46**	**0.46**	0.00	0.00
1.60	0.34	11,241	670.95	0.46	0.46	0.00	0.00
1.65	0.28	11,215	670.94	0.46	0.46	0.00	0.00
1.70	0.23	11,178	670.94	0.46	0.46	0.00	0.00
1.75	0.20	11,135	670.94	0.46	0.46	0.00	0.00
1.80	0.17	11,086	670.94	0.46	0.46	0.00	0.00
1.85	0.16	11,033	670.94	0.46	0.46	0.00	0.00
1.90	0.14	10,977	670.93	0.46	0.46	0.00	0.00
1.95	0.13	10,919	670.93	0.46	0.46	0.00	0.00
2.00	0.00	10,860	670.93	0.46	0.46	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	2.56 cfs @	0.57 hrs,	Volume=	0.157 af
Outflow	=	1.56 cfs @	1.05 hrs,	Volume=	0.146 af, Atten= 39%, Lag= 29.1 min
Primary	=	1.16 cfs @	1.05 hrs,	Volume=	0.125 af
Secondary	=	0.40 cfs @	1.05 hrs,	Volume=	0.022 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 677.86' @ 1.05 hrs Surf.Area= 3,020 sf Storage= 2,796 cf

Plug-Flow detention time= 25.6 min calculated for 0.146 af (93% of inflow)
Center-of-Mass det. time= 22.7 min (69.4 - 46.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.16 cfs @ 1.05 hrs HW=677.86' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.16 cfs @ 5.02 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.40 cfs @ 1.05 hrs HW=677.86' TW=670.84' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.98 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 0.28 cfs @ 0.80 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.05	0.00	0	670.75	0.00	0.00	0.00	0.00
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.15	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.05	3	670.95	0.00	0.00	0.00	0.00
0.25	0.26	24	672.47	0.00	0.00	0.00	0.00
0.30	0.69	91	676.56	0.11	0.01	0.10	0.00
0.35	1.26	222	676.76	0.29	0.19	0.11	0.00
0.40	1.82	422	676.90	0.50	0.39	0.11	0.00
0.45	2.23	677	677.03	0.68	0.57	0.11	0.00
0.50	2.46	965	677.17	0.81	0.70	0.11	0.00
0.55	**2.55**	1,262	677.29	0.92	0.80	0.11	0.00
0.60	**2.55**	1,550	677.41	1.00	0.89	0.12	0.00
0.65	2.45	1,817	677.51	1.07	0.96	0.12	0.00
0.70	2.30	2,051	677.60	1.13	1.01	0.12	0.00
0.75	2.13	2,245	677.67	1.17	1.05	0.12	0.00
0.80	1.98	2,403	677.73	1.20	1.08	0.12	0.00
0.85	1.88	2,534	677.77	1.23	1.11	0.12	0.00
0.90	1.82	2,644	677.81	1.27	1.13	**0.14**	0.00
0.95	1.76	2,730	677.84	1.41	1.15	0.26	0.00
1.00	1.68	2,780	677.85	1.52	1.15	0.36	0.00
1.05	1.56	**2,796**	**677.86**	**1.56**	**1.16**	**0.40**	0.00
1.10	1.40	2,786	677.86	1.53	1.16	0.38	0.00
1.15	1.21	2,754	677.84	1.46	1.15	0.31	0.00
1.20	0.98	2,701	677.83	1.35	1.14	0.21	0.00
1.25	0.76	2,625	677.80	1.25	1.13	0.12	0.00
1.30	0.57	2,524	677.77	1.23	1.11	0.12	0.00
1.35	0.43	2,396	677.72	1.20	1.08	0.12	0.00
1.40	0.32	2,250	677.67	1.17	1.05	0.12	0.00
1.45	0.25	2,094	677.62	1.14	1.02	0.12	0.00
1.50	0.19	1,932	677.56	1.10	0.98	0.12	0.00
1.55	0.14	1,767	677.49	1.06	0.94	0.12	0.00
1.60	0.11	1,602	677.43	1.02	0.90	0.12	0.00
1.65	0.08	1,440	677.37	0.97	0.86	0.12	0.00
1.70	0.06	1,283	677.30	0.92	0.81	0.11	0.00
1.75	0.05	1,131	677.24	0.87	0.76	0.11	0.00
1.80	0.04	986	677.17	0.82	0.71	0.11	0.00
1.85	0.03	849	677.11	0.76	0.65	0.11	0.00
1.90	0.02	722	677.05	0.70	0.59	0.11	0.00
1.95	0.02	603	677.00	0.64	0.53	0.11	0.00
2.00	0.00	496	676.94	0.57	0.46	0.11	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 2.14 cfs @ 0.73 hrs, Volume= 0.191 af, Depth= 0.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=1.94"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.04	0.00	0.00
0.10	0.16	0.00	0.00
0.15	0.32	0.00	0.00
0.20	0.48	0.00	0.00
0.25	0.63	0.02	0.01
0.30	0.74	0.05	0.08
0.35	0.84	0.07	0.29
0.40	0.93	0.11	0.63
0.45	1.02	0.14	1.02
0.50	1.10	0.17	1.37
0.55	1.17	0.21	1.67
0.60	1.23	0.24	1.90
0.65	1.29	0.27	2.06
0.70	1.34	0.29	**2.14**
0.75	1.39	0.32	**2.14**
0.80	1.43	0.34	2.08
0.85	1.47	0.36	2.00
0.90	1.51	0.38	1.90
0.95	1.55	0.41	1.81
1.00	1.58	0.42	1.73
1.05	1.60	0.44	1.65
1.10	1.63	0.45	1.57
1.15	1.65	0.47	1.47
1.20	1.67	0.48	1.34
1.25	1.69	0.49	1.20
1.30	1.70	0.50	1.08
1.35	1.72	0.51	1.00
1.40	1.74	0.53	0.95
1.45	1.76	0.54	0.92
1.50	1.78	0.55	0.90
1.55	1.80	0.56	0.89
1.60	1.82	0.58	0.89
1.65	1.84	0.59	0.89
1.70	1.86	0.60	0.89
1.75	1.88	0.61	0.89
1.80	1.89	0.62	0.89
1.85	1.90	0.63	0.87
1.90	1.91	0.63	0.82
1.95	1.92	0.64	0.73
2.00	**1.94**	**0.65**	0.66
2.05	1.94	0.65	0.61
2.10	1.94	0.65	0.58
2.15	1.94	0.65	0.52
2.20	1.94	0.65	0.41
2.25	1.94	0.65	0.28
2.30	1.94	0.65	0.18
2.35	1.94	0.65	0.11
2.40	1.94	0.65	0.07
2.45	1.94	0.65	0.05
2.50	1.94	0.65	0.03
2.55	1.94	0.65	0.02
2.60	1.94	0.65	0.01
2.65	1.94	0.65	0.01
2.70	1.94	0.65	0.00
2.75	1.94	0.65	0.00
2.80	1.94	0.65	0.00
2.85	1.94	0.65	0.00
2.90	1.94	0.65	0.00
2.95	1.94	0.65	0.00
3.00	1.94	0.65	0.00

Summary for Subcatchment 7S: South Property


Runoff = 4.22 cfs @ 0.85 hrs, Volume= 0.409 af, Depth> 0.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=1.94"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.04	0.00	0.00
0.10	0.16	0.00	0.00
0.15	0.32	0.00	0.00
0.20	0.48	0.00	0.00
0.25	0.63	0.02	0.01
0.30	0.74	0.05	0.05
0.35	0.84	0.07	0.19
0.40	0.93	0.11	0.48
0.45	1.02	0.14	0.94
0.50	1.10	0.17	1.52
0.55	1.17	0.21	2.14
0.60	1.23	0.24	2.75
0.65	1.29	0.27	3.29
0.70	1.34	0.29	3.71
0.75	1.39	0.32	4.00
0.80	1.43	0.34	4.17
0.85	1.47	0.36	**4.22**
0.90	1.51	0.38	4.19
0.95	1.55	0.41	4.09
1.00	1.58	0.42	3.97
1.05	1.60	0.44	3.83
1.10	1.63	0.45	3.69
1.15	1.65	0.47	3.52
1.20	1.67	0.48	3.33
1.25	1.69	0.49	3.12
1.30	1.70	0.50	2.89
1.35	1.72	0.51	2.66
1.40	1.74	0.53	2.46
1.45	1.76	0.54	2.30
1.50	1.78	0.55	2.18
1.55	1.80	0.56	2.09
1.60	1.82	0.58	2.03
1.65	1.84	0.59	1.99
1.70	1.86	0.60	1.96
1.75	1.88	0.61	1.95
1.80	1.89	0.62	1.94
1.85	1.90	0.63	1.92
1.90	1.91	0.63	1.87
1.95	1.92	0.64	1.80
2.00	**1.94**	**0.65**	1.69
2.05	1.94	0.65	1.57
2.10	1.94	0.65	1.46
2.15	1.94	0.65	1.35
2.20	1.94	0.65	1.22
2.25	1.94	0.65	1.05
2.30	1.94	0.65	0.86
2.35	1.94	0.65	0.67
2.40	1.94	0.65	0.51
2.45	1.94	0.65	0.37
2.50	1.94	0.65	0.27
2.55	1.94	0.65	0.20
2.60	1.94	0.65	0.14
2.65	1.94	0.65	0.11
2.70	1.94	0.65	0.08
2.75	1.94	0.65	0.06
2.80	1.94	0.65	0.04
2.85	1.94	0.65	0.03
2.90	1.94	0.65	0.02
2.95	1.94	0.65	0.01
3.00	1.94	0.65	0.01

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.53 cfs @ 1.05 hrs, Volume= 0.057 af, Depth> 0.57"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=1.94"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.04	0.00	0.00
0.10	0.16	0.00	0.00
0.15	0.32	0.00	0.00
0.20	0.48	0.00	0.00
0.25	0.63	0.01	0.00
0.30	0.74	0.03	0.00
0.35	0.84	0.05	0.01
0.40	0.93	0.08	0.02
0.45	1.02	0.10	0.04
0.50	1.10	0.13	0.07
0.55	1.17	0.16	0.12
0.60	1.23	0.19	0.18
0.65	1.29	0.21	0.24
0.70	1.34	0.24	0.31
0.75	1.39	0.26	0.37
0.80	1.43	0.28	0.42
0.85	1.47	0.30	0.47
0.90	1.51	0.32	0.50
0.95	1.55	0.34	0.52
1.00	1.58	0.36	0.53
1.05	1.60	0.37	**0.53**
1.10	1.63	0.38	0.53
1.15	1.65	0.39	0.52
1.20	1.67	0.40	0.50
1.25	1.69	0.42	0.49
1.30	1.70	0.43	0.46
1.35	1.72	0.44	0.44
1.40	1.74	0.45	0.42
1.45	1.76	0.46	0.39
1.50	1.78	0.47	0.37
1.55	1.80	0.48	0.35
1.60	1.82	0.50	0.34
1.65	1.84	0.51	0.32
1.70	1.86	0.52	0.31
1.75	1.88	0.53	0.31
1.80	1.89	0.54	0.30
1.85	1.90	0.54	0.30
1.90	1.91	0.55	0.29
1.95	1.92	0.56	0.28
2.00	**1.94**	**0.57**	0.28
2.05	1.94	0.57	0.26
2.10	1.94	0.57	0.25
2.15	1.94	0.57	0.24
2.20	1.94	0.57	0.22
2.25	1.94	0.57	0.20
2.30	1.94	0.57	0.18
2.35	1.94	0.57	0.16
2.40	1.94	0.57	0.14
2.45	1.94	0.57	0.11
2.50	1.94	0.57	0.09
2.55	1.94	0.57	0.08
2.60	1.94	0.57	0.06
2.65	1.94	0.57	0.05
2.70	1.94	0.57	0.04
2.75	1.94	0.57	0.03
2.80	1.94	0.57	0.02
2.85	1.94	0.57	0.02
2.90	1.94	0.57	0.01
2.95	1.94	0.57	0.01
3.00	1.94	0.57	0.01

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.31 cfs @ 0.63 hrs, Volume= 0.026 af, Depth= 0.57"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=1.94"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.04	0.00	0.00
0.10	0.16	0.00	0.00
0.15	0.32	0.00	0.00
0.20	0.48	0.00	0.00
0.25	0.63	0.01	0.00
0.30	0.74	0.03	0.03
0.35	0.84	0.05	0.10
0.40	0.93	0.08	0.17
0.45	1.02	0.10	0.22
0.50	1.10	0.13	0.26
0.55	1.17	0.16	0.29
0.60	1.23	0.19	**0.31**
0.65	1.29	0.21	**0.31**
0.70	1.34	0.24	0.30
0.75	1.39	0.26	0.28
0.80	1.43	0.28	0.27
0.85	1.47	0.30	0.25
0.90	1.51	0.32	0.24
0.95	1.55	0.34	0.23
1.00	1.58	0.36	0.22
1.05	1.60	0.37	0.21
1.10	1.63	0.38	0.19
1.15	1.65	0.39	0.17
1.20	1.67	0.40	0.15
1.25	1.69	0.42	0.13
1.30	1.70	0.43	0.13
1.35	1.72	0.44	0.12
1.40	1.74	0.45	0.12
1.45	1.76	0.46	0.12
1.50	1.78	0.47	0.13
1.55	1.80	0.48	0.13
1.60	1.82	0.50	0.13
1.65	1.84	0.51	0.13
1.70	1.86	0.52	0.13
1.75	1.88	0.53	0.13
1.80	1.89	0.54	0.13
1.85	1.90	0.54	0.11
1.90	1.91	0.55	0.09
1.95	1.92	0.56	0.08
2.00	**1.94**	**0.57**	0.08
2.05	1.94	0.57	0.08
2.10	1.94	0.57	0.07
2.15	1.94	0.57	0.04
2.20	1.94	0.57	0.02
2.25	1.94	0.57	0.01
2.30	1.94	0.57	0.00
2.35	1.94	0.57	0.00
2.40	1.94	0.57	0.00
2.45	1.94	0.57	0.00
2.50	1.94	0.57	0.00
2.55	1.94	0.57	0.00
2.60	1.94	0.57	0.00
2.65	1.94	0.57	0.00
2.70	1.94	0.57	0.00
2.75	1.94	0.57	0.00
2.80	1.94	0.57	0.00
2.85	1.94	0.57	0.00
2.90	1.94	0.57	0.00
2.95	1.94	0.57	0.00
3.00	1.94	0.57	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	4.61 cfs @	1.09 hrs, Volume=	0.480 af
Outflow	=	0.55 cfs @	2.43 hrs, Volume=	0.094 af, Atten= 88%, Lag= 80.8 min
Primary	=	0.55 cfs @	2.43 hrs, Volume=	0.094 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 671.24' @ 2.43 hrs Surf.Area= 28,275 sf Storage= 17,478 cf

Plug-Flow detention time= 78.1 min calculated for 0.094 af (20% of inflow)
Center-of-Mass det. time= 39.6 min (115.6 - 76.1)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.55 cfs @ 2.43 hrs HW=671.24' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.55 cfs @ 4.94 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.00	0	670.00	0.00	0.00	0.00	0.00
0.30	0.08	6	670.00	0.00	0.00	0.00	0.00
0.40	0.75	120	670.01	0.00	0.00	0.00	0.00
0.50	1.89	562	670.06	0.01	0.01	0.00	0.00
0.60	3.17	1,441	670.16	0.06	0.06	0.00	0.00
0.70	4.12	2,710	670.30	0.18	0.18	0.00	0.00
0.80	4.55	4,196	670.46	0.28	0.28	0.00	0.00
0.90	4.54	5,734	670.61	0.35	0.35	0.00	0.00
1.00	**4.43**	7,206	670.75	0.40	0.40	0.00	0.00
1.10	**4.60**	8,693	670.82	0.42	0.42	0.00	0.00
1.20	4.25	10,148	670.89	0.45	0.45	0.00	0.00
1.30	3.60	11,411	670.95	0.47	0.47	0.00	0.00
1.40	2.98	12,431	671.00	0.48	0.48	0.00	0.00
1.50	2.57	13,256	671.04	0.49	0.49	0.00	0.00
1.60	2.35	13,962	671.08	0.50	0.50	0.00	0.00
1.70	2.24	14,606	671.11	0.51	0.51	0.00	0.00
1.80	2.19	15,218	671.14	0.52	0.52	0.00	0.00
1.90	2.09	15,805	671.16	0.53	0.53	0.00	0.00
2.00	1.89	16,337	671.19	0.53	0.53	0.00	0.00
2.10	1.65	16,788	671.21	0.54	0.54	0.00	0.00
2.20	1.35	17,142	671.22	0.54	0.54	0.00	0.00
2.30	0.98	17,376	671.23	0.54	0.54	0.00	0.00
2.40	0.62	**17,473**	**671.24**	**0.55**	**0.55**	0.00	0.00
2.50	0.38	**17,458**	**671.24**	**0.54**	**0.54**	0.00	0.00
2.60	0.26	17,377	671.23	0.54	0.54	0.00	0.00
2.70	0.19	17,262	671.23	0.54	0.54	0.00	0.00
2.80	0.15	17,128	671.22	0.54	0.54	0.00	0.00
2.90	0.13	16,984	671.22	0.54	0.54	0.00	0.00
3.00	0.00	16,834	671.21	0.54	0.54	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	2.51 cfs @	0.78 hrs, Volume=	0.247 af
Outflow	=	1.97 cfs @	1.16 hrs, Volume=	0.242 af, Atten= 22%, Lag= 22.9 min
Primary	=	1.18 cfs @	1.16 hrs, Volume=	0.197 af
Secondary	=	0.79 cfs @	1.16 hrs, Volume=	0.045 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 677.90' @ 1.16 hrs Surf.Area= 3,069 sf Storage= 2,934 cf

Plug-Flow detention time= 27.6 min calculated for 0.242 af (98% of inflow)
Center-of-Mass det. time= 25.8 min (98.0 - 72.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.18 cfs @ 1.16 hrs HW=677.90' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.18 cfs @ 5.13 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.79 cfs @ 1.16 hrs HW=677.90' TW=670.87' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 10.03 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 0.66 cfs @ 1.07 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.00	0	670.75	0.00	0.00	0.00	0.00
0.30	0.08	6	671.16	0.00	0.00	0.00	0.00
0.40	0.65	101	676.59	0.13	0.02	0.10	0.00
0.50	1.45	369	676.87	0.45	0.34	0.11	0.00
0.60	2.08	785	677.08	0.73	0.62	0.11	0.00
0.70	**2.44**	1,304	677.31	0.93	0.81	0.11	0.00
0.80	**2.51**	1,841	677.52	1.08	0.96	0.12	0.00
0.90	2.40	2,323	677.70	1.19	1.07	0.12	0.00
1.00	2.25	2,720	677.83	1.38	1.14	0.24	0.00
1.10	2.10	**2,913**	**677.90**	**1.90**	**1.18**	**0.72**	0.00
1.20	1.84	**2,928**	**677.90**	**1.94**	**1.18**	**0.76**	0.00
1.30	1.55	2,868	677.88	1.76	1.17	0.59	0.00
1.40	1.36	2,795	677.86	1.55	1.16	0.40	0.00
1.50	1.27	2,734	677.84	1.41	1.15	0.27	0.00
1.60	1.22	2,688	677.82	1.33	1.14	0.19	0.00
1.70	1.20	2,655	677.81	1.28	1.13	0.15	0.00
1.80	1.19	2,630	677.80	1.25	1.13	0.13	0.00
1.90	1.11	2,600	677.79	1.24	1.12	0.12	0.00
2.00	0.93	2,524	677.77	1.23	1.11	0.12	0.00
2.10	0.83	2,403	677.72	1.20	1.08	0.12	0.00
2.20	0.63	2,247	677.67	1.17	1.05	0.12	0.00
2.30	0.36	2,014	677.59	1.12	1.00	0.12	0.00
2.40	0.21	1,724	677.48	1.05	0.93	0.12	0.00
2.50	0.12	1,419	677.36	0.96	0.85	0.12	0.00
2.60	0.07	1,122	677.23	0.87	0.75	0.11	0.00
2.70	0.04	847	677.11	0.76	0.65	0.11	0.00
2.80	0.02	604	677.00	0.64	0.53	0.11	0.00
2.90	0.01	404	676.89	0.49	0.38	0.11	0.00
3.00	0.00	259	676.79	0.33	0.23	0.11	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.86 cfs @ 0.94 hrs, Volume= 0.231 af, Depth= 0.79"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=2.14"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.04	0.01	0.00	0.00
0.08	0.05	0.00	0.00
0.12	0.11	0.00	0.00
0.16	0.20	0.00	0.00
0.20	0.29	0.00	0.00
0.24	0.38	0.00	0.00
0.28	0.48	0.00	0.00
0.32	0.58	0.01	0.00
0.36	0.66	0.03	0.03
0.40	0.74	0.05	0.12
0.44	0.81	0.06	0.27
0.48	0.86	0.08	0.50
0.52	0.92	0.10	0.74
0.56	0.97	0.12	0.97
0.60	1.03	0.14	1.17
0.64	1.08	0.16	1.32
0.68	1.13	0.19	1.45
0.72	1.18	0.21	1.55
0.76	1.22	0.23	1.65
0.80	1.27	0.25	1.72
0.84	1.31	0.27	1.79
0.88	1.34	0.29	1.83
0.92	1.38	0.31	**1.86**
0.96	1.41	0.33	**1.86**
1.00	1.44	0.35	1.83
1.04	1.47	0.36	1.79
1.08	1.50	0.38	1.74
1.12	1.53	0.40	1.69
1.16	1.55	0.41	1.64
1.20	1.58	0.42	1.58
1.24	1.60	0.44	1.53
1.28	1.62	0.45	1.47
1.32	1.65	0.47	1.42
1.36	1.67	0.48	1.37
1.40	1.69	0.49	1.33
1.44	1.71	0.51	1.30
1.48	1.73	0.52	1.27
1.52	1.75	0.53	1.25
1.56	1.76	0.54	1.22
1.60	1.78	0.55	1.18
1.64	1.79	0.56	1.12
1.68	1.80	0.56	1.06
1.72	1.81	0.57	1.00
1.76	1.83	0.58	0.93
1.80	1.84	0.59	0.86
1.84	1.85	0.59	0.81
1.88	1.86	0.60	0.76
1.92	1.87	0.61	0.73
1.96	1.88	0.62	0.71
2.00	1.90	0.62	0.70
2.04	1.91	0.63	0.69
2.08	1.92	0.64	0.68
2.12	1.93	0.65	0.68
2.16	1.94	0.66	0.68
2.20	1.95	0.66	0.68
2.24	1.96	0.67	0.68
2.28	1.98	0.68	0.68
2.32	1.99	0.69	0.68
2.36	2.00	0.69	0.68
2.40	2.01	0.70	0.68
2.44	2.02	0.71	0.69
2.48	2.03	0.72	0.69
2.52	2.04	0.73	0.69
2.56	2.06	0.73	0.69
2.60	2.07	0.74	0.69
2.64	2.08	0.75	0.69
2.68	2.08	0.75	0.69
2.72	2.09	0.76	0.67
2.76	2.09	0.76	0.64
2.80	2.10	0.76	0.60
2.84	2.11	0.77	0.55
2.88	2.11	0.77	0.50
2.92	2.12	0.78	0.46
2.96	2.13	0.78	0.43
3.00	**2.14**	**0.79**	0.42
3.04	2.14	0.79	0.43
3.08	2.14	0.79	0.44
3.12	2.14	0.79	0.44
3.16	2.14	0.79	0.39
3.20	2.14	0.79	0.32
3.24	2.14	0.79	0.25
3.28	2.14	0.79	0.17
3.32	2.14	0.79	0.12
3.36	2.14	0.79	0.08
3.40	2.14	0.79	0.06
3.44	2.14	0.79	0.04
3.48	2.14	0.79	0.03
3.52	2.14	0.79	0.02
3.56	2.14	0.79	0.01
3.60	2.14	0.79	0.01
3.64	2.14	0.79	0.01
3.68	2.14	0.79	0.00
3.72	2.14	0.79	0.00
3.76	2.14	0.79	0.00
3.80	2.14	0.79	0.00
3.84	2.14	0.79	0.00
3.88	2.14	0.79	0.00
3.92	2.14	0.79	0.00
3.96	2.14	0.79	0.00
4.00	2.14	0.79	0.00

Summary for Subcatchment 7S: South Property


Runoff = 3.77 cfs @ 1.05 hrs, Volume= 0.495 af, Depth> 0.79"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=2.14"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.04	0.01	0.00	0.00
0.08	0.05	0.00	0.00
0.12	0.11	0.00	0.00
0.16	0.20	0.00	0.00
0.20	0.29	0.00	0.00
0.24	0.38	0.00	0.00
0.28	0.48	0.00	0.00
0.32	0.58	0.01	0.00
0.36	0.66	0.03	0.02
0.40	0.74	0.05	0.07
0.44	0.81	0.06	0.19
0.48	0.86	0.08	0.38
0.52	0.92	0.10	0.66
0.56	0.97	0.12	1.01
0.60	1.03	0.14	1.39
0.64	1.08	0.16	1.76
0.68	1.13	0.19	2.13
0.72	1.18	0.21	2.46
0.76	1.22	0.23	2.75
0.80	1.27	0.25	3.00
0.84	1.31	0.27	3.21
0.88	1.34	0.29	3.40
0.92	1.38	0.31	3.55
0.96	1.41	0.33	3.66
1.00	1.44	0.35	3.73
1.04	1.47	0.36	**3.77**
1.08	1.50	0.38	3.77
1.12	1.53	0.40	3.73
1.16	1.55	0.41	3.68
1.20	1.58	0.42	3.60
1.24	1.60	0.44	3.52
1.28	1.62	0.45	3.42
1.32	1.65	0.47	3.32
1.36	1.67	0.48	3.22
1.40	1.69	0.49	3.12
1.44	1.71	0.51	3.03
1.48	1.73	0.52	2.95
1.52	1.75	0.53	2.88
1.56	1.76	0.54	2.81
1.60	1.78	0.55	2.74
1.64	1.79	0.56	2.66
1.68	1.80	0.56	2.57
1.72	1.81	0.57	2.47
1.76	1.83	0.58	2.35
1.80	1.84	0.59	2.22
1.84	1.85	0.59	2.10
1.88	1.86	0.60	1.98
1.92	1.87	0.61	1.87
1.96	1.88	0.62	1.78
2.00	1.90	0.62	1.70
2.04	1.91	0.63	1.64
2.08	1.92	0.64	1.59
2.12	1.93	0.65	1.56
2.16	1.94	0.66	1.53
2.20	1.95	0.66	1.51
2.24	1.96	0.67	1.50
2.28	1.98	0.68	1.49
2.32	1.99	0.69	1.48
2.36	2.00	0.69	1.48
2.40	2.01	0.70	1.47
2.44	2.02	0.71	1.47
2.48	2.03	0.72	1.47
2.52	2.04	0.73	1.48
2.56	2.06	0.73	1.48
2.60	2.07	0.74	1.48
2.64	2.08	0.75	1.48
2.68	2.08	0.75	1.48
2.72	2.09	0.76	1.47
2.76	2.09	0.76	1.45
2.80	2.10	0.76	1.42
2.84	2.11	0.77	1.36
2.88	2.11	0.77	1.29
2.92	2.12	0.78	1.22
2.96	2.13	0.78	1.14
3.00	**2.14**	**0.79**	1.08
3.04	2.14	0.79	1.03
3.08	2.14	0.79	1.00
3.12	2.14	0.79	0.97
3.16	2.14	0.79	0.95
3.20	2.14	0.79	0.89
3.24	2.14	0.79	0.81
3.28	2.14	0.79	0.71
3.32	2.14	0.79	0.60
3.36	2.14	0.79	0.49
3.40	2.14	0.79	0.39
3.44	2.14	0.79	0.30
3.48	2.14	0.79	0.23
3.52	2.14	0.79	0.18
3.56	2.14	0.79	0.14
3.60	2.14	0.79	0.11
3.64	2.14	0.79	0.09
3.68	2.14	0.79	0.07
3.72	2.14	0.79	0.05
3.76	2.14	0.79	0.04
3.80	2.14	0.79	0.03
3.84	2.14	0.79	0.02
3.88	2.14	0.79	0.02
3.92	2.14	0.79	0.01
3.96	2.14	0.79	0.01
4.00	2.14	0.79	0.01

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.49 cfs @ 1.25 hrs, Volume= 0.069 af, Depth> 0.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=2.14"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.08	1.92	0.55	0.27
0.04	0.01	0.00	0.00	2.12	1.93	0.56	0.26
0.08	0.05	0.00	0.00	2.16	1.94	0.57	0.25
0.12	0.11	0.00	0.00	2.20	1.95	0.57	0.25
0.16	0.20	0.00	0.00	2.24	1.96	0.58	0.24
0.20	0.29	0.00	0.00	2.28	1.98	0.59	0.24
0.24	0.38	0.00	0.00	2.32	1.99	0.60	0.23
0.28	0.48	0.00	0.00	2.36	2.00	0.60	0.23
0.32	0.58	0.00	0.00	2.40	2.01	0.61	0.23
0.36	0.66	0.02	0.00	2.44	2.02	0.62	0.23
0.40	0.74	0.03	0.00	2.48	2.03	0.63	0.22
0.44	0.81	0.04	0.01	2.52	2.04	0.63	0.22
0.48	0.86	0.06	0.01	2.56	2.06	0.64	0.22
0.52	0.92	0.07	0.02	2.60	2.07	0.65	0.22
0.56	0.97	0.09	0.04	2.64	2.08	0.65	0.22
0.60	1.03	0.11	0.07	2.68	2.08	0.66	0.22
0.64	1.08	0.13	0.10	2.72	2.09	0.66	0.22
0.68	1.13	0.14	0.13	2.76	2.09	0.67	0.22
0.72	1.18	0.16	0.17	2.80	2.10	0.67	0.22
0.76	1.22	0.18	0.21	2.84	2.11	0.67	0.21
0.80	1.27	0.20	0.25	2.88	2.11	0.68	0.21
0.84	1.31	0.22	0.29	2.92	2.12	0.68	0.20
0.88	1.34	0.24	0.33	2.96	2.13	0.69	0.19
0.92	1.38	0.25	0.36	3.00	**2.14**	**0.70**	0.19
0.96	1.41	0.27	0.39	3.04	2.14	0.70	0.18
1.00	1.44	0.29	0.42	3.08	2.14	0.70	0.17
1.04	1.47	0.30	0.44	3.12	2.14	0.70	0.16
1.08	1.50	0.32	0.46	3.16	2.14	0.70	0.16
1.12	1.53	0.33	0.47	3.20	2.14	0.70	0.15
1.16	1.55	0.34	0.48	3.24	2.14	0.70	0.14
1.20	1.58	0.36	0.49	3.28	2.14	0.70	0.14
1.24	1.60	0.37	**0.49**	3.32	2.14	0.70	0.12
1.28	1.62	0.38	0.49	3.36	2.14	0.70	0.11
1.32	1.65	0.39	0.48	3.40	2.14	0.70	0.10
1.36	1.67	0.41	0.48	3.44	2.14	0.70	0.09
1.40	1.69	0.42	0.47	3.48	2.14	0.70	0.08
1.44	1.71	0.43	0.46	3.52	2.14	0.70	0.06
1.48	1.73	0.44	0.45	3.56	2.14	0.70	0.05
1.52	1.75	0.45	0.44	3.60	2.14	0.70	0.04
1.56	1.76	0.46	0.43	3.64	2.14	0.70	0.04
1.60	1.78	0.47	0.42	3.68	2.14	0.70	0.03
1.64	1.79	0.48	0.41	3.72	2.14	0.70	0.03
1.68	1.80	0.48	0.40	3.76	2.14	0.70	0.02
1.72	1.81	0.49	0.39	3.80	2.14	0.70	0.02
1.76	1.83	0.50	0.38	3.84	2.14	0.70	0.01
1.80	1.84	0.50	0.37	3.88	2.14	0.70	0.01
1.84	1.85	0.51	0.35	3.92	2.14	0.70	0.01
1.88	1.86	0.52	0.34	3.96	2.14	0.70	0.01
1.92	1.87	0.52	0.32	4.00	2.14	0.70	0.01
1.96	1.88	0.53	0.31				
2.00	1.90	0.54	0.30				
2.04	1.91	0.55	0.28				

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.26 cfs @ 0.86 hrs, Volume= 0.032 af, Depth= 0.70"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=2.14"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.04	0.01	0.00	0.00
0.08	0.05	0.00	0.00
0.12	0.11	0.00	0.00
0.16	0.20	0.00	0.00
0.20	0.29	0.00	0.00
0.24	0.38	0.00	0.00
0.28	0.48	0.00	0.00
0.32	0.58	0.00	0.00
0.36	0.66	0.02	0.01
0.40	0.74	0.03	0.04
0.44	0.81	0.04	0.08
0.48	0.86	0.06	0.13
0.52	0.92	0.07	0.16
0.56	0.97	0.09	0.18
0.60	1.03	0.11	0.20
0.64	1.08	0.13	0.21
0.68	1.13	0.14	0.23
0.72	1.18	0.16	0.24
0.76	1.22	0.18	0.25
0.80	1.27	0.20	0.26
0.84	1.31	0.22	**0.26**
0.88	1.34	0.24	**0.26**
0.92	1.38	0.25	0.26
0.96	1.41	0.27	0.25
1.00	1.44	0.29	0.24
1.04	1.47	0.30	0.23
1.08	1.50	0.32	0.22
1.12	1.53	0.33	0.22
1.16	1.55	0.34	0.21
1.20	1.58	0.36	0.20
1.24	1.60	0.37	0.19
1.28	1.62	0.38	0.19
1.32	1.65	0.39	0.18
1.36	1.67	0.41	0.18
1.40	1.69	0.42	0.18
1.44	1.71	0.43	0.18
1.48	1.73	0.44	0.17
1.52	1.75	0.45	0.17
1.56	1.76	0.46	0.16
1.60	1.78	0.47	0.15
1.64	1.79	0.48	0.14
1.68	1.80	0.48	0.13
1.72	1.81	0.49	0.12
1.76	1.83	0.50	0.11
1.80	1.84	0.50	0.10
1.84	1.85	0.51	0.10
1.88	1.86	0.52	0.10
1.92	1.87	0.52	0.10
1.96	1.88	0.53	0.10
2.00	1.90	0.54	0.10
2.04	1.91	0.55	0.10
2.08	1.92	0.55	0.10
2.12	1.93	0.56	0.10
2.16	1.94	0.57	0.10
2.20	1.95	0.57	0.10
2.24	1.96	0.58	0.10
2.28	1.98	0.59	0.10
2.32	1.99	0.60	0.10
2.36	2.00	0.60	0.10
2.40	2.01	0.61	0.10
2.44	2.02	0.62	0.10
2.48	2.03	0.63	0.10
2.52	2.04	0.63	0.10
2.56	2.06	0.64	0.10
2.60	2.07	0.65	0.10
2.64	2.08	0.65	0.10
2.68	2.08	0.66	0.10
2.72	2.09	0.66	0.09
2.76	2.09	0.67	0.08
2.80	2.10	0.67	0.07
2.84	2.11	0.67	0.06
2.88	2.11	0.68	0.06
2.92	2.12	0.68	0.05
2.96	2.13	0.69	0.06
3.00	**2.14**	**0.70**	0.06
3.04	2.14	0.70	0.07
3.08	2.14	0.70	0.07
3.12	2.14	0.70	0.05
3.16	2.14	0.70	0.03
3.20	2.14	0.70	0.01
3.24	2.14	0.70	0.01
3.28	2.14	0.70	0.00
3.32	2.14	0.70	0.00
3.36	2.14	0.70	0.00
3.40	2.14	0.70	0.00
3.44	2.14	0.70	0.00
3.48	2.14	0.70	0.00
3.52	2.14	0.70	0.00
3.56	2.14	0.70	0.00
3.60	2.14	0.70	0.00
3.64	2.14	0.70	0.00
3.68	2.14	0.70	0.00
3.72	2.14	0.70	0.00
3.76	2.14	0.70	0.00
3.80	2.14	0.70	0.00
3.84	2.14	0.70	0.00
3.88	2.14	0.70	0.00
3.92	2.14	0.70	0.00
3.96	2.14	0.70	0.00
4.00	2.14	0.70	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	4.12 cfs @	1.04 hrs, Volume=	0.580 af
Outflow	=	0.58 cfs @	3.38 hrs, Volume=	0.135 af, Atten= 86%, Lag= 140.1 min
Primary	=	0.58 cfs @	3.38 hrs, Volume=	0.135 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Peak Elev= 671.36' @ 3.38 hrs Surf.Area= 28,298 sf Storage= 20,178 cf

Plug-Flow detention time= 102.4 min calculated for 0.135 af (23% of inflow)
Center-of-Mass det. time= 50.7 min (152.0 - 101.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.58 cfs @ 3.38 hrs HW=671.36' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.58 cfs @ 5.22 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.00	0	670.00	0.00	0.00	0.00	0.00
0.30	0.00	0	670.00	0.00	0.00	0.00	0.00
0.40	0.11	8	670.00	0.00	0.00	0.00	0.00
0.50	0.76	123	670.01	0.00	0.00	0.00	0.00
0.60	1.69	524	670.06	0.01	0.01	0.00	0.00
0.70	2.64	1,266	670.14	0.05	0.05	0.00	0.00
0.80	3.37	2,300	670.26	0.14	0.14	0.00	0.00
0.90	3.85	3,522	670.39	0.24	0.24	0.00	0.00
1.00	**4.09**	4,854	670.52	0.31	0.31	0.00	0.00
1.10	**4.09**	6,215	670.66	0.36	0.36	0.00	0.00
1.20	3.93	7,530	670.77	0.41	0.41	0.00	0.00
1.30	4.06	8,815	670.83	0.43	0.43	0.00	0.00
1.40	3.93	10,110	670.89	0.45	0.45	0.00	0.00
1.50	3.68	11,326	670.95	0.46	0.46	0.00	0.00
1.60	3.42	12,446	671.00	0.48	0.48	0.00	0.00
1.70	3.06	13,453	671.05	0.49	0.49	0.00	0.00
1.80	2.61	14,312	671.09	0.51	0.51	0.00	0.00
1.90	2.18	15,003	671.13	0.51	0.51	0.00	0.00
2.00	1.92	15,557	671.15	0.52	0.52	0.00	0.00
2.10	1.79	16,039	671.17	0.53	0.53	0.00	0.00
2.20	1.73	16,483	671.19	0.53	0.53	0.00	0.00
2.30	1.70	16,908	671.21	0.54	0.54	0.00	0.00
2.40	1.69	17,325	671.23	0.54	0.54	0.00	0.00
2.50	1.69	17,738	671.25	0.55	0.55	0.00	0.00
2.60	1.70	18,151	671.27	0.55	0.55	0.00	0.00
2.70	1.69	18,563	671.29	0.56	0.56	0.00	0.00
2.80	1.60	18,959	671.31	0.56	0.56	0.00	0.00
2.90	1.43	19,309	671.32	0.57	0.57	0.00	0.00
3.00	1.26	19,592	671.33	0.57	0.57	0.00	0.00
3.10	1.16	19,824	671.35	0.57	0.57	0.00	0.00
3.20	1.02	20,018	671.35	0.57	0.57	0.00	0.00
3.30	0.77	**20,146**	**671.36**	**0.58**	**0.58**	0.00	0.00
3.40	0.50	**20,176**	**671.36**	**0.58**	**0.58**	0.00	0.00
3.50	0.32	20,119	671.36	0.58	0.58	0.00	0.00
3.60	0.22	20,010	671.35	0.57	0.57	0.00	0.00
3.70	0.17	19,874	671.35	0.57	0.57	0.00	0.00
3.80	0.14	19,723	671.34	0.57	0.57	0.00	0.00
3.90	0.12	19,565	671.33	0.57	0.57	0.00	0.00
4.00	0.00	19,402	671.33	0.57	0.57	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	2.25 cfs @	0.99 hrs, Volume=	0.301 af
Outflow	=	1.80 cfs @	1.41 hrs, Volume=	0.299 af, Atten= 20%, Lag= 24.9 min
Primary	=	1.17 cfs @	1.41 hrs, Volume=	0.246 af
Secondary	=	0.63 cfs @	1.41 hrs, Volume=	0.053 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Peak Elev= 677.89' @ 1.41 hrs Surf.Area= 3,051 sf Storage= 2,882 cf

Plug-Flow detention time= 27.6 min calculated for 0.299 af (99% of inflow)
Center-of-Mass det. time= 26.9 min (124.2 - 97.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.17 cfs @ 1.41 hrs HW=677.89' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.17 cfs @ 5.09 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.63 cfs @ 1.41 hrs HW=677.89' TW=670.89' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 10.01 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 0.51 cfs @ 0.97 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.00	0	670.75	0.00	0.00	0.00	0.00
0.30	0.00	0	670.75	0.00	0.00	0.00	0.00
0.40	0.12	9	671.37	0.00	0.00	0.00	0.00
0.50	0.64	105	676.60	0.14	0.03	0.10	0.00
0.60	1.23	337	676.85	0.42	0.31	0.11	0.00
0.70	1.65	655	677.02	0.67	0.56	0.11	0.00
0.80	1.97	1,033	677.20	0.84	0.72	0.11	0.00
0.90	**2.19**	1,457	677.37	0.98	0.86	0.12	0.00
1.00	**2.25**	1,891	677.54	1.09	0.97	0.12	0.00
1.10	2.19	2,289	677.69	1.18	1.06	0.12	0.00
1.20	2.07	2,624	677.80	1.25	1.13	0.12	0.00
1.30	1.93	2,839	677.87	1.67	1.16	0.51	0.00
1.40	1.80	**2,883**	**677.89**	**1.80**	**1.17**	**0.63**	0.00
1.50	1.71	2,871	677.88	1.77	1.17	0.60	0.00
1.60	1.60	2,846	677.87	1.69	1.17	0.53	0.00
1.70	1.43	2,805	677.86	1.58	1.16	0.42	0.00
1.80	1.23	2,743	677.84	1.43	1.15	0.28	0.00
1.90	1.08	2,668	677.82	1.29	1.13	0.16	0.00
2.00	0.99	2,587	677.79	1.24	1.12	0.12	0.00
2.10	0.95	2,493	677.76	1.22	1.10	0.12	0.00
2.20	0.92	2,393	677.72	1.20	1.08	0.12	0.00
2.30	0.91	2,294	677.69	1.18	1.06	0.12	0.00
2.40	0.91	2,200	677.65	1.16	1.04	0.12	0.00
2.50	0.91	2,113	677.62	1.14	1.02	0.12	0.00
2.60	0.92	2,033	677.59	1.12	1.01	0.12	0.00
2.70	0.90	1,959	677.57	1.11	0.99	0.12	0.00
2.80	0.82	1,879	677.54	1.09	0.97	0.12	0.00
2.90	0.69	1,766	677.49	1.06	0.94	0.12	0.00
3.00	0.61	1,623	677.44	1.02	0.91	0.12	0.00
3.10	0.61	1,481	677.38	0.98	0.87	0.12	0.00
3.20	0.48	1,339	677.32	0.94	0.83	0.11	0.00
3.30	0.27	1,150	677.25	0.88	0.76	0.11	0.00
3.40	0.16	925	677.15	0.79	0.68	0.11	0.00
3.50	0.09	701	677.04	0.69	0.58	0.11	0.00
3.60	0.05	495	676.94	0.57	0.46	0.11	0.00
3.70	0.03	329	676.84	0.41	0.31	0.11	0.00
3.80	0.02	211	676.74	0.28	0.17	0.11	0.00
3.90	0.01	133	676.65	0.17	0.07	0.10	0.00
4.00	0.00	84	676.53	0.11	0.00	0.10	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.31 cfs @ 1.62 hrs, Volume= 0.310 af, Depth= 1.06"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=2.51"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.05	0.00	0.00
0.30	0.20	0.00	0.00
0.45	0.41	0.00	0.00
0.60	0.62	0.02	0.04
0.75	0.81	0.07	0.46
0.90	0.96	0.12	0.95
1.05	1.09	0.17	1.13
1.20	1.20	0.22	1.19
1.35	1.32	0.28	1.25
1.50	1.42	0.33	**1.29**
1.65	1.51	0.39	**1.31**
1.80	1.60	0.44	1.26
1.95	1.67	0.48	1.16
2.10	1.74	0.52	1.07
2.25	1.80	0.56	0.99
2.40	1.85	0.60	0.92
2.55	1.90	0.63	0.84
2.70	1.95	0.66	0.80
2.85	2.00	0.69	0.80
3.00	2.04	0.72	0.76
3.15	2.08	0.75	0.68
3.30	2.10	0.77	0.58
3.45	2.13	0.79	0.49
3.60	2.16	0.80	0.44
3.75	2.18	0.82	0.43
3.90	2.21	0.84	0.42
4.05	2.23	0.86	0.43
4.20	2.26	0.88	0.43
4.35	2.28	0.89	0.43
4.50	2.31	0.91	0.43
4.65	2.33	0.93	0.43
4.80	2.36	0.95	0.44
4.95	2.38	0.97	0.44
5.10	2.41	0.99	0.44
5.25	2.43	1.00	0.44
5.40	2.45	1.02	0.39
5.55	2.46	1.03	0.30
5.70	2.47	1.03	0.24
5.85	2.49	1.05	0.23
6.00	**2.51**	**1.06**	0.28
6.15	2.51	1.06	0.29
6.30	2.51	1.06	0.10
6.45	2.51	1.06	0.03
6.60	2.51	1.06	0.01
6.75	2.51	1.06	0.00
6.90	2.51	1.06	0.00
7.05	2.51	1.06	0.00
7.20	2.51	1.06	0.00
7.35	2.51	1.06	0.00
7.50	2.51	1.06	0.00
7.65	2.51	1.06	0.00
7.80	2.51	1.06	0.00
7.95	2.51	1.06	0.00

Summary for Subcatchment 7S: South Property


Runoff = 2.77 cfs @ 1.71 hrs, Volume= 0.665 af, Depth= 1.06"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=2.51"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.05	0.00	0.00
0.30	0.20	0.00	0.00
0.45	0.41	0.00	0.00
0.60	0.62	0.02	0.03
0.75	0.81	0.07	0.42
0.90	0.96	0.12	1.32
1.05	1.09	0.17	2.04
1.20	1.20	0.22	2.35
1.35	1.32	0.28	2.54
1.50	1.42	0.33	2.68
1.65	1.51	0.39	**2.76**
1.80	1.60	0.44	**2.75**
1.95	1.67	0.48	2.62
2.10	1.74	0.52	2.43
2.25	1.80	0.56	2.25
2.40	1.85	0.60	2.09
2.55	1.90	0.63	1.93
2.70	1.95	0.66	1.80
2.85	2.00	0.69	1.74
3.00	2.04	0.72	1.69
3.15	2.08	0.75	1.57
3.30	2.10	0.77	1.39
3.45	2.13	0.79	1.20
3.60	2.16	0.80	1.04
3.75	2.18	0.82	0.96
3.90	2.21	0.84	0.93
4.05	2.23	0.86	0.92
4.20	2.26	0.88	0.92
4.35	2.28	0.89	0.92
4.50	2.31	0.91	0.92
4.65	2.33	0.93	0.93
4.80	2.36	0.95	0.93
4.95	2.38	0.97	0.94
5.10	2.41	0.99	0.94
5.25	2.43	1.00	0.94
5.40	2.45	1.02	0.90
5.55	2.46	1.03	0.76
5.70	2.47	1.03	0.62
5.85	2.49	1.05	0.54
6.00	**2.51**	**1.06**	0.55
6.15	2.51	1.06	0.63
6.30	2.51	1.06	0.45
6.45	2.51	1.06	0.19
6.60	2.51	1.06	0.07
6.75	2.51	1.06	0.03
6.90	2.51	1.06	0.01
7.05	2.51	1.06	0.00
7.20	2.51	1.06	0.00
7.35	2.51	1.06	0.00
7.50	2.51	1.06	0.00
7.65	2.51	1.06	0.00
7.80	2.51	1.06	0.00
7.95	2.51	1.06	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.38 cfs @ 1.87 hrs, Volume= 0.095 af, Depth= 0.95"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=2.51"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.05	0.00	0.00
0.30	0.20	0.00	0.00
0.45	0.41	0.00	0.00
0.60	0.62	0.01	0.00
0.75	0.81	0.04	0.01
0.90	0.96	0.09	0.07
1.05	1.09	0.13	0.17
1.20	1.20	0.18	0.25
1.35	1.32	0.22	0.30
1.50	1.42	0.27	0.34
1.65	1.51	0.32	0.37
1.80	1.60	0.37	**0.38**
1.95	1.67	0.41	**0.38**
2.10	1.74	0.44	0.37
2.25	1.80	0.48	0.35
2.40	1.85	0.51	0.32
2.55	1.90	0.54	0.30
2.70	1.95	0.57	0.28
2.85	2.00	0.60	0.27
3.00	2.04	0.63	0.26
3.15	2.08	0.65	0.25
3.30	2.10	0.67	0.23
3.45	2.13	0.69	0.20
3.60	2.16	0.71	0.18
3.75	2.18	0.72	0.16
3.90	2.21	0.74	0.15
4.05	2.23	0.76	0.14
4.20	2.26	0.77	0.14
4.35	2.28	0.79	0.14
4.50	2.31	0.81	0.14
4.65	2.33	0.82	0.14
4.80	2.36	0.84	0.14
4.95	2.38	0.86	0.14
5.10	2.41	0.88	0.14
5.25	2.43	0.89	0.14
5.40	2.45	0.90	0.14
5.55	2.46	0.91	0.13
5.70	2.47	0.92	0.11
5.85	2.49	0.93	0.09
6.00	**2.51**	**0.95**	0.09
6.15	2.51	0.95	0.09
6.30	2.51	0.95	0.08
6.45	2.51	0.95	0.06
6.60	2.51	0.95	0.03
6.75	2.51	0.95	0.01
6.90	2.51	0.95	0.01
7.05	2.51	0.95	0.00
7.20	2.51	0.95	0.00
7.35	2.51	0.95	0.00
7.50	2.51	0.95	0.00
7.65	2.51	0.95	0.00
7.80	2.51	0.95	0.00
7.95	2.51	0.95	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.18 cfs @ 1.58 hrs, Volume= 0.044 af, Depth= 0.95"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=2.51"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.05	0.00	0.00
0.30	0.20	0.00	0.00
0.45	0.41	0.00	0.00
0.60	0.62	0.01	0.01
0.75	0.81	0.04	0.09
0.90	0.96	0.09	0.15
1.05	1.09	0.13	0.15
1.20	1.20	0.18	0.17
1.35	1.32	0.22	0.18
1.50	1.42	0.27	**0.18**
1.65	1.51	0.32	**0.18**
1.80	1.60	0.37	0.17
1.95	1.67	0.41	0.15
2.10	1.74	0.44	0.14
2.25	1.80	0.48	0.13
2.40	1.85	0.51	0.12
2.55	1.90	0.54	0.12
2.70	1.95	0.57	0.12
2.85	2.00	0.60	0.11
3.00	2.04	0.63	0.10
3.15	2.08	0.65	0.09
3.30	2.10	0.67	0.08
3.45	2.13	0.69	0.06
3.60	2.16	0.71	0.06
3.75	2.18	0.72	0.06
3.90	2.21	0.74	0.06
4.05	2.23	0.76	0.06
4.20	2.26	0.77	0.06
4.35	2.28	0.79	0.06
4.50	2.31	0.81	0.06
4.65	2.33	0.82	0.06
4.80	2.36	0.84	0.06
4.95	2.38	0.86	0.06
5.10	2.41	0.88	0.07
5.25	2.43	0.89	0.06
5.40	2.45	0.90	0.05
5.55	2.46	0.91	0.04
5.70	2.47	0.92	0.03
5.85	2.49	0.93	0.04
6.00	**2.51**	**0.95**	0.05
6.15	2.51	0.95	0.02
6.30	2.51	0.95	0.00
6.45	2.51	0.95	0.00
6.60	2.51	0.95	0.00
6.75	2.51	0.95	0.00
6.90	2.51	0.95	0.00
7.05	2.51	0.95	0.00
7.20	2.51	0.95	0.00
7.35	2.51	0.95	0.00
7.50	2.51	0.95	0.00
7.65	2.51	0.95	0.00
7.80	2.51	0.95	0.00
7.95	2.51	0.95	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	3.07 cfs @	1.70 hrs, Volume=	0.767 af
Outflow	=	0.61 cfs @	6.29 hrs, Volume=	0.311 af, Atten= 80%, Lag= 275.5 min
Primary	=	0.61 cfs @	6.29 hrs, Volume=	0.311 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Peak Elev= 671.49' @ 6.29 hrs Surf.Area= 30,689 sf Storage= 23,072 cf

Plug-Flow detention time= 196.1 min calculated for 0.311 af (41% of inflow)
Center-of-Mass det. time= 112.1 min (288.4 - 176.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.61 cfs @ 6.29 hrs HW=671.49' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.61 cfs @ 5.49 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.30	0.00	0	670.00	0.00	0.00	0.00	0.00
0.60	0.04	2	670.00	0.00	0.00	0.00	0.00
0.90	1.57	636	670.07	0.01	0.01	0.00	0.00
1.20	2.63	2,902	670.32	0.20	0.20	0.00	0.00
1.50	**2.98**	5,641	670.60	0.34	0.34	0.00	0.00
1.80	**3.04**	8,508	670.81	0.42	0.42	0.00	0.00
2.10	2.70	11,167	670.94	0.46	0.46	0.00	0.00
2.40	2.38	13,432	671.05	0.49	0.49	0.00	0.00
2.70	2.04	15,266	671.14	0.52	0.52	0.00	0.00
3.00	1.91	16,835	671.21	0.54	0.54	0.00	0.00
3.30	1.59	18,171	671.27	0.55	0.55	0.00	0.00
3.60	1.22	19,089	671.31	0.56	0.56	0.00	0.00
3.90	1.10	19,717	671.34	0.57	0.57	0.00	0.00
4.20	1.09	20,279	671.37	0.58	0.58	0.00	0.00
4.50	1.10	20,833	671.39	0.58	0.58	0.00	0.00
4.80	1.11	21,390	671.41	0.59	0.59	0.00	0.00
5.10	1.11	21,949	671.44	0.60	0.60	0.00	0.00
5.40	1.05	22,499	671.46	0.60	0.60	0.00	0.00
5.70	0.76	22,843	671.48	0.60	0.60	0.00	0.00
6.00	0.71	22,947	671.48	0.61	0.61	0.00	0.00
6.30	0.55	**23,071**	**671.49**	**0.61**	**0.61**	0.00	0.00
6.60	0.18	22,783	671.48	0.60	0.60	0.00	0.00
6.90	0.03	22,253	671.45	0.60	0.60	0.00	0.00
7.20	0.00	21,622	671.43	0.59	0.59	0.00	0.00
7.50	0.00	20,988	671.40	0.58	0.58	0.00	0.00
7.80	0.00	20,360	671.37	0.58	0.58	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	1.67 cfs @	1.67 hrs, Volume=	0.405 af
Outflow	=	1.32 cfs @	2.29 hrs, Volume=	0.404 af, Atten= 21%, Lag= 37.0 min
Primary	=	1.14 cfs @	2.29 hrs, Volume=	0.346 af
Secondary	=	0.19 cfs @	2.29 hrs, Volume=	0.059 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Peak Elev= 677.82' @ 2.29 hrs Surf.Area= 2,980 sf Storage= 2,686 cf

Plug-Flow detention time= 25.8 min calculated for 0.404 af (100% of inflow)
Center-of-Mass det. time= 25.1 min (195.8 - 170.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.14 cfs @ 2.29 hrs HW=677.82' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 1.14 cfs @ 4.94 fps)
└2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.19 cfs @ 2.29 hrs HW=677.82' TW=671.01' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.94 fps)
└5=**Sharp-Crested Rectangular Weir** (Weir Controls 0.06 cfs @ 0.49 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.30	0.00	0	670.75	0.00	0.00	0.00	0.00
0.60	0.04	3	670.93	0.00	0.00	0.00	0.00
0.90	1.02	345	676.85	0.43	0.32	0.11	0.00
1.20	1.43	1,003	677.18	0.82	0.71	0.11	0.00
1.50	**1.63**	1,662	677.45	1.03	0.92	0.12	0.00
1.80	**1.64**	2,264	677.68	1.18	1.06	0.12	0.00
2.10	1.43	**2,625**	**677.80**	**1.25**	**1.13**	**0.12**	0.00
2.40	1.24	**2,674**	**677.82**	**1.30**	**1.14**	**0.17**	0.00
2.70	1.09	2,560	677.78	1.24	1.11	0.12	0.00
3.00	1.01	2,389	677.72	1.20	1.08	0.12	0.00
3.30	0.81	2,120	677.62	1.14	1.03	0.12	0.00
3.60	0.61	1,696	677.47	1.04	0.93	0.12	0.00
3.90	0.57	1,266	677.29	0.92	0.80	0.11	0.00
4.20	0.57	946	677.16	0.80	0.69	0.11	0.00
4.50	0.57	741	677.06	0.71	0.60	0.11	0.00
4.80	0.58	621	677.01	0.65	0.54	0.11	0.00
5.10	0.58	560	676.98	0.61	0.51	0.11	0.00
5.40	0.53	526	676.96	0.59	0.48	0.11	0.00
5.70	0.35	405	676.89	0.49	0.38	0.11	0.00
6.00	0.37	304	676.82	0.38	0.28	0.11	0.00
6.30	0.18	268	676.80	0.34	0.24	0.11	0.00
6.60	0.04	106	676.61	0.14	0.04	0.10	0.00
6.90	0.01	40	673.63	0.02	0.00	0.02	0.00
7.20	0.00	39	673.54	0.00	0.00	0.00	0.00
7.50	0.00	39	673.52	0.00	0.00	0.00	0.00
7.80	0.00	39	673.51	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.16 cfs @ 5.56 hrs, Volume= 0.401 af, Depth= 1.37"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=2.91"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.00	0.00	0.00
0.40	0.02	0.00	0.00
0.60	0.04	0.00	0.00
0.80	0.08	0.00	0.00
1.00	0.12	0.00	0.00
1.20	0.16	0.00	0.00
1.40	0.21	0.00	0.00
1.60	0.25	0.00	0.00
1.80	0.29	0.00	0.00
2.00	0.33	0.00	0.00
2.20	0.37	0.00	0.00
2.40	0.41	0.00	0.00
2.60	0.45	0.00	0.00
2.80	0.50	0.00	0.03
3.00	0.56	0.01	0.07
3.20	0.62	0.02	0.12
3.40	0.68	0.03	0.18
3.60	0.75	0.05	0.24
3.80	0.82	0.07	0.31
4.00	0.91	0.10	0.40
4.20	1.00	0.13	0.52
4.40	1.10	0.17	0.65
4.60	1.21	0.22	0.78
4.80	1.32	0.28	0.91
5.00	1.44	0.34	1.04
5.20	1.55	0.41	1.11
5.40	1.66	0.47	**1.14**
5.60	1.76	0.54	**1.16**
5.80	1.86	0.60	1.11
6.00	1.94	0.65	1.04
6.20	2.02	0.71	0.96
6.40	2.08	0.75	0.89
6.60	2.15	0.80	0.82
6.80	2.20	0.84	0.76
7.00	2.26	0.88	0.71
7.20	2.31	0.91	0.68
7.40	2.35	0.95	0.64
7.60	2.40	0.98	0.60
7.80	2.44	1.01	0.57
8.00	2.48	1.04	0.53
8.20	2.51	1.06	0.49
8.40	2.54	1.09	0.45
8.60	2.57	1.11	0.41
8.80	2.60	1.13	0.40
9.00	2.63	1.16	0.40
9.20	2.66	1.18	0.39
9.40	2.68	1.20	0.36
9.60	2.70	1.21	0.32
9.80	2.72	1.23	0.28
10.00	2.74	1.24	0.27
10.20	2.76	1.26	0.27
10.40	2.78	1.27	0.27
10.60	2.80	1.29	0.27
10.80	2.82	1.30	0.27
11.00	2.84	1.32	0.27
11.20	2.85	1.33	0.24
11.40	2.87	1.34	0.19
11.60	2.88	1.35	0.16
11.80	2.89	1.36	0.18
12.00	**2.91**	**1.37**	0.22
12.20	2.91	1.37	0.15
12.40	2.91	1.37	0.03
12.60	2.91	1.37	0.00
12.80	2.91	1.37	0.00
13.00	2.91	1.37	0.00
13.20	2.91	1.37	0.00
13.40	2.91	1.37	0.00
13.60	2.91	1.37	0.00
13.80	2.91	1.37	0.00
14.00	2.91	1.37	0.00
14.20	2.91	1.37	0.00
14.40	2.91	1.37	0.00
14.60	2.91	1.37	0.00
14.80	2.91	1.37	0.00
15.00	2.91	1.37	0.00

Summary for Subcatchment 7S: South Property


Runoff = 2.46 cfs @ 5.65 hrs, Volume= 0.859 af, Depth= 1.37"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=2.91"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.00	0.00	0.00
0.40	0.02	0.00	0.00
0.60	0.04	0.00	0.00
0.80	0.08	0.00	0.00
1.00	0.12	0.00	0.00
1.20	0.16	0.00	0.00
1.40	0.21	0.00	0.00
1.60	0.25	0.00	0.00
1.80	0.29	0.00	0.00
2.00	0.33	0.00	0.00
2.20	0.37	0.00	0.00
2.40	0.41	0.00	0.00
2.60	0.45	0.00	0.00
2.80	0.50	0.00	0.03
3.00	0.56	0.01	0.10
3.20	0.62	0.02	0.20
3.40	0.68	0.03	0.31
3.60	0.75	0.05	0.44
3.80	0.82	0.07	0.57
4.00	0.91	0.10	0.74
4.20	1.00	0.13	0.97
4.40	1.10	0.17	1.23
4.60	1.21	0.22	1.51
4.80	1.32	0.28	1.79
5.00	1.44	0.34	2.07
5.20	1.55	0.41	2.28
5.40	1.66	0.47	2.39
5.60	1.76	0.54	**2.46**
5.80	1.86	0.60	**2.43**
6.00	1.94	0.65	2.31
6.20	2.02	0.71	2.15
6.40	2.08	0.75	1.99
6.60	2.15	0.80	1.84
6.80	2.20	0.84	1.70
7.00	2.26	0.88	1.58
7.20	2.31	0.91	1.50
7.40	2.35	0.95	1.42
7.60	2.40	0.98	1.34
7.80	2.44	1.01	1.26
8.00	2.48	1.04	1.18
8.20	2.51	1.06	1.09
8.40	2.54	1.09	1.01
8.60	2.57	1.11	0.92
8.80	2.60	1.13	0.87
9.00	2.63	1.16	0.86
9.20	2.66	1.18	0.85
9.40	2.68	1.20	0.82
9.60	2.70	1.21	0.74
9.80	2.72	1.23	0.66
10.00	2.74	1.24	0.60
10.20	2.76	1.26	0.59
10.40	2.78	1.27	0.58
10.60	2.80	1.29	0.58
10.80	2.82	1.30	0.58
11.00	2.84	1.32	0.58
11.20	2.85	1.33	0.54
11.40	2.87	1.34	0.47
11.60	2.88	1.35	0.38
11.80	2.89	1.36	0.36
12.00	**2.91**	**1.37**	0.42
12.20	2.91	1.37	0.43
12.40	2.91	1.37	0.18
12.60	2.91	1.37	0.05
12.80	2.91	1.37	0.01
13.00	2.91	1.37	0.00
13.20	2.91	1.37	0.00
13.40	2.91	1.37	0.00
13.60	2.91	1.37	0.00
13.80	2.91	1.37	0.00
14.00	2.91	1.37	0.00
14.20	2.91	1.37	0.00
14.40	2.91	1.37	0.00
14.60	2.91	1.37	0.00
14.80	2.91	1.37	0.00
15.00	2.91	1.37	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.35 cfs @ 5.80 hrs, Volume= 0.124 af, Depth= 1.24"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=2.91"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.00	0.00	0.00
0.40	0.02	0.00	0.00
0.60	0.04	0.00	0.00
0.80	0.08	0.00	0.00
1.00	0.12	0.00	0.00
1.20	0.16	0.00	0.00
1.40	0.21	0.00	0.00
1.60	0.25	0.00	0.00
1.80	0.29	0.00	0.00
2.00	0.33	0.00	0.00
2.20	0.37	0.00	0.00
2.40	0.41	0.00	0.00
2.60	0.45	0.00	0.00
2.80	0.50	0.00	0.00
3.00	0.56	0.00	0.00
3.20	0.62	0.01	0.01
3.40	0.68	0.02	0.02
3.60	0.75	0.03	0.04
3.80	0.82	0.05	0.05
4.00	0.91	0.07	0.08
4.20	1.00	0.10	0.10
4.40	1.10	0.13	0.14
4.60	1.21	0.18	0.18
4.80	1.32	0.23	0.22
5.00	1.44	0.28	0.26
5.20	1.55	0.34	0.30
5.40	1.66	0.40	0.33
5.60	1.76	0.46	0.35
5.80	1.86	0.52	**0.35**
6.00	1.94	0.57	0.35
6.20	2.02	0.61	0.33
6.40	2.08	0.66	0.31
6.60	2.15	0.70	0.29
6.80	2.20	0.74	0.27
7.00	2.26	0.77	0.25
7.20	2.31	0.81	0.23
7.40	2.35	0.84	0.22
7.60	2.40	0.87	0.21
7.80	2.44	0.90	0.20
8.00	2.48	0.93	0.19
8.20	2.51	0.95	0.17
8.40	2.54	0.97	0.16
8.60	2.57	0.99	0.15
8.80	2.60	1.02	0.14
9.00	2.63	1.04	0.13
9.20	2.66	1.06	0.13
9.40	2.68	1.07	0.13
9.60	2.70	1.09	0.12
9.80	2.72	1.11	0.11
10.00	2.74	1.12	0.10
10.20	2.76	1.13	0.09
10.40	2.78	1.15	0.09
10.60	2.80	1.16	0.09
10.80	2.82	1.18	0.09
11.00	2.84	1.19	0.09
11.20	2.85	1.20	0.09
11.40	2.87	1.21	0.08
11.60	2.88	1.22	0.07
11.80	2.89	1.23	0.06
12.00	**2.91**	**1.24**	0.06
12.20	2.91	1.24	0.07
12.40	2.91	1.24	0.05
12.60	2.91	1.24	0.02
12.80	2.91	1.24	0.01
13.00	2.91	1.24	0.00
13.20	2.91	1.24	0.00
13.40	2.91	1.24	0.00
13.60	2.91	1.24	0.00
13.80	2.91	1.24	0.00
14.00	2.91	1.24	0.00
14.20	2.91	1.24	0.00
14.40	2.91	1.24	0.00
14.60	2.91	1.24	0.00
14.80	2.91	1.24	0.00
15.00	2.91	1.24	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.17 cfs @ 5.50 hrs, Volume= 0.057 af, Depth= 1.24"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=2.91"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.00	0.00	0.00
0.40	0.02	0.00	0.00
0.60	0.04	0.00	0.00
0.80	0.08	0.00	0.00
1.00	0.12	0.00	0.00
1.20	0.16	0.00	0.00
1.40	0.21	0.00	0.00
1.60	0.25	0.00	0.00
1.80	0.29	0.00	0.00
2.00	0.33	0.00	0.00
2.20	0.37	0.00	0.00
2.40	0.41	0.00	0.00
2.60	0.45	0.00	0.00
2.80	0.50	0.00	0.00
3.00	0.56	0.00	0.01
3.20	0.62	0.01	0.01
3.40	0.68	0.02	0.02
3.60	0.75	0.03	0.03
3.80	0.82	0.05	0.04
4.00	0.91	0.07	0.06
4.20	1.00	0.10	0.08
4.40	1.10	0.13	0.10
4.60	1.21	0.18	0.12
4.80	1.32	0.23	0.14
5.00	1.44	0.28	0.15
5.20	1.55	0.34	0.16
5.40	1.66	0.40	**0.16**
5.60	1.76	0.46	**0.16**
5.80	1.86	0.52	0.16
6.00	1.94	0.57	0.14
6.20	2.02	0.61	0.13
6.40	2.08	0.66	0.12
6.60	2.15	0.70	0.11
6.80	2.20	0.74	0.11
7.00	2.26	0.77	0.10
7.20	2.31	0.81	0.10
7.40	2.35	0.84	0.09
7.60	2.40	0.87	0.09
7.80	2.44	0.90	0.08
8.00	2.48	0.93	0.07
8.20	2.51	0.95	0.07
8.40	2.54	0.97	0.06
8.60	2.57	0.99	0.06
8.80	2.60	1.02	0.06
9.00	2.63	1.04	0.06
9.20	2.66	1.06	0.06
9.40	2.68	1.07	0.05
9.60	2.70	1.09	0.04
9.80	2.72	1.11	0.04
10.00	2.74	1.12	0.04
10.20	2.76	1.13	0.04
10.40	2.78	1.15	0.04
10.60	2.80	1.16	0.04
10.80	2.82	1.18	0.04
11.00	2.84	1.19	0.04
11.20	2.85	1.20	0.03
11.40	2.87	1.21	0.03
11.60	2.88	1.22	0.02
11.80	2.89	1.23	0.03
12.00	**2.91**	**1.24**	0.04
12.20	2.91	1.24	0.01
12.40	2.91	1.24	0.00
12.60	2.91	1.24	0.00
12.80	2.91	1.24	0.00
13.00	2.91	1.24	0.00
13.20	2.91	1.24	0.00
13.40	2.91	1.24	0.00
13.60	2.91	1.24	0.00
13.80	2.91	1.24	0.00
14.00	2.91	1.24	0.00
14.20	2.91	1.24	0.00
14.40	2.91	1.24	0.00
14.60	2.91	1.24	0.00
14.80	2.91	1.24	0.00
15.00	2.91	1.24	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	2.74 cfs @	5.64 hrs, Volume=	1.004 af
Outflow	=	0.65 cfs @	11.31 hrs, Volume=	0.520 af, Atten= 76%, Lag= 340.0 min
Primary	=	0.65 cfs @	11.31 hrs, Volume=	0.520 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Peak Elev= 671.67' @ 11.31 hrs Surf.Area= 30,731 sf Storage= 27,201 cf

Plug-Flow detention time= 278.6 min calculated for 0.520 af (52% of inflow)
Center-of-Mass det. time= 174.7 min (597.3 - 422.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00'** L Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.65 cfs @ 11.31 hrs HW=671.67' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.65 cfs @ 5.87 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.40	0.00	0	670.00	0.00	0.00	0.00	0.00
0.80	0.00	0	670.00	0.00	0.00	0.00	0.00
1.20	0.00	0	670.00	0.00	0.00	0.00	0.00
1.60	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.40	0.00	0	670.00	0.00	0.00	0.00	0.00
2.80	0.03	8	670.00	0.00	0.00	0.00	0.00
3.20	0.30	191	670.02	0.00	0.00	0.00	0.00
3.60	0.57	791	670.09	0.02	0.02	0.00	0.00
4.00	0.91	1,750	670.20	0.09	0.09	0.00	0.00
4.40	1.44	3,173	670.35	0.22	0.22	0.00	0.00
4.80	2.03	5,243	670.56	0.32	0.32	0.00	0.00
5.20	2.55	8,012	670.79	0.41	0.41	0.00	0.00
5.60	**2.74**	11,211	670.94	0.46	0.46	0.00	0.00
6.00	**2.58**	14,402	671.10	0.51	0.51	0.00	0.00
6.40	2.24	17,138	671.22	0.54	0.54	0.00	0.00
6.80	1.93	19,358	671.32	0.57	0.57	0.00	0.00
7.20	1.71	21,150	671.40	0.59	0.59	0.00	0.00
7.60	1.54	22,652	671.47	0.60	0.60	0.00	0.00
8.00	1.37	23,887	671.52	0.62	0.62	0.00	0.00
8.40	1.18	24,846	671.57	0.62	0.62	0.00	0.00
8.80	1.04	25,537	671.60	0.63	0.63	0.00	0.00
9.20	1.02	26,104	671.62	0.64	0.64	0.00	0.00
9.60	0.89	26,586	671.64	0.64	0.64	0.00	0.00
10.00	0.75	26,839	671.66	0.64	0.64	0.00	0.00
10.40	0.73	26,969	671.66	0.65	0.65	0.00	0.00
10.80	0.73	27,087	671.67	0.65	0.65	0.00	0.00
11.20	0.68	**27,193**	**671.67**	**0.65**	**0.65**	0.00	0.00
11.60	0.51	**27,131**	**671.67**	**0.65**	**0.65**	0.00	0.00
12.00	0.56	26,931	671.66	0.65	0.65	0.00	0.00
12.40	0.28	26,735	671.65	0.64	0.64	0.00	0.00
12.80	0.03	26,038	671.62	0.64	0.64	0.00	0.00
13.20	0.00	25,143	671.58	0.63	0.63	0.00	0.00
13.60	0.00	24,246	671.54	0.62	0.62	0.00	0.00
14.00	0.00	23,361	671.50	0.61	0.61	0.00	0.00
14.40	0.00	22,489	671.46	0.60	0.60	0.00	0.00
14.80	0.00	21,630	671.43	0.59	0.59	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	1.50 cfs @	5.60 hrs, Volume=	0.525 af
Outflow	=	1.24 cfs @	6.32 hrs, Volume=	0.524 af, Atten= 18%, Lag= 43.2 min
Primary	=	1.12 cfs @	6.32 hrs, Volume=	0.436 af
Secondary	=	0.12 cfs @	6.32 hrs, Volume=	0.088 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Peak Elev= 677.78' @ 6.32 hrs Surf.Area= 2,940 sf Storage= 2,577 cf

Plug-Flow detention time= 23.9 min calculated for 0.523 af (100% of inflow)
Center-of-Mass det. time= 23.3 min (439.7 - 416.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.12 cfs @ 6.32 hrs HW=677.78' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 1.12 cfs @ 4.85 fps)
└2=Sharp-Crested **Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.12 cfs @ 6.32 hrs HW=677.78' TW=671.20' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.89 fps)
└5=Sharp-Crested **Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.40	0.00	0	670.75	0.00	0.00	0.00	0.00
0.80	0.00	0	670.75	0.00	0.00	0.00	0.00
1.20	0.00	0	670.75	0.00	0.00	0.00	0.00
1.60	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.40	0.00	0	670.75	0.00	0.00	0.00	0.00
2.80	0.03	9	671.36	0.00	0.00	0.00	0.00
3.20	0.13	69	675.65	0.09	0.00	0.09	0.00
3.60	0.28	154	676.68	0.21	0.10	0.10	0.00
4.00	0.48	280	676.80	0.36	0.25	0.11	0.00
4.40	0.79	508	676.95	0.58	0.47	0.11	0.00
4.80	1.13	897	677.14	0.78	0.67	0.11	0.00
5.20	1.41	1,474	677.38	0.98	0.87	0.12	0.00
5.60	**1.50**	2,061	677.60	1.13	1.01	0.12	0.00
6.00	1.39	**2,477**	**677.75**	**1.22**	**1.10**	**0.12**	0.00
6.40	1.20	**2,572**	**677.78**	**1.24**	**1.12**	**0.12**	0.00
6.80	1.02	2,413	677.73	1.21	1.09	0.12	0.00
7.20	0.91	2,108	677.62	1.14	1.02	0.12	0.00
7.60	0.81	1,763	677.49	1.06	0.94	0.12	0.00
8.00	0.71	1,406	677.35	0.96	0.85	0.12	0.00
8.40	0.61	1,055	677.20	0.84	0.73	0.11	0.00
8.80	0.54	741	677.06	0.71	0.60	0.11	0.00
9.20	0.52	550	676.97	0.61	0.50	0.11	0.00
9.60	0.44	440	676.91	0.52	0.41	0.11	0.00
10.00	0.37	336	676.85	0.42	0.31	0.11	0.00
10.40	0.36	294	676.81	0.37	0.27	0.11	0.00
10.80	0.36	285	676.81	0.36	0.26	0.11	0.00
11.20	0.32	274	676.80	0.35	0.24	0.11	0.00
11.60	0.22	209	676.74	0.27	0.17	0.11	0.00
12.00	0.28	190	676.72	0.25	0.14	0.11	0.00
12.40	0.07	139	676.66	0.18	0.08	0.10	0.00
12.80	0.01	40	673.63	0.02	0.00	0.02	0.00
13.20	0.00	39	673.53	0.00	0.00	0.00	0.00
13.60	0.00	39	673.51	0.00	0.00	0.00	0.00
14.00	0.00	39	673.50	0.00	0.00	0.00	0.00
14.40	0.00	39	673.50	0.00	0.00	0.00	0.00
14.80	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.10 cfs @ 11.90 hrs, Volume= 0.455 af, Depth= 1.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=3.14"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.04	0.00	0.00
1.20	0.08	0.00	0.00
1.60	0.12	0.00	0.00
2.00	0.16	0.00	0.00
2.40	0.21	0.00	0.00
2.80	0.25	0.00	0.00
3.20	0.29	0.00	0.00
3.60	0.33	0.00	0.00
4.00	0.38	0.00	0.00
4.40	0.42	0.00	0.00
4.80	0.46	0.00	0.01
5.20	0.51	0.01	0.03
5.60	0.57	0.01	0.05
6.00	0.63	0.02	0.08
6.40	0.68	0.03	0.10
6.80	0.74	0.05	0.12
7.20	0.80	0.06	0.14
7.60	0.86	0.08	0.16
8.00	0.92	0.10	0.20
8.40	1.00	0.13	0.24
8.80	1.07	0.16	0.28
9.20	1.16	0.20	0.33
9.60	1.25	0.24	0.38
10.00	1.35	0.30	0.44
10.40	1.47	0.36	0.57
10.80	1.63	0.45	0.77
11.20	1.80	0.56	0.94
11.60	1.98	0.68	**1.04**
12.00	2.16	0.80	**1.09**
12.40	2.31	0.91	0.99
12.80	2.44	1.01	0.85
13.20	2.54	1.09	0.74
13.60	2.63	1.16	0.62
14.00	2.71	1.22	0.53
14.40	2.77	1.27	0.45
14.80	2.83	1.31	0.38
15.20	2.87	1.35	0.34
15.60	2.92	1.38	0.30
16.00	2.96	1.41	0.30
16.40	3.00	1.45	0.30
16.80	3.04	1.48	0.26
17.20	3.07	1.50	0.22
17.60	3.10	1.53	0.23
18.00	**3.14**	**1.56**	0.28
18.40	3.14	1.56	0.03
18.80	3.14	1.56	0.00
19.20	3.14	1.56	0.00
19.60	3.14	1.56	0.00
20.00	3.14	1.56	0.00
20.40	3.14	1.56	0.00
20.80	3.14	1.56	0.00

Summary for Subcatchment 7S: South Property


Runoff = 2.33 cfs @ 12.03 hrs, Volume= 0.975 af, Depth= 1.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=3.14"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.04	0.00	0.00
1.20	0.08	0.00	0.00
1.60	0.12	0.00	0.00
2.00	0.16	0.00	0.00
2.40	0.21	0.00	0.00
2.80	0.25	0.00	0.00
3.20	0.29	0.00	0.00
3.60	0.33	0.00	0.00
4.00	0.38	0.00	0.00
4.40	0.42	0.00	0.00
4.80	0.46	0.00	0.01
5.20	0.51	0.01	0.05
5.60	0.57	0.01	0.10
6.00	0.63	0.02	0.15
6.40	0.68	0.03	0.20
6.80	0.74	0.05	0.24
7.20	0.80	0.06	0.28
7.60	0.86	0.08	0.32
8.00	0.92	0.10	0.40
8.40	1.00	0.13	0.48
8.80	1.07	0.16	0.57
9.20	1.16	0.20	0.67
9.60	1.25	0.24	0.78
10.00	1.35	0.30	0.90
10.40	1.47	0.36	1.12
10.80	1.63	0.45	1.52
11.20	1.80	0.56	1.93
11.60	1.98	0.68	2.16
12.00	2.16	0.80	**2.32**
12.40	2.31	0.91	**2.18**
12.80	2.44	1.01	1.91
13.20	2.54	1.09	1.65
13.60	2.63	1.16	1.40
14.00	2.71	1.22	1.19
14.40	2.77	1.27	1.01
14.80	2.83	1.31	0.85
15.20	2.87	1.35	0.75
15.60	2.92	1.38	0.66
16.00	2.96	1.41	0.64
16.40	3.00	1.45	0.64
16.80	3.04	1.48	0.59
17.20	3.07	1.50	0.50
17.60	3.10	1.53	0.48
18.00	**3.14**	**1.56**	0.57
18.40	3.14	1.56	0.21
18.80	3.14	1.56	0.02
19.20	3.14	1.56	0.00
19.60	3.14	1.56	0.00
20.00	3.14	1.56	0.00
20.40	3.14	1.56	0.00
20.80	3.14	1.56	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.34 cfs @ 12.17 hrs, Volume= 0.142 af, Depth= 1.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=3.14"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.04	0.00	0.00
1.20	0.08	0.00	0.00
1.60	0.12	0.00	0.00
2.00	0.16	0.00	0.00
2.40	0.21	0.00	0.00
2.80	0.25	0.00	0.00
3.20	0.29	0.00	0.00
3.60	0.33	0.00	0.00
4.00	0.38	0.00	0.00
4.40	0.42	0.00	0.00
4.80	0.46	0.00	0.00
5.20	0.51	0.00	0.00
5.60	0.57	0.00	0.00
6.00	0.63	0.01	0.01
6.40	0.68	0.02	0.02
6.80	0.74	0.03	0.03
7.20	0.80	0.04	0.03
7.60	0.86	0.05	0.04
8.00	0.92	0.07	0.05
8.40	1.00	0.10	0.06
8.80	1.07	0.12	0.07
9.20	1.16	0.16	0.09
9.60	1.25	0.20	0.10
10.00	1.35	0.24	0.12
10.40	1.47	0.30	0.15
10.80	1.63	0.38	0.20
11.20	1.80	0.48	0.26
11.60	1.98	0.59	0.31
12.00	2.16	0.71	**0.34**
12.40	2.31	0.81	**0.33**
12.80	2.44	0.90	0.30
13.20	2.54	0.97	0.26
13.60	2.63	1.04	0.22
14.00	2.71	1.10	0.19
14.40	2.77	1.14	0.16
14.80	2.83	1.18	0.14
15.20	2.87	1.22	0.12
15.60	2.92	1.25	0.10
16.00	2.96	1.28	0.10
16.40	3.00	1.31	0.10
16.80	3.04	1.34	0.09
17.20	3.07	1.37	0.08
17.60	3.10	1.39	0.07
18.00	**3.14**	**1.42**	0.08
18.40	3.14	1.42	0.06
18.80	3.14	1.42	0.01
19.20	3.14	1.42	0.00
19.60	3.14	1.42	0.00
20.00	3.14	1.42	0.00
20.40	3.14	1.42	0.00
20.80	3.14	1.42	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.16 cfs @ 11.83 hrs, Volume= 0.065 af, Depth= 1.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=3.14"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.04	0.00	0.00
1.20	0.08	0.00	0.00
1.60	0.12	0.00	0.00
2.00	0.16	0.00	0.00
2.40	0.21	0.00	0.00
2.80	0.25	0.00	0.00
3.20	0.29	0.00	0.00
3.60	0.33	0.00	0.00
4.00	0.38	0.00	0.00
4.40	0.42	0.00	0.00
4.80	0.46	0.00	0.00
5.20	0.51	0.00	0.00
5.60	0.57	0.00	0.01
6.00	0.63	0.01	0.01
6.40	0.68	0.02	0.01
6.80	0.74	0.03	0.01
7.20	0.80	0.04	0.02
7.60	0.86	0.05	0.02
8.00	0.92	0.07	0.03
8.40	1.00	0.10	0.03
8.80	1.07	0.12	0.04
9.20	1.16	0.16	0.05
9.60	1.25	0.20	0.05
10.00	1.35	0.24	0.06
10.40	1.47	0.30	0.09
10.80	1.63	0.38	0.12
11.20	1.80	0.48	0.14
11.60	1.98	0.59	**0.15**
12.00	2.16	0.71	**0.16**
12.40	2.31	0.81	0.14
12.80	2.44	0.90	0.12
13.20	2.54	0.97	0.10
13.60	2.63	1.04	0.09
14.00	2.71	1.10	0.08
14.40	2.77	1.14	0.06
14.80	2.83	1.18	0.05
15.20	2.87	1.22	0.05
15.60	2.92	1.25	0.04
16.00	2.96	1.28	0.04
16.40	3.00	1.31	0.04
16.80	3.04	1.34	0.04
17.20	3.07	1.37	0.03
17.60	3.10	1.39	0.04
18.00	**3.14**	**1.42**	0.04
18.40	3.14	1.42	0.00
18.80	3.14	1.42	0.00
19.20	3.14	1.42	0.00
19.60	3.14	1.42	0.00
20.00	3.14	1.42	0.00
20.40	3.14	1.42	0.00
20.80	3.14	1.42	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	2.60 cfs @	12.02 hrs, Volume=	1.159 af
Outflow	=	0.67 cfs @	17.06 hrs, Volume=	0.613 af, Atten= 74%, Lag= 302.3 min
Primary	=	0.67 cfs @	17.06 hrs, Volume=	0.613 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Peak Elev= 671.79' @ 17.06 hrs Surf.Area= 30,758 sf Storage= 29,765 cf

Plug-Flow detention time= 286.6 min calculated for 0.613 af (53% of inflow)
Center-of-Mass det. time= 163.4 min (908.9 - 745.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.67 cfs @ 17.06 hrs HW=671.79' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.67 cfs @ 6.09 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
3.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.00	0	670.00	0.00	0.00	0.00	0.00
5.00	0.03	20	670.00	0.00	0.00	0.00	0.00
6.00	0.24	482	670.05	0.01	0.01	0.00	0.00
7.00	0.38	1,512	670.17	0.07	0.07	0.00	0.00
8.00	0.53	2,671	670.30	0.18	0.18	0.00	0.00
9.00	0.77	4,164	670.45	0.27	0.27	0.00	0.00
10.00	1.07	6,301	670.67	0.37	0.37	0.00	0.00
11.00	1.99	10,038	670.89	0.45	0.45	0.00	0.00
12.00	**2.60**	16,738	671.20	0.54	0.54	0.00	0.00
13.00	**2.01**	23,164	671.49	0.61	0.61	0.00	0.00
14.00	1.38	26,976	671.66	0.65	0.65	0.00	0.00
15.00	0.95	28,751	671.74	0.66	0.66	0.00	0.00
16.00	0.80	29,412	671.77	0.67	0.67	0.00	0.00
17.00	0.68	**29,764**	**671.79**	**0.67**	**0.67**	0.00	0.00
18.00	0.71	**29,662**	**671.78**	**0.67**	**0.67**	0.00	0.00
19.00	0.01	28,393	671.73	0.66	0.66	0.00	0.00
20.00	0.00	26,065	671.62	0.64	0.64	0.00	0.00
21.00	0.00	23,812	671.52	0.61	0.61	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	1.43 cfs @	11.95 hrs, Volume=	0.597 af
Outflow	=	1.21 cfs @	12.67 hrs, Volume=	0.596 af, Atten= 15%, Lag= 43.0 min
Primary	=	1.09 cfs @	12.67 hrs, Volume=	0.478 af
Secondary	=	0.12 cfs @	12.67 hrs, Volume=	0.118 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Peak Elev= 677.74' @ 12.67 hrs Surf.Area= 2,894 sf Storage= 2,455 cf

Plug-Flow detention time= 22.1 min calculated for 0.596 af (100% of inflow)
Center-of-Mass det. time= 21.5 min (767.2 - 745.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.09 cfs @ 12.67 hrs HW=677.74' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 1.09 cfs @ 4.75 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.12 cfs @ 12.67 hrs HW=677.74' TW=671.41' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.84 fps)
└—5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.00	0	670.75	0.00	0.00	0.00	0.00
4.00	0.00	0	670.75	0.00	0.00	0.00	0.00
5.00	0.02	15	671.80	0.00	0.00	0.00	0.00
6.00	0.09	64	675.33	0.08	0.00	0.08	0.00
7.00	0.16	110	676.61	0.14	0.04	0.10	0.00
8.00	0.24	166	676.70	0.22	0.12	0.10	0.00
9.00	0.38	271	676.80	0.35	0.24	0.11	0.00
10.00	0.56	425	676.90	0.50	0.40	0.11	0.00
11.00	**1.11**	976	677.17	0.81	0.70	0.11	0.00
12.00	**1.43**	**2,095**	**677.62**	**1.14**	**1.02**	**0.12**	0.00
13.00	1.07	**2,376**	**677.72**	**1.20**	**1.08**	**0.12**	0.00
14.00	0.72	1,552	677.41	1.00	0.89	0.12	0.00
15.00	0.48	642	677.02	0.67	0.56	0.11	0.00
16.00	0.40	331	676.84	0.41	0.31	0.11	0.00
17.00	0.33	281	676.81	0.36	0.25	0.11	0.00
18.00	0.36	255	676.79	0.33	0.22	0.11	0.00
19.00	0.00	39	673.56	0.00	0.00	0.00	0.00
20.00	0.00	39	673.50	0.00	0.00	0.00	0.00
21.00	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.91 cfs @ 15.82 hrs, Volume= 0.503 af, Depth= 1.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=3.34"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.00	0.00	0.00
0.70	0.02	0.00	0.00
1.05	0.04	0.00	0.00
1.40	0.07	0.00	0.00
1.75	0.10	0.00	0.00
2.10	0.13	0.00	0.00
2.45	0.16	0.00	0.00
2.80	0.19	0.00	0.00
3.15	0.22	0.00	0.00
3.50	0.25	0.00	0.00
3.85	0.28	0.00	0.00
4.20	0.31	0.00	0.00
4.55	0.33	0.00	0.00
4.90	0.36	0.00	0.00
5.25	0.39	0.00	0.00
5.60	0.42	0.00	0.00
5.95	0.45	0.00	0.01
6.30	0.48	0.00	0.02
6.65	0.52	0.01	0.03
7.00	0.55	0.01	0.04
7.35	0.59	0.02	0.05
7.70	0.63	0.02	0.07
8.05	0.67	0.03	0.08
8.40	0.71	0.04	0.09
8.75	0.75	0.05	0.10
9.10	0.79	0.06	0.11
9.45	0.83	0.07	0.12
9.80	0.87	0.08	0.13
10.15	0.91	0.10	0.14
10.50	0.96	0.12	0.16
10.85	1.01	0.14	0.19
11.20	1.06	0.16	0.21
11.55	1.11	0.18	0.23
11.90	1.17	0.21	0.26
12.25	1.23	0.23	0.28
12.60	1.29	0.27	0.31
12.95	1.36	0.30	0.34
13.30	1.43	0.34	0.37
13.65	1.51	0.38	0.44
14.00	1.60	0.44	0.54
14.35	1.71	0.51	0.65
14.70	1.83	0.58	0.75
15.05	1.95	0.66	0.81
15.40	2.08	0.75	0.86
15.75	2.21	0.84	**0.90**
16.10	2.33	0.93	**0.87**
16.45	2.43	1.00	0.81
16.80	2.53	1.08	0.74
17.15	2.61	1.14	0.67
17.50	2.69	1.20	0.61
17.85	2.75	1.25	0.54
18.20	2.81	1.30	0.48
18.55	2.87	1.34	0.43
18.90	2.91	1.38	0.39
19.25	2.96	1.41	0.35
19.60	2.99	1.44	0.31
19.95	3.03	1.47	0.29
20.30	3.06	1.50	0.27
20.65	3.09	1.52	0.25
21.00	3.12	1.54	0.24
21.35	3.15	1.57	0.24
21.70	3.18	1.59	0.24
22.05	3.21	1.61	0.23
22.40	3.23	1.63	0.21
22.75	3.25	1.65	0.18
23.10	3.27	1.67	0.17
23.45	3.30	1.69	0.19
23.80	**3.32**	**1.71**	0.22
24.15	**3.34**	**1.72**	0.19
24.50	3.34	1.72	0.01
24.85	3.34	1.72	0.00
25.20	3.34	1.72	0.00
25.55	3.34	1.72	0.00
25.90	3.34	1.72	0.00
26.25	3.34	1.72	0.00
26.60	3.34	1.72	0.00
26.95	3.34	1.72	0.00

Summary for Subcatchment 7S: South Property


Runoff = 1.93 cfs @ 15.91 hrs, Volume= 1.078 af, Depth= 1.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=3.34"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.00	0.00	0.00
0.70	0.02	0.00	0.00
1.05	0.04	0.00	0.00
1.40	0.07	0.00	0.00
1.75	0.10	0.00	0.00
2.10	0.13	0.00	0.00
2.45	0.16	0.00	0.00
2.80	0.19	0.00	0.00
3.15	0.22	0.00	0.00
3.50	0.25	0.00	0.00
3.85	0.28	0.00	0.00
4.20	0.31	0.00	0.00
4.55	0.33	0.00	0.00
4.90	0.36	0.00	0.00
5.25	0.39	0.00	0.00
5.60	0.42	0.00	0.00
5.95	0.45	0.00	0.01
6.30	0.48	0.00	0.03
6.65	0.52	0.01	0.05
7.00	0.55	0.01	0.07
7.35	0.59	0.02	0.10
7.70	0.63	0.02	0.13
8.05	0.67	0.03	0.16
8.40	0.71	0.04	0.18
8.75	0.75	0.05	0.20
9.10	0.79	0.06	0.23
9.45	0.83	0.07	0.25
9.80	0.87	0.08	0.27
10.15	0.91	0.10	0.30
10.50	0.96	0.12	0.34
10.85	1.01	0.14	0.38
11.20	1.06	0.16	0.43
11.55	1.11	0.18	0.48
11.90	1.17	0.21	0.53
12.25	1.23	0.23	0.59
12.60	1.29	0.27	0.65
12.95	1.36	0.30	0.71
13.30	1.43	0.34	0.77
13.65	1.51	0.38	0.88
14.00	1.60	0.44	1.08
14.35	1.71	0.51	1.32
14.70	1.83	0.58	1.55
15.05	1.95	0.66	1.70
15.40	2.08	0.75	1.80
15.75	2.21	0.84	**1.90**
16.10	2.33	0.93	**1.90**
16.45	2.43	1.00	1.78
16.80	2.53	1.08	1.63
17.15	2.61	1.14	1.47
17.50	2.69	1.20	1.34
17.85	2.75	1.25	1.21
18.20	2.81	1.30	1.07
18.55	2.87	1.34	0.96
18.90	2.91	1.38	0.87
19.25	2.96	1.41	0.77
19.60	2.99	1.44	0.69
19.95	3.03	1.47	0.63
20.30	3.06	1.50	0.58
20.65	3.09	1.52	0.54
21.00	3.12	1.54	0.52
21.35	3.15	1.57	0.52
21.70	3.18	1.59	0.52
22.05	3.21	1.61	0.51
22.40	3.23	1.63	0.46
22.75	3.25	1.65	0.41
23.10	3.27	1.67	0.37
23.45	3.30	1.69	0.40
23.80	**3.32**	**1.71**	0.45
24.15	**3.34**	**1.72**	0.47
24.50	3.34	1.72	0.09
24.85	3.34	1.72	0.01
25.20	3.34	1.72	0.00
25.55	3.34	1.72	0.00
25.90	3.34	1.72	0.00
26.25	3.34	1.72	0.00
26.60	3.34	1.72	0.00
26.95	3.34	1.72	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.29 cfs @ 16.05 hrs, Volume= 0.158 af, Depth= 1.58"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=3.34"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.00	0.00	0.00
0.70	0.02	0.00	0.00
1.05	0.04	0.00	0.00
1.40	0.07	0.00	0.00
1.75	0.10	0.00	0.00
2.10	0.13	0.00	0.00
2.45	0.16	0.00	0.00
2.80	0.19	0.00	0.00
3.15	0.22	0.00	0.00
3.50	0.25	0.00	0.00
3.85	0.28	0.00	0.00
4.20	0.31	0.00	0.00
4.55	0.33	0.00	0.00
4.90	0.36	0.00	0.00
5.25	0.39	0.00	0.00
5.60	0.42	0.00	0.00
5.95	0.45	0.00	0.00
6.30	0.48	0.00	0.00
6.65	0.52	0.00	0.00
7.00	0.55	0.00	0.00
7.35	0.59	0.01	0.01
7.70	0.63	0.01	0.01
8.05	0.67	0.02	0.02
8.40	0.71	0.02	0.02
8.75	0.75	0.03	0.02
9.10	0.79	0.04	0.03
9.45	0.83	0.05	0.03
9.80	0.87	0.06	0.03
10.15	0.91	0.07	0.04
10.50	0.96	0.08	0.04
10.85	1.01	0.10	0.05
11.20	1.06	0.12	0.06
11.55	1.11	0.14	0.06
11.90	1.17	0.16	0.07
12.25	1.23	0.19	0.08
12.60	1.29	0.21	0.09
12.95	1.36	0.24	0.10
13.30	1.43	0.28	0.11
13.65	1.51	0.32	0.12
14.00	1.60	0.37	0.15
14.35	1.71	0.43	0.18
14.70	1.83	0.50	0.21
15.05	1.95	0.58	0.24
15.40	2.08	0.66	0.26
15.75	2.21	0.74	**0.28**
16.10	2.33	0.82	**0.28**
16.45	2.43	0.89	0.27
16.80	2.53	0.96	0.25
17.15	2.61	1.02	0.23
17.50	2.69	1.08	0.21
17.85	2.75	1.13	0.19
18.20	2.81	1.17	0.17
18.55	2.87	1.21	0.15
18.90	2.91	1.25	0.14
19.25	2.96	1.28	0.12
19.60	2.99	1.31	0.11
19.95	3.03	1.34	0.10
20.30	3.06	1.36	0.09
20.65	3.09	1.38	0.08
21.00	3.12	1.41	0.08
21.35	3.15	1.43	0.08
21.70	3.18	1.45	0.08
22.05	3.21	1.47	0.08
22.40	3.23	1.49	0.07
22.75	3.25	1.51	0.07
23.10	3.27	1.53	0.06
23.45	3.30	1.55	0.06
23.80	**3.32**	**1.57**	0.07
24.15	**3.34**	**1.58**	0.07
24.50	3.34	1.58	0.03
24.85	3.34	1.58	0.01
25.20	3.34	1.58	0.00
25.55	3.34	1.58	0.00
25.90	3.34	1.58	0.00
26.25	3.34	1.58	0.00
26.60	3.34	1.58	0.00
26.95	3.34	1.58	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.13 cfs @ 15.73 hrs, Volume= 0.072 af, Depth= 1.58"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=3.34"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.00	0.00	0.00
0.70	0.02	0.00	0.00
1.05	0.04	0.00	0.00
1.40	0.07	0.00	0.00
1.75	0.10	0.00	0.00
2.10	0.13	0.00	0.00
2.45	0.16	0.00	0.00
2.80	0.19	0.00	0.00
3.15	0.22	0.00	0.00
3.50	0.25	0.00	0.00
3.85	0.28	0.00	0.00
4.20	0.31	0.00	0.00
4.55	0.33	0.00	0.00
4.90	0.36	0.00	0.00
5.25	0.39	0.00	0.00
5.60	0.42	0.00	0.00
5.95	0.45	0.00	0.00
6.30	0.48	0.00	0.00
6.65	0.52	0.00	0.00
7.00	0.55	0.00	0.00
7.35	0.59	0.01	0.01
7.70	0.63	0.01	0.01
8.05	0.67	0.02	0.01
8.40	0.71	0.02	0.01
8.75	0.75	0.03	0.01
9.10	0.79	0.04	0.01
9.45	0.83	0.05	0.02
9.80	0.87	0.06	0.02
10.15	0.91	0.07	0.02
10.50	0.96	0.08	0.02
10.85	1.01	0.10	0.03
11.20	1.06	0.12	0.03
11.55	1.11	0.14	0.03
11.90	1.17	0.16	0.04
12.25	1.23	0.19	0.04
12.60	1.29	0.21	0.04
12.95	1.36	0.24	0.05
13.30	1.43	0.28	0.05
13.65	1.51	0.32	0.07
14.00	1.60	0.37	0.08
14.35	1.71	0.43	0.10
14.70	1.83	0.50	0.11
15.05	1.95	0.58	0.12
15.40	2.08	0.66	0.13
15.75	2.21	0.74	**0.13**
16.10	2.33	0.82	0.13
16.45	2.43	0.89	0.12
16.80	2.53	0.96	0.11
17.15	2.61	1.02	0.10
17.50	2.69	1.08	0.09
17.85	2.75	1.13	0.08
18.20	2.81	1.17	0.07
18.55	2.87	1.21	0.06
18.90	2.91	1.25	0.06
19.25	2.96	1.28	0.05
19.60	2.99	1.31	0.05
19.95	3.03	1.34	0.04
20.30	3.06	1.36	0.04
20.65	3.09	1.38	0.04
21.00	3.12	1.41	0.04
21.35	3.15	1.43	0.04
21.70	3.18	1.45	0.04
22.05	3.21	1.47	0.03
22.40	3.23	1.49	0.03
22.75	3.25	1.51	0.03
23.10	3.27	1.53	0.03
23.45	3.30	1.55	0.03
23.80	**3.32**	**1.57**	0.03
24.15	**3.34**	**1.58**	0.01
24.50	3.34	1.58	0.00
24.85	3.34	1.58	0.00
25.20	3.34	1.58	0.00
25.55	3.34	1.58	0.00
25.90	3.34	1.58	0.00
26.25	3.34	1.58	0.00
26.60	3.34	1.58	0.00
26.95	3.34	1.58	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	2.17 cfs @	15.90 hrs, Volume=	1.305 af
Outflow	=	0.67 cfs @	20.86 hrs, Volume=	0.785 af, Atten= 69%, Lag= 297.5 min
Primary	=	0.67 cfs @	20.86 hrs, Volume=	0.785 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Peak Elev= 671.77' @ 20.86 hrs Surf.Area= 30,754 sf Storage= 29,460 cf

Plug-Flow detention time= 331.6 min calculated for 0.783 af (60% of inflow)
Center-of-Mass det. time= 188.1 min (1,169.0 - 980.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.67 cfs @ 20.86 hrs HW=671.77' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.67 cfs @ 6.06 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.70	0.00	0	670.00	0.00	0.00	0.00	0.00
1.40	0.00	0	670.00	0.00	0.00	0.00	0.00
2.10	0.00	0	670.00	0.00	0.00	0.00	0.00
2.80	0.00	0	670.00	0.00	0.00	0.00	0.00
3.50	0.00	0	670.00	0.00	0.00	0.00	0.00
4.20	0.00	0	670.00	0.00	0.00	0.00	0.00
4.90	0.00	0	670.00	0.00	0.00	0.00	0.00
5.60	0.00	0	670.00	0.00	0.00	0.00	0.00
6.30	0.03	23	670.00	0.00	0.00	0.00	0.00
7.00	0.11	177	670.02	0.00	0.00	0.00	0.00
7.70	0.21	565	670.06	0.01	0.01	0.00	0.00
8.40	0.29	1,135	670.13	0.04	0.04	0.00	0.00
9.10	0.34	1,776	670.20	0.09	0.09	0.00	0.00
9.80	0.39	2,395	670.27	0.15	0.15	0.00	0.00
10.50	0.46	3,006	670.34	0.21	0.21	0.00	0.00
11.20	0.56	3,714	670.41	0.25	0.25	0.00	0.00
11.90	0.68	4,576	670.50	0.29	0.29	0.00	0.00
12.60	0.80	5,620	670.60	0.34	0.34	0.00	0.00
13.30	0.93	6,867	670.72	0.39	0.39	0.00	0.00
14.00	1.27	8,510	670.81	0.42	0.42	0.00	0.00
14.70	1.77	11,187	670.94	0.46	0.46	0.00	0.00
15.40	**2.05**	14,777	671.11	0.51	0.51	0.00	0.00
16.10	**2.14**	18,792	671.30	0.56	0.56	0.00	0.00
16.80	1.85	22,430	671.46	0.60	0.60	0.00	0.00
17.50	1.54	25,184	671.58	0.63	0.63	0.00	0.00
18.20	1.26	27,142	671.67	0.65	0.65	0.00	0.00
18.90	1.03	28,394	671.73	0.66	0.66	0.00	0.00
19.60	0.84	29,097	671.76	0.67	0.67	0.00	0.00
20.30	0.73	**29,404**	**671.77**	**0.67**	**0.67**	0.00	0.00
21.00	0.67	**29,459**	**671.77**	**0.67**	**0.67**	0.00	0.00
21.70	0.67	29,448	671.77	0.67	0.67	0.00	0.00
22.40	0.60	29,388	671.77	0.67	0.67	0.00	0.00
23.10	0.50	29,094	671.76	0.67	0.67	0.00	0.00
23.80	0.59	28,761	671.74	0.66	0.66	0.00	0.00
24.50	0.20	28,390	671.72	0.66	0.66	0.00	0.00
25.20	0.00	26,902	671.66	0.65	0.65	0.00	0.00
25.90	0.00	25,296	671.59	0.63	0.63	0.00	0.00
26.60	0.00	23,728	671.52	0.61	0.61	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	16.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	1.19 cfs @	15.85 hrs, Volume=	0.661 af
Outflow	=	1.08 cfs @	16.50 hrs, Volume=	0.660 af, Atten= 9%, Lag= 39.2 min
Primary	=	0.96 cfs @	16.50 hrs, Volume=	0.505 af
Secondary	=	0.12 cfs @	16.50 hrs, Volume=	0.155 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Peak Elev= 677.52' @ 16.50 hrs Surf.Area= 2,651 sf Storage= 1,836 cf

Plug-Flow detention time= 19.1 min calculated for 0.660 af (100% of inflow)
Center-of-Mass det. time= 18.3 min (1,000.9 - 982.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.96 cfs @ 16.50 hrs HW=677.52' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 0.96 cfs @ 4.17 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.12 cfs @ 16.50 hrs HW=677.52' TW=671.40' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.58 fps)
└—5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.70	0.00	0	670.75	0.00	0.00	0.00	0.00
1.40	0.00	0	670.75	0.00	0.00	0.00	0.00
2.10	0.00	0	670.75	0.00	0.00	0.00	0.00
2.80	0.00	0	670.75	0.00	0.00	0.00	0.00
3.50	0.00	0	670.75	0.00	0.00	0.00	0.00
4.20	0.00	0	670.75	0.00	0.00	0.00	0.00
4.90	0.00	0	670.75	0.00	0.00	0.00	0.00
5.60	0.00	0	670.75	0.00	0.00	0.00	0.00
6.30	0.02	15	671.85	0.00	0.00	0.00	0.00
7.00	0.04	45	673.98	0.04	0.00	0.04	0.00
7.70	0.08	59	675.00	0.07	0.00	0.07	0.00
8.40	0.11	79	676.38	0.10	0.00	0.10	0.00
9.10	0.13	101	676.59	0.13	0.03	0.10	0.00
9.80	0.16	117	676.63	0.15	0.05	0.10	0.00
10.50	0.21	146	676.67	0.19	0.09	0.10	0.00
11.20	0.26	186	676.72	0.24	0.14	0.10	0.00
11.90	0.33	235	676.77	0.31	0.20	0.11	0.00
12.60	0.40	294	676.82	0.37	0.27	0.11	0.00
13.30	0.48	361	676.86	0.45	0.34	0.11	0.00
14.00	0.69	514	676.95	0.58	0.47	0.11	0.00
14.70	0.97	886	677.13	0.78	0.67	0.11	0.00
15.40	**1.12**	1,349	677.33	0.94	0.83	0.11	0.00
16.10	**1.16**	**1,757**	**677.49**	**1.06**	**0.94**	**0.12**	0.00
16.80	0.99	**1,797**	**677.51**	**1.07**	**0.95**	**0.12**	0.00
17.50	0.82	1,475	677.38	0.98	0.87	0.12	0.00
18.20	0.65	1,028	677.19	0.83	0.72	0.11	0.00
18.90	0.53	627	677.01	0.66	0.55	0.11	0.00
19.60	0.42	391	676.88	0.47	0.37	0.11	0.00
20.30	0.36	302	676.82	0.38	0.27	0.11	0.00
21.00	0.32	256	676.79	0.33	0.22	0.11	0.00
21.70	0.32	250	676.78	0.32	0.22	0.11	0.00
22.40	0.28	228	676.76	0.30	0.19	0.11	0.00
23.10	0.23	184	676.72	0.24	0.14	0.10	0.00
23.80	0.28	202	676.74	0.26	0.16	0.11	0.00
24.50	0.04	106	676.61	0.14	0.04	0.10	0.00
25.20	0.00	39	673.51	0.00	0.00	0.00	0.00
25.90	0.00	39	673.51	0.00	0.00	0.00	0.00
26.60	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.55 cfs @ 41.44 hrs, Volume= 0.582 af, Depth= 1.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=3.66"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.02	0.00	0.00
2.40	0.04	0.00	0.00
3.00	0.06	0.00	0.00
3.60	0.08	0.00	0.00
4.20	0.11	0.00	0.00
4.80	0.13	0.00	0.00
5.40	0.16	0.00	0.00
6.00	0.19	0.00	0.00
6.60	0.22	0.00	0.00
7.20	0.25	0.00	0.00
7.80	0.28	0.00	0.00
8.40	0.30	0.00	0.00
9.00	0.32	0.00	0.00
9.60	0.34	0.00	0.00
10.20	0.36	0.00	0.00
10.80	0.39	0.00	0.00
11.40	0.41	0.00	0.00
12.00	0.44	0.00	0.00
12.60	0.47	0.00	0.01
13.20	0.50	0.00	0.01
13.80	0.52	0.01	0.02
14.40	0.55	0.01	0.02
15.00	0.58	0.01	0.02
15.60	0.61	0.02	0.03
16.20	0.64	0.02	0.03
16.80	0.67	0.03	0.03
17.40	0.70	0.04	0.04
18.00	0.72	0.04	0.04
18.60	0.75	0.05	0.04
19.20	0.78	0.06	0.05
19.80	0.81	0.07	0.05
20.40	0.84	0.07	0.05
21.00	0.87	0.08	0.05
21.60	0.90	0.09	0.06
22.20	0.92	0.10	0.06
22.80	0.95	0.11	0.06
23.40	0.98	0.12	0.06
24.00	1.01	0.14	0.07
24.60	1.04	0.15	0.07
25.20	1.07	0.16	0.08
25.80	1.11	0.18	0.09
26.40	1.14	0.19	0.10
27.00	1.18	0.21	0.10
27.60	1.22	0.23	0.10
28.20	1.25	0.24	0.09
28.80	1.28	0.26	0.09
29.40	1.31	0.27	0.09
30.00	1.34	0.29	0.10
30.60	1.37	0.31	0.11
31.20	1.41	0.33	0.12
31.80	1.45	0.35	0.13
32.40	1.50	0.38	0.15
33.00	1.55	0.41	0.17
33.60	1.60	0.44	0.19
34.20	1.66	0.47	0.20
34.80	1.72	0.51	0.21
35.40	1.77	0.54	0.21
36.00	1.83	0.58	0.22
36.60	1.89	0.62	0.23
37.20	1.95	0.66	0.26
37.80	2.02	0.71	0.28
38.40	2.10	0.76	0.30
39.00	2.18	0.82	0.35
39.60	2.27	0.89	0.40
40.20	2.38	0.97	0.46
40.80	2.50	1.05	0.52
41.40	2.62	1.15	**0.65**
42.00	2.74	1.24	0.55
42.60	2.86	1.33	0.55
43.20	2.97	1.43	0.54
43.80	3.08	1.51	0.52
44.40	3.18	1.60	0.48
45.00	3.27	1.67	0.43
45.60	3.35	1.74	0.39
46.20	3.43	1.80	0.37
46.80	3.51	1.86	0.38
47.40	3.58	1.93	0.38
48.00	**3.66**	**1.99**	0.38
48.60	3.66	1.99	0.01
49.20	3.66	1.99	0.00
49.80	3.66	1.99	0.00

Summary for Subcatchment 7S: South Property


Runoff = 1.18 cfs @ 41.70 hrs, Volume= 1.246 af, Depth= 1.99"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=3.66"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.02	0.00	0.00
2.40	0.04	0.00	0.00
3.00	0.06	0.00	0.00
3.60	0.08	0.00	0.00
4.20	0.11	0.00	0.00
4.80	0.13	0.00	0.00
5.40	0.16	0.00	0.00
6.00	0.19	0.00	0.00
6.60	0.22	0.00	0.00
7.20	0.25	0.00	0.00
7.80	0.28	0.00	0.00
8.40	0.30	0.00	0.00
9.00	0.32	0.00	0.00
9.60	0.34	0.00	0.00
10.20	0.36	0.00	0.00
10.80	0.39	0.00	0.00
11.40	0.41	0.00	0.00
12.00	0.44	0.00	0.00
12.60	0.47	0.00	0.01
13.20	0.50	0.00	0.02
13.80	0.52	0.01	0.03
14.40	0.55	0.01	0.04
15.00	0.58	0.01	0.05
15.60	0.61	0.02	0.06
16.20	0.64	0.02	0.06
16.80	0.67	0.03	0.07
17.40	0.70	0.04	0.08
18.00	0.72	0.04	0.09
18.60	0.75	0.05	0.09
19.20	0.78	0.06	0.10
19.80	0.81	0.07	0.10
20.40	0.84	0.07	0.11
21.00	0.87	0.08	0.12
21.60	0.90	0.09	0.12
22.20	0.92	0.10	0.13
22.80	0.95	0.11	0.13
23.40	0.98	0.12	0.14
24.00	1.01	0.14	0.14
24.60	1.04	0.15	0.15
25.20	1.07	0.16	0.17
25.80	1.11	0.18	0.19
26.40	1.14	0.19	0.21
27.00	1.18	0.21	0.22
27.60	1.22	0.23	0.21
28.20	1.25	0.24	0.20
28.80	1.28	0.26	0.19
29.40	1.31	0.27	0.19
30.00	1.34	0.29	0.21
30.60	1.37	0.31	0.23
31.20	1.41	0.33	0.25
31.80	1.45	0.35	0.28
32.40	1.50	0.38	0.32
33.00	1.55	0.41	0.36
33.60	1.60	0.44	0.40
34.20	1.66	0.47	0.44
34.80	1.72	0.51	0.45
35.40	1.77	0.54	0.46
36.00	1.83	0.58	0.46
36.60	1.89	0.62	0.49
37.20	1.95	0.66	0.54
37.80	2.02	0.71	0.59
38.40	2.10	0.76	0.64
39.00	2.18	0.82	0.72
39.60	2.27	0.89	0.84
40.20	2.38	0.97	0.96
40.80	2.50	1.05	1.10
41.40	2.62	1.15	**1.17**
42.00	2.74	1.24	**1.18**
42.60	2.86	1.33	1.17
43.20	2.97	1.43	1.16
43.80	3.08	1.51	1.12
44.40	3.18	1.60	1.04
45.00	3.27	1.67	0.95
45.60	3.35	1.74	0.86
46.20	3.43	1.80	0.80
46.80	3.51	1.86	0.81
47.40	3.58	1.93	0.81
48.00	**3.66**	**1.99**	0.81
48.60	3.66	1.99	0.08
49.20	3.66	1.99	0.00
49.80	3.66	1.99	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.18 cfs @ 42.20 hrs, Volume= 0.184 af, Depth= 1.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=3.66"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.02	0.00	0.00
2.40	0.04	0.00	0.00
3.00	0.06	0.00	0.00
3.60	0.08	0.00	0.00
4.20	0.11	0.00	0.00
4.80	0.13	0.00	0.00
5.40	0.16	0.00	0.00
6.00	0.19	0.00	0.00
6.60	0.22	0.00	0.00
7.20	0.25	0.00	0.00
7.80	0.28	0.00	0.00
8.40	0.30	0.00	0.00
9.00	0.32	0.00	0.00
9.60	0.34	0.00	0.00
10.20	0.36	0.00	0.00
10.80	0.39	0.00	0.00
11.40	0.41	0.00	0.00
12.00	0.44	0.00	0.00
12.60	0.47	0.00	0.00
13.20	0.50	0.00	0.00
13.80	0.52	0.00	0.00
14.40	0.55	0.00	0.00
15.00	0.58	0.01	0.00
15.60	0.61	0.01	0.01
16.20	0.64	0.01	0.01
16.80	0.67	0.02	0.01
17.40	0.70	0.02	0.01
18.00	0.72	0.03	0.01
18.60	0.75	0.03	0.01
19.20	0.78	0.04	0.01
19.80	0.81	0.04	0.01
20.40	0.84	0.05	0.01
21.00	0.87	0.06	0.01
21.60	0.90	0.07	0.02
22.20	0.92	0.07	0.02
22.80	0.95	0.08	0.02
23.40	0.98	0.09	0.02
24.00	1.01	0.10	0.02
24.60	1.04	0.11	0.02
25.20	1.07	0.12	0.02
25.80	1.11	0.14	0.03
26.40	1.14	0.15	0.03
27.00	1.18	0.17	0.03
27.60	1.22	0.18	0.03
28.20	1.25	0.19	0.03
28.80	1.28	0.21	0.03
29.40	1.31	0.22	0.03
30.00	1.34	0.24	0.03
30.60	1.37	0.25	0.03
31.20	1.41	0.27	0.04
31.80	1.45	0.29	0.04
32.40	1.50	0.31	0.04
33.00	1.55	0.34	0.05
33.60	1.60	0.37	0.06
34.20	1.66	0.40	0.06
34.80	1.72	0.43	0.06
35.40	1.77	0.47	0.07
36.00	1.83	0.50	0.07
36.60	1.89	0.54	0.07
37.20	1.95	0.58	0.08
37.80	2.02	0.62	0.09
38.40	2.10	0.67	0.09
39.00	2.18	0.72	0.10
39.60	2.27	0.78	0.12
40.20	2.38	0.86	0.14
40.80	2.50	0.94	0.16
41.40	2.62	1.03	0.18
42.00	2.74	1.12	**0.18**
42.60	2.86	1.21	**0.18**
43.20	2.97	1.29	0.18
43.80	3.08	1.38	0.17
44.40	3.18	1.46	0.16
45.00	3.27	1.53	0.15
45.60	3.35	1.59	0.13
46.20	3.43	1.65	0.12
46.80	3.51	1.71	0.12
47.40	3.58	1.78	0.12
48.00	**3.66**	**1.84**	0.13
48.60	3.66	1.84	0.03
49.20	3.66	1.84	0.00
49.80	3.66	1.84	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.08 cfs @ 41.66 hrs, Volume= 0.084 af, Depth= 1.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=3.66"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.02	0.00	0.00
2.40	0.04	0.00	0.00
3.00	0.06	0.00	0.00
3.60	0.08	0.00	0.00
4.20	0.11	0.00	0.00
4.80	0.13	0.00	0.00
5.40	0.16	0.00	0.00
6.00	0.19	0.00	0.00
6.60	0.22	0.00	0.00
7.20	0.25	0.00	0.00
7.80	0.28	0.00	0.00
8.40	0.30	0.00	0.00
9.00	0.32	0.00	0.00
9.60	0.34	0.00	0.00
10.20	0.36	0.00	0.00
10.80	0.39	0.00	0.00
11.40	0.41	0.00	0.00
12.00	0.44	0.00	0.00
12.60	0.47	0.00	0.00
13.20	0.50	0.00	0.00
13.80	0.52	0.00	0.00
14.40	0.55	0.00	0.00
15.00	0.58	0.01	0.00
15.60	0.61	0.01	0.00
16.20	0.64	0.01	0.00
16.80	0.67	0.02	0.00
17.40	0.70	0.02	0.00
18.00	0.72	0.03	0.00
18.60	0.75	0.03	0.01
19.20	0.78	0.04	0.01
19.80	0.81	0.04	0.01
20.40	0.84	0.05	0.01
21.00	0.87	0.06	0.01
21.60	0.90	0.07	0.01
22.20	0.92	0.07	0.01
22.80	0.95	0.08	0.01
23.40	0.98	0.09	0.01
24.00	1.01	0.10	0.01
24.60	1.04	0.11	0.01
25.20	1.07	0.12	0.01
25.80	1.11	0.14	0.01
26.40	1.14	0.15	0.01
27.00	1.18	0.17	0.01
27.60	1.22	0.18	0.01
28.20	1.25	0.19	0.01
28.80	1.28	0.21	0.01
29.40	1.31	0.22	0.01
30.00	1.34	0.24	0.01
30.60	1.37	0.25	0.02
31.20	1.41	0.27	0.02
31.80	1.45	0.29	0.02
32.40	1.50	0.31	0.02
33.00	1.55	0.34	0.02
33.60	1.60	0.37	0.03
34.20	1.66	0.40	0.03
34.80	1.72	0.43	0.03
35.40	1.77	0.47	0.03
36.00	1.83	0.50	0.03
36.60	1.89	0.54	0.03
37.20	1.95	0.58	0.04
37.80	2.02	0.62	0.04
38.40	2.10	0.67	0.05
39.00	2.18	0.72	0.05
39.60	2.27	0.78	0.06
40.20	2.38	0.86	0.07
40.80	2.50	0.94	0.08
41.40	2.62	1.03	**0.08**
42.00	2.74	1.12	**0.08**
42.60	2.86	1.21	0.08
43.20	2.97	1.29	0.08
43.80	3.08	1.38	0.08
44.40	3.18	1.46	0.07
45.00	3.27	1.53	0.06
45.60	3.35	1.59	0.06
46.20	3.43	1.65	0.06
46.80	3.51	1.71	0.06
47.40	3.58	1.78	0.06
48.00	**3.66**	**1.84**	0.06
48.60	3.66	1.84	0.00
49.20	3.66	1.84	0.00
49.80	3.66	1.84	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.37 cfs @	41.73 hrs, Volume=	1.593 af
Outflow	=	0.67 cfs @	48.33 hrs, Volume=	1.000 af, Atten= 51%, Lag= 396.3 min
Primary	=	0.67 cfs @	48.33 hrs, Volume=	1.000 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Peak Elev= 671.78' @ 48.33 hrs Surf.Area= 30,755 sf Storage= 29,560 cf

Plug-Flow detention time= 294.3 min calculated for 0.998 af (63% of inflow)
Center-of-Mass det. time= 40.6 min (2,311.0 - 2,270.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.67 cfs @ 48.33 hrs HW=671.78' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.67 cfs @ 6.07 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
1.20	0.00	0	670.00	0.00	0.00	0.00	0.00
2.40	0.00	0	670.00	0.00	0.00	0.00	0.00
3.60	0.00	0	670.00	0.00	0.00	0.00	0.00
4.80	0.00	0	670.00	0.00	0.00	0.00	0.00
6.00	0.00	0	670.00	0.00	0.00	0.00	0.00
7.20	0.00	0	670.00	0.00	0.00	0.00	0.00
8.40	0.00	0	670.00	0.00	0.00	0.00	0.00
9.60	0.00	0	670.00	0.00	0.00	0.00	0.00
10.80	0.00	0	670.00	0.00	0.00	0.00	0.00
12.00	0.00	2	670.00	0.00	0.00	0.00	0.00
13.20	0.02	56	670.01	0.00	0.00	0.00	0.00
14.40	0.08	247	670.03	0.00	0.00	0.00	0.00
15.60	0.10	558	670.06	0.01	0.01	0.00	0.00
16.80	0.12	930	670.10	0.03	0.03	0.00	0.00
18.00	0.14	1,314	670.15	0.05	0.05	0.00	0.00
19.20	0.16	1,679	670.19	0.08	0.08	0.00	0.00
20.40	0.18	2,007	670.22	0.11	0.11	0.00	0.00
21.60	0.20	2,295	670.26	0.14	0.14	0.00	0.00
22.80	0.22	2,549	670.29	0.16	0.16	0.00	0.00
24.00	0.24	2,777	670.31	0.19	0.19	0.00	0.00
25.20	0.28	3,019	670.34	0.21	0.21	0.00	0.00
26.40	0.32	3,373	670.37	0.23	0.23	0.00	0.00
27.60	0.33	3,758	670.41	0.25	0.25	0.00	0.00
28.80	0.30	4,001	670.44	0.27	0.27	0.00	0.00
30.00	0.33	4,164	670.45	0.27	0.27	0.00	0.00
31.20	0.37	4,447	670.48	0.29	0.29	0.00	0.00
32.40	0.44	4,891	670.53	0.31	0.31	0.00	0.00
33.60	0.54	5,598	670.60	0.34	0.34	0.00	0.00
34.80	0.58	6,500	670.68	0.38	0.38	0.00	0.00
36.00	0.60	7,371	670.76	0.40	0.40	0.00	0.00
37.20	0.68	8,320	670.81	0.42	0.42	0.00	0.00
38.40	0.79	9,627	670.87	0.44	0.44	0.00	0.00
39.60	1.01	11,460	670.96	0.47	0.47	0.00	0.00
40.80	**1.28**	14,257	671.09	0.51	0.51	0.00	0.00
42.00	**1.37**	17,818	671.25	0.55	0.55	0.00	0.00
43.20	1.35	21,256	671.41	0.59	0.59	0.00	0.00
44.40	1.22	24,311	671.54	0.62	0.62	0.00	0.00
45.60	1.02	26,483	671.64	0.64	0.64	0.00	0.00
46.80	0.97	27,922	671.70	0.65	0.65	0.00	0.00
48.00	0.98	**29,281**	**671.76**	**0.67**	**0.67**	0.00	0.00
49.20	0.01	**28,033**	**671.71**	**0.66**	**0.66**	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.73 cfs @	41.76 hrs, Volume=	0.765 af
Outflow	=	0.72 cfs @	42.85 hrs, Volume=	0.765 af, Atten= 1%, Lag= 65.8 min
Primary	=	0.61 cfs @	42.85 hrs, Volume=	0.502 af
Secondary	=	0.11 cfs @	42.85 hrs, Volume=	0.262 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Peak Elev= 677.07' @ 42.85 hrs Surf.Area= 2,166 sf Storage= 764 cf

Plug-Flow detention time= 14.8 min calculated for 0.763 af (100% of inflow)
Center-of-Mass det. time= 14.2 min (2,335.9 - 2,321.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.61 cfs @ 42.85 hrs HW=677.07' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 0.61 cfs @ 2.66 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 42.85 hrs HW=677.07' TW=671.37' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.11 cfs @ 9.02 fps)
└—5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.20	0.00	0	670.75	0.00	0.00	0.00	0.00
2.40	0.00	0	670.75	0.00	0.00	0.00	0.00
3.60	0.00	0	670.75	0.00	0.00	0.00	0.00
4.80	0.00	0	670.75	0.00	0.00	0.00	0.00
6.00	0.00	0	670.75	0.00	0.00	0.00	0.00
7.20	0.00	0	670.75	0.00	0.00	0.00	0.00
8.40	0.00	0	670.75	0.00	0.00	0.00	0.00
9.60	0.00	0	670.75	0.00	0.00	0.00	0.00
10.80	0.00	0	670.75	0.00	0.00	0.00	0.00
12.00	0.00	1	670.85	0.00	0.00	0.00	0.00
13.20	0.01	31	672.93	0.00	0.00	0.00	0.00
14.40	0.02	47	674.07	0.04	0.00	0.04	0.00
15.60	0.03	45	673.99	0.04	0.00	0.04	0.00
16.80	0.04	46	674.05	0.04	0.00	0.04	0.00
18.00	0.05	49	674.27	0.05	0.00	0.05	0.00
19.20	0.06	53	674.51	0.06	0.00	0.06	0.00
20.40	0.07	56	674.78	0.07	0.00	0.07	0.00
21.60	0.07	60	675.05	0.07	0.00	0.07	0.00
22.80	0.08	64	675.33	0.08	0.00	0.08	0.00
24.00	0.09	68	675.62	0.08	0.00	0.08	0.00
25.20	0.10	79	676.38	0.10	0.00	0.10	0.00
26.40	0.13	98	676.58	0.12	0.02	0.10	0.00
27.60	0.13	100	676.59	0.13	0.02	0.10	0.00
28.80	0.11	94	676.57	0.12	0.01	0.10	0.00
30.00	0.13	99	676.58	0.13	0.02	0.10	0.00
31.20	0.15	114	676.62	0.15	0.05	0.10	0.00
32.40	0.20	144	676.67	0.19	0.09	0.10	0.00
33.60	0.25	182	676.71	0.24	0.13	0.10	0.00
34.80	0.27	208	676.74	0.27	0.17	0.11	0.00
36.00	0.29	217	676.75	0.28	0.18	0.11	0.00
37.20	0.33	246	676.78	0.32	0.21	0.11	0.00
38.40	0.40	303	676.82	0.38	0.28	0.11	0.00
39.60	0.52	407	676.89	0.49	0.38	0.11	0.00
40.80	**0.68**	587	676.99	0.63	0.52	0.11	0.00
42.00	**0.73**	**749**	**677.07**	**0.71**	**0.60**	**0.11**	0.00
43.20	0.72	**764**	**677.07**	**0.72**	**0.61**	**0.11**	0.00
44.40	0.64	678	677.03	0.68	0.57	0.11	0.00
45.60	0.53	491	676.94	0.56	0.46	0.11	0.00
46.80	0.50	420	676.90	0.50	0.39	0.11	0.00
48.00	0.51	425	676.90	0.50	0.40	0.11	0.00
49.20	0.00	40	673.57	0.01	0.00	0.01	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.41 cfs @ 61.79 hrs, Volume= 0.659 af, Depth= 2.26"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=3.97"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.00	0.00	0.00
2.40	0.02	0.00	0.00
3.60	0.04	0.00	0.00
4.80	0.07	0.00	0.00
6.00	0.11	0.00	0.00
7.20	0.14	0.00	0.00
8.40	0.19	0.00	0.00
9.60	0.23	0.00	0.00
10.80	0.27	0.00	0.00
12.00	0.31	0.00	0.00
13.20	0.34	0.00	0.00
14.40	0.37	0.00	0.00
15.60	0.40	0.00	0.00
16.80	0.44	0.00	0.00
18.00	0.48	0.00	0.01
19.20	0.52	0.01	0.01
20.40	0.56	0.01	0.02
21.60	0.60	0.02	0.02
22.80	0.64	0.02	0.02
24.00	0.68	0.03	0.03
25.20	0.72	0.04	0.03
26.40	0.77	0.05	0.03
27.60	0.81	0.06	0.04
28.80	0.85	0.08	0.04
30.00	0.89	0.09	0.04
31.20	0.93	0.11	0.04
32.40	0.97	0.12	0.05
33.60	1.01	0.14	0.05
34.80	1.05	0.15	0.05
36.00	1.10	0.17	0.05
37.20	1.14	0.19	0.06
38.40	1.19	0.21	0.07
39.60	1.24	0.24	0.08
40.80	1.29	0.27	0.08
42.00	1.34	0.29	0.07
43.20	1.39	0.31	0.07
44.40	1.43	0.34	0.07
45.60	1.48	0.37	0.08
46.80	1.53	0.40	0.09
48.00	1.59	0.43	0.11
49.20	1.66	0.47	0.13
50.40	1.74	0.52	0.15
51.60	1.82	0.57	0.16
52.80	1.90	0.63	0.16
54.00	1.99	0.68	0.16
55.20	2.07	0.74	0.18
56.40	2.17	0.81	0.21
57.60	2.27	0.89	0.23
58.80	2.40	0.98	0.28
60.00	2.54	1.09	0.34
61.20	2.71	1.22	**0.40**
62.40	2.89	1.36	**0.41**
63.60	3.06	1.49	0.41
64.80	3.23	1.63	0.40
66.00	3.38	1.76	0.37
67.20	3.52	1.88	0.33
68.40	3.64	1.98	0.28
69.60	3.75	2.07	0.28
70.80	3.86	2.16	0.28
72.00	**3.97**	**2.26**	0.28
73.20	3.97	2.26	0.00
74.40	3.97	2.26	0.00

Summary for Subcatchment 7S: South Property


Runoff = 0.88 cfs @ 62.06 hrs, Volume= 1.413 af, Depth= 2.26"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=3.97"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.00	0.00	0.00
2.40	0.02	0.00	0.00
3.60	0.04	0.00	0.00
4.80	0.07	0.00	0.00
6.00	0.11	0.00	0.00
7.20	0.14	0.00	0.00
8.40	0.19	0.00	0.00
9.60	0.23	0.00	0.00
10.80	0.27	0.00	0.00
12.00	0.31	0.00	0.00
13.20	0.34	0.00	0.00
14.40	0.37	0.00	0.00
15.60	0.40	0.00	0.00
16.80	0.44	0.00	0.00
18.00	0.48	0.00	0.01
19.20	0.52	0.01	0.02
20.40	0.56	0.01	0.03
21.60	0.60	0.02	0.04
22.80	0.64	0.02	0.05
24.00	0.68	0.03	0.06
25.20	0.72	0.04	0.06
26.40	0.77	0.05	0.07
27.60	0.81	0.06	0.08
28.80	0.85	0.08	0.08
30.00	0.89	0.09	0.09
31.20	0.93	0.11	0.09
32.40	0.97	0.12	0.10
33.60	1.01	0.14	0.10
34.80	1.05	0.15	0.11
36.00	1.10	0.17	0.11
37.20	1.14	0.19	0.13
38.40	1.19	0.21	0.15
39.60	1.24	0.24	0.17
40.80	1.29	0.27	0.17
42.00	1.34	0.29	0.16
43.20	1.39	0.31	0.14
44.40	1.43	0.34	0.15
45.60	1.48	0.37	0.17
46.80	1.53	0.40	0.20
48.00	1.59	0.43	0.23
49.20	1.66	0.47	0.27
50.40	1.74	0.52	0.32
51.60	1.82	0.57	0.34
52.80	1.90	0.63	0.34
54.00	1.99	0.68	0.35
55.20	2.07	0.74	0.39
56.40	2.17	0.81	0.44
57.60	2.27	0.89	0.49
58.80	2.40	0.98	0.59
60.00	2.54	1.09	0.71
61.20	2.71	1.22	**0.84**
62.40	2.89	1.36	**0.88**
63.60	3.06	1.49	0.87
64.80	3.23	1.63	0.86
66.00	3.38	1.76	0.80
67.20	3.52	1.88	0.71
68.40	3.64	1.98	0.62
69.60	3.75	2.07	0.59
70.80	3.86	2.16	0.60
72.00	**3.97**	**2.26**	0.60
73.20	3.97	2.26	0.00
74.40	3.97	2.26	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.13 cfs @ 62.44 hrs, Volume= 0.210 af, Depth= 2.10"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=3.97"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.00	0.00	0.00
2.40	0.02	0.00	0.00
3.60	0.04	0.00	0.00
4.80	0.07	0.00	0.00
6.00	0.11	0.00	0.00
7.20	0.14	0.00	0.00
8.40	0.19	0.00	0.00
9.60	0.23	0.00	0.00
10.80	0.27	0.00	0.00
12.00	0.31	0.00	0.00
13.20	0.34	0.00	0.00
14.40	0.37	0.00	0.00
15.60	0.40	0.00	0.00
16.80	0.44	0.00	0.00
18.00	0.48	0.00	0.00
19.20	0.52	0.00	0.00
20.40	0.56	0.00	0.00
21.60	0.60	0.01	0.00
22.80	0.64	0.01	0.00
24.00	0.68	0.02	0.01
25.20	0.72	0.02	0.01
26.40	0.77	0.03	0.01
27.60	0.81	0.04	0.01
28.80	0.85	0.05	0.01
30.00	0.89	0.06	0.01
31.20	0.93	0.08	0.01
32.40	0.97	0.09	0.01
33.60	1.01	0.10	0.01
34.80	1.05	0.12	0.01
36.00	1.10	0.13	0.02
37.20	1.14	0.15	0.02
38.40	1.19	0.17	0.02
39.60	1.24	0.19	0.02
40.80	1.29	0.21	0.02
42.00	1.34	0.24	0.02
43.20	1.39	0.26	0.02
44.40	1.43	0.28	0.02
45.60	1.48	0.30	0.02
46.80	1.53	0.33	0.03
48.00	1.59	0.36	0.03
49.20	1.66	0.40	0.04
50.40	1.74	0.44	0.05
51.60	1.82	0.49	0.05
52.80	1.90	0.54	0.05
54.00	1.99	0.60	0.05
55.20	2.07	0.65	0.06
56.40	2.17	0.71	0.06
57.60	2.27	0.79	0.07
58.80	2.40	0.87	0.09
60.00	2.54	0.97	0.10
61.20	2.71	1.09	0.12
62.40	2.89	1.23	**0.13**
63.60	3.06	1.36	0.13
64.80	3.23	1.49	0.13
66.00	3.38	1.61	0.12
67.20	3.52	1.72	0.11
68.40	3.64	1.82	0.10
69.60	3.75	1.91	0.09
70.80	3.86	2.00	0.09
72.00	**3.97**	**2.10**	0.09
73.20	3.97	2.10	0.00
74.40	3.97	2.10	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass

[49] Hint: Tc<2dt may require smaller dt


Runoff = 0.06 cfs @ 61.80 hrs, Volume= 0.096 af, Depth= 2.10"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=3.97"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.00	0.00	0.00
2.40	0.02	0.00	0.00
3.60	0.04	0.00	0.00
4.80	0.07	0.00	0.00
6.00	0.11	0.00	0.00
7.20	0.14	0.00	0.00
8.40	0.19	0.00	0.00
9.60	0.23	0.00	0.00
10.80	0.27	0.00	0.00
12.00	0.31	0.00	0.00
13.20	0.34	0.00	0.00
14.40	0.37	0.00	0.00
15.60	0.40	0.00	0.00
16.80	0.44	0.00	0.00
18.00	0.48	0.00	0.00
19.20	0.52	0.00	0.00
20.40	0.56	0.00	0.00
21.60	0.60	0.01	0.00
22.80	0.64	0.01	0.00
24.00	0.68	0.02	0.00
25.20	0.72	0.02	0.00
26.40	0.77	0.03	0.00
27.60	0.81	0.04	0.00
28.80	0.85	0.05	0.00
30.00	0.89	0.06	0.01
31.20	0.93	0.08	0.01
32.40	0.97	0.09	0.01
33.60	1.01	0.10	0.01
34.80	1.05	0.12	0.01
36.00	1.10	0.13	0.01
37.20	1.14	0.15	0.01
38.40	1.19	0.17	0.01
39.60	1.24	0.19	0.01
40.80	1.29	0.21	0.01
42.00	1.34	0.24	0.01
43.20	1.39	0.26	0.01
44.40	1.43	0.28	0.01
45.60	1.48	0.30	0.01
46.80	1.53	0.33	0.01
48.00	1.59	0.36	0.02
49.20	1.66	0.40	0.02
50.40	1.74	0.44	0.02
51.60	1.82	0.49	0.02
52.80	1.90	0.54	0.02
54.00	1.99	0.60	0.02
55.20	2.07	0.65	0.03
56.40	2.17	0.71	0.03
57.60	2.27	0.79	0.03
58.80	2.40	0.87	0.04
60.00	2.54	0.97	0.05
61.20	2.71	1.09	**0.06**
62.40	2.89	1.23	**0.06**
63.60	3.06	1.36	0.06
64.80	3.23	1.49	0.06
66.00	3.38	1.61	0.06
67.20	3.52	1.72	0.05
68.40	3.64	1.82	0.04
69.60	3.75	1.91	0.04
70.80	3.86	2.00	0.04
72.00	**3.97**	**2.10**	0.04
73.20	3.97	2.10	0.00
74.40	3.97	2.10	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.05 cfs @	62.06 hrs, Volume=	1.878 af
Outflow	=	0.63 cfs @	72.25 hrs, Volume=	1.424 af, Atten= 40%, Lag= 611.1 min
Primary	=	0.63 cfs @	72.25 hrs, Volume=	1.424 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Peak Elev= 671.59' @ 72.25 hrs Surf.Area= 30,713 sf Storage= 25,438 cf

Plug-Flow detention time= 325.6 min calculated for 1.424 af (76% of inflow)
Center-of-Mass det. time= 82.5 min (3,449.7 - 3,367.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.63 cfs @ 72.25 hrs HW=671.59' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.63 cfs @ 5.71 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
2.40	0.00	0	670.00	0.00	0.00	0.00	0.00
4.80	0.00	0	670.00	0.00	0.00	0.00	0.00
7.20	0.00	0	670.00	0.00	0.00	0.00	0.00
9.60	0.00	0	670.00	0.00	0.00	0.00	0.00
12.00	0.00	0	670.00	0.00	0.00	0.00	0.00
14.40	0.00	0	670.00	0.00	0.00	0.00	0.00
16.80	0.00	3	670.00	0.00	0.00	0.00	0.00
19.20	0.05	125	670.01	0.00	0.00	0.00	0.00
21.60	0.09	516	670.06	0.01	0.01	0.00	0.00
24.00	0.09	1,021	670.11	0.03	0.03	0.00	0.00
26.40	0.11	1,486	670.17	0.07	0.07	0.00	0.00
28.80	0.14	1,859	670.21	0.10	0.10	0.00	0.00
31.20	0.15	2,149	670.24	0.12	0.12	0.00	0.00
33.60	0.17	2,383	670.27	0.15	0.15	0.00	0.00
36.00	0.19	2,580	670.29	0.17	0.17	0.00	0.00
38.40	0.24	2,861	670.32	0.19	0.19	0.00	0.00
40.80	0.28	3,350	670.37	0.23	0.23	0.00	0.00
43.20	0.24	3,567	670.39	0.24	0.24	0.00	0.00
45.60	0.29	3,694	670.41	0.25	0.25	0.00	0.00
48.00	0.35	4,146	670.45	0.27	0.27	0.00	0.00
50.40	0.44	5,008	670.54	0.31	0.31	0.00	0.00
52.80	0.47	6,079	670.64	0.36	0.36	0.00	0.00
55.20	0.52	7,024	670.74	0.39	0.39	0.00	0.00
57.60	0.63	8,441	670.81	0.42	0.42	0.00	0.00
60.00	**0.87**	10,989	670.93	0.46	0.46	0.00	0.00
62.40	**1.05**	15,279	671.14	0.52	0.52	0.00	0.00
64.80	1.03	19,561	671.33	0.57	0.57	0.00	0.00
67.20	0.87	22,807	671.48	0.60	0.60	0.00	0.00
69.60	0.74	24,298	671.54	0.62	0.62	0.00	0.00
72.00	0.75	**25,351**	**671.59**	**0.63**	**0.63**	0.00	0.00
74.40	0.00	**21,306**	**671.41**	**0.59**	**0.59**	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

[86] Warning: Oscillations may require smaller dt (severity=20)

Inflow	=	0.54 cfs @	62.07 hrs, Volume=	0.869 af
Outflow	=	0.54 cfs @	62.59 hrs, Volume=	0.868 af, Atten= 0%, Lag= 30.8 min
Primary	=	0.43 cfs @	62.59 hrs, Volume=	0.498 af
Secondary	=	0.11 cfs @	62.59 hrs, Volume=	0.370 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Peak Elev= 676.93' @ 62.59 hrs Surf.Area= 1,782 sf Storage= 464 cf

Plug-Flow detention time= 13.8 min calculated for 0.867 af (100% of inflow)
Center-of-Mass det. time= 13.0 min (3,462.4 - 3,449.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.43 cfs @ 62.59 hrs HW=676.93' (Free Discharge)
└─**1=Orifice/Grate** (Orifice Controls 0.43 cfs @ 2.22 fps)
└─**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 62.59 hrs HW=676.93' TW=671.15' (Dynamic Tailwater)
└─**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.83 fps)
└─**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└─**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
2.40	0.00	0	670.75	0.00	0.00	0.00	0.00
4.80	0.00	0	670.75	0.00	0.00	0.00	0.00
7.20	0.00	0	670.75	0.00	0.00	0.00	0.00
9.60	0.00	0	670.75	0.00	0.00	0.00	0.00
12.00	0.00	0	670.75	0.00	0.00	0.00	0.00
14.40	0.00	0	670.75	0.00	0.00	0.00	0.00
16.80	0.00	2	670.89	0.00	0.00	0.00	0.00
19.20	0.01	42	673.77	0.03	0.00	0.03	0.00
21.60	0.02	47	674.13	0.04	0.00	0.04	0.00
24.00	0.03	44	673.89	0.03	0.00	0.03	0.00
26.40	0.04	46	674.04	0.04	0.00	0.04	0.00
28.80	0.05	49	674.24	0.05	0.00	0.05	0.00
31.20	0.06	52	674.45	0.06	0.00	0.06	0.00
33.60	0.06	55	674.67	0.06	0.00	0.06	0.00
36.00	0.07	58	674.89	0.07	0.00	0.07	0.00
38.40	0.09	70	675.72	0.09	0.00	0.09	0.00
40.80	0.10	81	676.51	0.10	0.00	0.10	0.00
43.20	0.09	71	675.83	0.09	0.00	0.09	0.00
45.60	0.11	83	676.53	0.10	0.00	0.10	0.00
48.00	0.14	106	676.61	0.14	0.04	0.10	0.00
50.40	0.19	145	676.67	0.19	0.09	0.10	0.00
52.80	0.21	158	676.69	0.21	0.11	0.10	0.00
55.20	0.24	178	676.71	0.23	0.13	0.10	0.00
57.60	0.30	227	676.76	0.30	0.19	0.11	0.00
60.00	**0.44**	341	676.85	0.43	0.32	0.11	0.00
62.40	**0.54**	**465**	**676.93**	**0.54**	**0.43**	**0.11**	0.00
64.80	0.53	**458**	**676.92**	**0.53**	**0.43**	**0.11**	0.00
67.20	0.44	369	676.87	0.45	0.34	0.11	0.00
69.60	0.37	290	676.81	0.37	0.26	0.11	0.00
72.00	0.37	295	676.82	0.37	0.27	0.11	0.00
74.40	0.00	36	673.29	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.28 cfs @ 102.54 hrs, Volume= 0.774 af, Depth= 2.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=4.42"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.12	0.00	0.00
12.50	0.17	0.00	0.00
15.00	0.23	0.00	0.00
17.50	0.29	0.00	0.00
20.00	0.34	0.00	0.00
22.50	0.39	0.00	0.00
25.00	0.43	0.00	0.00
27.50	0.48	0.00	0.00
30.00	0.53	0.01	0.01
32.50	0.59	0.01	0.01
35.00	0.64	0.02	0.02
37.50	0.70	0.04	0.02
40.00	0.76	0.05	0.02
42.50	0.82	0.07	0.02
45.00	0.87	0.09	0.03
47.50	0.93	0.11	0.03
50.00	0.99	0.13	0.03
52.50	1.05	0.15	0.03
55.00	1.11	0.18	0.04
57.50	1.16	0.20	0.04
60.00	1.22	0.23	0.04
62.50	1.28	0.26	0.05
65.00	1.35	0.30	0.05
67.50	1.43	0.34	0.06
70.00	1.49	0.38	0.05
72.50	1.55	0.41	0.05
75.00	1.62	0.45	0.06
77.50	1.69	0.49	0.06
80.00	1.77	0.54	0.08
82.50	1.87	0.61	0.10
85.00	1.98	0.68	0.11
87.50	2.09	0.76	0.11
90.00	2.21	0.84	0.12
92.50	2.33	0.93	0.13
95.00	2.47	1.03	0.15
97.50	2.63	1.16	0.19
100.00	2.83	1.31	0.24
102.50	3.07	1.50	**0.28**
105.00	3.31	1.70	**0.28**
107.50	3.55	1.90	0.28
110.00	3.77	2.08	0.25
112.50	3.95	2.25	0.21
115.00	4.11	2.38	0.19
117.50	4.27	2.52	0.19
120.00	**4.42**	**2.65**	0.19
122.50	4.42	2.65	0.00
125.00	4.42	2.65	0.00
127.50	4.42	2.65	0.00
130.00	4.42	2.65	0.00

Summary for Subcatchment 7S: South Property


Runoff = 0.61 cfs @ 102.77 hrs, Volume= 1.659 af, Depth= 2.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=4.42"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.12	0.00	0.00
12.50	0.17	0.00	0.00
15.00	0.23	0.00	0.00
17.50	0.29	0.00	0.00
20.00	0.34	0.00	0.00
22.50	0.39	0.00	0.00
25.00	0.43	0.00	0.00
27.50	0.48	0.00	0.01
30.00	0.53	0.01	0.02
32.50	0.59	0.01	0.03
35.00	0.64	0.02	0.03
37.50	0.70	0.04	0.04
40.00	0.76	0.05	0.05
42.50	0.82	0.07	0.05
45.00	0.87	0.09	0.06
47.50	0.93	0.11	0.06
50.00	0.99	0.13	0.07
52.50	1.05	0.15	0.07
55.00	1.11	0.18	0.08
57.50	1.16	0.20	0.08
60.00	1.22	0.23	0.08
62.50	1.28	0.26	0.10
65.00	1.35	0.30	0.12
67.50	1.43	0.34	0.12
70.00	1.49	0.38	0.11
72.50	1.55	0.41	0.10
75.00	1.62	0.45	0.12
77.50	1.69	0.49	0.14
80.00	1.77	0.54	0.17
82.50	1.87	0.61	0.20
85.00	1.98	0.68	0.24
87.50	2.09	0.76	0.24
90.00	2.21	0.84	0.25
92.50	2.33	0.93	0.28
95.00	2.47	1.03	0.33
97.50	2.63	1.16	0.40
100.00	2.83	1.31	0.50
102.50	3.07	1.50	**0.61**
105.00	3.31	1.70	**0.60**
107.50	3.55	1.90	0.59
110.00	3.77	2.08	0.54
112.50	3.95	2.25	0.46
115.00	4.11	2.38	0.40
117.50	4.27	2.52	0.41
120.00	**4.42**	**2.65**	0.41
122.50	4.42	2.65	0.00
125.00	4.42	2.65	0.00
127.50	4.42	2.65	0.00
130.00	4.42	2.65	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.09 cfs @ 103.11 hrs, Volume= 0.248 af, Depth= 2.48"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=4.42"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.12	0.00	0.00
12.50	0.17	0.00	0.00
15.00	0.23	0.00	0.00
17.50	0.29	0.00	0.00
20.00	0.34	0.00	0.00
22.50	0.39	0.00	0.00
25.00	0.43	0.00	0.00
27.50	0.48	0.00	0.00
30.00	0.53	0.00	0.00
32.50	0.59	0.01	0.00
35.00	0.64	0.01	0.00
37.50	0.70	0.02	0.00
40.00	0.76	0.03	0.01
42.50	0.82	0.04	0.01
45.00	0.87	0.06	0.01
47.50	0.93	0.08	0.01
50.00	0.99	0.09	0.01
52.50	1.05	0.11	0.01
55.00	1.11	0.14	0.01
57.50	1.16	0.16	0.01
60.00	1.22	0.18	0.01
62.50	1.28	0.21	0.01
65.00	1.35	0.24	0.02
67.50	1.43	0.28	0.02
70.00	1.49	0.31	0.02
72.50	1.55	0.34	0.01
75.00	1.62	0.38	0.02
77.50	1.69	0.42	0.02
80.00	1.77	0.46	0.02
82.50	1.87	0.52	0.03
85.00	1.98	0.59	0.03
87.50	2.09	0.67	0.04
90.00	2.21	0.74	0.04
92.50	2.33	0.83	0.04
95.00	2.47	0.92	0.05
97.50	2.63	1.04	0.06
100.00	2.83	1.18	0.08
102.50	3.07	1.36	**0.09**
105.00	3.31	1.56	**0.09**
107.50	3.55	1.75	0.09
110.00	3.77	1.93	0.08
112.50	3.95	2.08	0.07
115.00	4.11	2.22	0.06
117.50	4.27	2.35	0.06
120.00	**4.42**	**2.48**	0.06
122.50	4.42	2.48	0.00
125.00	4.42	2.48	0.00
127.50	4.42	2.48	0.00
130.00	4.42	2.48	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.04 cfs @ 102.38 hrs, Volume= 0.114 af, Depth= 2.48"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=4.42"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.12	0.00	0.00
12.50	0.17	0.00	0.00
15.00	0.23	0.00	0.00
17.50	0.29	0.00	0.00
20.00	0.34	0.00	0.00
22.50	0.39	0.00	0.00
25.00	0.43	0.00	0.00
27.50	0.48	0.00	0.00
30.00	0.53	0.00	0.00
32.50	0.59	0.01	0.00
35.00	0.64	0.01	0.00
37.50	0.70	0.02	0.00
40.00	0.76	0.03	0.00
42.50	0.82	0.04	0.00
45.00	0.87	0.06	0.00
47.50	0.93	0.08	0.00
50.00	0.99	0.09	0.00
52.50	1.05	0.11	0.00
55.00	1.11	0.14	0.00
57.50	1.16	0.16	0.01
60.00	1.22	0.18	0.01
62.50	1.28	0.21	0.01
65.00	1.35	0.24	0.01
67.50	1.43	0.28	0.01
70.00	1.49	0.31	0.01
72.50	1.55	0.34	0.01
75.00	1.62	0.38	0.01
77.50	1.69	0.42	0.01
80.00	1.77	0.46	0.01
82.50	1.87	0.52	0.01
85.00	1.98	0.59	0.02
87.50	2.09	0.67	0.02
90.00	2.21	0.74	0.02
92.50	2.33	0.83	0.02
95.00	2.47	0.92	0.02
97.50	2.63	1.04	0.03
100.00	2.83	1.18	**0.04**
102.50	3.07	1.36	**0.04**
105.00	3.31	1.56	0.04
107.50	3.55	1.75	0.04
110.00	3.77	1.93	0.04
112.50	3.95	2.08	0.03
115.00	4.11	2.22	0.03
117.50	4.27	2.35	0.03
120.00	**4.42**	**2.48**	0.03
122.50	4.42	2.48	0.00
125.00	4.42	2.48	0.00
127.50	4.42	2.48	0.00
130.00	4.42	2.48	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	0.76 cfs @ 102.77 hrs, Volume=	2.325 af
Outflow	=	0.56 cfs @ 113.85 hrs, Volume=	2.246 af, Atten= 26%, Lag= 664.9 min
Primary	=	0.56 cfs @ 113.85 hrs, Volume=	2.246 af
Secondary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.05 hrs
Peak Elev= 671.28' @ 113.85 hrs Surf.Area= 28,283 sf Storage= 18,433 cf

Plug-Flow detention time= 364.4 min calculated for 2.245 af (97% of inflow)
Center-of-Mass det. time= 307.3 min (5,864.6 - 5,557.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.56 cfs @ 113.85 hrs HW=671.28' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.56 cfs @ 5.04 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
12.50	0.00	0	670.00	0.00	0.00	0.00	0.00
15.00	0.00	0	670.00	0.00	0.00	0.00	0.00
17.50	0.00	0	670.00	0.00	0.00	0.00	0.00
20.00	0.00	0	670.00	0.00	0.00	0.00	0.00
22.50	0.00	0	670.00	0.00	0.00	0.00	0.00
25.00	0.00	3	670.00	0.00	0.00	0.00	0.00
27.50	0.01	44	670.00	0.00	0.00	0.00	0.00
30.00	0.03	194	670.02	0.00	0.00	0.00	0.00
32.50	0.04	468	670.05	0.01	0.01	0.00	0.00
35.00	0.05	778	670.09	0.02	0.02	0.00	0.00
37.50	0.07	1,067	670.12	0.04	0.04	0.00	0.00
40.00	0.08	1,309	670.15	0.05	0.05	0.00	0.00
42.50	0.09	1,502	670.17	0.07	0.07	0.00	0.00
45.00	0.10	1,658	670.19	0.08	0.08	0.00	0.00
47.50	0.10	1,787	670.20	0.09	0.09	0.00	0.00
50.00	0.11	1,897	670.21	0.10	0.10	0.00	0.00
52.50	0.12	1,993	670.22	0.11	0.11	0.00	0.00
55.00	0.13	2,080	670.23	0.12	0.12	0.00	0.00
57.50	0.13	2,159	670.24	0.13	0.13	0.00	0.00
60.00	0.14	2,231	670.25	0.13	0.13	0.00	0.00
62.50	0.16	2,350	670.26	0.14	0.14	0.00	0.00
65.00	0.19	2,565	670.29	0.17	0.17	0.00	0.00
67.50	0.20	2,801	670.31	0.19	0.19	0.00	0.00
70.00	0.19	2,848	670.32	0.19	0.19	0.00	0.00
72.50	0.17	2,764	670.31	0.18	0.18	0.00	0.00
75.00	0.20	2,788	670.31	0.19	0.19	0.00	0.00
77.50	0.23	2,983	670.33	0.20	0.20	0.00	0.00
80.00	0.28	3,320	670.37	0.23	0.23	0.00	0.00
82.50	0.32	3,846	670.42	0.26	0.26	0.00	0.00
85.00	0.35	4,454	670.48	0.29	0.29	0.00	0.00
87.50	0.36	4,968	670.53	0.31	0.31	0.00	0.00
90.00	0.37	5,364	670.57	0.33	0.33	0.00	0.00
92.50	0.41	5,796	670.62	0.35	0.35	0.00	0.00
95.00	0.46	6,441	670.68	0.37	0.37	0.00	0.00
97.50	0.53	7,321	670.76	0.40	0.40	0.00	0.00
100.00	0.65	8,882	670.83	0.43	0.43	0.00	0.00
102.50	**0.76**	11,212	670.94	0.46	0.46	0.00	0.00
105.00	**0.75**	13,680	671.06	0.50	0.50	0.00	0.00
107.50	0.74	15,797	671.16	0.52	0.52	0.00	0.00
110.00	0.69	17,472	671.24	0.55	0.55	0.00	0.00
112.50	0.60	**18,318**	**671.28**	**0.55**	**0.55**	0.00	0.00
115.00	0.54	**18,379**	**671.28**	**0.56**	**0.56**	0.00	0.00
117.50	0.54	18,249	671.27	0.55	0.55	0.00	0.00
120.00	0.55	18,159	671.27	0.55	0.55	0.00	0.00
122.50	0.00	14,222	671.09	0.50	0.50	0.00	0.00
125.00	0.00	9,948	670.88	0.44	0.44	0.00	0.00
127.50	0.00	6,243	670.66	0.37	0.37	0.00	0.00
130.00	0.00	3,511	670.39	0.24	0.24	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.38 cfs @ 102.79 hrs,	Volume=	1.022 af
Outflow	=	0.38 cfs @ 103.23 hrs,	Volume=	1.021 af, Atten= 0%, Lag= 26.3 min
Primary	=	0.27 cfs @ 103.23 hrs,	Volume=	0.469 af
Secondary	=	0.11 cfs @ 103.23 hrs,	Volume=	0.553 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.05 hrs
Peak Elev= 676.82' @ 103.23 hrs Surf.Area= 1,329 sf Storage= 294 cf

Plug-Flow detention time= 13.9 min calculated for 1.021 af (100% of inflow)
Center-of-Mass det. time= 12.6 min (5,698.0 - 5,685.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.27 cfs @ 103.23 hrs HW=676.82' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 0.27 cfs @ 1.92 fps)
└2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 103.23 hrs HW=676.82' TW=670.98' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.69 fps)
└5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
12.50	0.00	0	670.75	0.00	0.00	0.00	0.00
15.00	0.00	0	670.75	0.00	0.00	0.00	0.00
17.50	0.00	0	670.75	0.00	0.00	0.00	0.00
20.00	0.00	0	670.75	0.00	0.00	0.00	0.00
22.50	0.00	0	670.75	0.00	0.00	0.00	0.00
25.00	0.00	2	670.87	0.00	0.00	0.00	0.00
27.50	0.00	22	672.35	0.00	0.00	0.00	0.00
30.00	0.01	40	673.62	0.01	0.00	0.01	0.00
32.50	0.01	40	673.62	0.01	0.00	0.01	0.00
35.00	0.02	41	673.67	0.02	0.00	0.02	0.00
37.50	0.02	42	673.72	0.02	0.00	0.02	0.00
40.00	0.03	42	673.77	0.03	0.00	0.03	0.00
42.50	0.03	43	673.84	0.03	0.00	0.03	0.00
45.00	0.03	44	673.90	0.03	0.00	0.03	0.00
47.50	0.04	45	673.97	0.04	0.00	0.04	0.00
50.00	0.04	46	674.04	0.04	0.00	0.04	0.00
52.50	0.04	47	674.10	0.04	0.00	0.04	0.00
55.00	0.05	48	674.17	0.05	0.00	0.05	0.00
57.50	0.05	49	674.24	0.05	0.00	0.05	0.00
60.00	0.05	50	674.31	0.05	0.00	0.05	0.00
62.50	0.06	54	674.57	0.06	0.00	0.06	0.00
65.00	0.07	59	674.96	0.07	0.00	0.07	0.00
67.50	0.07	62	675.15	0.07	0.00	0.07	0.00
70.00	0.07	58	674.92	0.07	0.00	0.07	0.00
72.50	0.06	55	674.70	0.06	0.00	0.06	0.00
75.00	0.07	61	675.09	0.07	0.00	0.07	0.00
77.50	0.09	68	675.59	0.08	0.00	0.08	0.00
80.00	0.10	81	676.50	0.10	0.00	0.10	0.00
82.50	0.13	99	676.58	0.12	0.02	0.10	0.00
85.00	0.14	110	676.61	0.14	0.04	0.10	0.00
87.50	0.15	115	676.62	0.15	0.05	0.10	0.00
90.00	0.15	118	676.63	0.15	0.05	0.10	0.00
92.50	0.18	134	676.65	0.17	0.07	0.10	0.00
95.00	0.20	152	676.68	0.20	0.10	0.10	0.00
97.50	0.25	184	676.72	0.24	0.14	0.10	0.00
100.00	0.31	235	676.77	0.31	0.20	0.11	0.00
102.50	**0.38**	**294**	**676.82**	**0.37**	**0.27**	**0.11**	0.00
105.00	**0.37**	**295**	**676.82**	**0.37**	**0.27**	**0.11**	0.00
107.50	0.37	291	676.81	0.37	0.26	0.11	0.00
110.00	0.34	264	676.79	0.34	0.23	0.11	0.00
112.50	0.29	223	676.76	0.29	0.19	0.11	0.00
115.00	0.25	192	676.73	0.25	0.15	0.11	0.00
117.50	0.25	194	676.73	0.25	0.15	0.11	0.00
120.00	0.26	195	676.73	0.26	0.15	0.11	0.00
122.50	0.00	39	673.50	0.00	0.00	0.00	0.00
125.00	0.00	39	673.50	0.00	0.00	0.00	0.00
127.50	0.00	39	673.50	0.00	0.00	0.00	0.00
130.00	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.19 cfs @ 204.41 hrs, Volume= 1.086 af, Depth= 3.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=5.60"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.04	0.00	0.00	140.00	1.89	0.62	0.04
12.50	0.06	0.00	0.00	142.50	1.93	0.65	0.04
15.00	0.09	0.00	0.00	145.00	1.97	0.67	0.04
17.50	0.12	0.00	0.00	147.50	2.01	0.70	0.04
20.00	0.15	0.00	0.00	150.00	2.05	0.73	0.04
22.50	0.18	0.00	0.00	152.50	2.09	0.76	0.04
25.00	0.22	0.00	0.00	155.00	2.14	0.79	0.05
27.50	0.26	0.00	0.00	157.50	2.19	0.83	0.05
30.00	0.29	0.00	0.00	160.00	2.24	0.87	0.06
32.50	0.33	0.00	0.00	162.50	2.30	0.91	0.06
35.00	0.36	0.00	0.00	165.00	2.37	0.96	0.07
37.50	0.40	0.00	0.00	167.50	2.44	1.01	0.08
40.00	0.43	0.00	0.00	170.00	2.51	1.06	0.08
42.50	0.47	0.00	0.00	172.50	2.58	1.12	0.08
45.00	0.49	0.00	0.00	175.00	2.65	1.17	0.08
47.50	0.52	0.01	0.00	177.50	2.73	1.23	0.08
50.00	0.55	0.01	0.00	180.00	2.80	1.29	0.08
52.50	0.57	0.01	0.01	182.50	2.88	1.35	0.09
55.00	0.60	0.02	0.01	185.00	2.96	1.41	0.09
57.50	0.64	0.02	0.01	187.50	3.04	1.48	0.10
60.00	0.67	0.03	0.01	190.00	3.13	1.55	0.11
62.50	0.71	0.04	0.01	192.50	3.23	1.63	0.11
65.00	0.74	0.05	0.01	195.00	3.33	1.72	0.13
67.50	0.78	0.06	0.01	197.50	3.45	1.82	0.15
70.00	0.82	0.07	0.02	200.00	3.58	1.93	0.16
72.50	0.85	0.08	0.02	202.50	3.73	2.05	**0.18**
75.00	0.89	0.09	0.02	205.00	3.88	2.19	**0.19**
77.50	0.93	0.10	0.02	207.50	4.04	2.32	0.19
80.00	0.96	0.12	0.02	210.00	4.19	2.45	0.19
82.50	1.00	0.13	0.02	212.50	4.34	2.59	0.19
85.00	1.04	0.15	0.02	215.00	4.49	2.72	0.18
87.50	1.07	0.16	0.02	217.50	4.64	2.85	0.18
90.00	1.11	0.18	0.02	220.00	4.77	2.97	0.17
92.50	1.14	0.19	0.02	222.50	4.89	3.08	0.15
95.00	1.18	0.21	0.02	225.00	5.01	3.18	0.14
97.50	1.22	0.23	0.02	227.50	5.11	3.28	0.13
100.00	1.25	0.25	0.03	230.00	5.21	3.37	0.12
102.50	1.29	0.26	0.03	232.50	5.31	3.45	0.13
105.00	1.33	0.28	0.03	235.00	5.41	3.54	0.13
107.50	1.36	0.30	0.03	237.50	5.50	3.63	0.13
110.00	1.40	0.32	0.03	240.00	**5.60**	**3.72**	0.13
112.50	1.44	0.34	0.03	242.50	5.60	3.72	0.00
115.00	1.47	0.36	0.03	245.00	5.60	3.72	0.00
117.50	1.51	0.38	0.03	247.50	5.60	3.72	0.00
120.00	1.55	0.41	0.03	250.00	5.60	3.72	0.00
122.50	1.58	0.43	0.03				
125.00	1.62	0.45	0.04				
127.50	1.67	0.48	0.04				
130.00	1.71	0.51	0.04				
132.50	1.76	0.54	0.04				
135.00	1.81	0.57	0.04				
137.50	1.85	0.60	0.04				

Summary for Subcatchment 7S: South Property


Runoff = 0.41 cfs @ 204.65 hrs, Volume= 2.326 af, Depth= 3.72"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=5.60"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.04	0.00	0.00
12.50	0.06	0.00	0.00
15.00	0.09	0.00	0.00
17.50	0.12	0.00	0.00
20.00	0.15	0.00	0.00
22.50	0.18	0.00	0.00
25.00	0.22	0.00	0.00
27.50	0.26	0.00	0.00
30.00	0.29	0.00	0.00
32.50	0.33	0.00	0.00
35.00	0.36	0.00	0.00
37.50	0.40	0.00	0.00
40.00	0.43	0.00	0.00
42.50	0.47	0.00	0.00
45.00	0.49	0.00	0.01
47.50	0.52	0.01	0.01
50.00	0.55	0.01	0.01
52.50	0.57	0.01	0.01
55.00	0.60	0.02	0.02
57.50	0.64	0.02	0.02
60.00	0.67	0.03	0.02
62.50	0.71	0.04	0.03
65.00	0.74	0.05	0.03
67.50	0.78	0.06	0.03
70.00	0.82	0.07	0.03
72.50	0.85	0.08	0.04
75.00	0.89	0.09	0.04
77.50	0.93	0.10	0.04
80.00	0.96	0.12	0.04
82.50	1.00	0.13	0.04
85.00	1.04	0.15	0.05
87.50	1.07	0.16	0.05
90.00	1.11	0.18	0.05
92.50	1.14	0.19	0.05
95.00	1.18	0.21	0.05
97.50	1.22	0.23	0.05
100.00	1.25	0.25	0.05
102.50	1.29	0.26	0.06
105.00	1.33	0.28	0.06
107.50	1.36	0.30	0.06
110.00	1.40	0.32	0.06
112.50	1.44	0.34	0.06
115.00	1.47	0.36	0.06
117.50	1.51	0.38	0.06
120.00	1.55	0.41	0.06
122.50	1.58	0.43	0.07
125.00	1.62	0.45	0.08
127.50	1.67	0.48	0.08
130.00	1.71	0.51	0.09
132.50	1.76	0.54	0.09
135.00	1.81	0.57	0.09
137.50	1.85	0.60	0.09
140.00	1.89	0.62	0.08
142.50	1.93	0.65	0.08
145.00	1.97	0.67	0.08
147.50	2.01	0.70	0.08
150.00	2.05	0.73	0.09
152.50	2.09	0.76	0.09
155.00	2.14	0.79	0.10
157.50	2.19	0.83	0.11
160.00	2.24	0.87	0.12
162.50	2.30	0.91	0.13
165.00	2.37	0.96	0.15
167.50	2.44	1.01	0.16
170.00	2.51	1.06	0.17
172.50	2.58	1.12	0.17
175.00	2.65	1.17	0.17
177.50	2.73	1.23	0.17
180.00	2.80	1.29	0.17
182.50	2.88	1.35	0.19
185.00	2.96	1.41	0.20
187.50	3.04	1.48	0.21
190.00	3.13	1.55	0.23
192.50	3.23	1.63	0.24
195.00	3.33	1.72	0.28
197.50	3.45	1.82	0.31
200.00	3.58	1.93	0.35
202.50	3.73	2.05	**0.38**
205.00	3.88	2.19	**0.41**
207.50	4.04	2.32	0.41
210.00	4.19	2.45	0.40
212.50	4.34	2.59	0.40
215.00	4.49	2.72	0.40
217.50	4.64	2.85	0.38
220.00	4.77	2.97	0.36
222.50	4.89	3.08	0.33
225.00	5.01	3.18	0.30
227.50	5.11	3.28	0.28
230.00	5.21	3.37	0.27
232.50	5.31	3.45	0.27
235.00	5.41	3.54	0.27
237.50	5.50	3.63	0.27
240.00	**5.60**	**3.72**	0.27
242.50	5.60	3.72	0.00
245.00	5.60	3.72	0.00
247.50	5.60	3.72	0.00
250.00	5.60	3.72	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.06 cfs @ 204.99 hrs, Volume= 0.352 af, Depth= 3.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=5.60"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.04	0.00	0.00	140.00	1.89	0.54	0.01
12.50	0.06	0.00	0.00	142.50	1.93	0.56	0.01
15.00	0.09	0.00	0.00	145.00	1.97	0.58	0.01
17.50	0.12	0.00	0.00	147.50	2.01	0.61	0.01
20.00	0.15	0.00	0.00	150.00	2.05	0.64	0.01
22.50	0.18	0.00	0.00	152.50	2.09	0.66	0.01
25.00	0.22	0.00	0.00	155.00	2.14	0.69	0.01
27.50	0.26	0.00	0.00	157.50	2.19	0.73	0.02
30.00	0.29	0.00	0.00	160.00	2.24	0.76	0.02
32.50	0.33	0.00	0.00	162.50	2.30	0.80	0.02
35.00	0.36	0.00	0.00	165.00	2.37	0.85	0.02
37.50	0.40	0.00	0.00	167.50	2.44	0.90	0.02
40.00	0.43	0.00	0.00	170.00	2.51	0.95	0.03
42.50	0.47	0.00	0.00	172.50	2.58	1.00	0.03
45.00	0.49	0.00	0.00	175.00	2.65	1.05	0.03
47.50	0.52	0.00	0.00	177.50	2.73	1.11	0.03
50.00	0.55	0.00	0.00	180.00	2.80	1.16	0.03
52.50	0.57	0.00	0.00	182.50	2.88	1.22	0.03
55.00	0.60	0.01	0.00	185.00	2.96	1.28	0.03
57.50	0.64	0.01	0.00	187.50	3.04	1.35	0.03
60.00	0.67	0.02	0.00	190.00	3.13	1.42	0.03
62.50	0.71	0.02	0.00	192.50	3.23	1.49	0.04
65.00	0.74	0.03	0.00	195.00	3.33	1.58	0.04
67.50	0.78	0.04	0.00	197.50	3.45	1.67	0.05
70.00	0.82	0.04	0.00	200.00	3.58	1.78	0.05
72.50	0.85	0.05	0.00	202.50	3.73	1.90	0.06
75.00	0.89	0.06	0.00	205.00	3.88	2.02	**0.06**
77.50	0.93	0.07	0.01	207.50	4.04	2.15	0.06
80.00	0.96	0.09	0.01	210.00	4.19	2.28	0.06
82.50	1.00	0.10	0.01	212.50	4.34	2.41	0.06
85.00	1.04	0.11	0.01	215.00	4.49	2.54	0.06
87.50	1.07	0.12	0.01	217.50	4.64	2.67	0.06
90.00	1.11	0.14	0.01	220.00	4.77	2.78	0.06
92.50	1.14	0.15	0.01	222.50	4.89	2.89	0.05
95.00	1.18	0.17	0.01	225.00	5.01	2.99	0.05
97.50	1.22	0.18	0.01	227.50	5.11	3.09	0.04
100.00	1.25	0.20	0.01	230.00	5.21	3.17	0.04
102.50	1.29	0.21	0.01	232.50	5.31	3.26	0.04
105.00	1.33	0.23	0.01	235.00	5.41	3.35	0.04
107.50	1.36	0.25	0.01	237.50	5.50	3.43	0.04
110.00	1.40	0.26	0.01	240.00	**5.60**	**3.52**	0.04
112.50	1.44	0.28	0.01	242.50	5.60	3.52	0.00
115.00	1.47	0.30	0.01	245.00	5.60	3.52	0.00
117.50	1.51	0.32	0.01	247.50	5.60	3.52	0.00
120.00	1.55	0.34	0.01	250.00	5.60	3.52	0.00
122.50	1.58	0.36	0.01				
125.00	1.62	0.38	0.01				
127.50	1.67	0.40	0.01				
130.00	1.71	0.43	0.01				
132.50	1.76	0.46	0.01				
135.00	1.81	0.49	0.01				
137.50	1.85	0.51	0.01				

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.03 cfs @ 204.26 hrs, Volume= 0.161 af, Depth= 3.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=5.60"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.04	0.00	0.00
12.50	0.06	0.00	0.00
15.00	0.09	0.00	0.00
17.50	0.12	0.00	0.00
20.00	0.15	0.00	0.00
22.50	0.18	0.00	0.00
25.00	0.22	0.00	0.00
27.50	0.26	0.00	0.00
30.00	0.29	0.00	0.00
32.50	0.33	0.00	0.00
35.00	0.36	0.00	0.00
37.50	0.40	0.00	0.00
40.00	0.43	0.00	0.00
42.50	0.47	0.00	0.00
45.00	0.49	0.00	0.00
47.50	0.52	0.00	0.00
50.00	0.55	0.00	0.00
52.50	0.57	0.00	0.00
55.00	0.60	0.01	0.00
57.50	0.64	0.01	0.00
60.00	0.67	0.02	0.00
62.50	0.71	0.02	0.00
65.00	0.74	0.03	0.00
67.50	0.78	0.04	0.00
70.00	0.82	0.04	0.00
72.50	0.85	0.05	0.00
75.00	0.89	0.06	0.00
77.50	0.93	0.07	0.00
80.00	0.96	0.09	0.00
82.50	1.00	0.10	0.00
85.00	1.04	0.11	0.00
87.50	1.07	0.12	0.00
90.00	1.11	0.14	0.00
92.50	1.14	0.15	0.00
95.00	1.18	0.17	0.00
97.50	1.22	0.18	0.00
100.00	1.25	0.20	0.00
102.50	1.29	0.21	0.00
105.00	1.33	0.23	0.00
107.50	1.36	0.25	0.00
110.00	1.40	0.26	0.00
112.50	1.44	0.28	0.00
115.00	1.47	0.30	0.00
117.50	1.51	0.32	0.00
120.00	1.55	0.34	0.00
122.50	1.58	0.36	0.00
125.00	1.62	0.38	0.01
127.50	1.67	0.40	0.01
130.00	1.71	0.43	0.01
132.50	1.76	0.46	0.01
135.00	1.81	0.49	0.01
137.50	1.85	0.51	0.01
140.00	1.89	0.54	0.01
142.50	1.93	0.56	0.01
145.00	1.97	0.58	0.01
147.50	2.01	0.61	0.01
150.00	2.05	0.64	0.01
152.50	2.09	0.66	0.01
155.00	2.14	0.69	0.01
157.50	2.19	0.73	0.01
160.00	2.24	0.76	0.01
162.50	2.30	0.80	0.01
165.00	2.37	0.85	0.01
167.50	2.44	0.90	0.01
170.00	2.51	0.95	0.01
172.50	2.58	1.00	0.01
175.00	2.65	1.05	0.01
177.50	2.73	1.11	0.01
180.00	2.80	1.16	0.01
182.50	2.88	1.22	0.01
185.00	2.96	1.28	0.01
187.50	3.04	1.35	0.02
190.00	3.13	1.42	0.02
192.50	3.23	1.49	0.02
195.00	3.33	1.58	0.02
197.50	3.45	1.67	0.02
200.00	3.58	1.78	0.02
202.50	3.73	1.90	**0.03**
205.00	3.88	2.02	**0.03**
207.50	4.04	2.15	0.03
210.00	4.19	2.28	0.03
212.50	4.34	2.41	0.03
215.00	4.49	2.54	0.03
217.50	4.64	2.67	0.03
220.00	4.77	2.78	0.03
222.50	4.89	2.89	0.02
225.00	5.01	2.99	0.02
227.50	5.11	3.09	0.02
230.00	5.21	3.17	0.02
232.50	5.31	3.26	0.02
235.00	5.41	3.35	0.02
237.50	5.50	3.43	0.02
240.00	**5.60**	**3.52**	0.02
242.50	5.60	3.52	0.00
245.00	5.60	3.52	0.00
247.50	5.60	3.52	0.00
250.00	5.60	3.52	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	0.54 cfs @ 204.64 hrs,	Volume=	3.492 af
Outflow	=	0.48 cfs @ 220.43 hrs,	Volume=	3.463 af, Atten= 12%, Lag= 947.7 min
Primary	=	0.48 cfs @ 220.43 hrs,	Volume=	3.463 af
Secondary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Peak Elev= 671.01' @ 220.43 hrs Surf.Area= 28,232 sf Storage= 12,515 cf

Plug-Flow detention time= 327.4 min calculated for 3.463 af (99% of inflow)
Center-of-Mass det. time= 298.5 min (11,225.4 - 10,926.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.48 cfs @ 220.43 hrs HW=671.01' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.48 cfs @ 4.36 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
15.00	0.00	0	670.00	0.00	0.00	0.00	0.00
20.00	0.00	0	670.00	0.00	0.00	0.00	0.00
25.00	0.00	0	670.00	0.00	0.00	0.00	0.00
30.00	0.00	0	670.00	0.00	0.00	0.00	0.00
35.00	0.00	0	670.00	0.00	0.00	0.00	0.00
40.00	0.00	5	670.00	0.00	0.00	0.00	0.00
45.00	0.01	82	670.01	0.00	0.00	0.00	0.00
50.00	0.01	272	670.03	0.00	0.00	0.00	0.00
55.00	0.02	523	670.06	0.01	0.01	0.00	0.00
60.00	0.04	811	670.09	0.02	0.02	0.00	0.00
65.00	0.05	1,062	670.12	0.04	0.04	0.00	0.00
70.00	0.05	1,234	670.14	0.05	0.05	0.00	0.00
75.00	0.06	1,362	670.15	0.06	0.06	0.00	0.00
80.00	0.07	1,464	670.16	0.06	0.06	0.00	0.00
85.00	0.08	1,551	670.17	0.07	0.07	0.00	0.00
90.00	0.08	1,627	670.18	0.08	0.08	0.00	0.00
95.00	0.09	1,694	670.19	0.08	0.08	0.00	0.00
100.00	0.09	1,755	670.20	0.09	0.09	0.00	0.00
105.00	0.10	1,810	670.20	0.09	0.09	0.00	0.00
110.00	0.10	1,860	670.21	0.10	0.10	0.00	0.00
115.00	0.10	1,906	670.21	0.10	0.10	0.00	0.00
120.00	0.11	1,949	670.22	0.11	0.11	0.00	0.00
125.00	0.13	2,063	670.23	0.12	0.12	0.00	0.00
130.00	0.15	2,255	670.25	0.14	0.14	0.00	0.00
135.00	0.15	2,407	670.27	0.15	0.15	0.00	0.00
140.00	0.14	2,344	670.26	0.14	0.14	0.00	0.00
145.00	0.13	2,220	670.25	0.13	0.13	0.00	0.00
150.00	0.15	2,296	670.26	0.14	0.14	0.00	0.00
155.00	0.17	2,487	670.28	0.16	0.16	0.00	0.00
160.00	0.21	2,766	670.31	0.18	0.18	0.00	0.00
165.00	0.25	3,195	670.36	0.22	0.22	0.00	0.00
170.00	0.28	3,761	670.41	0.25	0.25	0.00	0.00
175.00	0.28	4,092	670.45	0.27	0.27	0.00	0.00
180.00	0.29	4,267	670.46	0.28	0.28	0.00	0.00
185.00	0.32	4,541	670.49	0.29	0.29	0.00	0.00
190.00	0.35	5,031	670.54	0.32	0.32	0.00	0.00
195.00	0.40	5,738	670.61	0.35	0.35	0.00	0.00
200.00	**0.48**	6,999	670.73	0.39	0.39	0.00	0.00
205.00	**0.54**	8,874	670.83	0.43	0.43	0.00	0.00
210.00	0.54	10,661	670.92	0.45	0.45	0.00	0.00
215.00	0.53	11,901	670.98	0.47	0.47	0.00	0.00
220.00	0.49	**12,511**	**671.01**	**0.48**	**0.48**	0.00	0.00
225.00	0.43	**12,121**	**670.99**	**0.48**	**0.48**	0.00	0.00
230.00	0.39	10,960	670.93	0.46	0.46	0.00	0.00
235.00	0.39	9,894	670.88	0.44	0.44	0.00	0.00
240.00	0.39	9,108	670.84	0.43	0.43	0.00	0.00
245.00	0.00	3,398	670.38	0.23	0.23	0.00	0.00
250.00	0.00	1,268	670.14	0.05	0.05	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	0.25 cfs @ 204.66 hrs, Volume=	1.438 af
Outflow	=	0.25 cfs @ 205.00 hrs, Volume=	1.437 af, Atten= 0%, Lag= 20.6 min
Primary	=	0.15 cfs @ 205.00 hrs, Volume=	0.432 af
Secondary	=	0.11 cfs @ 205.00 hrs, Volume=	1.005 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Peak Elev= 676.73' @ 205.00 hrs Surf.Area= 957 sf Storage= 191 cf

Plug-Flow detention time= 15.0 min calculated for 1.436 af (100% of inflow)
Center-of-Mass det. time= 13.0 min (11,148.5 - 11,135.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.15 cfs @ 205.00 hrs HW=676.73' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 0.15 cfs @ 1.63 fps)
└2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 205.00 hrs HW=676.73' TW=670.83' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.57 fps)
└5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
15.00	0.00	0	670.75	0.00	0.00	0.00	0.00
20.00	0.00	0	670.75	0.00	0.00	0.00	0.00
25.00	0.00	0	670.75	0.00	0.00	0.00	0.00
30.00	0.00	0	670.75	0.00	0.00	0.00	0.00
35.00	0.00	0	670.75	0.00	0.00	0.00	0.00
40.00	0.00	3	670.94	0.00	0.00	0.00	0.00
45.00	0.00	39	673.54	0.00	0.00	0.00	0.00
50.00	0.01	39	673.56	0.01	0.00	0.01	0.00
55.00	0.01	40	673.58	0.01	0.00	0.01	0.00
60.00	0.01	40	673.61	0.01	0.00	0.01	0.00
65.00	0.02	40	673.64	0.02	0.00	0.02	0.00
70.00	0.02	41	673.67	0.02	0.00	0.02	0.00
75.00	0.02	41	673.71	0.02	0.00	0.02	0.00
80.00	0.02	42	673.74	0.02	0.00	0.02	0.00
85.00	0.03	42	673.78	0.03	0.00	0.03	0.00
90.00	0.03	43	673.81	0.03	0.00	0.03	0.00
95.00	0.03	43	673.85	0.03	0.00	0.03	0.00
100.00	0.03	44	673.88	0.03	0.00	0.03	0.00
105.00	0.03	44	673.91	0.03	0.00	0.03	0.00
110.00	0.04	45	673.95	0.04	0.00	0.04	0.00
115.00	0.04	45	673.98	0.04	0.00	0.04	0.00
120.00	0.04	46	674.01	0.04	0.00	0.04	0.00
125.00	0.05	48	674.17	0.05	0.00	0.05	0.00
130.00	0.05	51	674.38	0.05	0.00	0.05	0.00
135.00	0.05	52	674.43	0.06	0.00	0.06	0.00
140.00	0.05	50	674.29	0.05	0.00	0.05	0.00
145.00	0.05	48	674.19	0.05	0.00	0.05	0.00
150.00	0.05	51	674.40	0.05	0.00	0.05	0.00
155.00	0.06	55	674.66	0.06	0.00	0.06	0.00
160.00	0.08	62	675.17	0.07	0.00	0.07	0.00
165.00	0.09	72	675.91	0.09	0.00	0.09	0.00
170.00	0.10	82	676.52	0.10	0.00	0.10	0.00
175.00	0.11	84	676.53	0.11	0.00	0.10	0.00
180.00	0.11	86	676.54	0.11	0.01	0.10	0.00
185.00	0.12	98	676.58	0.12	0.02	0.10	0.00
190.00	0.14	107	676.61	0.14	0.04	0.10	0.00
195.00	0.17	132	676.65	0.17	0.07	0.10	0.00
200.00	**0.22**	160	676.69	0.21	0.11	0.10	0.00
205.00	**0.25**	**195**	**676.73**	**0.25**	**0.15**	**0.11**	0.00
210.00	0.25	192	676.72	0.25	0.15	0.11	0.00
215.00	0.25	188	676.72	0.25	0.14	0.11	0.00
220.00	0.22	168	676.70	0.22	0.12	0.10	0.00
225.00	0.19	144	676.67	0.19	0.09	0.10	0.00
230.00	0.17	129	676.64	0.17	0.06	0.10	0.00
235.00	0.17	129	676.64	0.17	0.06	0.10	0.00
240.00	0.17	130	676.65	0.17	0.06	0.10	0.00
245.00	0.00	39	673.50	0.00	0.00	0.00	0.00
250.00	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 5.62 cfs @ 0.48 hrs, Volume= 0.290 af, Depth= 1.00"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=2.42"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	2.42	1.00	2.29
0.02	0.03	0.00	0.00	1.06	2.42	1.00	2.18
0.04	0.13	0.00	0.00	1.08	2.42	1.00	2.07
0.06	0.27	0.00	0.00	1.10	2.42	1.00	1.96
0.08	0.43	0.00	0.00	1.12	2.42	1.00	1.83
0.10	0.60	0.02	0.00	1.14	2.42	1.00	1.69
0.12	0.75	0.05	0.01	1.16	2.42	1.00	1.53
0.14	0.88	0.09	0.03	1.18	2.42	1.00	1.37
0.16	0.98	0.12	0.10	1.20	2.42	1.00	1.20
0.18	1.07	0.16	0.22	1.22	2.42	1.00	1.05
0.20	1.16	0.20	0.43	1.24	2.42	1.00	0.90
0.22	1.25	0.24	0.73	1.26	2.42	1.00	0.76
0.24	1.33	0.28	1.13	1.28	2.42	1.00	0.64
0.26	1.41	0.33	1.62	1.30	2.42	1.00	0.53
0.28	1.48	0.37	2.16	1.32	2.42	1.00	0.44
0.30	1.54	0.40	2.72	1.34	2.42	1.00	0.36
0.32	1.60	0.44	3.28	1.36	2.42	1.00	0.30
0.34	1.65	0.47	3.83	1.38	2.42	1.00	0.25
0.36	1.70	0.50	4.32	1.40	2.42	1.00	0.21
0.38	1.74	0.53	4.75	1.42	2.42	1.00	0.18
0.40	1.78	0.55	5.09	1.44	2.42	1.00	0.15
0.42	1.82	0.58	5.34	1.46	2.42	1.00	0.12
0.44	1.86	0.60	5.50	1.48	2.42	1.00	0.10
0.46	1.90	0.63	5.59	1.50	2.42	1.00	0.08
0.48	1.94	0.65	**5.62**	1.52	2.42	1.00	0.07
0.50	1.97	0.67	5.59	1.54	2.42	1.00	0.06
0.52	2.00	0.69	5.53	1.56	2.42	1.00	0.05
0.54	2.02	0.71	5.42	1.58	2.42	1.00	0.04
0.56	2.04	0.72	5.30	1.60	2.42	1.00	0.03
0.58	2.06	0.74	5.15	1.62	2.42	1.00	0.03
0.60	2.08	0.75	5.00	1.64	2.42	1.00	0.02
0.62	2.10	0.76	4.81	1.66	2.42	1.00	0.02
0.64	2.12	0.78	4.62	1.68	2.42	1.00	0.01
0.66	2.14	0.79	4.41	1.70	2.42	1.00	0.01
0.68	2.16	0.80	4.20	1.72	2.42	1.00	0.01
0.70	2.18	0.82	3.98	1.74	2.42	1.00	0.01
0.72	2.20	0.83	3.78	1.76	2.42	1.00	0.01
0.74	2.21	0.85	3.58	1.78	2.42	1.00	0.00
0.76	2.23	0.86	3.40	1.80	2.42	1.00	0.00
0.78	2.25	0.87	3.25	1.82	2.42	1.00	0.00
0.80	2.27	0.89	3.11	1.84	2.42	1.00	0.00
0.82	2.29	0.90	3.00	1.86	2.42	1.00	0.00
0.84	2.31	0.92	2.91	1.88	2.42	1.00	0.00
0.86	2.33	0.93	2.84	1.90	2.42	1.00	0.00
0.88	2.35	0.94	2.78	1.92	2.42	1.00	0.00
0.90	2.36	0.95	2.73	1.94	2.42	1.00	0.00
0.92	2.37	0.96	2.69	1.96	2.42	1.00	0.00
0.94	2.38	0.96	2.64	1.98	2.42	1.00	0.00
0.96	2.39	0.97	2.59	2.00	2.42	1.00	0.00
0.98	2.40	0.98	2.53				
1.00	**2.42**	**1.00**	2.46				
1.02	2.42	1.00	2.38				

Summary for Subcatchment 7S: South Property


Runoff = 10.52 cfs @ 0.61 hrs, Volume= 0.622 af, Depth> 1.00"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=2.42"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	1.04	2.42	1.00	5.85
0.02	0.03	0.00	0.00	1.06	2.42	1.00	5.68
0.04	0.13	0.00	0.00	1.08	2.42	1.00	5.52
0.06	0.27	0.00	0.00	1.10	2.42	1.00	5.33
0.08	0.43	0.00	0.00	1.12	2.42	1.00	5.13
0.10	0.60	0.02	0.00	1.14	2.42	1.00	4.92
0.12	0.75	0.05	0.01	1.16	2.42	1.00	4.69
0.14	0.88	0.09	0.03	1.18	2.42	1.00	4.45
0.16	0.98	0.12	0.06	1.20	2.42	1.00	4.20
0.18	1.07	0.16	0.14	1.22	2.42	1.00	3.91
0.20	1.16	0.20	0.27	1.24	2.42	1.00	3.63
0.22	1.25	0.24	0.47	1.26	2.42	1.00	3.34
0.24	1.33	0.28	0.74	1.28	2.42	1.00	3.05
0.26	1.41	0.33	1.11	1.30	2.42	1.00	2.77
0.28	1.48	0.37	1.59	1.32	2.42	1.00	2.50
0.30	1.54	0.40	2.17	1.34	2.42	1.00	2.25
0.32	1.60	0.44	2.85	1.36	2.42	1.00	2.01
0.34	1.65	0.47	3.59	1.38	2.42	1.00	1.79
0.36	1.70	0.50	4.39	1.40	2.42	1.00	1.59
0.38	1.74	0.53	5.21	1.42	2.42	1.00	1.40
0.40	1.78	0.55	6.03	1.44	2.42	1.00	1.23
0.42	1.82	0.58	6.82	1.46	2.42	1.00	1.08
0.44	1.86	0.60	7.57	1.48	2.42	1.00	0.95
0.46	1.90	0.63	8.26	1.50	2.42	1.00	0.84
0.48	1.94	0.65	8.86	1.52	2.42	1.00	0.74
0.50	1.97	0.67	9.39	1.54	2.42	1.00	0.65
0.52	2.00	0.69	9.79	1.56	2.42	1.00	0.58
0.54	2.02	0.71	10.12	1.58	2.42	1.00	0.51
0.56	2.04	0.72	10.36	1.60	2.42	1.00	0.45
0.58	2.06	0.74	10.46	1.62	2.42	1.00	0.40
0.60	2.08	0.75	**10.50**	1.64	2.42	1.00	0.35
0.62	2.10	0.76	**10.48**	1.66	2.42	1.00	0.31
0.64	2.12	0.78	10.38	1.68	2.42	1.00	0.27
0.66	2.14	0.79	10.25	1.70	2.42	1.00	0.24
0.68	2.16	0.80	10.04	1.72	2.42	1.00	0.21
0.70	2.18	0.82	9.80	1.74	2.42	1.00	0.18
0.72	2.20	0.83	9.54	1.76	2.42	1.00	0.16
0.74	2.21	0.85	9.24	1.78	2.42	1.00	0.14
0.76	2.23	0.86	8.94	1.80	2.42	1.00	0.12
0.78	2.25	0.87	8.64	1.82	2.42	1.00	0.11
0.80	2.27	0.89	8.33	1.84	2.42	1.00	0.09
0.82	2.29	0.90	8.04	1.86	2.42	1.00	0.08
0.84	2.31	0.92	7.76	1.88	2.42	1.00	0.07
0.86	2.33	0.93	7.49	1.90	2.42	1.00	0.06
0.88	2.35	0.94	7.25	1.92	2.42	1.00	0.05
0.90	2.36	0.95	7.02	1.94	2.42	1.00	0.05
0.92	2.37	0.96	6.82	1.96	2.42	1.00	0.04
0.94	2.38	0.96	6.63	1.98	2.42	1.00	0.04
0.96	2.39	0.97	6.45	2.00	2.42	1.00	0.03
0.98	2.40	0.98	6.30				
1.00	**2.42**	**1.00**	6.14				
1.02	2.42	1.00	5.99				

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.29 cfs @ 0.76 hrs, Volume= 0.088 af, Depth> 0.88"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=2.42"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.02	0.03	0.00	0.00
0.04	0.13	0.00	0.00
0.06	0.27	0.00	0.00
0.08	0.43	0.00	0.00
0.10	0.60	0.01	0.00
0.12	0.75	0.03	0.00
0.14	0.88	0.06	0.00
0.16	0.98	0.09	0.00
0.18	1.07	0.12	0.01
0.20	1.16	0.16	0.01
0.22	1.25	0.19	0.02
0.24	1.33	0.23	0.03
0.26	1.41	0.27	0.05
0.28	1.48	0.30	0.07
0.30	1.54	0.34	0.10
0.32	1.60	0.37	0.14
0.34	1.65	0.40	0.18
0.36	1.70	0.42	0.24
0.38	1.74	0.45	0.30
0.40	1.78	0.47	0.36
0.42	1.82	0.50	0.43
0.44	1.86	0.52	0.51
0.46	1.90	0.54	0.59
0.48	1.94	0.56	0.67
0.50	1.97	0.58	0.75
0.52	2.00	0.60	0.83
0.54	2.02	0.62	0.90
0.56	2.04	0.63	0.97
0.58	2.06	0.64	1.03
0.60	2.08	0.65	1.09
0.62	2.10	0.67	1.14
0.64	2.12	0.68	1.19
0.66	2.14	0.69	1.22
0.68	2.16	0.71	1.25
0.70	2.18	0.72	1.27
0.72	2.20	0.73	1.28
0.74	2.21	0.74	1.29
0.76	2.23	0.76	**1.29**
0.78	2.25	0.77	1.28
0.80	2.27	0.78	1.27
0.82	2.29	0.80	1.25
0.84	2.31	0.81	1.23
0.86	2.33	0.82	1.21
0.88	2.35	0.84	1.18
0.90	2.36	0.84	1.16
0.92	2.37	0.85	1.14
0.94	2.38	0.86	1.11
0.96	2.39	0.86	1.09
0.98	2.40	0.87	1.06
1.00	**2.42**	**0.89**	1.04
1.02	2.42	0.89	1.01
1.04	2.42	0.89	0.99
1.06	2.42	0.89	0.97
1.08	2.42	0.89	0.95
1.10	2.42	0.89	0.92
1.12	2.42	0.89	0.90
1.14	2.42	0.89	0.88
1.16	2.42	0.89	0.85
1.18	2.42	0.89	0.83
1.20	2.42	0.89	0.80
1.22	2.42	0.89	0.77
1.24	2.42	0.89	0.74
1.26	2.42	0.89	0.71
1.28	2.42	0.89	0.67
1.30	2.42	0.89	0.64
1.32	2.42	0.89	0.61
1.34	2.42	0.89	0.57
1.36	2.42	0.89	0.53
1.38	2.42	0.89	0.50
1.40	2.42	0.89	0.46
1.42	2.42	0.89	0.43
1.44	2.42	0.89	0.40
1.46	2.42	0.89	0.37
1.48	2.42	0.89	0.34
1.50	2.42	0.89	0.31
1.52	2.42	0.89	0.28
1.54	2.42	0.89	0.26
1.56	2.42	0.89	0.24
1.58	2.42	0.89	0.22
1.60	2.42	0.89	0.20
1.62	2.42	0.89	0.18
1.64	2.42	0.89	0.16
1.66	2.42	0.89	0.15
1.68	2.42	0.89	0.14
1.70	2.42	0.89	0.13
1.72	2.42	0.89	0.11
1.74	2.42	0.89	0.10
1.76	2.42	0.89	0.10
1.78	2.42	0.89	0.09
1.80	2.42	0.89	0.08
1.82	2.42	0.89	0.07
1.84	2.42	0.89	0.07
1.86	2.42	0.89	0.06
1.88	2.42	0.89	0.06
1.90	2.42	0.89	0.05
1.92	2.42	0.89	0.05
1.94	2.42	0.89	0.04
1.96	2.42	0.89	0.04
1.98	2.42	0.89	0.03
2.00	2.42	0.89	0.03

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.90 cfs @ 0.38 hrs, Volume= 0.041 af, Depth= 0.89"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=2.42"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.02	0.03	0.00	0.00
0.04	0.13	0.00	0.00
0.06	0.27	0.00	0.00
0.08	0.43	0.00	0.00
0.10	0.60	0.01	0.00
0.12	0.75	0.03	0.00
0.14	0.88	0.06	0.02
0.16	0.98	0.09	0.06
0.18	1.07	0.12	0.13
0.20	1.16	0.16	0.24
0.22	1.25	0.19	0.36
0.24	1.33	0.23	0.49
0.26	1.41	0.27	0.60
0.28	1.48	0.30	0.70
0.30	1.54	0.34	0.77
0.32	1.60	0.37	0.83
0.34	1.65	0.40	0.88
0.36	1.70	0.42	0.90
0.38	1.74	0.45	**0.90**
0.40	1.78	0.47	0.89
0.42	1.82	0.50	0.87
0.44	1.86	0.52	0.84
0.46	1.90	0.54	0.81
0.48	1.94	0.56	0.77
0.50	1.97	0.58	0.74
0.52	2.00	0.60	0.72
0.54	2.02	0.62	0.69
0.56	2.04	0.63	0.66
0.58	2.06	0.64	0.63
0.60	2.08	0.65	0.59
0.62	2.10	0.67	0.54
0.64	2.12	0.68	0.50
0.66	2.14	0.69	0.46
0.68	2.16	0.71	0.43
0.70	2.18	0.72	0.41
0.72	2.20	0.73	0.40
0.74	2.21	0.74	0.38
0.76	2.23	0.76	0.38
0.78	2.25	0.77	0.37
0.80	2.27	0.78	0.37
0.82	2.29	0.80	0.37
0.84	2.31	0.81	0.37
0.86	2.33	0.82	0.37
0.88	2.35	0.84	0.37
0.90	2.36	0.84	0.37
0.92	2.37	0.85	0.36
0.94	2.38	0.86	0.35
0.96	2.39	0.86	0.33
0.98	2.40	0.87	0.31
1.00	**2.42**	**0.89**	0.29
1.02	2.42	0.89	0.27
1.04	2.42	0.89	0.25
1.06	2.42	0.89	0.24
1.08	2.42	0.89	0.22
1.10	2.42	0.89	0.19
1.12	2.42	0.89	0.15
1.14	2.42	0.89	0.12
1.16	2.42	0.89	0.09
1.18	2.42	0.89	0.06
1.20	2.42	0.89	0.04
1.22	2.42	0.89	0.03
1.24	2.42	0.89	0.02
1.26	2.42	0.89	0.02
1.28	2.42	0.89	0.01
1.30	2.42	0.89	0.01
1.32	2.42	0.89	0.01
1.34	2.42	0.89	0.00
1.36	2.42	0.89	0.00
1.38	2.42	0.89	0.00
1.40	2.42	0.89	0.00
1.42	2.42	0.89	0.00
1.44	2.42	0.89	0.00
1.46	2.42	0.89	0.00
1.48	2.42	0.89	0.00
1.50	2.42	0.89	0.00
1.52	2.42	0.89	0.00
1.54	2.42	0.89	0.00
1.56	2.42	0.89	0.00
1.58	2.42	0.89	0.00
1.60	2.42	0.89	0.00
1.62	2.42	0.89	0.00
1.64	2.42	0.89	0.00
1.66	2.42	0.89	0.00
1.68	2.42	0.89	0.00
1.70	2.42	0.89	0.00
1.72	2.42	0.89	0.00
1.74	2.42	0.89	0.00
1.76	2.42	0.89	0.00
1.78	2.42	0.89	0.00
1.80	2.42	0.89	0.00
1.82	2.42	0.89	0.00
1.84	2.42	0.89	0.00
1.86	2.42	0.89	0.00
1.88	2.42	0.89	0.00
1.90	2.42	0.89	0.00
1.92	2.42	0.89	0.00
1.94	2.42	0.89	0.00
1.96	2.42	0.89	0.00
1.98	2.42	0.89	0.00
2.00	2.42	0.89	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	15.02 cfs @	0.59 hrs, Volume=	0.847 af
Outflow	=	0.71 cfs @	1.56 hrs, Volume=	0.083 af, Atten= 95%, Lag= 58.0 min
Primary	=	0.71 cfs @	1.56 hrs, Volume=	0.083 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 671.97' @ 1.56 hrs Surf.Area= 30,801 sf Storage= 33,959 cf

Plug-Flow detention time= 55.0 min calculated for 0.082 af (10% of inflow)
Center-of-Mass det. time= 29.2 min (76.8 - 47.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00'** L Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.71 cfs @ 1.56 hrs HW=671.97' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.71 cfs @ 6.44 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.05	0.00	0	670.00	0.00	0.00	0.00	0.00
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.15	0.07	3	670.00	0.00	0.00	0.00	0.00
0.20	0.52	40	670.00	0.00	0.00	0.00	0.00
0.25	1.57	205	670.02	0.00	0.00	0.00	0.00
0.30	3.05	585	670.07	0.01	0.01	0.00	0.00
0.35	4.99	1,266	670.14	0.05	0.05	0.00	0.00
0.40	7.04	2,298	670.26	0.14	0.14	0.00	0.00
0.45	8.88	3,668	670.41	0.25	0.25	0.00	0.00
0.50	12.23	5,419	670.58	0.33	0.33	0.00	0.00
0.55	**14.60**	7,763	670.78	0.41	0.41	0.00	0.00
0.60	**15.01**	10,362	670.90	0.45	0.45	0.00	0.00
0.65	14.60	12,959	671.03	0.49	0.49	0.00	0.00
0.70	13.78	15,443	671.15	0.52	0.52	0.00	0.00
0.75	12.75	17,756	671.25	0.55	0.55	0.00	0.00
0.80	11.70	19,875	671.35	0.57	0.57	0.00	0.00
0.85	10.76	21,807	671.43	0.59	0.59	0.00	0.00
0.90	9.98	23,578	671.51	0.61	0.61	0.00	0.00
0.95	9.35	25,218	671.58	0.63	0.63	0.00	0.00
1.00	8.76	26,744	671.65	0.64	0.64	0.00	0.00
1.05	8.18	28,164	671.71	0.66	0.66	0.00	0.00
1.10	7.48	29,470	671.77	0.67	0.67	0.00	0.00
1.15	6.60	30,633	671.82	0.68	0.68	0.00	0.00
1.20	5.58	31,625	671.87	0.69	0.69	0.00	0.00
1.25	4.48	32,426	671.90	0.70	0.70	0.00	0.00
1.30	3.40	33,026	671.93	0.70	0.70	0.00	0.00
1.35	2.47	33,442	671.95	0.71	0.71	0.00	0.00
1.40	1.74	33,704	671.96	0.71	0.71	0.00	0.00
1.45	1.28	33,853	671.97	0.71	0.71	0.00	0.00
1.50	0.96	33,930	671.97	0.71	0.71	0.00	0.00
1.55	0.74	**33,958**	**671.97**	**0.71**	**0.71**	0.00	0.00
1.60	0.57	**33,950**	**671.97**	**0.71**	**0.71**	0.00	0.00
1.65	0.44	33,915	671.97	0.71	0.71	0.00	0.00
1.70	0.35	33,860	671.97	0.71	0.71	0.00	0.00
1.75	0.29	33,791	671.97	0.71	0.71	0.00	0.00
1.80	0.24	33,711	671.96	0.71	0.71	0.00	0.00
1.85	0.20	33,623	671.96	0.71	0.71	0.00	0.00
1.90	0.18	33,531	671.95	0.71	0.71	0.00	0.00
1.95	0.16	33,434	671.95	0.71	0.71	0.00	0.00
2.00	0.00	33,334	671.95	0.71	0.71	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	6.35 cfs @	0.52 hrs, Volume=	0.379 af
Outflow	=	6.12 cfs @	0.60 hrs, Volume=	0.360 af, Atten= 4%, Lag= 4.9 min
Primary	=	2.20 cfs @	0.60 hrs, Volume=	0.175 af
Secondary	=	3.92 cfs @	0.60 hrs, Volume=	0.185 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Peak Elev= 678.13' @ 0.60 hrs Surf.Area= 3,302 sf Storage= 3,649 cf

Plug-Flow detention time= 15.0 min calculated for 0.358 af (95% of inflow)
Center-of-Mass det. time= 12.9 min (56.9 - 44.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=2.20 cfs @ 0.60 hrs HW=678.13' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.29 cfs @ 5.61 fps)
└—**2=Sharp-Crested Rectangular Weir** (Weir Controls 0.91 cfs @ 1.19 fps)


Secondary OutFlow Max=3.92 cfs @ 0.60 hrs HW=678.13' TW=670.90' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.29 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 3.79 cfs @ 1.95 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.05	0.00	0	670.75	0.00	0.00	0.00	0.00
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.15	0.06	2	670.91	0.00	0.00	0.00	0.00
0.20	0.44	34	673.17	0.00	0.00	0.00	0.00
0.25	1.41	159	676.69	0.21	0.11	0.10	0.00
0.30	2.82	451	676.92	0.53	0.42	0.11	0.00
0.35	4.29	950	677.16	0.80	0.69	0.11	0.00
0.40	5.45	1,650	677.45	1.03	0.91	0.12	0.00
0.45	6.11	2,486	677.75	1.22	1.10	0.12	0.00
0.50	**6.34**	3,277	678.01	3.37	1.27	2.10	0.00
0.55	**6.30**	3,604	678.11	5.73	2.05	3.68	0.00
0.60	6.09	**3,650**	**678.13**	**6.12**	**2.20**	**3.92**	0.00
0.65	5.72	3,628	678.12	5.94	2.13	3.81	0.00
0.70	5.26	3,583	678.11	5.55	1.98	3.57	0.00
0.75	4.78	3,527	678.09	5.10	1.82	3.28	0.00
0.80	4.38	3,472	678.07	4.67	1.66	3.00	0.00
0.85	4.09	3,425	678.06	4.32	1.54	2.77	0.00
0.90	3.89	3,388	678.05	4.06	1.46	2.60	0.00
0.95	3.71	3,359	678.04	3.87	1.40	2.46	0.00
1.00	3.50	3,331	678.03	3.68	1.35	2.33	0.00
1.05	3.22	3,294	678.02	3.46	1.29	2.17	0.00
1.10	2.88	3,245	678.00	3.20	1.24	1.96	0.00
1.15	2.47	3,181	677.98	2.91	1.22	1.69	0.00
1.20	2.00	3,094	677.96	2.55	1.21	1.34	0.00
1.25	1.55	2,990	677.92	2.16	1.19	0.97	0.00
1.30	1.17	2,879	677.89	1.79	1.17	0.62	0.00
1.35	0.88	2,768	677.85	1.49	1.15	0.34	0.00
1.40	0.68	2,659	677.81	1.28	1.13	0.15	0.00
1.45	0.51	2,543	677.77	1.23	1.11	0.12	0.00
1.50	0.39	2,407	677.73	1.21	1.08	0.12	0.00
1.55	0.30	2,256	677.67	1.17	1.05	0.12	0.00
1.60	0.23	2,096	677.62	1.14	1.02	0.12	0.00
1.65	0.18	1,931	677.56	1.10	0.98	0.12	0.00
1.70	0.14	1,764	677.49	1.06	0.94	0.12	0.00
1.75	0.11	1,599	677.43	1.02	0.90	0.12	0.00
1.80	0.08	1,437	677.36	0.97	0.85	0.12	0.00
1.85	0.07	1,279	677.30	0.92	0.81	0.11	0.00
1.90	0.05	1,128	677.24	0.87	0.76	0.11	0.00
1.95	0.04	983	677.17	0.82	0.70	0.11	0.00
2.00	0.00	847	677.11	0.76	0.65	0.11	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 4.96 cfs @ 0.67 hrs, Volume= 0.420 af, Depth= 1.44"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=2.99"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.06	0.00	0.00
0.10	0.24	0.00	0.00
0.15	0.49	0.00	0.00
0.20	0.74	0.05	0.02
0.25	0.97	0.12	0.17
0.30	1.15	0.20	0.67
0.35	1.29	0.27	1.58
0.40	1.43	0.34	2.62
0.45	1.57	0.42	3.52
0.50	1.69	0.49	4.14
0.55	1.80	0.57	4.55
0.60	1.90	0.63	4.82
0.65	1.99	0.69	**4.94**
0.70	2.07	0.74	**4.92**
0.75	2.14	0.79	4.77
0.80	2.20	0.84	4.54
0.85	2.27	0.88	4.27
0.90	2.33	0.93	3.99
0.95	2.38	0.97	3.73
1.00	2.43	1.00	3.51
1.05	2.47	1.04	3.32
1.10	2.51	1.06	3.13
1.15	2.54	1.08	2.90
1.20	2.57	1.11	2.62
1.25	2.60	1.13	2.34
1.30	2.63	1.15	2.10
1.35	2.66	1.18	1.93
1.40	2.69	1.20	1.82
1.45	2.72	1.22	1.75
1.50	2.75	1.25	1.71
1.55	2.78	1.27	1.69
1.60	2.81	1.29	1.68
1.65	2.84	1.32	1.67
1.70	2.87	1.34	1.67
1.75	2.90	1.36	1.67
1.80	2.91	1.38	1.67
1.85	2.93	1.39	1.62
1.90	2.94	1.40	1.52
1.95	2.96	1.42	1.37
2.00	**2.99**	**1.44**	1.22
2.05	2.99	1.44	1.13
2.10	2.99	1.44	1.08
2.15	2.99	1.44	0.96
2.20	2.99	1.44	0.75
2.25	2.99	1.44	0.53
2.30	2.99	1.44	0.33
2.35	2.99	1.44	0.21
2.40	2.99	1.44	0.13
2.45	2.99	1.44	0.08
2.50	2.99	1.44	0.05
2.55	2.99	1.44	0.03
2.60	2.99	1.44	0.02
2.65	2.99	1.44	0.01
2.70	2.99	1.44	0.01
2.75	2.99	1.44	0.00
2.80	2.99	1.44	0.00
2.85	2.99	1.44	0.00
2.90	2.99	1.44	0.00
2.95	2.99	1.44	0.00
3.00	2.99	1.44	0.00

Summary for Subcatchment 7S: South Property


Runoff = 9.76 cfs @ 0.78 hrs, Volume= 0.899 af, Depth> 1.44"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=2.99"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.06	0.00	0.00
0.10	0.24	0.00	0.00
0.15	0.49	0.00	0.00
0.20	0.74	0.05	0.01
0.25	0.97	0.12	0.11
0.30	1.15	0.20	0.44
0.35	1.29	0.27	1.17
0.40	1.43	0.34	2.36
0.45	1.57	0.42	3.86
0.50	1.69	0.49	5.40
0.55	1.80	0.57	6.81
0.60	1.90	0.63	7.99
0.65	1.99	0.69	8.85
0.70	2.07	0.74	9.41
0.75	2.14	0.79	**9.70**
0.80	2.20	0.84	**9.74**
0.85	2.27	0.88	9.59
0.90	2.33	0.93	9.28
0.95	2.38	0.97	8.88
1.00	2.43	1.00	8.45
1.05	2.47	1.04	8.03
1.10	2.51	1.06	7.62
1.15	2.54	1.08	7.20
1.20	2.57	1.11	6.74
1.25	2.60	1.13	6.25
1.30	2.63	1.15	5.74
1.35	2.66	1.18	5.25
1.40	2.69	1.20	4.83
1.45	2.72	1.22	4.48
1.50	2.75	1.25	4.22
1.55	2.78	1.27	4.03
1.60	2.81	1.29	3.90
1.65	2.84	1.32	3.80
1.70	2.87	1.34	3.74
1.75	2.90	1.36	3.69
1.80	2.91	1.38	3.66
1.85	2.93	1.39	3.61
1.90	2.94	1.40	3.52
1.95	2.96	1.42	3.37
2.00	**2.99**	**1.44**	3.16
2.05	2.99	1.44	2.94
2.10	2.99	1.44	2.73
2.15	2.99	1.44	2.51
2.20	2.99	1.44	2.26
2.25	2.99	1.44	1.95
2.30	2.99	1.44	1.59
2.35	2.99	1.44	1.25
2.40	2.99	1.44	0.94
2.45	2.99	1.44	0.68
2.50	2.99	1.44	0.50
2.55	2.99	1.44	0.36
2.60	2.99	1.44	0.27
2.65	2.99	1.44	0.20
2.70	2.99	1.44	0.14
2.75	2.99	1.44	0.10
2.80	2.99	1.44	0.08
2.85	2.99	1.44	0.05
2.90	2.99	1.44	0.04
2.95	2.99	1.44	0.03
3.00	2.99	1.44	0.02

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.27 cfs @ 0.94 hrs, Volume= 0.130 af, Depth> 1.30"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=2.99"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.06	0.00	0.00
0.10	0.24	0.00	0.00
0.15	0.49	0.00	0.00
0.20	0.74	0.03	0.00
0.25	0.97	0.09	0.00
0.30	1.15	0.15	0.02
0.35	1.29	0.22	0.05
0.40	1.43	0.28	0.11
0.45	1.57	0.35	0.21
0.50	1.69	0.42	0.34
0.55	1.80	0.48	0.49
0.60	1.90	0.54	0.66
0.65	1.99	0.60	0.81
0.70	2.07	0.65	0.96
0.75	2.14	0.70	1.08
0.80	2.20	0.74	1.17
0.85	2.27	0.78	1.23
0.90	2.33	0.82	**1.27**
0.95	2.38	0.86	**1.27**
1.00	2.43	0.89	1.26
1.05	2.47	0.92	1.24
1.10	2.51	0.95	1.20
1.15	2.54	0.97	1.16
1.20	2.57	0.99	1.11
1.25	2.60	1.01	1.06
1.30	2.63	1.03	1.00
1.35	2.66	1.06	0.94
1.40	2.69	1.08	0.88
1.45	2.72	1.10	0.82
1.50	2.75	1.12	0.77
1.55	2.78	1.15	0.72
1.60	2.81	1.17	0.69
1.65	2.84	1.19	0.66
1.70	2.87	1.21	0.63
1.75	2.90	1.23	0.61
1.80	2.91	1.25	0.60
1.85	2.93	1.26	0.59
1.90	2.94	1.27	0.57
1.95	2.96	1.29	0.56
2.00	**2.99**	**1.31**	0.54
2.05	2.99	1.31	0.52
2.10	2.99	1.31	0.49
2.15	2.99	1.31	0.46
2.20	2.99	1.31	0.43
2.25	2.99	1.31	0.39
2.30	2.99	1.31	0.35
2.35	2.99	1.31	0.31
2.40	2.99	1.31	0.26
2.45	2.99	1.31	0.22
2.50	2.99	1.31	0.18
2.55	2.99	1.31	0.14
2.60	2.99	1.31	0.11
2.65	2.99	1.31	0.09
2.70	2.99	1.31	0.07
2.75	2.99	1.31	0.06
2.80	2.99	1.31	0.05
2.85	2.99	1.31	0.04
2.90	2.99	1.31	0.03
2.95	2.99	1.31	0.02
3.00	2.99	1.31	0.02

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.74 cfs @ 0.58 hrs, Volume= 0.060 af, Depth= 1.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=2.99"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.05	0.06	0.00	0.00
0.10	0.24	0.00	0.00
0.15	0.49	0.00	0.00
0.20	0.74	0.03	0.01
0.25	0.97	0.09	0.09
0.30	1.15	0.15	0.30
0.35	1.29	0.22	0.50
0.40	1.43	0.28	0.61
0.45	1.57	0.35	0.67
0.50	1.69	0.42	0.71
0.55	1.80	0.48	**0.74**
0.60	1.90	0.54	**0.74**
0.65	1.99	0.60	0.72
0.70	2.07	0.65	0.67
0.75	2.14	0.70	0.62
0.80	2.20	0.74	0.58
0.85	2.27	0.78	0.53
0.90	2.33	0.82	0.50
0.95	2.38	0.86	0.47
1.00	2.43	0.89	0.46
1.05	2.47	0.92	0.43
1.10	2.51	0.95	0.39
1.15	2.54	0.97	0.34
1.20	2.57	0.99	0.29
1.25	2.60	1.01	0.26
1.30	2.63	1.03	0.25
1.35	2.66	1.06	0.25
1.40	2.69	1.08	0.25
1.45	2.72	1.10	0.25
1.50	2.75	1.12	0.25
1.55	2.78	1.15	0.25
1.60	2.81	1.17	0.25
1.65	2.84	1.19	0.25
1.70	2.87	1.21	0.25
1.75	2.90	1.23	0.25
1.80	2.91	1.25	0.24
1.85	2.93	1.26	0.22
1.90	2.94	1.27	0.18
1.95	2.96	1.29	0.15
2.00	**2.99**	**1.31**	0.15
2.05	2.99	1.31	0.16
2.10	2.99	1.31	0.13
2.15	2.99	1.31	0.07
2.20	2.99	1.31	0.03
2.25	2.99	1.31	0.01
2.30	2.99	1.31	0.01
2.35	2.99	1.31	0.00
2.40	2.99	1.31	0.00
2.45	2.99	1.31	0.00
2.50	2.99	1.31	0.00
2.55	2.99	1.31	0.00
2.60	2.99	1.31	0.00
2.65	2.99	1.31	0.00
2.70	2.99	1.31	0.00
2.75	2.99	1.31	0.00
2.80	2.99	1.31	0.00
2.85	2.99	1.31	0.00
2.90	2.99	1.31	0.00
2.95	2.99	1.31	0.00
3.00	2.99	1.31	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	14.10 cfs @	0.77 hrs, Volume=	1.231 af
Outflow	=	0.83 cfs @	2.45 hrs, Volume=	0.147 af, Atten= 94%, Lag= 100.7 min
Primary	=	0.83 cfs @	2.45 hrs, Volume=	0.147 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 672.60' @ 2.45 hrs Surf.Area= 30,945 sf Storage= 48,250 cf

Plug-Flow detention time= 81.7 min calculated for 0.147 af (12% of inflow)
Center-of-Mass det. time= 42.4 min (112.9 - 70.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.83 cfs @ 2.45 hrs HW=672.60' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.83 cfs @ 7.48 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.02	1	670.00	0.00	0.00	0.00	0.00
0.30	0.82	82	670.01	0.00	0.00	0.00	0.00
0.40	3.08	703	670.08	0.02	0.02	0.00	0.00
0.50	6.23	2,298	670.26	0.14	0.14	0.00	0.00
0.60	9.44	4,922	670.53	0.31	0.31	0.00	0.00
0.70	**13.64**	9,038	670.84	0.43	0.43	0.00	0.00
0.80	**14.04**	13,900	671.07	0.50	0.50	0.00	0.00
0.90	13.26	18,662	671.29	0.56	0.56	0.00	0.00
1.00	12.09	23,041	671.49	0.61	0.61	0.00	0.00
1.10	10.91	26,977	671.66	0.65	0.65	0.00	0.00
1.20	9.58	30,457	671.82	0.68	0.68	0.00	0.00
1.30	8.10	33,416	671.95	0.71	0.71	0.00	0.00
1.40	6.78	35,850	672.06	0.73	0.73	0.00	0.00
1.50	5.90	37,869	672.15	0.74	0.74	0.00	0.00
1.60	5.40	39,632	672.23	0.76	0.76	0.00	0.00
1.70	5.14	41,255	672.30	0.77	0.77	0.00	0.00
1.80	5.00	42,803	672.36	0.78	0.78	0.00	0.00
1.90	4.72	44,283	672.43	0.80	0.80	0.00	0.00
2.00	4.12	45,604	672.49	0.81	0.81	0.00	0.00
2.10	3.44	46,686	672.53	0.81	0.81	0.00	0.00
2.20	2.66	47,508	672.57	0.82	0.82	0.00	0.00
2.30	1.72	48,016	672.59	0.82	0.82	0.00	0.00
2.40	1.06	**48,228**	**672.60**	**0.83**	**0.83**	0.00	0.00
2.50	0.62	**48,231**	**672.60**	**0.83**	**0.83**	0.00	0.00
2.60	0.39	48,114	672.60	0.83	0.83	0.00	0.00
2.70	0.26	47,933	672.59	0.82	0.82	0.00	0.00
2.80	0.19	47,717	672.58	0.82	0.82	0.00	0.00
2.90	0.15	47,482	672.57	0.82	0.82	0.00	0.00
3.00	0.00	47,237	672.56	0.82	0.82	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	5.89 cfs @	0.71 hrs, Volume=	0.550 af
Outflow	=	5.83 cfs @	0.76 hrs, Volume=	0.537 af, Atten= 1%, Lag= 3.2 min
Primary	=	2.09 cfs @	0.76 hrs, Volume=	0.264 af
Secondary	=	3.74 cfs @	0.76 hrs, Volume=	0.273 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Peak Elev= 678.12' @ 0.76 hrs Surf.Area= 3,292 sf Storage= 3,615 cf

Plug-Flow detention time= 16.9 min calculated for 0.537 af (98% of inflow)
Center-of-Mass det. time= 15.0 min (82.5 - 67.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=2.09 cfs @ 0.76 hrs HW=678.12' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.29 cfs @ 5.59 fps)
└—**2=Sharp-Crested Rectangular Weir** (Weir Controls 0.80 cfs @ 1.14 fps)


Secondary OutFlow Max=3.74 cfs @ 0.76 hrs HW=678.12' TW=670.99' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.28 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 3.62 cfs @ 1.92 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.02	0	670.78	0.00	0.00	0.00	0.00
0.30	0.69	70	675.74	0.09	0.00	0.09	0.00
0.40	2.74	527	676.96	0.59	0.48	0.11	0.00
0.50	4.48	1,540	677.41	1.00	0.88	0.12	0.00
0.60	5.47	2,911	677.90	1.89	1.18	0.71	0.00
0.70	**5.88**	**3,581**	**678.11**	**5.54**	**1.98**	**3.56**	0.00
0.80	**5.71**	**3,611**	**678.12**	**5.79**	**2.08**	**3.72**	0.00
0.90	5.26	3,566	678.10	5.42	1.93	3.48	0.00
1.00	4.78	3,506	678.08	4.93	1.76	3.18	0.00
1.10	4.33	3,450	678.07	4.50	1.61	2.90	0.00
1.20	3.73	3,377	678.04	3.98	1.44	2.55	0.00
1.30	3.11	3,280	678.01	3.38	1.27	2.11	0.00
1.40	2.70	3,187	677.99	2.93	1.22	1.71	0.00
1.50	2.48	3,116	677.96	2.64	1.21	1.43	0.00
1.60	2.36	3,071	677.95	2.46	1.20	1.25	0.00
1.70	2.30	3,044	677.94	2.36	1.20	1.16	0.00
1.80	2.26	3,029	677.93	2.30	1.20	1.10	0.00
1.90	2.10	3,006	677.93	2.22	1.19	1.02	0.00
2.00	1.76	2,941	677.91	1.99	1.18	0.81	0.00
2.10	1.57	2,866	677.88	1.75	1.17	0.58	0.00
2.20	1.18	2,781	677.85	1.52	1.15	0.37	0.00
2.30	0.68	2,623	677.80	1.25	1.13	0.12	0.00
2.40	0.40	2,375	677.72	1.20	1.08	0.12	0.00
2.50	0.23	2,067	677.61	1.13	1.01	0.12	0.00
2.60	0.13	1,739	677.48	1.05	0.94	0.12	0.00
2.70	0.08	1,412	677.35	0.96	0.85	0.12	0.00
2.80	0.05	1,105	677.23	0.86	0.75	0.11	0.00
2.90	0.03	826	677.10	0.75	0.64	0.11	0.00
3.00	0.00	583	676.99	0.63	0.52	0.11	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 4.11 cfs @ 0.87 hrs, Volume= 0.493 af, Depth= 1.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=3.30"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.08	2.96	1.41	1.28
0.04	0.02	0.00	0.00	2.12	2.98	1.43	1.27
0.08	0.08	0.00	0.00	2.16	2.99	1.44	1.26
0.12	0.17	0.00	0.00	2.20	3.01	1.46	1.26
0.16	0.30	0.00	0.00	2.24	3.03	1.47	1.26
0.20	0.45	0.00	0.00	2.28	3.05	1.48	1.26
0.24	0.59	0.02	0.00	2.32	3.06	1.50	1.26
0.28	0.74	0.05	0.03	2.36	3.08	1.51	1.26
0.32	0.89	0.09	0.15	2.40	3.10	1.53	1.26
0.36	1.02	0.14	0.44	2.44	3.12	1.54	1.26
0.40	1.14	0.19	0.93	2.48	3.14	1.56	1.27
0.44	1.24	0.24	1.56	2.52	3.15	1.57	1.27
0.48	1.33	0.29	2.23	2.56	3.17	1.59	1.27
0.52	1.42	0.33	2.83	2.60	3.19	1.60	1.27
0.56	1.50	0.38	3.27	2.64	3.20	1.61	1.27
0.60	1.58	0.43	3.56	2.68	3.21	1.62	1.26
0.64	1.66	0.48	3.74	2.72	3.22	1.63	1.23
0.68	1.74	0.52	3.86	2.76	3.23	1.63	1.18
0.72	1.81	0.57	3.95	2.80	3.24	1.64	1.10
0.76	1.88	0.62	4.02	2.84	3.25	1.65	1.01
0.80	1.95	0.66	4.07	2.88	3.26	1.66	0.92
0.84	2.01	0.71	**4.10**	2.92	3.27	1.67	0.84
0.88	2.07	0.75	**4.11**	2.96	3.28	1.68	0.79
0.92	2.13	0.78	4.08	3.00	**3.30**	**1.69**	0.77
0.96	2.18	0.82	4.01	3.04	3.30	1.69	0.78
1.00	2.23	0.85	3.91	3.08	3.30	1.69	0.80
1.04	2.27	0.89	3.77	3.12	3.30	1.69	0.79
1.08	2.32	0.92	3.63	3.16	3.30	1.69	0.72
1.12	2.36	0.95	3.48	3.20	3.30	1.69	0.59
1.16	2.40	0.98	3.34	3.24	3.30	1.69	0.44
1.20	2.43	1.01	3.20	3.28	3.30	1.69	0.31
1.24	2.47	1.03	3.06	3.32	3.30	1.69	0.22
1.28	2.50	1.06	2.93	3.36	3.30	1.69	0.15
1.32	2.54	1.09	2.80	3.40	3.30	1.69	0.10
1.36	2.58	1.11	2.69	3.44	3.30	1.69	0.07
1.40	2.61	1.14	2.60	3.48	3.30	1.69	0.05
1.44	2.64	1.16	2.53	3.52	3.30	1.69	0.03
1.48	2.67	1.19	2.47	3.56	3.30	1.69	0.02
1.52	2.70	1.21	2.41	3.60	3.30	1.69	0.02
1.56	2.72	1.23	2.34	3.64	3.30	1.69	0.01
1.60	2.74	1.24	2.25	3.68	3.30	1.69	0.01
1.64	2.76	1.26	2.15	3.72	3.30	1.69	0.01
1.68	2.78	1.27	2.03	3.76	3.30	1.69	0.00
1.72	2.80	1.29	1.89	3.80	3.30	1.69	0.00
1.76	2.82	1.30	1.76	3.84	3.30	1.69	0.00
1.80	2.83	1.31	1.63	3.88	3.30	1.69	0.00
1.84	2.85	1.33	1.52	3.92	3.30	1.69	0.00
1.88	2.87	1.34	1.44	3.96	3.30	1.69	0.00
1.92	2.89	1.36	1.38	4.00	3.30	1.69	0.00
1.96	2.90	1.37	1.33				
2.00	2.92	1.38	1.31				
2.04	2.94	1.40	1.29				

Summary for Subcatchment 7S: South Property


Runoff = 8.44 cfs @ 0.98 hrs, Volume= 1.057 af, Depth> 1.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=3.30"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	2.08	2.96	1.41	2.99
0.04	0.02	0.00	0.00	2.12	2.98	1.43	2.92
0.08	0.08	0.00	0.00	2.16	2.99	1.44	2.87
0.12	0.17	0.00	0.00	2.20	3.01	1.46	2.82
0.16	0.30	0.00	0.00	2.24	3.03	1.47	2.79
0.20	0.45	0.00	0.00	2.28	3.05	1.48	2.77
0.24	0.59	0.02	0.00	2.32	3.06	1.50	2.75
0.28	0.74	0.05	0.02	2.36	3.08	1.51	2.74
0.32	0.89	0.09	0.09	2.40	3.10	1.53	2.73
0.36	1.02	0.14	0.29	2.44	3.12	1.54	2.72
0.40	1.14	0.19	0.66	2.48	3.14	1.56	2.72
0.44	1.24	0.24	1.27	2.52	3.15	1.57	2.72
0.48	1.33	0.29	2.10	2.56	3.17	1.59	2.72
0.52	1.42	0.33	3.06	2.60	3.19	1.60	2.72
0.56	1.50	0.38	4.07	2.64	3.20	1.61	2.72
0.60	1.58	0.43	5.03	2.68	3.21	1.62	2.72
0.64	1.66	0.48	5.86	2.72	3.22	1.63	2.70
0.68	1.74	0.52	6.55	2.76	3.23	1.63	2.66
0.72	1.81	0.57	7.09	2.80	3.24	1.64	2.59
0.76	1.88	0.62	7.50	2.84	3.25	1.65	2.49
0.80	1.95	0.66	7.81	2.88	3.26	1.66	2.36
0.84	2.01	0.71	8.05	2.92	3.27	1.67	2.22
0.88	2.07	0.75	8.24	2.96	3.28	1.68	2.08
0.92	2.13	0.78	8.37	3.00	**3.30**	**1.69**	1.96
0.96	2.18	0.82	**8.42**	3.04	3.30	1.69	1.87
1.00	2.23	0.85	**8.42**	3.08	3.30	1.69	1.81
1.04	2.27	0.89	8.35	3.12	3.30	1.69	1.77
1.08	2.32	0.92	8.20	3.16	3.30	1.69	1.72
1.12	2.36	0.95	8.01	3.20	3.30	1.69	1.62
1.16	2.40	0.98	7.79	3.24	3.30	1.69	1.47
1.20	2.43	1.01	7.55	3.28	3.30	1.69	1.29
1.24	2.47	1.03	7.29	3.32	3.30	1.69	1.09
1.28	2.50	1.06	7.02	3.36	3.30	1.69	0.89
1.32	2.54	1.09	6.76	3.40	3.30	1.69	0.70
1.36	2.58	1.11	6.51	3.44	3.30	1.69	0.55
1.40	2.61	1.14	6.27	3.48	3.30	1.69	0.42
1.44	2.64	1.16	6.04	3.52	3.30	1.69	0.33
1.48	2.67	1.19	5.85	3.56	3.30	1.69	0.26
1.52	2.70	1.21	5.67	3.60	3.30	1.69	0.20
1.56	2.72	1.23	5.51	3.64	3.30	1.69	0.16
1.60	2.74	1.24	5.34	3.68	3.30	1.69	0.12
1.64	2.76	1.26	5.16	3.72	3.30	1.69	0.09
1.68	2.78	1.27	4.96	3.76	3.30	1.69	0.07
1.72	2.80	1.29	4.74	3.80	3.30	1.69	0.06
1.76	2.82	1.30	4.50	3.84	3.30	1.69	0.04
1.80	2.83	1.31	4.25	3.88	3.30	1.69	0.03
1.84	2.85	1.33	4.00	3.92	3.30	1.69	0.03
1.88	2.87	1.34	3.76	3.96	3.30	1.69	0.02
1.92	2.89	1.36	3.54	4.00	3.30	1.69	0.01
1.96	2.90	1.37	3.36				
2.00	2.92	1.38	3.21				
2.04	2.94	1.40	3.09				

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 1.14 cfs @ 1.13 hrs, Volume= 0.155 af, Depth> 1.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=3.30"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.04	0.02	0.00	0.00
0.08	0.08	0.00	0.00
0.12	0.17	0.00	0.00
0.16	0.30	0.00	0.00
0.20	0.45	0.00	0.00
0.24	0.59	0.01	0.00
0.28	0.74	0.03	0.00
0.32	0.89	0.06	0.00
0.36	1.02	0.11	0.01
0.40	1.14	0.15	0.02
0.44	1.24	0.19	0.05
0.48	1.33	0.23	0.10
0.52	1.42	0.27	0.16
0.56	1.50	0.32	0.24
0.60	1.58	0.36	0.34
0.64	1.66	0.40	0.44
0.68	1.74	0.45	0.54
0.72	1.81	0.49	0.64
0.76	1.88	0.53	0.74
0.80	1.95	0.57	0.82
0.84	2.01	0.61	0.90
0.88	2.07	0.65	0.96
0.92	2.13	0.69	1.02
0.96	2.18	0.72	1.06
1.00	2.23	0.75	1.10
1.04	2.27	0.78	1.12
1.08	2.32	0.81	1.14
1.12	2.36	0.84	**1.14**
1.16	2.40	0.87	1.14
1.20	2.43	0.90	1.13
1.24	2.47	0.92	1.12
1.28	2.50	0.95	1.10
1.32	2.54	0.97	1.07
1.36	2.58	1.00	1.05
1.40	2.61	1.02	1.02
1.44	2.64	1.04	0.99
1.48	2.67	1.07	0.96
1.52	2.70	1.08	0.93
1.56	2.72	1.10	0.91
1.60	2.74	1.12	0.88
1.64	2.76	1.13	0.86
1.68	2.78	1.15	0.83
1.72	2.80	1.16	0.80
1.76	2.82	1.17	0.78
1.80	2.83	1.19	0.75
1.84	2.85	1.20	0.71
1.88	2.87	1.21	0.68
1.92	2.89	1.23	0.65
1.96	2.90	1.24	0.62
2.00	2.92	1.25	0.59
2.04	2.94	1.27	0.56
2.08	2.96	1.28	0.54
2.12	2.98	1.29	0.51
2.16	2.99	1.31	0.50
2.20	3.01	1.32	0.48
2.24	3.03	1.34	0.47
2.28	3.05	1.35	0.46
2.32	3.06	1.36	0.45
2.36	3.08	1.38	0.44
2.40	3.10	1.39	0.44
2.44	3.12	1.40	0.43
2.48	3.14	1.42	0.43
2.52	3.15	1.43	0.43
2.56	3.17	1.45	0.43
2.60	3.19	1.46	0.42
2.64	3.20	1.47	0.42
2.68	3.21	1.48	0.42
2.72	3.22	1.49	0.42
2.76	3.23	1.49	0.42
2.80	3.24	1.50	0.41
2.84	3.25	1.51	0.40
2.88	3.26	1.51	0.39
2.92	3.27	1.52	0.38
2.96	3.28	1.53	0.37
3.00	**3.30**	**1.55**	0.35
3.04	3.30	1.55	0.34
3.08	3.30	1.55	0.32
3.12	3.30	1.55	0.31
3.16	3.30	1.55	0.30
3.20	3.30	1.55	0.28
3.24	3.30	1.55	0.27
3.28	3.30	1.55	0.25
3.32	3.30	1.55	0.23
3.36	3.30	1.55	0.21
3.40	3.30	1.55	0.19
3.44	3.30	1.55	0.17
3.48	3.30	1.55	0.14
3.52	3.30	1.55	0.12
3.56	3.30	1.55	0.10
3.60	3.30	1.55	0.08
3.64	3.30	1.55	0.07
3.68	3.30	1.55	0.06
3.72	3.30	1.55	0.05
3.76	3.30	1.55	0.04
3.80	3.30	1.55	0.03
3.84	3.30	1.55	0.03
3.88	3.30	1.55	0.02
3.92	3.30	1.55	0.02
3.96	3.30	1.55	0.02
4.00	3.30	1.55	0.01

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.60 cfs @ 0.80 hrs, Volume= 0.071 af, Depth= 1.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=3.30"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.04	0.02	0.00	0.00
0.08	0.08	0.00	0.00
0.12	0.17	0.00	0.00
0.16	0.30	0.00	0.00
0.20	0.45	0.00	0.00
0.24	0.59	0.01	0.00
0.28	0.74	0.03	0.01
0.32	0.89	0.06	0.07
0.36	1.02	0.11	0.18
0.40	1.14	0.15	0.32
0.44	1.24	0.19	0.44
0.48	1.33	0.23	0.51
0.52	1.42	0.27	0.55
0.56	1.50	0.32	0.56
0.60	1.58	0.36	0.56
0.64	1.66	0.40	0.57
0.68	1.74	0.45	0.58
0.72	1.81	0.49	0.59
0.76	1.88	0.53	0.60
0.80	1.95	0.57	**0.60**
0.84	2.01	0.61	0.60
0.88	2.07	0.65	0.59
0.92	2.13	0.69	0.57
0.96	2.18	0.72	0.54
1.00	2.23	0.75	0.52
1.04	2.27	0.78	0.49
1.08	2.32	0.81	0.47
1.12	2.36	0.84	0.45
1.16	2.40	0.87	0.44
1.20	2.43	0.90	0.42
1.24	2.47	0.92	0.40
1.28	2.50	0.95	0.38
1.32	2.54	0.97	0.37
1.36	2.58	1.00	0.36
1.40	2.61	1.02	0.36
1.44	2.64	1.04	0.35
1.48	2.67	1.07	0.34
1.52	2.70	1.08	0.33
1.56	2.72	1.10	0.31
1.60	2.74	1.12	0.29
1.64	2.76	1.13	0.27
1.68	2.78	1.15	0.25
1.72	2.80	1.16	0.23
1.76	2.82	1.17	0.21
1.80	2.83	1.19	0.20
1.84	2.85	1.20	0.19
1.88	2.87	1.21	0.19
1.92	2.89	1.23	0.19
1.96	2.90	1.24	0.19
2.00	2.92	1.25	0.19
2.04	2.94	1.27	0.19
2.08	2.96	1.28	0.19
2.12	2.98	1.29	0.19
2.16	2.99	1.31	0.19
2.20	3.01	1.32	0.19
2.24	3.03	1.34	0.19
2.28	3.05	1.35	0.19
2.32	3.06	1.36	0.19
2.36	3.08	1.38	0.19
2.40	3.10	1.39	0.19
2.44	3.12	1.40	0.19
2.48	3.14	1.42	0.19
2.52	3.15	1.43	0.19
2.56	3.17	1.45	0.19
2.60	3.19	1.46	0.19
2.64	3.20	1.47	0.19
2.68	3.21	1.48	0.18
2.72	3.22	1.49	0.16
2.76	3.23	1.49	0.14
2.80	3.24	1.50	0.13
2.84	3.25	1.51	0.11
2.88	3.26	1.51	0.11
2.92	3.27	1.52	0.10
2.96	3.28	1.53	0.11
3.00	**3.30**	**1.55**	0.12
3.04	3.30	1.55	0.13
3.08	3.30	1.55	0.13
3.12	3.30	1.55	0.09
3.16	3.30	1.55	0.05
3.20	3.30	1.55	0.03
3.24	3.30	1.55	0.01
3.28	3.30	1.55	0.01
3.32	3.30	1.55	0.00
3.36	3.30	1.55	0.00
3.40	3.30	1.55	0.00
3.44	3.30	1.55	0.00
3.48	3.30	1.55	0.00
3.52	3.30	1.55	0.00
3.56	3.30	1.55	0.00
3.60	3.30	1.55	0.00
3.64	3.30	1.55	0.00
3.68	3.30	1.55	0.00
3.72	3.30	1.55	0.00
3.76	3.30	1.55	0.00
3.80	3.30	1.55	0.00
3.84	3.30	1.55	0.00
3.88	3.30	1.55	0.00
3.92	3.30	1.55	0.00
3.96	3.30	1.55	0.00
4.00	3.30	1.55	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	12.24 cfs @	0.96 hrs, Volume=	1.427 af
Outflow	=	0.87 cfs @	3.40 hrs, Volume=	0.211 af, Atten= 93%, Lag= 146.3 min
Primary	=	0.87 cfs @	3.40 hrs, Volume=	0.211 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Peak Elev= 672.87' @ 3.40 hrs Surf.Area= 31,007 sf Storage= 54,236 cf

Plug-Flow detention time= 108.7 min calculated for 0.211 af (15% of inflow)
Center-of-Mass det. time= 56.4 min (148.8 - 92.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.87 cfs @ 3.40 hrs HW=672.87' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.87 cfs @ 7.89 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.10	0.00	0	670.00	0.00	0.00	0.00	0.00
0.20	0.00	0	670.00	0.00	0.00	0.00	0.00
0.30	0.08	3	670.00	0.00	0.00	0.00	0.00
0.40	1.08	134	670.01	0.00	0.00	0.00	0.00
0.50	3.21	800	670.09	0.02	0.02	0.00	0.00
0.60	5.71	2,302	670.26	0.14	0.14	0.00	0.00
0.70	7.55	4,574	670.49	0.29	0.29	0.00	0.00
0.80	11.10	7,691	670.78	0.41	0.41	0.00	0.00
0.90	**12.12**	11,729	670.97	0.47	0.47	0.00	0.00
1.00	**12.19**	15,946	671.17	0.53	0.53	0.00	0.00
1.10	11.68	20,077	671.36	0.58	0.58	0.00	0.00
1.20	10.84	23,951	671.53	0.62	0.62	0.00	0.00
1.30	9.90	27,491	671.68	0.65	0.65	0.00	0.00
1.40	9.01	30,683	671.83	0.68	0.68	0.00	0.00
1.50	8.29	33,568	671.96	0.71	0.71	0.00	0.00
1.60	7.65	36,204	672.07	0.73	0.73	0.00	0.00
1.70	6.86	38,586	672.18	0.75	0.75	0.00	0.00
1.80	5.87	40,644	672.27	0.77	0.77	0.00	0.00
1.90	4.93	42,339	672.34	0.78	0.78	0.00	0.00
2.00	4.25	43,725	672.40	0.79	0.79	0.00	0.00
2.10	3.86	44,905	672.46	0.80	0.80	0.00	0.00
2.20	3.64	45,969	672.50	0.81	0.81	0.00	0.00
2.30	3.53	46,968	672.55	0.82	0.82	0.00	0.00
2.40	3.47	47,933	672.59	0.82	0.82	0.00	0.00
2.50	3.45	48,882	672.63	0.83	0.83	0.00	0.00
2.60	3.45	49,823	672.67	0.84	0.84	0.00	0.00
2.70	3.41	50,759	672.71	0.85	0.85	0.00	0.00
2.80	3.19	51,656	672.75	0.85	0.85	0.00	0.00
2.90	2.73	52,435	672.79	0.86	0.86	0.00	0.00
3.00	2.26	53,034	672.82	0.86	0.86	0.00	0.00
3.10	2.03	53,501	672.84	0.87	0.87	0.00	0.00
3.20	1.77	53,885	672.85	0.87	0.87	0.00	0.00
3.30	1.31	54,148	672.87	0.87	0.87	0.00	0.00
3.40	0.82	**54,236**	**672.87**	**0.87**	**0.87**	0.00	0.00
3.50	0.49	54,165	672.87	0.87	0.87	0.00	0.00
3.60	0.32	54,000	672.86	0.87	0.87	0.00	0.00
3.70	0.22	53,786	672.85	0.87	0.87	0.00	0.00
3.80	0.17	53,545	672.84	0.87	0.87	0.00	0.00
3.90	0.14	53,289	672.83	0.86	0.86	0.00	0.00
4.00	0.00	53,026	672.82	0.86	0.86	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	5.10 cfs @	0.92 hrs,	Volume=	0.648 af
Outflow	=	5.09 cfs @	0.95 hrs,	Volume=	0.639 af, Atten= 0%, Lag= 2.1 min
Primary	=	1.81 cfs @	0.95 hrs,	Volume=	0.340 af
Secondary	=	3.28 cfs @	0.95 hrs,	Volume=	0.299 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Peak Elev= 678.09' @ 0.95 hrs Surf.Area= 3,264 sf Storage= 3,525 cf

Plug-Flow detention time= 19.3 min calculated for 0.639 af (99% of inflow)
Center-of-Mass det. time= 17.8 min (108.4 - 90.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.81 cfs @ 0.95 hrs HW=678.09' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.27 cfs @ 5.53 fps)
└—**2=Sharp-Crested Rectangular Weir** (Weir Controls 0.54 cfs @ 0.99 fps)


Secondary OutFlow Max=3.28 cfs @ 0.95 hrs HW=678.09' TW=671.08' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.13 cfs @ 10.25 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 3.15 cfs @ 1.82 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.10	0.00	0	670.75	0.00	0.00	0.00	0.00
0.20	0.00	0	670.75	0.00	0.00	0.00	0.00
0.30	0.08	4	671.01	0.00	0.00	0.00	0.00
0.40	0.95	114	676.62	0.15	0.04	0.10	0.00
0.50	2.67	581	676.99	0.63	0.52	0.11	0.00
0.60	3.89	1,464	677.37	0.98	0.86	0.12	0.00
0.70	4.50	2,569	677.78	1.24	1.12	0.12	0.00
0.80	4.89	3,409	678.05	4.20	1.51	2.70	0.00
0.90	**5.09**	**3,519**	**678.09**	**5.04**	**1.79**	**3.24**	0.00
1.00	**5.00**	**3,521**	**678.09**	**5.06**	**1.80**	**3.26**	0.00
1.10	4.69	3,490	678.08	4.81	1.71	3.10	0.00
1.20	4.33	3,445	678.07	4.47	1.59	2.87	0.00
1.30	3.95	3,394	678.05	4.10	1.47	2.63	0.00
1.40	3.62	3,341	678.03	3.75	1.37	2.38	0.00
1.50	3.39	3,299	678.02	3.49	1.30	2.19	0.00
1.60	3.14	3,260	678.01	3.27	1.25	2.02	0.00
1.70	2.78	3,201	677.99	2.99	1.22	1.77	0.00
1.80	2.38	3,116	677.96	2.64	1.21	1.42	0.00
1.90	2.07	3,027	677.93	2.29	1.20	1.10	0.00
2.00	1.89	2,957	677.91	2.04	1.18	0.86	0.00
2.10	1.79	2,911	677.90	1.89	1.18	0.71	0.00
2.20	1.74	2,882	677.89	1.80	1.17	0.63	0.00
2.30	1.71	2,865	677.88	1.75	1.17	0.58	0.00
2.40	1.70	2,855	677.88	1.72	1.17	0.55	0.00
2.50	1.70	2,850	677.88	1.70	1.17	0.54	0.00
2.60	1.70	2,848	677.88	1.70	1.17	0.53	0.00
2.70	1.67	2,846	677.87	1.69	1.17	0.53	0.00
2.80	1.51	2,825	677.87	1.63	1.16	0.47	0.00
2.90	1.26	2,764	677.85	1.48	1.15	0.33	0.00
3.00	1.12	2,685	677.82	1.32	1.14	0.18	0.00
3.10	1.12	2,626	677.80	1.25	1.13	0.12	0.00
3.20	0.87	2,556	677.78	1.23	1.11	0.12	0.00
3.30	0.50	2,375	677.71	1.20	1.08	0.12	0.00
3.40	0.29	2,098	677.62	1.14	1.02	0.12	0.00
3.50	0.17	1,785	677.50	1.06	0.95	0.12	0.00
3.60	0.10	1,464	677.38	0.98	0.86	0.12	0.00
3.70	0.06	1,155	677.25	0.88	0.77	0.11	0.00
3.80	0.04	871	677.12	0.77	0.66	0.11	0.00
3.90	0.02	621	677.01	0.65	0.54	0.11	0.00
4.00	0.00	414	676.90	0.49	0.39	0.11	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 2.85 cfs @ 0.98 hrs, Volume= 0.631 af, Depth= 2.17"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=3.86"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.08	0.00	0.00
0.30	0.31	0.00	0.00
0.45	0.63	0.02	0.02
0.60	0.96	0.11	0.62
0.75	1.25	0.25	1.92
0.90	1.48	0.37	**2.75**
1.05	1.67	0.48	**2.81**
1.20	1.85	0.60	2.71
1.35	2.02	0.71	2.71
1.50	2.18	0.82	2.69
1.65	2.33	0.93	2.64
1.80	2.46	1.02	2.49
1.95	2.57	1.11	2.25
2.10	2.67	1.19	2.05
2.25	2.76	1.26	1.88
2.40	2.85	1.32	1.72
2.55	2.92	1.39	1.57
2.70	3.00	1.45	1.49
2.85	3.08	1.51	1.47
3.00	3.14	1.56	1.39
3.15	3.19	1.60	1.24
3.30	3.24	1.64	1.06
3.45	3.28	1.67	0.89
3.60	3.31	1.70	0.79
3.75	3.35	1.74	0.77
3.90	3.39	1.77	0.76
4.05	3.43	1.80	0.76
4.20	3.47	1.83	0.77
4.35	3.51	1.87	0.77
4.50	3.55	1.90	0.77
4.65	3.59	1.93	0.77
4.80	3.63	1.97	0.78
4.95	3.67	2.00	0.78
5.10	3.70	2.03	0.78
5.25	3.74	2.06	0.77
5.40	3.76	2.08	0.68
5.55	3.78	2.10	0.52
5.70	3.80	2.11	0.43
5.85	3.83	2.14	0.41
6.00	**3.86**	**2.17**	0.50
6.15	3.86	2.17	0.51
6.30	3.86	2.17	0.18
6.45	3.86	2.17	0.05
6.60	3.86	2.17	0.01
6.75	3.86	2.17	0.00
6.90	3.86	2.17	0.00
7.05	3.86	2.17	0.00
7.20	3.86	2.17	0.00
7.35	3.86	2.17	0.00
7.50	3.86	2.17	0.00
7.65	3.86	2.17	0.00
7.80	3.86	2.17	0.00
7.95	3.86	2.17	0.00

Summary for Subcatchment 7S: South Property


Runoff = 5.78 cfs @ 1.48 hrs, Volume= 1.353 af, Depth= 2.17"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=3.86"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.08	0.00	0.00
0.30	0.31	0.00	0.00
0.45	0.63	0.02	0.01
0.60	0.96	0.11	0.50
0.75	1.25	0.25	2.33
0.90	1.48	0.37	4.51
1.05	1.67	0.48	5.60
1.20	1.85	0.60	5.76
1.35	2.02	0.71	**5.76**
1.50	2.18	0.82	**5.78**
1.65	2.33	0.93	5.73
1.80	2.46	1.02	5.55
1.95	2.57	1.11	5.18
2.10	2.67	1.19	4.72
2.25	2.76	1.26	4.32
2.40	2.85	1.32	3.97
2.55	2.92	1.39	3.63
2.70	3.00	1.45	3.36
2.85	3.08	1.51	3.22
3.00	3.14	1.56	3.11
3.15	3.19	1.60	2.87
3.30	3.24	1.64	2.54
3.45	3.28	1.67	2.18
3.60	3.31	1.70	1.88
3.75	3.35	1.74	1.73
3.90	3.39	1.77	1.67
4.05	3.43	1.80	1.65
4.20	3.47	1.83	1.64
4.35	3.51	1.87	1.64
4.50	3.55	1.90	1.65
4.65	3.59	1.93	1.65
4.80	3.63	1.97	1.66
4.95	3.67	2.00	1.66
5.10	3.70	2.03	1.67
5.25	3.74	2.06	1.66
5.40	3.76	2.08	1.58
5.55	3.78	2.10	1.35
5.70	3.80	2.11	1.08
5.85	3.83	2.14	0.94
6.00	**3.86**	**2.17**	0.97
6.15	3.86	2.17	1.10
6.30	3.86	2.17	0.78
6.45	3.86	2.17	0.33
6.60	3.86	2.17	0.13
6.75	3.86	2.17	0.05
6.90	3.86	2.17	0.02
7.05	3.86	2.17	0.01
7.20	3.86	2.17	0.00
7.35	3.86	2.17	0.00
7.50	3.86	2.17	0.00
7.65	3.86	2.17	0.00
7.80	3.86	2.17	0.00
7.95	3.86	2.17	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.84 cfs @ 1.71 hrs, Volume= 0.200 af, Depth= 2.00"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=3.86"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.08	0.00	0.00
0.30	0.31	0.00	0.00
0.45	0.63	0.01	0.00
0.60	0.96	0.08	0.02
0.75	1.25	0.20	0.13
0.90	1.48	0.31	0.36
1.05	1.67	0.41	0.60
1.20	1.85	0.51	0.73
1.35	2.02	0.62	0.79
1.50	2.18	0.72	0.82
1.65	2.33	0.82	**0.83**
1.80	2.46	0.91	**0.83**
1.95	2.57	0.99	0.81
2.10	2.67	1.07	0.76
2.25	2.76	1.13	0.70
2.40	2.85	1.20	0.65
2.55	2.92	1.26	0.60
2.70	3.00	1.32	0.55
2.85	3.08	1.37	0.52
3.00	3.14	1.42	0.49
3.15	3.19	1.46	0.47
3.30	3.24	1.50	0.43
3.45	3.28	1.53	0.38
3.60	3.31	1.56	0.33
3.75	3.35	1.59	0.29
3.90	3.39	1.62	0.27
4.05	3.43	1.65	0.26
4.20	3.47	1.68	0.26
4.35	3.51	1.72	0.25
4.50	3.55	1.75	0.25
4.65	3.59	1.78	0.25
4.80	3.63	1.81	0.25
4.95	3.67	1.84	0.26
5.10	3.70	1.88	0.26
5.25	3.74	1.90	0.26
5.40	3.76	1.92	0.25
5.55	3.78	1.94	0.23
5.70	3.80	1.96	0.20
5.85	3.83	1.98	0.17
6.00	**3.86**	**2.00**	0.15
6.15	3.86	2.00	0.16
6.30	3.86	2.00	0.15
6.45	3.86	2.00	0.10
6.60	3.86	2.00	0.05
6.75	3.86	2.00	0.03
6.90	3.86	2.00	0.01
7.05	3.86	2.00	0.01
7.20	3.86	2.00	0.00
7.35	3.86	2.00	0.00
7.50	3.86	2.00	0.00
7.65	3.86	2.00	0.00
7.80	3.86	2.00	0.00
7.95	3.86	2.00	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.41 cfs @ 0.88 hrs, Volume= 0.092 af, Depth= 2.00"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=3.86"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.15	0.08	0.00	0.00
0.30	0.31	0.00	0.00
0.45	0.63	0.01	0.01
0.60	0.96	0.08	0.17
0.75	1.25	0.20	**0.37**
0.90	1.48	0.31	**0.41**
1.05	1.67	0.41	0.38
1.20	1.85	0.51	0.39
1.35	2.02	0.62	0.39
1.50	2.18	0.72	0.39
1.65	2.33	0.82	0.38
1.80	2.46	0.91	0.34
1.95	2.57	0.99	0.31
2.10	2.67	1.07	0.29
2.25	2.76	1.13	0.26
2.40	2.85	1.20	0.24
2.55	2.92	1.26	0.22
2.70	3.00	1.32	0.22
2.85	3.08	1.37	0.22
3.00	3.14	1.42	0.19
3.15	3.19	1.46	0.17
3.30	3.24	1.50	0.14
3.45	3.28	1.53	0.12
3.60	3.31	1.56	0.11
3.75	3.35	1.59	0.11
3.90	3.39	1.62	0.12
4.05	3.43	1.65	0.12
4.20	3.47	1.68	0.12
4.35	3.51	1.72	0.12
4.50	3.55	1.75	0.12
4.65	3.59	1.78	0.12
4.80	3.63	1.81	0.12
4.95	3.67	1.84	0.12
5.10	3.70	1.88	0.12
5.25	3.74	1.90	0.11
5.40	3.76	1.92	0.09
5.55	3.78	1.94	0.06
5.70	3.80	1.96	0.06
5.85	3.83	1.98	0.07
6.00	**3.86**	**2.00**	0.09
6.15	3.86	2.00	0.04
6.30	3.86	2.00	0.00
6.45	3.86	2.00	0.00
6.60	3.86	2.00	0.00
6.75	3.86	2.00	0.00
6.90	3.86	2.00	0.00
7.05	3.86	2.00	0.00
7.20	3.86	2.00	0.00
7.35	3.86	2.00	0.00
7.50	3.86	2.00	0.00
7.65	3.86	2.00	0.00
7.80	3.86	2.00	0.00
7.95	3.86	2.00	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	8.37 cfs @	1.49 hrs, Volume=	1.762 af
Outflow	=	0.92 cfs @	6.31 hrs, Volume=	0.481 af, Atten= 89%, Lag= 289.4 min
Primary	=	0.92 cfs @	6.31 hrs, Volume=	0.481 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Peak Elev= 673.16' @ 6.31 hrs Surf.Area= 31,073 sf Storage= 60,610 cf

Plug-Flow detention time= 213.0 min calculated for 0.479 af (27% of inflow)
Center-of-Mass det. time= 127.6 min (284.5 - 156.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.92 cfs @ 6.31 hrs HW=673.16' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.92 cfs @ 8.30 fps)

Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)


Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Pond 3P: Southeast Chambers




Pond 3P: Southeast Chambers

Stage-Discharge



Pond 3P: Southeast Chambers

Stage-Area-Storage



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.30	0.00	0	670.00	0.00	0.00	0.00	0.00
0.60	0.77	102	670.01	0.00	0.00	0.00	0.00
0.90	5.04	2,892	670.32	0.20	0.20	0.00	0.00
1.20	8.19	9,460	670.86	0.44	0.44	0.00	0.00
1.50	**8.37**	17,912	671.26	0.55	0.55	0.00	0.00
1.80	8.01	26,224	671.63	0.64	0.64	0.00	0.00
2.10	6.69	33,557	671.96	0.71	0.71	0.00	0.00
2.40	5.48	39,382	672.21	0.76	0.76	0.00	0.00
2.70	4.49	43,935	672.41	0.79	0.79	0.00	0.00
3.00	4.06	47,701	672.58	0.82	0.82	0.00	0.00
3.30	3.15	50,789	672.72	0.85	0.85	0.00	0.00
3.60	2.14	52,737	672.80	0.86	0.86	0.00	0.00
3.90	1.90	53,956	672.86	0.87	0.87	0.00	0.00
4.20	1.88	55,052	672.91	0.88	0.88	0.00	0.00
4.50	1.88	56,132	672.96	0.88	0.88	0.00	0.00
4.80	1.89	57,211	673.00	0.89	0.89	0.00	0.00
5.10	1.90	58,293	673.05	0.90	0.90	0.00	0.00
5.40	1.79	59,351	673.10	0.91	0.91	0.00	0.00
5.70	1.26	60,044	673.13	0.91	0.91	0.00	0.00
6.00	1.18	60,311	673.15	0.91	0.91	0.00	0.00
6.30	0.90	**60,610**	**673.16**	**0.92**	**0.92**	0.00	0.00
6.60	0.24	60,182	673.14	0.91	0.91	0.00	0.00
6.90	0.12	59,382	673.10	0.91	0.91	0.00	0.00
7.20	0.01	58,482	673.06	0.90	0.90	0.00	0.00
7.50	0.00	57,514	673.02	0.89	0.89	0.00	0.00
7.80	0.00	56,552	672.97	0.89	0.89	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)
670.00	0
670.10	893
670.20	1,787
670.30	2,681
670.40	3,618
670.50	4,626
670.60	5,639
670.70	6,653
670.80	8,202
670.90	10,288
671.00	12,379
671.10	14,465
671.20	16,635
671.30	18,830
671.40	21,049
671.50	23,322
671.60	25,582
671.70	27,830
671.80	30,075
671.90	32,317
672.00	34,546
672.10	36,761
672.20	39,047
672.30	41,344
672.40	43,628
672.50	45,906
672.60	48,170
672.70	50,428
672.80	52,674
672.90	54,899
673.00	57,117
673.10	59,314
673.20	61,492
673.30	63,654
673.40	65,789
673.50	67,899
673.60	69,981
673.70	72,030
673.80	74,047
673.90	76,023
674.00	77,955
674.10	79,844
674.20	81,679
674.30	83,453
674.40	85,139
674.50	86,709
674.60	88,153
674.70	89,496
674.80	90,763
674.90	91,997
675.00	93,215
675.10	94,422
675.20	95,621
675.30	96,808
675.40	97,984
675.50	99,158
675.60	100,327
675.70	101,491
675.80	102,865
675.90	104,433
676.00	105,977
676.10	107,509
676.20	109,032
676.30	110,542
676.40	112,038
676.50	113,523
676.60	114,993
676.70	116,452
676.80	117,901
676.90	119,339
677.00	120,753
677.10	122,143
677.20	123,511
677.30	124,850
677.40	126,157
677.50	127,426
677.60	128,644
677.70	129,794
677.80	130,846
677.90	131,802
678.00	132,704
678.10	133,604
678.20	134,505
678.30	135,406
678.40	136,307
678.50	137,209
678.60	138,112
678.70	139,014
678.80	139,917
678.90	**140,821**

Summary for Pond 8P: North System

Inflow	=	3.51 cfs @	1.48 hrs,	Volume=	0.832 af
Outflow	=	3.51 cfs @	1.53 hrs,	Volume=	0.831 af, Atten= 0%, Lag= 2.9 min
Primary	=	1.30 cfs @	1.53 hrs,	Volume=	0.515 af
Secondary	=	2.21 cfs @	1.53 hrs,	Volume=	0.317 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Peak Elev= 678.02' @ 1.53 hrs Surf.Area= 3,195 sf Storage= 3,302 cf

Plug-Flow detention time= 22.9 min calculated for 0.831 af (100% of inflow)
Center-of-Mass det. time= 22.6 min (181.3 - 158.8)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.30 cfs @ 1.53 hrs HW=678.02' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.24 cfs @ 5.38 fps)
└—**2=Sharp-Crested Rectangular Weir** (Weir Controls 0.06 cfs @ 0.48 fps)


Secondary OutFlow Max=2.21 cfs @ 1.53 hrs HW=678.02' TW=671.30' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 10.17 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 2.08 cfs @ 1.58 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.30	0.00	0	670.75	0.00	0.00	0.00	0.00
0.60	0.64	92	676.56	0.11	0.01	0.10	0.00
0.90	3.11	1,518	677.40	0.99	0.88	0.12	0.00
1.20	**3.44**	3,267	678.01	3.31	1.26	2.05	0.00
1.50	**3.51**	**3,302**	**678.02**	**3.51**	**1.30**	**2.21**	0.00
1.80	3.33	**3,281**	**678.01**	**3.39**	**1.27**	**2.12**	0.00
2.10	2.80	3,181	677.98	2.91	1.22	1.69	0.00
2.40	2.37	3,074	677.95	2.47	1.20	1.27	0.00
2.70	2.04	2,973	677.92	2.10	1.19	0.91	0.00
3.00	1.88	2,927	677.90	1.94	1.18	0.76	0.00
3.30	1.49	2,822	677.87	1.62	1.16	0.46	0.00
3.60	1.12	2,655	677.81	1.28	1.13	0.15	0.00
3.90	1.03	2,470	677.75	1.22	1.10	0.12	0.00
4.20	1.02	2,282	677.68	1.18	1.06	0.12	0.00
4.50	1.02	2,130	677.63	1.15	1.03	0.12	0.00
4.80	1.03	2,014	677.59	1.12	1.00	0.12	0.00
5.10	1.04	1,929	677.55	1.10	0.98	0.12	0.00
5.40	0.93	1,848	677.52	1.08	0.96	0.12	0.00
5.70	0.63	1,555	677.41	1.00	0.89	0.12	0.00
6.00	0.65	1,176	677.26	0.89	0.77	0.11	0.00
6.30	0.33	919	677.14	0.79	0.68	0.11	0.00
6.60	0.06	385	676.88	0.47	0.36	0.11	0.00
6.90	0.01	103	676.60	0.13	0.03	0.10	0.00
7.20	0.00	39	673.55	0.00	0.00	0.00	0.00
7.50	0.00	39	673.53	0.00	0.00	0.00	0.00
7.80	0.00	39	673.51	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 2.23 cfs @ 5.46 hrs, Volume= 0.790 af, Depth= 2.71"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=4.48"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.03	0.00	0.00
0.60	0.07	0.00	0.00
0.80	0.12	0.00	0.00
1.00	0.18	0.00	0.00
1.20	0.25	0.00	0.00
1.40	0.32	0.00	0.00
1.60	0.39	0.00	0.00
1.80	0.45	0.00	0.00
2.00	0.51	0.00	0.03
2.20	0.57	0.01	0.09
2.40	0.63	0.02	0.14
2.60	0.70	0.04	0.19
2.80	0.77	0.06	0.27
3.00	0.86	0.08	0.37
3.20	0.95	0.11	0.49
3.40	1.05	0.15	0.60
3.60	1.15	0.20	0.72
3.80	1.27	0.25	0.84
4.00	1.40	0.32	1.02
4.20	1.54	0.40	1.25
4.40	1.69	0.50	1.49
4.60	1.86	0.60	1.71
4.80	2.04	0.72	1.93
5.00	2.21	0.85	2.13
5.20	2.39	0.97	2.21
5.40	2.56	1.10	**2.23**
5.60	2.72	1.22	**2.22**
5.80	2.86	1.33	2.10
6.00	2.99	1.44	1.94
6.20	3.10	1.53	1.77
6.40	3.21	1.62	1.62
6.60	3.30	1.69	1.49
6.80	3.39	1.77	1.37
7.00	3.47	1.84	1.28
7.20	3.55	1.90	1.21
7.40	3.63	1.96	1.14
7.60	3.69	2.02	1.07
7.80	3.76	2.08	1.00
8.00	3.81	2.13	0.93
8.20	3.87	2.17	0.86
8.40	3.91	2.21	0.78
8.60	3.96	2.25	0.72
8.80	4.00	2.29	0.70
9.00	4.05	2.33	0.69
9.20	4.09	2.37	0.69
9.40	4.13	2.40	0.63
9.60	4.16	2.43	0.56
9.80	4.19	2.45	0.49
10.00	4.22	2.48	0.47
10.20	4.25	2.51	0.47
10.40	4.28	2.53	0.47
10.60	4.31	2.56	0.47
10.80	4.34	2.59	0.47
11.00	4.37	2.61	0.46
11.20	4.39	2.63	0.41
11.40	4.41	2.65	0.33
11.60	4.43	2.66	0.27
11.80	4.45	2.68	0.30
12.00	**4.48**	**2.71**	0.37
12.20	4.48	2.71	0.27
12.40	4.48	2.71	0.05
12.60	4.48	2.71	0.01
12.80	4.48	2.71	0.00
13.00	4.48	2.71	0.00
13.20	4.48	2.71	0.00
13.40	4.48	2.71	0.00
13.60	4.48	2.71	0.00
13.80	4.48	2.71	0.00
14.00	4.48	2.71	0.00
14.20	4.48	2.71	0.00
14.40	4.48	2.71	0.00
14.60	4.48	2.71	0.00
14.80	4.48	2.71	0.00
15.00	4.48	2.71	0.00

Summary for Subcatchment 7S: South Property


Runoff = 4.77 cfs @ 5.56 hrs, Volume= 1.692 af, Depth= 2.71"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=4.48"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.03	0.00	0.00
0.60	0.07	0.00	0.00
0.80	0.12	0.00	0.00
1.00	0.18	0.00	0.00
1.20	0.25	0.00	0.00
1.40	0.32	0.00	0.00
1.60	0.39	0.00	0.00
1.80	0.45	0.00	0.00
2.00	0.51	0.00	0.03
2.20	0.57	0.01	0.12
2.40	0.63	0.02	0.23
2.60	0.70	0.04	0.34
2.80	0.77	0.06	0.48
3.00	0.86	0.08	0.67
3.20	0.95	0.11	0.90
3.40	1.05	0.15	1.15
3.60	1.15	0.20	1.39
3.80	1.27	0.25	1.64
4.00	1.40	0.32	1.97
4.20	1.54	0.40	2.40
4.40	1.69	0.50	2.89
4.60	1.86	0.60	3.38
4.80	2.04	0.72	3.85
5.00	2.21	0.85	4.31
5.20	2.39	0.97	4.61
5.40	2.56	1.10	**4.74**
5.60	2.72	1.22	**4.76**
5.80	2.86	1.33	4.63
6.00	2.99	1.44	4.35
6.20	3.10	1.53	4.00
6.40	3.21	1.62	3.66
6.60	3.30	1.69	3.37
6.80	3.39	1.77	3.08
7.00	3.47	1.84	2.85
7.20	3.55	1.90	2.69
7.40	3.63	1.96	2.53
7.60	3.69	2.02	2.38
7.80	3.76	2.08	2.23
8.00	3.81	2.13	2.08
8.20	3.87	2.17	1.93
8.40	3.91	2.21	1.77
8.60	3.96	2.25	1.62
8.80	4.00	2.29	1.52
9.00	4.05	2.33	1.50
9.20	4.09	2.37	1.48
9.40	4.13	2.40	1.42
9.60	4.16	2.43	1.29
9.80	4.19	2.45	1.14
10.00	4.22	2.48	1.04
10.20	4.25	2.51	1.01
10.40	4.28	2.53	1.00
10.60	4.31	2.56	1.00
10.80	4.34	2.59	1.00
11.00	4.37	2.61	1.00
11.20	4.39	2.63	0.93
11.40	4.41	2.65	0.80
11.60	4.43	2.66	0.66
11.80	4.45	2.68	0.62
12.00	**4.48**	**2.71**	0.73
12.20	4.48	2.71	0.73
12.40	4.48	2.71	0.31
12.60	4.48	2.71	0.09
12.80	4.48	2.71	0.03
13.00	4.48	2.71	0.01
13.20	4.48	2.71	0.00
13.40	4.48	2.71	0.00
13.60	4.48	2.71	0.00
13.80	4.48	2.71	0.00
14.00	4.48	2.71	0.00
14.20	4.48	2.71	0.00
14.40	4.48	2.71	0.00
14.60	4.48	2.71	0.00
14.80	4.48	2.71	0.00
15.00	4.48	2.71	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.71 cfs @ 5.69 hrs, Volume= 0.253 af, Depth= 2.53"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=4.48"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.03	0.00	0.00
0.60	0.07	0.00	0.00
0.80	0.12	0.00	0.00
1.00	0.18	0.00	0.00
1.20	0.25	0.00	0.00
1.40	0.32	0.00	0.00
1.60	0.39	0.00	0.00
1.80	0.45	0.00	0.00
2.00	0.51	0.00	0.00
2.20	0.57	0.00	0.00
2.40	0.63	0.01	0.01
2.60	0.70	0.02	0.02
2.80	0.77	0.04	0.04
3.00	0.86	0.06	0.06
3.20	0.95	0.08	0.09
3.40	1.05	0.12	0.13
3.60	1.15	0.15	0.16
3.80	1.27	0.20	0.20
4.00	1.40	0.26	0.24
4.20	1.54	0.33	0.30
4.40	1.69	0.42	0.37
4.60	1.86	0.52	0.44
4.80	2.04	0.63	0.52
5.00	2.21	0.74	0.59
5.20	2.39	0.86	0.65
5.40	2.56	0.98	0.69
5.60	2.72	1.10	**0.71**
5.80	2.86	1.21	**0.71**
6.00	2.99	1.30	0.68
6.20	3.10	1.39	0.64
6.40	3.21	1.48	0.59
6.60	3.30	1.55	0.55
6.80	3.39	1.62	0.50
7.00	3.47	1.69	0.46
7.20	3.55	1.75	0.43
7.40	3.63	1.81	0.41
7.60	3.69	1.87	0.38
7.80	3.76	1.92	0.36
8.00	3.81	1.97	0.34
8.20	3.87	2.01	0.31
8.40	3.91	2.05	0.29
8.60	3.96	2.09	0.27
8.80	4.00	2.13	0.25
9.00	4.05	2.16	0.24
9.20	4.09	2.20	0.23
9.40	4.13	2.23	0.23
9.60	4.16	2.26	0.21
9.80	4.19	2.29	0.19
10.00	4.22	2.31	0.17
10.20	4.25	2.34	0.16
10.40	4.28	2.36	0.16
10.60	4.31	2.39	0.16
10.80	4.34	2.41	0.16
11.00	4.37	2.44	0.16
11.20	4.39	2.46	0.15
11.40	4.41	2.47	0.14
11.60	4.43	2.49	0.12
11.80	4.45	2.51	0.10
12.00	**4.48**	**2.53**	0.11
12.20	4.48	2.53	0.12
12.40	4.48	2.53	0.08
12.60	4.48	2.53	0.04
12.80	4.48	2.53	0.01
13.00	4.48	2.53	0.01
13.20	4.48	2.53	0.00
13.40	4.48	2.53	0.00
13.60	4.48	2.53	0.00
13.80	4.48	2.53	0.00
14.00	4.48	2.53	0.00
14.20	4.48	2.53	0.00
14.40	4.48	2.53	0.00
14.60	4.48	2.53	0.00
14.80	4.48	2.53	0.00
15.00	4.48	2.53	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.33 cfs @ 5.44 hrs, Volume= 0.116 af, Depth= 2.53"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=4.48"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.20	0.01	0.00	0.00
0.40	0.03	0.00	0.00
0.60	0.07	0.00	0.00
0.80	0.12	0.00	0.00
1.00	0.18	0.00	0.00
1.20	0.25	0.00	0.00
1.40	0.32	0.00	0.00
1.60	0.39	0.00	0.00
1.80	0.45	0.00	0.00
2.00	0.51	0.00	0.00
2.20	0.57	0.00	0.01
2.40	0.63	0.01	0.02
2.60	0.70	0.02	0.02
2.80	0.77	0.04	0.04
3.00	0.86	0.06	0.05
3.20	0.95	0.08	0.07
3.40	1.05	0.12	0.09
3.60	1.15	0.15	0.10
3.80	1.27	0.20	0.13
4.00	1.40	0.26	0.16
4.20	1.54	0.33	0.19
4.40	1.69	0.42	0.23
4.60	1.86	0.52	0.26
4.80	2.04	0.63	0.30
5.00	2.21	0.74	0.32
5.20	2.39	0.86	0.33
5.40	2.56	0.98	**0.33**
5.60	2.72	1.10	**0.32**
5.80	2.86	1.21	0.30
6.00	2.99	1.30	0.28
6.20	3.10	1.39	0.25
6.40	3.21	1.48	0.23
6.60	3.30	1.55	0.21
6.80	3.39	1.62	0.20
7.00	3.47	1.69	0.19
7.20	3.55	1.75	0.18
7.40	3.63	1.81	0.17
7.60	3.69	1.87	0.16
7.80	3.76	1.92	0.15
8.00	3.81	1.97	0.14
8.20	3.87	2.01	0.12
8.40	3.91	2.05	0.11
8.60	3.96	2.09	0.11
8.80	4.00	2.13	0.11
9.00	4.05	2.16	0.11
9.20	4.09	2.20	0.10
9.40	4.13	2.23	0.09
9.60	4.16	2.26	0.08
9.80	4.19	2.29	0.07
10.00	4.22	2.31	0.07
10.20	4.25	2.34	0.07
10.40	4.28	2.36	0.07
10.60	4.31	2.39	0.07
10.80	4.34	2.41	0.07
11.00	4.37	2.44	0.07
11.20	4.39	2.46	0.06
11.40	4.41	2.47	0.04
11.60	4.43	2.49	0.04
11.80	4.45	2.51	0.05
12.00	**4.48**	**2.53**	0.06
12.20	4.48	2.53	0.01
12.40	4.48	2.53	0.00
12.60	4.48	2.53	0.00
12.80	4.48	2.53	0.00
13.00	4.48	2.53	0.00
13.20	4.48	2.53	0.00
13.40	4.48	2.53	0.00
13.60	4.48	2.53	0.00
13.80	4.48	2.53	0.00
14.00	4.48	2.53	0.00
14.20	4.48	2.53	0.00
14.40	4.48	2.53	0.00
14.60	4.48	2.53	0.00
14.80	4.48	2.53	0.00
15.00	4.48	2.53	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	6.80 cfs @	5.56 hrs, Volume=	2.155 af
Outflow	=	0.97 cfs @	11.40 hrs, Volume=	0.802 af, Atten= 86%, Lag= 350.8 min
Primary	=	0.97 cfs @	11.40 hrs, Volume=	0.802 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Peak Elev= 673.51' @ 11.40 hrs Surf.Area= 31,152 sf Storage= 68,010 cf

Plug-Flow detention time= 309.1 min calculated for 0.802 af (37% of inflow)
Center-of-Mass det. time= 190.9 min (588.1 - 397.2)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.97 cfs @ 11.40 hrs HW=673.51' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.97 cfs @ 8.77 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.40	0.00	0	670.00	0.00	0.00	0.00	0.00
0.80	0.00	0	670.00	0.00	0.00	0.00	0.00
1.20	0.00	0	670.00	0.00	0.00	0.00	0.00
1.60	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.04	7	670.00	0.00	0.00	0.00	0.00
2.40	0.35	235	670.03	0.00	0.00	0.00	0.00
2.80	0.62	885	670.10	0.03	0.03	0.00	0.00
3.20	1.08	1,977	670.22	0.11	0.11	0.00	0.00
3.60	1.61	3,628	670.40	0.25	0.25	0.00	0.00
4.00	2.24	5,888	670.62	0.35	0.35	0.00	0.00
4.40	3.24	9,164	670.85	0.43	0.43	0.00	0.00
4.80	5.16	14,035	671.08	0.50	0.50	0.00	0.00
5.20	**6.55**	21,767	671.43	0.59	0.59	0.00	0.00
5.60	**6.80**	30,523	671.82	0.68	0.68	0.00	0.00
6.00	6.10	38,949	672.20	0.75	0.75	0.00	0.00
6.40	4.98	45,875	672.50	0.81	0.81	0.00	0.00
6.80	4.04	51,231	672.74	0.85	0.85	0.00	0.00
7.20	3.39	55,335	672.92	0.88	0.88	0.00	0.00
7.60	2.89	58,607	673.07	0.90	0.90	0.00	0.00
8.00	2.41	61,150	673.18	0.92	0.92	0.00	0.00
8.40	2.01	63,003	673.27	0.93	0.93	0.00	0.00
8.80	1.75	64,344	673.33	0.94	0.94	0.00	0.00
9.20	1.70	65,464	673.38	0.95	0.95	0.00	0.00
9.60	1.48	66,433	673.43	0.96	0.96	0.00	0.00
10.00	1.23	66,996	673.46	0.96	0.96	0.00	0.00
10.40	1.19	67,342	673.47	0.96	0.96	0.00	0.00
10.80	1.19	67,661	673.49	0.97	0.97	0.00	0.00
11.20	1.10	**67,954**	**673.50**	**0.97**	**0.97**	0.00	0.00
11.60	0.80	**67,953**	**673.50**	**0.97**	**0.97**	0.00	0.00
12.00	0.90	67,714	673.49	0.97	0.97	0.00	0.00
12.40	0.41	67,474	673.48	0.96	0.96	0.00	0.00
12.80	0.10	66,420	673.43	0.96	0.96	0.00	0.00
13.20	0.00	65,094	673.37	0.95	0.95	0.00	0.00
13.60	0.00	63,737	673.30	0.94	0.94	0.00	0.00
14.00	0.00	62,391	673.24	0.93	0.93	0.00	0.00
14.40	0.00	61,059	673.18	0.92	0.92	0.00	0.00
14.80	0.00	59,740	673.12	0.91	0.91	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	2.93 cfs @	5.52 hrs, Volume=	1.043 af
Outflow	=	2.93 cfs @	5.58 hrs, Volume=	1.042 af, Atten= 0%, Lag= 3.5 min
Primary	=	1.22 cfs @	5.58 hrs, Volume=	0.695 af
Secondary	=	1.71 cfs @	5.58 hrs, Volume=	0.347 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-15.00 hrs, dt= 0.04 hrs
Peak Elev= 677.98' @ 5.58 hrs Surf.Area= 3,157 sf Storage= 3,186 cf

Plug-Flow detention time= 23.4 min calculated for 1.042 af (100% of inflow)
Center-of-Mass det. time= 22.9 min (421.4 - 398.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.22 cfs @ 5.58 hrs HW=677.98' (Free Discharge)
└1=**Orifice/Grate** (Orifice Controls 1.22 cfs @ 5.31 fps)
└2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=1.71 cfs @ 5.58 hrs HW=677.98' TW=671.80' (Dynamic Tailwater)
└4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 10.13 fps)
└5=**Sharp-Crested Rectangular Weir** (Weir Controls 1.58 cfs @ 1.44 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
└3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.40	0.00	0	670.75	0.00	0.00	0.00	0.00
0.80	0.00	0	670.75	0.00	0.00	0.00	0.00
1.20	0.00	0	670.75	0.00	0.00	0.00	0.00
1.60	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.03	8	671.32	0.00	0.00	0.00	0.00
2.40	0.15	78	676.33	0.10	0.00	0.10	0.00
2.80	0.31	168	676.70	0.22	0.12	0.10	0.00
3.20	0.58	339	676.85	0.42	0.32	0.11	0.00
3.60	0.88	611	677.00	0.65	0.54	0.11	0.00
4.00	1.27	1,046	677.20	0.84	0.73	0.11	0.00
4.40	1.85	1,871	677.53	1.09	0.97	0.12	0.00
4.80	2.44	3,002	677.93	2.20	1.19	1.01	0.00
5.20	**2.86**	**3,161**	**677.98**	**2.82**	**1.22**	**1.60**	0.00
5.60	**2.92**	**3,186**	**677.98**	**2.93**	**1.22**	**1.71**	0.00
6.00	2.62	3,129	677.97	2.69	1.21	1.48	0.00
6.40	2.21	3,024	677.93	2.28	1.20	1.09	0.00
6.80	1.87	2,925	677.90	1.93	1.18	0.75	0.00
7.20	1.64	2,845	677.87	1.69	1.17	0.52	0.00
7.60	1.46	2,775	677.85	1.51	1.15	0.35	0.00
8.00	1.27	2,693	677.82	1.33	1.14	0.20	0.00
8.40	1.07	2,556	677.78	1.23	1.11	0.12	0.00
8.80	0.94	2,253	677.67	1.17	1.05	0.12	0.00
9.20	0.92	1,950	677.56	1.11	0.99	0.12	0.00
9.60	0.77	1,647	677.45	1.03	0.91	0.12	0.00
10.00	0.64	1,246	677.29	0.91	0.80	0.11	0.00
10.40	0.63	925	677.15	0.79	0.68	0.11	0.00
10.80	0.63	741	677.06	0.71	0.60	0.11	0.00
11.20	0.56	631	677.01	0.66	0.55	0.11	0.00
11.60	0.39	445	676.91	0.52	0.41	0.11	0.00
12.00	0.48	361	676.86	0.44	0.34	0.11	0.00
12.40	0.13	261	676.79	0.34	0.23	0.11	0.00
12.80	0.02	61	675.12	0.07	0.00	0.07	0.00
13.20	0.00	39	673.54	0.00	0.00	0.00	0.00
13.60	0.00	39	673.52	0.00	0.00	0.00	0.00
14.00	0.00	39	673.50	0.00	0.00	0.00	0.00
14.40	0.00	39	673.50	0.00	0.00	0.00	0.00
14.80	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 2.01 cfs @ 11.90 hrs, Volume= 0.884 af, Depth= 3.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=4.84"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.12	0.00	0.00
1.60	0.19	0.00	0.00
2.00	0.25	0.00	0.00
2.40	0.32	0.00	0.00
2.80	0.38	0.00	0.00
3.20	0.45	0.00	0.00
3.60	0.52	0.01	0.03
4.00	0.58	0.01	0.07
4.40	0.65	0.02	0.10
4.80	0.72	0.04	0.13
5.20	0.79	0.06	0.18
5.60	0.88	0.09	0.23
6.00	0.97	0.12	0.27
6.40	1.05	0.15	0.31
6.80	1.14	0.19	0.34
7.20	1.23	0.23	0.36
7.60	1.32	0.28	0.40
8.00	1.42	0.34	0.47
8.40	1.53	0.40	0.55
8.80	1.66	0.47	0.63
9.20	1.79	0.55	0.71
9.60	1.93	0.65	0.80
10.00	2.08	0.75	0.90
10.40	2.27	0.88	1.14
10.80	2.51	1.06	1.51
11.20	2.77	1.27	1.79
11.60	3.05	1.49	**1.93**
12.00	3.32	1.71	**1.99**
12.40	3.56	1.91	1.77
12.80	3.76	2.08	1.51
13.20	3.92	2.22	1.30
13.60	4.06	2.34	1.09
14.00	4.18	2.44	0.92
14.40	4.27	2.53	0.77
14.80	4.36	2.60	0.65
15.20	4.43	2.66	0.58
15.60	4.50	2.72	0.52
16.00	4.56	2.78	0.51
16.40	4.63	2.84	0.51
16.80	4.68	2.89	0.45
17.20	4.73	2.93	0.37
17.60	4.78	2.98	0.39
18.00	**4.84**	**3.03**	0.47
18.40	4.84	3.03	0.05
18.80	4.84	3.03	0.00
19.20	4.84	3.03	0.00
19.60	4.84	3.03	0.00
20.00	4.84	3.03	0.00
20.40	4.84	3.03	0.00
20.80	4.84	3.03	0.00

Summary for Subcatchment 7S: South Property


Runoff = 4.27 cfs @ 11.98 hrs, Volume= 1.894 af, Depth= 3.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=4.84"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.12	0.00	0.00
1.60	0.19	0.00	0.00
2.00	0.25	0.00	0.00
2.40	0.32	0.00	0.00
2.80	0.38	0.00	0.00
3.20	0.45	0.00	0.00
3.60	0.52	0.01	0.06
4.00	0.58	0.01	0.12
4.40	0.65	0.02	0.19
4.80	0.72	0.04	0.25
5.20	0.79	0.06	0.34
5.60	0.88	0.09	0.46
6.00	0.97	0.12	0.56
6.40	1.05	0.15	0.64
6.80	1.14	0.19	0.70
7.20	1.23	0.23	0.76
7.60	1.32	0.28	0.83
8.00	1.42	0.34	0.97
8.40	1.53	0.40	1.13
8.80	1.66	0.47	1.30
9.20	1.79	0.55	1.48
9.60	1.93	0.65	1.67
10.00	2.08	0.75	1.86
10.40	2.27	0.88	2.27
10.80	2.51	1.06	3.00
11.20	2.77	1.27	3.69
11.60	3.05	1.49	**4.05**
12.00	3.32	1.71	**4.26**
12.40	3.56	1.91	3.94
12.80	3.76	2.08	3.40
13.20	3.92	2.22	2.92
13.60	4.06	2.34	2.46
14.00	4.18	2.44	2.07
14.40	4.27	2.53	1.74
14.80	4.36	2.60	1.46
15.20	4.43	2.66	1.29
15.60	4.50	2.72	1.14
16.00	4.56	2.78	1.10
16.40	4.63	2.84	1.10
16.80	4.68	2.89	1.01
17.20	4.73	2.93	0.85
17.60	4.78	2.98	0.82
18.00	**4.84**	**3.03**	0.96
18.40	4.84	3.03	0.36
18.80	4.84	3.03	0.03
19.20	4.84	3.03	0.00
19.60	4.84	3.03	0.00
20.00	4.84	3.03	0.00
20.40	4.84	3.03	0.00
20.80	4.84	3.03	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.65 cfs @ 12.10 hrs, Volume= 0.284 af, Depth= 2.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=4.84"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.12	0.00	0.00
1.60	0.19	0.00	0.00
2.00	0.25	0.00	0.00
2.40	0.32	0.00	0.00
2.80	0.38	0.00	0.00
3.20	0.45	0.00	0.00
3.60	0.52	0.00	0.00
4.00	0.58	0.01	0.01
4.40	0.65	0.01	0.02
4.80	0.72	0.02	0.02
5.20	0.79	0.04	0.04
5.60	0.88	0.06	0.05
6.00	0.97	0.09	0.07
6.40	1.05	0.12	0.08
6.80	1.14	0.15	0.09
7.20	1.23	0.19	0.10
7.60	1.32	0.23	0.11
8.00	1.42	0.28	0.13
8.40	1.53	0.33	0.15
8.80	1.66	0.40	0.18
9.20	1.79	0.47	0.21
9.60	1.93	0.56	0.24
10.00	2.08	0.66	0.27
10.40	2.27	0.78	0.31
10.80	2.51	0.95	0.41
11.20	2.77	1.14	0.53
11.60	3.05	1.35	0.60
12.00	3.32	1.57	**0.64**
12.40	3.56	1.76	**0.62**
12.80	3.76	1.92	0.55
13.20	3.92	2.06	0.47
13.60	4.06	2.17	0.40
14.00	4.18	2.27	0.34
14.40	4.27	2.35	0.29
14.80	4.36	2.43	0.24
15.20	4.43	2.49	0.21
15.60	4.50	2.54	0.18
16.00	4.56	2.60	0.17
16.40	4.63	2.66	0.17
16.80	4.68	2.71	0.16
17.20	4.73	2.75	0.14
17.60	4.78	2.79	0.13
18.00	**4.84**	**2.84**	0.14
18.40	4.84	2.84	0.10
18.80	4.84	2.84	0.02
19.20	4.84	2.84	0.00
19.60	4.84	2.84	0.00
20.00	4.84	2.84	0.00
20.40	4.84	2.84	0.00
20.80	4.84	2.84	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.30 cfs @ 11.81 hrs, Volume= 0.130 af, Depth= 2.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=4.84"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.40	0.01	0.00	0.00
0.80	0.06	0.00	0.00
1.20	0.12	0.00	0.00
1.60	0.19	0.00	0.00
2.00	0.25	0.00	0.00
2.40	0.32	0.00	0.00
2.80	0.38	0.00	0.00
3.20	0.45	0.00	0.00
3.60	0.52	0.00	0.00
4.00	0.58	0.01	0.01
4.40	0.65	0.01	0.01
4.80	0.72	0.02	0.02
5.20	0.79	0.04	0.02
5.60	0.88	0.06	0.03
6.00	0.97	0.09	0.04
6.40	1.05	0.12	0.04
6.80	1.14	0.15	0.05
7.20	1.23	0.19	0.05
7.60	1.32	0.23	0.06
8.00	1.42	0.28	0.07
8.40	1.53	0.33	0.08
8.80	1.66	0.40	0.09
9.20	1.79	0.47	0.11
9.60	1.93	0.56	0.12
10.00	2.08	0.66	0.14
10.40	2.27	0.78	0.18
10.80	2.51	0.95	0.24
11.20	2.77	1.14	0.27
11.60	3.05	1.35	**0.29**
12.00	3.32	1.57	**0.29**
12.40	3.56	1.76	0.26
12.80	3.76	1.92	0.22
13.20	3.92	2.06	0.19
13.60	4.06	2.17	0.16
14.00	4.18	2.27	0.13
14.40	4.27	2.35	0.11
14.80	4.36	2.43	0.10
15.20	4.43	2.49	0.09
15.60	4.50	2.54	0.08
16.00	4.56	2.60	0.08
16.40	4.63	2.66	0.08
16.80	4.68	2.71	0.07
17.20	4.73	2.75	0.05
17.60	4.78	2.79	0.06
18.00	**4.84**	**2.84**	0.08
18.40	4.84	2.84	0.00
18.80	4.84	2.84	0.00
19.20	4.84	2.84	0.00
19.60	4.84	2.84	0.00
20.00	4.84	2.84	0.00
20.40	4.84	2.84	0.00
20.80	4.84	2.84	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	5.99 cfs @	11.98 hrs, Volume=	2.372 af
Outflow	=	0.99 cfs @	18.22 hrs, Volume=	0.947 af, Atten= 83%, Lag= 374.5 min
Primary	=	0.99 cfs @	18.22 hrs, Volume=	0.947 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Peak Elev= 673.64' @ 18.22 hrs Surf.Area= 31,184 sf Storage= 70,872 cf

Plug-Flow detention time= 325.3 min calculated for 0.946 af (40% of inflow)
Center-of-Mass det. time= 165.7 min (885.0 - 719.3)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.99 cfs @ 18.22 hrs HW=673.64' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.99 cfs @ 8.95 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
1.00	0.00	0	670.00	0.00	0.00	0.00	0.00
2.00	0.00	0	670.00	0.00	0.00	0.00	0.00
3.00	0.00	0	670.00	0.00	0.00	0.00	0.00
4.00	0.19	215	670.02	0.00	0.00	0.00	0.00
5.00	0.42	1,258	670.14	0.05	0.05	0.00	0.00
6.00	0.70	2,875	670.32	0.19	0.19	0.00	0.00
7.00	0.89	4,832	670.52	0.31	0.31	0.00	0.00
8.00	1.15	7,117	670.75	0.40	0.40	0.00	0.00
9.00	1.60	10,497	670.91	0.45	0.45	0.00	0.00
10.00	2.11	15,393	671.14	0.52	0.52	0.00	0.00
11.00	**4.40**	23,610	671.51	0.61	0.61	0.00	0.00
12.00	**5.98**	40,621	672.27	0.77	0.77	0.00	0.00
13.00	4.14	56,337	672.96	0.89	0.89	0.00	0.00
14.00	2.39	64,696	673.35	0.95	0.95	0.00	0.00
15.00	1.58	68,180	673.51	0.97	0.97	0.00	0.00
16.00	1.30	69,686	673.59	0.98	0.98	0.00	0.00
17.00	1.10	70,629	673.63	0.99	0.99	0.00	0.00
18.00	1.14	**70,767**	**673.64**	**0.99**	**0.99**	0.00	0.00
19.00	0.03	**69,004**	**673.55**	**0.98**	**0.98**	0.00	0.00
20.00	0.00	65,547	673.39	0.95	0.95	0.00	0.00
21.00	0.00	62,163	673.23	0.93	0.93	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	2.64 cfs @	11.94 hrs, Volume=	1.168 af
Outflow	=	2.64 cfs @	11.99 hrs, Volume=	1.167 af, Atten= 0%, Lag= 2.8 min
Primary	=	1.21 cfs @	11.99 hrs, Volume=	0.819 af
Secondary	=	1.42 cfs @	11.99 hrs, Volume=	0.348 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-21.00 hrs, dt= 0.02 hrs
Peak Elev= 677.96' @ 11.99 hrs Surf.Area= 3,133 sf Storage= 3,115 cf

Plug-Flow detention time= 22.7 min calculated for 1.167 af (100% of inflow)
Center-of-Mass det. time= 22.3 min (741.3 - 719.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.21 cfs @ 11.99 hrs HW=677.96' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 1.21 cfs @ 5.26 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=1.42 cfs @ 11.99 hrs HW=677.96' TW=672.26' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 10.10 fps)
└—5=**Sharp-Crested Rectangular Weir** (Weir Controls 1.30 cfs @ 1.34 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.00	0.00	0	670.75	0.00	0.00	0.00	0.00
2.00	0.00	0	670.75	0.00	0.00	0.00	0.00
3.00	0.00	0	670.75	0.00	0.00	0.00	0.00
4.00	0.07	54	674.64	0.06	0.00	0.06	0.00
5.00	0.18	119	676.63	0.15	0.05	0.10	0.00
6.00	0.34	238	676.77	0.31	0.21	0.11	0.00
7.00	0.45	338	676.85	0.42	0.32	0.11	0.00
8.00	0.60	467	676.93	0.54	0.44	0.11	0.00
9.00	0.86	794	677.09	0.74	0.63	0.11	0.00
10.00	1.16	1,387	677.34	0.96	0.84	0.11	0.00
11.00	**2.16**	**2,923**	**677.90**	**1.93**	**1.18**	**0.75**	0.00
12.00	**2.63**	**3,115**	**677.96**	**2.63**	**1.21**	**1.42**	0.00
13.00	1.91	2,937	677.90	1.97	1.18	0.79	0.00
14.00	1.26	2,692	677.82	1.33	1.14	0.19	0.00
15.00	0.84	2,010	677.58	1.12	1.00	0.12	0.00
16.00	0.69	1,094	677.22	0.86	0.74	0.11	0.00
17.00	0.56	680	677.04	0.68	0.57	0.11	0.00
18.00	0.61	495	676.94	0.57	0.46	0.11	0.00
19.00	0.01	42	673.72	0.02	0.00	0.02	0.00
20.00	0.00	39	673.51	0.00	0.00	0.00	0.00
21.00	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 1.64 cfs @ 15.79 hrs, Volume= 0.965 af, Depth= 3.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=5.15"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00	18.20	4.34	2.58	0.83
0.35	0.01	0.00	0.00	18.55	4.42	2.65	0.75
0.70	0.03	0.00	0.00	18.90	4.49	2.72	0.67
1.05	0.06	0.00	0.00	19.25	4.56	2.78	0.59
1.40	0.10	0.00	0.00	19.60	4.62	2.83	0.53
1.75	0.15	0.00	0.00	19.95	4.67	2.88	0.49
2.10	0.20	0.00	0.00	20.30	4.72	2.92	0.45
2.45	0.24	0.00	0.00	20.65	4.76	2.96	0.42
2.80	0.29	0.00	0.00	21.00	4.81	3.00	0.41
3.15	0.33	0.00	0.00	21.35	4.86	3.04	0.41
3.50	0.38	0.00	0.00	21.70	4.90	3.09	0.42
3.85	0.42	0.00	0.00	22.05	4.94	3.12	0.39
4.20	0.47	0.00	0.01	22.40	4.98	3.16	0.35
4.55	0.52	0.01	0.03	22.75	5.01	3.19	0.31
4.90	0.56	0.01	0.05	23.10	5.05	3.22	0.29
5.25	0.61	0.02	0.07	23.45	5.08	3.25	0.33
5.60	0.65	0.03	0.08	23.80	**5.12**	**3.29**	0.37
5.95	0.70	0.04	0.10	24.15	**5.15**	**3.31**	0.33
6.30	0.75	0.05	0.11	24.50	5.15	3.31	0.02
6.65	0.80	0.06	0.14	24.85	5.15	3.31	0.00
7.00	0.85	0.08	0.17	25.20	5.15	3.31	0.00
7.35	0.91	0.10	0.20	25.55	5.15	3.31	0.00
7.70	0.98	0.12	0.22	25.90	5.15	3.31	0.00
8.05	1.04	0.15	0.24	26.25	5.15	3.31	0.00
8.40	1.10	0.17	0.26	26.60	5.15	3.31	0.00
8.75	1.16	0.20	0.27	26.95	5.15	3.31	0.00
9.10	1.22	0.23	0.29				
9.45	1.28	0.26	0.30				
9.80	1.34	0.29	0.32				
10.15	1.41	0.33	0.35				
10.50	1.48	0.37	0.39				
10.85	1.55	0.41	0.43				
11.20	1.63	0.46	0.47				
11.55	1.72	0.51	0.51				
11.90	1.80	0.56	0.56				
12.25	1.90	0.63	0.60				
12.60	1.99	0.69	0.65				
12.95	2.09	0.76	0.70				
13.30	2.20	0.84	0.74				
13.65	2.33	0.93	0.87				
14.00	2.47	1.03	1.05				
14.35	2.64	1.16	1.25				
14.70	2.82	1.31	1.43				
15.05	3.01	1.46	1.51				
15.40	3.21	1.62	1.57				
15.75	3.40	1.78	**1.64**				
16.10	3.59	1.93	**1.57**				
16.45	3.75	2.07	1.44				
16.80	3.90	2.20	1.30				
17.15	4.03	2.31	1.17				
17.50	4.14	2.41	1.06				
17.85	4.25	2.50	0.94				

Summary for Subcatchment 7S: South Property


Runoff = 3.49 cfs @ 15.88 hrs, Volume= 2.069 af, Depth= 3.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=5.15"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.01	0.00	0.00
0.70	0.03	0.00	0.00
1.05	0.06	0.00	0.00
1.40	0.10	0.00	0.00
1.75	0.15	0.00	0.00
2.10	0.20	0.00	0.00
2.45	0.24	0.00	0.00
2.80	0.29	0.00	0.00
3.15	0.33	0.00	0.00
3.50	0.38	0.00	0.00
3.85	0.42	0.00	0.00
4.20	0.47	0.00	0.02
4.55	0.52	0.01	0.05
4.90	0.56	0.01	0.09
5.25	0.61	0.02	0.13
5.60	0.65	0.03	0.16
5.95	0.70	0.04	0.20
6.30	0.75	0.05	0.23
6.65	0.80	0.06	0.28
7.00	0.85	0.08	0.34
7.35	0.91	0.10	0.41
7.70	0.98	0.12	0.47
8.05	1.04	0.15	0.51
8.40	1.10	0.17	0.54
8.75	1.16	0.20	0.58
9.10	1.22	0.23	0.61
9.45	1.28	0.26	0.64
9.80	1.34	0.29	0.67
10.15	1.41	0.33	0.72
10.50	1.48	0.37	0.80
10.85	1.55	0.41	0.89
11.20	1.63	0.46	0.97
11.55	1.72	0.51	1.06
11.90	1.80	0.56	1.16
12.25	1.90	0.63	1.25
12.60	1.99	0.69	1.35
12.95	2.09	0.76	1.46
13.30	2.20	0.84	1.56
13.65	2.33	0.93	1.76
14.00	2.47	1.03	2.13
14.35	2.64	1.16	2.54
14.70	2.82	1.31	2.94
15.05	3.01	1.46	3.17
15.40	3.21	1.62	3.32
15.75	3.40	1.78	**3.46**
16.10	3.59	1.93	**3.42**
16.45	3.75	2.07	3.17
16.80	3.90	2.20	2.88
17.15	4.03	2.31	2.59
17.50	4.14	2.41	2.34
17.85	4.25	2.50	2.10
18.20	4.34	2.58	1.86
18.55	4.42	2.65	1.66
18.90	4.49	2.72	1.49
19.25	4.56	2.78	1.33
19.60	4.62	2.83	1.18
19.95	4.67	2.88	1.08
20.30	4.72	2.92	1.00
20.65	4.76	2.96	0.92
21.00	4.81	3.00	0.89
21.35	4.86	3.04	0.89
21.70	4.90	3.09	0.89
22.05	4.94	3.12	0.86
22.40	4.98	3.16	0.78
22.75	5.01	3.19	0.70
23.10	5.05	3.22	0.63
23.45	5.08	3.25	0.67
23.80	**5.12**	**3.29**	0.76
24.15	**5.15**	**3.31**	0.79
24.50	5.15	3.31	0.16
24.85	5.15	3.31	0.02
25.20	5.15	3.31	0.00
25.55	5.15	3.31	0.00
25.90	5.15	3.31	0.00
26.25	5.15	3.31	0.00
26.60	5.15	3.31	0.00
26.95	5.15	3.31	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.53 cfs @ 16.00 hrs, Volume= 0.312 af, Depth= 3.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=5.15"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.01	0.00	0.00
0.70	0.03	0.00	0.00
1.05	0.06	0.00	0.00
1.40	0.10	0.00	0.00
1.75	0.15	0.00	0.00
2.10	0.20	0.00	0.00
2.45	0.24	0.00	0.00
2.80	0.29	0.00	0.00
3.15	0.33	0.00	0.00
3.50	0.38	0.00	0.00
3.85	0.42	0.00	0.00
4.20	0.47	0.00	0.00
4.55	0.52	0.00	0.00
4.90	0.56	0.00	0.00
5.25	0.61	0.01	0.01
5.60	0.65	0.01	0.01
5.95	0.70	0.02	0.02
6.30	0.75	0.03	0.03
6.65	0.80	0.04	0.03
7.00	0.85	0.05	0.04
7.35	0.91	0.07	0.05
7.70	0.98	0.09	0.06
8.05	1.04	0.11	0.07
8.40	1.10	0.13	0.07
8.75	1.16	0.16	0.08
9.10	1.22	0.18	0.08
9.45	1.28	0.21	0.09
9.80	1.34	0.24	0.09
10.15	1.41	0.27	0.10
10.50	1.48	0.30	0.11
10.85	1.55	0.34	0.12
11.20	1.63	0.39	0.14
11.55	1.72	0.43	0.15
11.90	1.80	0.48	0.16
12.25	1.90	0.54	0.18
12.60	1.99	0.60	0.19
12.95	2.09	0.67	0.21
13.30	2.20	0.74	0.23
13.65	2.33	0.82	0.25
14.00	2.47	0.92	0.30
14.35	2.64	1.04	0.36
14.70	2.82	1.18	0.42
15.05	3.01	1.32	0.47
15.40	3.21	1.47	0.50
15.75	3.40	1.63	**0.52**
16.10	3.59	1.78	**0.53**
16.45	3.75	1.91	0.50
16.80	3.90	2.03	0.46
17.15	4.03	2.14	0.42
17.50	4.14	2.24	0.38
17.85	4.25	2.33	0.34
18.20	4.34	2.41	0.30
18.55	4.42	2.48	0.27
18.90	4.49	2.54	0.24
19.25	4.56	2.60	0.22
19.60	4.62	2.65	0.19
19.95	4.67	2.69	0.17
20.30	4.72	2.74	0.16
20.65	4.76	2.78	0.15
21.00	4.81	2.82	0.14
21.35	4.86	2.86	0.14
21.70	4.90	2.90	0.14
22.05	4.94	2.94	0.14
22.40	4.98	2.97	0.13
22.75	5.01	3.00	0.11
23.10	5.05	3.03	0.10
23.45	5.08	3.06	0.10
23.80	**5.12**	**3.10**	0.11
24.15	**5.15**	**3.12**	0.12
24.50	5.15	3.12	0.06
24.85	5.15	3.12	0.01
25.20	5.15	3.12	0.00
25.55	5.15	3.12	0.00
25.90	5.15	3.12	0.00
26.25	5.15	3.12	0.00
26.60	5.15	3.12	0.00
26.95	5.15	3.12	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.25 cfs @ 15.71 hrs, Volume= 0.143 af, Depth= 3.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=5.15"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.35	0.01	0.00	0.00
0.70	0.03	0.00	0.00
1.05	0.06	0.00	0.00
1.40	0.10	0.00	0.00
1.75	0.15	0.00	0.00
2.10	0.20	0.00	0.00
2.45	0.24	0.00	0.00
2.80	0.29	0.00	0.00
3.15	0.33	0.00	0.00
3.50	0.38	0.00	0.00
3.85	0.42	0.00	0.00
4.20	0.47	0.00	0.00
4.55	0.52	0.00	0.00
4.90	0.56	0.00	0.00
5.25	0.61	0.01	0.01
5.60	0.65	0.01	0.01
5.95	0.70	0.02	0.01
6.30	0.75	0.03	0.01
6.65	0.80	0.04	0.02
7.00	0.85	0.05	0.02
7.35	0.91	0.07	0.03
7.70	0.98	0.09	0.03
8.05	1.04	0.11	0.03
8.40	1.10	0.13	0.04
8.75	1.16	0.16	0.04
9.10	1.22	0.18	0.04
9.45	1.28	0.21	0.04
9.80	1.34	0.24	0.05
10.15	1.41	0.27	0.05
10.50	1.48	0.30	0.06
10.85	1.55	0.34	0.06
11.20	1.63	0.39	0.07
11.55	1.72	0.43	0.08
11.90	1.80	0.48	0.08
12.25	1.90	0.54	0.09
12.60	1.99	0.60	0.10
12.95	2.09	0.67	0.10
13.30	2.20	0.74	0.11
13.65	2.33	0.82	0.14
14.00	2.47	0.92	0.16
14.35	2.64	1.04	0.20
14.70	2.82	1.18	0.22
15.05	3.01	1.32	0.23
15.40	3.21	1.47	**0.24**
15.75	3.40	1.63	**0.25**
16.10	3.59	1.78	0.23
16.45	3.75	1.91	0.21
16.80	3.90	2.03	0.19
17.15	4.03	2.14	0.17
17.50	4.14	2.24	0.16
17.85	4.25	2.33	0.14
18.20	4.34	2.41	0.12
18.55	4.42	2.48	0.11
18.90	4.49	2.54	0.10
19.25	4.56	2.60	0.09
19.60	4.62	2.65	0.08
19.95	4.67	2.69	0.07
20.30	4.72	2.74	0.07
20.65	4.76	2.78	0.06
21.00	4.81	2.82	0.06
21.35	4.86	2.86	0.06
21.70	4.90	2.90	0.06
22.05	4.94	2.94	0.06
22.40	4.98	2.97	0.05
22.75	5.01	3.00	0.05
23.10	5.05	3.03	0.05
23.45	5.08	3.06	0.05
23.80	**5.12**	**3.10**	0.06
24.15	**5.15**	**3.12**	0.02
24.50	5.15	3.12	0.00
24.85	5.15	3.12	0.00
25.20	5.15	3.12	0.00
25.55	5.15	3.12	0.00
25.90	5.15	3.12	0.00
26.25	5.15	3.12	0.00
26.60	5.15	3.12	0.00
26.95	5.15	3.12	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	4.70 cfs @	15.88 hrs, Volume=	2.541 af
Outflow	=	0.97 cfs @	22.34 hrs, Volume=	1.196 af, Atten= 79%, Lag= 387.9 min
Primary	=	0.97 cfs @	22.34 hrs, Volume=	1.196 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Peak Elev= 673.51' @ 22.34 hrs Surf.Area= 31,153 sf Storage= 68,027 cf

Plug-Flow detention time= 381.3 min calculated for 1.193 af (47% of inflow)
Center-of-Mass det. time= 191.0 min (1,136.9 - 945.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.97 cfs @ 22.34 hrs HW=673.51' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.97 cfs @ 8.77 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
0.70	0.00	0	670.00	0.00	0.00	0.00	0.00
1.40	0.00	0	670.00	0.00	0.00	0.00	0.00
2.10	0.00	0	670.00	0.00	0.00	0.00	0.00
2.80	0.00	0	670.00	0.00	0.00	0.00	0.00
3.50	0.00	0	670.00	0.00	0.00	0.00	0.00
4.20	0.02	5	670.00	0.00	0.00	0.00	0.00
4.90	0.14	168	670.02	0.00	0.00	0.00	0.00
5.60	0.26	654	670.07	0.01	0.01	0.00	0.00
6.30	0.35	1,342	670.15	0.05	0.05	0.00	0.00
7.00	0.47	2,133	670.24	0.12	0.12	0.00	0.00
7.70	0.60	3,060	670.34	0.21	0.21	0.00	0.00
8.40	0.68	4,072	670.45	0.27	0.27	0.00	0.00
9.10	0.76	5,142	670.55	0.32	0.32	0.00	0.00
9.80	0.82	6,260	670.66	0.37	0.37	0.00	0.00
10.50	0.97	7,501	670.77	0.40	0.40	0.00	0.00
11.20	1.15	9,092	670.84	0.43	0.43	0.00	0.00
11.90	1.35	11,094	670.94	0.46	0.46	0.00	0.00
12.60	1.56	13,533	671.06	0.50	0.50	0.00	0.00
13.30	1.78	16,426	671.19	0.53	0.53	0.00	0.00
14.00	2.41	20,102	671.36	0.58	0.58	0.00	0.00
14.70	3.45	25,669	671.60	0.63	0.63	0.00	0.00
15.40	**4.43**	34,228	671.99	0.71	0.71	0.00	0.00
16.10	**4.58**	43,930	672.41	0.79	0.79	0.00	0.00
16.80	3.70	52,466	672.79	0.86	0.86	0.00	0.00
17.50	2.83	58,533	673.06	0.90	0.90	0.00	0.00
18.20	2.10	62,489	673.25	0.93	0.93	0.00	0.00
18.90	1.71	64,956	673.36	0.95	0.95	0.00	0.00
19.60	1.37	66,464	673.43	0.96	0.96	0.00	0.00
20.30	1.18	67,276	673.47	0.96	0.96	0.00	0.00
21.00	1.06	67,641	673.49	0.97	0.97	0.00	0.00
21.70	1.06	**67,881**	**673.50**	**0.97**	**0.97**	0.00	0.00
22.40	0.95	**68,025**	**673.51**	**0.97**	**0.97**	0.00	0.00
23.10	0.78	67,763	673.49	0.97	0.97	0.00	0.00
23.80	0.92	67,422	673.48	0.96	0.96	0.00	0.00
24.50	0.26	67,008	673.46	0.96	0.96	0.00	0.00
25.20	0.00	64,854	673.36	0.95	0.95	0.00	0.00
25.90	0.00	62,491	673.25	0.93	0.93	0.00	0.00
26.60	0.00	60,166	673.14	0.91	0.91	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	2.16 cfs @	15.82 hrs, Volume=	1.277 af
Outflow	=	2.16 cfs @	15.89 hrs, Volume=	1.276 af, Atten= 0%, Lag= 4.6 min
Primary	=	1.19 cfs @	15.89 hrs, Volume=	0.947 af
Secondary	=	0.97 cfs @	15.89 hrs, Volume=	0.329 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-27.02 hrs, dt= 0.07 hrs
Peak Elev= 677.92' @ 15.89 hrs Surf.Area= 3,089 sf Storage= 2,991 cf

Plug-Flow detention time= 23.0 min calculated for 1.276 af (100% of inflow)
Center-of-Mass det. time= 22.5 min (970.1 - 947.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.19 cfs @ 15.89 hrs HW=677.92' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 1.19 cfs @ 5.17 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.97 cfs @ 15.89 hrs HW=677.92' TW=672.29' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.12 cfs @ 10.05 fps)
└—**5=Sharp-Crested Rectangular Weir** (Weir Controls 0.85 cfs @ 1.16 fps)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
0.70	0.00	0	670.75	0.00	0.00	0.00	0.00
1.40	0.00	0	670.75	0.00	0.00	0.00	0.00
2.10	0.00	0	670.75	0.00	0.00	0.00	0.00
2.80	0.00	0	670.75	0.00	0.00	0.00	0.00
3.50	0.00	0	670.75	0.00	0.00	0.00	0.00
4.20	0.01	5	671.09	0.00	0.00	0.00	0.00
4.90	0.05	48	674.21	0.05	0.00	0.05	0.00
5.60	0.10	69	675.70	0.09	0.00	0.09	0.00
6.30	0.14	100	676.59	0.13	0.02	0.10	0.00
7.00	0.21	143	676.67	0.19	0.08	0.10	0.00
7.70	0.28	200	676.73	0.26	0.16	0.11	0.00
8.40	0.33	242	676.78	0.32	0.21	0.11	0.00
9.10	0.37	280	676.80	0.36	0.25	0.11	0.00
9.80	0.41	315	676.83	0.40	0.29	0.11	0.00
10.50	0.50	377	676.87	0.46	0.35	0.11	0.00
11.20	0.60	482	676.94	0.56	0.45	0.11	0.00
11.90	0.72	620	677.01	0.65	0.54	0.11	0.00
12.60	0.84	821	677.10	0.75	0.64	0.11	0.00
13.30	0.97	1,081	677.22	0.85	0.74	0.11	0.00
14.00	1.35	1,587	677.42	1.01	0.90	0.12	0.00
14.70	1.85	2,744	677.84	1.44	1.15	0.29	0.00
15.40	**2.07**	**2,959**	**677.91**	**2.05**	**1.19**	**0.86**	0.00
16.10	**2.10**	**2,980**	**677.92**	**2.12**	**1.19**	**0.93**	0.00
16.80	1.76	2,884	677.89	1.81	1.17	0.63	0.00
17.50	1.43	2,764	677.85	1.48	1.15	0.33	0.00
18.20	1.13	2,607	677.80	1.24	1.12	0.12	0.00
18.90	0.91	2,156	677.64	1.15	1.03	0.12	0.00
19.60	0.72	1,496	677.39	0.99	0.87	0.12	0.00
20.30	0.61	926	677.15	0.79	0.68	0.11	0.00
21.00	0.55	580	676.99	0.63	0.52	0.11	0.00
21.70	0.55	491	676.94	0.56	0.46	0.11	0.00
22.40	0.48	439	676.91	0.52	0.41	0.11	0.00
23.10	0.39	335	676.85	0.42	0.31	0.11	0.00
23.80	0.48	360	676.86	0.44	0.34	0.11	0.00
24.50	0.07	195	676.73	0.25	0.15	0.11	0.00
25.20	0.00	39	673.55	0.00	0.00	0.00	0.00
25.90	0.00	39	673.51	0.00	0.00	0.00	0.00
26.60	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.96 cfs @ 41.27 hrs, Volume= 1.091 af, Depth= 3.74"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=5.62"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.03	0.00	0.00
2.40	0.06	0.00	0.00
3.00	0.09	0.00	0.00
3.60	0.12	0.00	0.00
4.20	0.16	0.00	0.00
4.80	0.20	0.00	0.00
5.40	0.25	0.00	0.00
6.00	0.29	0.00	0.00
6.60	0.34	0.00	0.00
7.20	0.38	0.00	0.00
7.80	0.42	0.00	0.00
8.40	0.46	0.00	0.01
9.00	0.50	0.00	0.01
9.60	0.53	0.01	0.02
10.20	0.56	0.01	0.02
10.80	0.59	0.02	0.03
11.40	0.63	0.02	0.04
12.00	0.67	0.03	0.05
12.60	0.72	0.04	0.06
13.20	0.76	0.05	0.07
13.80	0.80	0.06	0.07
14.40	0.85	0.08	0.08
15.00	0.89	0.09	0.09
15.60	0.94	0.11	0.09
16.20	0.98	0.12	0.10
16.80	1.02	0.14	0.10
17.40	1.07	0.16	0.11
18.00	1.11	0.18	0.11
18.60	1.16	0.20	0.12
19.20	1.20	0.22	0.12
19.80	1.24	0.24	0.13
20.40	1.29	0.26	0.13
21.00	1.33	0.29	0.13
21.60	1.38	0.31	0.14
22.20	1.42	0.33	0.14
22.80	1.46	0.36	0.14
23.40	1.51	0.38	0.15
24.00	1.55	0.41	0.15
24.60	1.60	0.44	0.16
25.20	1.65	0.47	0.18
25.80	1.70	0.50	0.19
26.40	1.76	0.53	0.21
27.00	1.81	0.57	0.21
27.60	1.87	0.61	0.20
28.20	1.92	0.64	0.19
28.80	1.96	0.67	0.18
29.40	2.01	0.70	0.18
30.00	2.06	0.73	0.20
30.60	2.11	0.77	0.22
31.20	2.17	0.81	0.24
31.80	2.23	0.86	0.26
32.40	2.30	0.91	0.30
33.00	2.37	0.96	0.33
33.60	2.46	1.02	0.37
34.20	2.55	1.09	0.39
34.80	2.63	1.16	0.40
35.40	2.72	1.23	0.40
36.00	2.81	1.30	0.41
36.60	2.90	1.37	0.43
37.20	3.00	1.45	0.47
37.80	3.11	1.53	0.51
38.40	3.22	1.63	0.55
39.00	3.35	1.73	0.62
39.60	3.49	1.85	0.72
40.20	3.65	1.99	0.82
40.80	3.83	2.14	**0.92**
41.40	4.02	2.31	**0.96**
42.00	4.21	2.47	0.95
42.60	4.39	2.63	0.94
43.20	4.57	2.78	0.93
43.80	4.73	2.93	0.88
44.40	4.89	3.07	0.81
45.00	5.03	3.20	0.73
45.60	5.15	3.31	0.66
46.20	5.27	3.42	0.63
46.80	5.39	3.53	0.63
47.40	5.50	3.63	0.63
48.00	**5.62**	**3.74**	0.63
48.60	5.62	3.74	0.01
49.20	5.62	3.74	0.00
49.80	5.62	3.74	0.00

Summary for Subcatchment 7S: South Property


Runoff = 2.05 cfs @ 41.45 hrs, Volume= 2.338 af, Depth= 3.74"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=5.62"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.03	0.00	0.00
2.40	0.06	0.00	0.00
3.00	0.09	0.00	0.00
3.60	0.12	0.00	0.00
4.20	0.16	0.00	0.00
4.80	0.20	0.00	0.00
5.40	0.25	0.00	0.00
6.00	0.29	0.00	0.00
6.60	0.34	0.00	0.00
7.20	0.38	0.00	0.00
7.80	0.42	0.00	0.00
8.40	0.46	0.00	0.01
9.00	0.50	0.00	0.03
9.60	0.53	0.01	0.04
10.20	0.56	0.01	0.04
10.80	0.59	0.02	0.06
11.40	0.63	0.02	0.08
12.00	0.67	0.03	0.10
12.60	0.72	0.04	0.12
13.20	0.76	0.05	0.14
13.80	0.80	0.06	0.16
14.40	0.85	0.08	0.17
15.00	0.89	0.09	0.18
15.60	0.94	0.11	0.20
16.20	0.98	0.12	0.21
16.80	1.02	0.14	0.22
17.40	1.07	0.16	0.23
18.00	1.11	0.18	0.24
18.60	1.16	0.20	0.25
19.20	1.20	0.22	0.26
19.80	1.24	0.24	0.27
20.40	1.29	0.26	0.28
21.00	1.33	0.29	0.29
21.60	1.38	0.31	0.29
22.20	1.42	0.33	0.30
22.80	1.46	0.36	0.31
23.40	1.51	0.38	0.31
24.00	1.55	0.41	0.32
24.60	1.60	0.44	0.34
25.20	1.65	0.47	0.37
25.80	1.70	0.50	0.41
26.40	1.76	0.53	0.45
27.00	1.81	0.57	0.46
27.60	1.87	0.61	0.44
28.20	1.92	0.64	0.42
28.80	1.96	0.67	0.39
29.40	2.01	0.70	0.39
30.00	2.06	0.73	0.42
30.60	2.11	0.77	0.46
31.20	2.17	0.81	0.50
31.80	2.23	0.86	0.55
32.40	2.30	0.91	0.63
33.00	2.37	0.96	0.70
33.60	2.46	1.02	0.78
34.20	2.55	1.09	0.83
34.80	2.63	1.16	0.85
35.40	2.72	1.23	0.86
36.00	2.81	1.30	0.87
36.60	2.90	1.37	0.91
37.20	3.00	1.45	0.99
37.80	3.11	1.53	1.07
38.40	3.22	1.63	1.16
39.00	3.35	1.73	1.29
39.60	3.49	1.85	1.50
40.20	3.65	1.99	1.71
40.80	3.83	2.14	1.93
41.40	4.02	2.31	**2.05**
42.00	4.21	2.47	2.04
42.60	4.39	2.63	2.01
43.20	4.57	2.78	1.99
43.80	4.73	2.93	1.91
44.40	4.89	3.07	1.76
45.00	5.03	3.20	1.60
45.60	5.15	3.31	1.44
46.20	5.27	3.42	1.35
46.80	5.39	3.53	1.35
47.40	5.50	3.63	1.35
48.00	**5.62**	**3.74**	1.36
48.60	5.62	3.74	0.14
49.20	5.62	3.74	0.00
49.80	5.62	3.74	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.32 cfs @ 41.75 hrs, Volume= 0.354 af, Depth= 3.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=5.62"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.03	0.00	0.00
2.40	0.06	0.00	0.00
3.00	0.09	0.00	0.00
3.60	0.12	0.00	0.00
4.20	0.16	0.00	0.00
4.80	0.20	0.00	0.00
5.40	0.25	0.00	0.00
6.00	0.29	0.00	0.00
6.60	0.34	0.00	0.00
7.20	0.38	0.00	0.00
7.80	0.42	0.00	0.00
8.40	0.46	0.00	0.00
9.00	0.50	0.00	0.00
9.60	0.53	0.00	0.00
10.20	0.56	0.00	0.00
10.80	0.59	0.01	0.01
11.40	0.63	0.01	0.01
12.00	0.67	0.02	0.01
12.60	0.72	0.02	0.01
13.20	0.76	0.03	0.02
13.80	0.80	0.04	0.02
14.40	0.85	0.05	0.02
15.00	0.89	0.06	0.02
15.60	0.94	0.08	0.03
16.20	0.98	0.09	0.03
16.80	1.02	0.11	0.03
17.40	1.07	0.12	0.03
18.00	1.11	0.14	0.03
18.60	1.16	0.16	0.03
19.20	1.20	0.17	0.04
19.80	1.24	0.19	0.04
20.40	1.29	0.21	0.04
21.00	1.33	0.23	0.04
21.60	1.38	0.25	0.04
22.20	1.42	0.27	0.04
22.80	1.46	0.30	0.04
23.40	1.51	0.32	0.05
24.00	1.55	0.34	0.05
24.60	1.60	0.37	0.05
25.20	1.65	0.39	0.05
25.80	1.70	0.42	0.06
26.40	1.76	0.46	0.06
27.00	1.81	0.49	0.07
27.60	1.87	0.52	0.07
28.20	1.92	0.55	0.06
28.80	1.96	0.58	0.06
29.40	2.01	0.61	0.06
30.00	2.06	0.64	0.06
30.60	2.11	0.67	0.07
31.20	2.17	0.71	0.07
31.80	2.23	0.75	0.08
32.40	2.30	0.80	0.09
33.00	2.37	0.85	0.10
33.60	2.46	0.91	0.11
34.20	2.55	0.98	0.12
34.80	2.63	1.04	0.13
35.40	2.72	1.10	0.13
36.00	2.81	1.17	0.13
36.60	2.90	1.24	0.14
37.20	3.00	1.31	0.15
37.80	3.11	1.40	0.16
38.40	3.22	1.48	0.17
39.00	3.35	1.58	0.19
39.60	3.49	1.70	0.22
40.20	3.65	1.83	0.26
40.80	3.83	1.98	0.29
41.40	4.02	2.14	**0.32**
42.00	4.21	2.30	**0.32**
42.60	4.39	2.45	0.31
43.20	4.57	2.61	0.31
43.80	4.73	2.75	0.30
44.40	4.89	2.89	0.28
45.00	5.03	3.01	0.26
45.60	5.15	3.12	0.23
46.20	5.27	3.22	0.21
46.80	5.39	3.33	0.21
47.40	5.50	3.43	0.21
48.00	**5.62**	**3.54**	0.21
48.60	5.62	3.54	0.06
49.20	5.62	3.54	0.00
49.80	5.62	3.54	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.15 cfs @ 41.10 hrs, Volume= 0.162 af, Depth= 3.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=5.62"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
0.60	0.00	0.00	0.00
1.20	0.01	0.00	0.00
1.80	0.03	0.00	0.00
2.40	0.06	0.00	0.00
3.00	0.09	0.00	0.00
3.60	0.12	0.00	0.00
4.20	0.16	0.00	0.00
4.80	0.20	0.00	0.00
5.40	0.25	0.00	0.00
6.00	0.29	0.00	0.00
6.60	0.34	0.00	0.00
7.20	0.38	0.00	0.00
7.80	0.42	0.00	0.00
8.40	0.46	0.00	0.00
9.00	0.50	0.00	0.00
9.60	0.53	0.00	0.00
10.20	0.56	0.00	0.00
10.80	0.59	0.01	0.00
11.40	0.63	0.01	0.00
12.00	0.67	0.02	0.01
12.60	0.72	0.02	0.01
13.20	0.76	0.03	0.01
13.80	0.80	0.04	0.01
14.40	0.85	0.05	0.01
15.00	0.89	0.06	0.01
15.60	0.94	0.08	0.01
16.20	0.98	0.09	0.01
16.80	1.02	0.11	0.01
17.40	1.07	0.12	0.01
18.00	1.11	0.14	0.02
18.60	1.16	0.16	0.02
19.20	1.20	0.17	0.02
19.80	1.24	0.19	0.02
20.40	1.29	0.21	0.02
21.00	1.33	0.23	0.02
21.60	1.38	0.25	0.02
22.20	1.42	0.27	0.02
22.80	1.46	0.30	0.02
23.40	1.51	0.32	0.02
24.00	1.55	0.34	0.02
24.60	1.60	0.37	0.02
25.20	1.65	0.39	0.03
25.80	1.70	0.42	0.03
26.40	1.76	0.46	0.03
27.00	1.81	0.49	0.03
27.60	1.87	0.52	0.03
28.20	1.92	0.55	0.03
28.80	1.96	0.58	0.03
29.40	2.01	0.61	0.03
30.00	2.06	0.64	0.03
30.60	2.11	0.67	0.03
31.20	2.17	0.71	0.04
31.80	2.23	0.75	0.04
32.40	2.30	0.80	0.05
33.00	2.37	0.85	0.05
33.60	2.46	0.91	0.06
34.20	2.55	0.98	0.06
34.80	2.63	1.04	0.06
35.40	2.72	1.10	0.06
36.00	2.81	1.17	0.06
36.60	2.90	1.24	0.07
37.20	3.00	1.31	0.07
37.80	3.11	1.40	0.08
38.40	3.22	1.48	0.08
39.00	3.35	1.58	0.10
39.60	3.49	1.70	0.11
40.20	3.65	1.83	0.13
40.80	3.83	1.98	**0.14**
41.40	4.02	2.14	**0.15**
42.00	4.21	2.30	0.14
42.60	4.39	2.45	0.14
43.20	4.57	2.61	0.14
43.80	4.73	2.75	0.13
44.40	4.89	2.89	0.12
45.00	5.03	3.01	0.11
45.60	5.15	3.12	0.10
46.20	5.27	3.22	0.10
46.80	5.39	3.33	0.10
47.40	5.50	3.43	0.10
48.00	**5.62**	**3.54**	0.10
48.60	5.62	3.54	0.00
49.20	5.62	3.54	0.00
49.80	5.62	3.54	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	2.31 cfs @	41.45 hrs,	Volume=	2.833 af
Outflow	=	0.92 cfs @	48.37 hrs,	Volume=	1.548 af, Atten= 60%, Lag= 414.7 min
Primary	=	0.92 cfs @	48.37 hrs,	Volume=	1.548 af
Secondary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Peak Elev= 673.18' @ 48.37 hrs Surf.Area= 31,078 sf Storage= 61,078 cf

Plug-Flow detention time= 362.3 min calculated for 1.545 af (55% of inflow)
Center-of-Mass det. time= (not calculated: outflow precedes inflow)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.92 cfs @ 48.37 hrs HW=673.18' (Free Discharge)
└─**1=Orifice/Grate** (Orifice Controls 0.92 cfs @ 8.33 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├─**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└─**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└─**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
1.20	0.00	0	670.00	0.00	0.00	0.00	0.00
2.40	0.00	0	670.00	0.00	0.00	0.00	0.00
3.60	0.00	0	670.00	0.00	0.00	0.00	0.00
4.80	0.00	0	670.00	0.00	0.00	0.00	0.00
6.00	0.00	0	670.00	0.00	0.00	0.00	0.00
7.20	0.00	0	670.00	0.00	0.00	0.00	0.00
8.40	0.01	9	670.00	0.00	0.00	0.00	0.00
9.60	0.04	143	670.02	0.00	0.00	0.00	0.00
10.80	0.09	437	670.05	0.01	0.01	0.00	0.00
12.00	0.17	926	670.10	0.03	0.03	0.00	0.00
13.20	0.23	1,584	670.18	0.07	0.07	0.00	0.00
14.40	0.28	2,240	670.25	0.13	0.13	0.00	0.00
15.60	0.31	2,820	670.32	0.19	0.19	0.00	0.00
16.80	0.34	3,311	670.37	0.23	0.23	0.00	0.00
18.00	0.36	3,775	670.42	0.25	0.25	0.00	0.00
19.20	0.38	4,222	670.46	0.28	0.28	0.00	0.00
20.40	0.40	4,660	670.50	0.30	0.30	0.00	0.00
21.60	0.42	5,089	670.55	0.32	0.32	0.00	0.00
22.80	0.43	5,510	670.59	0.34	0.34	0.00	0.00
24.00	0.45	5,921	670.63	0.35	0.35	0.00	0.00
25.20	0.50	6,380	670.67	0.37	0.37	0.00	0.00
26.40	0.58	7,059	670.74	0.40	0.40	0.00	0.00
27.60	0.57	7,867	670.78	0.41	0.41	0.00	0.00
28.80	0.52	8,452	670.81	0.42	0.42	0.00	0.00
30.00	0.56	8,896	670.83	0.43	0.43	0.00	0.00
31.20	0.64	9,604	670.87	0.44	0.44	0.00	0.00
32.40	0.78	10,684	670.92	0.45	0.45	0.00	0.00
33.60	0.94	12,355	671.00	0.48	0.48	0.00	0.00
34.80	1.01	14,501	671.10	0.51	0.51	0.00	0.00
36.00	1.04	16,671	671.20	0.54	0.54	0.00	0.00
37.20	1.17	18,973	671.31	0.56	0.56	0.00	0.00
38.40	1.35	21,884	671.44	0.59	0.59	0.00	0.00
39.60	1.72	25,705	671.61	0.63	0.63	0.00	0.00
40.80	**2.19**	31,204	671.85	0.69	0.69	0.00	0.00
42.00	**2.30**	37,994	672.15	0.75	0.75	0.00	0.00
43.20	2.25	44,515	672.44	0.80	0.80	0.00	0.00
44.40	2.00	50,328	672.70	0.84	0.84	0.00	0.00
45.60	1.66	54,606	672.89	0.87	0.87	0.00	0.00
46.80	1.56	57,613	673.02	0.90	0.90	0.00	0.00
48.00	1.56	**60,452**	**673.15**	**0.92**	**0.92**	0.00	0.00
49.20	0.00	**59,074**	**673.09**	**0.91**	**0.91**	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	1.27 cfs @	41.43 hrs, Volume=	1.445 af
Outflow	=	1.22 cfs @	43.51 hrs, Volume=	1.444 af, Atten= 4%, Lag= 124.7 min
Primary	=	1.10 cfs @	43.51 hrs, Volume=	1.110 af
Secondary	=	0.12 cfs @	43.51 hrs, Volume=	0.334 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-50.04 hrs, dt= 0.12 hrs
Peak Elev= 677.76' @ 43.51 hrs Surf.Area= 2,912 sf Storage= 2,503 cf

Plug-Flow detention time= 21.7 min calculated for 1.444 af (100% of inflow)
Center-of-Mass det. time= 21.3 min (2,262.8 - 2,241.5)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=1.10 cfs @ 43.51 hrs HW=677.76' (Free Discharge)
↑—1=**Orifice/Grate** (Orifice Controls 1.10 cfs @ 4.79 fps)
└—2=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.12 cfs @ 43.51 hrs HW=677.76' TW=672.51' (Dynamic Tailwater)
↑—4=**Orifice/Grate** (Orifice Controls 0.12 cfs @ 9.86 fps)
└—5=**Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—3=**Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
1.20	0.00	0	670.75	0.00	0.00	0.00	0.00
2.40	0.00	0	670.75	0.00	0.00	0.00	0.00
3.60	0.00	0	670.75	0.00	0.00	0.00	0.00
4.80	0.00	0	670.75	0.00	0.00	0.00	0.00
6.00	0.00	0	670.75	0.00	0.00	0.00	0.00
7.20	0.00	0	670.75	0.00	0.00	0.00	0.00
8.40	0.01	7	671.22	0.00	0.00	0.00	0.00
9.60	0.02	37	673.41	0.00	0.00	0.00	0.00
10.80	0.04	42	673.78	0.03	0.00	0.03	0.00
12.00	0.06	53	674.53	0.06	0.00	0.06	0.00
13.20	0.08	66	675.43	0.08	0.00	0.08	0.00
14.40	0.10	78	676.35	0.10	0.00	0.10	0.00
15.60	0.12	93	676.56	0.12	0.01	0.10	0.00
16.80	0.13	102	676.59	0.13	0.03	0.10	0.00
18.00	0.15	109	676.61	0.14	0.04	0.10	0.00
19.20	0.16	120	676.63	0.16	0.05	0.10	0.00
20.40	0.17	129	676.64	0.17	0.06	0.10	0.00
21.60	0.18	136	676.66	0.18	0.07	0.10	0.00
22.80	0.19	143	676.67	0.19	0.08	0.10	0.00
24.00	0.20	148	676.67	0.20	0.09	0.10	0.00
25.20	0.23	167	676.70	0.22	0.12	0.10	0.00
26.40	0.28	204	676.74	0.27	0.16	0.11	0.00
27.60	0.27	209	676.74	0.27	0.17	0.11	0.00
28.80	0.24	186	676.72	0.24	0.14	0.10	0.00
30.00	0.26	195	676.73	0.26	0.15	0.11	0.00
31.20	0.31	231	676.76	0.30	0.20	0.11	0.00
32.40	0.39	293	676.81	0.37	0.26	0.11	0.00
33.60	0.49	380	676.88	0.46	0.36	0.11	0.00
34.80	0.52	440	676.91	0.52	0.41	0.11	0.00
36.00	0.54	456	676.92	0.53	0.42	0.11	0.00
37.20	0.62	522	676.96	0.59	0.48	0.11	0.00
38.40	0.72	671	677.03	0.68	0.57	0.11	0.00
39.60	0.94	1,000	677.18	0.82	0.71	0.11	0.00
40.80	**1.21**	1,638	677.44	1.03	0.91	0.12	0.00
42.00	**1.26**	2,288	677.68	1.18	1.06	0.12	0.00
43.20	1.24	**2,493**	**677.76**	**1.22**	**1.10**	**0.12**	0.00
44.40	1.09	**2,340**	**677.70**	**1.19**	**1.07**	**0.12**	0.00
45.60	0.89	1,740	677.48	1.05	0.94	0.12	0.00
46.80	0.84	1,205	677.27	0.90	0.78	0.11	0.00
48.00	0.84	1,082	677.22	0.85	0.74	0.11	0.00
49.20	0.00	37	673.39	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.70 cfs @ 61.66 hrs, Volume= 1.207 af, Depth= 4.14"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=6.05"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.01	0.00	0.00
2.40	0.03	0.00	0.00
3.60	0.06	0.00	0.00
4.80	0.11	0.00	0.00
6.00	0.16	0.00	0.00
7.20	0.22	0.00	0.00
8.40	0.28	0.00	0.00
9.60	0.35	0.00	0.00
10.80	0.41	0.00	0.00
12.00	0.47	0.00	0.01
13.20	0.52	0.01	0.01
14.40	0.57	0.01	0.02
15.60	0.61	0.02	0.02
16.80	0.67	0.03	0.03
18.00	0.72	0.04	0.04
19.20	0.79	0.06	0.05
20.40	0.85	0.08	0.06
21.60	0.91	0.10	0.06
22.80	0.98	0.12	0.07
24.00	1.04	0.15	0.08
25.20	1.10	0.18	0.08
26.40	1.17	0.20	0.09
27.60	1.23	0.23	0.09
28.80	1.29	0.27	0.09
30.00	1.35	0.30	0.10
31.20	1.42	0.33	0.10
32.40	1.48	0.37	0.10
33.60	1.54	0.40	0.11
34.80	1.61	0.44	0.11
36.00	1.67	0.48	0.11
37.20	1.74	0.52	0.13
38.40	1.81	0.57	0.14
39.60	1.89	0.62	0.16
40.80	1.97	0.68	0.16
42.00	2.04	0.73	0.14
43.20	2.11	0.77	0.13
44.40	2.18	0.82	0.14
45.60	2.25	0.87	0.16
46.80	2.33	0.93	0.18
48.00	2.42	1.00	0.21
49.20	2.53	1.08	0.24
50.40	2.65	1.17	0.28
51.60	2.77	1.27	0.29
52.80	2.90	1.37	0.29
54.00	3.03	1.47	0.30
55.20	3.16	1.57	0.33
56.40	3.31	1.70	0.37
57.60	3.47	1.83	0.41
58.80	3.65	1.99	0.49
60.00	3.87	2.18	0.58
61.20	4.13	2.40	**0.68**
62.40	4.40	2.63	**0.69**
63.60	4.66	2.87	0.68
64.80	4.92	3.10	0.67
66.00	5.15	3.31	0.61
67.20	5.36	3.51	0.54
68.40	5.55	3.67	0.47
69.60	5.71	3.83	0.46
70.80	5.88	3.98	0.46
72.00	**6.05**	**4.14**	0.46
73.20	6.05	4.14	0.00
74.40	6.05	4.14	0.00

Summary for Subcatchment 7S: South Property


Runoff = 1.50 cfs @ 61.84 hrs, Volume= 2.586 af, Depth= 4.14"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=6.05"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.01	0.00	0.00
2.40	0.03	0.00	0.00
3.60	0.06	0.00	0.00
4.80	0.11	0.00	0.00
6.00	0.16	0.00	0.00
7.20	0.22	0.00	0.00
8.40	0.28	0.00	0.00
9.60	0.35	0.00	0.00
10.80	0.41	0.00	0.00
12.00	0.47	0.00	0.01
13.20	0.52	0.01	0.03
14.40	0.57	0.01	0.04
15.60	0.61	0.02	0.05
16.80	0.67	0.03	0.07
18.00	0.72	0.04	0.09
19.20	0.79	0.06	0.11
20.40	0.85	0.08	0.12
21.60	0.91	0.10	0.14
22.80	0.98	0.12	0.15
24.00	1.04	0.15	0.16
25.20	1.10	0.18	0.17
26.40	1.17	0.20	0.18
27.60	1.23	0.23	0.19
28.80	1.29	0.27	0.20
30.00	1.35	0.30	0.21
31.20	1.42	0.33	0.22
32.40	1.48	0.37	0.22
33.60	1.54	0.40	0.23
34.80	1.61	0.44	0.24
36.00	1.67	0.48	0.24
37.20	1.74	0.52	0.27
38.40	1.81	0.57	0.30
39.60	1.89	0.62	0.34
40.80	1.97	0.68	0.34
42.00	2.04	0.73	0.31
43.20	2.11	0.77	0.29
44.40	2.18	0.82	0.30
45.60	2.25	0.87	0.34
46.80	2.33	0.93	0.38
48.00	2.42	1.00	0.44
49.20	2.53	1.08	0.51
50.40	2.65	1.17	0.59
51.60	2.77	1.27	0.62
52.80	2.90	1.37	0.63
54.00	3.03	1.47	0.64
55.20	3.16	1.57	0.70
56.40	3.31	1.70	0.78
57.60	3.47	1.83	0.86
58.80	3.65	1.99	1.03
60.00	3.87	2.18	1.23
61.20	4.13	2.40	**1.44**
62.40	4.40	2.63	**1.49**
63.60	4.66	2.87	1.47
64.80	4.92	3.10	1.44
66.00	5.15	3.31	1.33
67.20	5.36	3.51	1.18
68.40	5.55	3.67	1.02
69.60	5.71	3.83	0.98
70.80	5.88	3.98	0.98
72.00	**6.05**	**4.14**	0.98
73.20	6.05	4.14	0.00
74.40	6.05	4.14	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.23 cfs @ 62.09 hrs, Volume= 0.393 af, Depth= 3.93"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=6.05"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.01	0.00	0.00
2.40	0.03	0.00	0.00
3.60	0.06	0.00	0.00
4.80	0.11	0.00	0.00
6.00	0.16	0.00	0.00
7.20	0.22	0.00	0.00
8.40	0.28	0.00	0.00
9.60	0.35	0.00	0.00
10.80	0.41	0.00	0.00
12.00	0.47	0.00	0.00
13.20	0.52	0.00	0.00
14.40	0.57	0.00	0.00
15.60	0.61	0.01	0.00
16.80	0.67	0.02	0.01
18.00	0.72	0.03	0.01
19.20	0.79	0.04	0.01
20.40	0.85	0.05	0.02
21.60	0.91	0.07	0.02
22.80	0.98	0.09	0.02
24.00	1.04	0.11	0.02
25.20	1.10	0.13	0.02
26.40	1.17	0.16	0.03
27.60	1.23	0.19	0.03
28.80	1.29	0.21	0.03
30.00	1.35	0.24	0.03
31.20	1.42	0.27	0.03
32.40	1.48	0.30	0.03
33.60	1.54	0.34	0.03
34.80	1.61	0.37	0.03
36.00	1.67	0.41	0.04
37.20	1.74	0.44	0.04
38.40	1.81	0.49	0.04
39.60	1.89	0.54	0.05
40.80	1.97	0.59	0.05
42.00	2.04	0.63	0.05
43.20	2.11	0.68	0.04
44.40	2.18	0.72	0.04
45.60	2.25	0.77	0.05
46.80	2.33	0.82	0.06
48.00	2.42	0.89	0.06
49.20	2.53	0.96	0.08
50.40	2.65	1.05	0.09
51.60	2.77	1.14	0.09
52.80	2.90	1.24	0.10
54.00	3.03	1.33	0.10
55.20	3.16	1.44	0.11
56.40	3.31	1.55	0.12
57.60	3.47	1.68	0.13
58.80	3.65	1.83	0.15
60.00	3.87	2.01	0.19
61.20	4.13	2.23	**0.22**
62.40	4.40	2.46	**0.23**
63.60	4.66	2.69	0.23
64.80	4.92	2.91	0.23
66.00	5.15	3.12	0.21
67.20	5.36	3.31	0.19
68.40	5.55	3.47	0.16
69.60	5.71	3.62	0.15
70.80	5.88	3.78	0.15
72.00	**6.05**	**3.93**	0.15
73.20	6.05	3.93	0.00
74.40	6.05	3.93	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.11 cfs @ 61.49 hrs, Volume= 0.180 af, Depth= 3.93"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=6.05"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
0.00	0.00	0.00	0.00
1.20	0.01	0.00	0.00
2.40	0.03	0.00	0.00
3.60	0.06	0.00	0.00
4.80	0.11	0.00	0.00
6.00	0.16	0.00	0.00
7.20	0.22	0.00	0.00
8.40	0.28	0.00	0.00
9.60	0.35	0.00	0.00
10.80	0.41	0.00	0.00
12.00	0.47	0.00	0.00
13.20	0.52	0.00	0.00
14.40	0.57	0.00	0.00
15.60	0.61	0.01	0.00
16.80	0.67	0.02	0.00
18.00	0.72	0.03	0.01
19.20	0.79	0.04	0.01
20.40	0.85	0.05	0.01
21.60	0.91	0.07	0.01
22.80	0.98	0.09	0.01
24.00	1.04	0.11	0.01
25.20	1.10	0.13	0.01
26.40	1.17	0.16	0.01
27.60	1.23	0.19	0.01
28.80	1.29	0.21	0.01
30.00	1.35	0.24	0.01
31.20	1.42	0.27	0.01
32.40	1.48	0.30	0.01
33.60	1.54	0.34	0.02
34.80	1.61	0.37	0.02
36.00	1.67	0.41	0.02
37.20	1.74	0.44	0.02
38.40	1.81	0.49	0.02
39.60	1.89	0.54	0.02
40.80	1.97	0.59	0.02
42.00	2.04	0.63	0.02
43.20	2.11	0.68	0.02
44.40	2.18	0.72	0.02
45.60	2.25	0.77	0.02
46.80	2.33	0.82	0.03
48.00	2.42	0.89	0.03
49.20	2.53	0.96	0.04
50.40	2.65	1.05	0.04
51.60	2.77	1.14	0.04
52.80	2.90	1.24	0.04
54.00	3.03	1.33	0.04
55.20	3.16	1.44	0.05
56.40	3.31	1.55	0.06
57.60	3.47	1.68	0.06
58.80	3.65	1.83	0.08
60.00	3.87	2.01	0.09
61.20	4.13	2.23	**0.11**
62.40	4.40	2.46	**0.11**
63.60	4.66	2.69	0.10
64.80	4.92	2.91	0.10
66.00	5.15	3.12	0.09
67.20	5.36	3.31	0.08
68.40	5.55	3.47	0.07
69.60	5.71	3.62	0.07
70.80	5.88	3.78	0.07
72.00	**6.05**	**3.93**	0.07
73.20	6.05	3.93	0.00
74.40	6.05	3.93	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.72 cfs @	61.84 hrs, Volume=	3.246 af
Outflow	=	0.87 cfs @	72.30 hrs, Volume=	2.198 af, Atten= 50%, Lag= 627.7 min
Primary	=	0.87 cfs @	72.30 hrs, Volume=	2.198 af
Secondary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Peak Elev= 672.83' @ 72.30 hrs Surf.Area= 30,998 sf Storage= 53,447 cf

Plug-Flow detention time= 393.7 min calculated for 2.198 af (68% of inflow)
Center-of-Mass det. time= 13.2 min (3,257.1 - 3,243.9)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.87 cfs @ 72.30 hrs HW=672.83' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.87 cfs @ 7.83 fps)


Secondary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
2.40	0.00	0	670.00	0.00	0.00	0.00	0.00
4.80	0.00	0	670.00	0.00	0.00	0.00	0.00
7.20	0.00	0	670.00	0.00	0.00	0.00	0.00
9.60	0.00	0	670.00	0.00	0.00	0.00	0.00
12.00	0.01	21	670.00	0.00	0.00	0.00	0.00
14.40	0.04	347	670.04	0.00	0.00	0.00	0.00
16.80	0.11	908	670.10	0.03	0.03	0.00	0.00
19.20	0.18	1,720	670.19	0.09	0.09	0.00	0.00
21.60	0.23	2,448	670.27	0.15	0.15	0.00	0.00
24.00	0.27	3,020	670.34	0.21	0.21	0.00	0.00
26.40	0.30	3,532	670.39	0.24	0.24	0.00	0.00
28.80	0.32	3,991	670.44	0.27	0.27	0.00	0.00
31.20	0.33	4,411	670.48	0.29	0.29	0.00	0.00
33.60	0.35	4,802	670.52	0.31	0.31	0.00	0.00
36.00	0.36	5,168	670.55	0.32	0.32	0.00	0.00
38.40	0.43	5,679	670.60	0.34	0.34	0.00	0.00
40.80	0.46	6,540	670.69	0.38	0.38	0.00	0.00
43.20	0.41	6,993	670.73	0.39	0.39	0.00	0.00
45.60	0.47	7,278	670.76	0.40	0.40	0.00	0.00
48.00	0.57	8,171	670.80	0.42	0.42	0.00	0.00
50.40	0.74	10,090	670.89	0.45	0.45	0.00	0.00
52.80	0.78	12,704	671.02	0.48	0.48	0.00	0.00
55.20	0.85	15,277	671.14	0.52	0.52	0.00	0.00
57.60	1.03	18,740	671.30	0.56	0.56	0.00	0.00
60.00	**1.43**	24,096	671.53	0.62	0.62	0.00	0.00
62.40	**1.71**	32,419	671.90	0.70	0.70	0.00	0.00
64.80	1.66	40,670	672.27	0.77	0.77	0.00	0.00
67.20	1.37	47,114	672.55	0.82	0.82	0.00	0.00
69.60	1.16	50,560	672.71	0.84	0.84	0.00	0.00
72.00	1.16	**53,200**	**672.82**	**0.86**	**0.86**	0.00	0.00
74.40	0.00	**47,787**	**672.58**	**0.82**	**0.82**	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.93 cfs @	61.81 hrs, Volume=	1.600 af
Outflow	=	0.92 cfs @	63.33 hrs, Volume=	1.599 af, Atten= 1%, Lag= 90.9 min
Primary	=	0.80 cfs @	63.33 hrs, Volume=	1.119 af
Secondary	=	0.11 cfs @	63.33 hrs, Volume=	0.480 af
Tertiary	=	0.00 cfs @	0.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 0.00-75.00 hrs, dt= 0.12 hrs
Peak Elev= 677.29' @ 63.33 hrs Surf.Area= 2,405 sf Storage= 1,265 cf

Plug-Flow detention time= 16.6 min calculated for 1.599 af (100% of inflow)
Center-of-Mass det. time= 16.1 min (3,349.5 - 3,333.4)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.80 cfs @ 63.33 hrs HW=677.29' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 0.80 cfs @ 3.48 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 63.33 hrs HW=677.29' TW=672.05' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 9.30 fps)
└—**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 0.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
0.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
2.40	0.00	0	670.75	0.00	0.00	0.00	0.00
4.80	0.00	0	670.75	0.00	0.00	0.00	0.00
7.20	0.00	0	670.75	0.00	0.00	0.00	0.00
9.60	0.00	0	670.75	0.00	0.00	0.00	0.00
12.00	0.01	12	671.63	0.00	0.00	0.00	0.00
14.40	0.02	37	673.40	0.00	0.00	0.00	0.00
16.80	0.04	45	673.98	0.04	0.00	0.04	0.00
19.20	0.07	56	674.74	0.06	0.00	0.06	0.00
21.60	0.08	66	675.46	0.08	0.00	0.08	0.00
24.00	0.10	77	676.22	0.10	0.00	0.10	0.00
26.40	0.11	88	676.55	0.11	0.01	0.10	0.00
28.80	0.12	97	676.58	0.12	0.02	0.10	0.00
31.20	0.13	102	676.60	0.13	0.03	0.10	0.00
33.60	0.14	107	676.61	0.14	0.04	0.10	0.00
36.00	0.15	114	676.62	0.15	0.04	0.10	0.00
38.40	0.19	140	676.66	0.18	0.08	0.10	0.00
40.80	0.21	156	676.69	0.21	0.10	0.10	0.00
43.20	0.18	137	676.66	0.18	0.07	0.10	0.00
45.60	0.21	155	676.69	0.21	0.10	0.10	0.00
48.00	0.27	202	676.74	0.26	0.16	0.11	0.00
50.40	0.37	279	676.80	0.36	0.25	0.11	0.00
52.80	0.39	309	676.83	0.39	0.28	0.11	0.00
55.20	0.43	340	676.85	0.42	0.32	0.11	0.00
57.60	0.54	446	676.92	0.52	0.42	0.11	0.00
60.00	**0.77**	744	677.06	0.71	0.60	0.11	0.00
62.40	**0.93**	**1,237**	**677.28**	**0.91**	**0.79**	**0.11**	0.00
64.80	0.90	**1,235**	**677.28**	**0.91**	**0.79**	**0.11**	0.00
67.20	0.73	904	677.14	0.78	0.67	0.11	0.00
69.60	0.61	557	676.98	0.61	0.50	0.11	0.00
72.00	0.61	557	676.98	0.61	0.50	0.11	0.00
74.40	0.00	38	673.44	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.47 cfs @ 102.44 hrs, Volume= 1.379 af, Depth= 4.73"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.10 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=6.68"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.18	0.00	0.00
12.00	0.24	0.00	0.00
14.00	0.31	0.00	0.00
16.00	0.38	0.00	0.00
18.00	0.45	0.00	0.00
20.00	0.52	0.01	0.01
22.00	0.58	0.01	0.01
24.00	0.63	0.02	0.01
26.00	0.68	0.03	0.02
28.00	0.73	0.04	0.03
30.00	0.80	0.06	0.04
32.00	0.87	0.08	0.04
34.00	0.94	0.11	0.04
36.00	1.01	0.14	0.05
38.00	1.08	0.16	0.05
40.00	1.15	0.20	0.06
42.00	1.22	0.23	0.06
44.00	1.29	0.26	0.06
46.00	1.36	0.30	0.07
48.00	1.43	0.34	0.07
50.00	1.50	0.38	0.07
52.00	1.57	0.42	0.07
54.00	1.64	0.46	0.07
56.00	1.70	0.50	0.08
58.00	1.77	0.55	0.08
60.00	1.84	0.59	0.08
62.00	1.92	0.64	0.09
64.00	2.00	0.69	0.10
66.00	2.09	0.76	0.11
68.00	2.18	0.82	0.11
70.00	2.26	0.88	0.10
72.00	2.33	0.93	0.09
74.00	2.40	0.98	0.10
76.00	2.49	1.05	0.11
78.00	2.57	1.11	0.12
80.00	2.68	1.19	0.15
82.00	2.79	1.28	0.17
84.00	2.92	1.38	0.19
86.00	3.06	1.50	0.20
88.00	3.20	1.61	0.20
90.00	3.34	1.72	0.20
92.00	3.49	1.85	0.23
94.00	3.65	1.98	0.25
96.00	3.83	2.14	0.28
98.00	4.03	2.31	0.34
100.00	4.28	2.53	0.40
102.00	4.56	2.78	**0.47**
104.00	4.86	3.04	**0.47**
106.00	5.15	3.31	0.46
108.00	5.43	3.56	0.45
110.00	5.69	3.80	0.41
112.00	5.92	4.02	0.36
114.00	6.12	4.21	0.31
116.00	6.31	4.38	0.31
118.00	6.49	4.55	0.31
120.00	**6.68**	**4.73**	0.31
122.00	6.68	4.73	0.00
124.00	6.68	4.73	0.00
126.00	6.68	4.73	0.00
128.00	6.68	4.73	0.00
130.00	6.68	4.73	0.00

Summary for Subcatchment 7S: South Property


Runoff = 1.01 cfs @ 102.62 hrs, Volume= 2.954 af, Depth= 4.73"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.10 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=6.68"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.18	0.00	0.00
12.00	0.24	0.00	0.00
14.00	0.31	0.00	0.00
16.00	0.38	0.00	0.00
18.00	0.45	0.00	0.01
20.00	0.52	0.01	0.02
22.00	0.58	0.01	0.03
24.00	0.63	0.02	0.03
26.00	0.68	0.03	0.04
28.00	0.73	0.04	0.06
30.00	0.80	0.06	0.07
32.00	0.87	0.08	0.09
34.00	0.94	0.11	0.10
36.00	1.01	0.14	0.10
38.00	1.08	0.16	0.11
40.00	1.15	0.20	0.12
42.00	1.22	0.23	0.13
44.00	1.29	0.26	0.13
46.00	1.36	0.30	0.14
48.00	1.43	0.34	0.14
50.00	1.50	0.38	0.15
52.00	1.57	0.42	0.15
54.00	1.64	0.46	0.16
56.00	1.70	0.50	0.16
58.00	1.77	0.55	0.17
60.00	1.84	0.59	0.17
62.00	1.92	0.64	0.19
64.00	2.00	0.69	0.22
66.00	2.09	0.76	0.24
68.00	2.18	0.82	0.23
70.00	2.26	0.88	0.21
72.00	2.33	0.93	0.20
74.00	2.40	0.98	0.21
76.00	2.49	1.05	0.24
78.00	2.57	1.11	0.26
80.00	2.68	1.19	0.31
82.00	2.79	1.28	0.36
84.00	2.92	1.38	0.41
86.00	3.06	1.50	0.43
88.00	3.20	1.61	0.43
90.00	3.34	1.72	0.44
92.00	3.49	1.85	0.48
94.00	3.65	1.98	0.54
96.00	3.83	2.14	0.59
98.00	4.03	2.31	0.71
100.00	4.28	2.53	0.85
102.00	4.56	2.78	**0.99**
104.00	4.86	3.04	**1.00**
106.00	5.15	3.31	0.99
108.00	5.43	3.56	0.97
110.00	5.69	3.80	0.88
112.00	5.92	4.02	0.78
114.00	6.12	4.21	0.67
116.00	6.31	4.38	0.65
118.00	6.49	4.55	0.66
120.00	**6.68**	**4.73**	0.66
122.00	6.68	4.73	0.00
124.00	6.68	4.73	0.00
126.00	6.68	4.73	0.00
128.00	6.68	4.73	0.00
130.00	6.68	4.73	0.00

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.16 cfs @ 102.91 hrs, Volume= 0.451 af, Depth= 4.51"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.10 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=6.68"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.18	0.00	0.00
12.00	0.24	0.00	0.00
14.00	0.31	0.00	0.00
16.00	0.38	0.00	0.00
18.00	0.45	0.00	0.00
20.00	0.52	0.00	0.00
22.00	0.58	0.00	0.00
24.00	0.63	0.01	0.00
26.00	0.68	0.02	0.00
28.00	0.73	0.03	0.01
30.00	0.80	0.04	0.01
32.00	0.87	0.06	0.01
34.00	0.94	0.08	0.01
36.00	1.01	0.10	0.01
38.00	1.08	0.13	0.02
40.00	1.15	0.15	0.02
42.00	1.22	0.18	0.02
44.00	1.29	0.21	0.02
46.00	1.36	0.24	0.02
48.00	1.43	0.28	0.02
50.00	1.50	0.31	0.02
52.00	1.57	0.35	0.02
54.00	1.64	0.39	0.02
56.00	1.70	0.43	0.02
58.00	1.77	0.47	0.02
60.00	1.84	0.51	0.03
62.00	1.92	0.55	0.03
64.00	2.00	0.60	0.03
66.00	2.09	0.66	0.04
68.00	2.18	0.72	0.03
70.00	2.26	0.77	0.03
72.00	2.33	0.82	0.03
74.00	2.40	0.87	0.03
76.00	2.49	0.93	0.04
78.00	2.57	1.00	0.04
80.00	2.68	1.07	0.05
82.00	2.79	1.16	0.05
84.00	2.92	1.25	0.06
86.00	3.06	1.36	0.06
88.00	3.20	1.47	0.07
90.00	3.34	1.58	0.07
92.00	3.49	1.70	0.07
94.00	3.65	1.83	0.08
96.00	3.83	1.98	0.09
98.00	4.03	2.15	0.11
100.00	4.28	2.36	0.13
102.00	4.56	2.60	**0.15**
104.00	4.86	2.86	**0.16**
106.00	5.15	3.11	0.15
108.00	5.43	3.37	0.15
110.00	5.69	3.60	0.14
112.00	5.92	3.81	0.12
114.00	6.12	4.00	0.11
116.00	6.31	4.17	0.10
118.00	6.49	4.34	0.10
120.00	**6.68**	**4.51**	0.10
122.00	6.68	4.51	0.00
124.00	6.68	4.51	0.00
126.00	6.68	4.51	0.00
128.00	6.68	4.51	0.00
130.00	6.68	4.51	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.07 cfs @ 102.27 hrs, Volume= 0.207 af, Depth= 4.51"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.10 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=6.68"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.18	0.00	0.00
12.00	0.24	0.00	0.00
14.00	0.31	0.00	0.00
16.00	0.38	0.00	0.00
18.00	0.45	0.00	0.00
20.00	0.52	0.00	0.00
22.00	0.58	0.00	0.00
24.00	0.63	0.01	0.00
26.00	0.68	0.02	0.00
28.00	0.73	0.03	0.00
30.00	0.80	0.04	0.00
32.00	0.87	0.06	0.01
34.00	0.94	0.08	0.01
36.00	1.01	0.10	0.01
38.00	1.08	0.13	0.01
40.00	1.15	0.15	0.01
42.00	1.22	0.18	0.01
44.00	1.29	0.21	0.01
46.00	1.36	0.24	0.01
48.00	1.43	0.28	0.01
50.00	1.50	0.31	0.01
52.00	1.57	0.35	0.01
54.00	1.64	0.39	0.01
56.00	1.70	0.43	0.01
58.00	1.77	0.47	0.01
60.00	1.84	0.51	0.01
62.00	1.92	0.55	0.01
64.00	2.00	0.60	0.01
66.00	2.09	0.66	0.02
68.00	2.18	0.72	0.02
70.00	2.26	0.77	0.01
72.00	2.33	0.82	0.01
74.00	2.40	0.87	0.01
76.00	2.49	0.93	0.02
78.00	2.57	1.00	0.02
80.00	2.68	1.07	0.02
82.00	2.79	1.16	0.03
84.00	2.92	1.25	0.03
86.00	3.06	1.36	0.03
88.00	3.20	1.47	0.03
90.00	3.34	1.58	0.03
92.00	3.49	1.70	0.03
94.00	3.65	1.83	0.04
96.00	3.83	1.98	0.04
98.00	4.03	2.15	0.05
100.00	4.28	2.36	0.06
102.00	4.56	2.60	**0.07**
104.00	4.86	2.86	**0.07**
106.00	5.15	3.11	0.07
108.00	5.43	3.37	0.07
110.00	5.69	3.60	0.06
112.00	5.92	3.81	0.06
114.00	6.12	4.00	0.05
116.00	6.31	4.17	0.05
118.00	6.49	4.34	0.05
120.00	**6.68**	**4.51**	0.05
122.00	6.68	4.51	0.00
124.00	6.68	4.51	0.00
126.00	6.68	4.51	0.00
128.00	6.68	4.51	0.00
130.00	6.68	4.51	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	1.19 cfs @ 102.62 hrs,	Volume=	3.909 af
Outflow	=	0.77 cfs @ 120.17 hrs,	Volume=	3.503 af, Atten= 36%, Lag= 1,053.1 min
Primary	=	0.77 cfs @ 120.17 hrs,	Volume=	3.503 af
Secondary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs,	Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.10 hrs
Peak Elev= 672.26' @ 120.17 hrs Surf.Area= 30,867 sf Storage= 40,524 cf

Plug-Flow detention time= 457.5 min calculated for 3.500 af (90% of inflow)
Center-of-Mass det. time= 259.1 min (5,588.8 - 5,329.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.77 cfs @ 120.17 hrs HW=672.26' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.77 cfs @ 6.94 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
15.00	0.00	0	670.00	0.00	0.00	0.00	0.00
20.00	0.02	139	670.02	0.00	0.00	0.00	0.00
25.00	0.04	818	670.09	0.02	0.02	0.00	0.00
30.00	0.12	1,590	670.18	0.07	0.07	0.00	0.00
35.00	0.17	2,275	670.25	0.14	0.14	0.00	0.00
40.00	0.20	2,705	670.30	0.18	0.18	0.00	0.00
45.00	0.23	3,047	670.34	0.21	0.21	0.00	0.00
50.00	0.25	3,384	670.38	0.23	0.23	0.00	0.00
55.00	0.27	3,736	670.41	0.25	0.25	0.00	0.00
60.00	0.28	4,057	670.44	0.27	0.27	0.00	0.00
65.00	0.35	4,633	670.50	0.30	0.30	0.00	0.00
70.00	0.33	5,273	670.56	0.33	0.33	0.00	0.00
75.00	0.34	5,252	670.56	0.33	0.33	0.00	0.00
80.00	0.43	6,026	670.64	0.36	0.36	0.00	0.00
85.00	0.56	8,065	670.79	0.41	0.41	0.00	0.00
90.00	0.57	10,437	670.91	0.45	0.45	0.00	0.00
95.00	0.71	13,413	671.05	0.49	0.49	0.00	0.00
100.00	**1.02**	19,094	671.31	0.56	0.56	0.00	0.00
105.00	**1.18**	28,723	671.74	0.66	0.66	0.00	0.00
110.00	1.05	36,634	672.09	0.73	0.73	0.00	0.00
115.00	0.81	39,637	672.23	0.76	0.76	0.00	0.00
120.00	0.81	**40,498**	**672.26**	**0.77**	**0.77**	0.00	0.00
125.00	0.00	**28,859**	**671.75**	**0.66**	**0.66**	0.00	0.00
130.00	0.00	17,908	671.26	0.55	0.55	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.63 cfs @ 102.60 hrs, Volume=	1.829 af
Outflow	=	0.63 cfs @ 103.27 hrs, Volume=	1.829 af, Atten= 0%, Lag= 40.5 min
Primary	=	0.52 cfs @ 103.27 hrs, Volume=	1.080 af
Secondary	=	0.11 cfs @ 103.27 hrs, Volume=	0.749 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-130.00 hrs, dt= 0.10 hrs
Peak Elev= 676.99' @ 103.27 hrs Surf.Area= 2,031 sf Storage= 578 cf

Plug-Flow detention time= 13.9 min calculated for 1.829 af (100% of inflow)
Center-of-Mass det. time= 13.1 min (5,513.8 - 5,500.7)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.52 cfs @ 103.27 hrs HW=676.99' (Free Discharge)
↑—**1=Orifice/Grate** (Orifice Controls 0.52 cfs @ 2.38 fps)
└—**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 103.27 hrs HW=676.99' TW=671.59' (Dynamic Tailwater)
↑—**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.91 fps)
└—**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
↑—**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
15.00	0.00	0	670.75	0.00	0.00	0.00	0.00
20.00	0.01	37	673.37	0.00	0.00	0.00	0.00
25.00	0.02	39	673.52	0.00	0.00	0.00	0.00
30.00	0.04	47	674.11	0.04	0.00	0.04	0.00
35.00	0.06	54	674.58	0.06	0.00	0.06	0.00
40.00	0.07	60	675.05	0.07	0.00	0.07	0.00
45.00	0.08	67	675.51	0.08	0.00	0.08	0.00
50.00	0.09	73	675.95	0.09	0.00	0.09	0.00
55.00	0.10	78	676.35	0.10	0.00	0.10	0.00
60.00	0.11	84	676.53	0.10	0.00	0.10	0.00
65.00	0.14	106	676.61	0.14	0.04	0.10	0.00
70.00	0.13	103	676.60	0.13	0.03	0.10	0.00
75.00	0.14	106	676.61	0.14	0.04	0.10	0.00
80.00	0.19	144	676.67	0.19	0.08	0.10	0.00
85.00	0.26	200	676.73	0.26	0.16	0.11	0.00
90.00	0.27	207	676.74	0.27	0.16	0.11	0.00
95.00	0.35	271	676.80	0.35	0.24	0.11	0.00
100.00	**0.53**	**439**	**676.91**	**0.52**	**0.41**	**0.11**	0.00
105.00	**0.62**	**570**	**676.98**	**0.62**	**0.51**	**0.11**	0.00
110.00	0.55	485	676.94	0.56	0.45	0.11	0.00
115.00	0.41	326	676.84	0.41	0.30	0.11	0.00
120.00	0.41	328	676.84	0.41	0.30	0.11	0.00
125.00	0.00	37	673.43	0.00	0.00	0.00	0.00
130.00	0.00	37	673.43	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

Summary for Subcatchment 1S: North Property


Runoff = 0.30 cfs @ 204.40 hrs, Volume= 1.813 af, Depth= 6.22"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=8.25"

Area (ac)	CN	Description
3.500	83	1/4 acre lots, 38% imp, HSG C
2.170		62.00% Pervious Area
1.330		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	550	0.0120	0.56		**Lag/CN Method,**

Subcatchment 1S: North Property



Hydrograph for Subcatchment 1S: North Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.06	0.00	0.00
12.50	0.09	0.00	0.00
15.00	0.13	0.00	0.00
17.50	0.17	0.00	0.00
20.00	0.22	0.00	0.00
22.50	0.27	0.00	0.00
25.00	0.32	0.00	0.00
27.50	0.38	0.00	0.00
30.00	0.43	0.00	0.00
32.50	0.48	0.00	0.00
35.00	0.54	0.01	0.01
37.50	0.59	0.01	0.01
40.00	0.64	0.02	0.01
42.50	0.69	0.03	0.01
45.00	0.73	0.04	0.01
47.50	0.77	0.05	0.01
50.00	0.80	0.06	0.02
52.50	0.84	0.08	0.02
55.00	0.89	0.09	0.02
57.50	0.94	0.11	0.03
60.00	0.99	0.13	0.03
62.50	1.04	0.15	0.03
65.00	1.10	0.17	0.03
67.50	1.15	0.20	0.03
70.00	1.20	0.22	0.04
72.50	1.26	0.25	0.04
75.00	1.31	0.28	0.04
77.50	1.36	0.30	0.04
80.00	1.42	0.33	0.04
82.50	1.47	0.36	0.04
85.00	1.53	0.39	0.04
87.50	1.58	0.43	0.04
90.00	1.63	0.46	0.05
92.50	1.69	0.49	0.05
95.00	1.74	0.52	0.05
97.50	1.79	0.56	0.05
100.00	1.85	0.59	0.05
102.50	1.90	0.63	0.05
105.00	1.96	0.66	0.05
107.50	2.01	0.70	0.05
110.00	2.06	0.74	0.05
112.50	2.12	0.78	0.05
115.00	2.17	0.81	0.05
117.50	2.22	0.85	0.05
120.00	2.28	0.89	0.06
122.50	2.33	0.93	0.06
125.00	2.39	0.98	0.06
127.50	2.46	1.02	0.07
130.00	2.52	1.07	0.07
132.50	2.59	1.13	0.08
135.00	2.66	1.18	0.07
137.50	2.73	1.23	0.07
140.00	2.79	1.28	0.07
142.50	2.85	1.32	0.06
145.00	2.90	1.37	0.06
147.50	2.96	1.41	0.07
150.00	3.02	1.46	0.07
152.50	3.08	1.51	0.08
155.00	3.15	1.57	0.08
157.50	3.22	1.63	0.09
160.00	3.30	1.69	0.10
162.50	3.39	1.77	0.11
165.00	3.49	1.85	0.12
167.50	3.59	1.93	0.13
170.00	3.70	2.02	0.13
172.50	3.80	2.12	0.13
175.00	3.91	2.21	0.13
177.50	4.02	2.30	0.13
180.00	4.13	2.40	0.13
182.50	4.24	2.49	0.14
185.00	4.35	2.60	0.15
187.50	4.48	2.71	0.16
190.00	4.61	2.83	0.17
192.50	4.76	2.95	0.18
195.00	4.91	3.09	0.21
197.50	5.09	3.25	0.23
200.00	5.28	3.43	0.26
202.50	5.49	3.62	**0.28**
205.00	5.72	3.83	**0.30**
207.50	5.95	4.05	0.30
210.00	6.18	4.26	0.29
212.50	6.40	4.46	0.29
215.00	6.62	4.67	0.29
217.50	6.83	4.87	0.28
220.00	7.03	5.05	0.26
222.50	7.21	5.23	0.24
225.00	7.38	5.39	0.22
227.50	7.53	5.53	0.20
230.00	7.68	5.67	0.19
232.50	7.82	5.81	0.19
235.00	7.96	5.94	0.19
237.50	8.11	6.08	0.19
240.00	**8.25**	**6.22**	0.19
242.50	8.25	6.22	0.00
245.00	8.25	6.22	0.00
247.50	8.25	6.22	0.00
250.00	8.25	6.22	0.00

Summary for Subcatchment 7S: South Property


Runoff = 0.65 cfs @ 204.58 hrs, Volume= 3.885 af, Depth= 6.22"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=8.25"

Area (ac)	CN	Description
7.500	83	1/4 acre lots, 38% imp, HSG C
4.650		62.00% Pervious Area
2.850		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
23.9	1,020	0.0150	0.71		**Lag/CN Method,**

Subcatchment 7S: South Property



Hydrograph for Subcatchment 7S: South Property

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)	Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.06	0.00	0.00	140.00	2.79	1.28	0.14
12.50	0.09	0.00	0.00	142.50	2.85	1.32	0.14
15.00	0.13	0.00	0.00	145.00	2.90	1.37	0.13
17.50	0.17	0.00	0.00	147.50	2.96	1.41	0.14
20.00	0.22	0.00	0.00	150.00	3.02	1.46	0.15
22.50	0.27	0.00	0.00	152.50	3.08	1.51	0.16
25.00	0.32	0.00	0.00	155.00	3.15	1.57	0.17
27.50	0.38	0.00	0.00	157.50	3.22	1.63	0.19
30.00	0.43	0.00	0.00	160.00	3.30	1.69	0.21
32.50	0.48	0.00	0.01	162.50	3.39	1.77	0.23
35.00	0.54	0.01	0.02	165.00	3.49	1.85	0.25
37.50	0.59	0.01	0.02	167.50	3.59	1.93	0.27
40.00	0.64	0.02	0.03	170.00	3.70	2.02	0.28
42.50	0.69	0.03	0.03	172.50	3.80	2.12	0.28
45.00	0.73	0.04	0.03	175.00	3.91	2.21	0.28
47.50	0.77	0.05	0.03	177.50	4.02	2.30	0.28
50.00	0.80	0.06	0.03	180.00	4.13	2.40	0.28
52.50	0.84	0.08	0.04	182.50	4.24	2.49	0.30
55.00	0.89	0.09	0.05	185.00	4.35	2.60	0.32
57.50	0.94	0.11	0.05	187.50	4.48	2.71	0.35
60.00	0.99	0.13	0.06	190.00	4.61	2.83	0.37
62.50	1.04	0.15	0.07	192.50	4.76	2.95	0.39
65.00	1.10	0.17	0.07	195.00	4.91	3.09	0.44
67.50	1.15	0.20	0.07	197.50	5.09	3.25	0.50
70.00	1.20	0.22	0.08	200.00	5.28	3.43	0.55
72.50	1.26	0.25	0.08	202.50	5.49	3.62	**0.61**
75.00	1.31	0.28	0.08	205.00	5.72	3.83	**0.65**
77.50	1.36	0.30	0.09	207.50	5.95	4.05	0.64
80.00	1.42	0.33	0.09	210.00	6.18	4.26	0.63
82.50	1.47	0.36	0.09	212.50	6.40	4.46	0.62
85.00	1.53	0.39	0.09	215.00	6.62	4.67	0.62
87.50	1.58	0.43	0.10	217.50	6.83	4.87	0.59
90.00	1.63	0.46	0.10	220.00	7.03	5.05	0.55
92.50	1.69	0.49	0.10	222.50	7.21	5.23	0.51
95.00	1.74	0.52	0.10	225.00	7.38	5.39	0.47
97.50	1.79	0.56	0.10	227.50	7.53	5.53	0.43
100.00	1.85	0.59	0.11	230.00	7.68	5.67	0.41
102.50	1.90	0.63	0.11	232.50	7.82	5.81	0.41
105.00	1.96	0.66	0.11	235.00	7.96	5.94	0.41
107.50	2.01	0.70	0.11	237.50	8.11	6.08	0.41
110.00	2.06	0.74	0.11	240.00	**8.25**	**6.22**	0.41
112.50	2.12	0.78	0.11	242.50	8.25	6.22	0.00
115.00	2.17	0.81	0.12	245.00	8.25	6.22	0.00
117.50	2.22	0.85	0.12	247.50	8.25	6.22	0.00
120.00	2.28	0.89	0.12	250.00	8.25	6.22	0.00
122.50	2.33	0.93	0.13				
125.00	2.39	0.98	0.14				
127.50	2.46	1.02	0.15				
130.00	2.52	1.07	0.16				
132.50	2.59	1.13	0.16				
135.00	2.66	1.18	0.16				
137.50	2.73	1.23	0.15				

Summary for Subcatchment 8S: Northwood Drive Bypass


Runoff = 0.10 cfs @ 204.83 hrs, Volume= 0.598 af, Depth= 5.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=8.25"

Area (ac)	CN	Description
1.200	81	1/3 acre lots, 30% imp, HSG C
0.840		70.00% Pervious Area
0.360		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
32.5	1,070	0.0100	0.55		**Lag/CN Method, Lag CN**

Subcatchment 8S: Northwood Drive Bypass



Hydrograph for Subcatchment 8S: Northwood Drive Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.06	0.00	0.00
12.50	0.09	0.00	0.00
15.00	0.13	0.00	0.00
17.50	0.17	0.00	0.00
20.00	0.22	0.00	0.00
22.50	0.27	0.00	0.00
25.00	0.32	0.00	0.00
27.50	0.38	0.00	0.00
30.00	0.43	0.00	0.00
32.50	0.48	0.00	0.00
35.00	0.54	0.00	0.00
37.50	0.59	0.01	0.00
40.00	0.64	0.01	0.00
42.50	0.69	0.02	0.00
45.00	0.73	0.03	0.00
47.50	0.77	0.03	0.00
50.00	0.80	0.04	0.00
52.50	0.84	0.05	0.01
55.00	0.89	0.06	0.01
57.50	0.94	0.08	0.01
60.00	0.99	0.09	0.01
62.50	1.04	0.11	0.01
65.00	1.10	0.13	0.01
67.50	1.15	0.15	0.01
70.00	1.20	0.17	0.01
72.50	1.26	0.20	0.01
75.00	1.31	0.22	0.01
77.50	1.36	0.25	0.01
80.00	1.42	0.27	0.01
82.50	1.47	0.30	0.01
85.00	1.53	0.33	0.01
87.50	1.58	0.36	0.01
90.00	1.63	0.39	0.01
92.50	1.69	0.42	0.01
95.00	1.74	0.45	0.01
97.50	1.79	0.48	0.02
100.00	1.85	0.51	0.02
102.50	1.90	0.54	0.02
105.00	1.96	0.58	0.02
107.50	2.01	0.61	0.02
110.00	2.06	0.64	0.02
112.50	2.12	0.68	0.02
115.00	2.17	0.71	0.02
117.50	2.22	0.75	0.02
120.00	2.28	0.79	0.02
122.50	2.33	0.83	0.02
125.00	2.39	0.87	0.02
127.50	2.46	0.91	0.02
130.00	2.52	0.96	0.02
132.50	2.59	1.01	0.02
135.00	2.66	1.06	0.02
137.50	2.73	1.11	0.02
140.00	2.79	1.15	0.02
142.50	2.85	1.20	0.02
145.00	2.90	1.24	0.02
147.50	2.96	1.28	0.02
150.00	3.02	1.33	0.02
152.50	3.08	1.38	0.02
155.00	3.15	1.43	0.03
157.50	3.22	1.49	0.03
160.00	3.30	1.55	0.03
162.50	3.39	1.62	0.03
165.00	3.49	1.70	0.04
167.50	3.59	1.78	0.04
170.00	3.70	1.87	0.04
172.50	3.80	1.96	0.04
175.00	3.91	2.05	0.04
177.50	4.02	2.14	0.04
180.00	4.13	2.23	0.04
182.50	4.24	2.32	0.05
185.00	4.35	2.42	0.05
187.50	4.48	2.53	0.05
190.00	4.61	2.65	0.06
192.50	4.76	2.77	0.06
195.00	4.91	2.91	0.07
197.50	5.09	3.06	0.08
200.00	5.28	3.23	0.09
202.50	5.49	3.42	**0.09**
205.00	5.72	3.63	**0.10**
207.50	5.95	3.84	0.10
210.00	6.18	4.05	0.10
212.50	6.40	4.25	0.10
215.00	6.62	4.45	0.10
217.50	6.83	4.65	0.09
220.00	7.03	4.83	0.09
222.50	7.21	5.00	0.08
225.00	7.38	5.16	0.07
227.50	7.53	5.30	0.07
230.00	7.68	5.44	0.07
232.50	7.82	5.57	0.07
235.00	7.96	5.71	0.07
237.50	8.11	5.84	0.07
240.00	**8.25**	**5.98**	0.07
242.50	8.25	5.98	0.00
245.00	8.25	5.98	0.00
247.50	8.25	5.98	0.00
250.00	8.25	5.98	0.00

Summary for Subcatchment 9S: ODH Subdivision Bypass


Runoff = 0.05 cfs @ 204.25 hrs, Volume= 0.274 af, Depth= 5.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=8.25"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Subcatchment 9S: ODH Subdivision Bypass



Hydrograph for Subcatchment 9S: ODH Subdivision Bypass

Time (hours)	Precip. (inches)	Excess (inches)	Runoff (cfs)
10.00	0.06	0.00	0.00
12.50	0.09	0.00	0.00
15.00	0.13	0.00	0.00
17.50	0.17	0.00	0.00
20.00	0.22	0.00	0.00
22.50	0.27	0.00	0.00
25.00	0.32	0.00	0.00
27.50	0.38	0.00	0.00
30.00	0.43	0.00	0.00
32.50	0.48	0.00	0.00
35.00	0.54	0.00	0.00
37.50	0.59	0.01	0.00
40.00	0.64	0.01	0.00
42.50	0.69	0.02	0.00
45.00	0.73	0.03	0.00
47.50	0.77	0.03	0.00
50.00	0.80	0.04	0.00
52.50	0.84	0.05	0.00
55.00	0.89	0.06	0.00
57.50	0.94	0.08	0.00
60.00	0.99	0.09	0.00
62.50	1.04	0.11	0.00
65.00	1.10	0.13	0.00
67.50	1.15	0.15	0.00
70.00	1.20	0.17	0.00
72.50	1.26	0.20	0.01
75.00	1.31	0.22	0.01
77.50	1.36	0.25	0.01
80.00	1.42	0.27	0.01
82.50	1.47	0.30	0.01
85.00	1.53	0.33	0.01
87.50	1.58	0.36	0.01
90.00	1.63	0.39	0.01
92.50	1.69	0.42	0.01
95.00	1.74	0.45	0.01
97.50	1.79	0.48	0.01
100.00	1.85	0.51	0.01
102.50	1.90	0.54	0.01
105.00	1.96	0.58	0.01
107.50	2.01	0.61	0.01
110.00	2.06	0.64	0.01
112.50	2.12	0.68	0.01
115.00	2.17	0.71	0.01
117.50	2.22	0.75	0.01
120.00	2.28	0.79	0.01
122.50	2.33	0.83	0.01
125.00	2.39	0.87	0.01
127.50	2.46	0.91	0.01
130.00	2.52	0.96	0.01
132.50	2.59	1.01	0.01
135.00	2.66	1.06	0.01
137.50	2.73	1.11	0.01
140.00	2.79	1.15	0.01
142.50	2.85	1.20	0.01
145.00	2.90	1.24	0.01
147.50	2.96	1.28	0.01
150.00	3.02	1.33	0.01
152.50	3.08	1.38	0.01
155.00	3.15	1.43	0.01
157.50	3.22	1.49	0.01
160.00	3.30	1.55	0.01
162.50	3.39	1.62	0.02
165.00	3.49	1.70	0.02
167.50	3.59	1.78	0.02
170.00	3.70	1.87	0.02
172.50	3.80	1.96	0.02
175.00	3.91	2.05	0.02
177.50	4.02	2.14	0.02
180.00	4.13	2.23	0.02
182.50	4.24	2.32	0.02
185.00	4.35	2.42	0.02
187.50	4.48	2.53	0.02
190.00	4.61	2.65	0.03
192.50	4.76	2.77	0.03
195.00	4.91	2.91	0.03
197.50	5.09	3.06	0.04
200.00	5.28	3.23	0.04
202.50	5.49	3.42	**0.04**
205.00	5.72	3.63	**0.05**
207.50	5.95	3.84	0.05
210.00	6.18	4.05	0.05
212.50	6.40	4.25	0.04
215.00	6.62	4.45	0.04
217.50	6.83	4.65	0.04
220.00	7.03	4.83	0.04
222.50	7.21	5.00	0.04
225.00	7.38	5.16	0.03
227.50	7.53	5.30	0.03
230.00	7.68	5.44	0.03
232.50	7.82	5.57	0.03
235.00	7.96	5.71	0.03
237.50	8.11	5.84	0.03
240.00	**8.25**	**5.98**	0.03
242.50	8.25	5.98	0.00
245.00	8.25	5.98	0.00
247.50	8.25	5.98	0.00
250.00	8.25	5.98	0.00

Summary for Pond 3P: Southeast Chambers

Inflow	=	0.80 cfs @ 204.58 hrs, Volume=	5.498 af
Outflow	=	0.64 cfs @ 222.99 hrs, Volume=	5.363 af, Atten= 19%, Lag= 1,104.8 min
Primary	=	0.64 cfs @ 222.99 hrs, Volume=	5.363 af
Secondary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Peak Elev= 671.66' @ 222.99 hrs Surf.Area= 30,728 sf Storage= 26,842 cf

Plug-Flow detention time= 416.5 min calculated for 5.362 af (98% of inflow)
Center-of-Mass det. time= 319.6 min (10,800.6 - 10,481.0)

Volume	Invert	Avail.Storage	Storage Description
#1	670.00'	8,508 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 36,469 cf Overall - 12,835 cf Embedded = 23,634 cf x 36.0% Voids
#2	670.75'	12,835 cf	**Cultec R-902HD @ 727.00' L** Inside #1 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 727.00'L = 12,835.2 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#3	670.00'	6,320 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 22,076 cf Overall - 4,520 cf Embedded = 17,557 cf x 36.0% Voids
#4	670.75'	4,520 cf	**Cultec R-902HD @ 256.00' L** Inside #3 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 256.00'L = 4,519.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#5	670.00'	17,648 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 80,732 cf Overall - 31,708 cf Embedded = 49,023 cf x 36.0% Voids
#6	670.75'	31,708 cf	**Cultec R-902HD @ 1,796.00' L** Inside #5 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 1,796.00'L = 31,708.4 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#7	675.25'	14,060 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 55,345 cf Overall - 16,291 cf Embedded = 39,054 cf x 36.0% Voids
#8	675.75'	16,291 cf	**Cultec R-280HD @ 2,683.00' L** Inside #7 Effective Size= 46.9"W x 26.0"H => 6.07 sf x 2,683.00'L = 16,290.5 cf Overall Size= 47.0"W x 26.5"H x 8.00'L with 1.00' Overlap
#9	670.00'	2,847 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 10,008 cf Overall - 2,101 cf Embedded = 7,907 cf x 36.0% Voids
#10	670.75'	2,101 cf	**Cultec R-902HD @ 119.00' L** Inside #9 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 119.00'L = 2,100.9 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#11	670.34'	4,845 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 17,077 cf Overall - 3,619 cf Embedded = 13,458 cf x 36.0% Voids
#12	671.09'	3,619 cf	**Cultec R-902HD @ 205.00' L** Inside #11 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 205.00'L = 3,619.3 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#13	670.41'	3,242 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 11,529 cf Overall - 2,525 cf Embedded = 9,005 cf x 36.0% Voids
#14	671.16'	2,525 cf	**Cultec R-902HD @ 143.00' L** Inside #13 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 143.00'L = 2,524.7 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
#15	671.37'	5,180 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc) 18,961 cf Overall - 4,573 cf Embedded = 14,388 cf x 36.0% Voids

#16	672.12'	4,573 cf	**Cultec R-902HD @ 259.00' L** Inside #15 Effective Size= 69.8"W x 48.0"H => 17.65 sf x 259.00'L = 4,572.6 cf Overall Size= 78.0"W x 48.0"H x 4.10'L with 0.44' Overlap
		140,821 cf	Total Available Storage

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	6,238	0	0
675.75	6,447	36,469	36,469

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	2,338	0	0
678.90	2,623	22,076	22,076

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	15,163	0	0
675.25	15,592	80,732	80,732

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
675.25	15,163	0	0
678.90	15,163	55,345	55,345

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.00	1,062	0	0
678.90	1,187	10,008	10,008

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.34	1,940	0	0
678.90	2,050	17,077	17,077

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.41	1,310	0	0
678.90	1,406	11,529	11,529

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
671.37	2,362	0	0
678.90	2,674	18,961	18,961

Device	Routing	Invert	Outlet Devices
#1	Primary	670.00'	**4.5" Vert. Orifice/Grate** C= 0.600
#2	Tertiary	678.40'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height


#4 Secondary 673.50' **1.5" Vert. Orifice/Grate** C= 0.600

Primary OutFlow Max=0.64 cfs @ 222.99 hrs HW=671.66' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.64 cfs @ 5.83 fps)


Secondary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' TW=670.75' (Dynamic Tailwater)
├**3=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)
└**4=Orifice/Grate** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.00' (Free Discharge)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Pond 3P: Southeast Chambers



Hydrograph for Pond 3P: Southeast Chambers

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.00	0.00	0.00	**0.00**	**0.00**
15.00	0.00	0	670.00	0.00	0.00	0.00	0.00
20.00	0.00	0	670.00	0.00	0.00	0.00	0.00
25.00	0.00	0	670.00	0.00	0.00	0.00	0.00
30.00	0.00	2	670.00	0.00	0.00	0.00	0.00
35.00	0.02	229	670.03	0.00	0.00	0.00	0.00
40.00	0.04	744	670.08	0.02	0.02	0.00	0.00
45.00	0.05	1,097	670.12	0.04	0.04	0.00	0.00
50.00	0.06	1,244	670.14	0.05	0.05	0.00	0.00
55.00	0.08	1,458	670.16	0.06	0.06	0.00	0.00
60.00	0.10	1,740	670.19	0.09	0.09	0.00	0.00
65.00	0.12	1,973	670.22	0.11	0.11	0.00	0.00
70.00	0.13	2,122	670.24	0.12	0.12	0.00	0.00
75.00	0.14	2,241	670.25	0.13	0.13	0.00	0.00
80.00	0.15	2,344	670.26	0.14	0.14	0.00	0.00
85.00	0.16	2,436	670.27	0.15	0.15	0.00	0.00
90.00	0.17	2,519	670.28	0.16	0.16	0.00	0.00
95.00	0.17	2,594	670.29	0.17	0.17	0.00	0.00
100.00	0.18	2,662	670.30	0.17	0.17	0.00	0.00
105.00	0.18	2,725	670.30	0.18	0.18	0.00	0.00
110.00	0.19	2,783	670.31	0.19	0.19	0.00	0.00
115.00	0.19	2,837	670.32	0.19	0.19	0.00	0.00
120.00	0.20	2,888	670.32	0.20	0.20	0.00	0.00
125.00	0.23	3,076	670.34	0.21	0.21	0.00	0.00
130.00	0.26	3,469	670.38	0.24	0.24	0.00	0.00
135.00	0.27	3,871	670.43	0.26	0.26	0.00	0.00
140.00	0.24	3,793	670.42	0.26	0.26	0.00	0.00
145.00	0.22	3,475	670.39	0.24	0.24	0.00	0.00
150.00	0.26	3,530	670.39	0.24	0.24	0.00	0.00
155.00	0.29	3,917	670.43	0.26	0.26	0.00	0.00
160.00	0.32	4,432	670.48	0.29	0.29	0.00	0.00
165.00	0.37	5,174	670.55	0.32	0.32	0.00	0.00
170.00	0.40	6,046	670.64	0.36	0.36	0.00	0.00
175.00	0.40	6,629	670.70	0.38	0.38	0.00	0.00
180.00	0.41	6,978	670.73	0.39	0.39	0.00	0.00
185.00	0.45	7,507	670.77	0.40	0.40	0.00	0.00
190.00	0.50	8,614	670.82	0.42	0.42	0.00	0.00
195.00	0.58	10,349	670.90	0.45	0.45	0.00	0.00
200.00	**0.70**	13,389	671.05	0.49	0.49	0.00	0.00
205.00	**0.80**	17,638	671.25	0.55	0.55	0.00	0.00
210.00	0.78	21,624	671.43	0.59	0.59	0.00	0.00
215.00	0.77	24,640	671.56	0.62	0.62	0.00	0.00
220.00	0.70	**26,544**	**671.64**	**0.64**	**0.64**	0.00	0.00
225.00	0.61	**26,714**	**671.65**	**0.64**	**0.64**	0.00	0.00
230.00	0.55	25,451	671.59	0.63	0.63	0.00	0.00
235.00	0.55	24,086	671.53	0.62	0.62	0.00	0.00
240.00	0.55	22,970	671.48	0.61	0.61	0.00	0.00
245.00	0.00	13,804	671.07	0.50	0.50	0.00	0.00
250.00	0.00	5,944	670.63	0.35	0.35	0.00	0.00

Stage-Discharge for Pond 3P: Southeast Chambers

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.00	0.00	0.00	0.00	0.00
670.20	0.09	0.09	0.00	0.00
670.40	0.25	0.25	0.00	0.00
670.60	0.34	0.34	0.00	0.00
670.80	0.42	0.42	0.00	0.00
671.00	0.48	0.48	0.00	0.00
671.20	0.54	0.54	0.00	0.00
671.40	0.59	0.59	0.00	0.00
671.60	0.63	0.63	0.00	0.00
671.80	0.68	0.68	0.00	0.00
672.00	0.72	0.72	0.00	0.00
672.20	0.75	0.75	0.00	0.00
672.40	0.79	0.79	0.00	0.00
672.60	0.83	0.83	0.00	0.00
672.80	0.86	0.86	0.00	0.00
673.00	0.89	0.89	0.00	0.00
673.20	0.92	0.92	0.00	0.00
673.40	0.95	0.95	0.00	0.00
673.60	0.99	0.98	0.01	0.00
673.80	1.04	1.01	0.03	0.00
674.00	1.08	1.04	0.04	0.00
674.20	1.11	1.07	0.05	0.00
674.40	1.15	1.09	0.05	0.00
674.60	1.18	1.12	0.06	0.00
674.80	1.21	1.14	0.07	0.00
675.00	1.24	1.17	0.07	0.00
675.20	1.27	1.19	0.08	0.00
675.40	1.29	1.21	0.08	0.00
675.60	1.32	1.24	0.08	0.00
675.80	1.35	1.26	0.09	0.00
676.00	1.37	1.28	0.09	0.00
676.20	1.40	1.30	0.10	0.00
676.40	1.43	1.33	0.10	0.00
676.60	1.45	1.35	0.10	0.00
676.80	1.47	1.37	0.11	0.00
677.00	1.50	1.39	0.11	0.00
677.20	1.52	1.41	0.11	0.00
677.40	1.54	1.43	0.12	0.00
677.60	1.57	1.45	0.12	0.00
677.80	1.59	1.47	0.12	0.00
678.00	3.40	1.49	1.91	0.00
678.20	6.77	1.51	5.26	0.00
678.40	11.25	1.52	9.72	0.00
678.60	18.46	1.54	15.13	1.79
678.80	**28.12**	**1.56**	**21.42**	**5.14**

Stage-Area-Storage for Pond 3P: Southeast Chambers

Elevation (feet)	Storage (cubic-feet)	Elevation (feet)	Storage (cubic-feet)
670.00	0	675.20	95,621
670.10	893	675.30	96,808
670.20	1,787	675.40	97,984
670.30	2,681	675.50	99,158
670.40	3,618	675.60	100,327
670.50	4,626	675.70	101,491
670.60	5,639	675.80	102,865
670.70	6,653	675.90	104,433
670.80	8,202	676.00	105,977
670.90	10,288	676.10	107,509
671.00	12,379	676.20	109,032
671.10	14,465	676.30	110,542
671.20	16,635	676.40	112,038
671.30	18,830	676.50	113,523
671.40	21,049	676.60	114,993
671.50	23,322	676.70	116,452
671.60	25,582	676.80	117,901
671.70	27,830	676.90	119,339
671.80	30,075	677.00	120,753
671.90	32,317	677.10	122,143
672.00	34,546	677.20	123,511
672.10	36,761	677.30	124,850
672.20	39,047	677.40	126,157
672.30	41,344	677.50	127,426
672.40	43,628	677.60	128,644
672.50	45,906	677.70	129,794
672.60	48,170	677.80	130,846
672.70	50,428	677.90	131,802
672.80	52,674	678.00	132,704
672.90	54,899	678.10	133,604
673.00	57,117	678.20	134,505
673.10	59,314	678.30	135,406
673.20	61,492	678.40	136,307
673.30	63,654	678.50	137,209
673.40	65,789	678.60	138,112
673.50	67,899	678.70	139,014
673.60	69,981	678.80	139,917
673.70	72,030	678.90	**140,821**
673.80	74,047		
673.90	76,023		
674.00	77,955		
674.10	79,844		
674.20	81,679		
674.30	83,453		
674.40	85,139		
674.50	86,709		
674.60	88,153		
674.70	89,496		
674.80	90,763		
674.90	91,997		
675.00	93,215		
675.10	94,422		

Summary for Pond 8P: North System

Inflow	=	0.40 cfs @ 204.54 hrs, Volume=	2.411 af
Outflow	=	0.40 cfs @ 204.91 hrs, Volume=	2.410 af, Atten= 0%, Lag= 22.7 min
Primary	=	0.30 cfs @ 204.91 hrs, Volume=	1.071 af
Secondary	=	0.11 cfs @ 204.91 hrs, Volume=	1.339 af
Tertiary	=	0.00 cfs @ 10.00 hrs, Volume=	0.000 af

Routing by Sim-Route method, Time Span= 10.00-250.00 hrs, dt= 0.05 hrs
Peak Elev= 676.84' @ 204.91 hrs Surf.Area= 1,404 sf Storage= 319 cf

Plug-Flow detention time= 13.7 min calculated for 2.410 af (100% of inflow)
Center-of-Mass det. time= 12.3 min (10,821.9 - 10,809.6)

Volume	Invert	Avail.Storage	Storage Description
#1	670.75'	6,908 cf	**Custom Stage Data (Prismatic)** Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
670.75	14	0	0
672.50	14	25	25
674.50	14	28	53
676.50	14	28	81
677.00	2,084	525	605
678.00	3,174	2,629	3,234
678.90	4,072	3,261	6,495
679.00	4,193	413	6,908


Device	Routing	Invert	Outlet Devices
#1	Primary	676.50'	**6.5" Vert. Orifice/Grate** C= 0.600
#2	Primary	678.00'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height
#3	Tertiary	678.60'	**35.0' long x 1.0' breadth Broad-Crested Rectangular Weir** Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 Coef. (English) 2.69 2.72 2.75 2.85 2.98 3.08 3.20 3.28 3.31 3.30 3.31 3.32
#4	Secondary	673.50'	**1.5" Vert. Orifice/Grate** C= 0.600
#5	Secondary	677.80'	**6.0' long Sharp-Crested Rectangular Weir** 2 End Contraction(s) 1.0' Crest Height

Primary OutFlow Max=0.30 cfs @ 204.91 hrs HW=676.84' (Free Discharge)
└**1=Orifice/Grate** (Orifice Controls 0.30 cfs @ 1.97 fps)
└**2=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)


Secondary OutFlow Max=0.11 cfs @ 204.91 hrs HW=676.84' TW=671.24' (Dynamic Tailwater)
└**4=Orifice/Grate** (Orifice Controls 0.11 cfs @ 8.71 fps)
└**5=Sharp-Crested Rectangular Weir** (Controls 0.00 cfs)

Tertiary OutFlow Max=0.00 cfs @ 10.00 hrs HW=670.75' (Free Discharge)
└**3=Broad-Crested Rectangular Weir** (Controls 0.00 cfs)


Pond 8P: North System



Pond 8P: North System



Pond 8P: North System



Hydrograph for Pond 8P: North System

Time (hours)	Inflow (cfs)	Storage (cubic-feet)	Elevation (feet)	Outflow (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
10.00	0.00	0	670.75	0.00	0.00	0.00	**0.00**
15.00	0.00	0	670.75	0.00	0.00	0.00	0.00
20.00	0.00	0	670.75	0.00	0.00	0.00	0.00
25.00	0.00	0	670.75	0.00	0.00	0.00	0.00
30.00	0.00	1	670.84	0.00	0.00	0.00	0.00
35.00	0.01	39	673.56	0.00	0.00	0.00	0.00
40.00	0.02	40	673.63	0.02	0.00	0.02	0.00
45.00	0.02	41	673.65	0.02	0.00	0.02	0.00
50.00	0.02	41	673.68	0.02	0.00	0.02	0.00
55.00	0.03	43	673.79	0.03	0.00	0.03	0.00
60.00	0.04	45	673.96	0.04	0.00	0.04	0.00
65.00	0.04	47	674.08	0.04	0.00	0.04	0.00
70.00	0.05	48	674.20	0.05	0.00	0.05	0.00
75.00	0.05	50	674.30	0.05	0.00	0.05	0.00
80.00	0.05	51	674.41	0.05	0.00	0.05	0.00
85.00	0.06	53	674.51	0.06	0.00	0.06	0.00
90.00	0.06	54	674.60	0.06	0.00	0.06	0.00
95.00	0.06	55	674.69	0.06	0.00	0.06	0.00
100.00	0.07	56	674.78	0.07	0.00	0.07	0.00
105.00	0.07	58	674.86	0.07	0.00	0.07	0.00
110.00	0.07	59	674.93	0.07	0.00	0.07	0.00
115.00	0.07	60	675.01	0.07	0.00	0.07	0.00
120.00	0.07	61	675.07	0.07	0.00	0.07	0.00
125.00	0.08	67	675.56	0.08	0.00	0.08	0.00
130.00	0.10	76	676.19	0.10	0.00	0.10	0.00
135.00	0.10	78	676.31	0.10	0.00	0.10	0.00
140.00	0.09	71	675.82	0.09	0.00	0.09	0.00
145.00	0.08	66	675.45	0.08	0.00	0.08	0.00
150.00	0.09	74	676.06	0.09	0.00	0.09	0.00
155.00	0.11	85	676.53	0.11	0.00	0.10	0.00
160.00	0.13	100	676.59	0.13	0.02	0.10	0.00
165.00	0.15	118	676.63	0.15	0.05	0.10	0.00
170.00	0.17	132	676.65	0.17	0.07	0.10	0.00
175.00	0.17	134	676.65	0.17	0.07	0.10	0.00
180.00	0.18	135	676.65	0.18	0.07	0.10	0.00
185.00	0.20	151	676.68	0.20	0.10	0.10	0.00
190.00	0.23	172	676.70	0.23	0.12	0.10	0.00
195.00	0.28	210	676.74	0.27	0.17	0.11	0.00
200.00	**0.34**	**265**	**676.79**	**0.34**	**0.23**	**0.11**	0.00
205.00	**0.40**	**321**	**676.84**	**0.40**	**0.30**	**0.11**	0.00
210.00	0.39	314	676.83	0.39	0.29	0.11	0.00
215.00	0.38	305	676.82	0.38	0.28	0.11	0.00
220.00	0.34	270	676.80	0.35	0.24	0.11	0.00
225.00	0.29	225	676.76	0.29	0.19	0.11	0.00
230.00	0.26	197	676.73	0.26	0.15	0.11	0.00
235.00	0.26	198	676.73	0.26	0.15	0.11	0.00
240.00	0.26	198	676.73	0.26	0.15	0.11	0.00
245.00	0.00	39	673.50	0.00	0.00	0.00	0.00
250.00	0.00	39	673.50	0.00	0.00	0.00	0.00

Stage-Discharge for Pond 8P: North System

Elevation (feet)	Discharge (cfs)	Primary (cfs)	Secondary (cfs)	Tertiary (cfs)
670.75	0.00	0.00	0.00	0.00
670.95	0.00	0.00	0.00	0.00
671.15	0.00	0.00	0.00	0.00
671.35	0.00	0.00	0.00	0.00
671.55	0.00	0.00	0.00	0.00
671.75	0.00	0.00	0.00	0.00
671.95	0.00	0.00	0.00	0.00
672.15	0.00	0.00	0.00	0.00
672.35	0.00	0.00	0.00	0.00
672.55	0.00	0.00	0.00	0.00
672.75	0.00	0.00	0.00	0.00
672.95	0.00	0.00	0.00	0.00
673.15	0.00	0.00	0.00	0.00
673.35	0.00	0.00	0.00	0.00
673.55	0.00	0.00	0.00	0.00
673.75	0.03	0.00	0.03	0.00
673.95	0.04	0.00	0.04	0.00
674.15	0.05	0.00	0.05	0.00
674.35	0.05	0.00	0.05	0.00
674.55	0.06	0.00	0.06	0.00
674.75	0.06	0.00	0.06	0.00
674.95	0.07	0.00	0.07	0.00
675.15	0.07	0.00	0.07	0.00
675.35	0.08	0.00	0.08	0.00
675.55	0.08	0.00	0.08	0.00
675.75	0.09	0.00	0.09	0.00
675.95	0.09	0.00	0.09	0.00
676.15	0.10	0.00	0.10	0.00
676.35	0.10	0.00	0.10	0.00
676.55	0.11	0.01	0.10	0.00
676.75	0.28	0.18	0.11	0.00
676.95	0.58	0.47	0.11	0.00
677.15	0.80	0.68	0.11	0.00
677.35	0.96	0.84	0.11	0.00
677.55	1.10	0.98	0.12	0.00
677.75	1.22	1.10	0.12	0.00
677.95	2.48	1.20	1.28	0.00
678.15	6.77	2.46	4.31	0.00
678.35	14.10	5.58	8.51	0.00
678.55	23.56	9.86	13.70	0.00
678.75	40.37	15.13	19.77	5.47
678.95	**67.61**	**21.27**	**26.68**	**19.66**

Stage-Area-Storage for Pond 8P: North System

Elevation (feet)	Surface (sq-ft)	Storage (cubic-feet)
670.75	14	0
670.85	14	1
670.95	14	3
671.05	14	4
671.15	14	6
671.25	14	7
671.35	14	8
671.45	14	10
671.55	14	11
671.65	14	13
671.75	14	14
671.85	14	15
671.95	14	17
672.05	14	18
672.15	14	20
672.25	14	21
672.35	14	22
672.45	14	24
672.55	14	25
672.65	14	27
672.75	14	28
672.85	14	29
672.95	14	31
673.05	14	32
673.15	14	34
673.25	14	35
673.35	14	36
673.45	14	38
673.55	14	39
673.65	14	41
673.75	14	42
673.85	14	43
673.95	14	45
674.05	14	46
674.15	14	48
674.25	14	49
674.35	14	50
674.45	14	52
674.55	14	53
674.65	14	55
674.75	14	56
674.85	14	57
674.95	14	59
675.05	14	60
675.15	14	62
675.25	14	63
675.35	14	64
675.45	14	66
675.55	14	67
675.65	14	69
675.75	14	70
675.85	14	71
675.95	14	73
676.05	14	74
676.15	14	76
676.25	14	77
676.35	14	78
676.45	14	80
676.55	221	86
676.65	635	129
676.75	1,049	213
676.85	1,463	339
676.95	1,877	506
677.05	2,138	711
677.15	2,247	930
677.25	2,357	1,160
677.35	2,466	1,401
677.45	2,575	1,653
677.55	2,683	1,916
677.65	2,792	2,190
677.75	2,902	2,475
677.85	3,011	2,770
677.95	3,120	3,077
678.05	3,224	3,394
678.15	3,324	3,721
678.25	3,423	4,059
678.35	3,523	4,406
678.45	3,623	4,763
678.55	3,723	5,131
678.65	3,823	5,508
678.75	3,922	5,895
678.85	4,022	6,292
678.95	**4,133**	**6,700**

APPENDIX C

EXISTING AND PROPOSED RUNOFF CALCULATIONS

Summary for Subcatchment 1S: (new Subcat)

Runoff = 3.56 cfs @ 0.62 hrs, Volume= 0.216 af, Depth> 1.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)


Runoff = 3.33 cfs @ 0.81 hrs, Volume= 0.312 af, Depth> 2.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Subcatchment 1S: (new Subcat)



Summary for Subcatchment 1S: (new Subcat)

Runoff = 2.01 cfs @ 1.53 hrs, Volume= 0.473 af, Depth= 3.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

Runoff = 1.67 cfs @ 5.58 hrs, Volume= 0.593 af, Depth= 4.45"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

Runoff = 1.50 cfs @ 12.01 hrs, Volume= 0.664 af, Depth= 4.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

Runoff = 1.23 cfs @ 15.90 hrs, Volume= 0.725 af, Depth= 5.44"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

Runoff = 0.72 cfs @ 41.52 hrs, Volume= 0.811 af, Depth= 6.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.51 cfs @ 61.93 hrs, Volume= 0.881 af, Depth= 6.61"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.34 cfs @ 102.84 hrs, Volume= 0.981 af, Depth= 7.36"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: (new Subcat)

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.21 cfs @ 205.04 hrs, Volume= 1.231 af, Depth= 9.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
1.600	74	>75% Grass cover, Good, HSG C
1.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.2	600	0.0100	0.40		**Lag/CN Method, Shallow Concentrated Flow**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 8.77 cfs @ 0.58 hrs, Volume= 0.507 af, Depth> 1.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 8.03 cfs @ 0.77 hrs, Volume= 0.727 af, Depth> 2.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 6.90 cfs @ 0.95 hrs, Volume= 0.856 af, Depth> 2.85"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 4.73 cfs @ 1.13 hrs, Volume= 1.095 af, Depth= 3.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 3.85 cfs @ 5.53 hrs, Volume= 1.367 af, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 3.44 cfs @ 11.97 hrs, Volume= 1.529 af, Depth= 5.10"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 2.80 cfs @ 15.86 hrs, Volume= 1.668 af, Depth= 5.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

Runoff = 1.63 cfs @ 41.44 hrs, Volume= 1.863 af, Depth= 6.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.17 cfs @ 61.85 hrs, Volume= 2.021 af, Depth= 6.74"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.77 cfs @ 102.74 hrs, Volume= 2.248 af, Depth= 7.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 3.6 Ac.

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.47 cfs @ 204.87 hrs, Volume= 2.813 af, Depth= 9.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
3.460	74	>75% Grass cover, Good, HSG C
0.140	98	Paved parking, HSG C
3.600	75	Weighted Average
3.460		96.11% Pervious Area
0.140		3.89% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
22.6	541	0.0100	0.40		**Lag/CN Method, 3.60 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 11.49 cfs @ 0.78 hrs, Volume= 0.821 af, Depth> 1.67"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 11.30 cfs @ 0.99 hrs, Volume= 1.187 af, Depth> 2.41"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 10.19 cfs @ 1.18 hrs, Volume= 1.399 af, Depth> 2.84"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 7.51 cfs @ 1.69 hrs, Volume= 1.795 af, Depth> 3.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 6.21 cfs @ 5.71 hrs, Volume= 2.241 af, Depth= 4.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 5.54 cfs @ 12.15 hrs, Volume= 2.505 af, Depth= 5.10"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 4.55 cfs @ 16.03 hrs, Volume= 2.733 af, Depth= 5.56"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 2.66 cfs @ 41.80 hrs, Volume= 3.053 af, Depth> 6.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

Runoff = 1.91 cfs @ 62.21 hrs, Volume= 3.313 af, Depth= 6.74"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.26 cfs @ 103.01 hrs, Volume= 3.684 af, Depth= 7.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 5.9 Ac.

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.77 cfs @ 205.33 hrs, Volume= 4.610 af, Depth= 9.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.160	98	Roofs, HSG C
5.740	74	>75% Grass cover, Good, HSG C
5.900	75	Weighted Average
5.740		97.29% Pervious Area
0.160		2.71% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
36.9	1,000	0.0100	0.45		**Lag/CN Method, 5.90 Ac.**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

Runoff = 1.15 cfs @ 0.40 hrs, Volume= 0.054 af, Depth= 1.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

Runoff = 0.96 cfs @ 0.61 hrs, Volume= 0.078 af, Depth= 2.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

Runoff = 0.78 cfs @ 0.81 hrs, Volume= 0.092 af, Depth= 2.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

Runoff = 0.55 cfs @ 0.90 hrs, Volume= 0.118 af, Depth= 3.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

Runoff = 0.42 cfs @ 5.42 hrs, Volume= 0.148 af, Depth= 4.45"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

Runoff = 0.38 cfs @ 11.84 hrs, Volume= 0.166 af, Depth= 4.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.31 cfs @ 15.73 hrs, Volume= 0.181 af, Depth= 5.44"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.18 cfs @ 41.19 hrs, Volume= 0.203 af, Depth= 6.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.13 cfs @ 61.60 hrs, Volume= 0.220 af, Depth= 6.61"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.09 cfs @ 102.53 hrs, Volume= 0.245 af, Depth= 7.36"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.40 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.05 cfs @ 204.71 hrs, Volume= 0.308 af, Depth= 9.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.400	74	>75% Grass cover, Good, HSG C
0.400		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	198	0.0080	0.28		**Lag/CN Method, 0.40**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

Runoff = 1.77 cfs @ 0.39 hrs, Volume= 0.081 af, Depth= 1.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

Runoff = 1.45 cfs @ 0.59 hrs, Volume= 0.117 af, Depth= 2.34"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

Runoff = 1.17 cfs @ 0.79 hrs, Volume= 0.138 af, Depth= 2.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

Runoff = 0.83 cfs @ 0.88 hrs, Volume= 0.177 af, Depth= 3.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

Runoff = 0.63 cfs @ 5.40 hrs, Volume= 0.222 af, Depth= 4.45"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

Runoff = 0.57 cfs @ 11.83 hrs, Volume= 0.249 af, Depth= 4.98"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.46 cfs @ 15.72 hrs, Volume= 0.272 af, Depth= 5.44"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.27 cfs @ 41.17 hrs, Volume= 0.304 af, Depth= 6.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.19 cfs @ 61.60 hrs, Volume= 0.330 af, Depth= 6.61"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.13 cfs @ 102.52 hrs, Volume= 0.368 af, Depth= 7.36"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.08 cfs @ 204.71 hrs, Volume= 0.462 af, Depth= 9.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.600	74	>75% Grass cover, Good, HSG C
0.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.5	200	0.0100	0.32		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

Runoff = 3.47 cfs @ 0.37 hrs, Volume= 0.154 af, Depth= 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

Runoff = 2.71 cfs @ 0.48 hrs, Volume= 0.210 af, Depth= 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

Runoff = 2.31 cfs @ 0.53 hrs, Volume= 0.241 af, Depth= 3.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

Runoff = 1.67 cfs @ 0.83 hrs, Volume= 0.299 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

Runoff = 1.01 cfs @ 5.10 hrs, Volume= 0.364 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

Runoff = 0.86 cfs @ 11.82 hrs, Volume= 0.402 af, Depth= 6.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.69 cfs @ 15.71 hrs, Volume= 0.435 af, Depth= 6.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.39 cfs @ 41.14 hrs, Volume= 0.480 af, Depth= 7.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.28 cfs @ 61.58 hrs, Volume= 0.517 af, Depth= 7.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.18 cfs @ 102.49 hrs, Volume= 0.570 af, Depth= 8.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.80 North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.11 cfs @ 204.67 hrs, Volume= 0.699 af, Depth=10.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.800	83	1/4 acre lots, 38% imp, HSG C
0.496		62.00% Pervious Area
0.304		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.6	320	0.0100	0.46		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

Runoff = 4.80 cfs @ 0.18 hrs, Volume= 0.181 af, Depth= 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

Runoff = 3.86 cfs @ 0.28 hrs, Volume= 0.247 af, Depth= 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

Runoff = 3.13 cfs @ 0.38 hrs, Volume= 0.284 af, Depth= 3.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 2.07 cfs @ 0.69 hrs, Volume= 0.352 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.19 cfs @ 4.91 hrs, Volume= 0.428 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.02 cfs @ 11.73 hrs, Volume= 0.473 af, Depth= 6.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.82 cfs @ 15.61 hrs, Volume= 0.511 af, Depth= 6.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.46 cfs @ 40.99 hrs, Volume= 0.565 af, Depth= 7.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.33 cfs @ 61.40 hrs, Volume= 0.608 af, Depth= 7.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.22 cfs @ 102.34 hrs, Volume= 0.669 af, Depth= 8.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 0.94 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.13 cfs @ 204.61 hrs, Volume= 0.821 af, Depth=10.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.940	83	1/4 acre lots, 38% imp, HSG C
0.583		62.00% Pervious Area
0.357		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 3.91 cfs @ 0.68 hrs, Volume= 0.254 af, Depth> 1.91"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 3.69 cfs @ 0.85 hrs, Volume= 0.358 af, Depth> 2.68"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 3.24 cfs @ 1.04 hrs, Volume= 0.417 af, Depth> 3.13"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 2.29 cfs @ 1.31 hrs, Volume= 0.528 af, Depth= 3.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 1.81 cfs @ 5.59 hrs, Volume= 0.653 af, Depth= 4.89"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 1.58 cfs @ 12.05 hrs, Volume= 0.726 af, Depth= 5.45"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 1.29 cfs @ 15.95 hrs, Volume= 0.789 af, Depth= 5.92"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.75 cfs @ 41.60 hrs, Volume= 0.878 af, Depth> 6.58"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.54 cfs @ 62.02 hrs, Volume= 0.950 af, Depth= 7.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.35 cfs @ 102.89 hrs, Volume= 1.052 af, Depth= 7.89"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.21 cfs @ 205.14 hrs, Volume= 1.307 af, Depth= 9.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

	Area (ac)	CN	Description
*	1.600	78	1/3 acre lots, 30% imp, HSG C
	1.120		70.00% Pervious Area
	0.480		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.4	875	0.0100	0.48		**Lag/CN Method, Lag CN**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

Runoff = 2.50 cfs @ 0.32 hrs, Volume= 0.103 af, Depth= 2.07"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

Runoff = 1.89 cfs @ 0.36 hrs, Volume= 0.143 af, Depth= 2.87"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

Runoff = 1.61 cfs @ 0.46 hrs, Volume= 0.166 af, Depth= 3.32"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

Runoff = 1.13 cfs @ 0.78 hrs, Volume= 0.209 af, Depth= 4.17"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

Runoff = 0.72 cfs @ 5.06 hrs, Volume= 0.256 af, Depth= 5.12"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.62 cfs @ 11.77 hrs, Volume= 0.284 af, Depth= 5.68"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.50 cfs @ 15.67 hrs, Volume= 0.308 af, Depth= 6.16"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.29 cfs @ 41.04 hrs, Volume= 0.342 af, Depth= 6.83"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.21 cfs @ 61.53 hrs, Volume= 0.369 af, Depth= 7.38"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.13 cfs @ 102.45 hrs, Volume= 0.408 af, Depth= 8.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 1S: 0.60 Ac Res Lot

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.08 cfs @ 204.65 hrs, Volume= 0.504 af, Depth=10.08"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.600	80	1/2 acre lots, 25% imp, HSG C
0.450		75.00% Pervious Area
0.150		25.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
7.3	160	0.0100	0.36		**Lag/CN Method, 1.0 Ac.**

Summary for Subcatchment 9S: ODH Subdivision Bypass

Runoff = 2.31 cfs @ 0.34 hrs, Volume= 0.098 af, Depth= 2.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

Runoff = 1.76 cfs @ 0.42 hrs, Volume= 0.136 af, Depth= 2.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

Runoff = 1.50 cfs @ 0.49 hrs, Volume= 0.157 af, Depth= 3.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

Runoff = 1.07 cfs @ 0.81 hrs, Volume= 0.196 af, Depth= 4.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

Runoff = 0.67 cfs @ 5.09 hrs, Volume= 0.240 af, Depth= 5.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

Runoff = 0.58 cfs @ 11.80 hrs, Volume= 0.266 af, Depth= 5.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.47 cfs @ 15.69 hrs, Volume= 0.288 af, Depth= 6.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.27 cfs @ 41.07 hrs, Volume= 0.319 af, Depth= 6.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.19 cfs @ 61.56 hrs, Volume= 0.344 af, Depth= 7.50"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.12 cfs @ 102.47 hrs, Volume= 0.380 af, Depth= 8.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 9S: ODH Subdivision Bypass

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.08 cfs @ 204.38 hrs, Volume= 0.468 af, Depth=10.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.30 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
0.550	81	1/3 acre lots, 30% imp, HSG C
0.385		70.00% Pervious Area
0.165		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
9.2	380	0.0240	0.69		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

Runoff = 5.31 cfs @ 0.18 hrs, Volume= 0.200 af, Depth= 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

Runoff = 4.28 cfs @ 0.28 hrs, Volume= 0.273 af, Depth= 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

Runoff = 3.47 cfs @ 0.38 hrs, Volume= 0.314 af, Depth= 3.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 2.29 cfs @ 0.69 hrs, Volume= 0.389 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.32 cfs @ 4.91 hrs, Volume= 0.473 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 1.12 cfs @ 11.73 hrs, Volume= 0.523 af, Depth= 6.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.90 cfs @ 15.61 hrs, Volume= 0.565 af, Depth= 6.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.51 cfs @ 40.99 hrs, Volume= 0.625 af, Depth= 7.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.36 cfs @ 61.40 hrs, Volume= 0.672 af, Depth= 7.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.24 cfs @ 102.34 hrs, Volume= 0.740 af, Depth= 8.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 1S: Proposed 1.04 Ac. North to Turnbull Woods

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.14 cfs @ 204.61 hrs, Volume= 0.909 af, Depth=10.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

Area (ac)	CN	Description
1.040	83	1/4 acre lots, 38% imp, HSG C
0.645		62.00% Pervious Area
0.395		38.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
3.4	263	0.0830	1.27		**Lag/CN Method,**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 1.74 cfs @ 0.64 hrs, Volume= 0.107 af, Depth> 2.14"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 1.59 cfs @ 0.79 hrs, Volume= 0.148 af, Depth> 2.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 1.37 cfs @ 0.96 hrs, Volume= 0.171 af, Depth> 3.42"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.99 cfs @ 1.14 hrs, Volume= 0.214 af, Depth= 4.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.72 cfs @ 5.49 hrs, Volume= 0.262 af, Depth= 5.23"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.62 cfs @ 12.01 hrs, Volume= 0.290 af, Depth= 5.80"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.50 cfs @ 15.90 hrs, Volume= 0.314 af, Depth= 6.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

Runoff = 0.29 cfs @ 41.51 hrs, Volume= 0.348 af, Depth= 6.96"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.21 cfs @ 61.91 hrs, Volume= 0.375 af, Depth= 7.50"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.14 cfs @ 102.82 hrs, Volume= 0.414 af, Depth= 8.28"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.08 cfs @ 204.99 hrs, Volume= 0.511 af, Depth=10.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

	Area (ac)	CN	Description
*	0.600	81	1/3 acre lots, 30% imp, HSG C
	0.420		70.00% Pervious Area
	0.180		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
27.7	875	0.0100	0.53		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 5.86 cfs @ 0.60 hrs, Volume= 0.347 af, Depth> 2.31"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-2.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 1.00 hrs Rainfall=4.03"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 5.25 cfs @ 0.75 hrs, Volume= 0.472 af, Depth> 3.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-3.00 hrs, dt= 0.01 hrs
Huff 0-10sm 1Q 2.00 hrs Rainfall=4.97"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 4.47 cfs @ 0.90 hrs, Volume= 0.543 af, Depth> 3.62"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-4.00 hrs, dt= 0.02 hrs
Huff 0-10sm 1Q 3.00 hrs Rainfall=5.49"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 3.28 cfs @ 1.08 hrs, Volume= 0.674 af, Depth= 4.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-8.01 hrs, dt= 0.03 hrs
Huff 0-10sm 1Q 6.00 hrs Rainfall=6.43"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 2.24 cfs @ 5.42 hrs, Volume= 0.819 af, Depth= 5.46"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-15.00 hrs, dt= 0.05 hrs
Huff 0-10sm 2Q 12.00 hrs Rainfall=7.46"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 1.91 cfs @ 11.98 hrs, Volume= 0.905 af, Depth= 6.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-21.00 hrs, dt= 0.07 hrs
Huff 0-10sm 3Q 18.00 hrs Rainfall=8.06"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 1.54 cfs @ 15.88 hrs, Volume= 0.978 af, Depth= 6.52"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-27.00 hrs, dt= 0.10 hrs
Huff 0-10sm 3Q 24.00 hrs Rainfall=8.57"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

Runoff = 0.88 cfs @ 41.44 hrs, Volume= 1.081 af, Depth= 7.21"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-49.98 hrs, dt= 0.17 hrs
Huff 0-10sm 4Q 48.00 hrs Rainfall=9.28"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.63 cfs @ 61.86 hrs, Volume= 1.164 af, Depth= 7.76"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-75.00 hrs, dt= 0.25 hrs
Huff 0-10sm 4Q 72.00 hrs Rainfall=9.85"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.41 cfs @ 102.75 hrs, Volume= 1.281 af, Depth= 8.54"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-130.00 hrs, dt= 0.40 hrs
Huff 0-10sm 4Q 120.00 hrs Rainfall=10.66"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Summary for Subcatchment 8S: Northwood Drive to Turnbull

[49] Hint: Tc<2dt may require smaller dt

Runoff = 0.25 cfs @ 204.87 hrs, Volume= 1.573 af, Depth=10.49"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 10.00-250.00 hrs, dt= 0.80 hrs
Huff 0-10sm 4Q 240.00 hrs Rainfall=12.65"

	Area (ac)	CN	Description
*	1.800	83	1/3 acre lots, 30% imp, HSG C
	1.260		70.00% Pervious Area
	0.540		30.00% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
25.9	875	0.0100	0.56		**Lag/CN Method, Lag CN**

Operation and Maintenance Requirements
As They Relate to
Storm Water Management Facilities
For
The Forest Edge Subdivision
1801 Green Bay Road
Glencoe, Illinois

June 8, 2020

Prepared By:
IG Consulting, Inc.
300 Marquardt Drive
Wheeling, Illinois 60090
847-215-1133

Introduction

This guide is prepared to assist the property owner in the inspection and maintenance of the stormwater management system for The Forest Edge Subdivision. Proper maintenance is essential for the long term performance of the system as well as the esthetics of the property. The owner, and the onsite or out-sourced maintenance staff should be made aware of the maintenance responsibility that is connected with the storm water detention system and water quality component that exists on this property. Specific care for the subject system must be incorporated into an ongoing maintenance plan, to see that the storm water impoundment system operates problem free and the water quality component operates at peak efficiency. This system should not be neglected and degrade to a level that it becomes a hazard for the property owner, the adjacent landowners or the Village of Glencoe's public infrastructure system. The following guidelines must be followed as set forth by the Metropolitan Water Reclamation District of Greater Chicago.

Homeowner's Association Responsibility

The Homeowner's Association (HOA) should retain on file, a list of names and contact information of all responsible parties, including contact information of the property maintenance company and/or contract services, that will be responsible for the maintenance of common grounds, and areas within the Storm Water Management Easement, which includes the storm water detention and sedimentation control system (Chamber/Rock Void Detention System) and common area landscaping. Contact information will be attached to this report and kept by the HOA, for the maintenance staff to review.

Inspection and Maintenance Schedule

An inspection and maintenance schedule should be created as part of the ongoing maintenance of the storm water management system. The schedule shall provide for routine examination of the detention system, surrounding landscaping that accompanies the system and any of its constructed components. A log book should be prepared and kept by the HOA, The logbook will contain inspection dates, facility components inspected along with any maintenance performed and repairs that were made. All inspections, whether routine or emergency, shall be recorded in the logbook. The HOA should familiarize themselves with the logbook and report, so that these individuals are aware of proper inspection and O&M procedures.

Minimum Requirements

Along with specific maintenance procedures for the onsite storm water detention system, the following minimum requirements shall be incorporated into the inspection and maintenance of the on-site system:

- O&M plan procedures and practices must be reviewed and assessed annually
- Access routes, sidewalks, pavements, shall be inspected annually and maintained as needed
- Drainage structures and flow restrictors (3 restrictor catch basins, one found to the northeast, in the back of Lot 23, another between lots 22 and 23 and to the southeast, between the back yards of lots 17 and 18) must be inspected and cleaned in the early spring, mid summer and late fall, after leaves have fallen and the northeast detention basin is cleaned of all debris from a scheduled fall cleanup. Additional inspections shall be provided, as needed.
- The detention system is comprised of an above ground basin in the northeast corner of the subdivision and a below ground, combination plastic arch pipe and stone chamber system that spans from the northeast corner to the southeast corner of the subdivision. The system shall be inspected during the same schedule as the flow restrictor and after significant rainfall events exceeding 1.5 inches.
- A logbook shall be kept complete and updated. Logbooks should be produced upon request of a service provider or contractor, to properly assess any problems with the detention system or other site amenities. The HOA shall provide copies of the logbook to the Village, on an annual basis.
- Vegetation shall be maintained on a regular basis.
- Pest control measures shall be implemented to address insects and rodents.
- Signage and fencing, if necessary, shall be installed and maintained to protect property and the public.

The following are O&M guidelines for the site-specific facilities found on this property:

Natural Landscaping and Trees

Regular tree maintenance is required such as pruning and trimming in late fall or winter to remove dead wood and access growth to maintain a healthy canopy. Maintenance such as lawn mowing and trimming will be necessary to maintain esthetics of the site.

General Planted Bioswale Maintenance and Care:

1. Watering: Within the first three weeks after planting, water the bioswale once per week. It is not necessary to water during a given week if one inch of rain accumulates.

2. Water the bioswale during periods of drought in mid-summer, if needed.

3. Weeding: Using a field guide, identify and separate weeds from bioswale plants. Remove identified weeds. To avoid confusion, bioswale plants may be marked with small planting stakes, until they are established.

4. Mulch: Until bioswale plants are established, mulching the edge / slope of the bioswale interior will discourage weed growth and soil erosion.

5. Sedimentation: It is always best to protect the bioswale from the possibility of silt entering the area. It is important to be diligent, as conditions change. If bioswales have sediment build up, an easy remedy is to dig small pits in the swale and remove the soil.

   Over time, the pits will naturally fill in and bioswale plants will grow over the area. Small pits are less invasive than to skim off silt in larger areas. Creating small pits will reduce disturbance to the plant community. In severe cases, it may be necessary to re-dig the entire swale/basin area.

6. Maintenance of bioswales includes replacement of dead or dying plant material. Identify dead or weak plantings which will not recover. Remove the plantings, including root structures. Clear the area and provide additional soil media, if necessary.

   Using the enclosed list of recommended plantings, replant the subject area, following proper spacing guidelines for each of the replanted species. Water as necessary, following guidelines mentioned in this plan for new planted material.

BIOSWALE PLANT LIST OF RECOMMENDED SPECIES	
Botanical Name	***Common Name***
Agropyron elongatum	Tall Wheatgrass
Alisma subcordatum	American Water Plantain
Symphyotrichum lanceolatum	Aster lanceolatus
Bidens cernua	Nodding Beggarticks
Bouteloua hirsuta	Hairy Grama
Carex stipata	Awlfruit Sedge
Carex vulpinoidea	Fox Sedge
Eleocharis obtusa	Blunt Spikerush
Elymus canadensis	Canada Wild Rye
Pascopyrum smithii	Western Wheatgrass
Helianthus gosseserratus	Sawtooth Sunflower
Panicum virgatum	Switchgrass
Schizachyrium scoparium	Little Bluestem
Bolboschoenus fluviatilis	River Bulrush
Schoenoplectus tabernaemontani	Softstem Bulrush
Spartina pectinata	Prairie Cordgrass
Verbena hastata	American Blue Vervain
Eleocharis erythopoda	Bald Spikerush
Solidago sempervirens	Seaside Goldenrod
Juncus effusus	Common Rush

Ongoing Maintenance Schedule:

As Needed -Mowing and trimming of vegetation

Monthly - Inspect all vegetation expected to trap silt, debris and sediment that can impede the storm sewer and detention system.

Twice-a-year - Inspect swales and slopes for erosion, scour and unwanted growth. Erosion repair and removal of unwanted growth should be executed with minimal disruption to the planting soil bed and remaining vegetation (See Bioswale Maintenance).

Once-a-year - Inspect inlets and catch basins for trapped sediment and flow capabilities. Remove sediment during dry periods.

Detention System

Maintenance is imperative, for continuous operation of storm water detention. This is the most important component of a development's storm water management system.

Schedule:

As Needed - Sediment should be removed from the below ground chamber system as defined in the maintenance schedule, provided by the manufacturer and attached to this O & M plan.
- Inspect basin after every storm greater than 1.5 inches of rainfall.

Quarterly - Inspect inlet and outlet pipes of the control structures (Restrictors) for clogging.
- Remove trash and debris.
- Grassed areas of the surface basin require mowing, trimming, weeding, dethatching and fertilizing
- Trees, shrubs will require maintenance as well.

Once-a-year - Inspection of the chamber system. Potential problems include pavement settlement, unusual settlement in yards within the chamber system location, access openings (unable to open) and debris removal.

A maintenance guide was provided by the chamber system manufacturer and is attached to this plan, for inspection and upkeep of the system. Qualified services can be retained to manage, provide maintenance and cleaning services for the system.

Permeable Paver System

Schedule:

As needed
- Permeable pavers shall be inspected and cleaned with a low-pressure power washer.
- Accumulated sediment from surface shall be vacuumed out and disposed of properly
- Remove litter and debris.
- Replace broken pavers and provide granular fill between paver joints as needed.

Maintenance of the onsite storm water management system can be minimal and cost effective, if a schedule is adhered to by the HOA and contracted service providers. This preventive type of management will provide a long lasting and effectively operating system that will benefit the property and surrounding area by providing water quality and potentially minimizing impacts to the Village's sewer system.

RECHARGER® CHAMBERS

STORMWATER MANAGEMENT SOLUTIONS



OPERATION & MAINTENANCE GUIDELINES

FOR 1801 GREEN BAY ROAD, GLENCOE, IL

This manual contains guidelines recommended by CULTEC, Inc. and may be used in conjunction with, but not to supersede, local regulations or regulatory authorities. OSHA Guidelines must be followed when inspecting or cleaning any structure.

Introduction

The CULTEC Subsurface Stormwater Management System is an open-bottom corrugated plastic arch chamber system arranged in parallel rows surrounded by crushed, open graded stone. The CULTEC chambers create voids within the washed stone to provide stormwater storage for detention and volume-control purposes. Non-woven geotextile fabric is placed between the native soil and stone interface to prevent the intrusion of fines into the system. In order to minimize the amount of sediment which may enter the CULTEC system, a sediment collection device is recommended upstream from the CULTEC chamber system. An appropriately sized catch basin with sump, pretreatment catchment device, oil grit separator, or baffled distribution box all serve this function. 1801 Green Bay Road has been designed with sumped catch basins directly upstream of each CULTEC chamber system to capture as much sediment as possible. Installation, operation, and maintenance of these devices shall be in accordance with manufacturer's recommendations. Fine sediment that is not captured by the sumped catch basin will be captured in the CULTEC Separator Row. The CULTEC Separator Row explained in more detail on page 3.

Best Management Practices allow for the maintenance of the preliminary collection systems prior to feeding the CULTEC chambers. The pretreatment structures shall be inspected for any debris that will restrict inlet flow rates. Outfall structures, if any, such as outlet control must also be inspected for any obstructions that would restrict outlet flow rates. OSHA Guidelines must be followed when inspecting or cleaning any structure.

Operation and Maintenance Requirements

I. Operation

CULTEC stormwater management systems shall be operated to receive only stormwater run-off in accordance with applicable local regulations. CULTEC subsurface stormwater management chambers operate at peak performance when installed in series with pretreatment. Pretreatment of suspended solids is superior to treatment of solids once they have been introduced into the system. The use of pretreatment is adequate as long as the structure is maintained and the site remains stable with finished impervious surfaces such as parking lots, walkways, and pervious areas are properly maintained. If there is to be an unstable condition, such as improvements to buildings or parking areas, all proper silt control measures shall be implemented according to local regulations.

II. Inspection and Maintenance

A. The CULTEC systems are equipped with an inspection port located on the Separator Rows. The CULTEC Inspection Port Kit is a circular PVC housing with a cast-iron frame and cover, supported with a concrete collar. When the lid is removed, a 6-inch (150 mm) pipe with a screw-in plug will be exposed. Remove the plug. This will provide access to the CULTEC Chamber row below. From the surface, through this access, the sediment may be measured at this location. A stadia rod may be used to measure the depth of sediment if any in this row. If the depth of sediment is in excess of 3 inches (76 mm), then this row should be cleaned with high pressure water through a culvert cleaning nozzle. This would be carried out through an upstream manhole.

1. Manhole Access

This inspection should only be carried out by persons trained in confined space entry and sewer inspection services. After the manhole cover has been removed a gas detector must be lowered into the manhole to ensure that there are not high concentrations of toxic gases present. The inspector should be lowered into the manhole with the proper safety equipment as per OSHA requirements. The inspector may be able to observe sediment from this location. If this is not possible, the inspector will need to deploy a CCTV robot to permit viewing of the sediment.


2. Separator Row

CULTEC's Separator™ Row is an inexpensive means of removing Total Suspended Solids from the CULTEC chamber system, as well as providing easier access for inspection and maintenance. The Separator Row is designed to capture the First Flush of a rain event and is typically included as part of the "Treatment Train" for water quality.


The CULTEC Separator Row is a row of CULTEC Recharger Chambers that are surrounded on all sides by filter fabric. One layer of CULTEC No. 4800™ Woven Geotextile are placed between the clean foundation stone and the chamber feet. The chambers are then completely wrapped with CULTEC No. 410™ non-woven geotextile. This configuration is designed to trap any sediment and/or debris that may pass through the upstream structures and into the chamber system.

Access manhole and/or catch basins are installed upstream of the Separator Rows for inspection and maintenance.The upstream manhole is designed with a sump to trap heavier sediment and allow for proper cleaning of the Separator Row. A JetVac process with a high pressure water nozzle is introduced down the Separator Row via the access manhole to clean all sediment and debris from the Separator Row. Captured pollutants are flushed into the sumped access manhole for vacuuming, and the process is repeated until the Separator Row is completely free of sediment and debris.





Typical Separator Row Plan-View Detail



Typical Separator Row Cross-Section Detail

Inspection and Maintenance

CULTEC recommends inspection of the Separator Row to be performed quarterly for the first year of service. Future inspection frequency can be adjusted based upon previous inspection observations. However annual inspections are recommended. Inspection of the Separator Row can be achieved via an inspection port riser installed during construction. This inspection port riser will connect the top of the Separator Row chambers to finished grade with a removable lid. Alternatively the Separator Row may be inspected via the manhole(s) located at the end(s) of the Separator Row. However this method of inspection requires confined space entry. If entry into the manhole is required, all local and OSHA rules for confined space entries must be strictly followed.

To inspect:

- Remove the inspection port lid.
- Remove the riser pipe cap.
- With a flashlight and stadia rod, measure the depth of sediment.
- Record results in a maintenance log.
- When depth of sediment exceeds 3" (76 mm), use the JetVac procedure described below.

The JetVac process utilizes a high pressure water nozzle controlled from the surface. The high pressure nozzle is introduced down the Separator Row via the access manhole(s). The high pressure water cleans all sediment and debris from the Separator Row as the nozzle is retrieved. Captured pollutants are flushed into the sumped access manhole for vacuuming. This process is repeated until the Separator Row is completely free of sediment and debris. A small diameter culvert cleaning nozzle is recommended for this procedure.



High pressure water nozzle



Cleaning Separator Row and pipes with high pressure water nozzle



SEPARATOR ROW: Separator Row prior to cleaning



ADJACENT ROW: When the Separator Row is working properly, the adjacent rows will not show signs of sediment.

III. Maintenance Guidelines

The following guidelines shall be adhered to for the operation and maintenance of the CULTEC stormwater management system:

A. The owner shall keep a maintenance log which shall include details of any events which would have an effect on the system's operational capacity.

B. The operation and maintenance procedure shall be reviewed periodically and changed to meet site conditions.

C. Maintenance of the stormwater management system shall be performed by qualified workers and shall follow applicable occupational health and safety requirements.

D. Debris removed from the stormwater management system shall be disposed of in accordance with applicable laws and regulations.

IV. Suggested Maintenance Schedules

A. Maintenance

The following suggested schedule shall be followed for routine maintenance during the regular operation of the stormwater system:

Frequency	Action
Quarterly	Check inlets and outlets for clogging and remove any debris, as required.
After rain events > 1 inch per hour	Check inlets and outlets for clogging and remove any debris, as required.
Annually	Inspect Separator Rows through inspection ports. Check all components for structural damage or erosion. Remove sediment from Separator Rows if necessary

BMP OPERATION & MAINTENANCE LOG

Project Name: _____

Today's Date:_____

Name of Person Performing Activity (Printed):_____

Signature: _____

BMP Name (As Shown in O&M Plan)	Brief Description of Implementation, Maintenance, and Inspection Activity Performed

This O&M Plan describes the designated responsible party for implementation of this WQMP, including: operation and maintenance of all the structural BMP(s), conducting the training/educational program and duties, and any other necessary activities. The O&M Plan includes detailed inspection and maintenance requirements for all structural BMPs, including copies of any maintenance contract agreements, manufacturer's maintenance requirements, permits, etc.

4.1.1 Project Information

Project name	
Address	
City, State Zip	
Site size	
List of structural BMPs, number of each	
Other notes	

4.1.2 Responsible Party

The responsible party for implementation of this WQMP is:

Name of Person or HOA Property Manager	
Address	
City, State Zip	
Phone number	
24-Hour Emergency Contact number	
Email	

4.1.3 Record Keeping

Parties responsible for the O&M plan shall retain records for at least 5 years.

All training and educational activities and BMP operation and maintenance shall be documented to verify compliance with this O&M Plan. A sample Training Log and Inspection and Maintenance Log are included in this document.

4.1.4 Electronic Data Submittal

This document along with the Site Plan and Attachments shall be provided in PDF format. AutoCAD files and/or GIS coordinates of BMPs shall also be submitted to the City.